

NumPy

NumPy (or Numpy) is a Linear Algebra Library for Python, the reason it is so important for Data Science with Python is that almost all of the libraries in the PyData Ecosystem rely on NumPy as one of their main building blocks.

Numpy is also incredibly fast, as it has bindings to C libraries. For more info on why you would want to use Arrays instead of lists, check out this great [StackOverflow post](http://stackoverflow.com/questions/993984/why-numpy-instead-of-python-lists) (<http://stackoverflow.com/questions/993984/why-numpy-instead-of-python-lists>).

We will only learn the basics of NumPy, to get started we need to install it!

Installation Instructions

It is highly recommended you install Python using the Anaconda distribution to make sure all underlying dependencies (such as Linear Algebra libraries) all sync up with the use of a conda install. If you have Anaconda, install NumPy by going to your terminal or command prompt and typing:

```
conda install numpy
```

If you do not have Anaconda and can not install it, please refer to [Numpy's official documentation on various installation instructions](http://docs.scipy.org/doc/numpy-1.10.1/user/install.html). (<http://docs.scipy.org/doc/numpy-1.10.1/user/install.html>)

Using NumPy

Once you've installed NumPy you can import it as a library:

In [1]:

```
1 import numpy
```

In [2]:

```
1 import numpy as np
```

to know the version of numpy

In [3]:

```
1 np.version.version
```

Out[3]:

```
'1.16.2'
```

In [1]:

```
1 import numpy as np
```

```
1 Numpy has many built-in functions and capabilities. We won't cover them all
  but instead we will focus on some of the most important aspects of Numpy:
  vectors, arrays, matrices, and number generation. Let's start by discussing
  arrays.
2
3 # Numpy Arrays
4
5 NumPy arrays are the main way we will use Numpy throughout the course. Numpy
  arrays essentially come in two flavors: vectors and matrices. Vectors are
  strictly 1-d arrays and matrices are 2-d (but you should note a matrix can
  still have only one row or one column).
6
7 Let's begin our introduction by exploring how to create NumPy arrays.
8
9 ## Creating NumPy Arrays
10
11 ### From a Python List
12
13 We can create an array by directly converting a list or list of lists:
```

In [4]:

```
1 mylist = [10,20,30]
2 print(mylist)
```

[10, 20, 30]

In [5]:

```
1 import numpy as np
2
3 my_array = np.array(mylist)
4
5 print(my_array)
6
7 print(type(my_array))
```

[10 20 30]
<class 'numpy.ndarray'>

In [19]:

```
1 my_list = [1,2,3]
2 my_list
```

Out[19]:

[1, 2, 3]

In [16]:

```
1 np.array(my_list)
```

Out[16]:

array([1, 2, 3])

In [6]:

```
1 mylist = [[10,20,30],[40,50,60],[60,70,80]]
2 print(mylist)
```

```
[[10, 20, 30], [40, 50, 60], [60, 70, 80]]
```

In [8]:

```
1 my_matrix = np.array(mylist)
2
3 print(my_matrix)
4
5 print(type(my_matrix))
```

```
[[10 20 30]
 [40 50 60]
 [60 70 80]]
<class 'numpy.ndarray'>
```

In [20]:

```
1 my_matrix = [[1,2,3],[4,5,6],[7,8,9]]
2 my_matrix
```

Out[20]:

```
[[1, 2, 3], [4, 5, 6], [7, 8, 9]]
```

In [9]:

```
1 np.array(my_matrix)
```

Out[9]:

```
array([[10, 20, 30],
       [40, 50, 60],
       [60, 70, 80]])
```

In []:

```
1
```

Built-in Methods

There are lots of built-in ways to generate Arrays

arange

Return evenly spaced values within a given interval.

In [13]:

```
1 np.arange(0,10)
```

Out[13]:

```
array([0, 1, 2, 3, 4, 5, 6, 7, 8, 9])
```

In [15]:

```
1 np.arange(0,11,2)
```

Out[15]:

```
array([ 0,  2,  4,  6,  8, 10])
```

In [22]:

```
1 np.zeros((2,2)) # multidimensional zero array
```

Out[22]:

```
array([[0., 0.],
       [0., 0.]])
```

In [19]:

```
1 np.zeros(shape=5)
```

Out[19]:

```
array([0., 0., 0., 0., 0., 0., 0., 0., 0., 0., 0., 0., 0., 0., 0.,
       0., 0.,
       0., 0., 0., 0., 0., 0., 0., 0.])
```

zeros and ones

Generate arrays of zeros or ones

In [23]:

```
1 np.zeros(3)
```

Out[23]:

```
array([0., 0., 0.])
```

In [25]:

```
1 np.zeros((5,5))
```

Out[25]:

```
array([[0., 0., 0., 0., 0.],
       [0., 0., 0., 0., 0.],
       [0., 0., 0., 0., 0.],
       [0., 0., 0., 0., 0.],
       [0., 0., 0., 0., 0.]])
```

In [27]:

```
1 np.ones(5)
```

Out[27]:

```
array([1., 1., 1., 1., 1.])
```

In [28]:

```
1 np.ones((3,3))
```

Out[28]:

```
array([[1., 1., 1.],
       [1., 1., 1.],
       [1., 1., 1.]])
```

In [27]:

```
1 np.ones(3)
```

Out[27]:

```
array([ 1.,  1.,  1.] )
```

In [28]:

```
1 np.ones((3,3))
```

Out[28]:

```
array([[ 1.,  1.,  1.],
       [ 1.,  1.,  1.],
       [ 1.,  1.,  1.]])
```

linspace

Return evenly spaced numbers over a specified interval.

In [32]:

```
1 np.linspace(2,3,num=20,retstep=True)
```

Out[32]:

```
(array([2.          , 2.05263158, 2.10526316, 2.15789474, 2.21052632,
        2.26315789, 2.31578947, 2.36842105, 2.42105263, 2.47368421,
        2.52631579, 2.57894737, 2.63157895, 2.68421053, 2.73684211,
        2.78947368, 2.84210526, 2.89473684, 2.94736842, 3.          ]),
 0.05263157894736842)
```

In [31]:

```
1 np.linspace(2,3,num=20)
```

Out[31]:

```
array([2.          , 2.05263158, 2.10526316, 2.15789474, 2.21052632,
        2.26315789, 2.31578947, 2.36842105, 2.42105263, 2.47368421,
        2.52631579, 2.57894737, 2.63157895, 2.68421053, 2.73684211,
        2.78947368, 2.84210526, 2.89473684, 2.94736842, 3.          ])
```

In [29]:

```
1 np.linspace(0,10,3)
```

Out[29]:

```
array([ 0.,  5., 10.]
```

In [33]:

```
1 np.linspace(0,10,50)
```

Out[33]:

```
array([ 0.          ,  0.20408163,  0.40816327,  0.6122449 ,  0.8163265
3,
        1.02040816,  1.2244898 ,  1.42857143,  1.63265306,  1.8367346
9,
        2.04081633,  2.24489796,  2.44897959,  2.65306122,  2.8571428
6,
        3.06122449,  3.26530612,  3.46938776,  3.67346939,  3.8775510
2,
        4.08163265,  4.28571429,  4.48979592,  4.69387755,  4.8979591
8,
        5.10204082,  5.30612245,  5.51020408,  5.71428571,  5.9183673
5,
        6.12244898,  6.32653061,  6.53061224,  6.73469388,  6.9387755
1,
        7.14285714,  7.34693878,  7.55102041,  7.75510204,  7.9591836
7,
        8.16326531,  8.36734694,  8.57142857,  8.7755102 ,  8.9795918
4,
        9.18367347,  9.3877551 ,  9.59183673,  9.79591837, 10.
])
```

In []:

```
1
```

eye

Creates an identity matrix

In [37]:

```
1 np.eye(4)
```

Out[37]:

```
array([[ 1.,  0.,  0.,  0.],
       [ 0.,  1.,  0.,  0.],
       [ 0.,  0.,  1.,  0.],
       [ 0.,  0.,  0.,  1.]])
```

Random

Numpy also has lots of ways to create random number arrays:

rand

Create an array of the given shape and populate it with random samples from a uniform distribution over $[0, 1)$.

In [39]:

```
1 np.random.rand(100)
```

Out[39]:

```
array([8.94650171e-01, 9.79226594e-01, 7.64087769e-01, 3.89042846e-0
1,
      3.66468493e-01, 4.48941235e-01, 8.35566850e-01, 8.18552341e-0
1,
      5.96208376e-01, 1.07947947e-01, 7.92567974e-01, 4.34653130e-0
1,
      4.79477793e-01, 3.43094395e-01, 4.97883318e-01, 5.14369214e-0
1,
      6.63776070e-01, 5.98419189e-01, 6.32073889e-01, 6.41324453e-0
1,
      7.87439479e-01, 5.50505387e-01, 3.60774455e-01, 9.23132276e-0
2,
      8.04627641e-01, 7.07630205e-01, 4.99133095e-01, 7.63396654e-0
1,
      1.73355427e-01, 4.06927907e-01, 3.35292827e-01, 8.89514355e-0
1,
      1.02988424e-01, 7.68691997e-01, 7.74987394e-01, 1.92594252e-0
1,
      9.64284533e-01, 7.58000720e-01, 1.62951869e-02, 7.93930902e-0
1,
      3.50591209e-01, 6.91974775e-01, 1.11633032e-01, 4.41497555e-0
1,
      7.07690624e-01, 4.69882596e-01, 5.44882116e-01, 4.76966468e-0
4,
      9.40605996e-01, 5.56439676e-01, 7.61924463e-01, 9.90576954e-0
1,
      8.05035612e-01, 4.38744620e-01, 6.78439720e-02, 8.28236436e-0
1,
      8.75093326e-02, 3.31350094e-01, 5.32914609e-01, 7.93003704e-0
1,
      9.80337400e-03, 1.05862627e-01, 8.28965492e-01, 6.72258912e-0
1,
      3.88528688e-01, 7.61363294e-01, 9.90115304e-01, 1.00384185e-0
1,
      2.62818206e-01, 2.08077277e-01, 9.56277813e-01, 9.78110260e-0
1,
      6.85987876e-01, 2.00771760e-01, 6.43309306e-01, 3.18596725e-0
2,
      4.63628734e-02, 5.28610627e-01, 3.93815828e-01, 8.75617303e-0
1,
      4.37033917e-01, 4.30159925e-01, 1.90087230e-02, 8.89999968e-0
1,
      1.02149838e-01, 7.09069633e-01, 8.85121991e-01, 5.15881416e-0
1,
      1.43840947e-01, 2.81577184e-02, 6.30630743e-01, 6.26374437e-0
1,
      4.90124965e-01, 2.55818224e-01, 2.81746329e-01, 6.79050021e-0
1,
      3.89931433e-01, 5.34172486e-01, 7.71647762e-01, 3.99091402e-0
1])
```


In [47]:

```
1 np.random.rand(2)
```

Out[47]:

```
array([ 0.11570539,  0.35279769])
```

In [40]:

```
1 np.random.rand(5,5)
```

Out[40]:

```
array([[0.75951951, 0.72807956, 0.68448304, 0.29781566, 0.15030654],
       [0.81455425, 0.86617146, 0.77332789, 0.88133021, 0.28842271],
       [0.11398111, 0.57798679, 0.06282019, 0.35273068, 0.95130955],
       [0.8862607 , 0.38382306, 0.13089583, 0.59603416, 0.31688529],
       [0.04514687, 0.98536565, 0.35441165, 0.67865398, 0.28528138]])
```

randn

Return a sample (or samples) from the "standard normal" distribution. Unlike rand which is uniform:

In [43]:

```
1 np.random.randn(5)
```

Out[43]:

```
array([-1.22769474, -0.59339774,  0.37167196,  0.39072925, -0.11187642])
```

In [48]:

```
1 np.random.randn(2)
```

Out[48]:

```
array([-0.27954018,  0.90078368])
```

In [44]:

```
1 np.random.randn(5,5)
```

Out[44]:

```
array([[ -0.35462371,  0.91424598,  0.2405601 ,  0.98423074,  0.415344
 1 ],
       [ 1.18082761, -0.05228707, -0.89882753,  1.79168507, -0.754186
54],
       [-1.28113367, -1.90530855, -1.03665151,  0.18042468,  0.180320
99],
       [ 0.43517816, -1.53495221,  0.44257103, -0.67334983, -3.256499
76],
       [ 0.1577172 ,  0.24773989,  0.32322112, -1.08097095, -0.178963
32]])
```

randint

Return random integers from `low` (inclusive) to `high` (exclusive).

In [50]:

```
1 np.random.randint(1,100)
```

Out[50]:

44

In [46]:

```
1 np.random.randint(1,50,30).astype("float")
```

Out[46]:

```
array([44., 20., 44., 34., 10., 45., 37., 25., 30., 28., 26., 35., 1
 7.,
      47.,  2., 21., 46., 28., 48., 31., 13., 16., 23., 41., 37.,
 6.,
      27., 21., 39., 36.])
```

In [47]:

```
1 np.random.randint(1,100,10)
```

Out[47]:

```
array([73, 47, 98, 56, 69,  2, 81, 61, 13, 42])
```

In [72]:

```
1 res = np.random.uniform(10.1,50.4,40)
```

Array Attributes and Methods

Let's discuss some useful attributes and methods of an array:

In [55]:

```
1 arr = np.arange(25)
2 ranarr = np.random.randint(0,50,10)
```

In [56]:

```
1 arr
```

Out[56]:

```
array([ 0,  1,  2,  3,  4,  5,  6,  7,  8,  9, 10, 11, 12, 13, 14, 1
 5, 16,
      17, 18, 19, 20, 21, 22, 23, 24])
```

In [51]:

```
1 myarr = np.random.randint(1,60,50)
```

In [52]:

```
1 myarr
```

Out[52]:

```
array([27,  2, 19, 58, 47, 12, 13,  4, 45, 32, 13, 52,  2, 41, 48,  5,
        1, 57,
        2, 15, 34,  8, 19, 52,  8, 35, 28, 40, 33, 50, 40, 48,  1,  3,
        4, 47,
        37, 42, 34, 51, 51, 33, 39, 29,  9, 12,  7, 15, 30, 36, 46,
        6])
```

In [54]:

```
1 myarr.reshape(5,10)
```

Out[54]:

```
array([[27,  2, 19, 58, 47, 12, 13,  4, 45, 32],
       [13, 52,  2, 41, 48, 51, 57,  2, 15, 34],
       [ 8, 19, 52,  8, 35, 28, 40, 33, 50, 40],
       [48,  1, 34, 47, 37, 42, 34, 51, 51, 33],
       [39, 29,  9, 12,  7, 15, 30, 36, 46,  6]])
```

Reshape

Returns an array containing the same data with a new shape.

In [57]:

```
1 myarr = myarr.reshape(5,10)
```

In [58]:

```
1 myarr
```

Out[58]:

```
array([[27,  2, 19, 58, 47, 12, 13,  4, 45, 32],
       [13, 52,  2, 41, 48, 51, 57,  2, 15, 34],
       [ 8, 19, 52,  8, 35, 28, 40, 33, 50, 40],
       [48,  1, 34, 47, 37, 42, 34, 51, 51, 33],
       [39, 29,  9, 12,  7, 15, 30, 36, 46,  6]])
```

max,min,argmax,argmin

These are useful methods for finding max or min values. Or to find their index locations using argmin or argmax

In [59]:

```
1 myarr
```

Out[59]:

```
array([[27,  2, 19, 58, 47, 12, 13,  4, 45, 32],
       [13, 52,  2, 41, 48, 51, 57,  2, 15, 34],
       [ 8, 19, 52,  8, 35, 28, 40, 33, 50, 40],
       [48,  1, 34, 47, 37, 42, 34, 51, 51, 33],
       [39, 29,  9, 12,  7, 15, 30, 36, 46,  6]])
```

In [60]:

```
1 myarr.max()
```

Out[60]:

58

In [61]:

```
1 myarr.argmax()
```

Out[61]:

3

In [62]:

```
1 myarr.min()
```

Out[62]:

1

In [63]:

```
1 myarr.argmin()
```

Out[63]:

31

Shape

Shape is an attribute that arrays have (not a method):

In [65]:

```
1 # Vector
2 myarr.shape
```

Out[65]:

(5, 10)

In [67]:

```
1 # Notice the two sets of brackets
2 myarr.reshape(1,50)
```

Out[67]:

```
array([[27,  2, 19, 58, 47, 12, 13,  4, 45, 32, 13, 52,  2, 41, 48, 5
1,
        57,  2, 15, 34,  8, 19, 52,  8, 35, 28, 40, 33, 50, 40, 48,
1,
        34, 47, 37, 42, 34, 51, 51, 33, 39, 29,  9, 12,  7, 15, 30, 3
6,
        46,  6]])
```

In [68]:

```
1 myarr.reshape(1,50).shape
```

Out[68]:

```
(1, 50)
```

In [69]:

```
1 myarr.reshape(50,1)
```

Out[69]:

```
array([[27],
       [ 2],
       [19],
       [58],
       [47],
       [12],
       [13],
       [ 4],
       [45],
       [32],
       [13],
       [52],
       [ 2],
       [41],
       [48],
       [51],
       [57],
       [ 2],
       [15],
       [34],
       [ 8],
       [19],
       [52],
       [ 8],
       [35],
       [28],
       [40],
       [33],
       [50],
       [40],
       [48],
       [ 1],
       [34],
       [47],
       [37],
       [42],
       [34],
       [51],
       [51],
       [33],
       [39],
       [29],
       [ 9],
       [12],
       [ 7],
       [15],
       [30],
       [36],
       [46],
       [ 6]])
```

In [70]:

```
1 myarr.reshape(50,1).shape
```

Out[70]:

```
(50, 1)
```

dtype

You can also grab the data type of the object in the array:

In [71]:

```
1 myarr.dtype
```

Out[71]:

```
dtype('int64')
```

Type *Markdown* and LaTeX: α^2

In [73]:

```
1 res.dtype
```

Out[73]:

```
dtype('float64')
```

In []:

```
1
```