# DCode®

DC3M

Mobile Label Printer

- Support direct USB charging;

- 50mm diameter paper roll

- OLED screen available;

- TSPL, EPL, ZPL, DPL, CPCL, ESC/POS command compatible.

DC3M
Mobile Label Printer

Printing	DC3M
Resolution	203 DPI
Printing method	Direct Thermal
Print speed	70mm (2.7") / s
Print width	72 mm (2.8")
Print length	1778 mm (70")
Media	
Media type	Continuous, gap, black mark
Media width	25.4 mm ~ 76 mm
Media thickness	0.06 mm ~0.16 mm
Performance Features	
Processor	32-bit CPU
Memory	8MB Flash Memory/ 8MB SDRAM
Interface	USB+Bluetooth
Screen	OLED (0.96") Resolution:128*64 pix
Sensors	①Gap sensor　②Cover opening sensor　③Black mark sensor
Fonts/Graphics/Symbologies	
Internal fonts	8 alpha-numeric bitmap fonts, Windows fonts are downloadable from software.
1D bar code	Code 39, Code 93, Code 128UCC, Code 128 subsets A, B, C, Codabar, Interleaved 2 of 5, EAN-8,EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on,MSI, PLESSEY, POSTNET, China POST
2D bar code	PDF-417, Maxicode, DataMatrix, QR code
Rotation	0°、90°、180°、270°
Emulaion	TSPL、EPL、ZPL、DPL、CPCL、ESC/POS
Physical Features	
Dimensions	120×112×60mm (D×W×H)
Weight	400 g
Reliability	
Printer head life	30Km
Software	
Operation system	Windows / Android / iOS
SDK	Windows / Android / iOS
Power supply	
USB	DC 5V/2A
Battery	2500mAh
Environmental Conditions	
Operation environment	5 ~ 40°C（41~104°F），Humidity: 25 ~ 85% no condensing
Storage environment	-40 ~ 60°C（-40~140°F），Humidity: 10 ~ 90% no condensing

www.dcodeinternational.com