# DCode®

DC2M

Mobile Receipt & Label Printer

- Printing speed: Min 50.8mm/s,
- Max 101mm/s
- Print width: 48mm
- Maximum roll diameter: 50mm
- Support thermal paper / thermal adhesive paper

DC2M

Mobile Receipt & Label Printer

Printing Features	Label print mode	Receipt print mode
Printing method	Direct thermal	
Resolution	203 DPI	
Print width	Max.48 mm	
Max.print speed	Min. 50.8 mm/s, Max. 101 mm/s	90 mm/s
Media		
Media type	Thermal paper roll /Thermal adhesive paper	Thermal paper
Media width	20mm ~ 60mm	58 mm
Media external diameter	50 mm	
Paper out method	Tearing-off	
Performance Features		
Print head detection	Thermistor	
Print head position detection	Micro Switch	
Media detection	Photoelectric Sensors	
Interface	USB+Bluetooth	
Storage	Flash 576 kb	
Fonts/Graphics/Symbologies		
Character size	Font 0 to Font8	Font A: 12x24,Font B: 9x17, CHN: 24*24
1D bar code	CODE128、EAN128、ITF、CODE25、CODE39、CODE39C、CODE39S、CODE93、EAN13、EAN13+2、EAN13+5、EAN8、EAN8+2、EAN8+5、CODABAR、POSTNET、UPC-A、UPCA+2、UPCA+5、UPCE、UPCE+2、UPCE+5、MSI、MSIC、PLESSEY、ITF14、EAN14	UPC-A/UPC-E/JAN13（EAN13）/ JAN8(EAN8)/CODE39/ITF/CODABAR/ CODE93/CODE128
2D bar code	QR CODE	
Rotation	0°、90°、180°、270°	
Physical Features		
Gross weight	122.28*93.99*60.07mm (L*W*H)	
Dimensions	0.343 kg	
Software		
Systems	Windows/Android/iOS	
Power supply		
Battery	DC 7.2V/2500MAH	
Charging input	Standard USB cable charging: 5V / 2A Optional DC adapter charging: 9V / 2A	
Environmental Conditions		
Work environment	0 ~ 45℃, 10 ~ 80%RH no condensing	
Storage environment	-10 ~ 60 ℃, ≤93% RH (40℃) no condensing	

www.dcodeinternational.com