

APPENDIX C — SAMPLE SEARCH AND SORT ALGORITHMS

Sequential Search

The Sequential Search Algorithm below finds the index of a value in an array of integers as follows:

1. Traverse `elements` until `target` is located, or the end of `elements` is reached.
2. If `target` is located, return the index of `target` in `elements`;
Otherwise return `-1`.

```
/**
 * Finds the index of a value in an array of integers.
 *
 * @param elements an array containing the items to be searched.
 * @param target the item to be found in elements.
 * @return an index of target in elements if found; -1 otherwise.
 */
public static int sequentialSearch(int[] elements, int target)
{
    for (int j = 0; j < elements.length; j++)
    {
        if (elements[j] == target)
        {
            return j;
        }
    }

    return -1;
}
```

Binary Search

The Binary Search Algorithm below finds the index of a value in an array of integers sorted in ascending order as follows:

1. Set `left` and `right` to the minimum and maximum indexes of `elements` respectively.
2. Loop until `target` is found, or `target` is determined not to be in `elements` by doing the following for each iteration:
 - a. Set `middle` to the index of the middle item in `elements[left] ... elements[right]` inclusive.
 - b. If `target` would have to be in `elements[left] ... elements[middle - 1]` inclusive, then set `right` to the maximum index for that range.
 - c. Otherwise, if `target` would have to be in `elements[middle + 1] ... elements[right]` inclusive, then set `left` to the minimum index for that range.
 - d. Otherwise, return `middle` because `target == elements[middle]`.
3. Return `-1` if `target` is not contained in `elements`.

```

/**
 * Find the index of a value in an array of integers sorted in ascending order.
 *
 * @param elements an array containing the items to be searched.
 * Precondition: items in elements are sorted in ascending order.
 * @param target the item to be found in elements.
 * @return an index of target in elements if target found;
 *         -1 otherwise.
 */
public static int binarySearch(int[] elements, int target)
{
    int left = 0;
    int right = elements.length - 1;
    while (left <= right)
    {
        int middle = (left + right) / 2;
        if (target < elements[middle])
        {
            right = middle - 1;
        }
        else if (target > elements[middle])
        {
            left = middle + 1;
        }
        else
        {
            return middle;
        }
    }
    return -1;
}

```

Selection Sort

The Selection Sort Algorithm below sorts an array of integers into ascending order as follows:

1. Loop from $j = 0$ to $j = \text{elements.length}-2$, inclusive, completing $\text{elements.length}-1$ passes.
2. In each pass, swap the item at index j with the minimum item in the rest of the array ($\text{elements}[j+1]$ through $\text{elements}[\text{elements.length}-1]$).

At the end of each pass, items in $\text{elements}[0]$ through $\text{elements}[j]$ are in ascending order and each item in this sorted portion is at its final position in the array

```
/**
 * Sort an array of integers into ascending order.
 *
 * @param elements an array containing the items to be sorted.
 *
 * Postcondition: elements contains its original items and items in elements
 *                  are sorted in ascending order.
 */
public static void selectionSort(int[] elements)
{
    for (int j = 0; j < elements.length - 1; j++)
    {
        int minIndex = j;
        for (int k = j + 1; k < elements.length; k++)
        {
            if (elements[k] < elements[minIndex])
            {
                minIndex = k;
            }
        }

        int temp = elements[j];
        elements[j] = elements[minIndex];
        elements[minIndex] = temp;
    }
}
```

Insertion Sort

The Insertion Sort Algorithm below sorts an array of integers into ascending order as follows:

1. Loop from $j = 1$ to $j = \text{elements.length}-1$ inclusive, completing $\text{elements.length}-1$ passes.
2. In each pass, move the item at index j to its proper position in $\text{elements}[0]$ to $\text{elements}[j]$:
 - a. Copy item at index j to temp , creating a “vacant” element at index j (denoted by possibleIndex).
 - b. Loop until the proper position to maintain ascending order is found for temp .
 - c. In each inner loop iteration, move the “vacant” element one position lower in the array.
3. Copy temp into the identified correct position (at possibleIndex).

At the end of each pass, items at $\text{elements}[0]$ through $\text{elements}[j]$ are in ascending order.

```
/**
 * Sort an array of integers into ascending order.
 *
 * @param elements an array containing the items to be sorted.
 *
 * Postcondition: elements contains its original items and items in elements
 *                  are sorted in ascending order.
 */
public static void insertionSort(int[] elements)
{
    for (int j = 1; j < elements.length; j++)
    {
        int temp = elements[j];
        int possibleIndex = j;
        while (possibleIndex > 0 && temp < elements[possibleIndex - 1])
        {
            elements[possibleIndex] = elements[possibleIndex - 1];
            possibleIndex--;
        }
        elements[possibleIndex] = temp;
    }
}
```

Merge Sort

The Merge Sort Algorithm below sorts an array of integers into ascending order as follows:

mergeSort

This top-level method creates the necessary temporary array and calls the `mergeSortHelper` recursive helper method.

mergeSortHelper

This recursive helper method uses the Merge Sort Algorithm to sort `elements[from] ... elements[to]` inclusive into ascending order:

1. If there is more than one item in this range,
 - a. divide the items into two adjacent parts, and
 - b. call `mergeSortHelper` to recursively sort each part, and
 - c. call the `merge` helper method to merge the two parts into sorted order.
2. Otherwise, exit because these items are sorted.

merge

This helper method merges two adjacent array parts, each of which has been sorted into ascending order, into one array part that is sorted into ascending order:

1. As long as both array parts have at least one item that hasn't been copied, compare the first un-copied item in each part and copy the minimal item to the next position in `temp`.
2. Copy any remaining items of the first part to `temp`.
3. Copy any remaining items of the second part to `temp`.
4. Copy the items from `temp[from] ... temp[to]` inclusive to the respective locations in `elements`.

```
/**
 * Sort an array of integers into ascending order.
 *
 * @param elements an array containing the items to be sorted.
 *
 * Postcondition: elements contains its original items and items in elements
 *                  are sorted in ascending order.
 */
public static void mergeSort(int[] elements)
{
    int n = elements.length;
    int[] temp = new int[n];
    mergeSortHelper(elements, 0, n - 1, temp);
}
```

```

/**
 * Sorts elements[from] ... elements[to] inclusive into ascending order.
 *
 * @param elements an array containing the items to be sorted.
 * @param from the beginning index of the items in elements to be sorted.
 * @param to the ending index of the items in elements to be sorted.
 * @param temp a temporary array to use during the merge process.
 *
 * Precondition:
 * (elements.length == 0 or
 *  0 <= from <= to <= elements.length) and
 *  elements.length == temp.length
 * Postcondition: elements contains its original items and the items in elements
 * [from] ... <= elements[to] are sorted in ascending order.
 */
private static void mergeSortHelper(int[] elements,
                                     int from, int to, int[] temp)
{
    if (from < to)
    {
        int middle = (from + to) / 2;
        mergeSortHelper(elements, from, middle, temp);
        mergeSortHelper(elements, middle + 1, to, temp);
        merge(elements, from, middle, to, temp);
    }
}

```

```

/**
 * Merges two adjacent array parts, each of which has been sorted into ascending
 * order, into one array part that is sorted into ascending order.
 *
 * @param elements an array containing the parts to be merged.
 * @param from the beginning index in elements of the first part.
 * @param mid the ending index in elements of the first part.
 *           mid+1 is the beginning index in elements of the second part.
 * @param to the ending index in elements of the second part.
 * @param temp a temporary array to use during the merge process.
 *
 * Precondition: 0 <= from <= mid <= to <= elements.length and
 *   elements[from] ... <= elements[mid] are sorted in ascending order and
 *   elements[mid + 1] ... <= elements[to] are sorted in ascending order and
 *   elements.length == temp.length
 * Postcondition: elements contains its original items and
 *   elements[from] ... <= elements[to] are sorted in ascending order and
 *   elements[0] ... elements[from - 1] are in original order and
 *   elements[to + 1] ... elements[elements.length - 1] are in original order.
 */
private static void merge(int[] elements,
                          int from, int mid, int to, int[] temp)
{
    int i = from;
    int j = mid + 1;
    int k = from;

    while (i <= mid && j <= to)
    {
        if (elements[i] < elements[j])
        {
            temp[k] = elements[i];
            i++;
        }
        else
        {
            temp[k] = elements[j];
            j++;
        }
        k++;
    }
}

```



```

while (i <= mid)
{
    temp[k] = elements[i];
    i++;
    k++;
}

while (j <= to)
{
    temp[k] = elements[j];
    j++;
    k++;
}

for (k = from; k <= to; k++)
{
    elements[k] = temp[k];
}
}

```