

Device Spec Sheet

KS 100 vessel terminal

Overview

A fixed mount satellite terminal for vessels between 24 and 58 feet. Powered from the vessel's 12 volt supply with a 36 hour internal battery. Designed to survive a wheelhouse that is wet, hot and vibrating.

Specification

Network	Low earth orbit short burst data, 1616 to 1626.5 MHz
Position accuracy	GNSS, 2.5 metres CEP
Beacon interval	10 minutes default, 60 seconds after a distress event
Distress latency, median	41 seconds to relay acknowledgement
Power	12 V vessel supply, 36 hour internal battery
Display	3.5 inch sunlight readable, Malayalam and English
Enclosure	IP67, salt spray tested to 720 hours
Dimensions	184 by 122 by 58 millimetres, 940 grams
Antenna	Mast mount, 4 metre cable, marine grade
Warranty	24 months, on vessel replacement

Distress function

A physical guarded button, held for three seconds, transmits position and vessel identifier to the coast guard relay and to the registered harbour society simultaneously. Transmission is acknowledged back to the vessel so the crew knows it was received.

Environmental

IP67 rated. Salt spray tested to 720 hours. Operating range 0 to 60 degrees Celsius. Field failure rate 2.1 percent over the first 24 months across 3,100 units.