```
Administrator Command Prompt - sqlplus / as sysdba                                         —    □    X

Microsoft Windows [Version 10.0.18363.628]
(c) 2019 Microsoft Corporation. All rights reserved.

C:\WINDOWS\system32>sqlplus / as sysdba

SQL*Plus: Release 19.0.0.0.0 - Production on Fri Jan 31 15:05:10 2020
Version 19.3.0.0.0

Copyright (c) 1982, 2019, Oracle.  All rights reserved.


Connected to:
Oracle Database 19c Enterprise Edition Release 19.0.0.0.0 - Production
Version 19.3.0.0.0

SQL>
```

```
SQL> create table person
  2         (driver_id varchar2(10) primary key,
  3          name varchar2(10),
  4          address varchar2(10));

Table created.

SQL> desc person
 Name                                      Null?    Type
 ----------------------------------------- -------- ----------------------------
 DRIVER_ID                                 NOT NULL VARCHAR2(10)
 NAME                                               VARCHAR2(10)
 ADDRESS                                            VARCHAR2(10)

SQL>
```

```
  4          year number(10));

Table created.

SQL> desc car
 Name                                      Null?    Type
 ----------------------------------------- -------- ----------------------------
 REGNO                                     NOT NULL VARCHAR2(10)
 MODEL                                              VARCHAR2(10)
 YEAR                                               NUMBER(10)

SQL> create table accident
  2          (repno number(10) primary key,
  3          regdate date,
  4          location varchar2(10));

Table created.

SQL>
```

```
Table created.

SQL> desc accident
 Name                                      Null?    Type
 ---------------------------------------   -------- ----------------------------
 REPNO                                     NOT NULL NUMBER(10)
 REGDATE                                            DATE
 LOCATION                                           VARCHAR2(10)

SQL> create table owner
  2         (driver_id varchar2(10) not null,
  3         regno varchar2(10),
  4         foreign key(driver_id) references person(driver_id),
  5         foreign key(regno) references car(regno));

Table created.

SQL> desc owner
 Name                                      Null?    Type
 ---------------------------------------   -------- ----------------------------
 DRIVER_ID                                 NOT NULL VARCHAR2(10)
 REGNO                                              VARCHAR2(10)

SQL>
```

```
DRIVER_ID                                      NOT NULL VARCHAR2(10)
REGNO                                                   VARCHAR2(10)

SQL> create table participation
  2         (driver_id varchar2(10),
  3          regno varchar2(10),
  4          repno number(10),
  5          damage_amt number(10),
  6          foreign key(driver_id) references person(driver_id),
  7          foreign key(regno) references car(regno),
  8          foreign key(repno) references accident(repno));

Table created.

SQL> desc participation
 Name                                    Null?     Type
 ----------------------------------      --------  ----------------------------

 DRIVER_ID                                         VARCHAR2(10)
 REGNO                                             VARCHAR2(10)
 REPNO                                             NUMBER(10)
 DAMAGE_AMT                                        NUMBER(10)

SQL> insert into person values ('&driver_id','&name','&address');
Enter value for driver_id: 1
Enter value for name: _
```

```
----------------------------------------     -----------------------------------
 DRIVER_ID                                     VARCHAR2(10)
 REGNO                                         VARCHAR2(10)
 REPNO                                         NUMBER(10)
 DAMAGE_AMT                                    NUMBER(10)

SQL> insert into person values ('&driver_id','&name','&address');
Enter value for driver_id: 1
Enter value for name: khushi
Enter value for address: saun
old    1: insert into person values ('&driver_id','&name','&address')
new    1: insert into person values ('1','khushi','saun')

1 row created.

SQL> /
Enter value for driver_id: 2
Enter value for name: mamata
Enter value for address: bgl
old    1: insert into person values ('&driver_id','&name','&address')
new    1: insert into person values ('2','mamata','bgl')

1 row created.

SQL>
```

```
old    1: insert into person values ('&driver_id','&name','&address')
new    1: insert into person values ('2','mamata','bgl')

1 row created.

SQL> /
Enter value for driver_id: 3
Enter value for name: shri
Enter value for address: abk
old    1: insert into person values ('&driver_id','&name','&address')
new    1: insert into person values ('3','shri','abk')

1 row created.

SQL> /
Enter value for driver_id: 4
Enter value for name: san
Enter value for address: ath
old    1: insert into person values ('&driver_id','&name','&address')
new    1: insert into person values ('4','san','ath')

1 row created.

SQL> /
Enter value for driver_id:
```

```
SQL> select * from person;

Fri Jan 31                                          page      1
                    **************PERSON**********

DRIVER_ID   NAME          ADDRESS
----------  ----------    ----------
1           khushi        saun
2           mamata        bgl
3           shri          abk
4           san           ath
5           savita        dwd



            **************END************

SQL>
```