## FastAPI

## Андрей Шулаев


Senior Software Engineer at EPAM Systems

Skillbox

## Краткий обзор основных возможностей

Устройство	Такты CPU	~ человеческий аналог
L1 cache	3	1 секунда
L2 cache	14	4,6 секунд
RAM	250	83 секунды
Disk	41 000 000	158 дней
Network	24 000 0000	2,5 лет

```
@app.get("/hello_async")
@async def hello_async() -> Dict[str, str]:
    return {"message": "Hello World"}
```



```
class FastAPI(Starlette):
    def __init__(
        self,
        *,
       debug: bool = False,
       routes: Optional[List[BaseRoute]] = None,
        title: str = "FastAPI",
       description: str = "",
       version: str = "0.1.0",
       openapi_url: Optional[str] = "/openapi.json",
       openapi_tags: Optional[List[Dict[str, Any]]] = None,
       servers: Optional[List[Dict[str, Union[str, Any]]]] = None,
       dependencies: Optional[Sequence[Depends]] = None,
       default_response_class: Type[Response] = Default(JSONResponse),
       docs_url: Optional[str] = "/docs",
       redoc_url: Optional[str] = "/redoc",
        swagger_ui_oauth2_redirect_url: Optional[str] = "/docs/oauth2-redirect",
       swagger_ui_init_oauth: Optional[Dict[str, Any]] = None,
       middleware: Optional[Sequence[Middleware]] = None,
        exception_handlers: Optional[
            Dict[
                Union[int, Type[Exception]],
                Callable[[Request, Any], Coroutine[Any, Any, Response]],
FastAPI
```

```
@app.get('/books/', response_model=List[schemas.BookOut])
@async def books() -> List[models.Book]:
    return await session.execute(select(models.Book))
```



default		
GET	/books/ Books	
Parameter		
No parame	ters	
Responses		
Code	Description	
200	Successful Response	
	Media type	
	application/json  Controls Accept header.	
	Example Value   Schema	
	[	