

Complexity: Problems for Week 4

Exercise 1 Given the running times of programs/algorithms, evaluate the corresponding complexities.

- (a) The running time of my program, on an argument of size n , is $3n^2 + 9n + 8$. Is this $O(n^2)$? Is it $O(n)$? Is it $O(n^3)$?
- (b) The running time of my program, on an argument of size n , is 5^n for $n < 1000$, and $3n^2 + 9n + 8$ for $n \geq 1000$. Is this $O(n^2)$? Is it $O(n)$? Is it $O(n^3)$?
- (c) On an argument of size n , I first run a program whose running time is in $O(n^2)$, and then run a program whose running time is in $O(n^3)$. Show that the total running time is in $O(n^3)$.
- (d) Suppose you have two algorithms to solve a given problem. The first algorithm has a running time of $3n^2 + 2n + 33$ while the second algorithm has a running time of $2^n - 5n + 5$. Which one will you prefer and why?

Exercise 2 The following program operates on an array of characters that are all **a** or **b**.

```
void f (char[] p) {
    elapse(1 second);
    for (nat i = 0; i < p.length(), i++) {
        if (p[i] == 'a') {
            elapse(1 second);
        } else {
            elapse(2 seconds);
        }
    }
    elapse (1 second);
}
```

What is the average time taken to process an array of length 4, assuming that the character in position i (starting from 0) has probability 2^{-i} of being **a**, and that the characters are independent? Also, what would be the worst case?

Exercise 3 (a) My program takes 2^{2^n} steps on every input of size $n < 100000$, and $5n^3 + 3n + 8$ steps on every input of size $n \geq 100000$. Show that the running time is in $O(n^3)$.

(b) Show that if $f \in O(g)$ and $g \in O(h)$ then $f \in O(h)$.

(c) Show that $2^n \in O(n!)$

Exercise 4 (a) A sorting method with Big-O complexity $O(n \log n)$ spends exactly 1 millisecond to sort 1000 data items. Assuming that time $T(n)$ of sorting n items is directly proportional to $n \log n$, that is, $T(n) = Cn \log n$, derive a formula for $T(n)$, given the time $T(N)$ for sorting $N = 1000$ items, and estimate how long this method will take to sort $n = 1000000$ items.

(b) One of the two software packages, A or B, should be chosen to process very big databases, containing up to 10^{16} records. Average processing time of the package A is $T_A(n) = 0.1n \log_2 n$ microseconds, and the average processing time of the package B is $T_B(n) = 6n$ microseconds.

Which algorithm has better performance in Big-O sense? Work out the exact conditions when these packages outperform each other.

Exercise 5 Compute the time complexity (with respect to N) of the following functions. Give an informal justification. (Complexity proof is not required.)

(a) The function $A()$ is doing some processing on a string:

```
void A(String str){
    nat N = str.length();
    for(nat i = 0; i < N; i = i+1){
        <do something here>
    }
    for(nat i = 0; i < N; i = i+1){
        for(nat j = 0; j < N; j = j+1){
            <do something here>
        }
    }
    for(nat i = 0; i < N; i = i+1){
        for(nat j = 0; j < N; j = j+1){
            <do something here>
        }
    }
}
```

(b) The function $B()$ is doing some processing on a string:

```
void B(String str){
    nat N = str.length();
    for(nat j = 2 * N; j > 0; j = j-1){
        for(nat i = N; i > 0; i = i/2){
            <do something here>
        }
    }
}
```

(c) The function $C()$ is doing some processing on a string:

```
void C(String str){
    nat N = str.length();
    nat i = 1000;
    nat k = 0;
    while(i > 1){
        for(nat j = 1; j < N*N; j = j+1){
            <do something here>
            if (j < N)
                k += 1;
        }
        i = i - 1;
    }
}
```

(d) The function $D()$ is processing the number N , using recursion:

```
nat D(nat N) {  
    if (N == 1) {  
        return 1;  
    }  
    else{  
        D(N-1);  
        D(N-1);  
    }  
}
```

Exercise 6 Callum writes a program that operates on an array of **a**'s and **b**'s. The time taken is $5A^2 + 2B^3$, where A is the number of **a**'s and B the number of **b**'s. If n is the length of the array, show that, in the worst case, the time taken is $O(n^3)$.