

Mark Scheme (Results)

January 2013

GCE Mechanics M2 (6678/01)

Edexcel and BTEC Qualifications

Edexcel and BTEC qualifications come from Pearson, the world's leading learning company. We provide a wide range of qualifications including academic, vocational, occupational and specific programmes for employers. For further information visit our qualifications websites at www.edexcel.com or www.btec.co.uk for our BTEC qualifications.

Alternatively, you can get in touch with us using the details on our contact us page at www.edexcel.com/contactus.

If you have any subject specific questions about this specification that require the help of a subject specialist, you can speak directly to the subject team at Pearson. Their contact details can be found on this link: www.edexcel.com/teachingservices.

You can also use our online Ask the Expert service at www.edexcel.com/ask. You will need an Edexcel username and password to access this service.

Pearson: helping people progress, everywhere

Our aim is to help everyone progress in their lives through education. We believe in every kind of learning, for all kinds of people, wherever they are in the world. We've been involved in education for over 150 years, and by working across 70 countries, in 100 languages, we have built an international reputation for our commitment to high standards and raising achievement through innovation in education. Find out more about how we can help you and your students at: www.pearson.com/uk

January 2013
Publications Code UA034765
All the material in this publication is copyright
© Pearson Education Ltd 2013

General Marking Guidance

- All candidates must receive the same treatment. Examiners must mark the first candidate in exactly the same way as they mark the last.
- Mark schemes should be applied positively. Candidates must be rewarded for what they have shown they can do rather than penalised for omissions.
- Examiners should mark according to the mark scheme not according to their perception of where the grade boundaries may lie.
- There is no ceiling on achievement. All marks on the mark scheme should be used appropriately.
- All the marks on the mark scheme are designed to be awarded. Examiners should always award full marks if deserved, i.e. if the answer matches the mark scheme. Examiners should also be prepared to award zero marks if the candidate's response is not worthy of credit according to the mark scheme.
- Where some judgement is required, mark schemes will provide the principles by which marks will be awarded and exemplification may be limited.
- When examiners are in doubt regarding the application of the mark scheme to a candidate's response, the team leader must be consulted.
- Crossed out work should be marked UNLESS the candidate has replaced it with an alternative response.

EDEXCEL GCE MATHEMATICS

General Instructions for Marking

- 1. The total number of marks for the paper is 75.
- 2. The Edexcel Mathematics mark schemes use the following types of marks:
- **M** marks: method marks are awarded for 'knowing a method and attempting to apply it', unless otherwise indicated.
- A marks: Accuracy marks can only be awarded if the relevant method (M) marks have been earned.
- **B** marks are unconditional accuracy marks (independent of M marks)
- Marks should not be subdivided.

In some instances, the mark distributions (e.g. M1, B1 and A1) printed on the candidate's response may differ from the final mark scheme.

3. Abbreviations

These are some of the traditional marking abbreviations that will appear in the mark schemes.

- bod benefit of doubt
- ft follow through
- the symbol $\sqrt{\text{will}}$ be used for correct ft
- cao correct answer only
- cso correct solution only. There must be no errors in this part of the question to obtain this mark
- isw ignore subsequent working
- awrt answers which round to
- SC: special case
- oe or equivalent (and appropriate)
- dep dependent
- indep independent
- dp decimal places
- sf significant figures
- * The answer is printed on the paper
- The second mark is dependent on gaining the first mark
- 4. All A marks are 'correct answer only' (cao.), unless shown, for example, as A1 ft to indicate that previous wrong working is to be followed through. After a misread however, the subsequent A marks affected are treated as A ft, but incorrect answers should never be awarded A marks.
- 5. For misreading which does not alter the character of a question or materially simplify it, deduct two from any A or B marks gained, in that part of the question affected.
- 6. If a candidate makes more than one attempt at any question:
 - If all but one attempt is crossed out, mark the attempt which is NOT crossed out.

- If either all attempts are crossed out or none are crossed out, mark all the attempts and score the highest single attempt.
- 7. Ignore wrong working or incorrect statements following a correct answer.
- 8. The maximum mark allocation for each question/part question(item) is set out in the marking grid and you should allocate a score of '0' or '1' for each mark, or "trait", as shown:

	0	1
аМ		•
аА	•	
bM1		•
bA1	•	
bB	•	
bM2		•
bA2		•

January 2013 6678 M2 Mark Scheme

Q.	Scheme	Marks		
1. (a)	0.5m 2 kg B 2m C	M1		
	$5\overline{y} - 2 \times 0.25(+0)$	A1	Moments equation with lengths ¼, 1 and (ratio of) masses 2, 3. Allow moments about a parallel axis Use of length for mass is M0.	
	$\overline{y} = \frac{2 \times 0.25}{5} = 0.1$		For distance from BC	
(b)	B G			
		M1		
	$\tan \theta = \frac{0.6}{0.5 - 0.1}$	A1ft	Must suspend from A. Use of tan with 0.6 and 0.5 - \overline{y} Could be wrong way up. Must be using 0.6	
		A1	Correct way up. ft their \overline{y} .	
	$\theta = \tan^{-1} \left(\frac{6}{4} \right) = 56.3^{\circ} = 56^{\circ}$		Accept awrt 56.3	

Q.	Scheme		Marks
2 (a)	$ \begin{array}{c} 0.4 \text{ m s}^{-2} \\ \end{array} $ $ \begin{array}{c} R & \longleftarrow & 1800 \text{ kg} \\ \end{array} $	B1	
	$T = \frac{30000}{20} (=1500)$	M1	Use of $P = Fv$
	T - R = 1800a	A1	Equation of motion. Need all 3 terms. Condone sign errors
	$T - R = 1800 \times 0.4$ $R = 1500 - 1800 \times 0.4$ $= 780$	A1	Equation correct (their T) Only
(b)	N \sim	M1	
	$T - 1800g \sin \alpha - R = 0$	A1	Equation of motion. Need all 3 terms. Weight must be resolved. Condone cos for sin. Condone sign errors Correct equation. Allow with <i>R</i> not substituted or with their <i>R</i> .
	$T = 1800 \times \frac{1}{12}g + 780$	DM1	
	Power = $\left(1800 \times \frac{1}{12} g + 780\right) \times 20$	A1	Use of $P = Tv$
		A1	Correctly substituted equation (for their <i>R</i>)
	= 45000 W or 45 kW		cao

Q	Scheme	Marks	
3	R $2 m$ $0.5 m$ $60 g$ $18 g$		
	$F = \mu N$ $R (\uparrow) \qquad 18g + 60g = N$ $= 78g$	B1 M1 A1	Used. Condone an inequality. Resolve vertically
P	$R(\rightarrow) R = F = \mu N$ $2.5 \times 18g \cos \alpha + 3 \times 60g \cos \alpha = 5F \sin \alpha$	M1A2	Moments equation. Condone sign errors. Condone sin/cos confusion
A C B W	$18g \times 2.5 \cos \alpha + 60g \times 3 \cos \alpha = R \times 5 \sin \alpha$ $\frac{1}{2} \cos \alpha \times 18g + 3 \sin \alpha F + 2 \sin \alpha R = 3 \cos \alpha N$ $5 \cos \alpha N = 5 \sin \alpha F + 2.5 \cos \alpha \times 18g + 2 \cos \alpha \times 60$ $\frac{1}{60g \times \frac{1}{2} \cos \alpha + 2.5N \cos \alpha = 2.5R \sin \alpha + 2.5F \sin \alpha}$		-1 each error
,,	$45 \times \frac{3}{5}g + 180 \times \frac{3}{5}g = 4R$	DM1	Eliminate α . Dependent on the second M1.
	$R = \frac{135}{4}g$ $78g\mu = \frac{135}{4}g$	DM1	Equation in μ only. (Dependent on the first two M marks.) NB g cancels. 0.43269,
	$\mu = \frac{135}{4 \times 78} = \frac{135}{312} = 0.432 = 0.43$ NB If use just two moments equations, M1A2 for the Remaining marks as above.	A1 ne better at	225 45 520, 104, awrt 0.433 Do not accept an inequality.
4		B1	

Q	Scheme			Marks	
(a)	$t = \frac{5}{4}$		M1	1.25	
(b)	$\mathbf{r} = (2t^2 - 5t)\mathbf{i} + 3t\mathbf{j}(+\mathbf{c})$			Integrate the velocity vector	
(c)	$t = 0 2\mathbf{i} + 5\mathbf{j} = \mathbf{c}$ $\mathbf{r} = (2t^2 - 5t)\mathbf{i} + 3t\mathbf{j} + (2\mathbf{i} + 5\mathbf{j})$ $(2t^2 - 5t + 2)\mathbf{i} + (3t + 5)\mathbf{j}$ $\mathbf{r}_o = 11\mathbf{i} + 2\mathbf{j} - 2t\mathbf{i} + ct\mathbf{j}$		A1 DM1 A1 B1	NB Also correct to use suvat with $\mathbf{a} = 4\mathbf{i}$ and $\mathbf{u} = -5\mathbf{i} + 3\mathbf{j}$. Correct Use \mathbf{r}_0 to find C oe Correct \mathbf{j} component of \mathbf{r}_0	
	$\mathbf{r}_{p} = (2t^{2} - 5t + 2)\mathbf{i} + (3t + 5)\mathbf{j}$ $\mathbf{r}_{p} = (2t^{2} - 5t + 2)\mathbf{i} + (3t + 5)\mathbf{j}$			Do not actually require the whole thing - can answer the Q by considering only the j component.	
	$\mathbf{r}_Q = \mathbf{r}_P = d\mathbf{i} + 14\mathbf{j}$		$2t^2-5t$	•	
	3t + 5 = 14	$2\ell^2 - 3\ell - 9$ $(2\ell + 3)(\ell - 3) = 0$ t = 3	M1	Form an equation in t only	
	t=3 A1 ft $2+ct=14 \Rightarrow c=4$ $d=11-2\times 3=5$ or $d=2\times 3^2-5\times 3+2 \Rightarrow d=5$		A1 A1 ft	Their t Their t	
	Alt: $2t^2 - 5t + 2 = 11 - 2t = d \Rightarrow t = \frac{11 - d}{2}$				
	$2\left(\frac{11-d}{2}\right)^{2} - 5\left(\frac{11-d}{2}\right) + 2 = d,$ $d^{2} - 19d + 70 = 0 = (d-5)(d-14)$				

Q.	Scheme	Marks		
5	$U \text{ m s}^{-1}$ θ 1.5 m			
(a)	$N = 2g\cos\theta = \frac{14}{25}g$	M1	Resolve perpendicular to plane. Condone trig confusion.	
	$F = \mu N = \frac{5}{12} \times \frac{14}{25} g = \frac{7g}{30}$	B1	Correct value of F seen or implied	
	Work done = $\frac{7}{30}$ g × 1.5 = 3.43 = 3.4 J	DM1	Their <i>F</i> x 1.5	
		A1	$\frac{7g}{20}$, 3.4 or 3.43 only	
(b)	$3.43 + 2g\sin\theta \times 1.5 = \frac{1}{2} \times 2U^2$	M1	Energy equation - needs all 3 terms, but condone sign errors & trig confusion. Must have an expression for the vertical height.	
	U = 5.626 = 5.6	A1 A1 A1	Correct with one slip for their WD. All correct for their WD 5.6 & 5.63 only	
(c)	v m s ⁻¹ 1.5 m			
	$2g\sin\theta \times 1.5 = 3.43 + \frac{1}{2} \times 2v^2$	M1	Energy equation - needs all three terms. Condone sign errors & trig. confusion. Extra terms give M0.	
	OR: $\frac{1}{2} \times 2U^2 = 2 \times 3.43 + \frac{1}{2} \times 2v^2$	A1	All correct (their WD & U)	
	$v^{2} = 3g \sin \theta - 3.43$ $v = 4.979$			
Alt	$Speed = 5.0 \text{ m s}^{-1}$	A1	Accept 4.98	
(c)	$mg \sin \theta - F = ma$ and $v^2 = (u^2) + 2as$	M1	Equation of motion - needs all three terms. Condone sign errors & trig. confusion. Together with <i>suvat</i>	
	$zg \sin\theta - \frac{7g}{30} = \frac{48g}{25} - \frac{7g}{30} = za$			
	$a = \frac{253g}{300} = 8.26 \dots$	A1	4.00	
	$v^2 = 24.794$, $v = 5.0$	A1	Accept 4.98	

Q.	Scheme	Marks		
6 (a)	$2 = -2u\sin\theta + \frac{1}{2}g \times 4$	M1	Vertical distance. Condone sign errors. Must have used $t = 2$, but could be using $u_y = u \sin \theta$	
	$\left(-2 = u \sin \theta t - \frac{1}{2}gt^{2}\right)$ $u \sin \theta = g - 1$	A1	All correct	
	$2u\cos\theta = 8 (u\cos\theta = 4)$ $(u\cos\theta t = 8)$	B1	Horizontal distance. Accept $u_x = 4$ o.e.	
	$\tan \theta = \frac{g-1}{4} = 2.2 *$	M1	Divide to obtain expression for tan 8	
	·	A1	Given answer It is acceptable to quote and use the equation for the projectile path. Incorrect equation is 0/5.	
(b)	$u\cos\theta = 4$	M1	Use the horizontal distance and θ to find u 9.67 or 9.7	
	$u = \frac{4}{\cos \theta} = 9.66 = 9.7$	A1	NB $\theta = 65.6^{\circ}$ leading to 9.68 is an accuracy penalty.	
	OR use components from (a) and Pythagoras.			
(c)	$6 = (1 - g)T + \frac{1}{2} \times 9.8T^2$	M1	Equation for vertical distance = ± 6 to give a quadratic in T . Allow their u_y	
	$4.9T^2 - 8.8T - 6 = 0$			
	$T = \frac{8.8 \pm \sqrt{\left[\left(-\right) 8.8 \right]^2 + 24 \times 4.9}}{9.8}$	DM1	Solve a 3 term quadratic	
	T = 2.323 = 2.32 or 2.3	A1	2.3 or 2.32 only	
(d)	$v^2 = 8.8^2 + 2g \times 6$ or $v = -8.8 + gT$	M1 A1	Use <i>suvat</i> to find vertical speed Correct equation their u_y , T	
	v = 13.96			
	Horiz speed = 4			
	$\tan \alpha = \frac{v}{4}$	DM1	Correct trig. with their vertical speed to find the required angle.	
		A1	Correct equation	
	$\alpha = 74.01 = 74^{\circ}$	A1	74° or 74.0°. Allow 106.	
	Alternative:			
	$\frac{1}{2}m(9.6664)^2 + 6mg = \frac{1}{2}mv^2$	M1	Conservation of energy to find speed	
	v = 14.52719	A1		
	$\cos \alpha = \frac{4}{1.4.5}$	DM1 A1	Correct method for α	
	$\alpha = 74.01 = 74^{\circ}$	A1	Allow 106	

Q	Scheme		Marks
7(a)	$ \begin{array}{ccc} & & & & & \downarrow & 0 \\ & & & & & \downarrow & 0 \\ & & & & & & \downarrow & 0 \\ & & & & & & \downarrow & 0 \\ & & & & & & \downarrow & 0 \\ & & & & & & \downarrow & 0 \\ & & & & & & \downarrow & 0 \\ & & & & & & \downarrow & 0 \\ & & & & & & \downarrow & 0 \\ & & & & & & \downarrow & 0 \\ & & & & & & \downarrow & 0 \\ & & & & & & \downarrow & 0 \\ & & & & & & \downarrow & 0 \\ & & & & & & \downarrow & 0 \\ & & & & & & \downarrow & 0 \\ & & & & & & \downarrow & 0 \\ & & & & & & \downarrow & 0 \\ & & & & & & \downarrow & 0 \\ & & & & & & \downarrow & 0 \\ & & & & & & \downarrow & 0 \\ & & & & & & \downarrow & 0 \\ & & & & & \downarrow & 0 \\ & & & & & \downarrow & 0 \\ & & & & & \downarrow & 0 \\ & & & & & \downarrow & 0 \\ & & & & & \downarrow & 0 \\ & & & & & \downarrow & 0 \\ & & & & & \downarrow & 0 \\ & & & & & \downarrow & 0 \\ & & & & & \downarrow & 0 \\ & & & & & \downarrow & 0 \\ & & & & & \downarrow & 0 \\ & & & & & \downarrow & 0 \\ & \downarrow $		If the signs on their diagram and in their working are inconsistent, ignore the diagram. Penalise inconsistency between the two equations in the second accuracy mark.
	mu = -mv + 3mw	M1	CLM. Allow for <i>v</i> in either direction. Needs all 3 terms. Condone sign errors.
	u = -v + 3w	A1	v in either direction. Ignore diagram if equations "correct" but inconsistent with diagram.
	eu = w + v	M1	Impact law. Must be the right way round, but condone sign errors
		A1	Correct equation. Signs consistent with CLM equn.
	$w = \frac{u}{4}(1+e)$	DM1	Solve for <i>v</i> or <i>w</i> .
		A1	One correct
	$v = -w + eu = \frac{u}{4}(3e - 1)$	A1	Both correct. $1 - 3e \rightarrow A0$ for v
(b)	$ \frac{1}{4}(1+e) \longrightarrow 0 $ $ B \qquad \qquad C $ $ 3m \qquad 4m $ $ Y \longleftarrow \qquad \longrightarrow X $ $ 3mw = 4mX - 3mY $ $ 2ew = X + Y $ $ 7Y = W(8e - 3) $ Or $2ue(1+e) - \frac{3u}{4}(1+e) = 7Y$	M1 A1ft B1ft DM1	If the signs on their diagram and in their working are inconsistent, ignore the diagram. Penalise inconsistency between the two equations in the B mark. CLM for their w. Correct unsimplified (their w) Impact law. Must be the right way up. Their w Solve for (7)Y
	2	A1	
		A1	NB No longer ft. Condone <.
(c)	$\frac{u}{28}(1+e)(8e-3) > \frac{u}{4}(3e-1)$	M1	For a second collision their $Y >$ their V
	$2e^{2} - 4e + 1 > 0$ $e = \frac{4 \pm \sqrt{16 - 8}}{4} = 1.707, \ 0.293$	DM1	Obtain the critical values
	$2e^2 - 4e + 1 < 0$ for $\frac{3}{8} < e \le \frac{1}{2}$ so no second	A1	Compare 0.293 (o.e.) with $\frac{3}{8}$ to reach correct conclusion for correct reason.
	collision.		

Further copies of this publication are available from Edexcel Publications, Adamsway, Mansfield, Notts, NG18 4FN

Telephone 01623 467467 Fax 01623 450481

Email <u>publication.orders@edexcel.com</u>
Order Code UA034765 January 2013

For more information on Edexcel qualifications, please visit our website $\underline{www.edexcel.com}$

Pearson Education Limited. Registered company number 872828 with its registered office at Edinburgh Gate, Harlow, Essex CM20 2JE





