

WHITEPAPER

Verifiable Charity on the XRP Ledger

Proof comes before payment.

Brianne Salato, Founder and Product Architect

Version 0.5 (Draft) | October 2026

verichar.net | VeriChar@proton.me

Contents

1 Executive summary
2 The problem
3 The VeriChar approach
4 System architecture
5 Cryptographic proof, explained
6 Donor and charity experience
7 Planned modules
8 Business model
9 Security and risk
10 Compliance considerations
11 Roadmap
12 Conclusion
A Appendix: XRPL.org references

Document status
This is a Version 0.5 draft. VeriChar is currently a working interactive prototype. The system described here is the intended design. It will be tested on the XRP Ledger test network, and reviewed by legal and security professionals, before any real funds are handled. Statements about how the XRP Ledger works were checked against XRPL.org, XRPLF and Ripple RLUSD documentation and are tagged [S1] to [S24] (see Appendix A). Design details marked "to be confirmed" are not yet verified against the XRPL specification.

1. Executive summary

Charitable giving runs on trust, and trust is hard to verify. Donors rarely see what their gift actually bought. Charities carry the burden of proving their impact after the money is already spent. Fraud, mismanagement and vague "administrative costs" thrive in that gap.

VeriChar (Verified Charity On-Chain) is a verification layer for charitable giving, built on the XRP Ledger (XRPL). Every donation funds one specific, itemized need and is paid in RLUSD, a USD stablecoin on the XRPL. The funds are locked in escrow on the ledger and released directly to the vendor only when two proofs are verified: an **itemized merchant invoice** and **cryptographic proof of delivery**. The charity never holds the cash, and every step is written to a public ledger that anyone can audit.

VeriChar is free for donors and charities. It is sustained by a 1% vendor settlement fee and by licensing audit-ready Corporate Social Responsibility (CSR) data to enterprise customers. Both are designed to be collected on the XRP Ledger.

The core principle
Proof comes before payment, not after. Trust is enforced by code, not demanded by slogans.

2. The problem

Today's giving systems ask donors to take organizations at their word. Four structural problems follow from that.

Opacity

Donations are usually pooled into general funds. A donor cannot trace a specific dollar to a specific purchase.

Diversion and fraud

Unverified organizations, misused funds and inflated costs are difficult to detect. When money moves first and reports follow later, problems surface only after the damage is done.

The burden of proof


Honest charities must assemble reports and receipts to demonstrate impact. The process is slow, manual and hard for an outsider to audit.

Privacy versus transparency

Many donors want to give without being tracked, yet still want proof that their gift was used properly. Existing platforms usually force a choice between the two.

3. The VeriChar approach

VeriChar changes the order of events. Instead of paying first and reporting later, funds are locked first and released only when the evidence exists.



- **Verified charities.** Each organization is checked against its EIN (Employer Identification Number) in IRS non-profit records and its wallet address is bound to that verified identity. The XRPL supports a two-way link between an account and a domain: the account's Domain field plus an xrp-ledger.toml file hosted at that domain [S12]. The EIN check itself happens off-ledger. XRPL Credentials are another possible fit: an issuer creates a credential for a subject account, and the subject must accept it [S19] (to be confirmed for VeriChar).
- **Itemized needs.** A charity lists a specific need with a price and a named vendor, for example "4 cases of water, $20." Donors fund that item directly.
- **Escrow.** The donation is locked in an escrow on the XRP Ledger. An escrow locks up XRP or fungible tokens, which cannot be used or destroyed until conditions are met [S17]. The escrow names its recipient, here the vendor, when it is created, and finishing it delivers the funds to that recipient [S17].
- **Two proofs.** The charity submits an itemized invoice and proof of delivery. Delivery proof may be a time-stamped, GPS-verified photo, a carrier delivery confirmation or a signed receipt, depending on the item.
- **Direct settlement.** When both proofs pass verification, the escrow is finished and the funds go straight to the vendor. The charity never touches the money.

4. System architecture

VeriChar has four layers, each with a single job.

Ledger layer: the XRP Ledger

VeriChar plans to use the XRPL's native escrow feature rather than custom smart-contract code, which is intended to keep the attack surface small. The XRPL is a decentralized blockchain [S1]. A new ledger version is created when 80% of validators agree on a set of transactions, a consensus process the documentation says takes 4 to 6 seconds [S1]. Transaction costs are small amounts of XRP quoted in drops, where 1 million drops equal 1 XRP [S9]; the documentation's example transactions use 10 to 12 drops [S8]. Speed matters for emergency orders that must reach merchants quickly. Cost matters most for small donations, as covered under Costs of escrow below.

Escrow is a native XRPL payment type that locks up XRP or fungible tokens until conditions are met, with an automated system in the ledger replacing the traditional third party [S17]. The XRPL supports three types: time-based, conditional and combination escrow [S17]. VeriChar's design uses a **conditional escrow**: a cryptographic condition acts as the lock, and the matching fulfillment key releases the funds [S17]. The lifecycle is:

- **Create.** The sender submits an EscrowCreate transaction that defines the amount, the release conditions and the recipient. For XRP escrows this can include a finish-after time, a crypto-condition and an optional expiry [S17]. A conditional escrow with no finish-after time must have an expiry (CancelAfter) [S17]. Since the fix1571 amendment, EscrowCreate must include a Condition or a FinishAfter [S20].
- **Finish.** An EscrowFinish transaction delivers the funds to the recipient if the conditions are met [S17]. In a conditional escrow anyone can finish it, but only by supplying the correct fulfillment [S17].
- **Expire and cancel.** If nobody finishes the escrow before its expiry, it becomes expired and can no longer be finished. Anyone can then cancel it with EscrowCancel, which returns the funds to the sender [S17]. An escrow with no CancelAfter field never expires and cannot be canceled [S17].

What this means for VeriChar. Every VeriChar escrow must carry an expiry, or a failed delivery could lock funds permanently. The oracle must guard the fulfillment, because whoever holds it can trigger release [S17]. The only crypto-condition type the XRPL supports is PREIMAGE-SHA-256 [S17]. Timed releases and expirations follow ledger close times and can vary by about five seconds, and escrows cannot be created with past time values [S17]. A Smart Escrows amendment, which would let developers program release rules with WebAssembly, is listed as in development, so VeriChar does not depend on it [S20].

Costs of escrow

The XRPL escrow documentation lists limits that matter to a charity platform [S17]. Escrow needs two transactions, one to create it and one to finish or cancel it. Crypto-conditions cost more than ordinary transactions, and the documentation says these costs can make escrow infeasible for small amounts. While an escrow is incomplete, the sender is responsible for its reserve. An EscrowFinish with a fulfillment must pay at least 330 drops plus 10 drops per 16 bytes of fulfillment, based on a 10-drop reference cost, and the formula scales if Fee Voting changes the reference fee. Multi-signing adds its own cost on top [S17]. VeriChar must measure these costs on the test network against real gift sizes such as "4 cases of water, $20."

Ledger facts that shape the design

- **Finality.** A transaction result is final only when it appears in a validated ledger [S8]. VeriChar will count only validated results, check for the result code tesSUCCESS, and read meta.delivered_amount instead of the Amount field, which can be exploited through partial payments [S15].
- **Reserves.** Every XRPL account must hold a base reserve (1 XRP on Mainnet), and each escrow an account owns adds an owner reserve (0.2 XRP on Mainnet) [S10]. Reserve values can change by validator vote [S10]. While an escrow is incomplete, the sender is responsible for its reserve [S17], so the design must decide which account sends each escrow and how that reserve is funded. A Sponsor amendment, which would let others cover fees and reserves for users, showed as open for voting at 31.43% and not enabled in the amendments page snapshot [S20]. VeriChar does not rely on it.
- **Accounts and keys.** There is no create-account transaction. A Payment of enough XRP to a valid address creates the account, and whoever holds the secret key has full control of it [S4]. An account can be authorized by a master key, a rotatable regular key or a multi-signing signer list, and the master key can be kept offline [S4, S14]. Defaults differ between tools: many client libraries such as xrpl.js default to Ed25519, while wallet_propose defaults to secp256k1, so one seed can give a different address unless the algorithm is set explicitly [S18]. The ripple-keypairs library also defaults to ed25519 [S16]. An account cannot send transactions until it is funded, and no administrator can reverse an applied transaction [S18].
- **Test networks.** Testnet and Devnet let developers create accounts funded with 1,000 test XRP [S1]. The XRPL Credentials tutorial funds Testnet accounts from a faucet and connects to a public Testnet server [S19].
- **Servers.** Serious use is better served by running our own xrpld and Clio servers, because a malicious server could misreport payments [S6].
- **RLUSD.** RLUSD (Ripple USD) is a USD stablecoin issued as a native XRPL token: an issuer holds real-world assets as collateral and creates equivalent tokens on the ledger [S22]. The Mainnet issuer address is rMxCKbEDwqr76QuheSUMdEGf4B9xJ8m5De and the Testnet issuer is rQhWct2fv4Vc4KRjRgMrxa8xPN9Zx9iLKV [S22]. An account must hold a trust line to the issuer before it can receive RLUSD [S22]. Ripple states that one RLUSD trust line takes at least 1.2 XRP (1 XRP base reserve plus 0.2 XRP owner reserve) [S22]. The XRPL Reserves page describes an exception for the first two trust lines [S10], so confirm on the test network. XRP is still needed for fees and reserves [S9, S10].
- **Escrowing RLUSD.** RLUSD is a trust line token. Trust line tokens can be escrowed only if the issuer enables Allow Trust Line Locking, and token escrows must always have an expiry [S17]. TokenEscrow showed as enabled on 2026-02-12 [S20]. The RLUSD issuer settings table lists clawback as enabled, Require Auth and No Freeze as not enabled, and does not list the locking flag [S23]. **Whether RLUSD can be escrowed is therefore not confirmed.** Test an RLUSD EscrowCreate against the Testnet issuer before building further. If authorization is not required, missing trust lines may be auto-created for escrow recipients [S17]. Transfer rates are captured at creation and apply at completion [S17], and the settings table does not list an RLUSD transfer rate [S23]. A deep-frozen holder cannot finish an escrow but can still cancel one [S17].
- **Credentials.** The Credentials amendment showed as enabled on 2025-09-04 [S20]. An issuer creates a credential for a subject account, the subject must accept it to make it valid, and either party can delete it [S19]. A credential is identified by its issuer, subject and credential type [S19]. VeriChar could issue a verified-charity credential to charity accounts after the EIN check (to be confirmed).

Verification layer: the dual-layer oracle

An "oracle" is a service that checks real-world facts and reports them to the ledger. VeriChar's oracle runs two checks that must both pass. (Not to be confused with the XRPL's own on-ledger Oracle objects, which carry price data [S10].)

- **Supplier log (invoice).** Optical character recognition (OCR) reads the merchant invoice and compares the vendor, line items and pricing with the funded need.
- **Delivery log (proof of delivery).** For photos, the oracle inspects embedded metadata (EXIF data), a cryptographic timestamp and the GPS location. For shipped goods, it can instead accept a carrier delivery confirmation.

When both checks pass, the oracle releases the fulfillment that unlocks the escrow [S17]. Because the recipient was named when the escrow was created, finishing the escrow delivers the funds to that recipient [S17].

Privacy layer

Donors can give as guests with no VeriChar account. An XRPL address is still needed to send funds, because only signed transactions from an account can be submitted [S4, S8]; an account that sends RLUSD needs an RLUSD trust line [S22] and XRP for fees and reserves [S9, S10], so how guest wallets are created and funded is an open design question. A donor who wants a tax receipt may provide an email address, which is encrypted and stored off-chain, never written to the ledger. XRPL transactions are public [S15]. A "Stealth Escrow" design is planned to reduce the visible link between a donor's wallet and a specific donation. Because the XRPL is a public ledger, this requires careful engineering and legal review, and it is not yet built.

Application layer

Three interfaces sit on top: a donor dashboard for browsing verified charities and funding needs, a charity portal for onboarding and submitting proof, and an enterprise dashboard for CSR reporting.

5. Cryptographic proof, explained

"Cryptographic proof" sounds abstract. Here is how it works in plain English.

Concept	What it means	Why it matters
Digital fingerprint (hash)	A record is converted into a short, unique code. Change any detail and the code changes completely. Every signed XRPL transaction has a unique hash [S8].	Tampering is easy to detect.
Digital signature	The record is signed with a private key, like a tamper-proof seal. A signed XRPL transaction is immutable, and its signature is not valid for any other transaction [S8]. XRPL key pairs use secp256k1 or ed25519 [S18]. The ripple-keypairs library can sign and verify arbitrary hex-encoded messages [S16]; whether VeriChar signs delivery records this way is to be confirmed.	Shows who confirmed the delivery and when.
Public ledger	Transactions in validated ledgers can be looked up by anyone using their hash [S3, S8]. Which VeriChar proof data is written on-ledger is to be confirmed.	Anyone can verify them. Recorded data cannot be altered retroactively unless a majority of validators agree [S1].

Proof depends on the item. A pallet of supplies may be proven by a carrier confirmation. A dental appointment may be proven by a signed provider record. The rule is constant: funds release only after the proof is verified.

6. Donor and charity experience

Donors

- Browse EIN-verified charities and search by keyword, state or cause type.
- Fund one itemized need from a shopping-cart-style list.
- Give as a guest. An optional email for a tax receipt is encrypted off-chain.
- Watch the status change from funds locked, to proof submitted, to released.

Charities

- Register with a name, wallet address and EIN, and pass verification.
- List needs with a price and vendor.
- Submit the invoice and proof of delivery when goods arrive.
- Pay nothing. VeriChar is free for charities.

7. Planned modules

Automated subscription escrows

For baseline essentials such as hygiene products, diapers or non-perishable inventory, donors can lock a pool of assets into a pre-authorized vault. Every 30 days the vault creates a new itemized escrow based on the shelter's updated inventory needs. Each monthly release still requires the same dual-layer verification before the vendor is paid. Because the sender covers the reserve of each incomplete escrow [S17, S10], the design must account for reserves across the monthly cycle.

Micro-donation aggregation ("From Dust to Dreams")

Small leftover balances, often called "crypto dust," from swaps and wallet settlements can be swept into pooled vaults tied to a cause the donor chooses. The funds stay locked on-chain and are deployed to an itemized escrow only when a full funding goal is met, with the same verification before vendor payment. The XRPL escrow documentation warns that escrow costs can make it infeasible for small amounts [S17], so pooling small balances until a full goal is met is meant to spread those costs across one escrow. Owner reserves [S10] must also be designed so they do not swamp very small balances. Whether this is economical must be tested.

8. Business model

VeriChar is free for donors and charities. Both revenue streams are designed to be collected on the XRP Ledger in RLUSD, using only features described in the documentation reviewed. Anything the sources do not confirm is marked as open.

Revenue	How it flows through the XRP Ledger
Vendor settlement fee (1%)	**Split escrow in RLUSD.** For each funded item, the sending account creates two conditional escrows of RLUSD: 99% of the listed price to the vendor and 1% to the VeriChar revenue account. An escrow names its amount, release conditions and recipient when it is created, and finishing it delivers the funds to that recipient [S17]. The oracle releases the fulfillment for both only after both proofs verify. If proof never arrives, both expire and anyone can cancel them, returning the funds to the sender [S17]. Token escrows must always carry an expiry [S17], which matches the design. A $20 item splits into 19.80 and 0.20 RLUSD, assuming 1 RLUSD equals 1 USD, which the pages reviewed do not state. **Why two escrows:** an escrow is created with one named recipient [S17]. **Blocking item:** RLUSD escrow is not confirmed (see Section 4). Without it, this flow cannot be built on RLUSD. **Other open items:** (a) whether one condition can lock both escrows; (b) whether BatchV1_1, shown as enabled on 2026-10-09 [S20], can bundle two EscrowCreate transactions; (c) two escrows double the reserves and XRP fees [S17, S10], and the documentation says escrow costs can make small amounts infeasible [S17].
Issuer transfer fee (not VeriChar revenue)	An issuer can charge a percentage fee when users send its token. The fee is debited from the sender, only the destination amount is credited, and the fee vanishes from the ledger, which benefits the issuer [S24]. The RLUSD issuer is Ripple, so a transfer fee cannot be VeriChar revenue. If one applied, it would reduce what recipients receive. The RLUSD settings table does not list one [S23], so check the issuer account with account_info on the test network [S13].
CSR dashboard licensing	**Payment.** Enterprise customers pay the VeriChar revenue account with an RLUSD Payment. The revenue account needs an RLUSD trust line first, because an account cannot receive RLUSD without one [S22]. The asfRequireDest flag forces a destination tag on every incoming payment [S12], and destination tags are the usual way to tell which customer a payment belongs to [S12]. VeriChar credits a subscription only after reading a validated transaction with result tesSUCCESS and meta.delivered_amount [S15]. The tutorial examples handle XRP, and the page notes that tokens need more precision [S15]. **Other options:** a Check [S20]. Payment Channels are described for XRP [S20], and their use with RLUSD is not covered by the sources. **Off-ledger:** invoicing, fiat billing and converting RLUSD to bank currency are outside the XRPL and are not covered by the sources. **What the data is:** every transaction has a hash anyone can look up [S8], validated ledger history is immutable [S3], all XRPL transactions are public [S15], and pending escrows can be looked up by destination account [S20]. Because the raw records are public, what VeriChar licenses is the verification, matching and reporting built on them (our assumption).
Revenue account and costs	**Account.** A Payment of at least the base reserve funds the account (1 XRP on Mainnet) [S4, S10]. Adding an RLUSD trust line brings the minimum to 1.2 XRP, per Ripple [S22]. Keep the master key offline and sign with a regular key [S18], and use multi-signing for withdrawals [S11]. **Costs paid in XRP:** every transaction burns an XRP fee [S9, S10]. An EscrowFinish with a fulfillment costs at least 330 drops plus 10 drops per 16 bytes of fulfillment, based on a 10-drop reference cost [S17]. Each open escrow adds a 0.2 XRP owner reserve for its sender, which stops counting once the escrow is removed [S10, S17]. Revenue is in RLUSD and costs are in XRP, so VeriChar must hold an XRP float. The sources give no dollar value for XRP or drops, so margins cannot be computed from them and must be measured on the test network.

Receiving a share of donor-funded escrows should be included in the money-transmission review in Section 10.

9. Security and risk

No system removes risk entirely. These are the principal risks VeriChar is designed to address, and the mitigations planned for each.

Risk	Planned mitigation
Forged or inflated invoices	Automated parsing, price checks against the listed need, duplicate detection, a verified vendor registry and human review of exceptions.
Photo or GPS spoofing	Metadata checks combined with signed capture, cross-checks against carrier or vendor confirmations, and random audits.
Collusion between charity and vendor	Vendor verification, price benchmarking, anomaly detection and a channel for reporting concerns.
Oracle compromise or error	Hardened key management, an auditable public log and a roadmap toward multiple independent oracles that must agree. The XRPL supports multi-signing, where a signer list of 1 to 32 addresses with weights and a quorum must authorize a transaction [S11]. Because anyone holding a conditional escrow's fulfillment can finish it [S17], fulfillment secrets must be guarded like keys. Whether multi-signing can gate release is to be confirmed.
Lost or stolen keys	Whoever holds an account's secret key has full control of it [S4]. Keep master keys offline and sign with a regular key, which can be rotated [S14, S4], and use multi-signing for high-value accounts [S11].
Misreading payments	Count only validated transactions with result tesSUCCESS, and use delivered_amount rather than the Amount field to avoid the partial payments exploit [S15, S8]. Token amounts need more precision than the XRP examples in the tutorial [S15].
Reserve shortfalls	Each escrow adds an owner reserve, and the sender covers it while the escrow is incomplete [S10, S17]. Fund reserves explicitly and monitor with account_info, which reports OwnerCount [S13, S10].
Stuck funds if delivery fails	Set an expiry (CancelAfter) on every escrow. After it passes, the escrow cannot be finished and anyone can cancel it, returning the funds to the sender [S17]. Without CancelAfter an escrow never expires and cannot be canceled [S17].
Cost on small gifts	Escrow needs two transactions, and crypto-conditions cost more than usual [S17]. The documentation says these costs can make escrow infeasible for small amounts [S17]. Measure real costs on the test network and set minimum item sizes or pooling accordingly.
Key algorithm mismatch	Tools use different default algorithms, so one seed can give different addresses [S18]. Set the algorithm explicitly in every tool and test address derivation.
Untrusted servers	Run our own xrpld and Clio servers for production use, since a malicious server can misreport payments [S6].
Asset value and XRP float	Gifts are paid in RLUSD, a USD stablecoin [S22], which removes most price swings on the gift itself. XRP is still needed for fees and reserves [S9, S10], so keep only a small XRP float.
Issuer actions on RLUSD	The issuer controls the token. The RLUSD settings table lists clawback as enabled and No Freeze as not enabled [S23], so the issuer can recover tokens or freeze them [S12, S20]. Freezes do not prevent finishing a trust line token escrow, but a deep-frozen holder cannot finish one and can only cancel [S17]. Whether clawback reaches escrowed RLUSD is not covered by the sources. Confirm the issuer address in Ripple documentation before launch [S22].

Risk	Planned mitigation
Privacy leaks	Data minimization, off-chain encryption and an independent privacy review before launch. All XRPL transactions are public [S15].

> **Honest limitations**
> Cryptographic proof shows that a record is authentic and unaltered. It cannot prove that the underlying event was honest. VeriChar reduces the opportunity for fraud and makes it much easier to detect, but no system can make fraud impossible.

10. Compliance considerations

Handling charitable funds involves regulation that varies by state and by activity. The following areas require review by qualified legal counsel before any live launch.

- **Money transmission.** Holding or moving customer funds may trigger federal (FinCEN) registration and state money-transmitter licensing. Escrow design aims to avoid VeriChar taking custody, but this must be confirmed.
- **Charitable solicitation.** Many states require registration for entities that solicit donations on behalf of charities.
- **Anti-money-laundering (AML).** Vendors and larger donors may need screening, even where small guest gifts remain private.
- **Tax treatment.** Digital assets are treated as property for US tax purposes. Charities, not VeriChar, issue tax receipts.
- **Data protection.** Encrypted email and any personal data must follow applicable privacy law.
- **Token and securities rules.** The XRPL documentation warns that some token offerings may be regulated as securities in the USA and advises researching the relevant regulations before engaging in any financial service business [S9].

11. Roadmap

Phase	Focus	Status
0. Prototype	Interactive demo of the donor flow, charity onboarding, oracle verification and release. Public website.	Complete
1. Test network	RLUSD conditional escrow with an expiry on the XRPL test network, using the Testnet RLUSD issuer and faucet [S22]: first confirm RLUSD can be escrowed, then test the create, finish and cancel paths, measure real costs on small gifts [S17], and settle reserve handling, key algorithms [S18] and the split-escrow vendor fee. Try a charity-verification credential [S19]. Working oracle for invoices and delivery proof. No real funds: Testnet RLUSD has no financial value [S22], and test accounts can be funded with 1,000 test XRP [S1].	Planned
2. Pilot	One to three partner charities and a small set of vendors, with small amounts, after legal and security review.	Planned

Phase	Focus	Status
3. Expansion	Subscription escrows, dust pools, multiple independent oracles and the enterprise CSR dashboard.	Planned

12. Conclusion

Generosity should not require surrendering your common sense. VeriChar applies a simple rule, proof before payment, using technology that already exists. Donors see exactly what their gift achieved. Honest charities gain a credible way to prove their work. Vendors are paid promptly. And the record belongs to everyone.

Trust should be enforced by code, not demanded by slogans.

Appendix A. XRPL.org references

Technical statements about the XRP Ledger in this document were checked against the XRPL.org pages below. Recheck against the current documentation before launch, since reserves, fees and amendments can change. Amendment statuses in [S20] are as of the page snapshot reviewed. [S22] and [S23] are Ripple documentation for RLUSD, not XRPL.org.

[S1] What is the XRP Ledger?
https://xrpl.org/docs/introduction/what-is-the-xrp-ledger

[S2] Concepts
https://xrpl.org/docs/concepts

[S3] Ledgers
https://xrpl.org/docs/concepts/ledgers

[S4] Accounts
https://xrpl.org/docs/concepts/accounts

[S5] Payment Types
https://xrpl.org/docs/concepts/payment-types

[S6] Networks and Servers
https://xrpl.org/docs/concepts/networks-and-servers

[S7] Consensus Protocol
https://xrpl.org/docs/concepts/consensus-protocol

[S8] Transactions
https://xrpl.org/docs/concepts/transactions

[S9] Tokens
https://xrpl.org/docs/concepts/tokens

[S10] Reserves
https://xrpl.org/docs/concepts/accounts/reserves

[S11] Multi-Signing
https://xrpl.org/docs/concepts/accounts/multi-signing

[S12] AccountSet
https://xrpl.org/docs/references/protocol/transactions/types/accountset

[S13] account_info
https://xrpl.org/docs/references/http-websocket-apis/public-api-methods/account-methods/account_info

[S14] wallet_propose
https://xrpl.org/docs/references/http-websocket-apis/admin-api-methods/key-generation-methods/wallet_propose

[S15] Monitor Incoming Payments with WebSocket
https://xrpl.org/docs/tutorials/advanced-developer-topics/client-library-development/monitor-incoming-payments-with-websocket

[S16] ripple-keypairs (xrpl.js package README)
https://github.com/XRPLF/xrpl.js/tree/main/packages/ripple-keypairs

[S17] Escrow
https://xrpl.org/docs/concepts/payment-types/escrow

[S18] Cryptographic Keys
https://xrpl.org/docs/concepts/accounts/cryptographic-keys

[S19] Manage Credentials
https://xrpl.org/docs/tutorials/compliance-features/manage-credentials

[S20] Known Amendments
https://xrpl.org/resources/known-amendments

[S21] Credential issuing service code sample
https://github.com/XRPLF/xrpl-dev-portal/tree/master/_code-samples/issue-credentials/js/

[S22] RLUSD on the XRP Ledger (Ripple documentation)
https://docs.ripple.com/products/stablecoin/developer-resources/rlusd-on-the-xrpl

[S23] RLUSD XRP Ledger settings (Ripple GitHub repository)
https://github.com/ripple/RLUSD-Implementation/blob/main/doc/rlusd-xrpl-settings.md

[S24] Stablecoin Configuration
https://xrpl.org/docs/concepts/tokens/fungible-tokens/stablecoins/configuration

About the author

Brianne Salato, Founder and Product Architect of VeriChar. Contact: VeriChar@proton.me | X: @VeriCharOnChain | verichar.net

Disclaimer. This document is for information only and is not legal, financial, tax or investment advice. It describes planned functionality of a product that is still in development, and some features may change or may not be built. Statements about future plans are goals, not guarantees. Nothing in this document is an offer to sell or a solicitation to buy any asset or security. VeriChar does not currently process real donations.