Static Analysis and Verification

Symbolic Execution

Ondřej Lengál

SAV 2026, FIT BUT

Manual Testing

- users try **input vectors**, trying to break a program
- pros:
  - **complete**: a failing input vector **can be "easily" executed**
    - not always easy: concurrency, nondeterministic memory layout, etc.
  - can be directed to some *corner cases*
- cons:
  - **unsound**: problematic coverage of unexpected corner cases
  - expensive (testers needed)

Random Testing

- generate *a lot of* ***random vectors*** and feed them into a program
- pros:
  - can easily create many inputs
- cons:
  - difficult to cover corner cases
  - many inputs can exercise the same paths through the program

Random Testing

- generate *a lot of* ***random vectors*** and feed them into a program
- pros:
  - can easily create many inputs
- cons:
  - difficult to cover corner cases
  - many inputs can exercise the same paths through the program
- e.g. QuickCheck for Haskell:

```
prop_RevRev xs = reverse (reverse xs) == xs

Main> quickCheck prop_RevRev
OK, passed 100 tests.
```

Random Testing — Example

```
char input[10];
read(fd, input, 10);
int counter = 0;
for (size_t i = 0; i < 10, ++i) {
  if (input[i] == 'B') {
    ++counter;
  }
}
assert(counter != 10);
```

Random Testing — Example

```
char input[10];
read(fd, input, 10);
int counter = 0;
for (size_t i = 0; i < 10, ++i) {
  if (input[i] == 'B') {
    ++counter;
  }
}
assert(counter != 10);
```

- difficult to hit the assertion failure:
  - there needs to be exactly 10 `B`'s read into `input`
  - all possible values of `input`: 2^{80}
  - $P(\texttt{counter == 10}) = 0.00000000000000000000000827$ (for uniform distribution)

Static Analysis

Data flow analysis, **abstract interpretation**, . . . :

- pros:
  - can analyze all possible runs of programs
  - sold by companies (AbsInt, Coverity, GrammaTech, etc.)
  - easy to use (with a catch)
- cons:
  - often unsound (in practice)
  - *abstraction* $\rightsquigarrow$ false positives (**incomplete**)
    - it can take a lot of effort to sieve through them
  - does not provide concrete failing input vectors

Static Analysis — Example

```
char input[10];
read(fd, input, 10);
int counter = 0;
for (size_t i = 0; i < 10, ++i) {
  if (input[i] == 'B') {
    ++counter;
  }
}
assert(counter != 10);
```

- e.g., abstract interpretation might just say that assert is reachable
- developer needs to assess whether it is true
- abstraction of static analysis can be different than the one used by developer

Symbolic Execution — A middle ground

```
int sign(int x) {
  if (x > 0)  return  1;
  if (x < 0)  return -1;
  return 0;
}
```

Testing: each run tries one execution

```
assert(sign( 5) ==  1);
assert(sign(-3) == -1);
```

- two runs, two of the three paths
- we *hope* a test generalizes to the values it did not try — nothing guarantees that it does
- the case `x == 0` is simply not tested

Symbolic Execution: one run, all values

- `x` is given an unknown **symbolic** value α
- a test on α **forks** the execution:

path condition	*returns*	*an input*
$\alpha > 0$	1	`x = 1`
$\alpha < 0$	-1	`x = -1`
$\alpha = 0$	0	`x = 0`

- each path yields an input that takes it — the forgotten one is computed, not guessed

Symbolic Execution

- can be seen as an execution of a program in a mixed symbolic domain
- similar to abstract interpretation (but with significant differences)

Standard execution semantics:

- in every step, all variables and allocated memory cells have concrete values
  - concrete state: configuration of a program

Symbolic Execution

- can be seen as an execution of a program in a mixed symbolic domain
- similar to abstract interpretation (but with significant differences)

Standard execution semantics:

- in every step, all variables and allocated memory cells have concrete values
  - concrete state: configuration of a program

Symbolic execution semantics:

- variables and allocated memory cells can also have **symbolic** values
  - e.g., α, $2 \cdot \beta + 3$, $\gamma +$ `"Hello World"`, ...
  - symbolic values are usually introduced to represent *inputs* of the program
- operators need to be extended to be able to work with symbolic values

Symbolic Execution (cntd.)

- **symbolic state** is a triple $st = (line, store, pc)$ where:
  - $line \in \mathbb{N}$ denotes a program line
  - $store$: $Mem \rightharpoonup Sym$ represents (symbolic) values of variables and allocated memory cells
    - Mem: the set of memory locations
    - Sym: the set of symbolic values (it also contains all concrete values)
    - ($\rightharpoonup$ denotes *partial function*)
  - pc: **path condition**, a formula of first-order logic (over some suitable theory $\mathbb{T}$ that represents program operations and tests) that accumulates conditions that needed to hold to reach st
    - initially set to $true$
    - extended when execution is forked: more formulae are appended using conjunction $\wedge$

Extending path condition

Let φ be a formula obtained by substituting (symbolic) values of variables into a test

- e.g. if $store = \{\mathtt{x} \mapsto \alpha, \mathtt{y} \mapsto 2 \cdot \sin \beta, \ldots\}$, and there is a test

```
if (3 * x > log(y)) {
  stmt1;
  ...
else {
  stmt2;
  ...
}
```

  we obtain for the `if` branch

Extending path condition

Let φ be a formula obtained by substituting (symbolic) values of variables into a test

- e.g. if $store = \{\mathtt{x} \mapsto \alpha, \mathtt{y} \mapsto 2 \cdot \sin \beta, \ldots\}$, and there is a test

```
if (3 * x > log(y)) {
  stmt1;
  ...
else {
  stmt2;
  ...
}
```

  we obtain for the `if` branch $\varphi\colon 3 \cdot \alpha > \log(2 \cdot \sin \beta)$

Extending path condition (cntd.)

- φ is a formula representing a test in a program (e.g. inside an `if` statement)
- suppose pc is $\mathbb{T}$-satisfiable, then at most one of the following can hold:
  1. $pc \Rightarrow_{\mathbb{T}} \varphi$ (the `then` branch)
  2. $pc \Rightarrow_{\mathbb{T}} \neg\varphi$ (the `else` branch)

  where $\Rightarrow_{\mathbb{T}}$ denotes logical consequence w.r.t. theory $\mathbb{T}$
  - i.e., whether all $\mathbb{T}$-models of pc are also $\mathbb{T}$-models of φ (or $\neg\varphi$)

Extending path condition (cntd.)

- φ is a formula representing a test in a program (e.g. inside an `if` statement)
- suppose pc is $\mathbb{T}$-satisfiable, then at most one of the following can hold:
  1. $pc \Rightarrow_{\mathbb{T}} \varphi$ (the `then` branch)
  2. $pc \Rightarrow_{\mathbb{T}} \neg\varphi$ (the `else` branch)

  where $\Rightarrow_{\mathbb{T}}$ denotes logical consequence w.r.t. theory $\mathbb{T}$
  - i.e., whether all $\mathbb{T}$-models of pc are also $\mathbb{T}$-models of φ (or $\neg\varphi$)
- if one of the logical consequences holds, no forking and extension of pc is required
  - only one branch is feasible
- when neither of the consequences holds, we speak about **forking execution**:
  - the execution forks because both branches are feasible; pc is then extended as:
    1. $pc' := pc \wedge \varphi$ (for the `then` branch)
    2. $pc' := pc \wedge \neg\varphi$ (for the `else` branch)
- logical consequence is checked using an **SMT Solver**

Example of symbolic execution

```
int power(x, y)
{
1:  int z = 1;

2:  int j = 1;

3:  while (y - j >= 0)
    {
4:    z *= x

5:    ++j;
    }

6:  return z
}
```

line	x	y	z	j	*pc*

Symbolic execution — high level algorithm

```
1 symState := (line: 0, store: ∅, pc: true)   // initial symbolic state
2 workSet := {symState}
3 while workSet ≠ ∅:
4   st := workSet.getAndRemove()          // many ways to implement
5   st' := symbolically execute from st until a fork to l1 and l2 with condition φ, or EXIT,
6          while checking for errors and modifying store accordingly
7   if st'.line == EXIT: continue
8   workSet.add((line: l1, store: st'.store, pc: st'.pc ∧ φ))
9   workSet.add((line: l2, store: st'.store, pc: st'.pc ∧ ¬φ))
```

Symbolic execution tree

paths taken in a symbolic execution can be expressed using a **symbolic execution tree**

- control points of the program are nodes
- statements are edges
- tests that are not logical conseq. of the pc for the branch above them have two outgoing edges:
  - $true$ (for `then`)
  - $false$ (for `else`)

properties of the tree:

- for each terminal leaf L, there are concrete (non-symbolic) inputs that can navigate execution to L
  - a terminal leaf corresponds to a finished path
- every two terminal nodes have distinct path conditions, i.e., $pc_1 \wedge pc_2$ is $\mathbb{T}$-UNSAT

Symbolic execution for verification

program verification:

- every `assume`(φ) (in function contracts) will update $pc' := pc \wedge \varphi$
- every `assert`(φ) will test whether $pc \Rightarrow_{\mathbb{T}} \varphi$, if not: report error
- during execution of a program (or in preprocessing), more statements are added, e.g.:

Symbolic execution for verification

program verification:

- every `assume(`φ`)` (in function contracts) will update $pc' := pc \wedge \varphi$
- every `assert(`φ`)` will test whether $pc \Rightarrow_{\mathbb{T}} \varphi$, if not: report error
- during execution of a program (or in preprocessing), more statements are added, e.g.:
  - for a fixed-size array `a` of size `N`, every access `a[x]` where `x` has a symbolic value changes:

```
                          assert(x < N && x >= 0);
a[x] = y;      -->        a[x] = y;
```

Symbolic execution for verification

program verification:

- every `assume(`φ`)` (in function contracts) will update $pc' := pc \wedge \varphi$
- every `assert(`φ`)` will test whether $pc \Rightarrow_{\mathbb{T}} \varphi$, if not: report error
- during execution of a program (or in preprocessing), more statements are added, e.g.:
  - for a fixed-size array `a` of size `N`, every access `a[x]` where `x` has a symbolic value changes:

```
                          assert(x < N && x >= 0);
a[x] = y;      -->        a[x] = y;
```

  - every integer division is checked for zero-division:

```
                          assert(x != 0);
y = 42 / x;    -->        y = 42 / x;
```

Symbolic execution for verification

program verification:

- every `assume`(φ) (in function contracts) will update $pc' := pc \wedge \varphi$
- every `assert`(φ) will test whether $pc \Rightarrow_{\mathbb{T}} \varphi$, if not: report error
- during execution of a program (or in preprocessing), more statements are added, e.g.:
  - for a fixed-size array `a` of size `N`, every access `a[x]` where `x` has a symbolic value changes:

```
                          assert(x < N && x >= 0);
a[x] = y;      -->        a[x] = y;
```

  - every integer division is checked for zero-division:

```
                          assert(x != 0);
y = 42 / x;    -->        y = 42 / x;
```

  - pointer accesses are checked for `nullptr`:

```
                          assert(x != nullptr);
y = *x;        -->        y = *x;
```

    (checking for dereference of undefined memory locations is more difficult)
  - etc.

Search strategies

given by the implementation of $workSet.getAndRemove()$

- if **stack**: DFS
  - can easily get stuck in some part of the program

Search strategies

given by the implementation of $workSet.getAndRemove()$

- if **stack**: DFS
  - can easily get stuck in some part of the program
- if **queue**: BFS
  - usually better, but still not guided by any higher-level knowledge

Search strategies

given by the implementation of $workSet.getAndRemove()$

- if **stack**: DFS
  - can easily get stuck in some part of the program
- if **queue**: BFS
  - usually better, but still not guided by any higher-level knowledge
- more complex strategies:
  - try to steer the search (using priorities) towards assertion failures
  - reasoning on the *control flow graph* (CFG) of the program

Search strategies

given by the implementation of $workSet.getAndRemove()$

- if **stack**: DFS
  - can easily get stuck in some part of the program
- if **queue**: BFS
  - usually better, but still not guided by any higher-level knowledge
- more complex strategies:
  - try to steer the search (using priorities) towards assertion failures
  - reasoning on the *control flow graph* (CFG) of the program
- **randomness**: we don't know which paths to take... why not pick them randomly?
  1. pick next path uniformly at random
  2. randomly restart search if nothing interesting found for a while
  3. when choosing between two paths with the same priority, flip a coin

Search strategies

- **coverage-guided heuristics**:
  - try to visit statements not seen before
  - increments statement's score when hit
  - pick a statement with lowest score
  - can be difficult to find how to get to a statement

Search strategies

- **coverage-guided heuristics**:
  - try to visit statements not seen before
  - increments statement's score when hit
  - pick a statement with lowest score
  - can be difficult to find how to get to a statement (undecidable)

Search strategies

- **coverage-guided heuristics**:
  - try to visit statements not seen before
  - increments statement's score when hit
  - pick a statement with lowest score
  - can be difficult to find how to get to a statement (undecidable)
- **generational search** (hybrid of BFS + coverage-guided):
  - **GEN 0**: pick one program path at random, run to completion
  - **GEN** $n+1$: take pc from GEN n and negate one branch condition, repeat
  - *modification*: negate *all* branch conditions, get several paths
  - often used with concolic execution

Search strategies

- **coverage-guided heuristics**:
  - try to visit statements not seen before
  - increments statement's score when hit
  - pick a statement with lowest score
  - can be difficult to find how to get to a statement (undecidable)
- **generational search** (hybrid of BFS + coverage-guided):
  - **GEN 0**: pick one program path at random, run to completion
  - **GEN** $n+1$: take pc from GEN n and negate one branch condition, repeat
  - *modification*: negate *all* branch conditions, get several paths
  - often used with concolic execution
- **combined search**:
  - run multiple searches at once

Issues

- we need to test logical consequence $pc \Rightarrow_{\mathbb{T}} \varphi$ between path conditions and tests
  - reasoning in some theories is still challenging for SMT solvers
    - e.g., arithmetic over natural numbers, string variables w/ operations, ...

Issues

- we need to test logical consequence $pc \Rightarrow_{\mathbb{T}} \varphi$ between path conditions and tests
  - reasoning in some theories is still challenging for SMT solvers
    - e.g., arithmetic over natural numbers, string variables w/ operations, ...
- fixed-size/precision integer and floating-point variables in concrete execution:
  - are often represented using "ideal" symbolic values from $\mathbb{N}$ or $\mathbb{R}$
  - more faithful representation uses theory of FixedSizeBitVectors and FloatingPoint

Issues

- we need to test logical consequence $pc \Rightarrow_{\mathbb{T}} \varphi$ between path conditions and tests
  - reasoning in some theories is still challenging for SMT solvers
    - e.g., arithmetic over natural numbers, string variables w/ operations, ...
- fixed-size/precision integer and floating-point variables in concrete execution:
  - are often represented using "ideal" symbolic values from $\mathbb{N}$ or $\mathbb{R}$
  - more faithful representation uses theory of FixedSizeBitVectors and FloatingPoint
- problems modelling **memory**:
  - checking for invalid memory accesses `a[x]` where
    - `a` is an array and
    - `x` has a symbolic value
  - unsatisfactory solution:
    - $ite(v(\mathtt{x}) = 1, v(\mathtt{a}[1]), ite(v(\mathtt{x}) = 2, v(\mathtt{a}[2]), \ldots))$
  - theory of arrays
  - even more problems with dynamic data structures
    - model the whole memory as a big array? ... does not scale

Issues

- **path explosion**:
  - when symbolic execution keeps forking
  - e.g. on cycles without a fixed number of iterations
  - cf. bounded model checking (BMC)

Issues

- **path explosion**:
  - when symbolic execution keeps forking
  - e.g. on cycles without a fixed number of iterations
  - cf. bounded model checking (BMC)
- **imprecision**: reasons
  - pointer manipulation
  - SMT solver limitations
  - complex arithmetic operations (hashing, encryption, etc.)
  - system/library calls (e.g. `libc`):
    - can contain native code
    - very complicated (e.g. call of `malloc`)
    - using a simpler version can be advantageous (e.g., `newlib`, a version of `libc` for embedded systems)
    - need to make a model (a lot of work)

Concolic testing

- **concolic** = **conc**rete + symb**olic**
- program is executed at the same time on symbolic and concrete inputs
  - program is given *concrete inputs* I, which are shadowed by *symbolic values*
    - the symbolic values generalize the concrete inputs
  - execution of the program is instrumented: computation of path condition
  - when a path terminates
    - choose a decision point d in its path condition $pc = \varphi \wedge d \wedge \psi$
    - obtain a new path condition prefix $pc' = \varphi \wedge \neg d$
    - generate new inputs $I' \models pc'$
    - re-run the program with I' as its inputs
- for system calls, use the concrete value
  - symbolic-ness is lost at such calls
- no need to call SMT solver at conditions

Tools

- **KLEE**: symbolic execution of LLVM bitcode
- **Pex**: symbolic execution for .NET
- **CREST**: concolic testing of `C` programs
- **SAGE**: targets file parsers (e.g., `.doc`, `.jpeg`)
  - used daily in Microsoft Win, Office, ...
  - found 100s of bugs in 100s of apps

```
paste -d\\ abcdefghijklmnopqrstuvwxyz
pr -e t2.txt
tac -r t3.txt t3.txt
mkdir -Z a b
mkfifo -Z a b
mknod -Z a b p
md5sum -c t1.txt
ptx -F\\ abcdefghijklmnopqrstuvwxyz
ptx x t4.txt
seq -f %0 1
```

t1.txt: `"\t \tMD5("`
t2.txt: `"\b\b\b\b\b\b\b\t"`
t3.txt: `"\n"`
t4.txt: `"a"`

Figure 7: KLEE-generated command lines and inputs (modified for readability) that cause program crashes in COREUTILS version 6.10 when run on Fedora Core 7 with SELinux on a Pentium machine.

Tools

- **Mergepoint**: static analysis + SE
- **Otter**: symbolic execution for `C`
  - provide a line number
  - Otter will try to get there
- **Symbiotic**: symbiosis of several approaches:
  1. program instrumentation (adding monitors for various properties)
  2. static program slicing (removing statements that are irrelevant to the property)
  3. symbolic execution based on KLEE
- **PyEx**: symbolic execution of Python programs