

# Verified Construction of Fair Voting Rules

Michael Kirsten

Karlsruhe Institute of Technology (KIT), Karlsruhe, Germany  
`kirsten@kit.edu`

December 12, 2024

## Abstract

Voting rules aggregate multiple individual preferences in order to make a collective decision. Commonly, these mechanisms are expected to respect a multitude of different notions of fairness and reliability, which must be carefully balanced to avoid inconsistencies.

This article contains a formalisation of a framework for the construction of such fair voting rules using composable modules [1, 2]. The framework is a formal and systematic approach for the flexible and verified construction of voting rules from individual composable modules to respect such social-choice properties by construction. Formal composition rules guarantee resulting social-choice properties from properties of the individual components which are of generic nature to be reused for various voting rules. We provide proofs for a selected set of structures and composition rules. The approach can be readily extended in order to support more voting rules, e.g., from the literature by extending the sets of modules and composition rules.

# Contents

<b>1</b>	<b>Social-Choice Types</b>	<b>9</b>
1.1	Auxiliary Lemmas . . . . .	9
1.2	Preference Relation . . . . .	10
1.2.1	Definition . . . . .	10
1.2.2	Ranking . . . . .	11
1.2.3	Limited Preference . . . . .	11
1.2.4	Auxiliary Lemmas . . . . .	16
1.2.5	Lifting Property . . . . .	26
1.3	Norm . . . . .	35
1.3.1	Definition . . . . .	35
1.3.2	Auxiliary Lemmas . . . . .	35
1.3.3	Common Norms . . . . .	37
1.3.4	Properties . . . . .	37
1.3.5	Theorems . . . . .	37
1.4	Electoral Result . . . . .	38
1.4.1	Auxiliary Functions . . . . .	38
1.4.2	Definition . . . . .	38
1.5	Preference Profile . . . . .	39
1.5.1	Definition . . . . .	39
1.5.2	Vote Count . . . . .	41
1.5.3	Voter Permutations . . . . .	44
1.5.4	List Representation . . . . .	47
1.5.5	Preference Counts . . . . .	52
1.5.6	Condorcet Winner . . . . .	55
1.5.7	Limited Profile . . . . .	57
1.5.8	Lifting Property . . . . .	58
1.6	Social Choice Result . . . . .	60
1.6.1	Definition . . . . .	60
1.6.2	Auxiliary Lemmas . . . . .	61
1.7	Social Welfare Result . . . . .	64
1.8	Electoral Result Types . . . . .	64
1.9	Symmetry Properties of Functions . . . . .	66
1.9.1	Functions . . . . .	66

1.9.2	Relations for Symmetry Constructions . . . . .	66
1.9.3	Invariance and Equivariance . . . . .	66
1.9.4	Auxiliary Lemmas . . . . .	67
1.9.5	Rewrite Rules . . . . .	68
1.9.6	Group Actions . . . . .	72
1.9.7	Invariance and Equivariance . . . . .	74
1.9.8	Function Composition . . . . .	79
1.10	Symmetry Properties of Voting Rules . . . . .	82
1.10.1	Definitions . . . . .	82
1.10.2	Auxiliary Lemmas . . . . .	84
1.10.3	Anonymity Lemmas . . . . .	94
1.10.4	Neutrality Lemmas . . . . .	101
1.10.5	Homogeneity Lemmas . . . . .	115
1.10.6	Reversal Symmetry Lemmas . . . . .	115
1.11	Result-Dependent Voting Rule Properties . . . . .	120
1.11.1	Property Definitions . . . . .	121
1.11.2	Interpretations . . . . .	121
<b>2</b>	<b>Refined Types</b>	<b>122</b>
2.1	Preference List . . . . .	122
2.1.1	Well-Formedness . . . . .	122
2.1.2	Auxiliary Lemmas About Lists . . . . .	122
2.1.3	Ranking . . . . .	127
2.1.4	Definition . . . . .	127
2.1.5	Limited Preference . . . . .	136
2.1.6	Auxiliary Definitions . . . . .	140
2.1.7	Auxiliary Lemmas . . . . .	140
2.1.8	First Occurrence Indices . . . . .	143
2.2	Preference (List) Profile . . . . .	145
2.2.1	Definition . . . . .	145
2.2.2	Refinement Proof . . . . .	146
2.3	Ordered Relation Type . . . . .	146
2.4	Alternative Election Type . . . . .	149
<b>3</b>	<b>Quotient Rules</b>	<b>151</b>
3.1	Quotients of Equivalence Relations . . . . .	151
3.1.1	Definitions . . . . .	151
3.1.2	Well-Definedness . . . . .	151
3.1.3	Equivalence Relations . . . . .	154
3.2	Quotients of Election Set Equivalences . . . . .	156
3.2.1	Auxiliary Lemmas . . . . .	156
3.2.2	Anonymity Quotient: Grid . . . . .	159
3.2.3	Homogeneity Quotient: Simplex . . . . .	168

<b>4</b>	<b>Component Types</b>	<b>189</b>
4.1	Distance	189
4.1.1	Definition	189
4.1.2	Conditions	190
4.1.3	Standard-Distance Property	190
4.1.4	Auxiliary Lemmas	190
4.1.5	Swap Distance	191
4.1.6	Spearman Distance	192
4.1.7	Properties	193
4.2	Votewise Distance	198
4.2.1	Definition	198
4.2.2	Inference Rules	198
4.3	Consensus	204
4.3.1	Definition	204
4.3.2	Consensus Conditions	204
4.3.3	Properties	205
4.3.4	Auxiliary Lemmas	205
4.3.5	Theorems	208
4.4	Electoral Module	212
4.4.1	Definition	212
4.4.2	Auxiliary Definitions	213
4.4.3	Auxiliary Properties	213
4.4.4	Social-Choice Modules	214
4.4.5	Equivalence Definitions	215
4.4.6	Auxiliary Lemmas	216
4.4.7	Non-Blocking	226
4.4.8	Electing	226
4.4.9	Properties	228
4.4.10	Inference Rules	232
4.4.11	Social-Choice Properties	234
4.4.12	Social-Welfare Properties	236
4.4.13	Property Relations	236
4.5	Electoral Module on Election Quotients	238
4.6	Evaluation Function	239
4.6.1	Definition	239
4.6.2	Property	239
4.6.3	Theorems	239
4.7	Elimination Module	241
4.7.1	General Definitions	241
4.7.2	Social-Choice Definitions	242
4.7.3	Social-Choice Eliminators	242
4.7.4	Soundness	242
4.7.5	Independence of Non-Voters	243
4.7.6	Non-Blocking	246

4.7.7	Non-Electing	248
4.7.8	Inference Rules	249
4.8	Aggregator	251
4.8.1	Definition	252
4.8.2	Properties	252
4.9	Maximum Aggregator	252
4.9.1	Definition	252
4.9.2	Auxiliary Lemma	253
4.9.3	Soundness	253
4.9.4	Properties	254
4.10	Termination Condition	255
4.11	Defer Equal Condition	255
<b>5</b>	<b>Basic Modules</b>	<b>257</b>
5.1	Defer Module	257
5.1.1	Definition	257
5.1.2	Soundness	257
5.1.3	Properties	257
5.2	Elect-First Module	258
5.2.1	Definition	258
5.2.2	Soundness	258
5.3	Consensus Class	259
5.3.1	Definition	259
5.3.2	Consensus Choice	259
5.3.3	Auxiliary Lemmas	260
5.3.4	Consensus Rules	263
5.3.5	Properties	263
5.3.6	Inference Rules	264
5.3.7	Theorems	267
5.4	Distance Rationalization	273
5.4.1	Definitions	274
5.4.2	Standard Definitions	274
5.4.3	Auxiliary Lemmas	275
5.4.4	Soundness	282
5.4.5	Properties	282
5.4.6	Inference Rules	282
5.5	Votewise Distance Rationalization	290
5.5.1	Common Rationalizations	290
5.5.2	Theorems	290
5.5.3	Equivalence Lemmas	292
5.6	Symmetry in Distance-Rationalizable Rules	292
5.6.1	Minimizer Function	292
5.6.2	Minimizer Translation	297
5.6.3	Inference Rules	305

5.7	Distance Rationalization on Election Quotients . . . . .	308
5.7.1	Distances . . . . .	308
5.7.2	Consensus and Results . . . . .	319
5.7.3	Distance Rationalization . . . . .	323
5.8	Code Generation Interpretations for Results and Properties .	330
5.8.1	Code Lemmas . . . . .	330
5.8.2	Interpretation Declarations and Constants . . . . .	332
5.9	Drop Module . . . . .	332
5.9.1	Definition . . . . .	332
5.9.2	Soundness . . . . .	333
5.9.3	Non-Electing . . . . .	333
5.9.4	Properties . . . . .	334
5.10	Pass Module . . . . .	334
5.10.1	Definition . . . . .	334
5.10.2	Soundness . . . . .	334
5.10.3	Non-Blocking . . . . .	335
5.10.4	Non-Electing . . . . .	336
5.10.5	Properties . . . . .	336
5.11	Elect Module . . . . .	342
5.11.1	Definition . . . . .	343
5.11.2	Soundness . . . . .	343
5.11.3	Electing . . . . .	343
5.12	Plurality Module . . . . .	343
5.12.1	Definition . . . . .	343
5.12.2	Soundness . . . . .	346
5.12.3	Non-Blocking . . . . .	347
5.12.4	Non-Electing . . . . .	347
5.12.5	Property . . . . .	348
5.13	Borda Module . . . . .	353
5.13.1	Definition . . . . .	353
5.13.2	Soundness . . . . .	353
5.13.3	Non-Blocking . . . . .	353
5.13.4	Non-Electing . . . . .	353
5.14	Condorcet Module . . . . .	354
5.14.1	Definition . . . . .	354
5.14.2	Soundness . . . . .	354
5.14.3	Property . . . . .	354
5.15	Copeland Module . . . . .	356
5.15.1	Definition . . . . .	356
5.15.2	Soundness . . . . .	356
5.15.3	Lemmas . . . . .	356
5.15.4	Property . . . . .	359
5.16	Minimax Module . . . . .	361
5.16.1	Definition . . . . .	362

5.16.2	Soundness . . . . .	362
5.16.3	Lemma . . . . .	362
5.16.4	Property . . . . .	363
<b>6</b>	<b>Compositional Structures</b>	<b>366</b>
6.1	Drop- and Pass-Compatibility . . . . .	366
6.2	Revision Composition . . . . .	371
6.2.1	Definition . . . . .	371
6.2.2	Soundness . . . . .	371
6.2.3	Composition Rules . . . . .	372
6.3	Sequential Composition . . . . .	375
6.3.1	Definition . . . . .	375
6.3.2	Soundness . . . . .	381
6.3.3	Lemmas . . . . .	382
6.3.4	Composition Rules . . . . .	386
6.4	Parallel Composition . . . . .	410
6.4.1	Definition . . . . .	410
6.4.2	Soundness . . . . .	410
6.4.3	Composition Rule . . . . .	411
6.5	Loop Composition . . . . .	413
6.5.1	Definition . . . . .	414
6.5.2	Soundness . . . . .	418
6.5.3	Lemmas . . . . .	419
6.5.4	Composition Rules . . . . .	431
6.6	Maximum Parallel Composition . . . . .	433
6.6.1	Definition . . . . .	434
6.6.2	Soundness . . . . .	434
6.6.3	Lemmas . . . . .	434
6.6.4	Composition Rules . . . . .	445
6.7	Elect Composition . . . . .	453
6.7.1	Definition . . . . .	454
6.7.2	Auxiliary Lemmas . . . . .	454
6.7.3	Soundness . . . . .	454
6.7.4	Electing . . . . .	454
6.7.5	Composition Rule . . . . .	456
6.8	Defer-One Loop Composition . . . . .	458
6.8.1	Soundness . . . . .	459
<b>7</b>	<b>Voting Rules</b>	<b>460</b>
7.1	Plurality Rule . . . . .	460
7.1.1	Definition . . . . .	460
7.1.2	Soundness . . . . .	463
7.1.3	Electing . . . . .	464
7.1.4	Properties . . . . .	467

7.2	Borda Rule . . . . .	469
7.2.1	Definition . . . . .	469
7.2.2	Soundness . . . . .	469
7.2.3	Anonymity . . . . .	469
7.3	Pairwise Majority Rule . . . . .	470
7.3.1	Definition . . . . .	470
7.3.2	Soundness . . . . .	470
7.3.3	Condorcet Consistency . . . . .	471
7.4	Copeland Rule . . . . .	471
7.4.1	Definition . . . . .	471
7.4.2	Soundness . . . . .	471
7.4.3	Condorcet Consistency . . . . .	471
7.5	Minimax Rule . . . . .	472
7.5.1	Definition . . . . .	472
7.5.2	Soundness . . . . .	472
7.5.3	Condorcet Consistency . . . . .	472
7.6	Black's Rule . . . . .	472
7.6.1	Definition . . . . .	473
7.6.2	Soundness . . . . .	473
7.6.3	Condorcet Consistency . . . . .	473
7.7	Nanson-Baldwin Rule . . . . .	473
7.7.1	Definition . . . . .	474
7.7.2	Soundness . . . . .	474
7.8	Classic Nanson Rule . . . . .	474
7.8.1	Definition . . . . .	474
7.8.2	Soundness . . . . .	474
7.9	Schwartz Rule . . . . .	475
7.9.1	Definition . . . . .	475
7.9.2	Soundness . . . . .	475
7.10	Sequential Majority Comparison . . . . .	475
7.10.1	Definition . . . . .	475
7.10.2	Soundness . . . . .	476
7.10.3	Electing . . . . .	476
7.10.4	(Weak) Monotonicity . . . . .	478
7.11	Kemeny Rule . . . . .	480
7.11.1	Definition . . . . .	481
7.11.2	Soundness . . . . .	481
7.11.3	Anonymity . . . . .	481
7.11.4	Neutrality . . . . .	481



# Chapter 1

## Social-Choice Types

### 1.1 Auxiliary Lemmas

```
theory Auxiliary-Lemmas
  imports Main
begin
```

Summation function is invariant under application of a (bijective) permutation on the elements.

```
lemma sum-comp:
  fixes
     $f :: 'x \Rightarrow ('z :: \text{comm-monoid-add})$  and
     $g :: 'y \Rightarrow 'x$  and
     $X :: 'x \text{ set}$  and
     $Y :: 'y \text{ set}$ 
  assumes bij-betw g Y X
  shows  $(\sum x \in X. f\ x) = (\sum x \in Y. (f \circ g)\ x)$ 
  using assms sum.reindex
  unfolding bij-betw-def
  by (metis (no-types))
```

The inversion of a composition of injective functions is equivalent to the composition of the two individual inverted functions.

```
lemma the-inv-comp:
  fixes
     $X :: 'x \text{ set}$  and
     $Y :: 'y \text{ set}$  and
     $Z :: 'z \text{ set}$  and
     $f :: 'y \Rightarrow 'x$  and
     $g :: 'z \Rightarrow 'y$  and
     $x :: 'x$ 
  assumes
    bij-betw f Y X and
    bij-betw g Z Y and
     $x \in X$ 
```

```

shows the-inv-into Z (f ∘ g) x = ((the-inv-into Z g) ∘ (the-inv-into Y f)) x
using assms the-inv-into-comp
unfolding bij-betw-def
by metis

end

```

## 1.2 Preference Relation

```

theory Preference-Relation
  imports Main
begin

```

The very core of the composable modules voting framework: types and functions, derivations, lemmas, operations on preference relations, etc.

### 1.2.1 Definition

Each voter expresses pairwise relations between all alternatives, thereby inducing a linear order.

```

type-synonym 'a Preference-Relation = 'a rel

```

```

type-synonym 'a Vote = 'a set × 'a Preference-Relation

```

```

fun is-less-preferred-than :: 'a ⇒ 'a Preference-Relation ⇒ 'a ⇒ bool
  (- ≤r - [50, 1000, 51] 50) where
  a ≤r b = ((a, b) ∈ r)

```

```

fun alts- $\mathcal{V}$  :: 'a Vote ⇒ 'a set where
  alts- $\mathcal{V}$  V = fst V

```

```

fun pref- $\mathcal{V}$  :: 'a Vote ⇒ 'a Preference-Relation where
  pref- $\mathcal{V}$  V = snd V

```

```

lemma lin-imp-antisym:

```

```

  fixes
    A :: 'a set and
    r :: 'a Preference-Relation
  assumes linear-order-on A r
  shows antisym r
  using assms
  unfolding linear-order-on-def partial-order-on-def
  by simp

```

```

lemma lin-imp-trans:
  fixes
     $A :: 'a \text{ set}$  and
     $r :: 'a \text{ Preference-Relation}$ 
  assumes linear-order-on A r
  shows trans r
  using assms order-on-defs
  by blast

```

### 1.2.2 Ranking

```

fun rank :: ' $a \text{ Preference-Relation} \Rightarrow 'a \Rightarrow \text{nat}$ ' where
  rank r a = card (above r a)

```

```

lemma rank-gt-zero:
  fixes
     $r :: 'a \text{ Preference-Relation}$  and
     $a :: 'a$ 
  assumes
    refl: a  $\preceq_r$  a and
    fin: finite r
  shows  $\text{rank } r \ a \geq 1$ 
proof (unfold rank.simps above-def)
  have  $a \in \{b \in \text{Field } r. (a, b) \in r\}$ 
  using FieldI2 refl
  by fastforce
  hence  $\{b \in \text{Field } r. (a, b) \in r\} \neq \{\}$ 
  by blast
  hence  $\text{card } \{b \in \text{Field } r. (a, b) \in r\} \neq 0$ 
  by (simp add: fin finite-Field)
  thus  $1 \leq \text{card } \{b. (a, b) \in r\}$ 
  using Collect-cong FieldI2 less-one not-le-imp-less
  by (metis (no-types, lifting))
qed

```

### 1.2.3 Limited Preference

```

definition limited :: ' $a \text{ set} \Rightarrow 'a \text{ Preference-Relation} \Rightarrow \text{bool}$ ' where
  limited A r  $\equiv r \subseteq A \times A$ 

```

```

lemma limited-dest:
  fixes
     $A :: 'a \text{ set}$  and
     $r :: 'a \text{ Preference-Relation}$  and
     $a \ b :: 'a$ 
  assumes
     $a \preceq_r b$  and
    limited A r
  shows  $a \in A \wedge b \in A$ 
  using assms

```

```

unfolding limited-def
by auto

fun limit :: 'a set  $\Rightarrow$  'a Preference-Relation  $\Rightarrow$  'a Preference-Relation where
  limit A r = {(a, b)  $\in$  r. a  $\in$  A  $\wedge$  b  $\in$  A}

definition connex :: 'a set  $\Rightarrow$  'a Preference-Relation  $\Rightarrow$  bool where
  connex A r  $\equiv$  limited A r  $\wedge$  ( $\forall$  a  $\in$  A.  $\forall$  b  $\in$  A. a  $\preceq_r$  b  $\vee$  b  $\preceq_r$  a)

lemma connex-imp-refl:
fixes
  A :: 'a set and
  r :: 'a Preference-Relation
assumes connex A r
shows refl-on A r
using assms
proof (unfold connex-def refl-on-def limited-def, elim conjE conjI, safe)
  fix a :: 'a
  assume a  $\in$  A
  hence a  $\preceq_r$  a
    using assms
    unfolding connex-def
    by metis
  thus (a, a)  $\in$  r
    by simp
qed

lemma lin-ord-imp-connex:
fixes
  A :: 'a set and
  r :: 'a Preference-Relation
assumes linear-order-on A r
shows connex A r
proof (unfold connex-def limited-def, safe)
  fix a b :: 'a
  assume (a, b)  $\in$  r
  moreover have refl-on A r
    using assms partial-order-onD
    unfolding linear-order-on-def
    by safe
  ultimately show
    a  $\in$  A and
    b  $\in$  A
    by (simp-all add: refl-on-domain)
next
  fix a b :: 'a
  assume
    a  $\in$  A and
    b  $\in$  A and

```

```

   $\neg b \preceq_r a$ 
  moreover from this
  have  $(b, a) \notin r$ 
  by simp
  moreover have refl-on  $A$   $r$ 
  using assms partial-order-onD
  unfolding linear-order-on-def
  by blast
  ultimately have  $(a, b) \in r$ 
  using assms refl-onD
  unfolding linear-order-on-def total-on-def
  by metis
  thus  $a \preceq_r b$ 
  by simp
qed

```

**lemma** *connex-antsym-and-trans-imp-lin-ord*:

```

  fixes
     $A :: 'a$  set and
     $r :: 'a$  Preference-Relation
  assumes
    connex-r: connex  $A$   $r$  and
    antisym-r: antisym  $r$  and
    trans-r: trans  $r$ 
  shows linear-order-on  $A$   $r$ 
proof (unfold connex-def linear-order-on-def partial-order-on-def
  preorder-on-def refl-on-def total-on-def, safe)
  fix  $a\ b :: 'a$ 
  assume  $(a, b) \in r$ 
  thus
     $a \in A$  and
     $b \in A$ 
    using connex-r refl-on-domain connex-imp-refl
    by (metis, metis)
next
  fix  $a :: 'a$ 
  assume  $a \in A$ 
  thus  $(a, a) \in r$ 
    using connex-r connex-imp-refl refl-onD
    by metis
next
  show trans  $r$ 
    using trans-r
    by simp
next
  show antisym  $r$ 
    using antisym-r
    by simp
next

```

```

fix  $a\ b :: 'a$ 
assume
   $a \in A$  and
   $b \in A$ 
hence  $(a, b) \in r \vee (b, a) \in r$ 
  using connex-r
  unfolding connex-def
  by simp
moreover assume  $(b, a) \notin r$ 
ultimately show  $(a, b) \in r$ 
  by metis
qed

```

```

lemma limit-to-limits:
fixes
   $A :: 'a\ set$  and
   $r :: 'a\ Preference-Relation$ 
shows limited A (limit A r)
unfolding limited-def
by fastforce

```

```

lemma limit-presv-connex:
fixes
   $A\ B :: 'a\ set$  and
   $r :: 'a\ Preference-Relation$ 
assumes
  connex: connex B r and
  subset: A ⊆ B
shows connex A (limit A r)
proof (unfold connex-def limited-def limit.simps is-less-preferred-than.simps, safe)
let  $?s = \{(a, b). (a, b) \in r \wedge a \in A \wedge b \in A\}$ 
fix  $a\ b :: 'a$ 
assume
  a-in-A: a ∈ A and
  b-in-A: b ∈ A and
  not-b-pref-r-a: (b, a) ∉ r
have  $b \preceq_r a \vee a \preceq_r b$ 
  using a-in-A b-in-A connex connex-def in-mono subset
  by metis
hence  $a \preceq_{?s} b \vee b \preceq_{?s} a$ 
  using a-in-A b-in-A
  by auto
thus  $(a, b) \in r$ 
  using not-b-pref-r-a
  by simp
qed

```

```

lemma limit-presv-antisym:
fixes

```

```

    A :: 'a set and
    r :: 'a Preference-Relation
  assumes antisym r
  shows antisym (limit A r)
  using assms
  unfolding antisym-def
  by simp

lemma limit-presv-trans:
  fixes
    A :: 'a set and
    r :: 'a Preference-Relation
  assumes trans r
  shows trans (limit A r)
  unfolding trans-def
  using transE assms
  by auto

lemma limit-presv-lin-ord:
  fixes
    A B :: 'a set and
    r :: 'a Preference-Relation
  assumes
    linear-order-on B r and
    A  $\subseteq$  B
  shows linear-order-on A (limit A r)
  using assms connex-antisym-and-trans-imp-lin-ord limit-presv-antisym limit-presv-connex
    limit-presv-trans lin-ord-imp-connex
  unfolding preorder-on-def partial-order-on-def linear-order-on-def
  by metis

lemma limit-presv-prefs:
  fixes
    A :: 'a set and
    r :: 'a Preference-Relation and
    a b :: 'a
  assumes
    a  $\preceq_r$  b and
    a  $\in$  A and
    b  $\in$  A
  shows let s = limit A r in a  $\preceq_s$  b
  using assms
  by simp

lemma limit-rel-presv-prefs:
  fixes
    A :: 'a set and
    r :: 'a Preference-Relation and
    a b :: 'a

```

```

assumes  $(a, b) \in \text{limit } A \ r$ 
shows  $a \preceq_r b$ 
using mem-Collect-eq assms
by simp

lemma limit-trans:
  fixes
     $A \ B :: 'a \ \text{set}$  and
     $r :: 'a \ \text{Preference-Relation}$ 
  assumes  $A \subseteq B$ 
  shows  $\text{limit } A \ r = \text{limit } A \ (\text{limit } B \ r)$ 
  using assms
  by auto

lemma lin-ord-not-empty:
  fixes  $r :: 'a \ \text{Preference-Relation}$ 
  assumes  $r \neq \{\}$ 
  shows  $\neg \text{linear-order-on } \{\} \ r$ 
  using assms connex-imp-refl lin-ord-imp-connex refl-on-domain subrelI
  by fastforce

lemma lin-ord-singleton:
  fixes  $a :: 'a$ 
  shows  $\forall \ r. \text{linear-order-on } \{a\} \ r \longrightarrow r = \{(a, a)\}$ 
proof (clarify)
  fix  $r :: 'a \ \text{Preference-Relation}$ 
  assume lin-ord-r-a: linear-order-on {a} r
  hence  $a \preceq_r a$ 
  using lin-ord-imp-connex singletonI
  unfolding connex-def
  by metis
  moreover from lin-ord-r-a
  have  $\forall \ (b, c) \in r. \ b = a \wedge c = a$ 
  using connex-imp-refl lin-ord-imp-connex refl-on-domain split-beta
  by fastforce
  ultimately show  $r = \{(a, a)\}$ 
  by auto
qed

```

### 1.2.4 Auxiliary Lemmas

```

lemma above-trans:
  fixes
     $r :: 'a \ \text{Preference-Relation}$  and
     $a \ b :: 'a$ 
  assumes
    trans r and
     $(a, b) \in r$ 
  shows  $\text{above } r \ b \subseteq \text{above } r \ a$ 

```



```

using Collect-mono assms transE
unfolding above-def
by metis

lemma above-refl:
fixes
   $A :: 'a \text{ set}$  and
   $r :: 'a \text{ Preference-Relation}$  and
   $a :: 'a$ 
assumes
   $\text{refl-on } A \ r$  and
   $a \in A$ 
shows  $a \in \text{above } r \ a$ 
using assms refl-onD
unfolding above-def
by simp

lemma above-subset-geq-one:
fixes
   $A :: 'a \text{ set}$  and
   $r \ r' :: 'a \text{ Preference-Relation}$  and
   $a :: 'a$ 
assumes
   $\text{linear-order-on } A \ r$  and
   $\text{linear-order-on } A \ r'$  and
   $\text{above } r \ a \subseteq \text{above } r' \ a$  and
   $\text{above } r' \ a = \{a\}$ 
shows  $\text{above } r \ a = \{a\}$ 
using assms connex-imp-refl above-refl insert-absorb lin-ord-imp-connex mem-Collect-eq
  refl-on-domain singletonI subset-singletonD
unfolding above-def
by metis

lemma above-connex:
fixes
   $A :: 'a \text{ set}$  and
   $r :: 'a \text{ Preference-Relation}$  and
   $a :: 'a$ 
assumes
   $\text{connex } A \ r$  and
   $a \in A$ 
shows  $a \in \text{above } r \ a$ 
using assms connex-imp-refl above-refl
by metis

lemma pref-imp-in-above:
fixes
   $r :: 'a \text{ Preference-Relation}$  and
   $a \ b :: 'a$ 

```

```

shows  $(a \preceq_r b) = (b \in \text{above } r \ a)$ 
unfolding above-def
by simp

lemma limit-presv-above:
  fixes
     $A :: 'a \text{ set}$  and
     $r :: 'a \text{ Preference-Relation}$  and
     $a \ b :: 'a$ 
  assumes
     $b \in \text{above } r \ a$  and
     $a \in A$  and
     $b \in A$ 
  shows  $b \in \text{above } (\text{limit } A \ r) \ a$ 
  using assms pref-imp-in-above limit-presv-prefs
  by metis

lemma limit-rel-presv-above:
  fixes
     $A \ B :: 'a \text{ set}$  and
     $r :: 'a \text{ Preference-Relation}$  and
     $a \ b :: 'a$ 
  assumes  $b \in \text{above } (\text{limit } B \ r) \ a$ 
  shows  $b \in \text{above } r \ a$ 
  using assms limit-rel-presv-prefs mem-Collect-eq pref-imp-in-above
  unfolding above-def
  by metis

lemma above-one:
  fixes
     $A :: 'a \text{ set}$  and
     $r :: 'a \text{ Preference-Relation}$ 
  assumes
    lin-ord-r: linear-order-on A r and
    fin-A: finite A and
    non-empty-A: A  $\neq$  {}
  shows  $\exists \ a \in A. \text{above } r \ a = \{a\} \wedge (\forall \ a' \in A. \text{above } r \ a' = \{a'\} \longrightarrow a' = a)$ 
proof –
  obtain  $n :: \text{nat}$  where
    len-n-plus-one: n + 1 = card A
  using Suc-eq-plus1 antisym-conv2 fin-A non-empty-A card-eq-0-iff
    gr0-implies-Suc le0
  by metis
  have linear-order-on A r  $\wedge$  finite A  $\wedge$   $A \neq \{\}$   $\wedge$   $n + 1 = \text{card } A$ 
     $\longrightarrow (\exists \ a \in A. \text{above } r \ a = \{a\})$ 
  proof (induction n arbitrary: A r; clarify)
  case 0
  fix
     $A' :: 'a \text{ set}$  and

```

```

   $r' :: 'a \text{ Preference-Relation}$ 
assume
   $\text{lin-ord-r: linear-order-on } A' \text{ } r' \text{ and}$ 
   $\text{len-A-is-one: } 0 + 1 = \text{card } A'$ 
then obtain  $a :: 'a$  where
   $A' = \{a\}$ 
  using  $\text{card-1-singletonE add.left-neutral}$ 
  by  $\text{metis}$ 
hence
   $a \in A' \text{ and}$ 
   $\text{above } r' \text{ } a = \{a\}$ 
  using  $\text{lin-ord-r connex-imp-refl above-refl lin-ord-imp-connex refl-on-domain}$ 
  unfolding  $\text{above-def}$ 
  by  $(\text{blast, fast})$ 
thus  $\exists a' \in A'. \text{above } r' \text{ } a' = \{a'\}$ 
  by  $\text{metis}$ 
next
case  $(\text{Suc } n)$ 
fix
   $A' :: 'a \text{ set and}$ 
   $r' :: 'a \text{ Preference-Relation}$ 
assume
   $\text{lin-ord-r: linear-order-on } A' \text{ } r' \text{ and}$ 
   $\text{fin-A: finite } A' \text{ and}$ 
   $\text{A-not-empty: } A' \neq \{\}$  and
   $\text{len-A-n-plus-one: } \text{Suc } n + 1 = \text{card } A'$ 
then obtain  $B :: 'a \text{ set where}$ 
   $\text{subset-B-card: } \text{card } B = n + 1 \wedge B \subseteq A'$ 
  using  $\text{Suc-inject add-Suc card.insert-remove finite.cases insert-Diff-single}$ 
   $\text{subset-insertI}$ 
  by  $(\text{metis (mono-tags, lifting)})$ 
then obtain  $a :: 'a \text{ where}$ 
   $a: A' - B = \{a\}$ 
using  $\text{Suc-eq-plus1 add-diff-cancel-left' fin-A len-A-n-plus-one card-1-singletonE}$ 
   $\text{card-Diff-subset finite-subset}$ 
  by  $\text{metis}$ 
have  $\exists a' \in B. \text{above } (\text{limit } B \text{ } r') \text{ } a' = \{a'\}$ 
using  $\text{subset-B-card Suc.IH add-diff-cancel-left' lin-ord-r card-eq-0-iff diff-le-self}$ 
   $\text{leD lessI limit-presv-lin-ord}$ 
  unfolding  $\text{One-nat-def}$ 
  by  $\text{metis}$ 
then obtain  $b :: 'a \text{ where}$ 
   $\text{alt-b: above } (\text{limit } B \text{ } r') \text{ } b = \{b\}$ 
  by  $\text{blast}$ 
hence  $b\text{-above: } \{a'. (b, a') \in \text{limit } B \text{ } r'\} = \{b\}$ 
  unfolding  $\text{above-def}$ 
  by  $\text{metis}$ 
hence  $b\text{-pref-b: } b \preceq_{r'} b$ 
  using  $\text{CollectD limit-rel-presv-prefs singletonI}$ 

```

by (*metis* (*lifting*))  
 show  $\exists a' \in A'. \text{above } r' a' = \{a'\}$   
 proof (*cases*)  
 assume *a-pref-r-b*:  $a \preceq_{r'} b$   
 have *refl-A*:  
 $\forall A'' r'' a' a''. \text{refl-on } A'' r'' \wedge (a' :: 'a, a'') \in r'' \longrightarrow a' \in A'' \wedge a'' \in A''$   
 using *refl-on-domain*  
 by *metis*  
 have  $\forall A'' r''. \text{linear-order-on } (A'' :: 'a \text{ set}) r'' \longrightarrow \text{connex } A'' r''$   
 by (*simp add: lin-ord-imp-connex*)  
 hence *refl-A'*: *refl-on*  $A' r'$   
 using *connex-imp-refl lin-ord-r*  
 by *metis*  
 hence  $a \in A' \wedge b \in A'$   
 using *refl-on-domain a-pref-r-b*  
 by *simp*  
 hence *b-in-r*:  $\forall a'. a' \in A' \longrightarrow b = a' \vee (b, a') \in r' \vee (a', b) \in r'$   
 using *lin-ord-r*  
 unfolding *linear-order-on-def total-on-def*  
 by *metis*  
 have *b-in-lim-B-r*:  $(b, b) \in \text{limit } B r'$   
 using *alt-b mem-Collect-eq singletonI*  
 unfolding *above-def*  
 by *metis*  
 have *b-wins*:  $\{a'. (b, a') \in \text{limit } B r'\} = \{b\}$   
 using *alt-b*  
 unfolding *above-def*  
 by (*metis* (*no-types*))  
 have *b-refl*:  $(b, b) \in \{(a', a''). (a', a'') \in r' \wedge a' \in B \wedge a'' \in B\}$   
 using *b-in-lim-B-r*  
 by *simp*  
 moreover have *b-wins-B*:  $\forall b' \in B. b \in \text{above } r' b'$   
 using *subset-B-card b-in-r b-wins b-refl CollectI Product-Type.Collect-case-prodD*  
 unfolding *above-def*  
 by *fastforce*  
 moreover have  $b \in \text{above } r' a$   
 using *a-pref-r-b pref-imp-in-above*  
 by *metis*  
 ultimately have *b-wins*:  $\forall a' \in A'. b \in \text{above } r' a'$   
 using *Diff-iff a empty-iff insert-iff*  
 by (*metis* (*no-types*))  
 hence  $\forall a' \in A'. a' \in \text{above } r' b \longrightarrow a' = b$   
 using *CollectD lin-ord-r lin-imp-antisym*  
 unfolding *above-def antisym-def*  
 by *metis*  
 hence  $\forall a' \in A'. (a' \in \text{above } r' b) = (a' = b)$   
 using *b-wins*  
 by *blast*

**moreover have** *above-b-in-A*:  $\text{above } r' \ b \subseteq A'$   
**unfolding** *above-def*  
**using** *refl-A' refl-A*  
**by** *auto*  
**ultimately have**  $\text{above } r' \ b = \{b\}$   
**using** *alt-b*  
**unfolding** *above-def*  
**by** *fastforce*  
**thus** *?thesis*  
**using** *above-b-in-A*  
**by** *blast*  
**next**  
**assume**  $\neg a \preceq_{r'} b$   
**hence**  $b \preceq_{r'} a$   
**using** *subset-B-card DiffE a lin-ord-r alt-b limit-to-limits limited-dest*  
*singletonI subset-iff lin-ord-imp-connex pref-imp-in-above*  
**unfolding** *connex-def*  
**by** *metis*  
**hence** *b-smaller-a*:  $(b, a) \in r'$   
**by** *simp*  
**have** *lin-ord-subset-A*:  
 $\forall B' B'' r''. \text{linear-order-on } (B'' :: 'a \text{ set}) \ r'' \wedge B' \subseteq B''$   
 $\longrightarrow \text{linear-order-on } B' \ (\text{limit } B' \ r'')$   
**using** *limit-presv-lin-ord*  
**by** *metis*  
**have**  $\{a'. (b, a') \in \text{limit } B \ r'\} = \{b\}$   
**using** *alt-b*  
**unfolding** *above-def*  
**by** *metis*  
**hence** *b-in-B*:  $b \in B$   
**by** *auto*  
**have** *limit-B*:  $\text{partial-order-on } B \ (\text{limit } B \ r') \wedge \text{total-on } B \ (\text{limit } B \ r')$   
**using** *lin-ord-subset-A subset-B-card lin-ord-r*  
**unfolding** *linear-order-on-def*  
**by** *metis*  
**have**  
 $\forall A'' r''. \text{total-on } A'' \ r'' =$   
 $(\forall a'. (a' :: 'a) \notin A''$   
 $\vee (\forall a''. a'' \notin A'' \vee a' = a'' \vee (a', a'') \in r'' \vee (a'', a') \in r''))$   
**unfolding** *total-on-def*  
**by** *metis*  
**hence**  
 $\forall a' a''. a' \in B \longrightarrow a'' \in B$   
 $\longrightarrow a' = a'' \vee (a', a'') \in \text{limit } B \ r' \vee (a'', a') \in \text{limit } B \ r'$   
**using** *limit-B*  
**by** *simp*

hence  $\forall a' \in B. b \in \text{above } r' a'$   
 using *limit-rel-presv-prefs pref-imp-in-above singletonD mem-Collect-eq*  
*lin-ord-r alt-b b-above b-pref-b subset-B-card b-in-B*  
 by (*metis (lifting)*)  
 hence  $\forall a' \in B. a' \preceq_{r'} b$   
 unfolding *above-def*  
 by *simp*  
 hence *b-wins*:  $\forall a' \in B. (a', b) \in r'$   
 by *simp*  
 have *trans*  $r'$   
 using *lin-ord-r lin-imp-trans*  
 by *metis*  
 hence  $\forall a' \in B. (a', a) \in r'$   
 using *transE b-smaller-a b-wins*  
 by *metis*  
 hence  $\forall a' \in B. a' \preceq_{r'} a$   
 by *simp*  
 hence *nothing-above-a*:  $\forall a' \in A'. a' \preceq_{r'} a$   
 using *a lin-ord-r lin-ord-imp-connex above-connex Diff-iff empty-iff insert-iff*  
*pref-imp-in-above*  
 by *metis*  
 have  $\forall a' \in A'. (a' \in \text{above } r' a) = (a' = a)$   
 using *lin-ord-r lin-imp-antisym nothing-above-a pref-imp-in-above CollectD*  
 unfolding *antisym-def above-def*  
 by *metis*  
 moreover have *above-a-in-A*:  $\text{above } r' a \subseteq A'$   
 using *lin-ord-r connex-imp-refl lin-ord-imp-connex mem-Collect-eq refl-on-domain*  
 unfolding *above-def*  
 by *fastforce*  
 ultimately have  $\text{above } r' a = \{a\}$   
 using *a*  
 unfolding *above-def*  
 by *blast*  
 thus ?thesis  
 using *above-a-in-A*  
 by *blast*  
 qed  
 qed  
 hence  $\exists a \in A. \text{above } r a = \{a\}$   
 using *fin-A non-empty-A lin-ord-r len-n-plus-one*  
 by *blast*  
 thus ?thesis  
 using *assms lin-ord-imp-connex pref-imp-in-above singletonD*  
 unfolding *connex-def*  
 by *metis*  
 qed  
 lemma *above-one-eq*:  
 fixes

```

  A :: 'a set and
  r :: 'a Preference-Relation and
  a b :: 'a
assumes
  lin-ord: linear-order-on A r and
  fin-A: finite A and
  not-empty-A: A ≠ {} and
  above-a: above r a = {a} and
  above-b: above r b = {b}
shows a = b
proof -
  have
    a ≼r a and
    b ≼r b
  using above-a above-b singletonI pref-imp-in-above
  by (metis, metis)
moreover have
  ∃ a' ∈ A. above r a' = {a'} ∧ (∀ a'' ∈ A. above r a'' = {a''} ⟶ a'' = a')
  using lin-ord fin-A not-empty-A
  by (simp add: above-one)
moreover have connex A r
  using lin-ord
  by (simp add: lin-ord-imp-connex)
ultimately show a = b
  using above-a above-b limited-dest
  unfolding connex-def
  by metis
qed

lemma above-one-imp-rank-one:
  fixes
    r :: 'a Preference-Relation and
    a :: 'a
  assumes above r a = {a}
  shows rank r a = 1
  using assms
  by simp

lemma rank-one-imp-above-one:
  fixes
    A :: 'a set and
    r :: 'a Preference-Relation and
    a :: 'a
  assumes
    lin-ord: linear-order-on A r and
    rank-one: rank r a = 1
  shows above r a = {a}
proof -
  from lin-ord

```

```

have refl-on A r
  using linear-order-on-def partial-order-onD
  by blast
moreover from assms
have a ∈ A
  unfolding rank.simps above-def linear-order-on-def partial-order-on-def
    preorder-on-def total-on-def
  using card-1-singletonE insertI1 mem-Collect-eq refl-onD1
  by metis
ultimately have a ∈ above r a
  using above-refl
  by fastforce
with rank-one
show above r a = {a}
  using card-1-singletonE rank.simps singletonD
  by metis
qed

```

```

theorem above-rank:
  fixes
    A :: 'a set and
    r :: 'a Preference-Relation and
    a :: 'a
  assumes linear-order-on A r
  shows (above r a = {a}) = (rank r a = 1)
  using assms above-one-imp-rank-one rank-one-imp-above-one
  by metis

```

```

lemma rank-unique:
  fixes
    A :: 'a set and
    r :: 'a Preference-Relation and
    a b :: 'a
  assumes
    lin-ord: linear-order-on A r and
    fin-A: finite A and
    a-in-A: a ∈ A and
    b-in-A: b ∈ A and
    a-neq-b: a ≠ b
  shows rank r a ≠ rank r b
proof (unfold rank.simps above-def, clarify)
  assume card-eq: card {a'. (a, a') ∈ r} = card {a'. (b, a') ∈ r}
  have refl-r: refl-on A r
  using lin-ord
  by (simp add: lin-ord-imp-connex connex-imp-refl)
  hence rel-refl-b: (b, b) ∈ r
  using b-in-A
  unfolding refl-on-def
  by (metis (no-types))

```



```

have rel-refl-a:  $(a, a) \in r$ 
  using a-in-A refl-r refl-onD
  by (metis (full-types))
obtain p :: 'a  $\Rightarrow$  bool where
  rel-b:  $\forall y. p\ y = ((b, y) \in r)$ 
  using is-less-preferred-than.simps
  by metis
hence finite (Collect p)
  using refl-r refl-on-domain fin-A rev-finite-subset mem-Collect-eq subsetI
  by metis
hence finite  $\{a'. (b, a') \in r\}$ 
  using rel-b
  by (simp add: Collect-mono rev-finite-subset)
moreover from this
have finite  $\{a'. (a, a') \in r\}$ 
  using card-eq card-gt-0-iff rel-refl-b
  by force
moreover have trans r
  using lin-ord lin-imp-trans
  by metis
moreover have  $(a, b) \in r \vee (b, a) \in r$ 
  using lin-ord a-in-A b-in-A a-neq-b
  unfolding linear-order-on-def total-on-def
  by metis
ultimately have sets-eq:  $\{a'. (a, a') \in r\} = \{a'. (b, a') \in r\}$ 
  using card-eq above-trans card-seteq order-refl
  unfolding above-def
  by metis
hence  $(b, a) \in r$ 
  using rel-refl-a sets-eq
  by blast
hence  $(a, b) \notin r$ 
  using lin-ord lin-imp-antisym a-neq-b antisymD
  by metis
thus False
  using lin-ord partial-order-onD sets-eq b-in-A
  unfolding linear-order-on-def refl-on-def
  by blast
qed

```

```

lemma above-presv-limit:
  fixes
    A :: 'a set and
    r :: 'a Preference-Relation and
    a :: 'a
  shows above (limit A r) a  $\subseteq$  A
  unfolding above-def
  by auto

```

### 1.2.5 Lifting Property

**definition** *equiv-rel-except-a* :: 'a set  $\Rightarrow$  'a Preference-Relation  $\Rightarrow$  'a Preference-Relation  $\Rightarrow$  bool **where**  
*equiv-rel-except-a* A r r' a  $\equiv$   
 linear-order-on A r  $\wedge$  linear-order-on A r'  $\wedge$  a  $\in$  A  $\wedge$   
 $(\forall a' \in A - \{a\}. \forall b' \in A - \{a\}. (a' \preceq_r b') = (a' \preceq_{r'} b'))$

**definition** *lifted* :: 'a set  $\Rightarrow$  'a Preference-Relation  $\Rightarrow$  'a Preference-Relation  $\Rightarrow$  bool **where**  
*lifted* A r r' a  $\equiv$   
*equiv-rel-except-a* A r r' a  $\wedge$   $(\exists a' \in A - \{a\}. a \preceq_r a' \wedge a' \preceq_{r'} a)$

**lemma** *trivial-equiv-rel*:

**fixes**

A :: 'a set **and**

r :: 'a Preference-Relation

**assumes** linear-order-on A r

**shows**  $\forall a \in A. \text{equiv-rel-except-a } A \ r \ r \ a$

**unfolding** *equiv-rel-except-a-def*

**using** *assms*

**by** *simp*

**lemma** *lifted-imp-equiv-rel-except-a*:

**fixes**

A :: 'a set **and**

r r' :: 'a Preference-Relation **and**

a :: 'a

**assumes** *lifted* A r r' a

**shows** *equiv-rel-except-a* A r r' a

**using** *assms*

**unfolding** *lifted-def* *equiv-rel-except-a-def*

**by** *simp*

**lemma** *lifted-imp-switched*:

**fixes**

A :: 'a set **and**

r r' :: 'a Preference-Relation **and**

a :: 'a

**assumes** *lifted* A r r' a

**shows**  $\forall a' \in A - \{a\}. \neg (a' \preceq_r a \wedge a \preceq_{r'} a')$

**proof** (*safe*)

**fix** b :: 'a

**assume**

b  $\preceq_r$  a **and**

a  $\preceq_{r'}$  b

**hence**

a-pref-b-rel: (a, b)  $\in$  r' **and**

b-pref-a-rel: (b, a)  $\in$  r

**by** *simp-all*

```

have antisym r
  using assms lifted-imp-equiv-rel-except-a lin-imp-antisym
  unfolding equiv-rel-except-a-def
  by metis
hence imp-b-eq-a:  $(b, a) \in r \longrightarrow (a, b) \in r \longrightarrow b = a$ 
  unfolding antisym-def
  by simp
have  $\exists a' \in A - \{a\}. a \preceq_r a' \wedge a' \preceq_{r'} a$ 
  using assms
  unfolding lifted-def
  by metis
then obtain c :: 'a where
   $c \in A - \{a\} \wedge a \preceq_r c \wedge c \preceq_{r'} a$ 
  by metis
hence c-eq-r-s-exc-a:  $c \in A - \{a\} \wedge (a, c) \in r \wedge (c, a) \in r'$ 
  by simp
have equiv-r-s-exc-a: equiv-rel-except-a A r r' a
  using assms
  unfolding lifted-def
  by metis
hence  $\forall a' \in A - \{a\}. \forall b' \in A - \{a\}. ((a', b') \in r) = ((a', b') \in r')$ 
  unfolding equiv-rel-except-a-def
  by simp
moreover have  $\forall a' b' c'. (a', b') \in r \longrightarrow (b', c') \in r \longrightarrow (a', c') \in r$ 
  using equiv-r-s-exc-a
  unfolding equiv-rel-except-a-def linear-order-on-def partial-order-on-def
    preorder-on-def trans-def
  by metis
moreover assume
   $b \in A$  and
   $b \neq a$ 
ultimately have  $(b, c) \in r'$ 
  using b-pref-a-rel c-eq-r-s-exc-a equiv-r-s-exc-a
    insertE insert-Diff
  unfolding equiv-rel-except-a-def
  by metis
hence  $(a, c) \in r'$ 
  using a-pref-b-rel equiv-r-s-exc-a
    lin-imp-trans transE
  unfolding equiv-rel-except-a-def
  by metis
thus False
  using c-eq-r-s-exc-a equiv-r-s-exc-a antisymD DiffD2 lin-imp-antisym singletonI
  unfolding equiv-rel-except-a-def
  by metis
qed

lemma lifted-mono:
  fixes

```

```

  A :: 'a set and
  r r' :: 'a Preference-Relation and
  a a' :: 'a
assumes
  lifted: lifted A r r' a and
  a'-pref-a: a'  $\preceq_r$  a
shows a'  $\preceq_{r'}$  a
proof (unfold is-less-preferred-than.simps)
  have a'-pref-a-rel: (a', a)  $\in$  r
    using a'-pref-a
  by simp
  hence a'-in-A: a'  $\in$  A
    using lifted connex-imp-refl lin-ord-imp-connex refl-on-domain
  unfolding equiv-rel-except-a-def lifted-def
  by metis
  have rest-eq:  $\forall b \in A - \{a\}. \forall b' \in A - \{a\}. ((b, b') \in r) = ((b, b') \in r')$ 
    using lifted
  unfolding lifted-def equiv-rel-except-a-def
  by simp
  have ex-lifted:  $\exists b \in A - \{a\}. (a, b) \in r \wedge (b, a) \in r'$ 
    using lifted
  unfolding lifted-def
  by simp
  show (a', a)  $\in$  r'
  proof (cases a' = a)
    case True
    thus ?thesis
      using connex-imp-refl refl-onD lifted lin-ord-imp-connex
      unfolding equiv-rel-except-a-def lifted-def
      by metis
  next
    case False
    thus ?thesis
      using a'-pref-a-rel a'-in-A rest-eq ex-lifted insertE insert-Diff
      lifted lin-imp-trans lifted-imp-equiv-rel-except-a
      unfolding equiv-rel-except-a-def trans-def
      by metis
  qed
qed

lemma lifted-above-subset:
  fixes
    A :: 'a set and
    r r' :: 'a Preference-Relation and
    a :: 'a
  assumes lifted A r r' a
  shows above r' a  $\subseteq$  above r a
proof (unfold above-def, safe)
  fix a' :: 'a

```

```

assume a-pref-x:  $(a, a') \in r'$ 
from assms
have lifted-r:  $\exists b \in A - \{a\}. (a, b) \in r \wedge (b, a) \in r'$ 
  unfolding lifted-def
  by simp
from assms
have rest-eq:  $\forall b \in A - \{a\}. \forall b' \in A - \{a\}. ((b, b') \in r) = ((b, b') \in r')$ 
  unfolding lifted-def equiv-rel-except-a-def
  by simp
from assms
have trans-r:  $\forall b c d. (b, c) \in r \longrightarrow (c, d) \in r \longrightarrow (b, d) \in r$ 
  using lin-imp-trans
  unfolding trans-def lifted-def equiv-rel-except-a-def
  by metis
from assms
have trans-s:  $\forall b c d. (b, c) \in r' \longrightarrow (c, d) \in r' \longrightarrow (b, d) \in r'$ 
  using lin-imp-trans
  unfolding trans-def lifted-def equiv-rel-except-a-def
  by metis
from assms
have refl-r:  $(a, a) \in r$ 
  using connex-imp-refl lin-ord-imp-connex refl-onD
  unfolding equiv-rel-except-a-def lifted-def
  by metis
from a-pref-x assms
have  $a' \in A$ 
  using connex-imp-refl lin-ord-imp-connex refl-onD2
  unfolding equiv-rel-except-a-def lifted-def
  by metis
with a-pref-x lifted-r rest-eq trans-r trans-s refl-r
show  $(a, a') \in r$ 
  using Diff-iff singletonD
  by (metis (full-types))
qed

```

**lemma** *lifted-above-mono*:

```

fixes
   $A :: 'a \text{ set}$  and
   $r \ r' :: 'a \text{ Preference-Relation}$  and
   $a \ a' :: 'a$ 
assumes
  lifted-a:  $\text{lifted } A \ r \ r' \ a$  and
  a'-in-A-sub-a:  $a' \in A - \{a\}$ 
shows  $\text{above } r \ a' \subseteq \text{above } r' \ a' \cup \{a\}$ 
proof (safe)
fix  $b :: 'a$ 
assume
  b-in-above-r:  $b \in \text{above } r \ a'$  and
  b-not-in-above-s:  $b \notin \text{above } r' \ a'$ 

```

**have**  $\forall b' \in A - \{a\}. (b' \in \text{above } r \ a') = (b' \in \text{above } r' \ a')$   
**using** *a'-in-A-sub-a lifted-a*  
**unfolding** *lifted-def equiv-rel-except-a-def above-def*  
**by** *simp*  
**thus**  $b = a$   
**using** *lifted-a b-not-in-above-s limited-dest lin-ord-imp-connex*  
*member-remove pref-imp-in-above b-in-above-r*  
**unfolding** *lifted-def equiv-rel-except-a-def remove-def connex-def*  
**by** *metis*  
**qed**

**lemma** *limit-lifted-imp-eq-or-lifted*:  
**fixes**  
 $A \ A' :: 'a \text{ set}$  **and**  
 $r \ r' :: 'a \text{ Preference-Relation}$  **and**  
 $a :: 'a$   
**assumes**  
*lifted: lifted  $A' \ r \ r' \ a$  and*  
*subset:  $A \subseteq A'$*   
**shows**  $\text{limit } A \ r = \text{limit } A \ r' \vee \text{lifted } A \ (\text{limit } A \ r) \ (\text{limit } A \ r') \ a$   
**proof** –  
**have**  $\forall a' \in A - \{a\}. \forall b' \in A - \{a\}. (a' \preceq_r b') = (a' \preceq_{r'} b')$   
**using** *lifted subset*  
**unfolding** *lifted-def equiv-rel-except-a-def*  
**by** *auto*  
**hence** *eql-rs*:  
 $\forall a' \in A - \{a\}. \forall b' \in A - \{a\}. ((a', b') \in (\text{limit } A \ r)) = ((a', b') \in (\text{limit } A \ r'))$   
**using** *DiffD1 limit-presv-prefs limit-rel-presv-prefs*  
**by** *simp*  
**have** *lin-ord-r-s: linear-order-on  $A \ (\text{limit } A \ r) \wedge \text{linear-order-on } A \ (\text{limit } A \ r')$*   
**using** *lifted subset lifted-def equiv-rel-except-a-def limit-presv-lin-ord*  
**by** *metis*  
**show** *?thesis*  
**proof** (*cases*)  
**assume** *a-in-A:  $a \in A$*   
**thus** *?thesis*  
**proof** (*cases*)  
**assume**  $\exists a' \in A - \{a\}. a \preceq_r a' \wedge a' \preceq_{r'} a$   
**thus** *?thesis*  
**using** *DiffD1 limit-presv-prefs a-in-A eql-rs lin-ord-r-s*  
**unfolding** *lifted-def equiv-rel-except-a-def*  
**by** *simp*  
**next**  
**assume**  $\neg (\exists a' \in A - \{a\}. a \preceq_r a' \wedge a' \preceq_{r'} a)$   
**hence** *strict-pref-to-a:  $\forall a' \in A - \{a\}. \neg (a \preceq_r a' \wedge a' \preceq_{r'} a)$*   
**by** *simp*  
**moreover** **have** *not-worse:  $\forall a' \in A - \{a\}. \neg (a' \preceq_r a \wedge a \preceq_{r'} a')$*   
**using** *lifted subset lifted-imp-switched*

by *fastforce*  
**moreover have** *connex*:  $\text{connex } A \ (\text{limit } A \ r) \wedge \text{connex } A \ (\text{limit } A \ r')$   
 using *lifted subset limit-presv-lin-ord lin-ord-imp-connex*  
 unfolding *lifted-def equiv-rel-except-a-def*  
 by *metis*  
**moreover have**  
 $\forall A'' \ r''. \text{connex } A'' \ r'' =$   
 $(\text{limited } A'' \ r''$   
 $\wedge (\forall b \ b'. (b :: 'a) \in A'' \longrightarrow b' \in A'' \longrightarrow (b \preceq_{r''} b' \vee b' \preceq_{r''} b)))$   
 unfolding *connex-def*  
 by (*simp add: Ball-def-raw*)  
**hence limit-rel-r**:  
 $\text{limited } A \ (\text{limit } A \ r)$   
 $\wedge (\forall b \ b'. b \in A \wedge b' \in A \longrightarrow (b, b') \in \text{limit } A \ r \vee (b', b) \in \text{limit } A \ r)$   
 using *connex*  
 by *simp*  
**have limit-imp-rel**:  $\forall b \ b' \ A'' \ r''. (b :: 'a, b') \in \text{limit } A'' \ r'' \longrightarrow b \preceq_{r''} b'$   
 using *limit-rel-presv-prefs*  
 by *metis*  
**have limit-rel-s**:  
 $\text{limited } A \ (\text{limit } A \ r')$   
 $\wedge (\forall b \ b'. b \in A \wedge b' \in A \longrightarrow (b, b') \in \text{limit } A \ r' \vee (b', b) \in \text{limit } A \ r')$   
 using *connex*  
 unfolding *connex-def*  
 by *simp*  
**ultimately have**  
 $\forall a' \in A - \{a\}. a \preceq_r a' \wedge a \preceq_{r'} a' \vee a' \preceq_r a \wedge a' \preceq_{r'} a$   
 using *DiffD1 limit-rel-r limit-rel-presv-prefs a-in-A*  
 by *metis*  
**have**  $\forall a' \in A - \{a\}. ((a, a') \in (\text{limit } A \ r)) = ((a, a') \in (\text{limit } A \ r'))$   
 using *DiffD1 limit-imp-rel limit-rel-r limit-rel-s a-in-A*  
*strict-pref-to-a not-worse*  
 by *metis*  
**hence**  
 $\forall a' \in A - \{a\}.$   
 $(\text{let } q = \text{limit } A \ r \text{ in } a \preceq_q a') = (\text{let } q = \text{limit } A \ r' \text{ in } a \preceq_q a')$   
 by *simp*  
**moreover have**  
 $\forall a' \in A - \{a\}. ((a', a) \in (\text{limit } A \ r)) = ((a', a) \in (\text{limit } A \ r'))$   
 using *a-in-A strict-pref-to-a not-worse DiffD1 limit-rel-presv-prefs*  
*limit-rel-s limit-rel-r*  
 by *metis*  
**moreover have**  $(a, a) \in (\text{limit } A \ r) \wedge (a, a) \in (\text{limit } A \ r')$   
 using *a-in-A connex connex-imp-refl refl-onD*  
 by *metis*  
**ultimately show** *?thesis*  
 using *eql-rs*  
 by *auto*  
**qed**

```

next
  assume  $a \notin A$ 
  thus ?thesis
    using limit-to-limits limited-dest subrelI subset-antisym eql-rs
    by auto
qed
qed

lemma negl-diff-imp-eq-limit:
  fixes
     $A A' :: 'a \text{ set}$  and
     $r r' :: 'a \text{ Preference-Relation}$  and
     $a :: 'a$ 
  assumes
    change: equiv-rel-except-a  $A' r r' a$  and
    subset:  $A \subseteq A'$  and
    not-in-A:  $a \notin A$ 
  shows limit  $A r = \text{limit } A r'$ 
proof -
  have  $A \subseteq A' - \{a\}$ 
  unfolding subset-Diff-insert
  using not-in-A subset
  by simp
  hence  $\forall b \in A. \forall b' \in A. (b \preceq_r b') = (b \preceq_{r'} b')$ 
  using change in-mono
  unfolding equiv-rel-except-a-def
  by metis
  thus ?thesis
  by auto
qed

theorem lifted-above-winner-alts:
  fixes
     $A :: 'a \text{ set}$  and
     $r r' :: 'a \text{ Preference-Relation}$  and
     $a a' :: 'a$ 
  assumes
    lifted-a: lifted  $A r r' a$  and
    a'-above-a': above  $r a' = \{a'\}$  and
    fin-A: finite  $A$ 
  shows above  $r' a' = \{a'\} \vee \text{above } r' a = \{a\}$ 
proof (cases)
  assume  $a = a'$ 
  thus ?thesis
    using above-subset-geq-one lifted-a a'-above-a' lifted-above-subset
    unfolding lifted-def equiv-rel-except-a-def
    by metis
next
  assume a-neq-a':  $a \neq a'$ 

```



```

thus ?thesis
proof (cases)
  assume above  $r'$   $a' = \{a'\}$ 
  thus ?thesis
  by simp
next
  assume  $a'$ -not-above- $a'$ : above  $r'$   $a' \neq \{a'\}$ 
  have  $\forall a'' \in A. a'' \preceq_r a'$ 
  proof (safe)
    fix  $b :: 'a$ 
    assume  $y$ -in- $A$ :  $b \in A$ 
    hence  $A \neq \{\}$ 
    by blast
    moreover have linear-order-on  $A$   $r$ 
    using lifted-a
    unfolding equiv-rel-except-a-def lifted-def
    by simp
    ultimately show  $b \preceq_r a'$ 
    using  $y$ -in- $A$   $a'$ -above- $a'$  lin-ord-imp-connex pref-imp-in-above
      singletonD limited-dest singletonI
    unfolding connex-def
    by (metis (no-types))
  qed
  moreover have equiv-rel-except-a  $A$   $r$   $r'$   $a$ 
  using lifted-a
  unfolding lifted-def
  by metis
  moreover have  $a' \in A - \{a\}$ 
  using  $a$ -neq- $a'$  calculation member-remove
    limited-dest lin-ord-imp-connex
  using equiv-rel-except-a-def remove-def connex-def
  by metis
  ultimately have  $\forall a'' \in A - \{a\}. a'' \preceq_r a'$ 
  using DiffD1 lifted-a
  unfolding equiv-rel-except-a-def
  by metis
  hence  $\forall a'' \in A - \{a\}. \text{above } r' a'' \neq \{a''\}$ 
  using  $a'$ -not-above- $a'$  empty-iff insert-iff pref-imp-in-above
  by metis
  hence above  $r'$   $a = \{a\}$ 
  using Diff-iff all-not-in-conv lifted-a above-one singleton-iff fin-A
  unfolding lifted-def equiv-rel-except-a-def
  by metis
  thus above  $r'$   $a' = \{a'\} \vee \text{above } r' a = \{a\}$ 
  by simp
qed
qed

```

**theorem** lifted-above-winner-single:

```

fixes
   $A :: 'a \text{ set}$  and
   $r \ r' :: 'a \text{ Preference-Relation}$  and
   $a :: 'a$ 
assumes
   $\text{lifted } A \ r \ r' \ a$  and
   $\text{above } r \ a = \{a\}$  and
   $\text{finite } A$ 
shows  $\text{above } r' \ a = \{a\}$ 
using assms lifted-above-winner-alts
by metis

theorem lifted-above-winner-other:
fixes
   $A :: 'a \text{ set}$  and
   $r \ r' :: 'a \text{ Preference-Relation}$  and
   $a \ a' :: 'a$ 
assumes
   $\text{lifted-}a$ :  $\text{lifted } A \ r \ r' \ a$  and
   $a'\text{-above-}a'$ :  $\text{above } r' \ a' = \{a'\}$  and
   $\text{fin-}A$ :  $\text{finite } A$  and
   $a\text{-not-}a'$ :  $a \neq a'$ 
shows  $\text{above } r \ a' = \{a'\}$ 
proof (rule ccontr)
assume  $\text{not-above-}x$ :  $\text{above } r \ a' \neq \{a'\}$ 
then obtain  $b :: 'a$  where
   $b\text{-above-}b$ :  $\text{above } r \ b = \{b\}$ 
using lifted-}a \text{ fin-}A \text{ insert-Diff insert-not-empty above-one}
unfolding lifted-def equiv-rel-except-a-def
by metis
hence  $\text{above } r' \ b = \{b\} \vee \text{above } r' \ a = \{a\}$ 
using lifted-}a \text{ fin-}A \text{ lifted-above-winner-alts}
by metis
moreover have  $\forall \ a''. \text{above } r' \ a'' = \{a''\} \longrightarrow a'' = a'$ 
using all-not-in-conv lifted-}a \ a'\text{-above-}a' \text{ fin-}A \text{ above-one-eq}
unfolding lifted-def equiv-rel-except-a-def
by metis
ultimately have  $b = a'$ 
using a-not-}a'
by presburger
moreover have  $b \neq a'$ 
using not-above-}x \ b\text{-above-}b
by blast
ultimately show False
by simp
qed

end

```

## 1.3 Norm

```

theory Norm
  imports HOL-Library.Extended-Real
           HOL-Combinatorics.List-Permutation
           Auxiliary-Lemmas
begin

```

A norm on  $R$  to  $n$  is a mapping  $N: R \mapsto n$  on  $R$  that has the following properties for all mappings  $u$  (and  $v$ ) in  $R$  to  $n$ :

- positive scalability:  $N(a * u) = |a| * N(u)$  for all  $a$  in  $R$ .
- positive semidefiniteness:  $N(u) \geq 0$  with  $N(u) = 0$  if and only if  $u = (0, 0, \dots, 0)$ .
- triangle inequality:  $N(u + v) \leq N(u) + N(v)$ .

### 1.3.1 Definition

```

type-synonym Norm = ereal list  $\Rightarrow$  ereal

```

```

definition norm :: Norm  $\Rightarrow$  bool where
  norm n  $\equiv \forall x :: \text{ereal list}. n\ x \geq 0 \wedge (\forall i < \text{length } x. x[i] = 0 \longrightarrow n\ x = 0)$ 

```

### 1.3.2 Auxiliary Lemmas

```

lemma sum-over-image-of-bijection:
  fixes
    A :: 'a set and
    A' :: 'b set and
    f :: 'a  $\Rightarrow$  'b and
    g :: 'a  $\Rightarrow$  ereal
  assumes bij-betw f A A'
  shows  $(\sum a \in A. g\ a) = (\sum a' \in A'. g\ (\text{the-inv-into } A\ f\ a'))$ 
  using assms
proof (induction card A arbitrary: A A')
  case 0
  thus ?case
    using bij-betw-same-card card-0-eq sum.empty sum.infinite
    by metis
next
  case (Suc x)
  fix
    A :: 'a set and
    A' :: 'b set and

```

```

  x :: nat
assume
  suc-x: Suc x = card A and
  bij-A-A': bij-betw f A A'
hence card-A'-from-x: card A' = Suc x
  using bij-betw-same-card
  by metis
have x-lt-card-A: x < card A
  using suc-x
  by presburger
obtain a :: 'a where
  a-in-A: a ∈ A
  using suc-x card-eq-SucD insertI1
  by metis
hence a-compl-A: insert a (A - {a}) = A
  using insert-absorb
  by simp
hence
  inj-on-A: inj-on f A and
  img-of-A: A' = f ` A
  using bij-A-A'
  unfolding bij-betw-def
  by (simp, simp)
hence inj-on f (insert a A)
  using a-compl-A
  by simp
hence A'-sub-fa: A' - {f a} = f ` (A - {a})
  using img-of-A
  by blast
hence bij-without-a: bij-betw f (A - {a}) (A' - {f a})
  using inj-on-A a-compl-A inj-on-insert
  unfolding bij-betw-def
  by (metis (no-types))
moreover have card-without-a: card (A - {a}) = x
  using suc-x a-in-A
  by simp
ultimately have card-A'-sub-f-eq-x: card (A' - {f a}) = x
  using bij-betw-same-card
  by metis
have (∑ a ∈ A. g a) = (∑ a ∈ A - {a}. g a) + g a
  using x-lt-card-A add.commute card-Diff1-less-iff card-without-a
    insert-Diff insert-Diff-single sum.insert-remove
  by (metis (no-types))
also have ... = (∑ a' ∈ A' - {f a}. g (the-inv-into A f a'))
  + g (the-inv-into A f (f a))
  using bij-without-a a-in-A bij-A-A' bij-betw-imp-inj-on the-inv-into-f-f
    A'-sub-fa DiffD1 sum.reindex-cong
  by (metis (mono-tags, lifting))
finally show (∑ a ∈ A. g a) = (∑ a' ∈ A'. g (the-inv-into A f a'))

```

using *add.commute card-Diff1-less-iff insert-Diff insert-Diff-single lessI*  
       *sum.insert-remove card-A'-from-x card-A'-sub-f-eq-x*  
 by *metis*  
 qed

### 1.3.3 Common Norms

**fun** *l-one* :: *Norm* **where**  
   *l-one* *x* = ( $\sum$  *i* < length *x*. |*x*!*i*|)

### 1.3.4 Properties

**definition** *symmetry* :: *Norm*  $\Rightarrow$  *bool* **where**  
   *symmetry* *n*  $\equiv \forall$  *x y*. *x* < $\sim\sim$ > *y*  $\longrightarrow$  *n* *x* = *n* *y*

### 1.3.5 Theorems

**theorem** *l-one-is-sym*: *symmetry* *l-one*  
**proof** (*unfold symmetry-def, safe*)  
   **fix** *l l'* :: *ereal list*  
   **assume** *perm*: *l* < $\sim\sim$ > *l'*  
   **then obtain**  $\pi$  :: *nat*  $\Rightarrow$  *nat*  
     **where**  
       *perm* $_{\pi}$ :  $\pi$  *permutes* {..*length* *l*} **and**  
       *l* $_{\pi}$ : *permute-list*  $\pi$  *l* = *l'*  
       **using** *mset-eq-permutation*  
       **by** *metis*  
   **hence** ( $\sum$  *i* < length *l*. |*l'*!*i*|) = ( $\sum$  *i* < length *l*. |*l*!( $\pi$  *i*)|)  
     **using** *permute-list-nth*  
     **by** *fastforce*  
   **also have** ... = ( $\sum$  *i* = 0 ..< length *l*. |*l*!( $\pi$  *i*)|)  
     **using** *lessThan-atLeast0*  
     **by** *presburger*  
   **also have** ( $\lambda$  *i*. |*l*!( $\pi$  *i*)|) = (( $\lambda$  *i*. |*l*!*i*|)  $\circ$   $\pi$ )  
     **by** *fastforce*  
   **also have** ( $\sum$  *y* = 0 ..< length *l*. (( $\lambda$  *i*. |*l*!*i*|)  $\circ$   $\pi$ ) *y*) =  
     ( $\sum$  *i* = 0 ..< length *l*. |*l*!*i*|)  
     **using** *perm $_{\pi}$  atLeast-upt set-upt sum.permute*  
     **by** *metis*  
   **also have** ... = ( $\sum$  *i* < length *l*. |*l*!*i*|)  
     **using** *atLeast0LessThan*  
     **by** *presburger*  
   **finally have** ( $\sum$  *i* < length *l*. |*l'*!*i*|) = ( $\sum$  *i* < length *l*. |*l*!*i*|)  
     **by** *metis*  
   **moreover have** length *l* = length *l'*  
     **using** *perm perm-length*  
     **by** *metis*  
   **ultimately show** *l-one* *l* = *l-one* *l'*  
     **using** *l-one.elims*  
     **by** *metis*

qed

end

## 1.4 Electoral Result

```
theory Result
  imports Main
begin
```

An electoral result is the principal result type of the composable modules voting framework, as it is a generalization of the set of winning alternatives from social choice functions. Electoral results are selections of the received (possibly empty) set of alternatives into the three disjoint groups of elected, rejected and deferred alternatives. Any of those sets, e.g., the set of winning (elected) alternatives, may also be left empty, as long as they collectively still hold all the received alternatives.

### 1.4.1 Auxiliary Functions

```
type-synonym 'r Result = 'r set * 'r set * 'r set
```

A partition of a set A are pairwise disjoint sets that "set equals partition" A. For this specific predicate, we have three disjoint sets in a triple.

```
fun disjoint3 :: 'r Result  $\Rightarrow$  bool where
  disjoint3 (e, r, d) =
    ((e  $\cap$  r = {})  $\wedge$ 
     (e  $\cap$  d = {})  $\wedge$ 
     (r  $\cap$  d = {}))
```

```
fun set-equals-partition :: 'r set  $\Rightarrow$  'r Result  $\Rightarrow$  bool where
  set-equals-partition X (e, r, d) = (e  $\cup$  r  $\cup$  d = X)
```

### 1.4.2 Definition

A result generally is related to the alternative set A (of type 'a). A result should be well-formed on the alternatives. Also it should be possible to limit a well-formed result to a subset of the alternatives.

Specific result types like social choice results (sets of alternatives) can be realized via sublocales of the result locale.

```
locale result =
  fixes
```

```

    well-formed :: 'a set  $\Rightarrow$  ('r Result)  $\Rightarrow$  bool and
    limit :: 'a set  $\Rightarrow$  'r set  $\Rightarrow$  'r set
assumes  $\forall$  (A :: 'a set) (r :: 'r Result).
    (set-equals-partition (limit A UNIV) r  $\wedge$  disjoint3 r)  $\longrightarrow$  well-formed A r

These three functions return the elect, reject, or defer set of a result.

fun (in result) limitR :: 'a set  $\Rightarrow$  'r Result  $\Rightarrow$  'r Result where
    limitR A (e, r, d) = (limit A e, limit A r, limit A d)

abbreviation elect-r :: 'r Result  $\Rightarrow$  'r set where
    elect-r r  $\equiv$  fst r

abbreviation reject-r :: 'r Result  $\Rightarrow$  'r set where
    reject-r r  $\equiv$  fst (snd r)

abbreviation defer-r :: 'r Result  $\Rightarrow$  'r set where
    defer-r r  $\equiv$  snd (snd r)

end

```

## 1.5 Preference Profile

```

theory Profile
imports Preference-Relation
    Auxiliary-Lemmas
    HOL-Library.Extended-Nat
    HOL-Combinatorics.Permutations
begin

```

Preference profiles denote the decisions made by the individual voters on the eligible alternatives. They are represented in the form of one preference relation (e.g., selected on a ballot) per voter, collectively captured in a mapping of voters onto their respective preference relations. If there are finitely many voters, they can be enumerated and the mapping can be interpreted as a list of preference relations. Unlike the common preference profiles in the social-choice sense, the profiles described here consider only the (sub-)set of alternatives that are received.

### 1.5.1 Definition

A profile contains one ballot for each voter. An election consists of a set of participating voters, a set of eligible alternatives, and a corresponding

profile.

**type-synonym**  $(\text{'a}, \text{'v}) \text{ Profile} = \text{'v} \Rightarrow (\text{'a} \text{ Preference-Relation})$

**type-synonym**  $(\text{'a}, \text{'v}) \text{ Election} = \text{'a set} \times \text{'v set} \times (\text{'a}, \text{'v}) \text{ Profile}$

**fun**  $\text{alternatives-}\mathcal{E} :: (\text{'a}, \text{'v}) \text{ Election} \Rightarrow \text{'a set}$  **where**  
 $\text{alternatives-}\mathcal{E} E = \text{fst } E$

**fun**  $\text{voters-}\mathcal{E} :: (\text{'a}, \text{'v}) \text{ Election} \Rightarrow \text{'v set}$  **where**  
 $\text{voters-}\mathcal{E} E = \text{fst } (\text{snd } E)$

**fun**  $\text{profile-}\mathcal{E} :: (\text{'a}, \text{'v}) \text{ Election} \Rightarrow (\text{'a}, \text{'v}) \text{ Profile}$  **where**  
 $\text{profile-}\mathcal{E} E = \text{snd } (\text{snd } E)$

**fun**  $\text{election-equality} :: (\text{'a}, \text{'v}) \text{ Election} \Rightarrow (\text{'a}, \text{'v}) \text{ Election} \Rightarrow \text{bool}$  **where**  
 $\text{election-equality } (A, V, p) (A', V', p') =$   
 $(A = A' \wedge V = V' \wedge (\forall v \in V. p v = p' v))$

A profile on a set of alternatives A and a voter set V consists of ballots that are linear orders on A for all voters in V. A finite profile is one with finitely many alternatives and voters.

**definition**  $\text{profile} :: \text{'v set} \Rightarrow \text{'a set} \Rightarrow (\text{'a}, \text{'v}) \text{ Profile} \Rightarrow \text{bool}$  **where**  
 $\text{profile } V A p \equiv \forall v \in V. \text{linear-order-on } A (p v)$

**abbreviation**  $\text{finite-profile} :: \text{'v set} \Rightarrow \text{'a set} \Rightarrow (\text{'a}, \text{'v}) \text{ Profile} \Rightarrow \text{bool}$  **where**  
 $\text{finite-profile } V A p \equiv \text{finite } A \wedge \text{finite } V \wedge \text{profile } V A p$

**abbreviation**  $\text{finite-election} :: (\text{'a}, \text{'v}) \text{ Election} \Rightarrow \text{bool}$  **where**  
 $\text{finite-election } E \equiv \text{finite-profile } (\text{voters-}\mathcal{E} E) (\text{alternatives-}\mathcal{E} E) (\text{profile-}\mathcal{E} E)$

**abbreviation**  $\text{finite-}\mathcal{V}\text{-election} :: (\text{'a}, \text{'v}) \text{ Election} \Rightarrow \text{bool}$  **where**  
 $\text{finite-}\mathcal{V}\text{-election } E \equiv \text{finite } (\text{voters-}\mathcal{E} E)$

**abbreviation**  $\text{well-formed-election} :: (\text{'a}, \text{'v}) \text{ Election} \Rightarrow \text{bool}$  **where**  
 $\text{well-formed-election } E \equiv \text{profile } (\text{voters-}\mathcal{E} E) (\text{alternatives-}\mathcal{E} E) (\text{profile-}\mathcal{E} E)$

**definition**  $\text{finite-}\mathcal{V}\text{-elections} :: (\text{'a}, \text{'v}) \text{ Election set}$  **where**  
 $\text{finite-}\mathcal{V}\text{-elections} \equiv \{E :: (\text{'a}, \text{'v}) \text{ Election}. \text{finite-}\mathcal{V}\text{-election } E\}$

**definition**  $\text{finite-elections} :: (\text{'a}, \text{'v}) \text{ Election set}$  **where**  
 $\text{finite-elections} \equiv \{E :: (\text{'a}, \text{'v}) \text{ Election}. \text{finite-election } E\}$

**definition**  $\text{well-formed-elections} :: (\text{'a}, \text{'v}) \text{ Election set}$  **where**  
 $\text{well-formed-elections} \equiv \{E :: (\text{'a}, \text{'v}) \text{ Election}. \text{well-formed-election } E\}$

**definition**  $\text{well-formed-finite-}\mathcal{V}\text{-elections} :: (\text{'a}, \text{'v}) \text{ Election set}$  **where**  
 $\text{well-formed-finite-}\mathcal{V}\text{-elections} \equiv$   
 $\{E :: (\text{'a}, \text{'v}) \text{ Election}. \text{finite-}\mathcal{V}\text{-election } E \wedge \text{well-formed-election } E\}$



**lemma** *well-formed-and-finite- $\mathcal{V}$ -elections*:  
*well-formed-finite- $\mathcal{V}$ -elections* = *well-formed-elections*  $\cap$  *finite- $\mathcal{V}$ -elections*  
**unfolding** *finite- $\mathcal{V}$ -elections-def* *well-formed-elections-def*  
*well-formed-finite- $\mathcal{V}$ -elections-def*  
**using** *Collect-conj-eq* *Int-commute*  
**by** *metis*

— This function subsumes elections with fixed alternatives, finite voters, and a default value for the profile value on non-voters.

**fun** *elections- $\mathcal{A}$*  :: '*a* set  $\Rightarrow$  ('*a*, '*v*) Election set **where**  
*elections- $\mathcal{A}$*  *A* =  
*well-formed-elections*  
 $\cap \{E. \text{alternatives-}\mathcal{E} \ E = A \wedge \text{finite} (\text{voters-}\mathcal{E} \ E)$   
 $\wedge (\forall \ v. v \notin \text{voters-}\mathcal{E} \ E \longrightarrow \text{profile-}\mathcal{E} \ E \ v = \{\})\}$

— Here, we count the occurrences of a ballot in an election, i.e., how many voters specifically chose that exact ballot.

**fun** *vote-count* :: '*a* Preference-Relation  $\Rightarrow$  ('*a*, '*v*) Election  $\Rightarrow$  nat **where**  
*vote-count* *p* *E* = *card*  $\{v \in (\text{voters-}\mathcal{E} \ E). (\text{profile-}\mathcal{E} \ E) \ v = p\}$

### 1.5.2 Vote Count

**lemma** *vote-count-sum*:  
**fixes** *E* :: ('*a*, '*v*) Election  
**assumes**  
*fin-voters*: *finite* (*voters- $\mathcal{E}$*  *E*) **and**  
*fin-UNIV*: *finite* (*UNIV* :: ('*a*  $\times$  '*a*) set)  
**shows** ( $\sum \ p \in \text{UNIV}. \text{vote-count } p \ E$ ) = *card* (*voters- $\mathcal{E}$*  *E*)  
**proof** (*unfold* *vote-count.simps*)  
**have**  $\forall \ p. \text{finite} \{v \in \text{voters-}\mathcal{E} \ E. \text{profile-}\mathcal{E} \ E \ v = p\}$   
**using** *fin-voters*  
**by** *force*  
**moreover** **have** *disjoint*  $\{\{v \in \text{voters-}\mathcal{E} \ E. \text{profile-}\mathcal{E} \ E \ v = p\} \mid p. p \in \text{UNIV}\}$   
**unfolding** *disjoint-def*  
**by** *blast*  
**moreover** **have** *partition-voters*:  
*voters- $\mathcal{E}$*  *E* =  $\bigcup \ \{\{v \in \text{voters-}\mathcal{E} \ E. \text{profile-}\mathcal{E} \ E \ v = p\} \mid p. p \in \text{UNIV}\}$   
**using** *Union-eq*  
**by** *blast*  
**ultimately** **have** *card-eq-sum'*:  
*card* (*voters- $\mathcal{E}$*  *E*) =  
 $\text{sum } \text{card} \ \{\{v \in \text{voters-}\mathcal{E} \ E. \text{profile-}\mathcal{E} \ E \ v = p\} \mid p. p \in \text{UNIV}\}$   
**using** *card-Union-disjoint*[*of*  
 $\{\{v \in \text{voters-}\mathcal{E} \ E. \text{profile-}\mathcal{E} \ E \ v = p\} \mid p. p \in \text{UNIV}\}$ ]  
**by** *auto*  
**have** *finite*  $\{\{v \in \text{voters-}\mathcal{E} \ E. \text{profile-}\mathcal{E} \ E \ v = p\} \mid p. p \in \text{UNIV}\}$   
**using** *partition-voters fin-voters*  
**by** (*simp* *add: finite-UnionD*)  
**moreover** **have**

$\{\{v \in \text{voters-}\mathcal{E} \ E. \text{profile-}\mathcal{E} \ E \ v = p\} \mid p. p \in \text{UNIV}\} =$   
 $\{\{v \in \text{voters-}\mathcal{E} \ E. \text{profile-}\mathcal{E} \ E \ v = p\}$   
 $\mid p. p \in \text{UNIV} \wedge \{v \in \text{voters-}\mathcal{E} \ E. \text{profile-}\mathcal{E} \ E \ v = p\} \neq \{\}\}$   
 $\cup \{\{v \in \text{voters-}\mathcal{E} \ E. \text{profile-}\mathcal{E} \ E \ v = p\}$   
 $\mid p. p \in \text{UNIV} \wedge \{v \in \text{voters-}\mathcal{E} \ E. \text{profile-}\mathcal{E} \ E \ v = p\} = \{\}\}$   
**by** *blast*  
**moreover have**  
 $\{\} =$   
 $\{\{v \in \text{voters-}\mathcal{E} \ E. \text{profile-}\mathcal{E} \ E \ v = p\}$   
 $\mid p. p \in \text{UNIV} \wedge \{v \in \text{voters-}\mathcal{E} \ E. \text{profile-}\mathcal{E} \ E \ v = p\} \neq \{\}\}$   
 $\cap \{\{v \in \text{voters-}\mathcal{E} \ E. \text{profile-}\mathcal{E} \ E \ v = p\}$   
 $\mid p. p \in \text{UNIV} \wedge \{v \in \text{voters-}\mathcal{E} \ E. \text{profile-}\mathcal{E} \ E \ v = p\} = \{\}\}$   
**by** *blast*  
**ultimately have**  
 $\text{sum card } \{\{v \in \text{voters-}\mathcal{E} \ E. \text{profile-}\mathcal{E} \ E \ v = p\} \mid p. p \in \text{UNIV}\} =$   
 $\text{sum card } \{\{v \in \text{voters-}\mathcal{E} \ E. \text{profile-}\mathcal{E} \ E \ v = p\}$   
 $\mid p. p \in \text{UNIV} \wedge \{v \in \text{voters-}\mathcal{E} \ E. \text{profile-}\mathcal{E} \ E \ v = p\} \neq \{\}\}$   
 $+ \text{sum card } \{\{v \in \text{voters-}\mathcal{E} \ E. \text{profile-}\mathcal{E} \ E \ v = p\}$   
 $\mid p. p \in \text{UNIV} \wedge \{v \in \text{voters-}\mathcal{E} \ E. \text{profile-}\mathcal{E} \ E \ v = p\} = \{\}\}$   
**using** *sum.union-disjoint[of*  
 $\{\{v \in \text{voters-}\mathcal{E} \ E. \text{profile-}\mathcal{E} \ E \ v = p\}$   
 $\mid p. p \in \text{UNIV} \wedge \{v \in \text{voters-}\mathcal{E} \ E. \text{profile-}\mathcal{E} \ E \ v = p\} \neq \{\}\}$   
 $\{\{v \in \text{voters-}\mathcal{E} \ E. \text{profile-}\mathcal{E} \ E \ v = p\}$   
 $\mid p. p \in \text{UNIV} \wedge \{v \in \text{voters-}\mathcal{E} \ E. \text{profile-}\mathcal{E} \ E \ v = p\} = \{\}\}$   
**by** *simp*  
**moreover have**  
 $\forall X \in \{\{v \in \text{voters-}\mathcal{E} \ E. \text{profile-}\mathcal{E} \ E \ v = p\}$   
 $\mid p. p \in \text{UNIV} \wedge \{v \in \text{voters-}\mathcal{E} \ E. \text{profile-}\mathcal{E} \ E \ v = p\} = \{\}\}.$   
 $\text{card } X = 0$   
**using** *card-eq-0-iff*  
**by** *fastforce*  
**ultimately have** *card-eq-sum*:  
 $\text{card } (\text{voters-}\mathcal{E} \ E) =$   
 $\text{sum card } \{\{v \in \text{voters-}\mathcal{E} \ E. \text{profile-}\mathcal{E} \ E \ v = p\}$   
 $\mid p. p \in \text{UNIV} \wedge \{v \in \text{voters-}\mathcal{E} \ E. \text{profile-}\mathcal{E} \ E \ v = p\} \neq \{\}\}$   
**using** *card-eq-sum'*  
**by** *simp*  
**have**  
 $\text{inj-on } (\lambda p. \{v \in \text{voters-}\mathcal{E} \ E. \text{profile-}\mathcal{E} \ E \ v = p\})$   
 $\{p. \{v \in \text{voters-}\mathcal{E} \ E. \text{profile-}\mathcal{E} \ E \ v = p\} \neq \{\}\}$   
**unfolding** *inj-on-def*  
**by** *blast*  
**moreover have**  
 $(\lambda p. \{v \in \text{voters-}\mathcal{E} \ E. \text{profile-}\mathcal{E} \ E \ v = p\})$   
 $\quad \quad \quad \{p. \{v \in \text{voters-}\mathcal{E} \ E. \text{profile-}\mathcal{E} \ E \ v = p\} \neq \{\}\}$   
 $\subseteq \{\{v \in \text{voters-}\mathcal{E} \ E. \text{profile-}\mathcal{E} \ E \ v = p\}$   
 $\mid p. p \in \text{UNIV} \wedge \{v \in \text{voters-}\mathcal{E} \ E. \text{profile-}\mathcal{E} \ E \ v = p\} \neq \{\}\}$   
**by** *blast*  
**moreover have**

$(\lambda p. \{v \in \text{voters-}\mathcal{E} \ E. \text{profile-}\mathcal{E} \ E \ v = p\})$   
 $\quad \{p. \{v \in \text{voters-}\mathcal{E} \ E. \text{profile-}\mathcal{E} \ E \ v = p\} \neq \{\}\}$   
 $\supseteq \{\{v \in \text{voters-}\mathcal{E} \ E. \text{profile-}\mathcal{E} \ E \ v = p\}$   
 $\quad | p. p \in \text{UNIV} \wedge \{v \in \text{voters-}\mathcal{E} \ E. \text{profile-}\mathcal{E} \ E \ v = p\} \neq \{\}\}$   
**by** *blast*  
**ultimately have**  
 $\text{bij-betw } (\lambda p. \{v \in \text{voters-}\mathcal{E} \ E. \text{profile-}\mathcal{E} \ E \ v = p\})$   
 $\quad \{p. \{v \in \text{voters-}\mathcal{E} \ E. \text{profile-}\mathcal{E} \ E \ v = p\} \neq \{\}$   
 $\quad \{v \in \text{voters-}\mathcal{E} \ E. \text{profile-}\mathcal{E} \ E \ v = p\}$   
 $\quad | p. p \in \text{UNIV} \wedge \{v \in \text{voters-}\mathcal{E} \ E. \text{profile-}\mathcal{E} \ E \ v = p\} \neq \{\}$   
**unfolding** *bij-betw-def*  
**by** *simp*  
**hence** *sum-rewrite*:  
 $(\sum x \in \{p. \{v \in \text{voters-}\mathcal{E} \ E. \text{profile-}\mathcal{E} \ E \ v = p\} \neq \{\}\}.$   
 $\quad \text{card } \{v \in \text{voters-}\mathcal{E} \ E. \text{profile-}\mathcal{E} \ E \ v = x\}) =$   
 $\quad \text{sum card } \{\{v \in \text{voters-}\mathcal{E} \ E. \text{profile-}\mathcal{E} \ E \ v = p\}$   
 $\quad | p. p \in \text{UNIV} \wedge \{v \in \text{voters-}\mathcal{E} \ E. \text{profile-}\mathcal{E} \ E \ v = p\} \neq \{\}\}$   
**using** *sum-comp[of*  
 $\quad \lambda p. \{v \in \text{voters-}\mathcal{E} \ E. \text{profile-}\mathcal{E} \ E \ v = p\} \text{ - - card}]$   
**unfolding** *comp-def*  
**by** *simp*  
**have**  $\{p. \{v \in \text{voters-}\mathcal{E} \ E. \text{profile-}\mathcal{E} \ E \ v = p\} = \{\}$   
 $\quad \cap \{p. \{v \in \text{voters-}\mathcal{E} \ E. \text{profile-}\mathcal{E} \ E \ v = p\} \neq \{\}\} = \{\}$   
**by** *blast*  
**moreover have**  
 $\{p. \{v \in \text{voters-}\mathcal{E} \ E. \text{profile-}\mathcal{E} \ E \ v = p\} = \{\}$   
 $\quad \cup \{p. \{v \in \text{voters-}\mathcal{E} \ E. \text{profile-}\mathcal{E} \ E \ v = p\} \neq \{\}\} = \text{UNIV}$   
**by** *blast*  
**ultimately have**  
 $(\sum p \in \text{UNIV}. \text{card } \{v \in \text{voters-}\mathcal{E} \ E. \text{profile-}\mathcal{E} \ E \ v = p\}) =$   
 $(\sum x \in \{p. \{v \in \text{voters-}\mathcal{E} \ E. \text{profile-}\mathcal{E} \ E \ v = p\} \neq \{\}\}.$   
 $\quad \text{card } \{v \in \text{voters-}\mathcal{E} \ E. \text{profile-}\mathcal{E} \ E \ v = x\})$   
 $+ (\sum x \in \{p. \{v \in \text{voters-}\mathcal{E} \ E. \text{profile-}\mathcal{E} \ E \ v = p\} = \{\}\}.$   
 $\quad \text{card } \{v \in \text{voters-}\mathcal{E} \ E. \text{profile-}\mathcal{E} \ E \ v = x\})$   
**using** *sum.union-disjoint[of*  
 $\quad \{p. \{v \in \text{voters-}\mathcal{E} \ E. \text{profile-}\mathcal{E} \ E \ v = p\} = \{\}$   
 $\quad \{p. \{v \in \text{voters-}\mathcal{E} \ E. \text{profile-}\mathcal{E} \ E \ v = p\} \neq \{\}\}$   
 $\quad \text{Finite-Set.finite-set add.commute finite-Un fin-UNIV}$   
**by** (*metis (mono-tags, lifting)*)  
**moreover have**  
 $\forall x \in \{p. \{v \in \text{voters-}\mathcal{E} \ E. \text{profile-}\mathcal{E} \ E \ v = p\} = \{\}\}.$   
 $\quad \text{card } \{v \in \text{voters-}\mathcal{E} \ E. \text{profile-}\mathcal{E} \ E \ v = x\} = 0$   
**using** *card-eq-0-iff*  
**by** *fastforce*  
**ultimately show**  
 $(\sum p \in \text{UNIV}. \text{card } \{v \in \text{voters-}\mathcal{E} \ E. \text{profile-}\mathcal{E} \ E \ v = p\}) =$   
 $\quad \text{card } (\text{voters-}\mathcal{E} \ E)$   
**using** *card-eq-sum sum-rewrite*  
**by** *simp*

qed

### 1.5.3 Voter Permutations

A common action of interest on elections is renaming the voters, e.g., when talking about anonymity.

**fun** *rename* :: ( $'v \Rightarrow 'v$ )  $\Rightarrow$  ( $'a, 'v$ ) *Election*  $\Rightarrow$  ( $'a, 'v$ ) *Election* **where**  
*rename*  $\pi$  ( $A, V, p$ ) = ( $A, \pi \text{ ` } V, p \circ (\text{the-inv } \pi)$ )

**lemma** *rename-sound*:

**fixes**

$A :: 'a \text{ set}$  **and**

$V :: 'v \text{ set}$  **and**

$p :: ('a, 'v) \text{ Profile}$  **and**

$\pi :: 'v \Rightarrow 'v$

**assumes**

*prof*: *profile*  $V A p$  **and**

*renamed*: ( $A, V', q$ ) = *rename*  $\pi$  ( $A, V, p$ ) **and**

*bij-perm*: *bij*  $\pi$

**shows** *profile*  $V' A q$

**proof** (*unfold profile-def, safe*)

**fix**  $v' :: 'v$

**assume**  $v' \in V'$

**moreover have**  $V' = \pi \text{ ` } V$

**using** *renamed*

**by** *simp*

**ultimately have** ( $(\text{the-inv } \pi) v'$ )  $\in V$

**using** *UNIV-I bij-perm bij-is-inj bij-is-surj*

*f-the-inv-into-f inj-image-mem-iff*

**by** *metis*

**thus** *linear-order-on*  $A (q v')$

**using** *renamed bij-perm prof*

**unfolding** *profile-def*

**by** *simp*

qed

**lemma** *rename-prof*:

**fixes**

$A :: 'a \text{ set}$  **and**

$V :: 'v \text{ set}$  **and**

$p :: ('a, 'v) \text{ Profile}$  **and**

$\pi :: 'v \Rightarrow 'v$

**assumes**

*profile*  $V A p$  **and**

( $A, V', q$ ) = *rename*  $\pi$  ( $A, V, p$ ) **and**

*bij*  $\pi$

**shows** *profile*  $V' A q$

**using** *assms rename-sound*

**by** *metis*

**lemma** *rename-finite*:

**fixes**

$A :: 'a \text{ set}$  **and**

$V :: 'v \text{ set}$  **and**

$p :: ('a, 'v) \text{ Profile}$  **and**

$\pi :: 'v \Rightarrow 'v$

**assumes**

*finite*  $V$  **and**

$(A, V', q) = \text{rename } \pi (A, V, p)$  **and**

*bij*  $\pi$

**shows** *finite*  $V'$

**using** *assms*

**by** *simp*

**lemma** *rename-inv*:

**fixes**

$\pi :: 'v \Rightarrow 'v$  **and**

$A :: 'a \text{ set}$  **and**

$V :: 'v \text{ set}$  **and**

$p :: ('a, 'v) \text{ Profile}$

**assumes** *bij*  $\pi$

**shows**  $\text{rename } \pi (\text{rename } (\text{the-inv } \pi) (A, V, p)) = (A, V, p)$

**proof** –

**have**  $\text{rename } \pi (\text{rename } (\text{the-inv } \pi) (A, V, p)) =$

$(A, \pi \text{ ` } (\text{the-inv } \pi) \text{ ` } V, p \circ (\text{the-inv } (\text{the-inv } \pi)) \circ (\text{the-inv } \pi))$

**by** *simp*

**moreover have**  $\pi \text{ ` } (\text{the-inv } \pi) \text{ ` } V = V$

**using** *assms*

**by** (*simp add: f-the-inv-into-f-bij-betw image-comp*)

**moreover have**  $(\text{the-inv } (\text{the-inv } \pi)) = \pi$

**using** *assms surj-def inj-on-the-inv-into surj-imp-inv-eq the-inv-f-f*

**unfolding** *bij-betw-def*

**by** (*metis (mono-tags, opaque-lifting)*)

**moreover have**  $\pi \circ (\text{the-inv } \pi) = \text{id}$

**using** *assms f-the-inv-into-f-bij-betw*

**by** *fastforce*

**ultimately show**  $\text{rename } \pi (\text{rename } (\text{the-inv } \pi) (A, V, p)) = (A, V, p)$

**by** (*simp add: rewriteR-comp-comp*)

**qed**

**lemma** *rename-inj*:

**fixes**  $\pi :: 'v \Rightarrow 'v$

**assumes** *bij*  $\pi$

**shows** *inj* ( $\text{rename } \pi$ )

**proof** (*unfold inj-def split-paired-All rename.simps, safe*)

**fix**

$A A' :: 'a \text{ set}$  **and**

$V V' :: 'v \text{ set}$  **and**

```

  p p' :: ('a, 'v) Profile and
  v :: 'v
assume
  p ∘ the-inv π = p' ∘ the-inv π and
  π ' V = π ' V'
thus
  v ∈ V ⇒ v ∈ V' and
  v ∈ V' ⇒ v ∈ V and
  p = p'
using assms
by (metis bij-betw-imp-inj-on inj-image-eq-iff,
      metis bij-betw-imp-inj-on inj-image-eq-iff,
      metis bij-betw-the-inv-into bij-is-surj surj-fun-eq)
qed

lemma rename-surj:
  fixes π :: 'v ⇒ 'v
  assumes bij π
  shows
    rename π ' well-formed-elections = well-formed-elections and
    rename π ' finite-elections = finite-elections
proof (safe)
  fix
    A A' :: 'a set and
    V V' :: 'v set and
    p p' :: ('a, 'v) Profile
  assume wf: (A, V, p) ∈ well-formed-elections
  hence rename (the-inv π) (A, V, p) ∈ well-formed-elections
    using assms bij-betw-the-inv-into rename-sound
    unfolding well-formed-elections-def
    by fastforce
  thus (A, V, p) ∈ rename π ' well-formed-elections
    using assms image-eqI rename-inv
    by metis
  assume (A', V', p') = rename π (A, V, p)
  thus (A', V', p') ∈ well-formed-elections
    using rename-sound wf assms
    unfolding well-formed-elections-def
    by fastforce
next
  fix
    A A' :: 'b set and
    V V' :: 'v set and
    p p' :: ('b, 'v) Profile
  assume finite: (A, V, p) ∈ finite-elections
  hence rename (the-inv π) (A, V, p) ∈ finite-elections
    using assms bij-betw-the-inv-into rename-prof rename-finite
    unfolding finite-elections-def
    by fastforce

```

```

thus (A, V, p) ∈ rename π ‘ finite-elections
using assms image-eqI rename-inv
by metis
assume (A', V', p') = rename π (A, V, p)
thus (A', V', p') ∈ finite-elections
using rename-sound finite assms
unfolding finite-elections-def
by fastforce
qed

```

#### 1.5.4 List Representation

A profile on a voter set that has a natural order can be viewed as a list of ballots.

```

fun to-list :: 'v :: linorder set ⇒ ('a, 'v) Profile ⇒
    ('a Preference-Relation) list where
  to-list V p = (if finite V
    then map p (sorted-list-of-set V)
    else [])

```

**lemma** map-helper:

```

fixes
  f :: 'x ⇒ 'y ⇒ 'z and
  g :: 'x ⇒ 'x and
  h :: 'y ⇒ 'y and
  l :: 'x list and
  l' :: 'y list
shows map2 f (map g l) (map h l') = map2 (λ x y. f (g x) (h y)) l l'
proof –
have map2 f (map g l) (map h l') =
    map (λ (x, y). f x y) (map (λ (x, y). (g x, h y)) (zip l l'))
using zip-map-map
by metis
thus ?thesis
by force
qed

```

**lemma** to-list-simp:

```

fixes
  i :: nat and
  V :: 'v :: linorder set and
  p :: ('a, 'v) Profile
assumes i < card V
shows (to-list V p)!i = p ((sorted-list-of-set V)!i)
using assms
by force

```

**lemma** to-list-comp:

```

fixes

```

```

    V :: 'v :: linorder set and
    p :: ('a, 'v) Profile and
    f :: 'a rel  $\Rightarrow$  'a rel
  shows to-list V (f  $\circ$  p) = map f (to-list V p)
  by simp

lemma set-card-upper-bound:
  fixes
    i :: nat and
    V :: nat set
  assumes
    fin-V: finite V and
    bound-v:  $\forall v \in V. v < i$ 
  shows card V  $\leq i$ 
proof (cases V = {})
  case True
  thus ?thesis
  by simp
next
  case False
  hence Max V  $\in V$ 
  using fin-V
  by simp
  thus ?thesis
  using assms Suc-leI card-le-Suc-Max order-trans
  by metis
qed

lemma sorted-list-of-set-nth-equals-card:
  fixes
    V :: 'v :: linorder set and
    x :: 'v
  assumes
    fin-V: finite V and
    x-V: x  $\in V$ 
  shows sorted-list-of-set V!(card {v  $\in V. v < x$ }) = x
proof -
  let ?c = card {v  $\in V. v < x$ } and
    ?set = {v  $\in V. v < x$ }
  have  $\forall v \in V. \exists n. n < \text{card } V \wedge (\text{sorted-list-of-set } V!n) = v$ 
  using length-sorted-list-of-set sorted-list-of-set-unique in-set-conv-nth fin-V
  by metis
  then obtain  $\varphi :: 'v \Rightarrow \text{nat}$  where
    index- $\varphi$ :  $\forall v \in V. \varphi v < \text{card } V \wedge (\text{sorted-list-of-set } V!(\varphi v)) = v$ 
  by metis
  —  $\varphi x = ?c$ , i.e.,  $\varphi x \geq ?c$  and  $\varphi x \leq ?c$ 
  let ?i =  $\varphi x$ 
  have inj- $\varphi$ : inj-on  $\varphi$  V
  using inj-onI index- $\varphi$ 

```



by *metis*  
**have**  $\forall v \in V. \forall v' \in V. v < v' \longrightarrow \varphi v < \varphi v'$   
 using *leD linorder-le-less-linear sorted-list-of-set-unique*  
       *sorted-sorted-list-of-set sorted-nth-mono fin-V index-φ*  
 by *metis*  
**hence**  $\forall j \in \{\varphi v \mid v. v \in ?set\}. j < ?i$   
 using *x-V*  
 by *blast*  
**moreover have** *fin-img: finite ?set*  
 using *fin-V*  
 by *simp*  
**ultimately have**  $?i \geq \text{card } \{\varphi v \mid v. v \in ?set\}$   
 using *set-card-upper-bound*  
 by *simp*  
**hence** *geg: ?c ≤ ?i*  
 using *inj-φ*  
 by (*simp add: card-image inj-on-subset setcompr-eq-image*)  
**have** *sorted-φ:*  
    $\forall i < \text{card } V. \forall j < \text{card } V. i < j$   
      $\longrightarrow (\text{sorted-list-of-set } V!i) < (\text{sorted-list-of-set } V!j)$   
 by (*simp add: sorted-wrt-nth-less*)  
**have** *leq: ?i ≤ ?c*  
**proof** (*rule ccontr, cases ?c < card V*)  
   case *True*  
   let  $?A = \lambda j. \{\text{sorted-list-of-set } V!j\}$   
   assume  $\neg ?i \leq ?c$   
   **hence**  $?c < ?i$   
   by *simp*  
   **hence**  $\forall j \leq ?c. \text{sorted-list-of-set } V!j \in V \wedge \text{sorted-list-of-set } V!j < x$   
   using *sorted-φ geg index-φ x-V fin-V set-sorted-list-of-set*  
       *length-sorted-list-of-set nth-mem order.strict-trans1*  
   by (*metis (mono-tags, lifting)*)  
   **hence**  $\{\text{sorted-list-of-set } V!j \mid j. j \leq ?c\} \subseteq \{v \in V. v < x\}$   
   by *blast*  
   **also have**  $\{\text{sorted-list-of-set } V!j \mid j. j \leq ?c\} =$   
      $\{\text{sorted-list-of-set } V!j \mid j. j \in \{0 ..< (?c + 1)\}\}$   
   using *add commute*  
   by *auto*  
   **also have**  $\dots = (\bigcup j \in \{0 ..< (?c + 1)\}. \{\text{sorted-list-of-set } V!j\})$   
   by *blast*  
   **finally have** *subset:*  $(\bigcup j \in \{0 ..< (?c + 1)\}. ?A j) \subseteq \{v \in V. v < x\}$   
   by *simp*  
   **have**  $\forall i \leq ?c. \forall j \leq ?c.$   
      $i \neq j \longrightarrow \text{sorted-list-of-set } V!i \neq \text{sorted-list-of-set } V!j$   
   using *True*  
   by (*simp add: nth-eq-iff-index-eq*)  
   **hence**  $\forall i \in \{0 ..< (?c + 1)\}. \forall j \in \{0 ..< (?c + 1)\}.$   
      $(i \neq j \longrightarrow \{\text{sorted-list-of-set } V!i\} \cap \{\text{sorted-list-of-set } V!j\} = \{\})$   
   by *fastforce*

```

hence disjoint-family-on ?A {0 ..< (?c + 1)}
  unfolding disjoint-family-on-def
  by simp
moreover have  $\forall j \in \{0 \dots (?c + 1)\}. \text{card } (?A\ j) = 1$ 
  by simp
ultimately have
   $\text{card } (\bigcup j \in \{0 \dots (?c + 1)\}. ?A\ j) = (\sum j \in \{0 \dots (?c + 1)\}. 1)$ 
  using card-UN-disjoint'
  by fastforce
hence  $\text{card } (\bigcup j \in \{0 \dots (?c + 1)\}. ?A\ j) = ?c + 1$ 
  by simp
hence  $?c + 1 \leq ?c$ 
  using subset card-mono fin-img
  by (metis (no-types, lifting))
thus False
  by simp
next
case False
thus False
  using x-V index-φ geq order-le-less-trans
  by blast
qed
thus ?thesis
  using geq leq x-V index-φ
  by simp
qed

lemma to-list-permutes-under-bij:
  fixes
    π :: 'v :: linorder ⇒ 'v and
    V :: 'v set and
    p :: ('a, 'v) Profile
  assumes bij π
  shows
    let φ = λ i. card {v ∈ π ' V. v < π ((sorted-list-of-set V)!i)}
    in (to-list V p) = permute-list φ (to-list (π ' V) (λ x. p (the-inv π x)))
proof (cases finite V)
case False
  — If V is infinite, both lists are empty.
  hence to-list V p = []
    by simp
  moreover have infinite (π ' V)
    using False assms bij-betw-finite bij-betw-subset top-greatest
    by metis
  hence to-list (π ' V) (λ x. p (the-inv π x)) = []
    by simp
  ultimately show ?thesis
    by simp
next

```

**case** *True*  
**let**  
     $?q = \lambda x. p \text{ (the-inv } \pi x) \text{ and}$   
     $?img = \pi \text{ ' } V \text{ and}$   
     $?n = \text{length (to-list } V p) \text{ and}$   
     $?perm = \lambda i. \text{card } \{v \in \pi \text{ ' } V. v < \pi ((\text{sorted-list-of-set } V)!i)\}$   
    — These are auxiliary statements equating everything with  $?n$ .  
**have** *card-eq*:  $\text{card } ?img = \text{card } V$   
    **using** *assms bij-betw-same-card bij-betw-subset top-greatest*  
    **by** *metis*  
**also have** *card-length-V*:  $?n = \dots$   
    **by** *simp*  
**also have** *card-length-img*:  $\text{length (to-list } ?img ?q) = \text{card } ?img$   
    **using** *True*  
    **by** *simp*  
**finally have** *eq-length*:  $\text{length (to-list } ?img ?q) = ?n$   
    **by** *simp*  
**show** *?thesis*  
**proof** (*unfold Let-def permute-list-def, rule nth-equalityI*)  
    — The lists have equal lengths.  
**show**  
     $\text{length (to-list } V p) =$   
     $\text{length (map}$   
     $\quad (\lambda i. \text{to-list } ?img ?q!(\text{card } \{v \in ?img.$   
     $\quad \quad v < \pi (\text{sorted-list-of-set } V!i)\}))$   
     $\quad [0 ..< \text{length (to-list } ?img ?q)])$   
    **using** *eq-length*  
    **by** *simp*  
**next**  
    — The  $i$ th entries of the lists coincide.  
**fix**  $i :: \text{nat}$   
**assume** *in-bnds*:  $i < ?n$   
**let**  $?c = \text{card } \{v \in ?img. v < \pi (\text{sorted-list-of-set } V!i)\}$   
**have**  $\text{map } (\lambda i. (\text{to-list } ?img ?q)!?c) [0 ..< ?n]!i =$   
     $p ((\text{sorted-list-of-set } V)!i)$   
**proof** —  
    **have**  $\forall v. v \in ?img \longrightarrow \{v' \in ?img. v' < v\} \subseteq ?img - \{v\}$   
    **by** *blast*  
**moreover have** *elem-of-img*:  $\pi (\text{sorted-list-of-set } V!i) \in ?img$   
    **using** *True in-bnds image-eqI nth-mem card-length-V*  
     $\text{length-sorted-list-of-set set-sorted-list-of-set}$   
    **by** *metis*  
**ultimately have**  
     $\{v \in ?img. v < \pi (\text{sorted-list-of-set } V!i)\}$   
     $\subseteq ?img - \{\pi (\text{sorted-list-of-set } V!i)\}$   
    **by** *simp*  
**hence**  $\{v \in ?img. v < \pi (\text{sorted-list-of-set } V!i)\} \subset ?img$   
    **using** *elem-of-img*  
    **by** *blast*

```

moreover have img-card-eq-V-length:  $\text{card } ?img = ?n$ 
  using card-eq card-length-V
  by presburger
ultimately have card-in-bnds:  $?c < ?n$ 
  using True finite-imageI psubset-card-mono
  by (metis (mono-tags, lifting))
moreover have img-list-map:
   $\text{map } (\lambda i. \text{to-list } ?img ?q! ?c) [0 ..< ?n]!i = \text{to-list } ?img ?q! ?c$ 
  using in-bnds
  by simp
also have img-list-card-eq-inv-img-list:
   $\dots = ?q ((\text{sorted-list-of-set } ?img)! ?c)$ 
  using in-bnds to-list-simp in-bnds img-card-eq-V-length card-in-bnds
  by (metis (no-types, lifting))
also have img-card-eq-img-list-i:
   $\dots = ?q (\pi (\text{sorted-list-of-set } V!i))$ 
  using True elem-of-img
  by (simp add: sorted-list-of-set-nth-equals-card)
finally show ?thesis
  using assms bij-betw-imp-inj-on the-inv-f-f
    img-list-map img-card-eq-img-list-i
    img-list-card-eq-inv-img-list
  by metis
qed
also have to-list V p!i = p ((sorted-list-of-set V)!i)
  using True in-bnds
  by simp
finally show to-list V p!i =
   $\text{map } (\lambda i. (\text{to-list } ?img ?q!)(\text{card } \{v \in ?img. v < \pi (\text{sorted-list-of-set } V!i)\}))$ 
   $[0 ..< \text{length } (\text{to-list } ?img ?q)]!i$ 
  using in-bnds eq-length Collect-cong card-eq
  by simp
qed
qed

```

### 1.5.5 Preference Counts

The win count for an alternative  $a$  with respect to a finite voter set  $V$  in a profile  $p$  is the amount of ballots from  $V$  in  $p$  that rank alternative  $a$  in first position. If the voter set is infinite, counting is not generally possible.

```

fun win-count :: ' $v$  set  $\Rightarrow$  (' $a$ , ' $v$ ) Profile  $\Rightarrow$  ' $a \Rightarrow$  enat where
  win-count V p a = (if finite V
    then card {v  $\in$  V. above (p v) a = {a}} else  $\infty$ )

```

```

fun prefer-count :: ' $v$  set  $\Rightarrow$  (' $a$ , ' $v$ ) Profile  $\Rightarrow$  ' $a \Rightarrow$  ' $a \Rightarrow$  enat where
  prefer-count V p x y = (if finite V
    then card {v  $\in$  V. let  $r = (p v)$  in ( $y \preceq_r x$ )} else  $\infty$ )

```

```

lemma pref-count-voter-set-card:

```

```

fixes
   $V :: 'v \text{ set}$  and
   $p :: ('a, 'v) \text{ Profile}$  and
   $a \ b :: 'a$ 
assumes finite V
shows  $\text{prefer-count } V \ p \ a \ b \leq \text{card } V$ 
using assms
by (simp add: card-mono)

lemma set-compr:
fixes
   $A :: 'a \text{ set}$  and
   $f :: 'a \Rightarrow 'a \text{ set}$ 
shows  $\{f \ x \mid x. x \in A\} = f \ ` \ A$ 
by blast

lemma pref-count-set-compr:
fixes
   $A :: 'a \text{ set}$  and
   $V :: 'v \text{ set}$  and
   $p :: ('a, 'v) \text{ Profile}$  and
   $a :: 'a$ 
shows  $\{\text{prefer-count } V \ p \ a \ a' \mid a'. a' \in A - \{a\}\} =$ 
   $(\text{prefer-count } V \ p \ a) \ ` \ (A - \{a\})$ 
by blast

lemma pref-count:
fixes
   $A :: 'a \text{ set}$  and
   $V :: 'v \text{ set}$  and
   $p :: ('a, 'v) \text{ Profile}$  and
   $a \ b :: 'a$ 
assumes
  prof: profile V A p and
  fn: finite V and
  a-in-A: a ∈ A and
  b-in-A: b ∈ A and
  neg: a ≠ b
shows  $\text{prefer-count } V \ p \ a \ b = \text{card } V - (\text{prefer-count } V \ p \ b \ a)$ 
proof -
have  $\forall v \in V. \text{let } r = (p \ v) \text{ in } \neg b \preceq_r a \longrightarrow a \preceq_r b$ 
using a-in-A b-in-A prof lin-ord-imp-connex
unfolding profile-def connex-def
by metis
moreover have  $\forall v \in V. (b, a) \in (p \ v) \longrightarrow (a, b) \notin (p \ v)$ 
using antisymD neg lin-imp-antisym prof
unfolding profile-def
by metis
ultimately have

```

```

    {v ∈ V. let r = p v in b ≤r a} =
      V - {v ∈ V. let r = p v in a ≤r b}
  by auto
thus ?thesis
  using fin
  by (simp add: card-Diff-subset)
qed

lemma pref-count-sym:
  fixes
    p :: ('a, 'v) Profile and
    V :: 'v set and
    a b c :: 'a
  assumes
    pref-count-ineq: prefer-count V p a c ≥ prefer-count V p c b and
    prof: profile V A p and
    a-in-A: a ∈ A and
    b-in-A: b ∈ A and
    c-in-A: c ∈ A and
    a-neq-c: a ≠ c and
    c-neq-b: c ≠ b
  shows prefer-count V p b c ≥ prefer-count V p c a
proof (cases finite V)
  case True
  moreover have
    prefer-count V p c a ∈ ℕ and
    prefer-count V p b c ∈ ℕ
  unfolding Nats-def
  using True of-nat-eq-enat
  by (simp, simp)
  moreover have prefer-count V p c a ≤ card V
  using True prof pref-count-voter-set-card
  by metis
  moreover have
    prefer-count V p a c = card V - (prefer-count V p c a) and
    prefer-count V p c b = card V - (prefer-count V p b c)
  using True pref-count prof c-in-A
  by (metis (no-types, opaque-lifting) a-in-A a-neq-c,
      metis (no-types, opaque-lifting) b-in-A c-neq-b)
  ultimately show ?thesis
  using pref-count-ineq
  by simp
next
  case False
  thus ?thesis
  by simp
qed

lemma empty-prof-imp-zero-pref-count:

```

```

fixes
   $p :: ('a, 'v) \text{ Profile}$  and
   $V :: 'v \text{ set}$  and
   $a \ b :: 'a$ 
assumes  $V = \{\}$ 
shows  $\text{prefer-count } V \ p \ a \ b = 0$ 
unfolding  $\text{zero-enat-def}$ 
using  $\text{assms}$ 
by  $\text{simp}$ 

fun  $\text{wins} :: 'v \text{ set} \Rightarrow 'a \Rightarrow ('a, 'v) \text{ Profile} \Rightarrow 'a \Rightarrow \text{bool}$  where
   $\text{wins } V \ a \ p \ b =$ 
     $(\text{prefer-count } V \ p \ a \ b > \text{prefer-count } V \ p \ b \ a)$ 

```

**lemma**  $\text{wins-inf-voters}$ :

```

fixes
   $p :: ('a, 'v) \text{ Profile}$  and
   $a \ b :: 'a$  and
   $V :: 'v \text{ set}$ 
assumes  $\text{infinite } V$ 
shows  $\neg \text{wins } V \ b \ p \ a$ 
using  $\text{assms}$ 
by  $\text{simp}$ 

```

Having alternative  $a$  win against  $b$  implies that  $b$  does not win against  $a$ .

**lemma**  $\text{wins-antisym}$ :

```

fixes
   $p :: ('a, 'v) \text{ Profile}$  and
   $a \ b :: 'a$  and
   $V :: 'v \text{ set}$ 
assumes  $\text{wins } V \ a \ p \ b$  — This already implies that  $V$  is finite.
shows  $\neg \text{wins } V \ b \ p \ a$ 
using  $\text{assms}$ 
by  $\text{simp}$ 

```

**lemma**  $\text{wins-irreflex}$ :

```

fixes
   $p :: ('a, 'v) \text{ Profile}$  and
   $a :: 'a$  and
   $V :: 'v \text{ set}$ 
shows  $\neg \text{wins } V \ a \ p \ a$ 
using  $\text{wins-antisym}$ 
by  $\text{metis}$ 

```

### 1.5.6 Condorcet Winner

```

fun  $\text{condorcet-winner} :: 'v \text{ set} \Rightarrow 'a \text{ set} \Rightarrow ('a, 'v) \text{ Profile} \Rightarrow 'a \Rightarrow \text{bool}$  where
   $\text{condorcet-winner } V \ A \ p \ a =$ 
     $(\text{finite-profile } V \ A \ p \wedge a \in A \wedge (\forall x \in A - \{a\}. \text{wins } V \ a \ p \ x))$ 

```

```

lemma cond-winner-unique-eq:
  fixes
     $V :: 'v \text{ set}$  and
     $A :: 'a \text{ set}$  and
     $p :: ('a, 'v) \text{ Profile}$  and
     $a \ b :: 'a$ 
  assumes
    condorcet-winner  $V \ A \ p \ a$  and
    condorcet-winner  $V \ A \ p \ b$ 
  shows  $b = a$ 
proof (rule ccontr)
  assume  $b \text{-neq-} a: b \neq a$ 
  hence wins  $V \ b \ p \ a$ 
    using insert-Diff insert-iff assms
    by simp
  hence  $\neg \text{wins } V \ a \ p \ b$ 
    by (simp add: wins-antisym)
  moreover have wins  $V \ a \ p \ b$ 
    using Diff-iff b-neq-a singletonD assms
    by auto
  ultimately show False
    by simp
qed

```

```

lemma cond-winner-unique:
  fixes
     $A :: 'a \text{ set}$  and
     $p :: ('a, 'v) \text{ Profile}$  and
     $a :: 'a$ 
  assumes condorcet-winner  $V \ A \ p \ a$ 
  shows  $\{a' \in A. \text{condorcet-winner } V \ A \ p \ a'\} = \{a\}$ 
proof (safe)
  fix  $a' :: 'a$ 
  assume condorcet-winner  $V \ A \ p \ a'$ 
  thus  $a' = a$ 
    using assms cond-winner-unique-eq
    by metis
next
  show  $a \in A$ 
    using assms
    unfolding condorcet-winner.simps
    by (metis (no-types))
next
  show condorcet-winner  $V \ A \ p \ a$ 
    using assms
    by presburger
qed

```



```

lemma cond-winner-unique':
  fixes
     $V :: 'v \text{ set}$  and
     $A :: 'a \text{ set}$  and
     $p :: ('a, 'v) \text{ Profile}$  and
     $a \ b :: 'a$ 
  assumes
    condorcet-winner  $V \ A \ p \ a$  and
     $b \neq a$ 
  shows  $\neg \text{condorcet-winner } V \ A \ p \ b$ 
  using cond-winner-unique-eq assms
  by metis

```

### 1.5.7 Limited Profile

This function restricts a profile  $p$  to a set  $A$  of alternatives and a set  $V$  of voters s.t. voters outside of  $V$  do not have any preferences or do not cast a vote. This keeps all of  $A$ 's preferences.

```

fun limit-profile ::  $'a \text{ set} \Rightarrow ('a, 'v) \text{ Profile} \Rightarrow ('a, 'v) \text{ Profile}$  where
  limit-profile  $A \ p = (\lambda v. \text{limit } A \ (p \ v))$ 

```

```

lemma limit-prof-trans:
  fixes
     $A \ B \ C :: 'a \text{ set}$  and
     $p :: ('a, 'v) \text{ Profile}$ 
  assumes
     $B \subseteq A$  and
     $C \subseteq B$ 
  shows limit-profile  $C \ p = \text{limit-profile } C \ (\text{limit-profile } B \ p)$ 
  using assms
  by auto

```

```

lemma limit-profile-sound:
  fixes
     $A \ B :: 'a \text{ set}$  and
     $V :: 'v \text{ set}$  and
     $p :: ('a, 'v) \text{ Profile}$ 
  assumes
    profile  $V \ B \ p$  and
     $A \subseteq B$ 
  shows profile  $V \ A \ (\text{limit-profile } A \ p)$ 
proof (unfold profile-def)
  have  $\forall v \in V. \text{linear-order-on } A \ (\text{limit } A \ (p \ v))$ 
    using assms limit-presv-lin-ord
    unfolding profile-def
    by metis
  thus  $\forall v \in V. \text{linear-order-on } A \ ((\text{limit-profile } A \ p) \ v)$ 
    by simp

```

qed

### 1.5.8 Lifting Property

**definition** *equiv-prof-except-a* :: 'v set  $\Rightarrow$  'a set  $\Rightarrow$  ('a, 'v) Profile  $\Rightarrow$  ('a, 'v) Profile  $\Rightarrow$  'a  $\Rightarrow$  bool **where**  
*equiv-prof-except-a* V A p p' a  $\equiv$   
 profile V A p  $\wedge$  profile V A p'  $\wedge$  a  $\in$  A  $\wedge$   
 ( $\forall$  v  $\in$  V. *equiv-rel-except-a* A (p v) (p' v) a)

An alternative gets lifted from one profile to another iff its ranking increases in at least one ballot, and nothing else changes.

**definition** *lifted* :: 'v set  $\Rightarrow$  'a set  $\Rightarrow$  ('a, 'v) Profile  $\Rightarrow$  ('a, 'v) Profile  $\Rightarrow$  'a  $\Rightarrow$  bool **where**  
*lifted* V A p p' a  $\equiv$   
 finite-profile V A p  $\wedge$  finite-profile V A p'  $\wedge$  a  $\in$  A  
 $\wedge$  ( $\forall$  v  $\in$  V.  $\neg$  Preference-Relation.lifted A (p v) (p' v) a  $\longrightarrow$  (p v) = (p' v))  
 $\wedge$  ( $\exists$  v  $\in$  V. Preference-Relation.lifted A (p v) (p' v) a)

**lemma** *lifted-imp-equiv-prof-except-a*:

**fixes**

A :: 'a set **and**

V :: 'v set **and**

p p' :: ('a, 'v) Profile **and**

a :: 'a

**assumes** *lifted* V A p p' a

**shows** *equiv-prof-except-a* V A p p' a

**proof** (*unfold equiv-prof-except-a-def, safe*)

**show**

profile V A p **and**

profile V A p' **and**

a  $\in$  A

**using** *assms*

**unfolding** *lifted-def*

**by** (*metis, metis, metis*)

**next**

**fix** v :: 'v

**assume** v  $\in$  V

**thus** *equiv-rel-except-a* A (p v) (p' v) a

**using** *assms lifted-imp-equiv-rel-except-a trivial-equiv-rel*

**unfolding** *lifted-def profile-def*

**by** (*metis (no-types)*)

qed

**lemma** *negl-diff-imp-eq-limit-prof*:

**fixes**

A A' :: 'a set **and**

V :: 'v set **and**

p p' :: ('a, 'v) Profile **and**

$a :: 'a$   
**assumes**  
*change*: *equiv-prof-except-a*  $V A' p q a$  **and**  
*subset*:  $A \subseteq A'$  **and**  
*not-in-A*:  $a \notin A$   
**shows**  $\forall v \in V. (\text{limit-profile } A \ p) \ v = (\text{limit-profile } A \ q) \ v$   
— With the current definitions of *equiv-prof-except-a* and *limit-prof*, we can only conclude that the limited profiles coincide on the given voter set, since *limit-prof* may change the profiles everywhere, while *equiv-prof-except-a* only makes statements about the voter set.  
**proof** (*clarify*)  
**fix**  $v :: 'v$   
**assume**  $v \in V$   
**hence** *equiv-rel-except-a*  $A' (p \ v) (q \ v) a$   
**using** *change equiv-prof-except-a-def*  
**by** *metis*  
**thus** *limit-profile*  $A \ p \ v = \text{limit-profile } A \ q \ v$   
**using** *subset not-in-A negl-diff-imp-eq-limit*  
**by** *simp*  
**qed**

**lemma** *limit-prof-eq-or-lifted*:  
**fixes**  
 $A \ A' :: 'a \text{ set}$  **and**  
 $V :: 'v \text{ set}$  **and**  
 $p \ p' :: ('a, 'v) \text{ Profile}$  **and**  
 $a :: 'a$   
**assumes**  
*lifted-a*: *lifted*  $V A' p \ p' a$  **and**  
*subset*:  $A \subseteq A'$   
**shows**  $(\forall v \in V. \text{limit-profile } A \ p \ v = \text{limit-profile } A \ p' \ v)$   
 $\vee \text{lifted } V A (\text{limit-profile } A \ p) (\text{limit-profile } A \ p') a$   
**proof** (*cases*  $a \in A$ )  
**case** *True*  
**have**  $\forall v \in V. \text{Preference-Relation.lifted } A' (p \ v) (p' \ v) a \vee (p \ v) = (p' \ v)$   
**using** *lifted-a*  
**unfolding** *lifted-def*  
**by** *metis*  
**hence** *one*:  
 $\forall v \in V.$   
 $\text{Preference-Relation.lifted } A (\text{limit } A \ (p \ v)) (\text{limit } A \ (p' \ v)) a \vee$   
 $(\text{limit } A \ (p \ v)) = (\text{limit } A \ (p' \ v))$   
**using** *limit-lifted-imp-eq-or-lifted subset*  
**by** *metis*  
**thus** *?thesis*  
**proof** (*cases*  $\forall v \in V. \text{limit } A \ (p \ v) = \text{limit } A \ (p' \ v)$ )  
**case** *True*  
**thus** *?thesis*  
**by** *simp*

```

next
  case False
  let ?p = limit-profile A p
  let ?q = limit-profile A p'
  have
    profile V A ?p and
    profile V A ?q
  using lifted-a subset limit-profile-sound
  unfolding lifted-def
  by (safe, safe)
  moreover have
     $\exists v \in V. \text{Preference-Relation.lifted } A \text{ } (?p \ v) \text{ } (?q \ v) \ a$ 
  using False one
  unfolding limit-profile.simps
  by (metis (no-types, lifting))
  ultimately have lifted V A ?p ?q a
  using True lifted-a one rev-finite-subset subset
  unfolding lifted-def limit-profile.simps
  by (metis (no-types, lifting))
  thus ?thesis
  by simp
qed
next
  case False
  thus ?thesis
  using lifted-a negl-diff-imp-eq-limit-prof subset lifted-imp-equiv-prof-except-a
  by metis
qed
end

```

## 1.6 Social Choice Result

```

theory Social-Choice-Result
  imports Result
begin

```

### 1.6.1 Definition

A social choice result contains three sets of alternatives: elected, rejected, and deferred alternatives.

```

fun well-formed-SCF :: 'a set  $\Rightarrow$  'a Result  $\Rightarrow$  bool where
  well-formed-SCF A res = (disjoint3 res  $\wedge$  set-equals-partition A res)

```

```

fun limit-SCF :: 'a set  $\Rightarrow$  'a set  $\Rightarrow$  'a set where
  limit-SCF A r = A  $\cap$  r

```

## 1.6.2 Auxiliary Lemmas

```

lemma result-imp-rej:
  fixes A e r d :: 'a set
  assumes well-formed-SCF A (e, r, d)
  shows A - (e  $\cup$  d) = r
proof (safe)
  fix a :: 'a
  assume
    a  $\in$  A and
    a  $\notin$  r and
    a  $\notin$  d
  moreover have
    (e  $\cap$  r = {})  $\wedge$  (e  $\cap$  d = {})  $\wedge$  (r  $\cap$  d = {})  $\wedge$  (e  $\cup$  r  $\cup$  d = A)
  using assms
  by simp
  ultimately show a  $\in$  e
  by blast
next
  fix a :: 'a
  assume a  $\in$  r
  moreover have
    (e  $\cap$  r = {})  $\wedge$  (e  $\cap$  d = {})  $\wedge$  (r  $\cap$  d = {})  $\wedge$  (e  $\cup$  r  $\cup$  d = A)
  using assms
  by simp
  ultimately show a  $\in$  A
  by blast
next
  fix a :: 'a
  assume
    a  $\in$  r and
    a  $\in$  e
  moreover have
    (e  $\cap$  r = {})  $\wedge$  (e  $\cap$  d = {})  $\wedge$  (r  $\cap$  d = {})  $\wedge$  (e  $\cup$  r  $\cup$  d = A)
  using assms
  by simp
  ultimately show False
  by auto
next
  fix a :: 'a
  assume
    a  $\in$  r and
    a  $\in$  d
  moreover have
    (e  $\cap$  r = {})  $\wedge$  (e  $\cap$  d = {})  $\wedge$  (r  $\cap$  d = {})  $\wedge$  (e  $\cup$  r  $\cup$  d = A)
  using assms

```

by *simp*  
 ultimately show *False*  
 by *blast*  
 qed

**lemma** *result-count*:  
 fixes  $A\ e\ r\ d :: 'a\ set$   
 assumes  
   *wf-result*: *well-formed-SCF*  $A\ (e,\ r,\ d)$  **and**  
   *fin-A*: *finite*  $A$   
 shows  $\text{card } A = \text{card } e + \text{card } r + \text{card } d$   
**proof** –  
 have  $e \cup r \cup d = A$   
   using *wf-result*  
   by *simp*  
 moreover have  $(e \cap r = \{\}) \wedge (e \cap d = \{\}) \wedge (r \cap d = \{\})$   
   using *wf-result*  
   by *simp*  
 ultimately show ?thesis  
   using *fin-A Int-Un-distrib2 finite-Un card-Un-disjoint sup-bot.right-neutral*  
   by *metis*  
 qed

**lemma** *defer-subset*:  
 fixes  
    $A :: 'a\ set$  **and**  
    $r :: 'a\ Result$   
 assumes *well-formed-SCF*  $A\ r$   
 shows  $\text{defer-}r\ r \subseteq A$   
**proof** (*safe*)  
 fix  $a :: 'a$   
 assume  $a \in \text{defer-}r\ r$   
 moreover obtain  
    $f :: 'a\ Result \Rightarrow 'a\ set \Rightarrow 'a\ set$  **and**  
    $g :: 'a\ Result \Rightarrow 'a\ set \Rightarrow 'a\ Result$  **where**  
    $A = f\ r\ A \wedge r = g\ r\ A \wedge \text{disjoint3 } (g\ r\ A) \wedge \text{set-equals-partition } (f\ r\ A) (g\ r\ A)$   
   using *assms*  
   by *simp*  
 moreover have  
    $\forall p. \exists e\ r\ d. \text{set-equals-partition } A\ p \longrightarrow (e,\ r,\ d) = p \wedge e \cup r \cup d = A$   
   by *simp*  
 ultimately show  $a \in A$   
   using *UnCI snd-conv*  
   by *metis*  
 qed

**lemma** *elect-subset*:  
 fixes  
    $A :: 'a\ set$  **and**

```

    r :: 'a Result
  assumes well-formed-SCF A r
  shows elect-r r  $\subseteq$  A
proof (safe)
  fix a :: 'a
  assume a  $\in$  elect-r r
  moreover obtain
    f :: 'a Result  $\Rightarrow$  'a set  $\Rightarrow$  'a set and
    g :: 'a Result  $\Rightarrow$  'a set  $\Rightarrow$  'a Result where
    A = f r A  $\wedge$  r = g r A  $\wedge$  disjoint3 (g r A)  $\wedge$  set-equals-partition (f r A) (g r A)
  using assms
  by simp
  moreover have
     $\forall p. \exists e r d. \text{set-equals-partition } A \ p \longrightarrow (e, r, d) = p \wedge e \cup r \cup d = A$ 
  by simp
  ultimately show a  $\in$  A
  using UnCI assms fst-conv
  by metis
qed

```

lemma reject-subset:

```

  fixes
    A :: 'a set and
    r :: 'a Result
  assumes well-formed-SCF A r
  shows reject-r r  $\subseteq$  A
proof (safe)
  fix a :: 'a
  assume a  $\in$  reject-r r
  moreover obtain
    f :: 'a Result  $\Rightarrow$  'a set  $\Rightarrow$  'a set and
    g :: 'a Result  $\Rightarrow$  'a set  $\Rightarrow$  'a Result where
    A = f r A  $\wedge$  r = g r A  $\wedge$  disjoint3 (g r A)  $\wedge$  set-equals-partition (f r A) (g r A)
  using assms
  by simp
  moreover have
     $\forall p. \exists e r d. \text{set-equals-partition } A \ p \longrightarrow (e, r, d) = p \wedge e \cup r \cup d = A$ 
  by simp
  ultimately show a  $\in$  A
  using UnCI assms fst-conv snd-conv disjoint3.cases
  by metis
qed

```

end

## 1.7 Social Welfare Result

```

theory Social-Welfare-Result
  imports Result
           Preference-Relation
begin

```

A social welfare result contains three sets of relations: elected, rejected, and deferred. A well-formed social welfare result consists only of linear orders on the alternatives.

```

fun well-formed-SWF :: 'a set  $\Rightarrow$  ('a Preference-Relation) Result  $\Rightarrow$  bool where
  well-formed-SWF A res = (disjoint3 res  $\wedge$ 
                           set-equals-partition {r. linear-order-on A r} res)

```

```

fun limit-SWF :: 'a set  $\Rightarrow$  ('a Preference-Relation) set  $\Rightarrow$ 
  ('a Preference-Relation) set where
  limit-SWF A res = {limit A r | r. r  $\in$  res  $\wedge$  linear-order-on A (limit A r)}

```

```

end

```

## 1.8 Electoral Result Types

```

theory Result-Interpretations
  imports Social-Choice-Result
           Social-Welfare-Result
           Collections.Locale-Code
begin

```

Interpretations of the result locale are placed inside a Locale-Code block in order to enable code generation of later definitions in the locale. Those definitions need to be added via a Locale-Code block as well.

```

setup Locale-Code.open-block

```

Results from social choice functions (*SCFs*), for the purpose of composability and modularity given as three sets of (potentially tied) alternatives. See *Social\_Choice\_Result.thy* for details.

```

global-interpretation SCF-result: result well-formed-SCF limit-SCF

```

```

proof (unfold-locales, safe)

```

```

  fix A e r d :: 'a set

```

```

  assume

```

```

    set-equals-partition (limit-SCF A UNIV) (e, r, d) and

```

```

    disjoint3 (e, r, d)

```

```

  thus well-formed-SCF A (e, r, d)

```

```

    by simp

```

```

qed

```



Results from committee functions, for the purpose of composability and modularity given as three sets of (potentially tied) sets of alternatives or committees. *[[Not actually used yet.]]*

```

global-interpretation committee-result: result
   $\lambda A r. \text{set-equals-partition } (\text{Pow } A) r \wedge \text{disjoint3 } r$ 
   $\lambda A rs. \{r \cap A \mid r. r \in rs\}$ 
proof (unfold-locales, safe)
  fix
     $A :: 'b \text{ set}$  and
     $e r d :: 'b \text{ set set}$ 
  assume set-equals-partition  $\{r \cap A \mid r. r \in \text{UNIV}\} (e, r, d)$ 
  thus set-equals-partition  $(\text{Pow } A) (e, r, d)$ 
  by force
qed

```

Results from social welfare functions (*SWFs*), for the purpose of composability and modularity given as three sets of (potentially tied) linear orders over the alternatives. See `Social_Welfare_Result.thy` for details.

```

global-interpretation SWF-result: result well-formed-SWF limit-SWF
proof (unfold-locales, safe)
  fix
     $A :: 'a \text{ set}$  and
     $e r d :: ('a \text{ Preference-Relation}) \text{ set}$ 
  assume
    set-equals-partition  $(\text{limit-SWF } A \text{ UNIV}) (e, r, d)$  and
    disjoint3  $(e, r, d)$ 
  moreover have
     $\text{limit-SWF } A \text{ UNIV} = \{r' \mid r'. \text{linear-order-on } A (\text{limit } A r')\}$ 
    by simp
  moreover have  $\dots = \{r'. \text{linear-order-on } A r'\}$ 
  proof (safe)
    fix  $r' :: 'a \text{ Preference-Relation}$ 
    assume lin-ord: linear-order-on  $A r'$ 
    hence  $\forall (a, b) \in r'. (a, b) \in \text{limit } A r'$ 
    unfolding linear-order-on-def partial-order-on-def preorder-on-def refl-on-def
    by force
    hence  $r' = \text{limit } A r'$ 
    by force
    thus  $\exists x. r' = \text{limit } A x \wedge \text{linear-order-on } A (\text{limit } A x)$ 
    using lin-ord
    by metis
  qed
  ultimately show well-formed-SWF  $A (e, r, d)$ 
  by simp
qed

```

**setup** Locale-Code.close-block

end

## 1.9 Symmetry Properties of Functions

```
theory Symmetry-Of-Functions
  imports HOL-Algebra.Group-Action
        HOL-Algebra.Generated-Groups
begin
```

### 1.9.1 Functions

```
type-synonym ('x, 'y) binary-fun = 'x  $\Rightarrow$  'y  $\Rightarrow$  'y

fun extensional-continuation :: ('x  $\Rightarrow$  'y)  $\Rightarrow$  'x set  $\Rightarrow$  ('x  $\Rightarrow$  'y) where
  extensional-continuation f S = ( $\lambda$  x. if  $x \in S$  then f x else undefined)

fun preimg :: ('x  $\Rightarrow$  'y)  $\Rightarrow$  'x set  $\Rightarrow$  'y  $\Rightarrow$  'x set where
  preimg f S y = {x  $\in$  S. f x = y}
```

### 1.9.2 Relations for Symmetry Constructions

```
fun restricted-rel :: 'x rel  $\Rightarrow$  'x set  $\Rightarrow$  'x set  $\Rightarrow$  'x rel where
  restricted-rel r S S' = r  $\cap$  (S  $\times$  S')

fun closed-restricted-rel :: 'x rel  $\Rightarrow$  'x set  $\Rightarrow$  'x set  $\Rightarrow$  bool where
  closed-restricted-rel r S T = ((restricted-rel r T S) “ T  $\subseteq$  T)

fun action-induced-rel :: 'x set  $\Rightarrow$  'y set  $\Rightarrow$  ('x, 'y) binary-fun  $\Rightarrow$  'y rel where
  action-induced-rel S T  $\varphi$  = {(y, y'). y  $\in$  T  $\wedge$  ( $\exists$  x  $\in$  S.  $\varphi$  x y = y')}

fun product :: 'x rel  $\Rightarrow$  ('x * 'x) rel where
  product r = {(p, p'). (fst p, fst p')  $\in$  r  $\wedge$  (snd p, snd p')  $\in$  r}

fun equivariance :: 'x set  $\Rightarrow$  'y set  $\Rightarrow$  ('x, 'y) binary-fun  $\Rightarrow$  ('y * 'y) rel where
  equivariance S T  $\varphi$  =
    {((u, v), (x, y)). (u, v)  $\in$  T  $\times$  T  $\wedge$  ( $\exists$  z  $\in$  S. x =  $\varphi$  z u  $\wedge$  y =  $\varphi$  z v)}

fun singleton-set-system :: 'x set  $\Rightarrow$  'x set set where
  singleton-set-system S = {{x} | x. x  $\in$  S}

fun set-action :: ('x, 'r) binary-fun  $\Rightarrow$  ('x, 'r set) binary-fun where
  set-action  $\psi$  x = image ( $\psi$  x)
```

### 1.9.3 Invariance and Equivariance

Invariance and equivariance are symmetry properties of functions: Invariance means that related preimages have identical images and equivariance denotes

consistent changes.

**datatype** ('x, 'y) *symmetry* =

*Invariance* 'x *rel* |

*Equivariance* 'x *set* (('x  $\Rightarrow$  'x)  $\times$  ('y  $\Rightarrow$  'y)) *set*

**fun** *is-symmetry* :: ('x  $\Rightarrow$  'y)  $\Rightarrow$  ('x, 'y) *symmetry*  $\Rightarrow$  *bool* **where**

*is-symmetry* f (*Invariance* r) = ( $\forall$  x.  $\forall$  y. (x, y)  $\in$  r  $\longrightarrow$  f x = f y) |

*is-symmetry* f (*Equivariance* s  $\tau$ ) = ( $\forall$  ( $\varphi$ ,  $\psi$ )  $\in$   $\tau$ .  $\forall$  x  $\in$  s. f ( $\varphi$  x) =  $\psi$  (f x))

**definition** *action-induced-equivariance* :: 'z *set*  $\Rightarrow$  'x *set*  $\Rightarrow$  ('z, 'x) *binary-fun*  $\Rightarrow$

('z, 'y) *binary-fun*  $\Rightarrow$  ('x, 'y) *symmetry* **where**

*action-induced-equivariance* T S  $\varphi$   $\psi \equiv$  *Equivariance* S {( $\varphi$  z,  $\psi$  z) | z. z  $\in$  T}

### 1.9.4 Auxiliary Lemmas

**lemma** *un-left-inv-singleton-set-system*:  $\bigcup \circ \text{singleton-set-system} = \text{id}$

**proof**

**fix** s :: 'x *set*

**have** ( $\bigcup \circ \text{singleton-set-system}$ ) s = {x. {x}  $\in$  *singleton-set-system* s}

**by** *force*

**thus** ( $\bigcup \circ \text{singleton-set-system}$ ) s = *id* s

**by** *simp*

**qed**

**lemma** *preimg-comp*:

**fixes**

f :: 'x  $\Rightarrow$  'y **and**

g :: 'x  $\Rightarrow$  'x **and**

S :: 'x *set* **and**

x :: 'y

**shows** *preimg* f (g ' S) x = g ' *preimg* (f  $\circ$  g) S x

**proof** (*safe*)

**fix** y :: 'x

**assume** y  $\in$  *preimg* f (g ' S) x

**then obtain** z :: 'x **where**

g z = y **and**

z  $\in$  *preimg* (f  $\circ$  g) S x

**unfolding** *comp-def*

**by** *fastforce*

**thus** y  $\in$  g ' *preimg* (f  $\circ$  g) S x

**by** *blast*

**next**

**fix** y :: 'x

**assume** y  $\in$  *preimg* (f  $\circ$  g) S x

**thus** g y  $\in$  *preimg* f (g ' S) x

**by** *simp*

**qed**

### 1.9.5 Rewrite Rules

**theorem** *rewrite-invar-as-equivar*:

```

fixes
   $f :: 'x \Rightarrow 'y$  and
   $S :: 'x \text{ set}$  and
   $T :: 'z \text{ set}$  and
   $\varphi :: ('z, 'x) \text{ binary-fun}$ 
shows is-symmetry  $f$  (Invariance (action-induced-rel  $T$   $S$   $\varphi$ )) =
  is-symmetry  $f$  (action-induced-equivariance  $T$   $S$   $\varphi$  ( $\lambda g. id$ ))
proof (unfold action-induced-equivariance-def is-symmetry.simps, safe)
fix
   $x :: 'x$  and
   $g :: 'z$ 
assume
   $x \in S$  and
   $g \in T$  and
   $\forall x\ y. (x, y) \in \text{action-induced-rel } T\ S\ \varphi \longrightarrow f\ x = f\ y$ 
moreover with this have  $(x, \varphi\ g\ x) \in \text{action-induced-rel } T\ S\ \varphi$ 
  unfolding action-induced-rel.simps
  by blast
ultimately show  $f\ (\varphi\ g\ x) = id\ (f\ x)$ 
  by simp
next
fix  $x\ y :: 'x$ 
assume
  equivar:
     $\forall (\varphi, \psi) \in \{(\varphi\ g, id) \mid g. g \in T\}. \forall x \in S. f\ (\varphi\ x) = \psi\ (f\ x)$  and
  rel:  $(x, y) \in \text{action-induced-rel } T\ S\ \varphi$ 
then obtain  $g :: 'z$  where
  img:  $\varphi\ g\ x = y$  and
  elt:  $g \in T$ 
  unfolding action-induced-rel.simps
  by blast
moreover have  $x \in S$ 
  using rel
  by simp
ultimately have  $f\ (\varphi\ g\ x) = id\ (f\ x)$ 
  using equivar elt
  by blast
thus  $f\ x = f\ y$ 
  using img elt
  by simp
qed

```

**lemma** *rewrite-invar-ind-by-act*:

```

fixes
   $f :: 'x \Rightarrow 'y$  and
   $S :: 'z \text{ set}$  and
   $T :: 'x \text{ set}$  and

```

```

     $\varphi :: ('z, 'x) \text{ binary-fun}$ 
shows is-symmetry  $f$  (Invariance (action-induced-rel  $S$   $T$   $\varphi$ )) =
    ( $\forall x \in S. \forall y \in T. f\ y = f\ (\varphi\ x\ y)$ )
proof (safe)
  fix
     $y :: 'x$  and
     $x :: 'z$ 
  assume
    is-symmetry  $f$  (Invariance (action-induced-rel  $S$   $T$   $\varphi$ )) and
     $y \in T$  and
     $x \in S$ 
  moreover from this have  $(y, \varphi\ x\ y) \in \text{action-induced-rel } S\ T\ \varphi$ 
  unfolding action-induced-rel.simps
  by blast
  ultimately show  $f\ y = f\ (\varphi\ x\ y)$ 
  by simp
next
  assume  $\forall x \in S. \forall y \in T. f\ y = f\ (\varphi\ x\ y)$ 
  moreover have
     $\forall (x, y) \in \text{action-induced-rel } S\ T\ \varphi. x \in T \wedge (\exists z \in S. y = \varphi\ z\ x)$ 
  by auto
  ultimately show is-symmetry  $f$  (Invariance (action-induced-rel  $S$   $T$   $\varphi$ ))
  by auto
qed

```

**lemma** *rewrite-equivariance:*

```

fixes
   $f :: 'x \Rightarrow 'y$  and
   $S :: 'z \text{ set}$  and
   $T :: 'x \text{ set}$  and
   $\varphi :: ('z, 'x) \text{ binary-fun}$  and
   $\psi :: ('z, 'y) \text{ binary-fun}$ 
shows is-symmetry  $f$  (action-induced-equivariance  $S$   $T$   $\varphi\ \psi$ ) =
  ( $\forall x \in S. \forall y \in T. f\ (\varphi\ x\ y) = \psi\ x\ (f\ y)$ )
unfolding action-induced-equivariance-def
by auto

```

**lemma** *rewrite-group-action-img:*

```

fixes
   $m :: 'x \text{ monoid}$  and
   $S\ T :: 'y \text{ set}$  and
   $\varphi :: ('x, 'y) \text{ binary-fun}$  and
   $x\ y :: 'x$ 
assumes
   $T \subseteq S$  and
   $x \in \text{carrier } m$  and
   $y \in \text{carrier } m$  and
  group-action  $m\ S\ \varphi$ 
shows  $\varphi\ (x \otimes_m y) \text{ ` } T = \varphi\ x \text{ ` } \varphi\ y \text{ ` } T$ 

```

```

proof (safe)
  fix  $z :: 'y$ 
  assume  $z\text{-in-}t: z \in T$ 
  hence  $\varphi (x \otimes_m y) z = \varphi x (\varphi y z)$ 
    using assms group-action.composition-rule[of m S]
    by blast
  thus
     $\varphi (x \otimes_m y) z \in \varphi x \text{ ' } \varphi y \text{ ' } T$  and
     $\varphi x (\varphi y z) \in \varphi (x \otimes_m y) \text{ ' } T$ 
    using z-in-t
    by (blast, force)
qed

lemma rewrite-carrier:  $\text{carrier } (BijGroup\ UNIV) = \{f. \text{bij } f\}$ 
  unfolding BijGroup-def Bij-def
  by simp

lemma universal-set-carrier-imp-bij-group:
  fixes  $f :: 'a \Rightarrow 'a$ 
  assumes  $f \in \text{carrier } (BijGroup\ UNIV)$ 
  shows bij f
  using rewrite-carrier assms
  by blast

lemma rewrite-sym-group:
  fixes
     $f\ g :: 'a \Rightarrow 'a$  and
     $S :: 'a\ \text{set}$ 
  assumes
     $f \in \text{carrier } (BijGroup\ S)$  and
     $g \in \text{carrier } (BijGroup\ S)$ 
  shows
    rewrite-mult:  $f \otimes_{BijGroup\ S} g = \text{extensional-continuation } (f \circ g)\ S$  and
    rewrite-mult-univ:  $S = UNIV \longrightarrow f \otimes_{BijGroup\ S} g = f \circ g$ 
  using assms
  unfolding BijGroup-def compose-def comp-def restrict-def
  by (simp, fastforce)

lemma simp-extensional-univ:
  fixes  $f :: 'a \Rightarrow 'b$ 
  shows extensional-continuation f UNIV = f
  unfolding If-def
  by simp

lemma extensional-continuation-subset:
  fixes
     $f :: 'a \Rightarrow 'b$  and
     $S\ T :: 'a\ \text{set}$  and
     $x :: 'a$ 

```

```

assumes
   $T \subseteq S$  and
   $x \in T$ 
shows  $\text{extensional-continuation } f \ S \ x = \text{extensional-continuation } f \ T \ x$ 
using assms
unfolding subset-iff
by simp

lemma rel-ind-by-coinciding-action-on-subset-eq-restr:
fixes
   $\varphi \ \psi :: ('a, 'b) \text{ binary-fun}$  and
   $S :: 'a \text{ set}$  and
   $T \ U :: 'b \text{ set}$ 
assumes
   $U \subseteq T$  and
   $\forall x \in S. \forall y \in U. \varphi \ x \ y = \psi \ x \ y$ 
shows  $\text{action-induced-rel } S \ U \ \psi = \text{restricted-rel } (\text{action-induced-rel } S \ T \ \varphi) \ U$ 
UNIV
proof (unfold action-induced-rel.simps restricted-rel.simps, safe)
  fix  $x :: 'b$ 
  assume  $x \in U$ 
  thus  $x \in T$ 
    using assms
    by blast
next
  fix
     $g :: 'a$  and
     $x :: 'b$ 
  assume
     $g\text{-in-}S: g \in S$  and
     $x\text{-in-}U: x \in U$ 
  hence  $\varphi \ g \ x = \psi \ g \ x$ 
    using assms
    by simp
  thus  $\exists g' \in S. \varphi \ g' \ x = \psi \ g \ x$ 
    using g-in-S
    by blast
next
  fix
     $g :: 'a$  and
     $x :: 'b$ 
  show  $\psi \ g \ x \in \text{UNIV}$ 
    by blast
next
  fix
     $g :: 'a$  and
     $x :: 'b$ 
  assume
     $g\text{-in-}S: g \in S$  and

```

```

  x-in-U:  $x \in U$ 
  hence  $\psi \ g \ x = \varphi \ g \ x$ 
  using assms
  by simp
  thus  $\exists \ g' \in S. \ \psi \ g' \ x = \varphi \ g \ x$ 
  using g-in-S
  by blast
qed

```

```

lemma coinciding-actions-ind-equal-rel:
  fixes
     $S :: 'x \text{ set}$  and
     $T :: 'y \text{ set}$  and
     $\varphi \ \psi :: ('x, 'y) \text{ binary-fun}$ 
  assumes  $\forall \ x \in S. \ \forall \ y \in T. \ \varphi \ x \ y = \psi \ x \ y$ 
  shows action-induced-rel  $S \ T \ \varphi = \text{action-induced-rel } S \ T \ \psi$ 
  unfolding extensional-continuation.simps
  using assms
  by auto

```

### 1.9.6 Group Actions

```

lemma const-id-is-group-action:
  fixes  $m :: 'x \text{ monoid}$ 
  assumes group  $m$ 
  shows group-action  $m \ UNIV \ (\lambda \ x. \ id)$ 
  using assms
proof (unfold group-action-def group-hom-def group-hom-axioms-def hom-def, safe)
  show group (BijGroup  $UNIV$ )
    using group-BijGroup
    by metis
next
  show  $id \in \text{carrier } (\text{BijGroup } UNIV)$ 
    unfolding BijGroup-def Bij-def
    by simp
  thus  $id = id \otimes \text{BijGroup } UNIV \ id$ 
    using rewrite-mult-univ comp-id
    by metis
qed

```

```

theorem group-act-induces-set-group-act:
  fixes
     $m :: 'x \text{ monoid}$  and
     $S :: 'y \text{ set}$  and
     $\varphi :: ('x, 'y) \text{ binary-fun}$ 
  defines  $\varphi\text{-img} \equiv (\lambda \ x. \ \text{extensional-continuation } (\text{image } (\varphi \ x)) \ (\text{Pow } S))$ 
  assumes group-action  $m \ S \ \varphi$ 
  shows group-action  $m \ (\text{Pow } S) \ \varphi\text{-img}$ 
proof (unfold group-action-def group-hom-def group-hom-axioms-def hom-def, safe)

```



```

show group m
  using assms
  unfolding group-action-def group-hom-def
  by simp
next
show group (BijGroup (Pow S))
  using group-BijGroup
  by metis
next
{
  fix x :: 'x
  assume x ∈ carrier m
  hence bij-betw (φ x) S S
    using assms group-action.surj-prop
    unfolding bij-betw-def
    by (simp add: group-action.inj-prop)
  hence bij-betw (image (φ x)) (Pow S) (Pow S)
    using bij-betw-Pow
    by metis
  moreover have ∀ t ∈ Pow S. φ-img x t = image (φ x) t
    unfolding φ-img-def
    by simp
  ultimately have bij-betw (φ-img x) (Pow S) (Pow S)
    using bij-betw-cong
    by fastforce
  moreover have φ-img x ∈ extensional (Pow S)
    unfolding φ-img-def extensional-def
    by simp
  ultimately show φ-img x ∈ carrier (BijGroup (Pow S))
    unfolding BijGroup-def Bij-def
    by simp
}
fix x y :: 'x
note
  ⟨x ∈ carrier m ⟹ φ-img x ∈ carrier (BijGroup (Pow S))⟩ and
  ⟨y ∈ carrier m ⟹ φ-img y ∈ carrier (BijGroup (Pow S))⟩
moreover assume
  carrier-x: x ∈ carrier m and
  carrier-y: y ∈ carrier m
ultimately have
  carrier-election-x: φ-img x ∈ carrier (BijGroup (Pow S)) and
  carrier-election-y: φ-img y ∈ carrier (BijGroup (Pow S))
  by (presburger, presburger)
hence h-closed: ∀ T ∈ Pow S. φ-img y T ∈ Pow S
  using bij-betw-apply Int-Collect
  unfolding BijGroup-def Bij-def partial-object.select-convs
  by (metis (no-types))
from carrier-election-x carrier-election-y
have φ-img x ⊗ BijGroup (Pow S) φ-img y =

```

```

      extensional-continuation ( $\varphi$ -img  $x \circ \varphi$ -img  $y$ ) (Pow  $S$ )
    using rewrite-mult
    by blast
  moreover have
     $\forall T. T \notin \text{Pow } S \longrightarrow \text{extensional-continuation } (\varphi\text{-img } x \circ \varphi\text{-img } y) (\text{Pow } S) T = \text{undefined}$ 
    by simp
  moreover have
     $\forall T. T \notin \text{Pow } S \longrightarrow \varphi\text{-img } (x \otimes_m y) T = \text{undefined}$  and
     $\forall T \in \text{Pow } S.$ 
      extensional-continuation ( $\varphi$ -img  $x \circ \varphi$ -img  $y$ ) (Pow  $S$ )  $T = \varphi x \text{ ' } \varphi y \text{ ' } T$ 
    using h-closed
    unfolding  $\varphi$ -img-def
    by (simp, simp)
  moreover have  $\forall T \in \text{Pow } S. \varphi\text{-img } (x \otimes_m y) T = \varphi x \text{ ' } \varphi y \text{ ' } T$ 
    unfolding  $\varphi$ -img-def extensional-continuation.simps
    using rewrite-group-action-img carrier-x carrier-y assms PowD
    by metis
  ultimately have
     $\forall T. \varphi\text{-img } (x \otimes_m y) T = (\varphi\text{-img } x \otimes_{\text{BijGroup } (\text{Pow } S)} \varphi\text{-img } y) T$ 
    by metis
  thus  $\varphi\text{-img } (x \otimes_m y) = \varphi\text{-img } x \otimes_{\text{BijGroup } (\text{Pow } S)} \varphi\text{-img } y$ 
    by blast
qed

```

### 1.9.7 Invariance and Equivariance

It suffices to show equivariance under the group action of a generating set of a group to show equivariance under the group action of the whole group. For example, it is enough to show invariance under transpositions to show invariance under a complete finite symmetric group.

**theorem** *equivar-generators-imp-equivar-group*:

```

fixes
   $f :: 'x \Rightarrow 'y$  and
   $m :: 'z \text{ monoid}$  and
   $S :: 'z \text{ set}$  and
   $T :: 'x \text{ set}$  and
   $\varphi :: ('z, 'x) \text{ binary-fun}$  and
   $\psi :: ('z, 'y) \text{ binary-fun}$ 
assumes
  equivar: is-symmetry  $f$  (action-induced-equivariance  $S$   $T$   $\varphi$   $\psi$ ) and
  action- $\varphi$ : group-action  $m$   $T$   $\varphi$  and
  action- $\psi$ : group-action  $m$  ( $f \text{ ' } T$ )  $\psi$  and
  gen: carrier  $m = \text{generate } m S$ 
shows is-symmetry  $f$  (action-induced-equivariance (carrier  $m$ )  $T$   $\varphi$   $\psi$ )
proof (unfold is-symmetry.simps action-induced-equivariance-def action-induced-rel.simps,
  safe)
fix

```

```

  g :: 'z and
  x :: 'x
assume
  group-elem: g ∈ carrier m and
  x-in-t: x ∈ T
have g ∈ generate m S
  using group-elem gen
  by blast
hence ∀ x ∈ T. f (φ g x) = ψ g (f x)
proof (induct g rule: generate.induct)
  case one
  hence ∀ x ∈ T. φ 1_m x = x
    using action-φ group-action.id-eq-one restrict-apply
    by metis
  moreover with one have ∀ y ∈ (f ' T). ψ 1_m y = y
    using action-ψ group-action.id-eq-one restrict-apply
    by metis
  ultimately show ?case
    by simp
next
  case (incl g)
  hence ∀ x ∈ T. φ g x ∈ T
    using action-φ gen generate.incl group-action.element-image
    by metis
  thus ?case
    using incl equivar rewrite-equivariance
    unfolding is-symmetry.simps
    by metis
next
  case (inv g)
  hence in-t: ∀ x ∈ T. φ (inv m g) x ∈ T
    using action-φ gen generate.inv group-action.element-image
    by metis
  hence ∀ x ∈ T. f (φ g (φ (inv m g) x)) = ψ g (f (φ (inv m g) x))
    using gen action-φ equivar local.inv rewrite-equivariance
    by metis
  moreover have ∀ x ∈ T. φ g (φ (inv m g) x) = x
    using action-φ gen generate.incl group.inv-closed group-action.orbit-sym-aux
      group.inv-inv group-action.group-hom local.inv
    unfolding group-hom-def
    by (metis (full-types))
  ultimately have ∀ x ∈ T. ψ g (f (φ (inv m g) x)) = f x
    by simp
  moreover have in-img-t: ∀ x ∈ T. f (φ (inv m g) x) ∈ f ' T
    using in-t
    by blast
  ultimately have
    ∀ x ∈ T. ψ (inv m g) (ψ g (f (φ (inv m g) x))) = ψ (inv m g) (f x)
    using action-ψ gen

```

```

    by metis
  moreover have
     $\forall x \in T. \psi (\text{inv } m \ g) (\psi \ g \ (f (\varphi (\text{inv } m \ g) \ x))) = f (\varphi (\text{inv } m \ g) \ x)$ 
    using in-img-t action- $\psi$  gen generate.incl group-action.orbit-sym-aux local.inv
    by metis
  ultimately show ?case
    by simp
next
case (eng g1 g2)
assume
  equivar1:  $\forall x \in T. f (\varphi \ g_1 \ x) = \psi \ g_1 \ (f \ x)$  and
  equivar2:  $\forall x \in T. f (\varphi \ g_2 \ x) = \psi \ g_2 \ (f \ x)$  and
  gen1:  $g_1 \in \text{generate } m \ S$  and
  gen2:  $g_2 \in \text{generate } m \ S$ 
hence  $\forall x \in T. \varphi \ g_2 \ x \in T$ 
  using gen action- $\varphi$  group-action.element-image
  by metis
hence  $\forall x \in T. f (\varphi \ g_1 \ (\varphi \ g_2 \ x)) = \psi \ g_1 \ (f (\varphi \ g_2 \ x))$ 
  using equivar1
  by simp
moreover have  $\forall x \in T. f (\varphi \ g_2 \ x) = \psi \ g_2 \ (f \ x)$ 
  using equivar2
  by simp
ultimately show ?case
  using action- $\varphi$  action- $\psi$  gen gen1 gen2 group-action.composition-rule imageI
  by (metis (no-types, lifting))
qed
thus  $f (\varphi \ g \ x) = \psi \ g \ (f \ x)$ 
  using x-in-t
  by simp
qed

lemma invar-parameterized-fun:
  fixes
     $f :: 'x \Rightarrow ('x \Rightarrow 'y)$  and
     $r :: 'x \text{ rel}$ 
  assumes
     $\forall x. \text{is-symmetry } (f \ x) \ (\text{Invariance } r)$  and
     $\text{is-symmetry } f \ (\text{Invariance } r)$ 
  shows  $\text{is-symmetry } (\lambda x. f \ x \ x) \ (\text{Invariance } r)$ 
  using assms
  by simp

lemma invar-under-subset-rel:
  fixes
     $f :: 'x \Rightarrow 'y$  and
     $r \ s :: 'x \text{ rel}$ 
  assumes
     $\text{subset: } r \subseteq s$  and

```

*invar*: *is-symmetry* *f* (*Invariance* *s*)  
**shows** *is-symmetry* *f* (*Invariance* *r*)  
**using** *assms*  
**by** *auto*

**lemma** *equivar-ind-by-act-coincide*:

**fixes**  
 $S :: 'x \text{ set}$  **and**  
 $T :: 'y \text{ set}$  **and**  
 $f :: 'y \Rightarrow 'z$  **and**  
 $\varphi \ \varphi' :: ('x, 'y) \text{ binary-fun}$  **and**  
 $\psi :: ('x, 'z) \text{ binary-fun}$   
**assumes**  $\forall x \in S. \forall y \in T. \varphi \ x \ y = \varphi' \ x \ y$   
**shows** *is-symmetry* *f* (*action-induced-equivariance* *S* *T*  $\varphi \ \psi$ ) =  
*is-symmetry* *f* (*action-induced-equivariance* *S* *T*  $\varphi' \ \psi$ )  
**using** *assms*  
**unfolding** *rewrite-equivariance*  
**by** *simp*

**lemma** *equivar-under-subset*:

**fixes**  
 $f :: 'x \Rightarrow 'y$  **and**  
 $S \ T :: 'x \text{ set}$  **and**  
 $\tau :: (('x \Rightarrow 'x) \times ('y \Rightarrow 'y)) \text{ set}$   
**assumes**  
*is-symmetry* *f* (*Equivariance* *S*  $\tau$ ) **and**  
 $T \subseteq S$   
**shows** *is-symmetry* *f* (*Equivariance* *T*  $\tau$ )  
**using** *assms*  
**unfolding** *is-symmetry.simps*  
**by** *blast*

**lemma** *equivar-under-subset'*:

**fixes**  
 $f :: 'x \Rightarrow 'y$  **and**  
 $S :: 'x \text{ set}$  **and**  
 $\tau \ v :: (('x \Rightarrow 'x) \times ('y \Rightarrow 'y)) \text{ set}$   
**assumes**  
*is-symmetry* *f* (*Equivariance* *S*  $\tau$ ) **and**  
 $v \subseteq \tau$   
**shows** *is-symmetry* *f* (*Equivariance* *S* *v*)  
**using** *assms*  
**unfolding** *is-symmetry.simps*  
**by** *blast*

**theorem** *group-action-equivar-f-imp-equivar-preimg*:

**fixes**  
 $f :: 'x \Rightarrow 'y$  **and**  
 $\mathcal{D}_f \ S :: 'x \text{ set}$  **and**

```

  m :: 'z monoid and
  φ :: ('z, 'x) binary-fun and
  ψ :: ('z, 'y) binary-fun and
  x :: 'z
defines equivar-prop ≡ action-induced-equivariance (carrier m)  $\mathcal{D}_f$  φ ψ
assumes
  action-φ: group-action m S φ and
  action-res: group-action m UNIV ψ and
  dom-in-s:  $\mathcal{D}_f \subseteq S$  and
  closed-domain:
    closed-restricted-rel (action-induced-rel (carrier m) S φ) S  $\mathcal{D}_f$  and
  equivar-f: is-symmetry f equivar-prop and
  group-elem-x:  $x \in \text{carrier } m$ 
shows  $\forall y. \text{preimg } f \mathcal{D}_f (\psi \ x \ y) = (\varphi \ x) \cdot (\text{preimg } f \mathcal{D}_f \ y)$ 
proof (safe)
  interpret action-φ: group-action m S φ
    using action-φ
    by simp
  interpret action-results: group-action m UNIV ψ
    using action-res
    by simp
  have group-elem-inv:  $(\text{inv } m \ x) \in \text{carrier } m$ 
    using group.inv-closed action-φ.group-hom group-elem-x
    unfolding group-hom-def
    by metis
  fix
    y :: 'y and
    z :: 'x
  assume preimg-el:  $z \in \text{preimg } f \mathcal{D}_f (\psi \ x \ y)$ 
  obtain a :: 'x where
    img:  $a = \varphi (\text{inv } m \ x) \ z$ 
    by simp
  have domain:  $z \in \mathcal{D}_f \wedge z \in S$ 
    using preimg-el dom-in-s
    by auto
  hence  $a \in S$ 
    using dom-in-s action-φ group-elem-inv preimg-el img action-φ.element-image
    by auto
  hence  $(z, a) \in (\text{action-induced-rel (carrier m) S } \varphi) \cap (\mathcal{D}_f \times S)$ 
    using img preimg-el domain group-elem-inv
    by auto
  hence  $a \in ((\text{action-induced-rel (carrier m) S } \varphi) \cap (\mathcal{D}_f \times S)) \text{ `` } \mathcal{D}_f$ 
    using img preimg-el domain group-elem-inv
    by auto
  hence a-in-domain:  $a \in \mathcal{D}_f$ 
    using closed-domain
    by auto
  moreover have  $(\varphi (\text{inv } m \ x), \psi (\text{inv } m \ x)) \in \{(\varphi \ g, \psi \ g) \mid g. g \in \text{carrier } m\}$ 
    using group-elem-inv

```

```

    by auto
  ultimately have  $f a = \psi (\text{inv } m \ x) (f z)$ 
    using domain equivar-f img
    unfolding equivar-prop-def action-induced-equivariance-def
    by simp
  hence  $f a = y$ 
    using preimg-el action-results.group-hom action-results.orbit-sym-aux
      group-elem-x
    by simp
  hence  $a \in \text{preimg } f \ \mathcal{D}_f \ y$ 
    using a-in-domain
    by simp
  moreover have  $z = \varphi \ x \ a$ 
    using action- $\varphi$ .group-hom action- $\varphi$ .orbit-sym-aux img domain
      a-in-domain group-elem-x group-elem-inv group.inv-inv
    unfolding group-hom-def
    by metis
  ultimately show  $z \in (\varphi \ x) \text{ ' } (\text{preimg } f \ \mathcal{D}_f \ y)$ 
    by simp
next
fix
  y :: 'y and
  z :: 'x
  assume  $z \in \text{preimg } f \ \mathcal{D}_f \ y$ 
  hence domain:  $f z = y \wedge z \in \mathcal{D}_f \wedge z \in S$ 
    using dom-in-s
    by auto
  hence  $\varphi \ x \ z \in S$ 
    using group-elem-x group-action.element-image action- $\varphi$ 
    by metis
  hence  $(z, \varphi \ x \ z) \in (\text{action-induced-rel } (\text{carrier } m) \ S \ \varphi) \cap (\mathcal{D}_f \times S) \cap \mathcal{D}_f \times S$ 
    using group-elem-x domain
    by auto
  hence  $\varphi \ x \ z \in \mathcal{D}_f$ 
    using closed-domain
    by auto
  moreover have  $(\varphi \ x, \psi \ x) \in \{(\varphi \ a, \psi \ a) \mid a. a \in \text{carrier } m\}$ 
    using group-elem-x
    by blast
  ultimately show  $\varphi \ x \ z \in \text{preimg } f \ \mathcal{D}_f \ (\psi \ x \ y)$ 
    using equivar-f domain
    unfolding equivar-prop-def action-induced-equivariance-def
    by simp
qed

```

### 1.9.8 Function Composition

lemma *invar-comp*:  
 fixes

```

    f :: 'x ⇒ 'y and
    g :: 'y ⇒ 'z and
    r :: 'x rel
  assumes is-symmetry f (Invariance r)
  shows is-symmetry (g ∘ f) (Invariance r)
  using assms
  by simp

lemma equivar-comp:
  fixes
    f :: 'x ⇒ 'y and
    g :: 'y ⇒ 'z and
    S :: 'x set and
    T :: 'y set and
    τ :: (('x ⇒ 'x) × ('y ⇒ 'y)) set and
    v :: (('y ⇒ 'y) × ('z ⇒ 'z)) set
  defines
    transitive-acts ≡
      {(φ, ψ). ∃ χ :: 'y ⇒ 'y. (φ, χ) ∈ τ ∧ (χ, ψ) ∈ v ∧ χ ' f ' S ⊆ T}
  assumes
    f ' S ⊆ T and
    is-symmetry f (Equivariance S τ) and
    is-symmetry g (Equivariance T v)
  shows is-symmetry (g ∘ f) (Equivariance S transitive-acts)
proof (unfold transitive-acts-def is-symmetry.simps comp-def, safe)
  fix
    φ :: 'x ⇒ 'x and
    χ :: 'y ⇒ 'y and
    ψ :: 'z ⇒ 'z and
    x :: 'x
  assume
    x-in-X: x ∈ S and
    χ-img-f-img-g-in-t: χ ' f ' S ⊆ T and
    act-f: (φ, χ) ∈ τ and
    act-g: (χ, ψ) ∈ v
  hence f x ∈ T ∧ χ (f x) ∈ T
  using assms
  by blast
  hence ψ (g (f x)) = g (χ (f x))
  using act-g assms
  by fastforce
  also have g (f (φ x)) = g (χ (f x))
  using assms act-f x-in-X
  by fastforce
  finally show g (f (φ x)) = ψ (g (f x))
  by simp
qed

lemma equivar-ind-by-action-comp:

```



**fixes**  
 $f :: 'x \Rightarrow 'y$  **and**  
 $g :: 'y \Rightarrow 'z$  **and**  
 $S :: 'w \text{ set}$  **and**  
 $T :: 'x \text{ set}$  **and**  
 $U :: 'y \text{ set}$  **and**  
 $\varphi :: ('w, 'x) \text{ binary-fun}$  **and**  
 $\chi :: ('w, 'y) \text{ binary-fun}$  **and**  
 $\psi :: ('w, 'z) \text{ binary-fun}$   
**assumes**  
 $f \text{ ' } T \subseteq U$  **and**  
 $\forall x \in S. \chi x \text{ ' } f \text{ ' } T \subseteq U$  **and**  
 $\text{is-symmetry } f \text{ (action-induced-equivariance } S \ T \ \varphi \ \chi)$  **and**  
 $\text{is-symmetry } g \text{ (action-induced-equivariance } S \ U \ \chi \ \psi)$   
**shows**  $\text{is-symmetry } (g \circ f) \text{ (action-induced-equivariance } S \ T \ \varphi \ \psi)$   
**proof** –  
**let**  $?a_\varphi = \{(\varphi \ a, \chi \ a) \mid a. a \in S\}$  **and**  
 $?a_\psi = \{(\chi \ a, \psi \ a) \mid a. a \in S\}$   
**have**  $\forall a \in S. (\varphi \ a, \chi \ a) \in \{(\varphi \ a, \chi \ a) \mid b. b \in S\}$   
 $\wedge (\chi \ a, \psi \ a) \in \{(\chi \ b, \psi \ b) \mid b. b \in S\} \wedge \chi \ a \text{ ' } f \text{ ' } T \subseteq U$   
**using** *assms*  
**by** *blast*  
**hence**  $\{(\varphi \ a, \psi \ a) \mid a. a \in S\}$   
 $\subseteq \{(\varphi, \psi). \exists v. (\varphi, v) \in ?a_\varphi \wedge (v, \psi) \in ?a_\psi \wedge v \text{ ' } f \text{ ' } T \subseteq U\}$   
**by** *blast*  
**hence**  $\text{is-symmetry } (g \circ f) \text{ (Equivariance } T \ \{(\varphi \ a, \psi \ a) \mid a. a \in S\})$   
**using** *assms equivar-comp[of - - - ?a<sub>φ</sub> - ?a<sub>ψ</sub>] equivar-under-subset'*  
**unfolding** *action-induced-equivariance-def*  
**by** (*metis (no-types, lifting)*)  
**thus** *?thesis*  
**unfolding** *action-induced-equivariance-def*  
**by** *blast*  
**qed**

**lemma** *equivar-set-minus:*

**fixes**  
 $f \ g :: 'x \Rightarrow 'y \text{ set}$  **and**  
 $S :: 'z \text{ set}$  **and**  
 $T :: 'x \text{ set}$  **and**  
 $\varphi :: ('z, 'x) \text{ binary-fun}$  **and**  
 $\psi :: ('z, 'y) \text{ binary-fun}$   
**assumes**  
 $f\text{-equivar: is-symmetry } f \text{ (action-induced-equivariance } S \ T \ \varphi \text{ (set-action } \psi))$   
**and**  
 $g\text{-equivar: is-symmetry } g \text{ (action-induced-equivariance } S \ T \ \varphi \text{ (set-action } \psi))$   
**and**  
 $\text{bij-}a: \forall a \in S. \text{bij } (\psi \ a)$   
**shows**  
 $\text{is-symmetry } (\lambda b. f \ b - g \ b) \text{ (action-induced-equivariance } S \ T \ \varphi \text{ (set-action } \psi))$

```

proof –
  have
     $\forall a \in S. \forall x \in T. f (\varphi a x) = \psi a ' (f x)$  and
     $\forall a \in S. \forall x \in T. g (\varphi a x) = \psi a ' (g x)$ 
    using f-equivar g-equivar
    unfolding rewrite-equivariance
    by (simp, simp)
  hence  $\forall a \in S. \forall b \in T. f (\varphi a b) - g (\varphi a b) = \psi a ' (f b) - \psi a ' (g b)$ 
    by blast
  moreover have  $\forall a \in S. \forall u v. \psi a ' u - \psi a ' v = \psi a ' (u - v)$ 
    using bij-a image-set-diff
    unfolding bij-def
    by blast
  ultimately show ?thesis
    unfolding set-action.simps
    using rewrite-equivariance
    by fastforce
qed

lemma equivar-union-under-image-action:
  fixes
     $f :: 'x \Rightarrow 'y$  and
     $S :: 'z \text{ set}$  and
     $\varphi :: ('z, 'x) \text{ binary-fun}$ 
  shows is-symmetry  $\bigcup (action-induced-equivariance S UNIV$ 
     $(set-action (set-action \varphi)) (set-action \varphi))$ 
  unfolding action-induced-equivariance-def is-symmetry.simps set-action.simps
  by blast

end

```

## 1.10 Symmetry Properties of Voting Rules

```

theory Voting-Symmetry
  imports Symmetry-Of-Functions
    Social-Choice-Result
    Social-Welfare-Result
    Profile
begin

```

### 1.10.1 Definitions

```

fun result-action ::  $('x, 'r) \text{ binary-fun} \Rightarrow ('x, 'r \text{ Result}) \text{ binary-fun}$  where
  result-action  $\psi x = (\lambda r. (\psi x ' \text{elect-r } r, \psi x ' \text{reject-r } r, \psi x ' \text{defer-r } r))$ 

```

## Anonymity

Bijection group on the set of voters.

**definition**  $bijection_{\mathcal{VG}} :: ('v \Rightarrow 'v) \text{ monoid } \mathbf{where}$   
 $bijection_{\mathcal{VG}} \equiv BijGroup (UNIV :: 'v \text{ set})$

Permutation action on the set of voters. Invariance under this action implies anonymity.

**fun**  $\varphi\text{-anon} :: ('a, 'v) \text{ Election set} \Rightarrow ('v \Rightarrow 'v) \Rightarrow$   
 $(( 'a, 'v) \text{ Election} \Rightarrow ('a, 'v) \text{ Election}) \mathbf{where}$   
 $\varphi\text{-anon } \mathcal{E} \pi = \text{extensional-continuation } (\text{rename } \pi) \mathcal{E}$

**fun**  $\text{anonymity}_{\mathcal{R}} :: ('a, 'v) \text{ Election set} \Rightarrow ('a, 'v) \text{ Election rel } \mathbf{where}$   
 $\text{anonymity}_{\mathcal{R}} \mathcal{E} = \text{action-induced-rel } (\text{carrier } bijection_{\mathcal{VG}}) \mathcal{E} (\varphi\text{-anon } \mathcal{E})$

## Neutrality

**fun**  $\text{rel-rename} :: ('a \Rightarrow 'a, 'a \text{ Preference-Relation}) \text{ binary-fun } \mathbf{where}$   
 $\text{rel-rename } \pi r = \{(\pi a, \pi b) \mid a b. (a, b) \in r\}$

**fun**  $\text{alternatives-rename} :: ('a \Rightarrow 'a, ('a, 'v) \text{ Election}) \text{ binary-fun } \mathbf{where}$   
 $\text{alternatives-rename } \pi \mathcal{E} =$   
 $(\pi \text{ ' } (\text{alternatives-}\mathcal{E} \mathcal{E}), \text{voters-}\mathcal{E} \mathcal{E}, (\text{rel-rename } \pi) \circ (\text{profile-}\mathcal{E} \mathcal{E}))$

Bijection group on the set of alternatives. Invariance under this action implies neutrality.

**definition**  $bijection_{\mathcal{AG}} :: ('a \Rightarrow 'a) \text{ monoid } \mathbf{where}$   
 $bijection_{\mathcal{AG}} \equiv BijGroup (UNIV :: 'a \text{ set})$

Permutation action on the set of alternatives.

**fun**  $\varphi\text{-neutral} :: ('a, 'v) \text{ Election set} \Rightarrow$   
 $('a \Rightarrow 'a, ('a, 'v) \text{ Election}) \text{ binary-fun } \mathbf{where}$   
 $\varphi\text{-neutral } \mathcal{E} \pi = \text{extensional-continuation } (\text{alternatives-rename } \pi) \mathcal{E}$

**fun**  $\text{neutrality}_{\mathcal{R}} :: ('a, 'v) \text{ Election set} \Rightarrow ('a, 'v) \text{ Election rel } \mathbf{where}$   
 $\text{neutrality}_{\mathcal{R}} \mathcal{E} = \text{action-induced-rel } (\text{carrier } bijection_{\mathcal{AG}}) \mathcal{E} (\varphi\text{-neutral } \mathcal{E})$

**fun**  $\psi\text{-neutral}_c :: ('a \Rightarrow 'a, 'a) \text{ binary-fun } \mathbf{where}$   
 $\psi\text{-neutral}_c \pi r = \pi r$

**fun**  $\psi\text{-neutral}_w :: ('a \Rightarrow 'a, 'a \text{ rel}) \text{ binary-fun } \mathbf{where}$   
 $\psi\text{-neutral}_w \pi r = \text{rel-rename } \pi r$

## Homogeneity

**fun**  $\text{homogeneity}_{\mathcal{R}} :: ('a, 'v) \text{ Election set} \Rightarrow ('a, 'v) \text{ Election rel } \mathbf{where}$   
 $\text{homogeneity}_{\mathcal{R}} \mathcal{E} =$   
 $\{(E, E'). E \in \mathcal{E}\}$

$$\begin{aligned}
& \wedge \text{alternatives-}\mathcal{E} \ E = \text{alternatives-}\mathcal{E} \ E' \\
& \wedge \text{finite} \ (\text{voters-}\mathcal{E} \ E) \wedge \text{finite} \ (\text{voters-}\mathcal{E} \ E') \\
& \wedge (\exists \ n > 0. \forall \ r :: 'a \text{ Preference-Relation.} \\
& \quad \text{vote-count } r \ E = n * (\text{vote-count } r \ E'))
\end{aligned}$$

**fun** *copy-list* :: *nat*  $\Rightarrow$  *'x list*  $\Rightarrow$  *'x list* **where**  
*copy-list* 0 *l* = [] |  
*copy-list* (Suc *n*) *l* = *copy-list* *n* *l* @ *l*

**fun** *homogeneity<sub>R</sub>'* :: (*'a*, *'v* :: *linorder*) *Election set*  $\Rightarrow$  (*'a*, *'v*) *Election rel* **where**  
*homogeneity<sub>R</sub>'*  $\mathcal{E}$  =  
 {(*E*, *E'*). *E*  $\in$   $\mathcal{E}$   
 $\wedge$  *alternatives- $\mathcal{E}$*  *E* = *alternatives- $\mathcal{E}$*  *E'*  
 $\wedge$  *finite* (*voters- $\mathcal{E}$*  *E*)  $\wedge$  *finite* (*voters- $\mathcal{E}$*  *E'*)  
 $\wedge$  ( $\exists \ n > 0.$   
     *to-list* (*voters- $\mathcal{E}$*  *E'*) (*profile- $\mathcal{E}$*  *E'*) =

*copy-list* *n* (*to-list* (*voters- $\mathcal{E}$*  *E*) (*profile- $\mathcal{E}$*  *E*)))}

## Reversal Symmetry

**fun** *reverse-rel* :: *'a rel*  $\Rightarrow$  *'a rel* **where**  
*reverse-rel* *r* = {(*a*, *b*). (*b*, *a*)  $\in$  *r*}

**fun** *rel-app* :: (*'a rel*  $\Rightarrow$  *'a rel*)  $\Rightarrow$  (*'a*, *'v*) *Election*  $\Rightarrow$  (*'a*, *'v*) *Election* **where**  
*rel-app* *f* (*A*, *V*, *p*) = (*A*, *V*, *f*  $\circ$  *p*)

**definition** *reversal<sub>G</sub>* :: (*'a rel*  $\Rightarrow$  *'a rel*) *monoid* **where**  
*reversal<sub>G</sub>*  $\equiv$  ( $\llbracket$  *carrier* = {*reverse-rel*, *id*}, *monoid.mult* = *comp*, *one* = *id*)

**fun**  $\varphi$ -*reverse* :: (*'a*, *'v*) *Election set*  
 $\Rightarrow$  (*'a rel*  $\Rightarrow$  *'a rel*, (*'a*, *'v*) *Election*) *binary-fun* **where**  
 $\varphi$ -*reverse*  $\mathcal{E}$   $\varphi$  = *extensional-continuation* (*rel-app*  $\varphi$ )  $\mathcal{E}$

**fun**  $\psi$ -*reverse* :: (*'a rel*  $\Rightarrow$  *'a rel*, *'a rel*) *binary-fun* **where**  
 $\psi$ -*reverse*  $\varphi$  *r* =  $\varphi$  *r*

**fun** *reversal<sub>R</sub>* :: (*'a*, *'v*) *Election set*  $\Rightarrow$  (*'a*, *'v*) *Election rel* **where**  
*reversal<sub>R</sub>*  $\mathcal{E}$  = *action-induced-rel* (*carrier reversal<sub>G</sub>*)  $\mathcal{E}$  ( $\varphi$ -*reverse*  $\mathcal{E}$ )

### 1.10.2 Auxiliary Lemmas

**fun** *n-app* :: *nat*  $\Rightarrow$  (*'x*  $\Rightarrow$  *'x*)  $\Rightarrow$  (*'x*  $\Rightarrow$  *'x*) **where**  
*n-app-id*: *n-app* 0 *f* = *id* |  
*n-app-suc*: *n-app* (Suc *n*) *f* = *f*  $\circ$  *n-app* *n* *f*

**lemma** *n-app-rewrite*:  
**fixes**  
*f* :: *'x*  $\Rightarrow$  *'x* **and**  
*n* :: *nat* **and**  
*x* :: *'x*

**shows**  $(f \circ n\text{-app } n f) x = (n\text{-app } n f \circ f) x$   
**proof** (*unfold comp-def, induction n f arbitrary: x rule: n-app.induct*)  
**case** (1 f)  
**fix**  
 $f :: 'x \Rightarrow 'x$  **and**  
 $x :: 'x$   
**show**  $f (n\text{-app } 0 f x) = n\text{-app } 0 f (f x)$   
**by** *simp*  
**next**  
**case** (2 n f)  
**fix**  
 $f :: 'x \Rightarrow 'x$  **and**  
 $n :: \text{nat}$  **and**  
 $x :: 'x$   
**assume**  $\bigwedge y. f (n\text{-app } n f y) = n\text{-app } n f (f y)$   
**thus**  $f (n\text{-app } (\text{Suc } n) f x) = n\text{-app } (\text{Suc } n) f (f x)$   
**by** *simp*  
**qed**

**lemma** *n-app-leaves-set:*

**fixes**  
 $A B :: 'x \text{ set}$  **and**  
 $f :: 'x \Rightarrow 'x$  **and**  
 $x :: 'x$   
**assumes**  
 $\text{fin-A: finite } A$  **and**  
 $\text{fin-B: finite } B$  **and**  
 $\text{x-el: } x \in A - B$  **and**  
 $\text{bij-f: bij-betw } f A B$   
**obtains**  $n :: \text{nat}$  **where**  
 $n > 0$  **and**  
 $n\text{-app } n f x \in B - A$  **and**  
 $\forall m > 0. m < n \longrightarrow n\text{-app } m f x \in A \cap B$   
**proof** –  
**have**  $n\text{-app-f-x-in-A: } n\text{-app } 0 f x \in A$   
**using** *x-el*  
**by** *simp*  
**moreover have** *ex-A:*  
 $\exists n > 0. n\text{-app } n f x \in B - A \wedge (\forall m > 0. m < n \longrightarrow n\text{-app } m f x \in A)$   
**proof** (*rule ccontr,*  
*unfold Diff-iff conj-assoc not-ex de-Morgan-conj not-gr-zero*  
*simp-thms not-all not-imp disj-not1 imp-disj2*)  
**assume** *nex:*  
 $\forall n. n\text{-app } n f x \in B$   
 $\longrightarrow n = 0 \vee n\text{-app } n f x \in A \vee (\exists m > 0. m < n \wedge n\text{-app } m f x \notin A)$   
**hence**  $\forall n > 0. n\text{-app } n f x \in B$   
 $\longrightarrow n\text{-app } n f x \in A \vee (\exists m > 0. m < n \wedge n\text{-app } m f x \notin A)$   
**by** *blast*  
**moreover have**  $\neg (\forall n > 0. n\text{-app } n f x \in B \longrightarrow n\text{-app } n f x \in A)$

```

proof (safe)
  assume in-A:  $\forall n > 0. n\text{-app } n \ f \ x \in B \longrightarrow n\text{-app } n \ f \ x \in A$ 
  hence  $\forall n > 0. n\text{-app } n \ f \ x \in A \longrightarrow n\text{-app } (Suc \ n) \ f \ x \in A$ 
    using n-app.simps bij-f
    unfolding bij-betw-def
    by force
  hence in-AB-imp-in-AB:
     $\forall n > 0. n\text{-app } n \ f \ x \in A \cap B \longrightarrow n\text{-app } (Suc \ n) \ f \ x \in A \cap B$ 
    using n-app.simps bij-f
    unfolding bij-betw-def
    by auto
  have in-int:  $\forall n > 0. n\text{-app } n \ f \ x \in A \cap B$ 
  proof (clarify)
    fix n :: nat
    assume  $n > 0$ 
    thus  $n\text{-app } n \ f \ x \in A \cap B$ 
    proof (induction n)
      case 0
      thus ?case
        by safe
    next
      case (Suc n)
      assume  $0 < n \implies n\text{-app } n \ f \ x \in A \cap B$ 
      moreover have  $n = 0 \longrightarrow n\text{-app } (Suc \ n) \ f \ x = f \ x$ 
        by simp
      ultimately show  $n\text{-app } (Suc \ n) \ f \ x \in A \cap B$ 
        using x-el bij-f in-A in-AB-imp-in-AB
        unfolding bij-betw-def
        by blast
    qed
  qed
  hence  $\{n\text{-app } n \ f \ x \mid n. n > 0\} \subseteq A \cap B$ 
    by blast
  hence finite  $\{n\text{-app } n \ f \ x \mid n. n > 0\}$ 
    using fin-A fin-B rev-finite-subset
    by blast
  moreover have
    inj-on  $(\lambda n. n\text{-app } n \ f \ x) \ \{n. n > 0\}$ 
       $\longrightarrow$  infinite  $((\lambda n. n\text{-app } n \ f \ x) \ \{n. n > 0\})$ 
    using diff-is-0-eq' finite-imageD finite-nat-set-iff-bounded lessI
      less-imp-diff-less mem-Collect-eq nless-le
    by metis
  moreover have  $(\lambda n. n\text{-app } n \ f \ x) \ \{n. n > 0\} = \{n\text{-app } n \ f \ x \mid n. n > 0\}$ 
    by auto
  ultimately have  $\exists n > 0. \exists m > n. n\text{-app } n \ f \ x = n\text{-app } m \ f \ x$ 
    using linorder-inj-onI' mem-Collect-eq
    by (metis (no-types, lifting))
  hence  $\exists n\text{-min} > 0.$ 
     $(\exists m > n\text{-min}. n\text{-app } n\text{-min} \ f \ x = n\text{-app } m \ f \ x)$ 

```

$\wedge (\forall n < n\text{-min}. \neg (0 < n \wedge (\exists m > n. n\text{-app } n \ f \ x = n\text{-app } m \ f \ x)))$   
**using** *exists-least-iff*[*of*  
 $\lambda n. n > 0 \wedge (\exists m > n. n\text{-app } n \ f \ x = n\text{-app } m \ f \ x)$ ]  
**by** *presburger*  
**then obtain**  $n\text{-min} :: \text{nat}$  **where**  
 $n\text{-min-pos}: n\text{-min} > 0$  **and**  
 $ex\text{-gt-}n\text{-min}: \exists m > n\text{-min}. n\text{-app } n\text{-min} \ f \ x = n\text{-app } m \ f \ x$  **and**  
 $neq: \forall n < n\text{-min}. \neg (n > 0 \wedge (\exists m > n. n\text{-app } n \ f \ x = n\text{-app } m \ f \ x))$   
**by** *blast*  
**then obtain**  $m :: \text{nat}$  **where**  
 $m\text{-gt-}n\text{-min}: m > n\text{-min}$  **and**  
 $n\text{-app-}n\text{-min-eq}: n\text{-app } n\text{-min} \ f \ x = f \ (n\text{-app } (m - 1) \ f \ x)$   
**using** *comp-apply diff-Suc-1 less-nat-zero-code n-app.elims*  
**by** (*metis (mono-tags, lifting)*)  
**moreover have**  $n\text{-app } n\text{-min} \ f \ x = f \ (n\text{-app } (n\text{-min} - 1) \ f \ x)$   
**using** *Suc-pred' n-min-pos comp-eq-id-dest id-comp diff-Suc-1*  
 $less\text{-nat-zero-code } n\text{-app.elims}$   
**by** (*metis (mono-tags, opaque-lifting)*)  
**moreover have**  $n\text{-app } (m - 1) \ f \ x \in A \wedge n\text{-app } (n\text{-min} - 1) \ f \ x \in A$   
**using** *in-int x-el n-min-pos m-gt-n-min Diff-iff IntD1 diff-le-self id-apply*  
 $nless\text{-le cancel-comm-monoid-add-class.diff-cancel } n\text{-app-id}$   
**by** *metis*  
**ultimately have**  $n\text{-app } (m - 1) \ f \ x = n\text{-app } (n\text{-min} - 1) \ f \ x$   
**using** *bij-f*  
**unfolding** *bij-betw-def inj-def inj-on-def*  
**by** *simp*  
**moreover have**  $m - 1 > n\text{-min} - 1$   
**using** *m-gt-n-min n-min-pos*  
**by** *simp*  
**moreover have**  $n\text{-app } (m - 1) \ f \ x \in B$   
**using** *in-int m-gt-n-min n-min-pos*  
**by** *simp*  
**ultimately show** *False*  
**using** *x-el neq n-min-pos diff-less zero-less-one Diff-iff*  
 $bot\text{-nat-0.not-eq-extremum id-apply } n\text{-app-id}$   
**by** *metis*  
**qed**  
**ultimately obtain**  $n :: \text{nat}$  **where**  
 $n\text{-pos}: n > 0$  **and**  
 $not\text{-in-}A: n\text{-app } n \ f \ x \notin A$  **and**  
 $less\text{-in-}A: \forall m. (0 < m \wedge m < n) \longrightarrow n\text{-app } m \ f \ x \in A$   
**using** *exists-least-iff*[*of*  $\lambda n. n > 0 \wedge n\text{-app } n \ f \ x \notin A$ ]  
**by** *blast*  
**hence**  $n\text{-app } (n - 1) \ f \ x \in A$   
**using** *n-app-f-x-in-A bot-nat-0.not-eq-extremum diff-less zero-less-one*  
**by** *metis*  
**moreover have**  $n\text{-app } n \ f \ x = f \ (n\text{-app } (n - 1) \ f \ x)$   
**using** *n-app-suc Suc-pred' n-pos comp-eq-id-dest fun.map-id*  
**by** (*metis (mono-tags, opaque-lifting)*)

```

ultimately show False
  using bij-f nex not-in-A n-pos less-in-A
  unfolding bij-betw-def
  by blast
qed
ultimately have
   $\forall n. (\forall m > 0. m < n \longrightarrow n\text{-app } m \ f \ x \in A)$ 
     $\longrightarrow (\forall m > 0. m < n \longrightarrow n\text{-app } (m - 1) \ f \ x \in A)$ 
  using bot-nat-0.not-eq-extremum less-imp-diff-less
  by metis
moreover have  $\forall m > 0. n\text{-app } m \ f \ x = f \ (n\text{-app } (m - 1) \ f \ x)$ 
  using bot-nat-0.not-eq-extremum comp-apply diff-Suc-1 n-app.elims
  by (metis (mono-tags, lifting))
ultimately show ?thesis
  using that bij-f imageI IntI ex-A
  unfolding bij-betw-def
  by metis
qed

lemma n-app-rev:
  fixes
     $A \ B :: 'x \ \text{set}$  and
     $f :: 'x \Rightarrow 'x$  and
     $m \ n :: \text{nat}$  and
     $x \ y :: 'x$ 
  assumes
    x-in-A:  $x \in A$  and
    y-in-A:  $y \in A$  and
    n-geq-m:  $n \geq m$  and
    n-app-eq-m-n:  $n\text{-app } n \ f \ x = n\text{-app } m \ f \ y$  and
    n-app-x-in-A:  $\forall n' < n. n\text{-app } n' \ f \ x \in A$  and
    n-app-y-in-A:  $\forall m' < m. n\text{-app } m' \ f \ y \in A$  and
    fin-A: finite A and
    fin-B: finite B and
    bij-f-A-B: bij-betw f A B
  shows  $n\text{-app } (n - m) \ f \ x = y$ 
  using assms
proof (induction n f arbitrary: m x y rule: n-app.induct)
case (1 f)
fix
   $f :: 'x \Rightarrow 'x$  and
   $m :: \text{nat}$  and
   $x \ y :: 'x$ 
assume
   $m \leq 0$  and
   $n\text{-app } 0 \ f \ x = n\text{-app } m \ f \ y$ 
thus  $n\text{-app } (0 - m) \ f \ x = y$ 
  by simp
next

```



**case** ( $2\ n\ f$ )  
**fix**  
 $f :: 'x \Rightarrow 'x$  **and**  
 $m\ n :: nat$  **and**  
 $x\ y :: 'x$   
**assume**  
 $bij\text{-}f$ :  $bij\text{-}betw\ f\ A\ B$  **and**  
 $x\text{-in-}A$ :  $x \in A$  **and**  
 $y\text{-in-}A$ :  $y \in A$  **and**  
 $m\text{-leq-suc-}n$ :  $m \leq Suc\ n$  **and**  
 $x\text{-dom}$ :  $\forall\ n' < Suc\ n. n\text{-app}\ n'\ f\ x \in A$  **and**  
 $y\text{-dom}$ :  $\forall\ m' < m. n\text{-app}\ m'\ f\ y \in A$  **and**  
 $eq$ :  $n\text{-app}\ (Suc\ n)\ f\ x = n\text{-app}\ m\ f\ y$  **and**  
 $hyp$ :  
 $\bigwedge\ m\ x\ y.$   
 $x \in A \implies$   
 $y \in A \implies$   
 $m \leq n \implies$   
 $n\text{-app}\ n\ f\ x = n\text{-app}\ m\ f\ y \implies$   
 $\forall\ n' < n. n\text{-app}\ n'\ f\ x \in A \implies$   
 $\forall\ m' < m. n\text{-app}\ m'\ f\ y \in A \implies$   
 $finite\ A \implies finite\ B \implies bij\text{-}betw\ f\ A\ B \implies n\text{-app}\ (n - m)\ f\ x = y$   
**hence**  $m > 0 \longrightarrow f\ (n\text{-app}\ n\ f\ x) = f\ (n\text{-app}\ (m - 1)\ f\ y)$   
**using**  $Suc\text{-pred' comp-apply}\ n\text{-app-suc}$   
**by** ( $metis\ (mono\text{-}tags,\ opaque\text{-}lifting)$ )  
**moreover have**  $n\text{-app}\ n\ f\ x \in A$   
**using**  $x\text{-in-}A\ x\text{-dom}$   
**by**  $blast$   
**moreover have**  $m > 0 \longrightarrow n\text{-app}\ (m - 1)\ f\ y \in A$   
**using**  $y\text{-dom}$   
**by**  $simp$   
**ultimately have**  $m > 0 \longrightarrow n\text{-app}\ n\ f\ x = n\text{-app}\ (m - 1)\ f\ y$   
**using**  $bij\text{-}f$   
**unfolding**  $bij\text{-}betw\text{-}def\ inj\text{-}on\text{-}def$   
**by**  $blast$   
**moreover have**  $m - 1 \leq n$   
**using**  $m\text{-leq-suc-}n$   
**by**  $simp$   
**hence**  $m > 0 \longrightarrow n\text{-app}\ (n - (m - 1))\ f\ x = y$   
**using**  $hyp\ x\text{-in-}A\ y\text{-in-}A\ x\text{-dom}\ y\text{-dom}\ Suc\text{-pred}\ fin\text{-}A\ fin\text{-}B$   
 $bij\text{-}f\ calculation\ less\text{-}SucI$   
**unfolding**  $One\text{-}nat\text{-}def$   
**by**  $metis$   
**thus**  $n\text{-app}\ (Suc\ n - m)\ f\ x = y$   
**using**  $eq$   
**by**  $force$   
**qed**

**lemma**  $n\text{-app-inv}$ :

```

fixes
   $A\ B :: 'x\ set$  and
   $f :: 'x \Rightarrow 'x$  and
   $n :: nat$  and
   $x :: 'x$ 
assumes
   $x \in B$  and
   $\forall\ m \geq 0. m < n \longrightarrow n\text{-app}\ m\ (the\text{-inv-into}\ A\ f)\ x \in B$  and
   $bij\text{-betw}\ f\ A\ B$ 
shows  $n\text{-app}\ n\ f\ (n\text{-app}\ n\ (the\text{-inv-into}\ A\ f)\ x) = x$ 
using assms
proof (induction n f arbitrary: x rule: n-app.induct)
  case (1  $f$ )
  fix  $f :: 'x \Rightarrow 'x$ 
  show ?case
    by simp
next
  case (2  $n\ f$ )
  fix
     $n :: nat$  and
     $f :: 'x \Rightarrow 'x$  and
     $x :: 'x$ 
  assume
     $x\text{-in-}B: x \in B$  and
     $bij\text{-}f: bij\text{-betw}\ f\ A\ B$  and
     $stays\text{-in-}B: \forall\ m \geq 0. m < Suc\ n \longrightarrow n\text{-app}\ m\ (the\text{-inv-into}\ A\ f)\ x \in B$  and
     $hyp: \bigwedge\ x. x \in B \Longrightarrow$ 
       $\forall\ m \geq 0. m < n \longrightarrow n\text{-app}\ m\ (the\text{-inv-into}\ A\ f)\ x \in B \Longrightarrow$ 
       $bij\text{-betw}\ f\ A\ B \Longrightarrow n\text{-app}\ n\ f\ (n\text{-app}\ n\ (the\text{-inv-into}\ A\ f)\ x) = x$ 
  have  $n\text{-app}\ (Suc\ n)\ f\ (n\text{-app}\ (Suc\ n)\ (the\text{-inv-into}\ A\ f)\ x) =$ 
     $n\text{-app}\ n\ f\ (f\ (n\text{-app}\ (Suc\ n)\ (the\text{-inv-into}\ A\ f)\ x))$ 
    using n-app-rewrite
    by simp
  also have  $\dots = n\text{-app}\ n\ f\ (n\text{-app}\ n\ (the\text{-inv-into}\ A\ f)\ x)$ 
    using stays-in-B bij-f
    by (simp add: f-the-inv-into-f-bij-betw)
  finally show  $n\text{-app}\ (Suc\ n)\ f\ (n\text{-app}\ (Suc\ n)\ (the\text{-inv-into}\ A\ f)\ x) = x$ 
    using hyp bij-f stays-in-B x-in-B
    by simp
qed

```

**lemma** *bij-betw-finite-ind-global-bij:*

```

fixes
   $A\ B :: 'x\ set$  and
   $f :: 'x \Rightarrow 'x$ 
assumes
   $fin\text{-}A: finite\ A$  and
   $fin\text{-}B: finite\ B$  and
   $bij\text{-}f: bij\text{-betw}\ f\ A\ B$ 

```

**obtains**  $g :: 'x \Rightarrow 'x$  **where**  
   **bij**  $g$  **and**  
    $\forall a \in A. g\ a = f\ a$  **and**  
    $\forall b \in B - A. g\ b \in A - B \wedge (\exists n > 0. n\text{-app}\ n\ f\ (g\ b) = b)$  **and**  
    $\forall x \in UNIV - A - B. g\ x = x$   
**proof** –  
   **assume** *existence-witness*:  
      $\bigwedge g. \text{bij}\ g \implies$   
        $\forall a \in A. g\ a = f\ a \implies$   
        $\forall b \in B - A. g\ b \in A - B \wedge (\exists n > 0. n\text{-app}\ n\ f\ (g\ b) = b) \implies$   
        $\forall x \in UNIV - A - B. g\ x = x \implies ?thesis$   
   **have** *bij-inv*: *bij-betw* (*the-inv-into*  $A\ f$ )  $B\ A$   
     **using** *bij-f bij-betw-the-inv-into*  
     **by** *blast*  
   **then obtain**  $g' :: 'x \Rightarrow nat$  **where**  
      $g'\text{-greater-zero}$ :  $\forall x \in B - A. g'\ x > 0$  **and**  
      $in\text{-set-diff}$ :  $\forall x \in B - A. n\text{-app}\ (g'\ x)\ (the\text{-inv-into}\ A\ f)\ x \in A - B$  **and**  
      $minimal$ :  $\forall x \in B - A. \forall n > 0.$   
        $n < g'\ x \longrightarrow n\text{-app}\ n\ (the\text{-inv-into}\ A\ f)\ x \in B \cap A$   
     **using** *n-app-leaves-set fin-A fin-B*  
     **by** *metis*  
   **obtain**  $g :: 'x \Rightarrow 'x$  **where**  
      $def\text{-}g$ :  
        $g = (\lambda x. \text{if } x \in A \text{ then } f\ x \text{ else}$   
          $\text{if } x \in B - A \text{ then } n\text{-app}\ (g'\ x)\ (the\text{-inv-into}\ A\ f)\ x \text{ else } x)$   
     **by** *simp*  
   **hence** *coincide*:  $\forall a \in A. g\ a = f\ a$   
     **by** *simp*  
   **have** *id*:  $\forall x \in UNIV - A - B. g\ x = x$   
     **using** *def-g*  
     **by** *simp*  
   **have**  $\forall x \in B - A. n\text{-app}\ 0\ (the\text{-inv-into}\ A\ f)\ x \in B$   
     **by** *simp*  
   **moreover have**  
      $\forall x \in B - A. \forall n > 0.$   
        $n < g'\ x \longrightarrow n\text{-app}\ n\ (the\text{-inv-into}\ A\ f)\ x \in B$   
     **using** *minimal*  
     **by** *blast*  
   **ultimately have**  
      $\forall x \in B - A. n\text{-app}\ (g'\ x)\ f\ (n\text{-app}\ (g'\ x)\ (the\text{-inv-into}\ A\ f)\ x) = x$   
     **using** *n-app-inv bij-f DiffD1 antisym-conv2*  
     **by** *metis*  
   **hence**  $\forall x \in B - A. n\text{-app}\ (g'\ x)\ f\ (g\ x) = x$   
     **using** *def-g*  
     **by** *simp*  
   **with**  $g'\text{-greater-zero}\ in\text{-set-diff}$   
   **have** *reverse*:  $\forall x \in B - A. g\ x \in A - B \wedge (\exists n > 0. n\text{-app}\ n\ f\ (g\ x) = x)$   
     **using** *def-g*  
     **by** *auto*

**have**  $\forall x \in UNIV - A - B. g\ x = id\ x$   
**using** *def-g*  
**by** *simp*  
**hence**  $g\ ' (UNIV - A - B) = UNIV - A - B$   
**by** *simp*  
**moreover have**  $g\ ' A = B$   
**using** *def-g bij-f*  
**unfolding** *bij-betw-def*  
**by** *simp*  
**moreover have**  $A \cup (UNIV - A - B) = UNIV - (B - A)$   
 $\wedge B \cup (UNIV - A - B) = UNIV - (A - B)$   
**by** *blast*  
**ultimately have** *surj-cases*:  $g\ ' (UNIV - (B - A)) = UNIV - (A - B)$   
**using** *image-Un*  
**by** *metis*  
**have**  $inj\text{-}on\ g\ A \wedge inj\text{-}on\ g\ (UNIV - A - B)$   
**using** *def-g bij-f*  
**unfolding** *bij-betw-def inj-on-def*  
**by** *simp*  
**hence** *inj-cases*:  $inj\text{-}on\ g\ (UNIV - (B - A))$   
**unfolding** *inj-on-def*  
**using** *DiffD2 DiffI bij-f bij-betwE def-g*  
**by** (*metis* (*no-types*, *lifting*))  
**have**  $card\ A = card\ B$   
**using** *fin-A fin-B bij-f bij-betw-same-card*  
**by** *blast*  
**with** *fin-A fin-B*  
**have**  $finite\ (B - A) \wedge finite\ (A - B) \wedge card\ (B - A) = card\ (A - B)$   
**using** *card-le-sym-Diff finite-Diff2 nle-le*  
**by** *metis*  
**moreover have**  $(\lambda x. n\text{-}app\ (g'\ x)\ (the\text{-}inv\text{-}into\ A\ f)\ x)\ ' (B - A) \subseteq A - B$   
**using** *in-set-diff*  
**by** *blast*  
**moreover have**  $inj\text{-}on\ (\lambda x. n\text{-}app\ (g'\ x)\ (the\text{-}inv\text{-}into\ A\ f)\ x)\ (B - A)$   
**proof** (*unfold inj-on-def, safe*)  
**fix**  $x\ y :: 'x$   
**assume**  
 $x\text{-}in\text{-}B$ :  $x \in B$  **and**  
 $x\text{-}not\text{-}in\text{-}A$ :  $x \notin A$  **and**  
 $y\text{-}in\text{-}B$ :  $y \in B$  **and**  
 $y\text{-}not\text{-}in\text{-}A$ :  $y \notin A$  **and**  
 $n\text{-}app\ (g'\ x)\ (the\text{-}inv\text{-}into\ A\ f)\ x = n\text{-}app\ (g'\ y)\ (the\text{-}inv\text{-}into\ A\ f)\ y$   
**moreover from this have**  
 $\forall n < g'\ x. n\text{-}app\ n\ (the\text{-}inv\text{-}into\ A\ f)\ x \in B$  **and**  
 $\forall n < g'\ y. n\text{-}app\ n\ (the\text{-}inv\text{-}into\ A\ f)\ y \in B$   
**using** *minimal Diff-iff Int-iff bot-nat-0.not-eq-extremum eq-id-iff n-app-id*  
**by** (*metis*, *metis*)  
**ultimately have** *x-to-y*:  
 $n\text{-}app\ (g'\ x - g'\ y)\ (the\text{-}inv\text{-}into\ A\ f)\ x = y$

$\vee n\text{-app } (g' y - g' x) (\text{the-inv-into } A f) y = x$   
**using**  $x\text{-in-}B \ y\text{-in-}B \ \text{bij-inv } \text{fin-}A \ \text{fin-}B$   
 $n\text{-app-rev}[\text{of } x] \ n\text{-app-rev}[\text{of } y \ B \ x \ g' x \ g' y]$   
**by** *fastforce*  
**hence**  $g' x \neq g' y \longrightarrow$   
 $((\exists n > 0. n < g' x \wedge n\text{-app } n (\text{the-inv-into } A f) x \in B - A) \vee$   
 $(\exists n > 0. n < g' y \wedge n\text{-app } n (\text{the-inv-into } A f) y \in B - A))$   
**using**  $g'\text{-greater-zero } x\text{-in-}B \ x\text{-not-in-}A \ y\text{-in-}B \ y\text{-not-in-}A \ \text{Diff-iff}$   
 $\text{diff-less-mono2 } \text{diff-zero } \text{id-apply } \text{less-Suc-eq-0-disj } n\text{-app.elims}$   
**by** (*metis* (*full-types*))  
**thus**  $x = y$   
**using**  $\text{minimal } x\text{-in-}B \ x\text{-not-in-}A \ y\text{-in-}B \ y\text{-not-in-}A \ x\text{-to-}y$   
**by** *force*  
**qed**  
**ultimately have**  
 $\text{bij-betw } (\lambda x. n\text{-app } (g' x) (\text{the-inv-into } A f) x) (B - A) (A - B)$   
**unfolding**  $\text{bij-betw-def}$   
**by** (*simp add: card-image card-subset-eq*)  
**hence**  $\text{bij-case: } \text{bij-betw } g (B - A) (A - B)$   
**using**  $\text{def-g}$   
**unfolding**  $\text{bij-betw-def } \text{inj-on-def}$   
**by** *simp*  
**hence**  $g \text{ ' } UNIV = UNIV$   
**using**  $\text{surj-cases } Un\text{-Diff-cancel2 } \text{image-Un } \text{sup-top-left}$   
**unfolding**  $\text{bij-betw-def}$   
**by** *metis*  
**moreover have**  $\text{inj } g$   
**using**  $\text{inj-cases } \text{bij-case } \text{DiffD2 } \text{DiffI } \text{imageI } \text{surj-cases}$   
**unfolding**  $\text{bij-betw-def } \text{inj-def } \text{inj-on-def}$   
**by** *metis*  
**ultimately have**  $\text{bij } g$   
**unfolding**  $\text{bij-def}$   
**by** *safe*  
**thus** *?thesis*  
**using**  $\text{coincide id reverse existence-witness}$   
**by** *blast*  
**qed**  
**lemma**  $\text{bij-betw-ext:}$   
**fixes**  
 $f :: 'x \Rightarrow 'y$  **and**  
 $X :: 'x \text{ set}$  **and**  
 $Y :: 'y \text{ set}$   
**assumes**  $\text{bij-betw } f \ X \ Y$   
**shows**  $\text{bij-betw } (\text{extensional-continuation } f \ X) \ X \ Y$   
**proof** –  
**have**  $\forall x \in X. \text{extensional-continuation } f \ X \ x = f \ x$   
**by** *simp*  
**thus** *?thesis*

using *assms bij-betw-cong*  
 by *metis*  
 qed

### 1.10.3 Anonymity Lemmas

**lemma** *anon-rel-vote-count*:

**fixes**

$\mathcal{E} :: ('a, 'v)$  *Election set* **and**

$E\ E' :: ('a, 'v)$  *Election*

**assumes**

*finite (voters- $\mathcal{E}$   $E$ )* **and**

$(E, E') \in \text{anonymity}_{\mathcal{R}}\ \mathcal{E}$

**shows** *alternatives- $\mathcal{E}$   $E = \text{alternatives-}\mathcal{E}\ E' \wedge E \in \mathcal{E}$*   
 $\wedge (\forall p. \text{vote-count } p\ E = \text{vote-count } p\ E')$

**proof** –

**have**  $E \in \mathcal{E}$

using *assms*

unfolding *anonymity $_{\mathcal{R}}$ .sims action-induced-rel.sims*

by *safe*

**with** *assms*

**obtain**  $\pi :: 'v \Rightarrow 'v$  **where**

*bijection- $\pi$ : bij  $\pi$*  **and**

*renamed:  $E' = \text{rename } \pi\ E$*

unfolding *anonymity $_{\mathcal{R}}$ .sims bijection $_{\mathcal{V}\mathcal{G}}$ -def*

using *universal-set-carrier-imp-bij-group*

by *auto*

**have** *eq-alts: alternatives- $\mathcal{E}$   $E' = \text{alternatives-}\mathcal{E}\ E$*

using *eq-fst-iff rename.sims alternatives- $\mathcal{E}$ .elims renamed*

by (*metis (no-types)*)

**have**  $\forall v \in \text{voters-}\mathcal{E}\ E'. (\text{profile-}\mathcal{E}\ E')\ v = (\text{profile-}\mathcal{E}\ E) (\text{the-inv } \pi\ v)$

unfolding *profile- $\mathcal{E}$ .sims*

using *renamed rename.sims comp-apply prod.collapse snd-conv*

by (*metis (no-types, lifting)*)

**hence** *rewrite:*

$\forall p. \{v \in (\text{voters-}\mathcal{E}\ E'). (\text{profile-}\mathcal{E}\ E')\ v = p\} =$

$\{v \in (\text{voters-}\mathcal{E}\ E'). (\text{profile-}\mathcal{E}\ E) (\text{the-inv } \pi\ v) = p\}$

by *blast*

**have**  $\forall v \in \text{voters-}\mathcal{E}\ E'. \text{the-inv } \pi\ v \in \text{voters-}\mathcal{E}\ E$

unfolding *voters- $\mathcal{E}$ .sims*

using *renamed UNIV-I bijection- $\pi$  bij-betw-imp-surj bij-is-inj f-the-inv-into-f*

*prod.sel inj-image-mem-iff prod.collapse rename.sims*

by (*metis (no-types, lifting)*)

**hence**

$\forall p. \forall v \in \text{voters-}\mathcal{E}\ E'. (\text{profile-}\mathcal{E}\ E) (\text{the-inv } \pi\ v) = p$

$\longrightarrow v \in \pi^{-1} \{v \in \text{voters-}\mathcal{E}\ E. (\text{profile-}\mathcal{E}\ E) v = p\}$

using *bijection- $\pi$  f-the-inv-into-f-bij-betw image-iff*

by *fastforce*

**hence** *subset:*

$\forall p. \{v \in \text{voters-}\mathcal{E} \ E'. (\text{profile-}\mathcal{E} \ E) (\text{the-inv } \pi \ v) = p\} \subseteq$   
 $\pi \text{ ' } \{v \in \text{voters-}\mathcal{E} \ E. (\text{profile-}\mathcal{E} \ E) \ v = p\}$   
**by** *blast*  
**from** *renamed* **have**  $\forall v \in \text{voters-}\mathcal{E} \ E. \pi \ v \in \text{voters-}\mathcal{E} \ E'$   
**unfolding** *voters-}\mathcal{E}.simps*  
**using** *bijection-}\mathcal{E} \ E. (\text{profile-}\mathcal{E} \ E) (\text{the-inv } \pi \ v) = p\}  
**by** (*metis* (*mono-tags*, *lifting*))  
**hence**  
 $\forall p. \pi \text{ ' } \{v \in \text{voters-}\mathcal{E} \ E. (\text{profile-}\mathcal{E} \ E) \ v = p\} \subseteq$   
 $\{v \in \text{voters-}\mathcal{E} \ E'. (\text{profile-}\mathcal{E} \ E) (\text{the-inv } \pi \ v) = p\}$   
**using** *bijection-}\mathcal{E} \ E. (\text{profile-}\mathcal{E} \ E) (\text{the-inv } \pi \ v) = p\}  
**by** *fastforce*  
**hence**  
 $\forall p. \{v \in \text{voters-}\mathcal{E} \ E'. (\text{profile-}\mathcal{E} \ E') \ v = p\} =$   
 $\pi \text{ ' } \{v \in \text{voters-}\mathcal{E} \ E. (\text{profile-}\mathcal{E} \ E) \ v = p\}$   
**using** *subset rewrite*  
**by** (*simp add: subset-antisym*)  
**moreover have**  
 $\forall p. \text{card } (\pi \text{ ' } \{v \in \text{voters-}\mathcal{E} \ E. (\text{profile-}\mathcal{E} \ E) \ v = p\}) =$   
 $\text{card } \{v \in \text{voters-}\mathcal{E} \ E. (\text{profile-}\mathcal{E} \ E) \ v = p\}$   
**using** *bijection-}\mathcal{E} \ E. (\text{profile-}\mathcal{E} \ E) (\text{the-inv } \pi \ v) = p\}  
**by** (*metis* (*no-types*, *lifting*))  
**ultimately show**  
 $\text{alternatives-}\mathcal{E} \ E =$   
 $\text{alternatives-}\mathcal{E} \ E' \wedge E \in \mathcal{E} \wedge (\forall p. \text{vote-count } p \ E = \text{vote-count } p \ E')$   
**using** *eq-alts assms*  
**by** *simp*  
**qed*****

**lemma** *vote-count-anon-rel:*

**fixes**

$\mathcal{E} :: ('a, 'v) \text{ Election set}$  **and**

$E \ E' :: ('a, 'v) \text{ Election}$

**assumes**

*fin-voters-E: finite (voters-}\mathcal{E} \ E)* **and**

*fin-voters-E': finite (voters-}\mathcal{E} \ E')* **and**

*default-non-v: \forall v. v \notin \text{voters-}\mathcal{E} \ E \longrightarrow \text{profile-}\mathcal{E} \ E \ v = \{\}* **and**

*default-non-v': \forall v. v \notin \text{voters-}\mathcal{E} \ E' \longrightarrow \text{profile-}\mathcal{E} \ E' \ v = \{\}* **and**

*eq: alternatives-}\mathcal{E} \ E = \text{alternatives-}\mathcal{E} \ E' \wedge (E, E') \in \mathcal{E} \times \mathcal{E}*

$\wedge (\forall p. \text{vote-count } p \ E = \text{vote-count } p \ E')$

**shows**  $(E, E') \in \text{anonymity}_{\mathcal{R}} \ \mathcal{E}$

**proof** –

**have**  $\forall p. \text{card } \{v \in \text{voters-}\mathcal{E} \ E. \text{profile-}\mathcal{E} \ E \ v = p\} =$

$\text{card } \{v \in \text{voters-}\mathcal{E} \ E'. \text{profile-}\mathcal{E} \ E' \ v = p\}$

**using** *eq*

**unfolding** *vote-count.simps*

**by** *blast*

**moreover have**

$\forall p. \text{finite } \{v \in \text{voters-}\mathcal{E} \ E. \text{profile-}\mathcal{E} \ E \ v = p\}$

$\wedge \text{finite } \{v \in \text{voters-}\mathcal{E} \ E'. \text{profile-}\mathcal{E} \ E' \ v = p\}$   
**using** *assms*  
**by** *simp*  
**ultimately have**  
 $\forall p. \exists \pi_p. \text{bij-betw } \pi_p$   
 $\{v \in \text{voters-}\mathcal{E} \ E. \text{profile-}\mathcal{E} \ E \ v = p\}$   
 $\{v \in \text{voters-}\mathcal{E} \ E'. \text{profile-}\mathcal{E} \ E' \ v = p\}$   
**using** *bij-betw-iff-card*  
**by** *blast*  
**then obtain**  $\pi :: 'a \text{ Preference-Relation} \Rightarrow ('v \Rightarrow 'v)$  **where**  
 $\text{bij-}\pi: \forall p. \text{bij-betw } (\pi \ p) \ \{v \in \text{voters-}\mathcal{E} \ E. \text{profile-}\mathcal{E} \ E \ v = p\}$   
 $\{v \in \text{voters-}\mathcal{E} \ E'. \text{profile-}\mathcal{E} \ E' \ v = p\}$   
**by** (*metis (no-types)*)  
**obtain**  $\pi' :: 'v \Rightarrow 'v$  **where**  
 $\pi'\text{-perm}: \forall v \in \text{voters-}\mathcal{E} \ E. \pi' \ v = \pi (\text{profile-}\mathcal{E} \ E \ v) \ v$   
**by** *fastforce*  
**hence**  $\forall v \in \text{voters-}\mathcal{E} \ E. \forall v' \in \text{voters-}\mathcal{E} \ E.$   
 $\pi' \ v = \pi' \ v' \longrightarrow \pi (\text{profile-}\mathcal{E} \ E \ v) \ v = \pi (\text{profile-}\mathcal{E} \ E \ v') \ v'$   
**by** *simp*  
**moreover have**  
 $\forall w \in \text{voters-}\mathcal{E} \ E. \forall w' \in \text{voters-}\mathcal{E} \ E.$   
 $\pi (\text{profile-}\mathcal{E} \ E \ w) \ w = \pi (\text{profile-}\mathcal{E} \ E \ w') \ w'$   
 $\longrightarrow \{v \in \text{voters-}\mathcal{E} \ E'. \text{profile-}\mathcal{E} \ E' \ v = \text{profile-}\mathcal{E} \ E \ w\}$   
 $\cap \{v \in \text{voters-}\mathcal{E} \ E'. \text{profile-}\mathcal{E} \ E' \ v = \text{profile-}\mathcal{E} \ E \ w'\} \neq \{\}$   
**using** *bij-}\pi*  
**unfolding** *bij-betw-def*  
**by** *blast*  
**moreover have**  
 $\forall w \ w'.$   
 $\{v \in \text{voters-}\mathcal{E} \ E'. \text{profile-}\mathcal{E} \ E' \ v = \text{profile-}\mathcal{E} \ E \ w\}$   
 $\cap \{v \in \text{voters-}\mathcal{E} \ E'. \text{profile-}\mathcal{E} \ E' \ v = \text{profile-}\mathcal{E} \ E \ w'\} \neq \{\}$   
 $\longrightarrow \text{profile-}\mathcal{E} \ E \ w = \text{profile-}\mathcal{E} \ E \ w'$   
**by** *blast*  
**ultimately have** *eq-prof*:  
 $\forall v \in \text{voters-}\mathcal{E} \ E. \forall v' \in \text{voters-}\mathcal{E} \ E.$   
 $\pi' \ v = \pi' \ v' \longrightarrow \text{profile-}\mathcal{E} \ E \ v = \text{profile-}\mathcal{E} \ E \ v'$   
**by** *blast*  
**hence**  $\forall v \in \text{voters-}\mathcal{E} \ E. \forall v' \in \text{voters-}\mathcal{E} \ E.$   
 $\pi' \ v = \pi' \ v' \longrightarrow \pi (\text{profile-}\mathcal{E} \ E \ v) \ v = \pi (\text{profile-}\mathcal{E} \ E \ v') \ v'$   
**using**  $\pi'\text{-perm}$   
**by** *metis*  
**hence**  $\forall v \in \text{voters-}\mathcal{E} \ E. \forall v' \in \text{voters-}\mathcal{E} \ E. \pi' \ v = \pi' \ v' \longrightarrow v = v'$   
**using** *bij-}\pi \text{ eq-prof mem-Collect-eq}*  
**unfolding** *bij-betw-def inj-on-def*  
**by** (*metis (mono-tags, lifting)*)  
**hence** *inj*:  $\text{inj-on } \pi' (\text{voters-}\mathcal{E} \ E)$   
**unfolding** *inj-on-def*  
**by** *simp*  
**have**  $\pi' \text{ ` voters-}\mathcal{E} \ E = \{\pi (\text{profile-}\mathcal{E} \ E \ v) \ v \mid v. v \in \text{voters-}\mathcal{E} \ E\}$



**using**  $\pi'$ -perm  
**unfolding** Setcompr-eq-image  
**by** simp  
**also have**  
 $\dots = \bigcup \{ \pi \ p \ ' \{ v \in \text{voters-}\mathcal{E} \ E. \text{profile-}\mathcal{E} \ E \ v = p \} \mid p. \ p \in \text{UNIV} \}$   
**unfolding** Union-eq  
**by** blast  
**also have**  
 $\dots = \bigcup \{ \{ v \in \text{voters-}\mathcal{E} \ E'. \text{profile-}\mathcal{E} \ E' \ v = p \} \mid p. \ p \in \text{UNIV} \}$   
**using** bij- $\pi$   
**unfolding** bij-betw-def  
**by** (metis (mono-tags, lifting))  
**finally have**  $\pi' \ ' \text{voters-}\mathcal{E} \ E = \text{voters-}\mathcal{E} \ E'$   
**by** blast  
**with** inj **have**  $\text{bij}': \text{bij-betw } \pi' (\text{voters-}\mathcal{E} \ E) (\text{voters-}\mathcal{E} \ E')$   
**using** bij- $\pi$   
**unfolding** bij-betw-def  
**by** blast  
**then obtain**  $\pi\text{-global} :: 'v \Rightarrow 'v$  **where**  
 $\text{bijection-}\pi_g: \text{bij } \pi\text{-global}$  **and**  
 $\pi\text{-global-eq-}\pi': \forall v \in \text{voters-}\mathcal{E} \ E. \pi\text{-global } v = \pi' \ v$  **and**  
 $\pi\text{-global-eq-n-app-}\pi':$   
 $\forall v \in \text{voters-}\mathcal{E} \ E' - \text{voters-}\mathcal{E} \ E.$   
 $\pi\text{-global } v \in \text{voters-}\mathcal{E} \ E - \text{voters-}\mathcal{E} \ E' \wedge$   
 $(\exists n > 0. n\text{-app } n \ \pi' (\pi\text{-global } v) = v)$  **and**  
 $\pi\text{-global-non-voters}: \forall v \in \text{UNIV} - \text{voters-}\mathcal{E} \ E - \text{voters-}\mathcal{E} \ E'. \pi\text{-global } v = v$   
**using** fin-voters-E fin-voters-E' bij-betw-finite-ind-global-bij  
**by** blast  
**hence**  $\text{inv}: \forall v \ v'. (\pi\text{-global } v' = v) = (v' = \text{the-inv } \pi\text{-global } v)$   
**using** UNIV-I bij-betw-imp-inj-on bij-betw-imp-surj-on f-the-inv-into-f the-inv-f-f  
**by** metis  
**moreover have**  
 $\forall v \in \text{UNIV} - (\text{voters-}\mathcal{E} \ E' - \text{voters-}\mathcal{E} \ E).$   
 $\pi\text{-global } v \in \text{UNIV} - (\text{voters-}\mathcal{E} \ E - \text{voters-}\mathcal{E} \ E')$   
**using**  $\pi\text{-global-eq-}\pi' \ \pi\text{-global-non-voters} \ \text{bij}' \ \text{bijection-}\pi_g$   
 $\text{DiffD1 DiffD2 DiffI bij-betwE}$   
**by** (metis (no-types, lifting))  
**ultimately have**  
 $\forall v \in \text{voters-}\mathcal{E} \ E - \text{voters-}\mathcal{E} \ E'.$   
 $\text{the-inv } \pi\text{-global } v \in \text{voters-}\mathcal{E} \ E' - \text{voters-}\mathcal{E} \ E$   
**using**  $\text{bijection-}\pi_g \ \pi\text{-global-eq-n-app-}\pi' \ \text{DiffD2 DiffI UNIV-I}$   
**by** metis  
**hence**  $\forall v \in \text{voters-}\mathcal{E} \ E - \text{voters-}\mathcal{E} \ E'. \forall n > 0.$   
 $\text{profile-}\mathcal{E} \ E (\text{the-inv } \pi\text{-global } v) = \{ \}$   
**using** default-non-v  
**by** simp  
**moreover have**  $\forall v \in \text{voters-}\mathcal{E} \ E - \text{voters-}\mathcal{E} \ E'. \text{profile-}\mathcal{E} \ E' \ v = \{ \}$   
**using** default-non-v'  
**by** simp

**ultimately have** *comp-on-voters-diff*:  
 $\forall v \in \text{voters-}\mathcal{E} \ E - \text{voters-}\mathcal{E} \ E'.$   
 $\text{profile-}\mathcal{E} \ E' \ v = (\text{profile-}\mathcal{E} \ E \circ \text{the-inv } \pi\text{-global}) \ v$   
**by** *auto*  
**have**  $\forall v \in \text{voters-}\mathcal{E} \ E'. \exists v' \in \text{voters-}\mathcal{E} \ E. \pi\text{-global} \ v' = v \wedge \pi' \ v' = v$   
**using** *bij' imageE  $\pi$ -global-eq- $\pi'$*   
**unfolding** *bij-betw-def*  
**by** (*metis* (*mono-tags*, *opaque-lifting*))  
**hence**  $\forall v \in \text{voters-}\mathcal{E} \ E'. \exists v' \in \text{voters-}\mathcal{E} \ E. v' = \text{the-inv } \pi\text{-global} \ v \wedge \pi' \ v' = v$   
**using** *inv*  
**by** *metis*  
**hence**  $\forall v \in \text{voters-}\mathcal{E} \ E'.$   
 $\text{the-inv } \pi\text{-global} \ v \in \text{voters-}\mathcal{E} \ E \wedge \pi' (\text{the-inv } \pi\text{-global} \ v) = v$   
**by** *blast*  
**moreover have**  $\forall v' \in \text{voters-}\mathcal{E} \ E. \text{profile-}\mathcal{E} \ E' (\pi' \ v') = \text{profile-}\mathcal{E} \ E \ v'$   
**using**  *$\pi'$ -perm bij- $\pi$  bij-betwE mem-Collect-eq*  
**by** *fastforce*  
**ultimately have** *comp-on- $E'$ -voters*:  
 $\forall v \in \text{voters-}\mathcal{E} \ E'. \text{profile-}\mathcal{E} \ E' \ v = (\text{profile-}\mathcal{E} \ E \circ \text{the-inv } \pi\text{-global}) \ v$   
**unfolding** *comp-def*  
**by** *metis*  
**have**  $\forall v \in \text{UNIV} - \text{voters-}\mathcal{E} \ E - \text{voters-}\mathcal{E} \ E'.$   
 $\text{profile-}\mathcal{E} \ E' \ v = (\text{profile-}\mathcal{E} \ E \circ \text{the-inv } \pi\text{-global}) \ v$   
**using**  *$\pi$ -global-non-voters default-non-v default-non- $v'$  inv*  
**by** *simp*  
**hence**  $\text{profile-}\mathcal{E} \ E' = \text{profile-}\mathcal{E} \ E \circ \text{the-inv } \pi\text{-global}$   
**using** *comp-on-voters-diff comp-on- $E'$ -voters*  
**by** *blast*  
**moreover have**  $\pi\text{-global} \ ' (\text{voters-}\mathcal{E} \ E) = \text{voters-}\mathcal{E} \ E'$   
**using**  *$\pi$ -global-eq- $\pi'$  bij' bij-betw-imp-surj-on*  
**by** *fastforce*  
**ultimately have**  $E' = \text{rename } \pi\text{-global} \ E$   
**using** *rename.simps eq prod.collapse*  
**unfolding** *voters- $\mathcal{E}$ .simps profile- $\mathcal{E}$ .simps alternatives- $\mathcal{E}$ .simps*  
**by** *metis*  
**thus** *?thesis*  
**unfolding** *extensional-continuation.simps anonymity $\mathcal{R}$ .simps*  
 $\text{action-induced-rel.simps } \varphi\text{-anon.simps bijection}_{\mathcal{V}\mathcal{G}\text{-def}}$   
**using** *eq bijection- $\pi_g$  case-prodI rewrite-carrier*  
**by** *auto*  
**qed**

**lemma** *rename-comp*:  
**fixes**  $\pi \ \pi' :: 'v \Rightarrow 'v$   
**assumes**  
 $\text{bij } \pi$  **and**  
 $\text{bij } \pi'$   
**shows**  $\text{rename } \pi \circ \text{rename } \pi' = \text{rename } (\pi \circ \pi')$   
**proof**

```

fix  $E :: ('a, 'v) Election$ 
have  $rename\ \pi'\ E =$ 
   $(alternatives\text{-}\mathcal{E}\ E, \pi' \text{' } (voters\text{-}\mathcal{E}\ E), (profile\text{-}\mathcal{E}\ E) \circ (the\text{-}inv\ \pi'))$ 
unfolding  $alternatives\text{-}\mathcal{E}.simps\ voters\text{-}\mathcal{E}.simps\ profile\text{-}\mathcal{E}.simps$ 
using  $prod.collapse\ rename.simps$ 
by  $metis$ 
hence
   $(rename\ \pi \circ rename\ \pi')\ E =$ 
   $rename\ \pi\ (alternatives\text{-}\mathcal{E}\ E, \pi' \text{' } (voters\text{-}\mathcal{E}\ E), (profile\text{-}\mathcal{E}\ E) \circ (the\text{-}inv\ \pi'))$ 
unfolding  $comp\text{-}def$ 
by  $presburger$ 
also have
   $\dots = (alternatives\text{-}\mathcal{E}\ E, \pi \text{' } \pi' \text{' } (voters\text{-}\mathcal{E}\ E),$ 
   $(profile\text{-}\mathcal{E}\ E) \circ (the\text{-}inv\ \pi') \circ (the\text{-}inv\ \pi))$ 
by  $simp$ 
also have
   $\dots = (alternatives\text{-}\mathcal{E}\ E, (\pi \circ \pi') \text{' } (voters\text{-}\mathcal{E}\ E),$ 
   $(profile\text{-}\mathcal{E}\ E) \circ the\text{-}inv\ (\pi \circ \pi'))$ 
using  $assms\ the\text{-}inv\text{-}comp[of\ \pi\ -\ -\ \pi']$ 
unfolding  $comp\text{-}def\ image\text{-}image$ 
by  $simp$ 
finally show  $(rename\ \pi \circ rename\ \pi')\ E = rename\ (\pi \circ \pi')\ E$ 
unfolding  $alternatives\text{-}\mathcal{E}.simps\ voters\text{-}\mathcal{E}.simps\ profile\text{-}\mathcal{E}.simps$ 
using  $prod.collapse\ rename.simps$ 
by  $metis$ 
qed

interpretation  $anonymous\text{-}group\text{-}action:$ 
   $group\text{-}action\ bijection_{\mathcal{G}}\ well\text{-}formed\text{-}elections\ \varphi\text{-}anon\ well\text{-}formed\text{-}elections$ 
proof  $(unfold\ group\text{-}action\text{-}def\ group\text{-}hom\text{-}def\ bijection_{\mathcal{G}}\text{-}def$ 
   $group\text{-}hom\text{-}axioms\text{-}def\ hom\text{-}def,\ intro\ conjI\ group\text{-}BijGroup,\ safe)$ 
fix  $\pi :: 'v \Rightarrow 'v$ 
assume  $bij\text{-}carrier: \pi \in carrier\ (BijGroup\ UNIV)$ 
hence  $bij\text{-}\pi: bij\ \pi$ 
using  $rewrite\text{-}carrier$ 
by  $blast$ 
hence  $rename\ \pi \text{' } well\text{-}formed\text{-}elections = well\text{-}formed\text{-}elections$ 
using  $rename\text{-}surj\ bij\text{-}\pi$ 
by  $blast$ 
moreover have  $inj\text{-}on\ (rename\ \pi)\ well\text{-}formed\text{-}elections$ 
using  $rename\text{-}inj\ bij\text{-}\pi\ subset\text{-}inj\text{-}on$ 
by  $blast$ 
ultimately have  $bij\text{-}betw\ (rename\ \pi)\ well\text{-}formed\text{-}elections\ well\text{-}formed\text{-}elections$ 
unfolding  $bij\text{-}betw\text{-}def$ 
by  $blast$ 
hence  $bij\text{-}betw\ (\varphi\text{-}anon\ well\text{-}formed\text{-}elections\ \pi)\ well\text{-}formed\text{-}elections\ well\text{-}formed\text{-}elections$ 
unfolding  $\varphi\text{-}anon.simps\ extensional\text{-}continuation.simps$ 
using  $bij\text{-}betw\text{-}ext$ 
by  $simp$ 

```

**moreover have**  $\varphi$ -anon well-formed-elections  $\pi \in \text{extensional well-formed-elections}$   
**unfolding** *extensional-def*  
**by force**  
**ultimately show** *bij-car-elect*:  
 $\varphi$ -anon well-formed-elections  $\pi \in \text{carrier (BijGroup well-formed-elections)}$   
**unfolding** *BijGroup-def Bij-def*  
**by simp**  
**fix**  $\pi' :: 'v \Rightarrow 'v$   
**assume** *bij-carrier*:  $\pi' \in \text{carrier (BijGroup UNIV)}$   
**hence** *bij- $\pi'$* : *bij  $\pi'$*   
**using** *rewrite-carrier*  
**by blast**  
**hence** *rename  $\pi'$  ‘ well-formed-elections = well-formed-elections*  
**using** *rename-surj bij- $\pi$*   
**by blast**  
**moreover have** *inj-on (rename  $\pi'$ ) well-formed-elections*  
**using** *rename-inj bij- $\pi'$  subset-inj-on*  
**by blast**  
**ultimately have** *bij-betw (rename  $\pi'$ ) well-formed-elections well-formed-elections*  
**unfolding** *bij-betw-def*  
**by blast**  
**hence** *bij-betw ( $\varphi$ -anon well-formed-elections  $\pi'$ ) well-formed-elections well-formed-elections*  
**unfolding**  *$\varphi$ -anon.simps extensional-continuation.simps*  
**using** *bij-betw-ext*  
**by simp**  
**moreover from this have** *wf-closed'*:  
 $\varphi$ -anon well-formed-elections  $\pi' \text{ ‘ well-formed-elections } \subseteq \text{ well-formed-elections}$   
**using** *bij-betw-imp-surj-on*  
**by blast**  
**moreover have**  $\varphi$ -anon well-formed-elections  $\pi' \in \text{extensional well-formed-elections}$   
**unfolding** *extensional-def*  
**by force**  
**ultimately have** *bij-car-elect'*:  
 $\varphi$ -anon well-formed-elections  $\pi' \in \text{carrier (BijGroup well-formed-elections)}$   
**unfolding** *BijGroup-def Bij-def*  
**by simp**  
**have**  
 $\varphi$ -anon well-formed-elections  $\pi$   
 $\otimes$  *BijGroup well-formed-elections ( $\varphi$ -anon well-formed-elections)  $\pi' =$*   
*extensional-continuation*  
 $(\varphi\text{-anon well-formed-elections } \pi \circ \varphi\text{-anon well-formed-elections } \pi') \text{ well-formed-elections}$   
**using** *rewrite-mult bij-car-elect bij-car-elect'*  
**by blast**  
**moreover have**  
 $\forall E \in \text{well-formed-elections.}$   
*extensional-continuation*  
 $(\varphi\text{-anon well-formed-elections } \pi \circ \varphi\text{-anon well-formed-elections } \pi') \text{ well-formed-elections } E =$   
 $(\varphi\text{-anon well-formed-elections } \pi \circ \varphi\text{-anon well-formed-elections } \pi') E$

```

    by simp
  moreover have
     $\forall E \in \text{well-formed-elections}.$ 
       $(\varphi\text{-anon well-formed-elections } \pi \circ \varphi\text{-anon well-formed-elections } \pi') E =$ 
       $\text{rename } \pi (\text{rename } \pi' E)$ 
    unfolding  $\varphi\text{-anon.simps}$ 
    using  $\text{wf-closed'}$ 
    by auto
  moreover have
     $\forall E \in \text{well-formed-elections}.$   $\text{rename } \pi (\text{rename } \pi' E) = \text{rename } (\pi \circ \pi') E$ 
    using  $\text{rename-comp bij-}\pi \text{ bij-}\pi' \text{ comp-apply}$ 
    by metis
  moreover have
     $\forall E \in \text{well-formed-elections}.$   $\text{rename } (\pi \circ \pi') E =$ 
     $\varphi\text{-anon well-formed-elections } (\pi \otimes \text{BijGroup UNIV } \pi') E$ 
    unfolding  $\varphi\text{-anon.simps}$ 
    using  $\text{rewrite-mult-univ bij-}\pi \text{ bij-}\pi' \text{ rewrite-carrier mem-Collect-eq}$ 
    by fastforce
  moreover have
     $\forall E. E \notin \text{well-formed-elections}$ 
       $\longrightarrow \text{extensional-continuation}$ 
       $(\varphi\text{-anon well-formed-elections } \pi$ 
         $\circ \varphi\text{-anon well-formed-elections } \pi') \text{ well-formed-elections } E =$ 
       $\text{undefined}$ 
    by simp
  moreover have
     $\forall E. E \notin \text{well-formed-elections}$ 
       $\longrightarrow \varphi\text{-anon well-formed-elections } (\pi \otimes \text{BijGroup UNIV } \pi') E =$ 
       $\text{undefined}$ 
    by simp
  ultimately have
     $\forall E. \varphi\text{-anon well-formed-elections } (\pi \otimes \text{BijGroup UNIV } \pi') E =$ 
     $(\varphi\text{-anon well-formed-elections } \pi$ 
       $\otimes \text{BijGroup well-formed-elections } \varphi\text{-anon well-formed-elections } \pi') E$ 
    by metis
  thus  $\varphi\text{-anon well-formed-elections } (\pi \otimes \text{BijGroup UNIV } \pi') =$ 
     $\varphi\text{-anon well-formed-elections } \pi$ 
     $\otimes \text{BijGroup well-formed-elections } \varphi\text{-anon well-formed-elections } \pi'$ 
    by blast
qed

lemma (in result) anonymity-action-presv-symmetry: is-symmetry  $(\lambda E. \text{limit}$ 
   $(\text{alternatives-}\mathcal{E} E) \text{ UNIV}) (\text{Invariance } (\text{anonymity}_{\mathcal{R}} \text{ well-formed-elections}))$ 
  unfolding  $\text{anonymity}_{\mathcal{R}}.\text{simps}$ 
  by clarsimp

```

#### 1.10.4 Neutrality Lemmas

lemma *rel-rename-helper*:

```

fixes
   $r :: 'a \text{ rel}$  and
   $\pi :: 'a \Rightarrow 'a$  and
   $a \ b :: 'a$ 
assumes  $\text{bij } \pi$ 
shows  $(\pi \ a, \pi \ b) \in \{(\pi \ x, \pi \ y) \mid x \ y. (x, y) \in r\}$ 
   $\longleftrightarrow (a, b) \in \{(x, y) \mid x \ y. (x, y) \in r\}$ 
proof (safe)
  fix  $x \ y :: 'a$ 
  assume
     $(x, y) \in r$  and
     $\pi \ a = \pi \ x$  and
     $\pi \ b = \pi \ y$ 
  thus  $\exists x \ y. (a, b) = (x, y) \wedge (x, y) \in r$ 
    using assms bij-is-inj the-inv-f-f
    by metis
next
  fix  $x \ y :: 'a$ 
  assume  $(a, b) \in r$ 
  thus  $\exists x \ y. (\pi \ a, \pi \ b) = (\pi \ x, \pi \ y) \wedge (x, y) \in r$ 
    by metis
qed

lemma rel-rename-comp:
  fixes  $\pi \ \pi' :: 'a \Rightarrow 'a$ 
  shows  $\text{rel-rename } (\pi \circ \pi') = \text{rel-rename } \pi \circ \text{rel-rename } \pi'$ 
proof
  fix  $r :: 'a \text{ rel}$ 
  have  $\text{rel-rename } (\pi \circ \pi') \ r = \{(\pi \ (\pi' \ a), \pi \ (\pi' \ b)) \mid a \ b. (a, b) \in r\}$ 
    by simp
  also have  $\dots = \{(\pi \ a, \pi \ b) \mid a \ b. (a, b) \in \text{rel-rename } \pi' \ r\}$ 
    unfolding rel-rename.simps
    by blast
  finally show  $\text{rel-rename } (\pi \circ \pi') \ r = (\text{rel-rename } \pi \circ \text{rel-rename } \pi') \ r$ 
    unfolding comp-def
    by simp
qed

lemma rel-rename-sound:
  fixes
     $\pi :: 'a \Rightarrow 'a$  and
     $r :: 'a \text{ rel}$  and
     $A :: 'a \text{ set}$ 
  assumes inj  $\pi$ 
  shows
     $\text{refl-on } A \ r \longrightarrow \text{refl-on } (\pi \text{ ` } A) \ (\text{rel-rename } \pi \ r)$  and
     $\text{antisym } r \longrightarrow \text{antisym } (\text{rel-rename } \pi \ r)$  and
     $\text{total-on } A \ r \longrightarrow \text{total-on } (\pi \text{ ` } A) \ (\text{rel-rename } \pi \ r)$  and
     $\text{Relation.trans } r \longrightarrow \text{Relation.trans } (\text{rel-rename } \pi \ r)$ 

```

```

proof (unfold antisym-def total-on-def Relation.trans-def, safe)
  assume refl-on A r
  thus refl-on ( $\pi$  ' A) (rel-rename  $\pi$  r)
    unfolding refl-on-def rel-rename.simps
    by blast
next
  fix a b :: 'a
  assume
    (a, b)  $\in$  rel-rename  $\pi$  r and
    (b, a)  $\in$  rel-rename  $\pi$  r
  then obtain
    c c' d d' :: 'a where
      c-rel-d: (c, d)  $\in$  r and
      d'-rel-c': (d', c')  $\in$  r and
       $\pi_c$ -eq-a:  $\pi$  c = a and
       $\pi_{c'}$ -eq-a:  $\pi$  c' = a and
       $\pi_d$ -eq-b:  $\pi$  d = b and
       $\pi_{d'}$ -eq-b:  $\pi$  d' = b
    unfolding rel-rename.simps
    by auto
  hence c = c'  $\wedge$  d = d'
    using assms
    unfolding inj-def
    by presburger
  moreover assume  $\forall$  a b. (a, b)  $\in$  r  $\longrightarrow$  (b, a)  $\in$  r  $\longrightarrow$  a = b
  ultimately have c = d
    using d'-rel-c' c-rel-d
    by simp
  thus a = b
    using  $\pi_c$ -eq-a  $\pi_d$ -eq-b
    by simp
next
  fix a b :: 'a
  assume
    total:  $\forall$  x  $\in$  A.  $\forall$  y  $\in$  A. x  $\neq$  y  $\longrightarrow$  (x, y)  $\in$  r  $\vee$  (y, x)  $\in$  r and
    a-in-A: a  $\in$  A and
    b-in-A: b  $\in$  A and
     $\pi_a$ -neq- $\pi_b$ :  $\pi$  a  $\neq$   $\pi$  b and
     $\pi_b$ -not-rel- $\pi_a$ : ( $\pi$  b,  $\pi$  a)  $\notin$  rel-rename  $\pi$  r
  hence (b, a)  $\notin$  r  $\wedge$  a  $\neq$  b
    unfolding rel-rename.simps
    by blast
  hence (a, b)  $\in$  r
    using a-in-A b-in-A total
    by blast
  thus ( $\pi$  a,  $\pi$  b)  $\in$  rel-rename  $\pi$  r
    unfolding rel-rename.simps
    by blast
next

```

```

fix  $a\ b\ c :: 'a$ 
assume
   $(a, b) \in \text{rel-rename } \pi\ r$  and
   $(b, c) \in \text{rel-rename } \pi\ r$ 
then obtain
   $d\ e\ s\ t :: 'a$  where
     $d\text{-rel-}e: (d, e) \in r$  and
     $s\text{-rel-}t: (s, t) \in r$  and
     $\pi_d\text{-eq-}a: \pi\ d = a$  and
     $\pi_s\text{-eq-}b: \pi\ s = b$  and
     $\pi_t\text{-eq-}c: \pi\ t = c$  and
     $\pi_e\text{-eq-}b: \pi\ e = b$ 
  unfolding  $\text{alternatives-}\mathcal{E}.\text{simps voters-}\mathcal{E}.\text{simps profile-}\mathcal{E}.\text{simps}$ 
  using  $\text{rel-rename.simps Pair-inject mem-Collect-eq}$ 
  by auto
hence  $s = e$ 
  using  $\text{assms rangeI range-ex1-eq}$ 
  by metis
hence  $(d, e) \in r \wedge (e, t) \in r$ 
  using  $d\text{-rel-}e\ s\text{-rel-}t$ 
  by simp
moreover assume  $\forall\ x\ y\ z. (x, y) \in r \longrightarrow (y, z) \in r \longrightarrow (x, z) \in r$ 
ultimately have  $(d, t) \in r$ 
  by blast
thus  $(a, c) \in \text{rel-rename } \pi\ r$ 
  unfolding  $\text{rel-rename.simps}$ 
  using  $\pi_d\text{-eq-}a\ \pi_t\text{-eq-}c$ 
  by blast
qed

lemma rename-subset:
fixes
   $r\ s :: 'a\ \text{rel}$  and
   $a\ b :: 'a$  and
   $\pi :: 'a \Rightarrow 'a$ 
assumes
   $\text{bij-}\pi: \text{bij } \pi$  and
   $\text{rel-rename } \pi\ r = \text{rel-rename } \pi\ s$  and
   $(a, b) \in r$ 
shows  $(a, b) \in s$ 
proof –
have  $(\pi\ a, \pi\ b) \in \{(\pi\ a, \pi\ b) \mid a\ b. (a, b) \in s\}$ 
  using assms
  unfolding  $\text{rel-rename.simps}$ 
  by blast
hence  $\exists\ c\ d. (c, d) \in s \wedge \pi\ c = \pi\ a \wedge \pi\ d = \pi\ b$ 
  by fastforce
moreover have  $\forall\ c\ d. \pi\ c = \pi\ d \longrightarrow c = d$ 
  using  $\text{bij-}\pi\ \text{bij-pointE}$ 

```



```

    by metis
  ultimately show  $(a, b) \in s$ 
    by blast
qed

lemma rel-rename-bij:
  fixes  $\pi :: 'a \Rightarrow 'a$ 
  assumes bij- $\pi$ : bij  $\pi$ 
  shows bij (rel-rename  $\pi$ )
proof (unfold bij-def inj-def surj-def, safe)
  fix
     $r s :: 'a \text{ rel}$  and
     $a b :: 'a$ 
  assume rename: rel-rename  $\pi$   $r = \text{rel-rename } \pi s$ 
  {
    moreover assume  $(a, b) \in r$ 
    ultimately have  $(\pi a, \pi b) \in \{(\pi a, \pi b) \mid a b. (a, b) \in s\}$ 
      unfolding rel-rename.simps
      by blast
    hence  $\exists c d. (c, d) \in s \wedge \pi c = \pi a \wedge \pi d = \pi b$ 
      by fastforce
    moreover have  $\forall c d. \pi c = \pi d \longrightarrow c = d$ 
      using bij- $\pi$  bij-pointE
      by metis
    ultimately show subset:  $(a, b) \in s$ 
      by blast
  }
  moreover assume  $(a, b) \in s$ 
  ultimately show  $(a, b) \in r$ 
    using rename rename-subset bij- $\pi$ 
    by (metis (no-types))
next
  fix  $r :: 'a \text{ rel}$ 
  have rel-rename  $\pi \{((\text{the-inv } \pi) a, (\text{the-inv } \pi) b) \mid a b. (a, b) \in r\} =$ 
     $\{(\pi ((\text{the-inv } \pi) a), \pi ((\text{the-inv } \pi) b)) \mid a b. (a, b) \in r\}$ 
    by auto
  also have  $\dots = \{(a, b) \mid a b. (a, b) \in r\}$ 
    using the-inv-f-f bij- $\pi$ 
    by (simp add: f-the-inv-into-f-bij-betw)
  finally have rel-rename  $\pi (\text{rel-rename } (\text{the-inv } \pi) r) = r$ 
    by simp
  thus  $\exists s. r = \text{rel-rename } \pi s$ 
    by blast
qed

lemma alternatives-rename-comp:
  fixes  $\pi \pi' :: 'a \Rightarrow 'a$ 
  shows alternatives-rename  $\pi \circ \text{alternatives-rename } \pi' =$ 
    alternatives-rename  $(\pi \circ \pi')$ 

```

```

proof
  fix  $\mathcal{E} :: ('a, 'v) \text{ Election}$ 
  have  $(\text{alternatives-rename } \pi \circ \text{alternatives-rename } \pi') \mathcal{E} =$ 
     $(\pi \text{ ' } \pi' \text{ ' } (\text{alternatives-}\mathcal{E} \mathcal{E}), \text{ voters-}\mathcal{E} \mathcal{E},$ 
     $(\text{rel-rename } \pi) \circ (\text{rel-rename } \pi') \circ (\text{profile-}\mathcal{E} \mathcal{E}))$ 
    by  $(\text{simp add: fun.map-comp})$ 
  also have
     $\dots = ((\pi \circ \pi') \text{ ' } (\text{alternatives-}\mathcal{E} \mathcal{E}), \text{ voters-}\mathcal{E} \mathcal{E},$ 
     $(\text{rel-rename } (\pi \circ \pi')) \circ (\text{profile-}\mathcal{E} \mathcal{E}))$ 
    using  $\text{rel-rename-comp image-comp}$ 
    by  $\text{metis}$ 
  also have  $\dots = \text{alternatives-rename } (\pi \circ \pi') \mathcal{E}$ 
    by  $\text{simp}$ 
  finally show
     $(\text{alternatives-rename } \pi \circ \text{alternatives-rename } \pi') \mathcal{E} =$ 
     $\text{alternatives-rename } (\pi \circ \pi') \mathcal{E}$ 
    by  $\text{blast}$ 
qed

```

**lemma** *alternatives-rename-sound*:

```

fixes
   $A \ A' :: 'a \text{ set}$  and
   $V \ V' :: 'v \text{ set}$  and
   $p \ p' :: ('a, 'v) \text{ Profile}$  and
   $\pi :: 'a \Rightarrow 'a$ 
assumes
   $\text{bij-}\pi$ :  $\text{bij } \pi$  and
   $\text{wf-elects}$ :  $(A, V, p) \in \text{well-formed-elections}$  and
   $\text{renamed}$ :  $(A', V', p') = \text{alternatives-rename } \pi \ (A, V, p)$ 
shows  $(A', V', p') \in \text{well-formed-elections}$ 
proof –
  have
     $A' = \pi \text{ ' } A$  and
     $V = V'$ 
    using  $\text{renamed}$ 
    by  $(\text{simp}, \text{simp})$ 
  moreover from this have  $\forall v \in V'. \text{linear-order-on } A \ (p \ v)$ 
    using  $\text{wf-elects}$ 
    unfolding  $\text{well-formed-elections-def profile-def}$ 
    by  $\text{simp}$ 
  moreover have  $\forall v \in V'. p' \ v = \text{rel-rename } \pi \ (p \ v)$ 
    using  $\text{renamed}$ 
    by  $\text{simp}$ 
  ultimately have  $\forall v \in V'. \text{linear-order-on } A' \ (p' \ v)$ 
    unfolding  $\text{linear-order-on-def partial-order-on-def preorder-on-def}$ 
    using  $\text{bij-}\pi \text{ rel-rename-sound bij-is-inj}$ 
    by  $\text{metis}$ 
  thus  $(A', V', p') \in \text{well-formed-elections}$ 
    unfolding  $\text{well-formed-elections-def profile-def}$ 

```

```

    by simp
qed

lemma alternatives-rename-bij:
  fixes  $\pi :: ('a \Rightarrow 'a)$ 
  assumes  $\text{bij-}\pi$ :  $\text{bij } \pi$ 
  shows  $\text{bij-betw } (\text{alternatives-rename } \pi) \text{ well-formed-elections well-formed-elections}$ 
proof (unfold  $\text{bij-betw-def}$ , safe, intro  $\text{inj-onI}$ , clarify)
  fix
     $A A' :: 'a \text{ set}$  and
     $V V' :: 'v \text{ set}$  and
     $p p' :: ('a, 'v) \text{ Profile}$ 
  assume
     $\text{renamed: alternatives-rename } \pi (A, V, p) = \text{alternatives-rename } \pi (A', V', p')$ 
  hence
     $\pi\text{-eq-img-}A\text{-}A'$ :  $\pi \text{ ` } A = \pi \text{ ` } A'$  and
     $\text{rel-rename-eq}$ :  $\text{rel-rename } \pi \circ p = \text{rel-rename } \pi \circ p'$ 
    by (simp, simp)
  hence  $(\text{the-inv } (\text{rel-rename } \pi)) \circ \text{rel-rename } \pi \circ p =$ 
     $(\text{the-inv } (\text{rel-rename } \pi)) \circ \text{rel-rename } \pi \circ p'$ 
    using  $\text{fun.map-comp}$ 
    by metis
  also have  $(\text{the-inv } (\text{rel-rename } \pi)) \circ \text{rel-rename } \pi = \text{id}$ 
    using  $\text{bij-}\pi \text{ rel-rename-bij inv-o-cancel surj-imp-inv-eq the-inv-f-f}$ 
    unfolding  $\text{bij-betw-def}$ 
    by (metis (no-types, opaque-lifting))
  finally have  $p = p'$ 
    by simp
  hence
     $A = A'$  and
     $p = p'$ 
    using  $\text{bij-}\pi \pi\text{-eq-img-}A\text{-}A' \text{ bij-betw-imp-inj-on inj-image-eq-iff}$ 
    by (metis, safe)
  thus  $A = A' \wedge (V, p) = (V', p')$ 
    using  $\text{renamed}$ 
    by simp
next
  fix
     $A A' :: 'a \text{ set}$  and
     $V V' :: 'v \text{ set}$  and
     $p p' :: ('a, 'v) \text{ Profile}$ 
  assume  $\text{renamed: } (A', V', p') = \text{alternatives-rename } \pi (A, V, p)$ 
  hence  $\text{rewr: } V = V' \wedge A' = \pi \text{ ` } A$ 
    by simp
  moreover assume  $(A, V, p) \in \text{well-formed-elections}$ 
  ultimately have  $\forall v \in V'. \text{linear-order-on } A (p v)$ 
    unfolding  $\text{well-formed-elections-def profile-def}$ 
    by simp
  moreover have  $\forall v \in V'. p' v = \text{rel-rename } \pi (p v)$ 

```

```

    using renamed
    by simp
  ultimately have  $\forall v \in V'. \text{linear-order-on } A' (p' v)$ 
    unfolding linear-order-on-def partial-order-on-def preorder-on-def
    using rewr rel-rename-sound bij-is-inj assms
    by metis
  thus  $(A', V', p') \in \text{well-formed-elections}$ 
    unfolding well-formed-elections-def profile-def
    by simp
next
fix
  A :: 'a set and
  V :: 'v set and
  p :: ('a, 'v) Profile
  assume wf-elects:  $(A, V, p) \in \text{well-formed-elections}$ 
  have rename-inv:
    alternatives-rename (the-inv  $\pi$ ) (A, V, p) =
      ((the-inv  $\pi$ ) ' A, V, rel-rename (the-inv  $\pi$ )  $\circ$  p)
    by simp
  also have
    alternatives-rename  $\pi$  ((the-inv  $\pi$ ) ' A, V, rel-rename (the-inv  $\pi$ )  $\circ$  p) =
      ( $\pi$  ' (the-inv  $\pi$ ) ' A, V, rel-rename  $\pi \circ$  rel-rename (the-inv  $\pi$ )  $\circ$  p)
    by auto
  also have  $\dots = (A, V, \text{rel-rename } (\pi \circ \text{the-inv } \pi) \circ p)$ 
    using bij- $\pi$  rel-rename-comp[of  $\pi$ ] the-inv-f-f
    by (simp add: bij-betw-imp-surj-on bij-is-inj f-the-inv-into-f image-comp)
  also have  $(A, V, \text{rel-rename } (\pi \circ \text{the-inv } \pi) \circ p) = (A, V, \text{rel-rename id } \circ p)$ 
    using UNIV-I assms comp-apply f-the-inv-into-f-bij-betw id-apply
    by metis
  finally have
    alternatives-rename  $\pi$  (alternatives-rename (the-inv  $\pi$ ) (A, V, p)) =
      (A, V, p)
    unfolding rel-rename.simps
    by auto
  moreover have alternatives-rename (the-inv  $\pi$ ) (A, V, p)  $\in \text{well-formed-elections}$ 
    using rename-inv wf-elects alternatives-rename-sound bij- $\pi$  bij-betw-the-inv-into
    by (metis (no-types))
  ultimately show  $(A, V, p) \in \text{alternatives-rename } \pi$  ' well-formed-elections
    using image-eqI
    by metis
qed

interpretation  $\varphi$ -neutral-action: group-action bijectionAG well-formed-elections
   $\varphi$ -neutral well-formed-elections
proof (unfold group-action-def group-hom-def group-hom-axioms-def hom-def
  bijectionAG-def, intro conjI group-BijGroup, safe)
  fix  $\pi :: 'a \Rightarrow 'a$ 
  assume bij-carrier:  $\pi \in \text{carrier } (\text{BijGroup UNIV})$ 
  hence

```

**bij-betw** ( $\varphi$ -neutral well-formed-elections  $\pi$ ) well-formed-elections well-formed-elections  
**using** universal-set-carrier-imp-bij-group alternatives-rename-bij bij-betw-ext  
**unfolding**  $\varphi$ -neutral.simps  
**by** metis  
**thus** *bij-carrier-elect*:  
 $\varphi$ -neutral well-formed-elections  $\pi \in \text{carrier}$  (*BijGroup* well-formed-elections)  
**unfolding**  $\varphi$ -neutral.simps *BijGroup-def* *Bij-def* extensional-def  
**by** simp  
**fix**  $\pi' :: 'a \Rightarrow 'a$   
**assume** *bij-carrier'*:  $\pi' \in \text{carrier}$  (*BijGroup* UNIV)  
**hence**  
**bij-betw** ( $\varphi$ -neutral well-formed-elections  $\pi'$ ) well-formed-elections well-formed-elections  
**using** universal-set-carrier-imp-bij-group alternatives-rename-bij bij-betw-ext  
**unfolding**  $\varphi$ -neutral.simps  
**by** metis  
**hence** *bij-carrier-elect'*:  
 $\varphi$ -neutral well-formed-elections  $\pi' \in \text{carrier}$  (*BijGroup* well-formed-elections)  
**unfolding**  $\varphi$ -neutral.simps *BijGroup-def* *Bij-def* extensional-def  
**by** simp  
**hence** *carrier-elects*:  
 $\varphi$ -neutral well-formed-elections  $\pi \in \text{carrier}$  (*BijGroup* well-formed-elections)  
 $\wedge \varphi$ -neutral well-formed-elections  $\pi' \in \text{carrier}$  (*BijGroup* well-formed-elections)  
**using** *bij-carrier-elect*  
**by** metis  
**hence** *bij-betw* ( $\varphi$ -neutral well-formed-elections  $\pi'$ ) well-formed-elections well-formed-elections  
**unfolding** *BijGroup-def* *Bij-def* extensional-def  
**by** auto  
**hence** *wf-closed'*:  
 $\varphi$ -neutral well-formed-elections  $\pi' \text{ ' well-formed-elections } \subseteq \text{ well-formed-elections}$   
**using** *bij-betw-imp-surj-on*  
**by** blast  
**have**  $\varphi$ -neutral well-formed-elections  $\pi$   
 $\otimes$  *BijGroup* well-formed-elections  $\varphi$ -neutral well-formed-elections  $\pi' =$   
extensional-continuation  
 $(\varphi$ -neutral well-formed-elections  $\pi \circ \varphi$ -neutral well-formed-elections  $\pi')$   
well-formed-elections  
**using** *carrier-elects* rewrite-mult  
**by** auto  
**moreover have**  
 $\forall \mathcal{E} \in \text{well-formed-elections. extensional-continuation}$   
 $(\varphi$ -neutral well-formed-elections  $\pi \circ \varphi$ -neutral well-formed-elections  $\pi')$   
well-formed-elections  $\mathcal{E} =$   
 $(\varphi$ -neutral well-formed-elections  $\pi \circ \varphi$ -neutral well-formed-elections  $\pi')$   $\mathcal{E}$   
**by** simp  
**moreover have**  
 $\forall \mathcal{E} \in \text{well-formed-elections.}$   
 $(\varphi$ -neutral well-formed-elections  $\pi \circ \varphi$ -neutral well-formed-elections  $\pi')$   $\mathcal{E} =$   
alternatives-rename  $\pi$  (alternatives-rename  $\pi'$   $\mathcal{E}$ )  
**unfolding**  $\varphi$ -neutral.simps

```

using wf-closed'
by auto
moreover have
   $\forall \mathcal{E} \in \text{well-formed-elections.}$ 
    alternatives-rename  $\pi$  (alternatives-rename  $\pi'$   $\mathcal{E}$ ) =
      alternatives-rename  $(\pi \circ \pi')$   $\mathcal{E}$ 
using alternatives-rename-comp comp-apply
by metis
moreover have
   $\forall \mathcal{E} \in \text{well-formed-elections.}$  alternatives-rename  $(\pi \circ \pi')$   $\mathcal{E}$  =
     $\varphi$ -neutral well-formed-elections  $(\pi \otimes \text{BijGroup UNIV } \pi')$   $\mathcal{E}$ 
using rewrite-mult-univ bij-carrier bij-carrier'
unfolding  $\varphi$ -anon.simps  $\varphi$ -neutral.simps extensional-continuation.simps
by metis
moreover have
   $\forall \mathcal{E}. \mathcal{E} \notin \text{well-formed-elections} \longrightarrow$ 
    extensional-continuation
     $(\varphi\text{-neutral well-formed-elections } \pi \circ \varphi\text{-neutral well-formed-elections } \pi')$ 
    well-formed-elections  $\mathcal{E}$  = undefined
by simp
moreover have
   $\forall \mathcal{E}. \mathcal{E} \notin \text{well-formed-elections}$ 
     $\longrightarrow \varphi\text{-neutral well-formed-elections } (\pi \otimes \text{BijGroup UNIV } \pi') \mathcal{E} = \text{undefined}$ 
by simp
ultimately have
   $\forall \mathcal{E}. \varphi\text{-neutral well-formed-elections } (\pi \otimes \text{BijGroup UNIV } \pi') \mathcal{E} =$ 
     $(\varphi\text{-neutral well-formed-elections } \pi$ 
       $\otimes \text{BijGroup well-formed-elections } \varphi\text{-neutral well-formed-elections } \pi') \mathcal{E}$ 
by metis
thus
   $\varphi\text{-neutral well-formed-elections } (\pi \otimes \text{BijGroup UNIV } \pi') =$ 
     $\varphi\text{-neutral well-formed-elections } \pi$ 
     $\otimes \text{BijGroup well-formed-elections } \varphi\text{-neutral well-formed-elections } \pi'$ 
by blast
qed

interpretation  $\psi\text{-neutral}_c\text{-action}$ : group-action bijectionAG UNIV  $\psi\text{-neutral}_c$ 
proof (unfold group-action-def group-hom-def hom-def bijectionAG-def
  group-hom-axioms-def, intro conjI group-BijGroup, safe)
fix  $\pi :: 'a \Rightarrow 'a$ 
assume  $\pi \in \text{carrier } (\text{BijGroup UNIV})$ 
hence  $\text{bij } \pi$ 
unfolding BijGroup-def Bij-def
by simp
thus  $\psi\text{-neutral}_c \pi \in \text{carrier } (\text{BijGroup UNIV})$ 
unfolding  $\psi\text{-neutral}_c.\text{simps}$ 
using rewrite-carrier
by blast
fix  $\pi' :: 'a \Rightarrow 'a$ 

```

**show**  $\psi\text{-neutral}_c (\pi \otimes \text{BijGroup UNIV } \pi') =$   
 $\psi\text{-neutral}_c \pi \otimes \text{BijGroup UNIV } \psi\text{-neutral}_c \pi'$   
**unfolding**  $\psi\text{-neutral}_c.\text{simps}$   
**by** *safe*  
**qed**

**interpretation**  $\psi\text{-neutral}_w\text{-action}$ : *group-action bijection<sub>AG</sub> UNIV  $\psi\text{-neutral}_w$*   
**proof** (*unfold group-action-def group-hom-def hom-def bijection<sub>AG</sub>-def*  
*group-hom-axioms-def, intro conjI group-BijGroup, safe*)

**fix**  $\pi :: 'a \Rightarrow 'a$   
**assume** *bij-carrier*:  $\pi \in \text{carrier} (\text{BijGroup UNIV})$   
**hence** *bij*  $\pi$   
**unfolding** *bijection<sub>AG</sub>-def BijGroup-def Bij-def*  
**by** *simp*  
**hence** *bij* ( $\psi\text{-neutral}_w \pi$ )  
**unfolding** *bijection<sub>AG</sub>-def BijGroup-def Bij-def  $\psi\text{-neutral}_w.\text{simps}$*   
**using** *rel-rename-bij*  
**by** *blast*  
**thus** *group-elem*:  $\psi\text{-neutral}_w \pi \in \text{carrier} (\text{BijGroup UNIV})$   
**using** *rewrite-carrier*  
**by** *blast*  
**moreover** **fix**  $\pi' :: 'a \Rightarrow 'a$   
**assume** *bij-carrier'*:  $\pi' \in \text{carrier} (\text{BijGroup UNIV})$   
**hence** *bij*  $\pi'$   
**unfolding** *bijection<sub>AG</sub>-def BijGroup-def Bij-def*  
**by** *simp*  
**hence** *bij* ( $\psi\text{-neutral}_w \pi'$ )  
**unfolding** *bijection<sub>AG</sub>-def BijGroup-def Bij-def  $\psi\text{-neutral}_w.\text{simps}$*   
**using** *rel-rename-bij*  
**by** *blast*  
**hence** *group-elem'*:  $\psi\text{-neutral}_w \pi' \in \text{carrier} (\text{BijGroup UNIV})$   
**using** *rewrite-carrier*  
**by** *blast*  
**moreover** **have**  $\psi\text{-neutral}_w (\pi \otimes \text{BijGroup UNIV } \pi') = \psi\text{-neutral}_w (\pi \circ \pi')$   
**using** *bij-carrier bij-carrier' rewrite-mult-univ*  
**by** *metis*  
**ultimately show**  
 $\psi\text{-neutral}_w (\pi \otimes \text{BijGroup UNIV } \pi') =$   
 $\psi\text{-neutral}_w \pi \otimes \text{BijGroup UNIV } \psi\text{-neutral}_w \pi'$   
**using** *rewrite-mult-univ*  
**by** *fastforce*  
**qed**

**lemma** *neutral-act-presv-SCF-symmetry*: *is-symmetry* ( $\lambda \mathcal{E}. \text{limit-SCF}$   
 $(\text{alternatives-}\mathcal{E} \ \mathcal{E}) \text{ UNIV}) (\text{action-induced-equivariance} (\text{carrier bijection}_{AG})$   
 $\text{well-formed-elections } (\varphi\text{-neutral well-formed-elections}) (\text{set-action } \psi\text{-neutral}_c))$   
**proof** (*unfold rewrite-equivariance, safe*)  
**fix**  
 $\pi :: 'a \Rightarrow 'a$  **and**

```

  A :: 'a set and
  V :: 'v set and
  p :: 'v  $\Rightarrow$  ('a  $\times$  'a) set and
  r :: 'a
assume
  carrier- $\pi$ :  $\pi \in$  carrier bijectionAG and
  prof: (A, V, p)  $\in$  well-formed-elections
{
  moreover assume
    r  $\in$  limit-SCF
    (alternatives- $\mathcal{E}$  ( $\varphi$ -neutral well-formed-elections  $\pi$  (A, V, p))) UNIV
  ultimately show
    r  $\in$  set-action  $\psi$ -neutralc  $\pi$  (limit-SCF (alternatives- $\mathcal{E}$  (A, V, p))) UNIV
  by auto
}
{
  moreover assume
    r  $\in$  set-action  $\psi$ -neutralc  $\pi$  (limit-SCF (alternatives- $\mathcal{E}$  (A, V, p))) UNIV
  ultimately show
    r  $\in$  limit-SCF
    (alternatives- $\mathcal{E}$  ( $\varphi$ -neutral well-formed-elections  $\pi$  (A, V, p))) UNIV
  using prof
  by simp
}
qed

lemma neutral-act-presv-SWF-symmetry: is-symmetry ( $\lambda \mathcal{E}. \text{limit-SWF}$ 
  (alternatives- $\mathcal{E}$   $\mathcal{E}$ ) UNIV) (action-induced-equivariance (carrier bijectionAG)
  well-formed-elections ( $\varphi$ -neutral well-formed-elections) (set-action  $\psi$ -neutralw))
proof (unfold rewrite-equivariance voters- $\mathcal{E}$ .simps profile- $\mathcal{E}$ .simps set-action.simps,
  safe)
show  $\bigwedge \pi A V p r.$ 
   $\pi \in$  carrier bijectionAG  $\implies$  (A, V, p)  $\in$  well-formed-elections
 $\implies r \in$  limit-SWF
  (alternatives- $\mathcal{E}$  ( $\varphi$ -neutral well-formed-elections  $\pi$  (A, V, p))) UNIV
 $\implies r \in \psi$ -neutralw  $\pi$  ' limit-SWF (alternatives- $\mathcal{E}$  (A, V, p)) UNIV
proof -
fix
   $\pi :: 'c \Rightarrow 'c$  and
  A :: 'c set and
  V :: 'v set and
  p :: ('c, 'v) Profile and
  r :: 'c rel
let ?r-inv =  $\psi$ -neutralw (the-inv  $\pi$ ) r
assume
  carrier- $\pi$ :  $\pi \in$  carrier bijectionAG and
  prof: (A, V, p)  $\in$  well-formed-elections
have inv-carrier: the-inv  $\pi \in$  carrier bijectionAG
  using carrier- $\pi$  bij-betw-the-inv-into

```



```

unfolding bijectionAG-def rewrite-carrier
by simp
moreover have the-inv  $\pi \circ \pi = id$ 
using carrier- $\pi$  universal-set-carrier-imp-bij-group bij-is-inj the-inv-f-f
unfolding bijectionAG-def
by fastforce
moreover have 1 bijectionAG = id
unfolding bijectionAG-def BijGroup-def
by auto
ultimately have the-inv  $\pi \otimes \text{bijection}_{AG} \pi = \mathbf{1}$  bijectionAG
using carrier- $\pi$  rewrite-mult-univ
unfolding bijectionAG-def
by metis
hence inv bijectionAG  $\pi = \text{the-inv } \pi$ 
using carrier- $\pi$  inv-carrier  $\psi$ -neutralc-action.group-hom group.inv-closed
group.inv-solve-right group.l-inv group-BijGroup group-hom.hom-one
group-hom.one-closed
unfolding bijectionAG-def
by metis
hence neutral-r:  $r = \psi\text{-neutral}_w \pi \text{ ?}r\text{-inv}$ 
using carrier- $\pi$  inv-carrier iso-tuple-UNIV-I  $\psi$ -neutralw-action.orbit-sym-aux
by metis
have bij-inv: bij (the-inv  $\pi$ )
using carrier- $\pi$  bij-betw-the-inv-into universal-set-carrier-imp-bij-group
unfolding bijectionAG-def
by blast
hence the-inv- $\pi$ : (the-inv  $\pi$ ) ‘  $\pi$  ‘  $A = A$ 
using carrier- $\pi$  UNIV-I bij-betw-imp-surj universal-set-carrier-imp-bij-group
f-the-inv-into-f-bij-betw image-f-inv-f surj-imp-inv-eq
unfolding bijectionAG-def
by metis
assume
 $r \in \text{limit-SWF}$ 
(alternatives- $\mathcal{E}$  ( $\varphi$ -neutral well-formed-elections  $\pi (A, V, p)$ )) UNIV
hence  $r \in \text{limit-SWF } (\pi \text{ ‘ } A)$  UNIV
unfolding  $\varphi$ -neutral.simps
using prof
by simp
hence linear-order-on ( $\pi \text{ ‘ } A$ )  $r$ 
by auto
hence lin-inv: linear-order-on  $A$  ?r-inv
using rel-rename-sound bij-inv bij-is-inj the-inv- $\pi$ 
unfolding  $\psi$ -neutralw.simps linear-order-on-def preorder-on-def partial-order-on-def
by metis
hence  $\forall (a, b) \in ?r\text{-inv}. a \in A \wedge b \in A$ 
unfolding linear-order-on-def partial-order-on-def preorder-on-def
using refl-on-def'
by metis
hence limit  $A$  ?r-inv =  $\{(a, b). (a, b) \in ?r\text{-inv}\}$ 

```

by *auto*  
 also have  $\dots = ?r\text{-inv}$   
 by *blast*  
 finally have  $\dots = \text{limit } A \text{ } ?r\text{-inv}$   
 by *blast*  
 hence  $\exists r' \in \text{UNIV}. \psi\text{-neutral}_w (\text{the-inv } \pi) r = \text{limit } A \text{ } r' \wedge \text{linear-order-on}$   
 $A (\text{limit } A \text{ } r')$   
 using *UNIV-I lin-inv*  
 by (*metis (no-types)*)  
 hence  $?r\text{-inv} \in \text{limit-SWF } (\text{alternatives-}\mathcal{E} (A, V, p)) \text{ UNIV}$   
 unfolding *limit-SWF.simps alternatives-}\mathcal{E}.simps*  
 using *fst-conv mem-Collect-eq*  
 by (*metis (mono-tags, lifting)*)  
 thus *lim-el- $\pi$* :  
 $r \in \psi\text{-neutral}_w \pi \text{ ' limit-SWF } (\text{alternatives-}\mathcal{E} (A, V, p)) \text{ UNIV}$   
 using *neutral-r*  
 by *blast*  
 qed  
 moreover  
 fix  
 $\pi :: 'a \Rightarrow 'a$  and  
 $A :: 'a \text{ set}$  and  
 $V :: 'v \text{ set}$  and  
 $p :: ('a, 'v) \text{ Profile}$  and  
 $r :: 'a \text{ rel}$   
 assume  
 $\text{carrier-}\pi: \pi \in \text{carrier bijection}_{AG}$  and  
 $\text{prof}: (A, V, p) \in \text{well-formed-elections}$   
 hence *prof- $\pi$* :  
 $\varphi\text{-neutral well-formed-elections } \pi (A, V, p) \in \text{well-formed-elections}$   
 using  *$\varphi\text{-neutral-action.element-image}$*   
 by *blast*  
 moreover have *inv-group-elem*:  $\text{inv bijection}_{AG} \pi \in \text{carrier bijection}_{AG}$   
 using *carrier- $\pi$   $\psi\text{-neutral}_c\text{-action.group-hom group.inv-closed}$*   
 unfolding *group-hom-def*  
 by *metis*  
 moreover have  $\varphi\text{-neutral well-formed-elections } (\text{inv bijection}_{AG} \pi)$   
 $(\varphi\text{-neutral well-formed-elections } \pi (A, V, p)) \in \text{well-formed-elections}$   
 using *prof  $\varphi\text{-neutral-action.element-image inv-group-elem prof-}\pi$*   
 by *metis*  
 moreover assume  $r \in \text{limit-SWF } (\text{alternatives-}\mathcal{E} (A, V, p)) \text{ UNIV}$   
 hence  $r \in \text{limit-SWF}$   
 $(\text{alternatives-}\mathcal{E} (\varphi\text{-neutral well-formed-elections } (\text{inv bijection}_{AG} \pi)$   
 $(\varphi\text{-neutral well-formed-elections } \pi (A, V, p)))) \text{ UNIV}$   
 using  *$\varphi\text{-neutral-action.orbit-sym-aux carrier-}\pi \text{ prof}$*   
 by *metis*  
 ultimately have  
 $r \in \psi\text{-neutral}_w (\text{inv bijection}_{AG} \pi) \text{ '}$   
 $\text{limit-SWF}$

```

      (alternatives- $\mathcal{E}$  ( $\varphi$ -neutral well-formed-elections  $\pi$  ( $A$ ,  $V$ ,  $p$ ))) UNIV
    using prod.collapse
  by metis
thus  $\psi$ -neutralw  $\pi$   $r \in \text{limit-SWF}$ 
      (alternatives- $\mathcal{E}$  ( $\varphi$ -neutral well-formed-elections  $\pi$  ( $A$ ,  $V$ ,  $p$ ))) UNIV
    using carrier- $\pi$   $\psi$ -neutralw-action.group-action-axioms
       $\psi$ -neutralw-action.inj-prop group-action.orbit-sym-aux
      inj-image-mem-iff inv-group-elem iso-tuple-UNIV-I
    by (metis (no-types, lifting))
qed

```

### 1.10.5 Homogeneity Lemmas

**definition**  $\text{reflp-on}' :: 'a \text{ set} \Rightarrow 'a \text{ rel} \Rightarrow \text{bool}$  **where**  
 $\text{reflp-on}' A r \equiv \text{reflp-on } A (\lambda x y. (x, y) \in r)$

**lemma**  $\text{refl-homogeneity}_{\mathcal{R}}$ :  
**fixes**  $\mathcal{E} :: ('a, 'v) \text{ Election set}$   
**assumes**  $\mathcal{E} \subseteq \text{finite-}\mathcal{V}\text{-elections}$   
**shows**  $\text{reflp-on}' \mathcal{E} (\text{homogeneity}_{\mathcal{R}} \mathcal{E})$   
**using** *assms*  
**unfolding**  $\text{reflp-on}'\text{-def}$   $\text{reflp-on-def}$   $\text{finite-}\mathcal{V}\text{-elections-def}$   
**by** *auto*

**lemma** (**in result**)  $\text{homogeneity-action-presv-symmetry}$ :  
 $\text{is-symmetry } (\lambda \mathcal{E}. \text{limit } (\text{alternatives-}\mathcal{E} \mathcal{E}) \text{ UNIV})$   
 $(\text{Invariance } (\text{homogeneity}_{\mathcal{R}} \text{ UNIV}))$   
**by** *simp*

**lemma**  $\text{refl-homogeneity}_{\mathcal{R}}'$ :  
**fixes**  $\mathcal{E} :: ('a, 'v :: \text{linorder}) \text{ Election set}$   
**assumes**  $\mathcal{E} \subseteq \text{finite-}\mathcal{V}\text{-elections}$   
**shows**  $\text{reflp-on}' \mathcal{E} (\text{homogeneity}_{\mathcal{R}}' \mathcal{E})$   
**using** *assms*  
**unfolding**  $\text{homogeneity}_{\mathcal{R}}'\text{-simps}$   $\text{reflp-on}'\text{-def}$   $\text{reflp-on-def}$   $\text{finite-}\mathcal{V}\text{-elections-def}$   
**by** *auto*

**lemma** (**in result**)  $\text{homogeneity}'\text{-action-presv-symmetry}$ :  
 $\text{is-symmetry } (\lambda \mathcal{E}. \text{limit } (\text{alternatives-}\mathcal{E} \mathcal{E}) \text{ UNIV})$   
 $(\text{Invariance } (\text{homogeneity}_{\mathcal{R}}' \text{ UNIV}))$   
**by** *simp*

### 1.10.6 Reversal Symmetry Lemmas

**lemma**  $\text{reverse-reverse-id}$ :  $\text{reverse-rel} \circ \text{reverse-rel} = \text{id}$   
**by** *auto*

**lemma**  $\text{reverse-rel-limit}$ :  
**fixes**  
 $A :: 'a \text{ set}$  **and**

```

  r :: 'a rel
shows reverse-rel (limit A r) = limit A (reverse-rel r)
unfolding reverse-rel.simps limit.simps
by blast

lemma reverse-rel-lin-ord:
  fixes
    A :: 'a set and
    r :: 'a rel
  assumes linear-order-on A r
  shows linear-order-on A (reverse-rel r)
  using assms
  unfolding reverse-rel.simps linear-order-on-def partial-order-on-def
    total-on-def antisym-def preorder-on-def refl-on-def trans-def
  by blast

interpretation reversalG-group: group reversalG
proof
  show 1 reversalG ∈ carrier reversalG
    unfolding reversalG-def
    by simp
next
  show carrier reversalG ⊆ Units reversalG
    unfolding reversalG-def Units-def
    using reverse-inverse-id
    by auto
next
  fix α :: 'a rel ⇒ 'a rel
  show α ⊗ reversalG 1 reversalG = α
    unfolding reversalG-def
    by auto
  assume α-elem: α ∈ carrier reversalG
  thus 1 reversalG ⊗ reversalG α = α
    unfolding reversalG-def
    by auto
  fix α' :: 'a rel ⇒ 'a rel
  assume α'-elem: α' ∈ carrier reversalG
  thus α ⊗ reversalG α' ∈ carrier reversalG
    using α-elem reverse-inverse-id
    unfolding reversalG-def
    by auto
  fix z :: 'a rel ⇒ 'a rel
  assume z ∈ carrier reversalG
  thus α ⊗ reversalG α' ⊗ reversalG z = α ⊗ reversalG (α' ⊗ reversalG z)
    using α-elem α'-elem
    unfolding reversalG-def
    by auto
qed

```

**interpretation**  $\varphi$ -reverse-action: group-action reversal<sub>G</sub> well-formed-elections  
 $\varphi$ -reverse well-formed-elections

**proof** (unfold group-action-def group-hom-def group-hom-axioms-def hom-def,  
intro conjI group-BijGroup CollectI ballI funcsetI)  
**show** Group.group reversal<sub>G</sub>  
by safe

**next**  
**show** carrier-elect-gen:  
 $\bigwedge \pi. \pi \in \text{carrier reversal}_G$   
 $\implies \varphi$ -reverse well-formed-elections  $\pi \in \text{carrier (BijGroup well-formed-elections)}$

**proof** –  
**fix**  $\pi :: 'c \text{ rel} \Rightarrow 'c \text{ rel}$   
**assume**  $\pi \in \text{carrier reversal}_G$   
**hence**  $\pi$ -cases:  $\pi \in \{\text{id}, \text{reverse-rel}\}$   
**unfolding** reversal<sub>G</sub>-def  
by auto  
**hence** [simp]:  $\text{rel-app } \pi \circ \text{rel-app } \pi = \text{id}$   
**using** reverse-reverse-id  
by fastforce  
**have**  $\forall \mathcal{E}. \text{rel-app } \pi (\text{rel-app } \pi \mathcal{E}) = \mathcal{E}$   
by (simp add: pointfree-idE)

**moreover have**  $\forall \mathcal{E} \in \text{well-formed-elections}. \text{rel-app } \pi \mathcal{E} \in \text{well-formed-elections}$   
**unfolding** well-formed-elections-def profile-def  
**using**  $\pi$ -cases reverse-rel-lin-ord rel-app.simps fun.map-id  
by fastforce  
**hence**  $\text{rel-app } \pi \text{ ` well-formed-elections } \subseteq \text{well-formed-elections}$   
by blast

**ultimately have**  $\text{bij-betw } (\text{rel-app } \pi) \text{ well-formed-elections well-formed-elections}$   
**using** bij-betw-byWitness[of well-formed-elections]  
by blast  
**hence**  $\text{bij-betw } (\varphi\text{-reverse well-formed-elections } \pi) \text{ well-formed-elections well-formed-elections}$   
**unfolding**  $\varphi$ -reverse.simps  
**using** bij-betw-ext  
by blast

**moreover have**  $\varphi$ -reverse well-formed-elections  $\pi \in \text{extensional well-formed-elections}$   
**unfolding** extensional-def  
by simp

**ultimately show**  
 $\varphi$ -reverse well-formed-elections  $\pi \in \text{carrier (BijGroup well-formed-elections)}$   
**unfolding** BijGroup-def Bij-def  
by simp

**qed**

**moreover fix**  $\pi \pi' :: 'a \text{ rel} \Rightarrow 'a \text{ rel}$   
**assume**  
rev:  $\pi \in \text{carrier reversal}_G$  and  
rev':  $\pi' \in \text{carrier reversal}_G$

**ultimately have** carrier-elect:  
 $\varphi$ -reverse well-formed-elections  $\pi \in \text{carrier (BijGroup well-formed-elections)}$

```

  by blast
have  $\varphi$ -reverse well-formed-elections  $(\pi \otimes \text{reversal}_{\mathcal{G}} \pi') =$ 
  extensional-continuation  $(\text{rel-app } (\pi \circ \pi'))$  well-formed-elections
  unfolding reversal $_{\mathcal{G}}$ -def
  by simp
moreover have  $\text{rel-app } (\pi \circ \pi') = \text{rel-app } \pi \circ \text{rel-app } \pi'$ 
  using rel-app.simps
  by fastforce
ultimately have
   $\varphi$ -reverse well-formed-elections  $(\pi \otimes \text{reversal}_{\mathcal{G}} \pi') =$ 
  extensional-continuation  $(\text{rel-app } \pi \circ \text{rel-app } \pi')$  well-formed-elections
  by metis
moreover have
   $\forall A \ V \ p. \forall v \in V. \text{linear-order-on } A \ (p \ v) \longrightarrow \text{linear-order-on } A \ (\pi' \ (p \ v))$ 
  using empty-iff id-apply insert-iff rev' reverse-rel-lin-ord
  unfolding partial-object.simps reversal $_{\mathcal{G}}$ -def
  by metis
hence extensional-continuation
   $(\varphi$ -reverse well-formed-elections  $\pi \circ \varphi$ -reverse well-formed-elections  $\pi')$ 
  well-formed-elections =
  extensional-continuation  $(\text{rel-app } \pi \circ \text{rel-app } \pi')$  well-formed-elections
  unfolding well-formed-elections-def profile-def
  by fastforce
moreover have extensional-continuation
   $(\varphi$ -reverse well-formed-elections  $\pi \circ \varphi$ -reverse well-formed-elections  $\pi')$ 
  well-formed-elections =
   $\varphi$ -reverse well-formed-elections  $\pi$ 
   $\otimes \text{BijGroup well-formed-elections } \varphi$ -reverse well-formed-elections  $\pi'$ 
  using carrier-elect-gen carrier-elect rev' rewrite-mult
  by metis
ultimately show
   $\varphi$ -reverse well-formed-elections  $(\pi \otimes \text{reversal}_{\mathcal{G}} \pi') =$ 
   $\varphi$ -reverse well-formed-elections  $\pi$ 
   $\otimes \text{BijGroup well-formed-elections } \varphi$ -reverse well-formed-elections  $\pi'$ 
  by metis
qed

interpretation  $\psi$ -reverse-action: group-action reversal $_{\mathcal{G}}$  UNIV  $\psi$ -reverse
proof (unfold group-action-def group-hom-def group-hom-axioms-def hom-def  $\psi$ -reverse.simps,
  intro conjI group-BijGroup CollectI ballI funcsetI)
  show Group.group reversal $_{\mathcal{G}}$ 
  by safe
next
  fix  $\pi :: 'a \text{ rel} \Rightarrow 'a \text{ rel}$ 
  assume  $\pi \in \text{carrier reversal}_{\mathcal{G}}$ 
  hence  $\pi \in \{\text{id}, \text{reverse-rel}\}$ 
  unfolding reversal $_{\mathcal{G}}$ -def
  by force
  hence bij  $\pi$ 

```

```

    using reverse-reverse-id bij-id insertE o-bij singleton-iff
    by metis
  thus  $\pi \in \text{carrier } (\text{BijGroup } \text{UNIV})$ 
    using rewrite-carrier
    by blast
next
  fix  $\pi \pi' :: 'a \text{ rel} \Rightarrow 'a \text{ rel}$ 
  assume
     $\pi \in \text{carrier reversal}_G$  and
     $\pi' \in \text{carrier reversal}_G$ 
  hence  $\text{bij } \pi' \wedge \text{bij } \pi$ 
    using singleton-iff comp-apply id-apply involuntary-imp-bij reverse-reverse-id
    unfolding bij-id insert-iff reversalG-def partial-object.select-convs
    by (metis (mono-tags, opaque-lifting))
  hence  $\pi \otimes \text{BijGroup } \text{UNIV } \pi' = \pi \circ \pi'$ 
    using rewrite-carrier rewrite-mult-univ
    by blast
  also have  $\dots = \pi \otimes \text{reversal}_G \pi'$ 
    unfolding reversalG-def
    by force
  finally show  $\pi \otimes \text{reversal}_G \pi' = \pi \otimes \text{BijGroup } \text{UNIV } \pi'$ 
    by presburger
qed

lemma reversal-symm-act-presv-symmetry: is-symmetry  $(\lambda \mathcal{E}. \text{limit-SWF } (\text{alternatives-}\mathcal{E} \text{ } \mathcal{E}) \text{ UNIV})$ 
  (action-induced-equivariance (carrier reversalG) well-formed-elections
   ( $\varphi$ -reverse well-formed-elections) (set-action  $\psi$ -reverse))
proof (unfold rewrite-equivariance, clarify)
  fix
     $\pi :: 'a \text{ rel} \Rightarrow 'a \text{ rel}$  and
     $A :: 'a \text{ set}$  and
     $V :: 'v \text{ set}$  and
     $p :: ('a, 'v) \text{ Profile}$ 
  assume  $\pi \in \text{carrier reversal}_G$ 
  hence cases:  $\pi \in \{\text{id}, \text{reverse-rel}\}$ 
    unfolding reversalG-def
    by force
  assume  $(A, V, p) \in \text{well-formed-elections}$ 
  hence eq-A:
    alternatives- $\mathcal{E}$  ( $\varphi$ -reverse well-formed-elections  $\pi (A, V, p)$ ) =  $A$ 
    by simp
  have
     $\forall r \in \{\text{limit } A \text{ } r \mid r. r \in \text{UNIV} \wedge \text{linear-order-on } A (\text{limit } A \text{ } r)\}.$ 
     $\exists r' \in \text{UNIV}. \text{reverse-rel } r = \text{limit } A (\text{reverse-rel } r')$ 
     $\wedge \text{reverse-rel } r' \in \text{UNIV} \wedge \text{linear-order-on } A (\text{limit } A (\text{reverse-rel } r'))$ 
    using reverse-rel-limit[of A] reverse-rel-lin-ord
    by force
  hence

```

$\forall r \in \{\text{limit } A \ r \mid r. r \in \text{UNIV} \wedge \text{linear-order-on } A \ (\text{limit } A \ r)\}.$   
 $\text{reverse-rel } r \in \{\text{limit } A \ (\text{reverse-rel } r') \mid r'. \text{reverse-rel } r' \in \text{UNIV} \wedge \text{linear-order-on } A \ (\text{limit } A \ (\text{reverse-rel } r'))\}$   
**by** *blast*  
**moreover have**  
 $\{\text{limit } A \ (\text{reverse-rel } r') \mid r'. \text{reverse-rel } r' \in \text{UNIV} \wedge \text{linear-order-on } A \ (\text{limit } A \ (\text{reverse-rel } r'))\}$   
 $\subseteq \{\text{limit } A \ r \mid r. r \in \text{UNIV} \wedge \text{linear-order-on } A \ (\text{limit } A \ r)\}$   
**by** *blast*  
**ultimately have**  
 $\forall r \in \text{limit-SWF } A \ \text{UNIV}. \text{reverse-rel } r \in \text{limit-SWF } A \ \text{UNIV}$   
**unfolding** *limit-SWF.simps*  
**by** *blast*  
**hence subset:**  
 $\forall r \in \text{limit-SWF } A \ \text{UNIV}. \pi \ r \in \text{limit-SWF } A \ \text{UNIV}$   
**using** *cases*  
**by** *fastforce*  
**hence**  $\forall r \in \text{limit-SWF } A \ \text{UNIV}. r \in \pi \text{ 'limit-SWF } A \ \text{UNIV}$   
**using** *reverse-reverse-id comp-apply empty-iff id-apply image-eqI insert-iff cases*  
**by** *metis*  
**hence**  $\pi \text{ 'limit-SWF } A \ \text{UNIV} = \text{limit-SWF } A \ \text{UNIV}$   
**using** *subset*  
**by** *blast*  
**hence**  $\text{set-action } \psi\text{-reverse } \pi \ (\text{limit-SWF } A \ \text{UNIV}) = \text{limit-SWF } A \ \text{UNIV}$   
**unfolding** *set-action.simps*  
**by** *simp*  
**also have**  
 $\dots = \text{limit-SWF}$   
 $(\text{alternatives-}\mathcal{E} \ (\varphi\text{-reverse well-formed-elections } \pi \ (A, V, p))) \ \text{UNIV}$   
**using** *eq-A*  
**by** *simp*  
**finally show**  
 $\text{limit-SWF} \ (\text{alternatives-}\mathcal{E} \ (\varphi\text{-reverse well-formed-elections } \pi \ (A, V, p))) \ \text{UNIV}$   
 $=$   
 $\text{set-action } \psi\text{-reverse } \pi \ (\text{limit-SWF} \ (\text{alternatives-}\mathcal{E} \ (A, V, p))) \ \text{UNIV}$   
**by** *simp*  
**qed**  
**end**

## 1.11 Result-Dependent Voting Rule Properties

**theory** *Property-Interpretations*  
**imports** *Voting-Symmetry*  
*Result-Interpretations*  
**begin**



### 1.11.1 Property Definitions

The interpretation of equivariance properties generally depends on the result type. For example, neutrality for social choice rules means that single winners are renamed when the candidates in the votes are consistently renamed. For social welfare results, the complete result rankings must be renamed. New result-type-dependent definitions for properties can be added here.

```

locale result-properties = result +
  fixes  $\psi :: ('a \Rightarrow 'a, 'b) \text{ binary-fun}$  and
     $\nu :: 'v \text{ itself}$ 
  assumes
    action-neutral: group-action bijectionAG UNIV  $\psi$  and
    neutrality:
      is-symmetry ( $\lambda \mathcal{E} :: ('a, 'v) \text{ Election. limit (alternatives-}\mathcal{E} \mathcal{E}) \text{ UNIV}$ )
        (action-induced-equivariance (carrier bijectionAG)
          well-formed-elections
            ( $\varphi$ -neutral well-formed-elections) (set-action  $\psi$ ))

sublocale result-properties  $\subseteq$  result
  using result-axioms
  by safe

```

### 1.11.2 Interpretations

```

global-interpretation SCF-properties: result-properties well-formed-SCF
  limit-SCF  $\psi$ -neutralc
  unfolding result-properties-def result-properties-axioms-def
  using neutral-act-presv-SCF-symmetry  $\psi$ -neutralc-action.group-action-axioms
    SCF-result.result-axioms
  by blast

global-interpretation SWF-properties: result-properties well-formed-SWF
  limit-SWF  $\psi$ -neutralw
  unfolding result-properties-def result-properties-axioms-def
  using neutral-act-presv-SWF-symmetry  $\psi$ -neutralw-action.group-action-axioms
    SWF-result.result-axioms
  by blast

end

```

## Chapter 2

# Refined Types

### 2.1 Preference List

```
theory Preference-List
  imports ../Preference-Relation
           HOL-Combinatorics.Multiset-Permutations
           List-Index.List-Index
begin
```

Preference lists derive from preference relations, ordered from most to least preferred alternative.

#### 2.1.1 Well-Formedness

```
type-synonym 'a Preference-List = 'a list
```

```
abbreviation well-formed-l :: 'a Preference-List  $\Rightarrow$  bool where
  well-formed-l l  $\equiv$  distinct l
```

#### 2.1.2 Auxiliary Lemmas About Lists

```
lemma is-arg-min-equal:
```

```
  fixes
    f g :: 'a  $\Rightarrow$  'b :: ord and
    S :: 'a set and
    x :: 'a
  assumes  $\forall x \in S. f\ x = g\ x$ 
  shows is-arg-min f  $(\lambda s. s \in S) x = is-arg-min\ g\ (\lambda s. s \in S) x$ 
proof (unfold is-arg-min-def, cases  $x \notin S$ )
  case True
  thus  $(x \in S \wedge (\nexists y. y \in S \wedge f\ y < f\ x)) = (x \in S \wedge (\nexists y. y \in S \wedge g\ y < g\ x))$ 
    by safe
next
  case x-in-S: False
  thus  $(x \in S \wedge (\nexists y. y \in S \wedge f\ y < f\ x)) = (x \in S \wedge (\nexists y. y \in S \wedge g\ y < g\ x))$ 
```

```

proof (cases  $\exists y. (\lambda s. s \in S) y \wedge f y < f x$ )
  case y: True
  then obtain y :: 'a where
     $(\lambda s. s \in S) y \wedge f y < f x$ 
  by metis
  hence  $(\lambda s. s \in S) y \wedge g y < g x$ 
  using x-in-S assms
  by metis
  thus ?thesis
  using y
  by metis
next
  case not-y: False
  have  $\neg (\exists y. (\lambda s. s \in S) y \wedge g y < g x)$ 
  proof (safe)
    fix y :: 'a
    assume
      y  $\in S$  and
      g y  $< g x$ 
    moreover have  $\forall a \in S. f a = g a$ 
    using assms
    by simp
    moreover from this have g x = f x
    using x-in-S
    by metis
    ultimately show False
    using not-y
    by (metis (no-types))
  qed
  thus ?thesis
  using x-in-S not-y
  by simp
qed
qed

lemma list-cons-presv-finiteness:
  fixes
    A :: 'a set and
    S :: 'a list set
  assumes
    fin-A: finite A and
    fin-B: finite S
  shows finite  $\{a \# l \mid a \in A \wedge l \in S\}$ 
proof –
  let ?P =  $\lambda A. \text{finite } \{a \# l \mid a \in A \wedge l \in S\}$ 
  have  $\forall a \in A'. \text{finite } A' \longrightarrow a \notin A' \longrightarrow ?P A' \longrightarrow ?P (\text{insert } a A')$ 
  proof (safe)
    fix
      a :: 'a and

```

```

    A' :: 'a set
  assume finite {a#l | a l. a ∈ A' ∧ l ∈ S}
  moreover have
    {a'#l | a' l. a' ∈ insert a A' ∧ l ∈ S} =
      {a#l | a l. a ∈ A' ∧ l ∈ S} ∪ {a#l | l. l ∈ S}
  by blast
  moreover have finite {a#l | l. l ∈ S}
  using fin-B
  by simp
  ultimately show ?P (insert a A')
  by simp
qed
thus ?P A
  using finite-induct[of - ?P] fin-A
  by simp
qed

```

```

lemma listset-finiteness:
  fixes l :: 'a set list
  assumes ∀ i :: nat. i < length l ⟶ finite (!i)
  shows finite (listset l)
  using assms
proof (induct l)
  case Nil
  show finite (listset [])
  by simp
next
  case (Cons a l)
  fix
    a :: 'a set and
    l :: 'a set list
  assume ∀ i :: nat < length (a#l). finite ((a#l)!i)
  hence
    finite a and
    ∀ i < length l. finite (!i)
  by auto
  moreover assume
    ∀ i :: nat < length l. finite (!i) ⟹ finite (listset l)
  ultimately have
    finite (listset l) and
    finite {a'#l' | a' l'. a' ∈ a ∧ l' ∈ (listset l)}
  using list-cons-presv-finiteness
  by (blast, blast)
  thus finite (listset (a#l))
  by (simp add: set-Cons-def)
qed

```

```

lemma all-ls-elems-same-len:
  fixes l :: 'a set list

```

**shows**  $\forall l' :: 'a \text{ list}. l' \in \text{listset } l \longrightarrow \text{length } l' = \text{length } l$   
**proof** (*induct l, safe*)  
   **case** *Nil*  
   **fix**  $l :: 'a \text{ list}$   
   **assume**  $l \in \text{listset } []$   
   **thus**  $\text{length } l = \text{length } []$   
     **by** *simp*  
**next**  
   **case** (*Cons a l*)  
   **moreover fix**  
      $a :: 'a \text{ set}$  **and**  
      $l :: 'a \text{ set list}$  **and**  
      $m :: 'a \text{ list}$   
   **assume**  
      $\forall l'. l' \in \text{listset } l \longrightarrow \text{length } l' = \text{length } l$  **and**  
      $m \in \text{listset } (a \# l)$   
   **moreover have**  
      $\forall a' l' :: 'a \text{ set list}. \text{listset } (a' \# l') =$   
        $\{b \# m \mid b \text{ m. } b \in a' \wedge m \in \text{listset } l'\}$   
     **by** (*simp add: set-Cons-def*)  
   **ultimately show**  $\text{length } m = \text{length } (a \# l)$   
     **by** *force*  
**qed**

**lemma** *all-ls-elems-in-ls-set*:  
   **fixes**  $l :: 'a \text{ set list}$   
   **shows**  $\forall l' \in \text{listset } l. \forall i :: \text{nat} < \text{length } l'. l'!i \in l!i$   
**proof** (*induct l, safe*)  
   **case** *Nil*  
   **fix**  
      $l' :: 'a \text{ list}$  **and**  
      $i :: \text{nat}$   
   **assume**  
      $l' \in \text{listset } []$  **and**  
      $i < \text{length } l'$   
   **thus**  $l'!i \in []!i$   
     **by** *simp*  
**next**  
   **case** (*Cons a l*)  
   **moreover fix**  
      $a :: 'a \text{ set}$  **and**  
      $l :: 'a \text{ set list}$  **and**  
      $l' :: 'a \text{ list}$  **and**  
      $i :: \text{nat}$   
   **assume**  
      $\forall l' \in \text{listset } l. \forall i :: \text{nat} < \text{length } l'. l'!i \in l!i$  **and**  
      $l' \in \text{listset } (a \# l)$  **and**  
      $i < \text{length } l'$   
   **moreover from this have**  $l' \in \text{set-Cons } a (\text{listset } l)$

by *simp*  
 hence  $\exists b m. l' = b \# m \wedge b \in a \wedge m \in (\text{listset } l)$   
 unfolding *set-Cons-def*  
 by *simp*  
 ultimately show  $l'!i \in (a \# l)!i$   
 using *nth-Cons-Suc Suc-less-eq gr0-conv-Suc*  
       *length-Cons nth-non-equal-first-eq*  
 by *metis*  
 qed

**lemma** *all-ls-in-ls-set*:  
 fixes  $l :: 'a \text{ set list}$   
 shows  $\forall l'. \text{length } l' = \text{length } l$   
        $\wedge (\forall i < \text{length } l'. l'!i \in l!i) \longrightarrow l' \in \text{listset } l$   
**proof** (*induction l, safe*)  
 case *Nil*  
 fix  $l' :: 'a \text{ list}$   
 assume  $\text{length } l' = \text{length } []$   
 thus  $l' \in \text{listset } []$   
 by *simp*  
 next  
 case (*Cons a l*)  
 fix  
    $l :: 'a \text{ set list}$  and  
    $l' :: 'a \text{ list}$  and  
    $s :: 'a \text{ set}$   
 assume  $\text{length } l' = \text{length } (s \# l)$   
 moreover then obtain  
    $t :: 'a \text{ list}$  and  
    $x :: 'a$  where  
    $l' \text{-cons}: l' = x \# t$   
 using *length-Suc-conv*  
 by *metis*  
 moreover assume  
    $\forall m. \text{length } m = \text{length } l \wedge (\forall i < \text{length } m. m!i \in l!i)$   
        $\longrightarrow m \in \text{listset } l$  and  
    $\forall i < \text{length } l'. l'!i \in (s \# l)!i$   
 ultimately have  
    $x \in s$  and  
    $t \in \text{listset } l$   
 using *diff-Suc-1 diff-Suc-eq-diff-pred zero-less-diff*  
       *zero-less-Suc length-Cons*  
 by (*metis nth-Cons-0, metis nth-Cons-Suc*)  
 thus  $l' \in \text{listset } (s \# l)$   
 using *l'-cons*  
 unfolding *listset-def set-Cons-def*  
 by *simp*  
 qed

### 2.1.3 Ranking

Rank 1 is the top preference, rank 2 the second, and so on. Rank 0 does not exist.

```
fun rank-l :: 'a Preference-List  $\Rightarrow$  'a  $\Rightarrow$  nat where
  rank-l l a = (if a  $\in$  set l then index l a + 1 else 0)
```

```
fun rank-l-idx :: 'a Preference-List  $\Rightarrow$  'a  $\Rightarrow$  nat where
  rank-l-idx l a =
    (let i = index l a in
     if i = length l then 0 else i + 1)
```

```
lemma rank-l-equiv: rank-l = rank-l-idx
unfolding member-def
by (simp add: ext index-size-conv)
```

```
lemma rank-zero-imp-not-present:
fixes
  p :: 'a Preference-List and
  a :: 'a
assumes rank-l p a = 0
shows a  $\notin$  set p
using assms
by force
```

```
definition above-l :: 'a Preference-List  $\Rightarrow$  'a  $\Rightarrow$  'a Preference-List where
  above-l r a  $\equiv$  take (rank-l r a) r
```

### 2.1.4 Definition

```
fun is-less-preferred-than-l :: 'a  $\Rightarrow$  'a Preference-List  $\Rightarrow$  'a  $\Rightarrow$  bool
  (-  $\lesssim$  - [50, 1000, 51] 50) where
  a  $\lesssim_l$  b = (a  $\in$  set l  $\wedge$  b  $\in$  set l  $\wedge$  index l a  $\geq$  index l b)
```

```
lemma rank-gt-zero:
fixes
  l :: 'a Preference-List and
  a :: 'a
assumes a  $\lesssim_l$  a
shows rank-l l a  $\geq$  1
using assms
by simp
```

```
definition pl- $\alpha$  :: 'a Preference-List  $\Rightarrow$  'a Preference-Relation where
  pl- $\alpha$  l  $\equiv$  {(a, b). a  $\lesssim_l$  b}
```

```
lemma rel-trans:
fixes l :: 'a Preference-List
shows trans (pl- $\alpha$  l)
```

```

unfolding Relation.trans-def pl- $\alpha$ -def
by simp

lemma pl- $\alpha$ -lin-order:
  fixes
    A :: 'a set and
    r :: 'a rel
  assumes r  $\in$  pl- $\alpha$  'permutations-of-set A
  shows linear-order-on A r
proof (cases A = {}, unfold linear-order-on-def total-on-def
  partial-order-on-def antisym-def preorder-on-def,
  intro conjI impI allI ballI)
  case True
  fix x y :: 'a
  show
    refl-on A r and
    trans r and
     $(x, y) \in r \implies x = y$  and
     $x \in A \implies (x, y) \in r \vee (y, x) \in r$ 
    using assms True
    unfolding pl- $\alpha$ -def
    by (simp, simp, simp, simp)
  next
  case False
  fix x y :: 'a
  show  $((\text{refl-on } A \ r \wedge \text{trans } r) \wedge$ 
     $(\forall x \ y. (x, y) \in r \longrightarrow (y, x) \in r \longrightarrow x = y))$ 
     $\wedge (\forall x \in A. \forall y \in A. x \neq y \longrightarrow (x, y) \in r \vee (y, x) \in r)$ 
  proof (intro conjI ballI allI impI)
    have  $\forall l \in \text{permutations-of-set } A. l \neq []$ 
    using assms False permutations-of-setD
    by force
    hence  $\forall a \in A. \forall l \in \text{permutations-of-set } A. (a, a) \in \text{pl-}\alpha \ l$ 
    unfolding is-less-preferred-than-l.simps
    permutations-of-set-def pl- $\alpha$ -def
    by simp
    hence  $\forall a \in A. (a, a) \in r$ 
    using assms
    by blast
    moreover have  $r \subseteq A \times A$ 
    using assms
    unfolding pl- $\alpha$ -def permutations-of-set-def
    by auto
    ultimately show refl-on A r
    unfolding refl-on-def
    by safe
  next
  show trans r
  using assms rel-trans

```



```

    by safe
next
fix x y :: 'a
assume
  (x, y) ∈ r and
  (y, x) ∈ r
moreover have
  ∀ x y. ∀ l ∈ permutations-of-set A. x ≲l y ∧ y ≲l x ⟶ x = y
  using is-less-preferred-than-l.simps index-eq-index-conv nle-le
  unfolding permutations-of-set-def
  by metis
hence ∀ x y. ∀ l ∈ pl-α ' permutations-of-set A.
  (x, y) ∈ l ∧ (y, x) ∈ l ⟶ x = y
  unfolding pl-α-def permutations-of-set-def antisym-on-def
  by blast
ultimately show x = y
  using assms
  by metis
next
fix x y :: 'a
assume
  x ∈ A and
  y ∈ A and
  x ≠ y
moreover have
  ∀ x ∈ A. ∀ y ∈ A. ∀ l ∈ permutations-of-set A.
    x ≠ y ∧ (¬ y ≲l x) ⟶ x ≲l y
  using is-less-preferred-than-l.simps
  unfolding permutations-of-set-def
  by auto
hence ∀ x ∈ A. ∀ y ∈ A. ∀ l ∈ pl-α ' permutations-of-set A.
  x ≠ y ∧ (y, x) ∉ l ⟶ (x, y) ∈ l
  using is-less-preferred-than-l.simps
  unfolding permutations-of-set-def
  unfolding pl-α-def permutations-of-set-def
  by blast
ultimately show (x, y) ∈ r ∨ (y, x) ∈ r
  using assms
  by metis
qed
qed

lemma lin-order-pl-α:
  fixes
    r :: 'a rel and
    A :: 'a set
  assumes
    lin-order: linear-order-on A r and
    fin: finite A

```

**shows**  $r \in \text{pl-}\alpha \text{ ' permutations-of-set } A$   
**proof** –  
**let**  $? \varphi = \lambda a. \text{card } ((\text{underS } r \ a) \cap A)$   
**let**  $? \text{inv} = \text{the-inv-into } A \ ? \varphi$   
**let**  $? l = \text{map } (\lambda x. ? \text{inv } x) (\text{rev } [0 ..< \text{card } A])$   
**have antisym:**  
 $\forall a \in A. \forall b \in A.$   
 $a \in (\text{underS } r \ b) \wedge b \in (\text{underS } r \ a) \longrightarrow \text{False}$   
**using** *lin-order*  
**unfolding** *underS-def linear-order-on-def partial-order-on-def antisym-def*  
**by** *blast*  
**hence**  $\forall a \in A. \forall b \in A. \forall c \in A.$   
 $a \in (\text{underS } r \ b) \longrightarrow b \in (\text{underS } r \ c) \longrightarrow a \in (\text{underS } r \ c)$   
**using** *lin-order CollectD CollectI transD*  
**unfolding** *underS-def linear-order-on-def*  
 $\text{partial-order-on-def preorder-on-def}$   
**by** (*metis (mono-tags, lifting)*)  
**hence** *a-lt-b-imp:*  
 $\forall a \in A. \forall b \in A. a \in (\text{underS } r \ b) \longrightarrow (\text{underS } r \ a) \subset (\text{underS } r \ b)$   
**using** *preorder-on-def partial-order-on-def linear-order-on-def*  
 $\text{antisym lin-order psubsetI underS-E underS-incr}$   
**by** *metis*  
**hence** *mon:*  $\forall a \in A. \forall b \in A. a \in (\text{underS } r \ b) \longrightarrow ? \varphi \ a < ? \varphi \ b$   
**using** *Int-iff Int-mono a-lt-b-imp card-mono card-subset-eq*  
 $\text{fin finite-Int order-le-imp-less-or-eq underS-E}$   
 $\text{subset-iff-psubset-eq}$   
**by** *metis*  
**moreover** **have** *total-underS:*  
 $\forall a \in A. \forall b \in A. a \neq b \longrightarrow a \in (\text{underS } r \ b) \vee b \in (\text{underS } r \ a)$   
**using** *lin-order totalp-onD totalp-on-total-on-eq*  
**unfolding** *underS-def linear-order-on-def partial-order-on-def antisym-def*  
**by** *fastforce*  
**ultimately** **have**  $\forall a \in A. \forall b \in A. a \neq b \longrightarrow ? \varphi \ a \neq ? \varphi \ b$   
**using** *order-less-imp-not-eq2*  
**by** *metis*  
**hence** *inj:*  $\text{inj-on } ? \varphi \ A$   
**using** *inj-on-def*  
**by** *blast*  
**have** *in-bounds:*  $\forall a \in A. ? \varphi \ a < \text{card } A$   
**using** *CollectD IntD1 card-seteq fin inf-le2 linorder-le-less-linear*  
**unfolding** *underS-def*  
**by** (*metis (mono-tags, lifting)*)  
**hence**  $? \varphi \text{ ' } A \subseteq \{0 ..< \text{card } A\}$   
**using** *atLeast0LessThan*  
**by** *blast*  
**moreover** **have**  $\text{card } (? \varphi \text{ ' } A) = \text{card } A$   
**using** *inj fin card-image*  
**by** *blast*  
**ultimately** **have**  $? \varphi \text{ ' } A = \{0 ..< \text{card } A\}$

```

  by (simp add: card-subset-eq)
hence bij-A: bij-betw ? $\varphi$  A {0 ..< card A}
  using inj
  unfolding bij-betw-def
  by safe
hence bij-inv: bij-betw ?inv {0 ..< card A} A
  using bij-betw-the-inv-into
  by metis
hence ?inv ‘ {0 ..< card A} = A
  unfolding bij-betw-def
  by metis
hence set-eq-A: set ?l = A
  by simp
moreover have dist-l: distinct ?l
  using bij-inv
  unfolding distinct-map
  using bij-betw-imp-inj-on
  by simp
ultimately have ?l  $\in$  permutations-of-set A
  by auto
moreover have index-eq:  $\forall a \in A. \text{index } ?l \ a = \text{card } A - 1 - ?\varphi \ a$ 
proof
  fix a :: 'a
  assume a-in-A: a  $\in$  A
  have  $\forall l. \forall i < \text{length } l. (\text{rev } l)!i = l!(\text{length } l - 1 - i)$ 
    using rev-nth
    by auto
  hence  $\forall i < \text{length } [0 ..< \text{card } A]. (\text{rev } [0 ..< \text{card } A])!i =$ 
     $[0 ..< \text{card } A]!(\text{length } [0 ..< \text{card } A] - 1 - i)$ 
    by blast
  moreover have  $\forall i < \text{card } A. [0 ..< \text{card } A]!i = i$ 
    by simp
  moreover have card-A-len:  $\text{length } [0 ..< \text{card } A] = \text{card } A$ 
    by simp
  ultimately have  $\forall i < \text{card } A. (\text{rev } [0 ..< \text{card } A])!i = \text{card } A - 1 - i$ 
    using diff-Suc-eq-diff-pred diff-less diff-self-eq-0
    less-imp-diff-less zero-less-Suc
    by metis
  moreover have  $\forall i < \text{card } A. ?l!i = ?inv ((\text{rev } [0 ..< \text{card } A])!i)$ 
    by simp
  ultimately have  $\forall i < \text{card } A. ?l!i = ?inv (\text{card } A - 1 - i)$ 
    by presburger
  moreover have
     $\text{card } A - 1 - (\text{card } A - 1 - \text{card } (\text{underS } r \ a \cap A)) =$ 
     $\text{card } (\text{underS } r \ a \cap A)$ 
    using in-bounds a-in-A
    by auto
  moreover have ?inv ( $\text{card } (\text{underS } r \ a \cap A)$ ) = a
    using a-in-A inj the-inv-into-f

```

```

    by fastforce
  ultimately have  $?!(\text{card } A - 1 - \text{card } (\text{underS } r \ a \cap A)) = a$ 
    using in-bounds a-in-A card-Diff-singleton
           card-Suc-Diff1 diff-less-Suc fin
    by metis
  thus  $\text{index } ?l \ a = \text{card } A - 1 - \text{card } (\text{underS } r \ a \cap A)$ 
    using bij-inv dist-l a-in-A card-A-len card-Diff-singleton card-Suc-Diff1
           diff-less-Suc fin index-nth-id length-map length-rev
    by metis
qed
moreover have  $pl-\alpha \ ?l = r$ 
proof (intro equalityI, unfold pl- $\alpha$ -def is-less-preferred-than-l.simps, safe)
  fix a b :: 'a
  assume
    in-bounds-a:  $a \in \text{set } ?l$  and
    in-bounds-b:  $b \in \text{set } ?l$ 
  moreover have  $\text{element-a: } ?inv \ (\text{index } ?l \ a) \in A$ 
    using bij-inv in-bounds-a atLeast0LessThan set-eq-A bij-inv
           cancel-comm-monoid-add-class.diff-cancel diff-Suc-eq-diff-pred
           diff-less in-bounds index-eq lessThan-iff less-imp-diff-less
           zero-less-Suc inj dist-l image-eqI image-eqI length-upt
    unfolding bij-betw-def
    by (metis (no-types, lifting))
  moreover have  $\text{el-b: } ?inv \ (\text{index } ?l \ b) \in A$ 
    using bij-inv in-bounds-b atLeast0LessThan set-eq-A bij-inv
           cancel-comm-monoid-add-class.diff-cancel diff-Suc-eq-diff-pred
           diff-less in-bounds index-eq lessThan-iff less-imp-diff-less
           zero-less-Suc inj dist-l image-eqI image-eqI length-upt
    unfolding bij-betw-def
    by (metis (no-types, lifting))
  moreover assume  $\text{index } ?l \ b \leq \text{index } ?l \ a$ 
  ultimately have  $\text{card } A - 1 - (? \varphi \ b) \leq \text{card } A - 1 - (? \varphi \ a)$ 
    using index-eq set-eq-A
    by metis
  moreover have  $\forall a < \text{card } A. \ ? \varphi \ (?inv \ a) < \text{card } A$ 
    using fin bij-inv bij-A
    unfolding bij-betw-def
    by fastforce
  hence  $? \varphi \ b \leq \text{card } A - 1 \wedge ? \varphi \ a \leq \text{card } A - 1$ 
    using in-bounds-a in-bounds-b fin
    by fastforce
  ultimately have  $? \varphi \ b \geq ? \varphi \ a$ 
    using fin le-diff-iff'
    by blast
  hence  $? \varphi \ a < ? \varphi \ b \vee ? \varphi \ a = ? \varphi \ b$ 
    by auto
  moreover have
     $\forall a \in A. \forall b \in A. \ ? \varphi \ a < ? \varphi \ b \longrightarrow a \in \text{underS } r \ b$ 
    using mon total-underS antisym order-less-not-sym

```

```

    by metis
  hence  $? \varphi \ a < ? \varphi \ b \longrightarrow a \in \text{underS } r \ b$ 
    using element-a el-b in-bounds-a in-bounds-b set-eq-A
    by blast
  hence  $? \varphi \ a < ? \varphi \ b \longrightarrow (a, b) \in r$ 
    unfolding underS-def
    by simp
  moreover have  $\forall \ a \in A. \forall \ b \in A. ? \varphi \ a = ? \varphi \ b \longrightarrow a = b$ 
    using mon total-underS antisym order-less-not-sym
    by metis
  hence  $? \varphi \ a = ? \varphi \ b \longrightarrow a = b$ 
    using element-a el-b in-bounds-a in-bounds-b set-eq-A
    by blast
  hence  $? \varphi \ a = ? \varphi \ b \longrightarrow (a, b) \in r$ 
    using lin-order element-a el-b in-bounds-a
      in-bounds-b set-eq-A
    unfolding linear-order-on-def partial-order-on-def
      preorder-on-def refl-on-def
    by auto
  ultimately show  $(a, b) \in r$ 
    by auto
next
fix a b :: 'a
assume a-b-rel:  $(a, b) \in r$ 
hence
  a-in-A:  $a \in A$  and
  b-in-A:  $b \in A$  and
  a-under-b-or-eq:  $a \in \text{underS } r \ b \vee a = b$ 
  using lin-order
  unfolding linear-order-on-def partial-order-on-def
    preorder-on-def refl-on-def underS-def
  by auto
thus
  a  $\in \text{set } ?l$  and
  b  $\in \text{set } ?l$ 
  using bij-inv set-eq-A
  by (metis, metis)
hence  $? \varphi \ a \leq ? \varphi \ b$ 
  using mon le-eq-less-or-eq a-under-b-or-eq
    a-in-A b-in-A
  by auto
thus  $\text{index } ?l \ b \leq \text{index } ?l \ a$ 
  using index-eq a-in-A b-in-A diff-le-mono2
  by metis
qed
ultimately show  $r \in \text{pl-}\alpha \text{ ' permutations-of-set } A$ 
  by auto
qed

```

**lemma** *index-helper*:  
**fixes**  
 $l :: 'x \text{ list}$  **and**  
 $x :: 'x$   
**assumes**  
 $\text{finite } (\text{set } l)$  **and**  
 $\text{distinct } l$  **and**  
 $x \in \text{set } l$   
**shows**  $\text{index } l \ x = \text{card } \{y \in \text{set } l. \text{index } l \ y < \text{index } l \ x\}$   
**proof** –  
**have** *bij-l*:  $\text{bij-betw } (\text{index } l) (\text{set } l) \{0 ..< \text{length } l\}$   
**using** *assms bij-betw-index*  
**by** *blast*  
**hence**  $\text{card } \{y \in \text{set } l. \text{index } l \ y < \text{index } l \ x\} =$   
 $\text{card } (\text{index } l \ ^\circ \{y \in \text{set } l. \text{index } l \ y < \text{index } l \ x\})$   
**using** *CollectD bij-betw-same-card bij-betw-subset subsetI*  
**by** (*metis (no-types, lifting)*)  
**also have**  $\text{index } l \ ^\circ \{y \in \text{set } l. \text{index } l \ y < \text{index } l \ x\} =$   
 $\{m \mid m. m \in \text{index } l \ ^\circ (\text{set } l) \wedge m < \text{index } l \ x\}$   
**by** *blast*  
**also have**  
 $\{m \mid m. m \in \text{index } l \ ^\circ (\text{set } l) \wedge m < \text{index } l \ x\} =$   
 $\{m \mid m. m < \text{index } l \ x\}$   
**using** *bij-l assms atLeastLessThan-iff bot-nat-0.extremum*  
 $\text{index-image index-less-size-conv order-less-trans}$   
**by** *metis*  
**also have**  $\text{card } \{m \mid m. m < \text{index } l \ x\} = \text{index } l \ x$   
**by** *simp*  
**finally show** *?thesis*  
**by** *simp*  
**qed**

**lemma** *pl- $\alpha$ -eq-imp-list-eq*:  
**fixes**  $l \ l' :: 'x \text{ list}$   
**assumes**  
 $\text{fin-set-}l$ :  $\text{finite } (\text{set } l)$  **and**  
 $\text{set-eq}$ :  $\text{set } l = \text{set } l'$  **and**  
 $\text{dist-}l$ :  $\text{distinct } l$  **and**  
 $\text{dist-}l'$ :  $\text{distinct } l'$  **and**  
 $\text{pl-}\alpha\text{-eq}$ :  $\text{pl-}\alpha \ l = \text{pl-}\alpha \ l'$   
**shows**  $l = l'$   
**proof** (*rule ccontr*)  
**assume**  $l \neq l'$   
**moreover with** *set-eq*  
**have**  $l \neq [] \wedge l' \neq []$   
**by** *auto*  
**ultimately obtain**  
 $i :: \text{nat}$  **and**  
 $x :: 'x$  **where**

*i* < length *l* **and**  
*l*! *i* ≠ *l'*! *i* **and**  
*x* = *l*! *i* **and**  
*x*-in-*l*: *x* ∈ set *l*  
**using** *dist-l dist-l' distinct-remdups-id*  
*length-remdups-card-conv nth-equalityI*  
*nth-mem set-eq*  
**by** *metis*  
**moreover with** *set-eq*  
**have** *neq-ind: index l x ≠ index l' x*  
**using** *dist-l index-nth-id nth-index*  
**by** *metis*  
**ultimately have**  
*card {y ∈ set l. index l y < index l x} ≠*  
*card {y ∈ set l. index l' y < index l' x}*  
**using** *dist-l dist-l' set-eq index-helper fin-set-l*  
**by** (*metis (mono-tags)*)  
**then obtain** *y :: 'x* **where**  
*y*-in-set-*l*: *y* ∈ set *l* **and**  
*y*-neq-*x*: *y* ≠ *x* **and**  
*neq-indices*:  
*index l y < index l x ∧ index l' y > index l' x*  
*∨ index l' y < index l' x ∧ index l y > index l x*  
**using** *index-eq-index-conv not-less-iff-gr-or-eq set-eq*  
**by** (*metis (mono-tags, lifting)*)  
**hence**  
*is-less-preferred-than-l x l y ∧ is-less-preferred-than-l y l' x*  
*∨ is-less-preferred-than-l x l' y ∧ is-less-preferred-than-l y l x*  
**unfolding** *is-less-preferred-than-l.simps*  
**using** *y-in-set-l less-imp-le-nat set-eq x-in-l*  
**by** *blast*  
**hence** (*x, y*) ∈ *pl-α l* ∧ (*x, y*) ∉ *pl-α l'*  
*∨ (x, y) ∈ pl-α l' ∧ (x, y) ∉ pl-α l*  
**unfolding** *pl-α-def*  
**using** *is-less-preferred-than-l.simps y-neq-x neq-indices*  
*case-prod-conv linorder-not-less mem-Collect-eq*  
**by** *metis*  
**thus** *False*  
**using** *pl-α-eq*  
**by** *blast*  
**qed**

**lemma** *pl-α-bij-betw*:  
**fixes** *X :: 'x set*  
**assumes** *finite X*  
**shows** *bij-betw pl-α (permutations-of-set X) {r. linear-order-on X r}*  
**proof** (*unfold bij-betw-def, safe*)  
**show** *inj-on pl-α (permutations-of-set X)*  
**unfolding** *inj-on-def permutations-of-set-def*

```

    using pl- $\alpha$ -eq-imp-list-eq assms
    by fastforce
next
  fix l :: 'x list
  assume l  $\in$  permutations-of-set X
  thus linear-order-on X (pl- $\alpha$  l)
    using assms pl- $\alpha$ -lin-order
    by blast
next
  fix r :: 'x rel
  assume linear-order-on X r
  thus r  $\in$  pl- $\alpha$  'permutations-of-set X
    using assms lin-order-pl- $\alpha$ 
    by blast
qed

```

### 2.1.5 Limited Preference

**definition** *limited* :: '*a* set  $\Rightarrow$  '*a* Preference-List  $\Rightarrow$  bool **where**  
*limited* *A* *r*  $\equiv \forall a. a \in \text{set } r \longrightarrow a \in A$

**fun** *limit-l* :: '*a* set  $\Rightarrow$  '*a* Preference-List  $\Rightarrow$  '*a* Preference-List **where**  
*limit-l* *A* *l* = *List.filter* ( $\lambda a. a \in A$ ) *l*

**lemma** *limited-dest*:

```

fixes
  A :: 'a set and
  l :: 'a Preference-List and
  a b :: 'a
assumes
  a  $\lesssim_l$  b and
  limited A l
shows a  $\in A \wedge b \in A$ 
using assms
unfolding limited-def
by simp

```

**lemma** *limit-equiv*:

```

fixes
  A :: 'a set and
  l :: 'a list
assumes well-formed-l l
shows pl- $\alpha$  (limit-l A l) = limit A (pl- $\alpha$  l)
using assms
proof (induction l)
case Nil
show pl- $\alpha$  (limit-l A []) = limit A (pl- $\alpha$  [])
unfolding pl- $\alpha$ -def
by simp

```



```

next
case (Cons a l)
fix
  a :: 'a and
  l :: 'a list
assume
  wf-imp-limit: well-formed-l l  $\implies$  pl- $\alpha$  (limit-l A l) = limit A (pl- $\alpha$  l) and
  wf-a-l: well-formed-l (a#l)
show pl- $\alpha$  (limit-l A (a#l)) = limit A (pl- $\alpha$  (a#l))
proof (unfold limit-l.simps limit.simps, intro equalityI, safe)
  fix b c :: 'a
  assume b-less-c: (b, c)  $\in$  pl- $\alpha$  (filter ( $\lambda$  a. a  $\in$  A) (a#l))
  moreover have limit-preference-list-assoc:
    pl- $\alpha$  (limit-l A l) = limit A (pl- $\alpha$  l)
  using wf-a-l wf-imp-limit
  by simp
ultimately have
  b  $\in$  set (a#l) and
  c  $\in$  set (a#l)
  using case-prodD filter-set mem-Collect-eq member-filter
    is-less-preferred-than-l.simps
  unfolding pl- $\alpha$ -def
  by (metis, metis)
thus (b, c)  $\in$  pl- $\alpha$  (a#l)
proof (unfold pl- $\alpha$ -def is-less-preferred-than-l.simps, safe)
  have idx-set-eq:
     $\forall$  a' l' a''. (a' :: 'a)  $\lesssim_{l'}$  a'' =
      (a'  $\in$  set l'  $\wedge$  a''  $\in$  set l'  $\wedge$  index l' a''  $\leq$  index l' a')
  using is-less-preferred-than-l.simps
  by blast
  moreover from this
  have {(a', b'). a'  $\lesssim_{(\text{limit-l A l})}$  b'} =
    {(a', a''). a'  $\in$  set (limit-l A l)  $\wedge$  a''  $\in$  set (limit-l A l)  $\wedge$ 
      index (limit-l A l) a''  $\leq$  index (limit-l A l) a'}
  by presburger
  moreover from this
  have {(a', b'). a'  $\lesssim_l$  b'} =
    {(a', a''). a'  $\in$  set l  $\wedge$  a''  $\in$  set l  $\wedge$  index l a''  $\leq$  index l a'}
  using is-less-preferred-than-l.simps
  by auto
  ultimately have {(a', b').
    a'  $\in$  set (limit-l A l)  $\wedge$  b'  $\in$  set (limit-l A l)
     $\wedge$  index (limit-l A l) b'  $\leq$  index (limit-l A l) a'} =
    limit A {(a', b'). a'  $\in$  set l
     $\wedge$  b'  $\in$  set l  $\wedge$  index l b'  $\leq$  index l a'}
  using pl- $\alpha$ -def limit-preference-list-assoc
  by (metis (no-types))
hence idx-imp:
  b  $\in$  set (limit-l A l)  $\wedge$  c  $\in$  set (limit-l A l)

```

$\wedge \text{index } (\text{limit-}l \ A \ l) \ c \leq \text{index } (\text{limit-}l \ A \ l) \ b$   
 $\longrightarrow b \in \text{set } l \wedge c \in \text{set } l \wedge \text{index } l \ c \leq \text{index } l \ b$   
**by** *auto*  
**have**  $b \lesssim_{(\text{filter } (\lambda a. a \in A) (a \# l))} c$   
**using** *b-less-c case-prodD mem-Collect-eq*  
**unfolding** *pl- $\alpha$ -def*  
**by** (*metis (no-types)*)  
**moreover obtain**  
 $f \ h :: 'a \Rightarrow 'a \ \text{list} \Rightarrow 'a \Rightarrow 'a$  **and**  
 $g :: 'a \Rightarrow 'a \ \text{list} \Rightarrow 'a \Rightarrow 'a \ \text{list}$  **where**  
 $\forall \ d \ s \ e. \ d \lesssim_s e \longrightarrow$   
 $d = f \ e \ s \ d \wedge s = g \ e \ s \ d \wedge e = h \ e \ s \ d$   
 $\wedge f \ e \ s \ d \in \text{set } (g \ e \ s \ d) \wedge h \ e \ s \ d \in \text{set } (g \ e \ s \ d)$   
 $\wedge \text{index } (g \ e \ s \ d) \ (h \ e \ s \ d) \leq \text{index } (g \ e \ s \ d) \ (f \ e \ s \ d)$   
**by** *fastforce*  
**ultimately have**  
 $b = f \ c \ (\text{filter } (\lambda a. a \in A) (a \# l)) \ b$   
 $\wedge \text{filter } (\lambda a. a \in A) (a \# l) =$   
 $g \ c \ (\text{filter } (\lambda a. a \in A) (a \# l)) \ b$   
 $\wedge c = h \ c \ (\text{filter } (\lambda a. a \in A) (a \# l)) \ b$   
 $\wedge f \ c \ (\text{filter } (\lambda a. a \in A) (a \# l)) \ b$   
 $\in \text{set } (g \ c \ (\text{filter } (\lambda a. a \in A) (a \# l)) \ b)$   
 $\wedge h \ c \ (\text{filter } (\lambda a. a \in A) (a \# l)) \ b$   
 $\in \text{set } (g \ c \ (\text{filter } (\lambda a. a \in A) (a \# l)) \ b)$   
 $\wedge \text{index } (g \ c \ (\text{filter } (\lambda a. a \in A) (a \# l)) \ b)$   
 $(h \ c \ (\text{filter } (\lambda a. a \in A) (a \# l)) \ b)$   
 $\leq \text{index } (g \ c \ (\text{filter } (\lambda a. a \in A) (a \# l)) \ b)$   
 $(f \ c \ (\text{filter } (\lambda a. a \in A) (a \# l)) \ b)$   
**by** *blast*  
**moreover have**  $\text{filter } (\lambda a. a \in A) \ l = \text{limit-}l \ A \ l$   
**by** *simp*  
**moreover have**  
 $\text{index } (\text{limit-}l \ A \ l) \ c \neq$   
 $\text{index } (g \ c \ (\text{filter } (\lambda a. a \in A) (a \# l)) \ b)$   
 $(h \ c \ (\text{filter } (\lambda a. a \in A) (a \# l)) \ b)$   
 $\vee \text{index } (\text{limit-}l \ A \ l) \ b \neq$   
 $\text{index } (g \ c \ (\text{filter } (\lambda a. a \in A) (a \# l)) \ b)$   
 $(f \ c \ (\text{filter } (\lambda a. a \in A) (a \# l)) \ b)$   
 $\vee \text{index } (\text{limit-}l \ A \ l) \ c \leq \text{index } (\text{limit-}l \ A \ l) \ b$   
 $\vee \neg \text{index } (g \ c \ (\text{filter } (\lambda a. a \in A) (a \# l)) \ b)$   
 $(h \ c \ (\text{filter } (\lambda a. a \in A) (a \# l)) \ b)$   
 $\leq \text{index } (g \ c \ (\text{filter } (\lambda a. a \in A) (a \# l)) \ b)$   
 $(f \ c \ (\text{filter } (\lambda a. a \in A) (a \# l)) \ b)$   
**by** *presburger*  
**ultimately have**  $a \neq c \longrightarrow \text{index } (a \# l) \ c \leq \text{index } (a \# l) \ b$   
**using** *add-le-cancel-right idx-imp index-Cons le-zero-eq*  
*nth-index set-ConsD wf-a-l*  
**unfolding** *filter.simps is-less-preferred-than-l.elims*  
*distinct.simps*

```

      by metis
    thus  $\text{index } (a\#l) \ c \leq \text{index } (a\#l) \ b$ 
      by force
  qed
show
   $b \in A$  and
   $c \in A$ 
  using b-less-c case-prodD mem-Collect-eq set-filter
  unfolding pl- $\alpha$ -def is-less-preferred-than-l.simps
  by (metis (no-types, lifting),
      metis (no-types, lifting))
next
fix  $b \ c :: 'a$ 
assume
  b-less-c:  $(b, c) \in \text{pl-}\alpha \ (a\#l)$  and
  b-in-A:  $b \in A$  and
  c-in-A:  $c \in A$ 
have  $(b, c) \in \text{pl-}\alpha \ (a\#l)$ 
  by (simp add: b-less-c)
hence  $b \lesssim_{(a\#l)} c$ 
  using case-prodD mem-Collect-eq
  unfolding pl- $\alpha$ -def
  by metis
moreover have
   $\text{pl-}\alpha \ (\text{filter } (\lambda a. a \in A) \ l) =$ 
     $\{(a, b). (a, b) \in \text{pl-}\alpha \ l \wedge a \in A \wedge b \in A\}$ 
  using wf-a-l wf-imp-limit
  by simp
ultimately have
   $\text{index } (\text{filter } (\lambda a. a \in A) \ (a\#l)) \ c$ 
     $\leq \text{index } (\text{filter } (\lambda a. a \in A) \ (a\#l)) \ b$ 
  unfolding pl- $\alpha$ -def
  using add-leE add-le-cancel-right case-prodI c-in-A
    b-in-A index-Cons set-ConsD not-one-le-zero
    in-rel-Collect-case-prod-eq mem-Collect-eq
    linorder-le-cases
  by fastforce
moreover have
   $b \in \text{set } (\text{filter } (\lambda a. a \in A) \ (a\#l))$  and
   $c \in \text{set } (\text{filter } (\lambda a. a \in A) \ (a\#l))$ 
  using b-less-c b-in-A c-in-A
  unfolding pl- $\alpha$ -def
  by (fastforce, fastforce)
ultimately show  $(b, c) \in \text{pl-}\alpha \ (\text{filter } (\lambda a. a \in A) \ (a\#l))$ 
  unfolding pl- $\alpha$ -def
  by simp
qed
qed

```

### 2.1.6 Auxiliary Definitions

**definition** *total-on-l* :: 'a set  $\Rightarrow$  'a Preference-List  $\Rightarrow$  bool **where**  
*total-on-l* A l  $\equiv \forall a \in A. a \in \text{set } l$

**definition** *refl-on-l* :: 'a set  $\Rightarrow$  'a Preference-List  $\Rightarrow$  bool **where**  
*refl-on-l* A l  $\equiv (\forall a. a \in \text{set } l \longrightarrow a \in A) \wedge (\forall a \in A. a \lesssim_l a)$

**definition** *trans* :: 'a Preference-List  $\Rightarrow$  bool **where**  
*trans* l  $\equiv \forall (a, b, c) \in \text{set } l \times \text{set } l \times \text{set } l. a \lesssim_l b \wedge b \lesssim_l c \longrightarrow a \lesssim_l c$

**definition** *preorder-on-l* :: 'a set  $\Rightarrow$  'a Preference-List  $\Rightarrow$  bool **where**  
*preorder-on-l* A l  $\equiv \text{refl-on-l } A \ l \wedge \text{trans } l$

**definition** *antisym-l* :: 'a list  $\Rightarrow$  bool **where**  
*antisym-l* l  $\equiv \forall a \ b. a \lesssim_l b \wedge b \lesssim_l a \longrightarrow a = b$

**definition** *partial-order-on-l* :: 'a set  $\Rightarrow$  'a Preference-List  $\Rightarrow$  bool **where**  
*partial-order-on-l* A l  $\equiv \text{preorder-on-l } A \ l \wedge \text{antisym-l } l$

**definition** *linear-order-on-l* :: 'a set  $\Rightarrow$  'a Preference-List  $\Rightarrow$  bool **where**  
*linear-order-on-l* A l  $\equiv \text{partial-order-on-l } A \ l \wedge \text{total-on-l } A \ l$

**definition** *connex-l* :: 'a set  $\Rightarrow$  'a Preference-List  $\Rightarrow$  bool **where**  
*connex-l* A l  $\equiv \text{limited } A \ l \wedge (\forall a \in A. \forall b \in A. a \lesssim_l b \vee b \lesssim_l a)$

**abbreviation** *ballot-on* :: 'a set  $\Rightarrow$  'a Preference-List  $\Rightarrow$  bool **where**  
*ballot-on* A l  $\equiv \text{well-formed-l } l \wedge \text{linear-order-on-l } A \ l$

### 2.1.7 Auxiliary Lemmas

**lemma** *list-trans[simp]*:  
**fixes** l :: 'a Preference-List  
**shows** *trans* l  
**unfolding** *trans-def*  
**by** *simp*

**lemma** *list-antisym[simp]*:  
**fixes** l :: 'a Preference-List  
**shows** *antisym-l* l  
**unfolding** *antisym-l-def*  
**by** *auto*

**lemma** *lin-order-equiv-list-of-alts*:  
**fixes**  
A :: 'a set **and**  
l :: 'a Preference-List  
**shows** *linear-order-on-l* A l = (A = set l)  
**unfolding** *linear-order-on-l-def* *total-on-l-def*  
*partial-order-on-l-def* *preorder-on-l-def*

```

      refl-on-l-def
by auto

lemma connex-imp-refl:
  fixes
    A :: 'a set and
    l :: 'a Preference-List
  assumes connex-l A l
  shows refl-on-l A l
  unfolding refl-on-l-def
  using assms connex-l-def Preference-List.limited-def
  by metis

lemma lin-ord-imp-connex-l:
  fixes
    A :: 'a set and
    l :: 'a Preference-List
  assumes linear-order-on-l A l
  shows connex-l A l
  using assms linorder-le-cases
  unfolding connex-l-def linear-order-on-l-def preorder-on-l-def
    limited-def refl-on-l-def partial-order-on-l-def
    is-less-preferred-than-l.simps
  by metis

lemma above-trans:
  fixes
    l :: 'a Preference-List and
    a b :: 'a
  assumes
    trans l and
     $a \lesssim_l b$ 
  shows set (above-l l b)  $\subseteq$  set (above-l l a)
  using assms set-take-subset-set-take rank-l.simps
    Suc-le-mono add commute add-0 add-Suc
  unfolding Preference-List.is-less-preferred-than-l.simps
    above-l-def One-nat-def
  by metis

lemma less-preferred-l-rel-equiv:
  fixes
    l :: 'a Preference-List and
    a b :: 'a
  shows  $a \lesssim_l b =$ 
    Preference-Relation.is-less-preferred-than a (pl- $\alpha$  l) b
  unfolding pl- $\alpha$ -def
  by simp

theorem above-equiv:

```

```

fixes
   $l :: 'a \text{ Preference-List}$  and
   $a :: 'a$ 
shows  $\text{set } (\text{above-}l \ l \ a) = \text{above } (pl-\alpha \ l) \ a$ 
proof (safe)
  fix  $b :: 'a$ 
  assume  $b \in \text{set } (\text{above-}l \ l \ a)$ 
  hence  $\text{index } l \ b \leq \text{index } l \ a$ 
    unfolding rank-l.simps above-l-def
    using Suc-eq-plus1 Suc-le-eq index-take linorder-not-less
      bot-nat-0.extremum-strict
    by (metis (full-types))
  hence  $a \lesssim_l b$ 
    using Suc-le-mono add-Suc le-antisym take-0 b-member
      in-set-takeD index-take le0 rank-l.simps
    unfolding above-l-def is-less-preferred-than-l.simps
    by metis
  thus  $b \in \text{above } (pl-\alpha \ l) \ a$ 
    using less-preferred-l-rel-equiv pref-imp-in-above
    by metis
next
  fix  $b :: 'a$ 
  assume  $b \in \text{above } (pl-\alpha \ l) \ a$ 
  hence  $a \lesssim_l b$ 
    using pref-imp-in-above less-preferred-l-rel-equiv
    by metis
  thus  $b \in \text{set } (\text{above-}l \ l \ a)$ 
    unfolding above-l-def is-less-preferred-than-l.simps
      rank-l.simps
    using Suc-eq-plus1 Suc-le-eq index-less-size-conv
      set-take-if-index le-imp-less-Suc
    by (metis (full-types))
qed

theorem rank-equiv:
  fixes
     $l :: 'a \text{ Preference-List}$  and
     $a :: 'a$ 
  assumes well-formed-l l
  shows  $\text{rank-}l \ l \ a = \text{rank } (pl-\alpha \ l) \ a$ 
proof (unfold rank-l.simps rank.simps, cases a ∈ set l)
  case True
  moreover have  $\text{above } (pl-\alpha \ l) \ a = \text{set } (\text{above-}l \ l \ a)$ 
    unfolding above-equiv
    by simp
  moreover have  $\text{distinct } (\text{above-}l \ l \ a)$ 
    unfolding above-l-def
    using assms distinct-take
    by blast

```

```

moreover from this
have card (set (above-l l a)) = length (above-l l a)
  using distinct-card
  by blast
moreover have length (above-l l a) = rank-l l a
  unfolding above-l-def
  using Suc-le-eq
  by (simp add: in-set-member)
ultimately show
  (if a ∈ set l then index l a + 1 else 0) =
    card (above (pl-α l) a)
  by simp
next
case False
hence above (pl-α l) a = {}
  unfolding above-def
  using less-preferred-l-rel-equiv
  by fastforce
thus (if a ∈ set l then index l a + 1 else 0) =
  card (above (pl-α l) a)
  using False
  by fastforce
qed

lemma lin-ord-equiv:
fixes
  A :: 'a set and
  l :: 'a Preference-List
shows linear-order-on-l A l = linear-order-on A (pl-α l)
unfolding is-less-preferred-than-l.simps antisym-def total-on-def
  pl-α-def linear-order-on-l-def linear-order-on-def
  refl-on-l-def Relation.trans-def preorder-on-l-def
  partial-order-on-l-def partial-order-on-def
  total-on-l-def preorder-on-def refl-on-def
by auto

```

### 2.1.8 First Occurrence Indices

```

lemma pos-in-list-yields-rank:
fixes
  l :: 'a Preference-List and
  a :: 'a and
  n :: nat
assumes
   $\forall (j :: nat) \leq n. !j \neq a$ 
   $!(n - 1) = a$ 
shows rank-l l a = n
using assms
proof (induction l arbitrary: n)

```

```

    case Nil
    thus ?case
      by simp
next
fix
  l :: 'a Preference-List and
  a :: 'a
case (Cons a l)
thus ?case
  by simp
qed

lemma ranked-alt-not-at-pos-before:
  fixes
    l :: 'a Preference-List and
    a :: 'a and
    n :: nat
  assumes
    a ∈ set l and
    n < (rank-l l a) - 1
  shows l!n ≠ a
  using index-first member-def rank-l.simps
    assms add-diff-cancel-right'
  by metis

lemma pos-in-list-yields-pos:
  fixes
    l :: 'a Preference-List and
    a :: 'a
  assumes a ∈ set l
  shows l!(rank-l l a - 1) = a
  using assms
proof (induction l)
case Nil
thus ?case
  by simp
next
fix
  l :: 'a Preference-List and
  b :: 'a
case (Cons b l)
assume a ∈ set (b#l)
moreover from this
have rank-l (b#l) a = 1 + index (b#l) a
  using Suc-eq-plus1 add-Suc add-cancel-left-left
    rank-l.simps
  by metis
ultimately show (b#l)!(rank-l (b#l) a - 1) = a
  using diff-add-inverse nth-index

```



```

    by metis
qed

lemma rel-of-pref-pred-for-set-eq-list-to-rel:
  fixes l :: 'a Preference-List
  shows relation-of ( $\lambda y z. y \lesssim_l z$ ) (set l) = pl- $\alpha$  l
proof (unfold relation-of-def, safe)
  fix a b :: 'a
  assume a  $\lesssim_l$  b
  moreover have a  $\lesssim_l$  b = (a  $\preceq_{(pl-\alpha\ l)}$  b)
    using less-preferred-l-rel-equiv
    by (metis (no-types))
  ultimately show (a, b)  $\in$  pl- $\alpha$  l
    by simp
next
  fix a b :: 'a
  assume (a, b)  $\in$  pl- $\alpha$  l
  thus a  $\lesssim_l$  b
    using less-preferred-l-rel-equiv
    unfolding is-less-preferred-than.simps
    by metis
  thus
    a  $\in$  set l and
    b  $\in$  set l
    by (simp, simp)
qed

end

```

## 2.2 Preference (List) Profile

```

theory Profile-List
  imports ../Profile
    Preference-List
begin

```

### 2.2.1 Definition

A profile (list) contains one ballot for each voter.

**type-synonym** 'a Profile-List = 'a Preference-List list

**type-synonym** 'a Election-List = 'a set  $\times$  'a Profile-List

Abstraction from profile list to profile.

**fun** pl-to-pr- $\alpha$  :: 'a Profile-List  $\Rightarrow$  ('a, nat) Profile **where**

```

pl-to-pr-α pl = (λ n. if n < length pl ∧ n ≥ 0
                    then (map pl-α pl)!n
                    else {})

```

```

lemma prof-abstr-presv-size:
  fixes p :: 'a Profile-List
  shows length p = length (to-list {0 ..< length p} (pl-to-pr-α p))
  by simp

```

### 2.2.2 Refinement Proof

A profile on a finite set of alternatives A contains only ballots that are lists of linear orders on A.

```

definition profile-l :: 'a set ⇒ 'a Profile-List ⇒ bool where
  profile-l A p ≡ ∀ i < length p. ballot-on A (p!i)

```

```

lemma profile-list-refines-profile:
  fixes
    A :: 'a set and
    p :: 'a Profile-List
  assumes profile-l A p
  shows profile {0 ..< length p} A (pl-to-pr-α p)
proof (unfold profile-def, safe)
  fix i :: nat
  assume in-range: i ∈ {0 ..< length p}
  moreover have well-formed-l (p!i)
    using assms in-range
    unfolding profile-l-def
    by simp
  moreover have linear-order-on-l A (p!i)
    using assms in-range
    unfolding profile-l-def
    by simp
  ultimately show linear-order-on A (pl-to-pr-α p i)
    using lin-ord-equiv length-map nth-map
    by auto
qed

end

```

## 2.3 Ordered Relation Type

```

theory Ordered-Relation
  imports Preference-Relation
          ./Refined-Types/Preference-List
          HOL-Combinatorics.Multiset-Permutations

```

```

begin

lemma fin-ordered:
  fixes  $X :: 'x \text{ set}$ 
  assumes finite  $X$ 
  obtains  $\text{ord} :: 'x \text{ rel}$  where
    linear-order-on  $X \text{ ord}$ 
proof -
  obtain  $l :: 'x \text{ list}$  where
    set-l:  $\text{set } l = X$ 
    using finite-list assms
    by blast
  let  $?r = \text{pl-}\alpha \text{ } l$ 
  have antisym  $?r$ 
    using set-l Collect-mono-iff antisym index-eq-index-conv pl-}\alpha\text{-def}
    unfolding antisym-def
    by fastforce
  moreover have refl-on  $X \text{ } ?r$ 
    using set-l
    unfolding refl-on-def pl-}\alpha\text{-def is-less-preferred-than-l.simps}
    by blast
  moreover have Relation.trans  $?r$ 
    unfolding Relation.trans-def pl-}\alpha\text{-def is-less-preferred-than-l.simps}
    by auto
  moreover have total-on  $X \text{ } ?r$ 
    using set-l
    unfolding total-on-def pl-}\alpha\text{-def is-less-preferred-than-l.simps}
    by force
  ultimately have linear-order-on  $X \text{ } ?r$ 
    unfolding linear-order-on-def preorder-on-def partial-order-on-def
    by blast
  moreover assume
     $\bigwedge \text{ord. } \text{linear-order-on } X \text{ ord} \implies ?thesis$ 
  ultimately show  $?thesis$ 
    by blast
qed

typedef  $'a \text{ Ordered-Preference} =$ 
   $\{p :: 'a :: \text{finite Preference-Relation. } \text{linear-order-on } (UNIV :: 'a \text{ set}) \text{ } p\}$ 
  morphisms ord2pref pref2ord
proof (unfold mem-Collect-eq)
  have finite  $(UNIV :: 'a \text{ set})$ 
    by simp
  then obtain  $p :: 'a \text{ Preference-Relation}$  where
    linear-order-on  $(UNIV :: 'a \text{ set}) \text{ } p$ 
    using fin-ordered
    by metis
  thus  $\exists p :: 'a \text{ Preference-Relation. } \text{linear-order } p$ 
    by blast

```

qed

```

instance Ordered-Preference :: (finite) finite
proof
  have (UNIV :: 'a Ordered-Preference set) =
    pref2ord ' {p :: 'a Preference-Relation.
      linear-order-on (UNIV :: 'a set) p}
  using type-definition.Abs-image
    type-definition-Ordered-Preference
  by blast
  moreover have
    finite {p :: 'a Preference-Relation.
      linear-order-on (UNIV :: 'a set) p}
  by simp
  ultimately show
    finite (UNIV :: 'a Ordered-Preference set)
  using finite-imageI
  by metis
qed

```

```

lemma range-ord2pref: range ord2pref = {p. linear-order p}
  using type-definition-Ordered-Preference type-definition.Rep-range
  by metis

```

```

lemma card-ord-pref: card (UNIV :: 'a :: finite Ordered-Preference set) =
  fact (card (UNIV :: 'a set))
proof –
  let ?n = card (UNIV :: 'a set) and
    ?perm = permutations-of-set (UNIV :: 'a set)
  have (UNIV :: 'a Ordered-Preference set) =
    pref2ord ' {p :: 'a Preference-Relation.
      linear-order-on (UNIV :: 'a set) p}
  using type-definition-Ordered-Preference type-definition.Abs-image
  by blast
  moreover have
    inj-on pref2ord {p :: 'a Preference-Relation.
      linear-order-on (UNIV :: 'a set) p}
  using inj-onCI pref2ord-inject
  by metis
  ultimately have
    bij-betw pref2ord
      {p :: 'a Preference-Relation.
        linear-order-on (UNIV :: 'a set) p}
      (UNIV :: 'a Ordered-Preference set)
  using bij-betw-imageI
  by metis
  hence card (UNIV :: 'a Ordered-Preference set) =
    card {p :: 'a Preference-Relation.
      linear-order-on (UNIV :: 'a set) p}

```

```

    using bij-betw-same-card
    by metis
  moreover have card ?perm = fact ?n
    by simp
  ultimately show ?thesis
    using bij-betw-same-card pl-α-bij-betw finite
    by metis
qed

end

```

## 2.4 Alternative Election Type

```

theory Quotient-Type-Election
  imports Profile
begin

```

```

lemma election-equality-equiv:
  election-equality E E and
  election-equality E E'  $\longrightarrow$  election-equality E' E and
  election-equality E E'  $\longrightarrow$  election-equality E' F
     $\longrightarrow$  election-equality E F
proof (safe)
  have election-equality
    (fst E, fst (snd E), snd (snd E)) (fst E, fst (snd E), snd (snd E))
  unfolding election-equality.simps
  by safe
  thus election-equality E E
    by clarsimp
next
  assume election-equality E E'
  hence election-equality
    (fst E, fst (snd E), snd (snd E)) (fst E', fst (snd E'), snd (snd E'))
  by simp
  hence election-equality
    (fst E', fst (snd E'), snd (snd E')) (fst E, fst (snd E), snd (snd E))
  unfolding election-equality.simps
  by (metis (mono-tags, lifting))
  thus election-equality E' E
    by clarsimp
next
  assume
    election-equality E E' and
    election-equality E' F
  hence
    election-equality
      (fst E, fst (snd E), snd (snd E)) (fst E', fst (snd E'), snd (snd E')) and

```

```

    election-equality
      (fst E', fst (snd E'), snd (snd E')) (fst F, fst (snd F), snd (snd F))
    by (simp, simp)
  hence election-equality
    (fst E, fst (snd E), snd (snd E)) (fst F, fst (snd F), snd (snd F))
  unfolding election-equality.simps
  by (metis (no-types, lifting))
  thus election-equality E F
    by clarsimp
qed

quotient-type ('a, 'v) ElectionQ =
  'a set × 'v set × ('a, 'v) Profile / election-equality
unfolding equivp-reflp-symp-transp reflp-def symp-def transp-def
using election-equality-equiv
by simp

fun fstQ :: ('a, 'v) ElectionQ ⇒ 'a set where
  fstQ E = fst (rep-ElectionQ E)

fun sndQ :: ('a, 'v) ElectionQ ⇒ 'v set × ('a, 'v) Profile where
  sndQ E = snd (rep-ElectionQ E)

abbreviation alternatives- $\mathcal{E}_Q$  :: ('a, 'v) ElectionQ ⇒ 'a set where
  alternatives- $\mathcal{E}_Q$  E ≡ fstQ E

abbreviation voters- $\mathcal{E}_Q$  :: ('a, 'v) ElectionQ ⇒ 'v set where
  voters- $\mathcal{E}_Q$  E ≡ fst (sndQ E)

abbreviation profile- $\mathcal{E}_Q$  :: ('a, 'v) ElectionQ ⇒ ('a, 'v) Profile where
  profile- $\mathcal{E}_Q$  E ≡ snd (sndQ E)

end

```

## Chapter 3

# Quotient Rules

### 3.1 Quotients of Equivalence Relations

```
theory Relation-Quotients
imports ../Social-Choice-Types/Symmetry-Of-Functions
begin
```

#### 3.1.1 Definitions

```
fun singleton-set :: 'x set  $\Rightarrow$  'x where
  singleton-set s = (if card s = 1 then the-inv ( $\lambda$  x. {x}) s else undefined)
— This is undefined if card s  $\neq$  1. Note that "undefined = undefined" is the only
provable equality for undefined.
```

For a given function, we define a function on sets that maps each set to the unique image under *f* of its elements, if one exists. Otherwise, the result is undefined.

```
fun  $\pi_Q$  :: ('x  $\Rightarrow$  'y)  $\Rightarrow$  ('x set  $\Rightarrow$  'y) where
   $\pi_Q$  f s = singleton-set (f ` s)
```

For a given function *f* on sets and a mapping from elements to sets, we define a function on the set element type that maps each element to the image of its corresponding set under *f*. A natural mapping is from elements to their classes under a relation.

```
fun inv- $\pi_Q$  :: ('x  $\Rightarrow$  'x set)  $\Rightarrow$  ('x set  $\Rightarrow$  'y)  $\Rightarrow$  ('x  $\Rightarrow$  'y) where
  inv- $\pi_Q$  cls f x = f (cls x)
```

```
fun relation-class :: 'x rel  $\Rightarrow$  'x  $\Rightarrow$  'x set where
  relation-class r x = r `` {x}
```

#### 3.1.2 Well-Definedness

```
lemma singleton-set-undef-if-card-neq-one:
fixes s :: 'x set
```

```

assumes  $\text{card } s \neq 1$ 
shows  $\text{singleton-set } s = \text{undefined}$ 
using assms
by simp

```

```

lemma singleton-set-def-if-card-one:
  fixes  $s :: 'x \text{ set}$ 
  assumes  $\text{card } s = 1$ 
  shows  $\exists! x. x = \text{singleton-set } s \wedge \{x\} = s$ 
  using assms card-1-singletonE inj-def singleton-inject the-inv-f-f
  unfolding singleton-set.simps
  by (metis (mono-tags, lifting))

```

If the given function is invariant under an equivalence relation, the induced function on sets is well-defined for all equivalence classes of that relation.

```

theorem pass-to-quotient:
  fixes
     $f :: 'x \Rightarrow 'y$  and
     $r :: 'x \text{ rel}$  and
     $s :: 'x \text{ set}$ 
  assumes
     $f$  respects  $r$  and
    equiv  $s$   $r$ 
  shows  $\forall t \in s // r. \forall x \in t. \pi_Q f t = f x$ 
proof (safe)
  fix
     $t :: 'x \text{ set}$  and
     $x :: 'x$ 
  have  $\forall y \in r `` \{x\}. (x, y) \in r$ 
    unfolding Image-def
    by simp
  hence func-eq-x:
     $\{f y \mid y. y \in r `` \{x\}\} = \{f x \mid y. y \in r `` \{x\}\}$ 
    using assms
    unfolding congruent-def
    by fastforce
  assume
     $t \in s // r$  and
     $x \text{-in-} t: x \in t$ 
  moreover from this have  $r `` \{x\} \in s // r$ 
    using assms quotient-eq-iff equiv-class-eq-iff quotientI
    by metis
  ultimately have  $r \text{-img-elem-} x \text{-eq-} t: r `` \{x\} = t$ 
    using assms quotient-eq-iff Image-singleton-iff
    by metis
  hence  $\{f x \mid y. y \in r `` \{x\}\} = \{f x\}$ 
    using  $x \text{-in-} t$ 
    by blast
  hence  $f ` t = \{f x\}$ 

```



```

    using Setcompr-eq-image r-img-elem-x-eq-t func-eq-x
    by metis
  thus  $\pi_Q f t = f x$ 
    using singleton-set-def-if-card-one is-singletonI
      is-singleton-altdef the-elem-eq
    unfolding  $\pi_Q.simps$ 
    by metis
qed

```

A function on sets induces a function on the element type that is invariant under a given equivalence relation.

```

theorem pass-to-quotient-inv:
  fixes
     $f :: 'x \text{ set} \Rightarrow 'x$  and
     $r :: 'x \text{ rel}$  and
     $s :: 'x \text{ set}$ 
  assumes equiv s r
  defines induced-fun  $\equiv (inv\text{-}\pi_Q (relation\text{-}class\ r) f)$ 
  shows
    induced-fun respects r and
     $\forall A \in s // r. \pi_Q \text{ induced-fun } A = f A$ 
proof (safe)
  have  $\forall (a, b) \in r. relation\text{-}class\ r\ a = relation\text{-}class\ r\ b$ 
    using assms equiv-class-eq
    unfolding relation-class.simps
    by fastforce
  hence  $\forall (a, b) \in r. induced\text{-}fun\ a = induced\text{-}fun\ b$ 
    unfolding induced-fun-def inv- $\pi_Q.simps$ 
    by auto
  thus induced-fun respects r
    unfolding congruent-def
    by metis
  moreover fix  $A :: 'x \text{ set}$ 
  assume  $A \in s // r$ 
  moreover with assms
  obtain  $a :: 'x$  where
     $a \in A$  and
     $A\text{-eq-rel-class-r-a}: A = relation\text{-}class\ r\ a$ 
    using equiv-Eps-in proj-Eps
    unfolding proj-def relation-class.simps
    by metis
  ultimately have  $\pi_Q \text{ induced-fun } A = induced\text{-}fun\ a$ 
    using pass-to-quotient assms
    by blast
  thus  $\pi_Q \text{ induced-fun } A = f A$ 
    using A-eq-rel-class-r-a
    unfolding induced-fun-def
    by simp
qed

```

### 3.1.3 Equivalence Relations

**lemma** *restr-equals-restricted-rel*:

```

fixes
   $s\ t :: 'a\ set$  and
   $r :: 'a\ rel$ 
assumes
  closed-restricted-rel  $r\ s\ t$  and
   $t \subseteq s$ 
shows restricted-rel  $r\ t\ s = Restr\ r\ t$ 
proof (unfold restricted-rel.simps, safe)
  fix  $a\ b :: 'a$ 
  assume
     $(a, b) \in r$  and
     $a \in t$  and
     $b \in s$ 
  thus  $b \in t$ 
    using assms
    unfolding closed-restricted-rel.simps restricted-rel.simps
    by blast
next
  fix  $a\ b :: 'a$ 
  assume  $b \in t$ 
  thus  $b \in s$ 
    using assms
    by blast
qed

```

**lemma** *equiv-rel-restr*:

```

fixes
   $s\ t :: 'x\ set$  and
   $r :: 'x\ rel$ 
assumes
  equiv  $s\ r$  and
   $t \subseteq s$ 
shows equiv  $t\ (Restr\ r\ t)$ 
proof (unfold equiv-def refl-on-def, safe)
  fix  $x :: 'x$ 
  assume  $x \in t$ 
  thus  $(x, x) \in r$ 
    using assms
    unfolding equiv-def refl-on-def
    by blast
next
  show sym  $(Restr\ r\ t)$ 
    using assms
    unfolding equiv-def sym-def
    by blast
next
  show Relation.trans  $(Restr\ r\ t)$ 

```

```

    using assms
    unfolding equiv-def Relation.trans-def
    by blast
qed

lemma rel-ind-by-group-act-equiv:
  fixes
     $m :: 'x \text{ monoid}$  and
     $s :: 'y \text{ set}$  and
     $\varphi :: ('x, 'y) \text{ binary-fun}$ 
  assumes group-action m s  $\varphi$ 
  shows equiv s (action-induced-rel (carrier m) s  $\varphi$ )
proof (unfold equiv-def refl-on-def sym-def Relation.trans-def
         action-induced-rel.simps, safe)
  fix  $y :: 'y$ 
  assume  $y \in s$ 
  hence  $\varphi \mathbf{1} \ m \ y = y$ 
    using assms group-action.id-eq-one restrict-apply'
    by metis
  thus  $\exists g \in \text{carrier } m. \varphi \ g \ y = y$ 
    using assms group.is-monoid group-hom.axioms
    unfolding group-action-def
    by blast
next
fix
   $y :: 'y$  and
   $g :: 'x$ 
  assume
    y-in-s:  $y \in s$  and
    carrier-g:  $g \in \text{carrier } m$ 
  hence  $y = \varphi \ (\text{inv } m \ g) \ (\varphi \ g \ y)$ 
    using assms
    by (simp add: group-action.orbit-sym-aux)
  thus  $\exists h \in \text{carrier } m. \varphi \ h \ (\varphi \ g \ y) = y$ 
    using assms carrier-g group.inv-closed
         group-action.group-hom
    unfolding group-hom-def
    by metis
next
fix
   $y :: 'y$  and
   $g \ h :: 'x$ 
  assume
    y-in-s:  $y \in s$  and
    carrier-g:  $g \in \text{carrier } m$  and
    carrier-h:  $h \in \text{carrier } m$ 
  hence  $\varphi \ (h \otimes m \ g) \ y = \varphi \ h \ (\varphi \ g \ y)$ 
    using assms
    by (simp add: group-action.composition-rule)

```

```

thus  $\exists f \in \text{carrier } m. \varphi f y = \varphi h (\varphi g y)$ 
  using assms carrier-g carrier-h group-action.group-hom
        monoid.m-closed
  unfolding group-def group-hom-def
  by metis
next
fix
   $y :: 'y$  and
   $g :: 'x$ 
assume
   $y \in s$  and
   $g \in \text{carrier } m$ 
thus  $\varphi g y \in s$ 
  using assms group-action.element-image
  by metis
next
fix
   $y :: 'y$  and
   $g :: 'x$ 
assume
   $y \in s$  and
   $g \in \text{carrier } m$ 
thus  $\varphi g y \in s$ 
  using assms group-action.element-image
  by metis
qed

end

```

## 3.2 Quotients of Election Set Equivalences

```

theory Election-Quotients
  imports Relation-Quotients
        ../Social-Choice-Types/Voting-Symmetry
        ../Social-Choice-Types/Ordered-Relation
        HOL-Analysis.Convex
        HOL-Analysis.Cartesian-Space
begin

```

### 3.2.1 Auxiliary Lemmas

```

lemma obtain-partition:
  fixes
     $A :: 'a \text{ set}$  and
     $V :: 'v \text{ set}$  and
     $f :: 'v \Rightarrow \text{nat}$ 
  assumes

```

```

    finite A and
    finite V and
    ( $\sum v :: 'v \in V. f v = \text{card } A$ )
  shows  $\exists \mathcal{B} :: 'v \Rightarrow 'a \text{ set.}$ 
     $A = \bigcup \{\mathcal{B} v \mid v :: 'v. v \in V\} \wedge (\forall v :: 'v \in V. \text{card } (\mathcal{B} v) = f v)$ 
     $\wedge (\forall v v' :: 'v. v \neq v' \longrightarrow v \in V \wedge v' \in V \longrightarrow \mathcal{B} v \cap \mathcal{B} v' = \{\})$ 
  using assms
proof (induction card V arbitrary: A V)
  case 0
  fix
    A :: 'a set and
    V :: 'v set
  let ?B =  $\lambda v :: 'v. \{\}$ 
  assume
    finite V and
    0 = card V
  hence V-empty:  $V = \{\}$ 
  using 0
  by simp
  hence ( $\sum v :: 'v \in V. f v = 0$ )
  by simp
  moreover assume
    finite A and
    ( $\sum v :: 'v \in V. f v = \text{card } A$ )
  ultimately have  $A = \{\}$ 
  by simp
  hence  $A = \bigcup \{\mathcal{B} v \mid v :: 'v. v \in V\}$ 
  by blast
  moreover have  $\forall v v' :: 'v. v \neq v' \longrightarrow v \in V \wedge v' \in V \longrightarrow \mathcal{B} v \cap \mathcal{B} v' = \{\}$ 
  by blast
  ultimately show
     $\exists \mathcal{B} :: 'v \Rightarrow 'a \text{ set.}$ 
     $A = \bigcup \{\mathcal{B} v \mid v :: 'v. v \in V\} \wedge (\forall v :: 'v \in V. \text{card } (\mathcal{B} v) = f v)$ 
     $\wedge (\forall v v' :: 'v. v \neq v' \longrightarrow v \in V \wedge v' \in V \longrightarrow \mathcal{B} v \cap \mathcal{B} v' = \{\})$ 
    using V-empty
    by simp
next
  case (Suc n)
  fix
    n :: nat and
    A :: 'a set and
    V :: 'v set
  assume
    card-V:  $\text{Suc } n = \text{card } V$  and
    fin-V: finite V and
    fin-A: finite A and
    card-A: ( $\sum v :: 'v \in V. f v = \text{card } A$ ) and
    hyp:
       $\bigwedge V' (A' :: 'a \text{ set}).$ 

```

$n = \text{card } V' \implies$   
 $\text{finite } A' \implies$   
 $\text{finite } V' \implies$   
 $(\sum v :: 'v \in V'. f v) = \text{card } A' \implies$   
 $\exists \mathcal{B} :: 'v \Rightarrow 'a \text{ set.}$   
 $A' = \bigcup \{ \mathcal{B} v \mid v :: 'v. v \in V' \} \wedge$   
 $(\forall v :: 'v \in V'. \text{card } (\mathcal{B} v) = f v) \wedge$   
 $(\forall v v' :: 'v. v \neq v' \longrightarrow v \in V' \wedge v' \in V' \longrightarrow \mathcal{B} v \cap \mathcal{B} v' = \{\})$

**then obtain**

$V' :: 'v \text{ set and}$   
 $v :: 'v \text{ where}$   
 $\text{ins-}V: V = \text{insert } v \ V' \text{ and}$   
 $\text{card-}V': \text{card } V' = n \text{ and}$   
 $\text{fin-}V': \text{finite } V' \text{ and}$   
 $\text{v-not-in-}V': v \notin V'$   
**using** *card-Suc-eq-finite*  
**by** (*metis (no-types, lifting)*)

**hence**  $f v \leq \text{card } A$

**using** *card-A le-add1 n-not-Suc-n sum.insert*  
**by** *metis*

**then obtain**  $A' :: 'a \text{ set where}$

$A'\text{-in-}A: A' \subseteq A \text{ and}$   
 $\text{card-}A': \text{card } A' = f v$   
**using** *fin-A ex-card*  
**by** *metis*

**hence**  $\text{finite } (A - A') \wedge \text{card } (A - A') = (\sum v' :: 'v \in V'. f v')$

**using** *card-V card-A fin-A ins-V card-V' fin-V' Suc-n-not-n*  
 $\text{add-diff-cancel-left' card-Diff-subset card-insert-if}$   
 $\text{finite-Diff finite-subset sum.insert}$   
**by** *metis*

**then obtain**  $\mathcal{B} :: 'v \Rightarrow 'a \text{ set where}$

$\text{part: } A - A' = \bigcup \{ \mathcal{B} v' \mid v' :: 'v. v' \in V' \} \text{ and}$   
 $\text{disj: } \forall v' v'' :: 'v. v' \neq v'' \longrightarrow v' \in V' \wedge v'' \in V' \longrightarrow \mathcal{B} v' \cap \mathcal{B} v'' = \{\} \text{ and}$   
 $\text{card: } \forall v' :: 'v \in V'. \text{card } (\mathcal{B} v') = f v'$   
**using** *hyp[of V' A - A'] fin-V' card-V'*  
**by** *auto*

**then obtain**  $\mathcal{B}' :: 'v \Rightarrow 'a \text{ set where}$

$\text{map': } \mathcal{B}' = (\lambda z :: 'v. \text{if } z = v \text{ then } A' \text{ else } \mathcal{B} z)$   
**by** *simp*

**hence**  $\text{eq-}\mathcal{B}: \forall v' :: 'v \in V'. \mathcal{B}' v' = \mathcal{B} v'$

**using** *v-not-in-V'*  
**by** *simp*

**have**  $V = \{v\} \cup V'$

**using** *ins-V*  
**by** *simp*

**hence**  $\bigcup \{ \mathcal{B}' v' \mid v' :: 'v. v' \in V \} = \mathcal{B}' v \cup \bigcup \{ \mathcal{B}' v' \mid v' :: 'v. v' \in V' \}$

**by** *blast*  
**also have**  $\dots = A' \cup \bigcup \{ \mathcal{B} v' \mid v' :: 'v. v' \in V' \}$   
**using** *map' eq-B*

by *fastforce*  
**finally have** *part'*:  $A = \bigcup \{\mathcal{B}' v' \mid v' :: 'v. v' \in V\}$   
 using *part Diff-partition A'-in-A*  
 by *metis*  
**have**  $\forall v' :: 'v \in V'. \mathcal{B}' v' \subseteq A - A'$   
 using *part eq-B Setcompr-eq-image UN-upper*  
 by *metis*  
**hence**  $\forall v' :: 'v \in V'. \mathcal{B}' v' \cap A' = \{\}$   
 by *blast*  
**hence**  $\forall v' :: 'v \in V'. \mathcal{B}' v' \cap \mathcal{B}' v = \{\}$   
 using *map'*  
 by *simp*  
**hence**  $\forall v' v'' :: 'v. v' \neq v'' \longrightarrow v' \in V \wedge v'' \in V \longrightarrow \mathcal{B}' v' \cap \mathcal{B}' v'' = \{\}$   
 using *map' disj ins-V inf commute insertE*  
 by (*metis (no-types, lifting)*)  
**moreover have**  $\forall v' :: 'v \in V. \text{card } (\mathcal{B}' v') = f v'$   
 using *map' card card-A' ins-V*  
 by *simp*  
**ultimately show**  
 $\exists \mathcal{B} :: 'v \Rightarrow 'a \text{ set.}$   
 $A = \bigcup \{\mathcal{B} v' \mid v' :: 'v. v' \in V\} \wedge (\forall v' :: 'v \in V. \text{card } (\mathcal{B} v') = f v')$   
 $\wedge (\forall v' v'' :: 'v. v' \neq v'' \longrightarrow v' \in V \wedge v'' \in V \longrightarrow \mathcal{B} v' \cap \mathcal{B} v'' = \{\})$   
 using *part'*  
 by *blast*  
**qed**

### 3.2.2 Anonymity Quotient: Grid

**fun** *anonymity*<sub>Q</sub> ::  $'a \text{ set} \Rightarrow ('a, 'v) \text{ Election set set}$  **where**  
*anonymity*<sub>Q</sub>  $A = \text{quotient } (\text{elections-}\mathcal{A} \ A) \ (\text{anonymity}_{\mathcal{R}} \ (\text{elections-}\mathcal{A} \ A))$

— Here, we count the occurrences of a ballot per election in a set of elections for which the occurrences of the ballot per election coincide for all elections in the set.

**fun** *vote-count*<sub>Q</sub> ::  $'a \text{ Preference-Relation} \Rightarrow ('a, 'v) \text{ Election set} \Rightarrow \text{nat}$  **where**  
*vote-count*<sub>Q</sub>  $r = \pi_Q \ (\text{vote-count } r)$

**fun** *anonymity-class* ::  $('a :: \text{finite}, 'v) \text{ Election set} \Rightarrow$   
 $(\text{nat}, 'a \text{ Ordered-Preference}) \text{ vec}$  **where**  
*anonymity-class*  $\mathcal{C} = (\chi \ p. \text{vote-count}_Q \ (\text{ord2pref } p) \ \mathcal{C})$

**lemma** *anon-rel-equiv*:  $\text{equiv } (\text{elections-}\mathcal{A} \ \text{UNIV}) \ (\text{anonymity}_{\mathcal{R}} \ (\text{elections-}\mathcal{A} \ \text{UNIV}))$

**proof** —

**have** *subset*:  $\text{elections-}\mathcal{A} \ \text{UNIV} \subseteq \text{well-formed-elections}$

by *simp*

**have** *equiv*:  $\text{equiv } \text{well-formed-elections} \ (\text{anonymity}_{\mathcal{R}} \ \text{well-formed-elections})$

using *anonymous-group-action.group-action-axioms rel-ind-by-group-act-equiv* [of  
*bijection<sub>VG</sub> well-formed-elections  $\varphi$ -anon well-formed-elections*]  
*rel-ind-by-coinciding-action-on-subset-eq-restr*

by *fastforce*

```

have closed:
  closed-restricted-rel
  (anonymityR well-formed-elections) well-formed-elections (elections-A UNIV)
proof (unfold closed-restricted-rel.simps restricted-rel.simps, safe)
  fix
    A A' :: 'c set and
    V V' :: 'd set and
    p p' :: ('c, 'd) Profile
  assume elt: (A, V, p) ∈ elections-A UNIV
  hence wf-elections: (A, V, p) ∈ well-formed-elections
    unfolding elections-A.simps
    by blast
  assume ((A, V, p), A', V', p') ∈ anonymityR well-formed-elections
  then obtain π :: 'd ⇒ 'd where
    bij-π: bij π and
    img: (A', V', p') = rename π (A, V, p)
    unfolding anonymityR.simps action-induced-rel.simps
      bijectionVG-def φ-anon.simps rewrite-carrier
      extensional-continuation.simps
    by auto
  hence (A', V', p') ∈ well-formed-elections
    using wf-elections rename-sound
    unfolding well-formed-elections-def
    by fastforce
  moreover have A' = A ∧ finite V
    using bij-π elt img rename.simps wf-elections well-formed-elections-def
    by auto
  moreover have  $\forall v. v \notin V' \longrightarrow (the\_inv\ \pi\ v) \notin V$ 
    using elt Pair-inject UNIV-I bij-π rename.simps
      f-the-inv-into-f-bij-betw image-eqI img
    unfolding elections-A.simps
    by (metis (mono-tags, opaque-lifting))
  moreover have  $\forall v. v \notin V' \longrightarrow p'\ v = p\ (the\_inv\ \pi\ v)$ 
    using img
    by simp
  ultimately show (A', V', p') ∈ elections-A UNIV
    using elt img
    unfolding elections-A.simps rename.simps
    by auto
qed
have
  anonymityR (elections-A UNIV) =
    restricted-rel (anonymityR well-formed-elections) (elections-A UNIV)
    well-formed-elections
proof (unfold restricted-rel.simps, safe)
  fix
    A A' :: 'c set and
    V V' :: 'd set and
    p p' :: ('c, 'd) Profile

```



**assume**  $rel: ((A, V, p), A', V', p') \in \text{anonymity}_{\mathcal{R}} \text{ (elections-}\mathcal{A} \text{ UNIV)}$   
**hence**  $(A, V, p) \in \text{well-formed-elections}$   
**unfolding**  $\text{anonymity}_{\mathcal{R}}.\text{sims action-induced-rel.sims elections-}\mathcal{A}.\text{sims}$   
**by** *blast*  
**moreover obtain**  $\pi :: 'd \Rightarrow 'd$  **where**  
**bij**  $\pi$  **and**  
 $(A', V', p') = \text{rename } \pi (A, V, p)$   
**using**  $rel$   
**unfolding**  $\text{anonymity}_{\mathcal{R}}.\text{sims action-induced-rel.sims}$   
 $\text{bijection}_{\text{VG-def}} \varphi\text{-anon.sims rewrite-carrier}$   
 $\text{extensional-continuation.sims}$   
**by** *auto*  
**ultimately show**  $((A, V, p), A', V', p') \in \text{anonymity}_{\mathcal{R}} \text{ well-formed-elections}$   
**unfolding**  $\text{anonymity}_{\mathcal{R}}.\text{sims action-induced-rel.sims}$   
 $\text{bijection}_{\text{VG-def}} \varphi\text{-anon.sims rewrite-carrier}$   
**by** *auto*  
**next**  
**fix**  
 $A \ A' :: 'c \text{ set and}$   
 $V \ V' :: 'd \text{ set and}$   
 $p \ p' :: ('c, 'd) \text{ Profile}$   
**assume**  $((A, V, p), A', V', p') \in \text{anonymity}_{\mathcal{R}} \text{ (elections-}\mathcal{A} \text{ UNIV)}$   
**thus**  $(A, V, p) \in \text{elections-}\mathcal{A} \text{ UNIV}$   
**unfolding**  $\text{anonymity}_{\mathcal{R}}.\text{sims action-induced-rel.sims}$   
**by** *blast*  
**next**  
**fix**  
 $A \ A' :: 'c \text{ set and}$   
 $V \ V' :: 'd \text{ set and}$   
 $p \ p' :: ('c, 'd) \text{ Profile}$   
**assume**  
 $rel: ((A, V, p), A', V', p') \in \text{anonymity}_{\mathcal{R}} \text{ (elections-}\mathcal{A} \text{ UNIV)}$   
**hence**  $((A, V, p), A', V', p') \in \text{anonymity}_{\mathcal{R}} \text{ well-formed-elections}$   
**unfolding**  $\text{anonymity}_{\mathcal{R}}.\text{sims action-induced-rel.sims}$   
**by** *fastforce*  
**moreover have**  $elt: (A, V, p) \in \text{elections-}\mathcal{A} \text{ UNIV}$   
**using**  $rel$   
**unfolding**  $\text{anonymity}_{\mathcal{R}}.\text{sims action-induced-rel.sims}$   
**by** *blast*  
**ultimately have**  
 $((A, V, p), A', V', p') \in \text{restricted-rel}$   
 $(\text{anonymity}_{\mathcal{R}} \text{ well-formed-elections}) \text{ (elections-}\mathcal{A} \text{ UNIV)} \text{ well-formed-elections}$   
**using** *equiv*  
**unfolding**  $\text{restricted-rel.sims equiv-def refl-on-def}$   
**by** *blast*  
**hence**  $(A', V', p') \in \text{elections-}\mathcal{A} \text{ UNIV}$   
**using** *closed elt*  
**unfolding**  $\text{closed-restricted-rel.sims}$   
**by** *blast*

```

thus  $(A', V', p') \in \text{well-formed-elections}$ 
  using subset
  by blast
next
fix
   $A\ A' :: 'c\ \text{set}$  and
   $V\ V' :: 'd\ \text{set}$  and
   $p\ p' :: ('c, 'd)\ \text{Profile}$ 
assume
   $(A, V, p) \in \text{elections-}\mathcal{A}\ \text{UNIV}$  and
   $((A, V, p), A', V', p') \in \text{anonymity}_{\mathcal{R}}\ \text{well-formed-elections}$ 
moreover from this
obtain  $\pi :: 'd \Rightarrow 'd$  where
  bij  $\pi$  and
   $(A', V', p') = \text{rename } \pi\ (A, V, p)$ 
unfolding anonymityR.sims action-induced-rel.sims
  bijectionVG-def  $\varphi$ -anon.sims rewrite-carrier
  extensional-continuation.sims
by auto
ultimately show  $((A, V, p), A', V', p') \in \text{anonymity}_{\mathcal{R}}\ (\text{elections-}\mathcal{A}\ \text{UNIV})$ 
unfolding anonymityR.sims action-induced-rel.sims
  bijectionVG-def  $\varphi$ -anon.sims rewrite-carrier
  extensional-continuation.sims
by auto
qed
also have  $\dots = \text{Restr } (\text{anonymity}_{\mathcal{R}}\ \text{well-formed-elections})\ (\text{elections-}\mathcal{A}\ \text{UNIV})$ 
using restr-equals-restricted-rel closed subset
by blast
finally have
   $\text{anonymity}_{\mathcal{R}}\ (\text{elections-}\mathcal{A}\ \text{UNIV}) =$ 
   $\text{Restr } (\text{anonymity}_{\mathcal{R}}\ \text{well-formed-elections})\ (\text{elections-}\mathcal{A}\ \text{UNIV})$ 
by simp
thus ?thesis
using equiv-rel-restr subset equiv
by metis
qed

```

We assume that all elections consist of a fixed finite alternative set of size  $n$  and finite subsets of an infinite voter universe. Profiles are linear orders on the alternatives. Then, we can operate on the natural-number-vectors of dimension  $n!$  instead of the equivalence classes of the anonymity relation: Each dimension corresponds to one possible linear order on the alternative set, i.e., the possible preferences. Each equivalence class of elections corresponds to a vector whose entries denote the amount of voters per election in that class who vote the respective corresponding preference.

**theorem** *anonymity<sub>Q</sub>-isomorphism:*  
**assumes** *infinite*  $(\text{UNIV} :: 'v\ \text{set})$   
**shows** *bij-betw*  $(\text{anonymity-class} :: ('a :: \text{finite}, 'v)\ \text{Election set})$

$\Rightarrow \text{nat} \hat{\sim} ('a \text{ Ordered-Preference})) (\text{anonymity}_{\mathcal{Q}} (\text{UNIV} :: 'a \text{ set}))$   
 $(\text{UNIV} :: (\text{nat} \hat{\sim} ('a \text{ Ordered-Preference})) \text{ set})$   
**proof** (unfold bij-betw-def inj-on-def, intro conjI ballI impI)  
**fix**  $X Y :: ('a, 'v) \text{ Election set}$   
**assume**  
 $\text{class-}X: X \in \text{anonymity}_{\mathcal{Q}} \text{ UNIV}$  **and**  
 $\text{class-}Y: Y \in \text{anonymity}_{\mathcal{Q}} \text{ UNIV}$  **and**  
 $\text{eq-vec}: \text{anonymity-class } X = \text{anonymity-class } Y$   
**have**  $\forall E \in \text{elections-}\mathcal{A} \text{ UNIV}. \text{finite} (\text{voters-}\mathcal{E} E)$   
**by** simp  
**hence**  $\forall (E, E') \in \text{anonymity}_{\mathcal{R}} (\text{elections-}\mathcal{A} \text{ UNIV}). \text{finite} (\text{voters-}\mathcal{E} E)$   
**by** simp  
**moreover** **have**  $\text{subset}: \text{elections-}\mathcal{A} \text{ UNIV} \subseteq \text{well-formed-elections}$   
**by** simp  
**ultimately** **have**  
 $\forall (E, E') \in \text{anonymity}_{\mathcal{R}} (\text{elections-}\mathcal{A} \text{ UNIV}).$   
 $\forall p. \text{vote-count } p E = \text{vote-count } p E'$   
**using** anon-rel-vote-count  
**by** blast  
**hence** vote-count-invar:  
 $\forall p. (\text{vote-count } p) \text{ respects } (\text{anonymity}_{\mathcal{R}} (\text{elections-}\mathcal{A} \text{ UNIV}))$   
**unfolding** congruent-def  
**by** blast  
**have** quotient-count:  
 $\forall X \in \text{anonymity}_{\mathcal{Q}} \text{ UNIV}. \forall p. \forall E \in X. \text{vote-count}_{\mathcal{Q}} p X = \text{vote-count } p E$   
**using** pass-to-quotient[of anonymity<sub>R</sub> (elections- $\mathcal{A}$  UNIV)]  
vote-count-invar anon-rel-equiv  
**unfolding** anonymity<sub>Q</sub>.simps anonymity<sub>R</sub>.simps vote-count<sub>Q</sub>.simps  
**by** metis  
**moreover** **from** anon-rel-equiv  
**obtain**  
 $E E' :: ('a, 'v) \text{ Election}$  **where**  
 $E\text{-in-}X: E \in X$  **and**  
 $E'\text{-in-}Y: E' \in Y$   
**using** class-X class-Y equiv-Eps-in  
**unfolding** anonymity<sub>Q</sub>.simps  
**by** metis  
**ultimately** **have**  
 $\forall p. \text{vote-count}_{\mathcal{Q}} p X = \text{vote-count } p E \wedge \text{vote-count}_{\mathcal{Q}} p Y = \text{vote-count } p E'$   
**using** class-X class-Y  
**by** blast  
**moreover** **with** eq-vec **have**  
 $\forall p. \text{vote-count}_{\mathcal{Q}} (\text{ord2pref } p) X = \text{vote-count}_{\mathcal{Q}} (\text{ord2pref } p) Y$   
**unfolding** anonymity-class.simps  
**using** UNIV-I vec-lambda-inverse  
**by** metis  
**ultimately** **have**  $\forall p. \text{vote-count } (\text{ord2pref } p) E = \text{vote-count } (\text{ord2pref } p) E'$   
**by** simp  
**hence** eq:  $\forall p \in \{r. \text{linear-order-on } (\text{UNIV} :: 'a \text{ set}) r\}.$

$vote\_count\ p\ E = vote\_count\ p\ E'$   
**using** *pref2ord-inverse*  
**by** *metis*  
**from** *anon-rel-equiv class-X class-Y* **have** *subset-fixed-alts*:  
 $X \subseteq elections\text{-}\mathcal{A}\ UNIV \wedge Y \subseteq elections\text{-}\mathcal{A}\ UNIV$   
**unfolding** *anonymity<sub>Q</sub>.simps*  
**using** *in-quotient-imp-subset*  
**by** *blast*  
**hence** *eq-alts: alternatives- $\mathcal{E}$   $E = UNIV \wedge alternatives\text{-}\mathcal{E}\ E' = UNIV$*   
**using** *E-in-X E'-in-Y*  
**unfolding** *elections- $\mathcal{A}$ .simps*  
**by** *blast*  
**with** *subset-fixed-alts* **have** *eq-complement*:  
 $\forall p \in UNIV - \{r. linear\_order\_on\ (UNIV :: 'a\ set)\ r\}.$   
 $\{v \in voters\text{-}\mathcal{E}\ E. profile\text{-}\mathcal{E}\ E\ v = p\} = \{\}$   
 $\wedge \{v \in voters\text{-}\mathcal{E}\ E'. profile\text{-}\mathcal{E}\ E'\ v = p\} = \{\}$   
**using** *E-in-X E'-in-Y*  
**unfolding** *elections- $\mathcal{A}$ .simps well-formed-elections-def profile-def*  
**by** *auto*  
**hence**  $\forall p \in UNIV - \{r. linear\_order\_on\ (UNIV :: 'a\ set)\ r\}.$   
 $vote\_count\ p\ E = 0 \wedge vote\_count\ p\ E' = 0$   
**unfolding** *card-eq-0-iff vote-count.simps*  
**by** *simp*  
**with** *eq* **have** *eq-vote-count:  $\forall p. vote\_count\ p\ E = vote\_count\ p\ E'$*   
**using** *DiffI UNIV-I*  
**by** *metis*  
**moreover from** *subset-fixed-alts E-in-X E'-in-Y*  
**have** *finite (voters- $\mathcal{E}$  E)  $\wedge$  finite (voters- $\mathcal{E}$  E')*  
**unfolding** *elections- $\mathcal{A}$ .simps*  
**by** *blast*  
**moreover from** *subset-fixed-alts E-in-X E'-in-Y*  
**have**  $(E, E') \in (elections\text{-}\mathcal{A}\ UNIV) \times (elections\text{-}\mathcal{A}\ UNIV)$   
**by** *blast*  
**moreover from** *this*  
**have**  $(\forall v. v \notin voters\text{-}\mathcal{E}\ E \longrightarrow profile\text{-}\mathcal{E}\ E\ v = \{\})$   
 $\wedge (\forall v. v \notin voters\text{-}\mathcal{E}\ E' \longrightarrow profile\text{-}\mathcal{E}\ E'\ v = \{\})$   
**by** *simp*  
**ultimately have**  $(E, E') \in anonymity_{\mathcal{R}}\ (elections\text{-}\mathcal{A}\ UNIV)$   
**using** *eq-alts vote-count-anon-rel*  
**by** *metis*  
**hence**  $anonymity_{\mathcal{R}}\ (elections\text{-}\mathcal{A}\ UNIV) \text{ “ } \{E\} =$   
 $anonymity_{\mathcal{R}}\ (elections\text{-}\mathcal{A}\ UNIV) \text{ “ } \{E'\}$   
**using** *anon-rel-equiv equiv-class-eq*  
**by** *metis*  
**also have**  $anonymity_{\mathcal{R}}\ (elections\text{-}\mathcal{A}\ UNIV) \text{ “ } \{E\} = X$   
**using** *E-in-X class-X anon-rel-equiv Image-singleton-iff equiv-class-eq quotientE*  
**unfolding** *anonymity<sub>Q</sub>.simps*  
**by** *(metis (no-types, lifting))*  
**also have**  $anonymity_{\mathcal{R}}\ (elections\text{-}\mathcal{A}\ UNIV) \text{ “ } \{E'\} = Y$

```

using  $E'$ -in- $Y$  class- $Y$  anon-rel-equiv Image-singleton-iff equiv-class-eq quotientE
unfolding anonymityQ.simps
by (metis (no-types, lifting))
finally show  $X = Y$ 
by simp
next
have ( $UNIV :: (nat, 'a \text{ Ordered-Preference}) \text{ vec set}$ )  $\subseteq$ 
  ( $\text{anonymity-class} :: ('a, 'v) \text{ Election set} \Rightarrow (nat, 'a \text{ Ordered-Preference}) \text{ vec}$ ) '
  anonymityQ UNIV
proof (unfold anonymity-class.simps, safe)
fix  $x :: (nat, 'a \text{ Ordered-Preference}) \text{ vec}$ 
have finite ( $UNIV :: 'a \text{ Ordered-Preference set}$ )
by simp
hence finite  $\{x\$i \mid i. i \in UNIV\}$ 
using finite-Atleast-Atmost-nat
by blast
hence  $(\sum i \in UNIV. x\$i) < \infty$ 
using enat-ord-code
by simp
moreover have  $0 \leq (\sum i \in UNIV. x\$i)$ 
by blast
ultimately obtain  $V :: 'v \text{ set}$  where
  fin-V: finite  $V$  and
  card  $V = (\sum i \in UNIV. x\$i)$ 
using assms infinite-arbitrarily-large
by metis
then obtain  $X' :: 'a \text{ Ordered-Preference} \Rightarrow 'v \text{ set}$  where
  card':  $\forall i. \text{card } (X' i) = x\$i$  and
  partition':  $V = \bigcup \{X' i \mid i. i \in UNIV\}$  and
  disjoint':  $\forall i j. i \neq j \longrightarrow X' i \cap X' j = \{\}$ 
using obtain-partition[of  $V$  UNIV  $(\$)$   $x$ ]
by auto
obtain  $X :: 'a \text{ Preference-Relation} \Rightarrow 'v \text{ set}$  where
  def-X:  $X = (\lambda i. \text{if } i \in \{r. \text{linear-order } r\}$ 
     $\text{then } X' (\text{pref2ord } i) \text{ else } \{\})$ 
by simp
hence  $\{X i \mid i. i \notin \{r. \text{linear-order } r\}\} \subseteq \{\{\}\}$ 
by auto
moreover have
   $\{X i \mid i. i \in \{r. \text{linear-order } r\}\} =$ 
   $\{X' (\text{pref2ord } i) \mid i. i \in \{r. \text{linear-order } r\}\}$ 
using def-X
by metis
moreover have
   $\{X i \mid i. i \in UNIV\} =$ 
   $\{X i \mid i. i \in \{r. \text{linear-order } r\}\}$ 
   $\cup \{X i \mid i. i \in UNIV - \{r. \text{linear-order } r\}\}$ 
by blast
ultimately have

```

$\{X\ i \mid i. i \in UNIV\} = \{X' (pref2ord\ i) \mid i. i \in \{r. linear-order\ r\}\}$   
 $\vee \{X\ i \mid i. i \in UNIV\} =$   
 $\{X' (pref2ord\ i) \mid i. i \in \{r. linear-order\ r\}\} \cup \{\{\}\}$   
 by *auto*  
 also have  
 $\{X' (pref2ord\ i) \mid i. i \in \{r. linear-order\ r\}\} = \{X' i \mid i. i \in UNIV\}$   
 using *iso-tuple-UNIV-I pref2ord-cases*  
 by *metis*  
 finally have  
 $\{X\ i \mid i. i \in UNIV\} = \{X' i \mid i. i \in UNIV\} \vee$   
 $\{X\ i \mid i. i \in UNIV\} = \{X' i \mid i. i \in UNIV\} \cup \{\{\}\}$   
 by *simp*  
 hence  $\bigcup \{X\ i \mid i. i \in UNIV\} = \bigcup \{X' i \mid i. i \in UNIV\}$   
 using *Sup-union-distrib ccpo-Sup-singleton sup-bot.right-neutral*  
 by *(metis (no-types, lifting))*  
 hence *partition*:  $V = \bigcup \{X\ i \mid i. i \in UNIV\}$   
 using *partition'*  
 by *simp*  
 moreover have  $\forall\ i\ j. i \neq j \longrightarrow X\ i \cap X\ j = \{\}$   
 using *disjoint' def-X pref2ord-inject*  
 by *auto*  
 ultimately have  $\forall\ v \in V. \exists!\ i. v \in X\ i$   
 by *auto*  
 then obtain  $p' :: 'v \Rightarrow 'a\ Preference-Relation$  where  
 $p-X: \forall\ v \in V. v \in X\ (p'\ v)$  and  
 $p-disj: \forall\ v \in V. \forall\ i. i \neq p'\ v \longrightarrow v \notin X\ i$   
 by *metis*  
 then obtain  $p :: 'v \Rightarrow 'a\ Preference-Relation$  where  
 $p-in-V-then-p': p = (\lambda\ v. if\ v \in V\ then\ p'\ v\ else\ \{\})$   
 by *simp*  
 hence *lin-ord*:  $\forall\ v \in V. linear-order\ (p\ v)$   
 using *def-X p-X p-disj*  
 by *fastforce*  
 hence *wf-elections*:  $(UNIV, V, p) \in elections-A\ UNIV$   
 using *fin-V*  
 unfolding *p-in-V-then-p' elections-A.simps*  
*well-formed-elections-def profile-def*  
 by *auto*  
 hence  $\forall\ i. \forall\ E \in anonymity_{\mathcal{R}}\ (elections-A\ UNIV) \text{ “ } \{(UNIV, V, p)\}.$   
*vote-count\ i\ E = vote-count\ i\ (UNIV, V, p)*  
 using *fin-V anon-rel-vote-count[of (UNIV, V, p) - elections-A UNIV]*  
 by *simp*  
 moreover have  
 $(UNIV, V, p) \in anonymity_{\mathcal{R}}\ (elections-A\ UNIV) \text{ “ } \{(UNIV, V, p)\}$   
 using *anon-rel-equiv wf-elections*  
 unfolding *Image-def equiv-def refl-on-def*  
 by *blast*  
 ultimately have *eq-vote-count*:  
 $\forall\ i. vote-count\ i\ ‘$

$(\text{anonymity}_{\mathcal{R}} (\text{elections-}\mathcal{A} \text{ UNIV}) \text{ “ } \{(UNIV, V, p)\} =$   
 $\{ \text{vote-count } i (UNIV, V, p) \}$   
 by *blast*  
 have  $\forall i. \forall v \in V. p \ v = i \longleftrightarrow v \in X \ i$   
 using *p-X p-disj*  
 unfolding *p-in-V-then-p'*  
 by *metis*  
 hence  $\forall i. \{v \in V. p \ v = i\} = \{v \in V. v \in X \ i\}$   
 by *blast*  
 moreover have  $\forall i. X \ i \subseteq V$   
 using *partition*  
 by *blast*  
 ultimately have *rewr-preimg*:  $\forall i. \{v \in V. p \ v = i\} = X \ i$   
 by *auto*  
 hence  $\forall i \in \{r. \text{linear-order } r\}.$   
 $\text{vote-count } i (UNIV, V, p) = x\$(\text{pref2ord } i)$   
 using *def-X card'*  
 by *simp*  
 hence  $\forall i \in \{r. \text{linear-order } r\}.$   
 $\text{vote-count } i \text{ “ } (\text{anonymity}_{\mathcal{R}} (\text{elections-}\mathcal{A} \text{ UNIV}) \text{ “ } \{(UNIV, V, p)\} =$   
 $\{x\$(\text{pref2ord } i)\}$   
 using *eq-vote-count*  
 by *metis*  
 hence  
 $\forall i \in \{r. \text{linear-order } r\}.$   
 $\text{vote-count}_{\mathcal{Q}} \ i (\text{anonymity}_{\mathcal{R}} (\text{elections-}\mathcal{A} \text{ UNIV}) \text{ “ } \{(UNIV, V, p)\} =$   
 $x\$(\text{pref2ord } i)$   
 unfolding *vote-count<sub>Q</sub>.simps* *π<sub>Q</sub>.simps* *singleton-set.simps*  
 using *is-singleton-altdef* *singleton-set-def-if-card-one*  
 by *fastforce*  
 hence  $\forall i. \text{vote-count}_{\mathcal{Q}} (\text{ord2pref } i)$   
 $(\text{anonymity}_{\mathcal{R}} (\text{elections-}\mathcal{A} \text{ UNIV}) \text{ “ } \{(UNIV, V, p)\}) = x\$i$   
 using *ord2pref ord2pref-inverse*  
 by *metis*  
 hence *anonymity-class*  
 $(\text{anonymity}_{\mathcal{R}} (\text{elections-}\mathcal{A} \text{ UNIV}) \text{ “ } \{(UNIV, V, p)\}) = x$   
 using *anonymity-class.simps* *vec-lambda-unique*  
 by (*metis* (*no-types*, *lifting*))  
 moreover have  
 $\text{anonymity}_{\mathcal{R}} (\text{elections-}\mathcal{A} \text{ UNIV}) \text{ “ } \{(UNIV, V, p)\} \in \text{anonymity}_{\mathcal{Q}} \text{ UNIV}$   
 using *wf-elections*  
 unfolding *anonymity<sub>Q</sub>.simps* *quotient-def*  
 by *blast*  
 ultimately show  
 $x \in (\lambda X :: ('a, 'v) \text{Election set. } \chi \ p. \text{vote-count}_{\mathcal{Q}} (\text{ord2pref } p) \ X)$   
 $\text{“ } \text{anonymity}_{\mathcal{Q}} \text{ UNIV}$   
 using *anonymity-class.elims*  
 by *blast*  
 qed

**thus** (*anonymity-class* :: ('a, 'v) Election set  
 $\Rightarrow$  (nat, 'a Ordered-Preference) vec) '  
*anonymity*<sub>Q</sub> UNIV =  
 (UNIV :: (nat, 'a Ordered-Preference) vec set)  
**by** blast  
**qed**

### 3.2.3 Homogeneity Quotient: Simplex

**fun** *vote-fraction* :: 'a Preference-Relation  $\Rightarrow$  ('a, 'v) Election  $\Rightarrow$  rat **where**  
*vote-fraction* r E =  
 (if finite (voters- $\mathcal{E}$  E)  $\wedge$  voters- $\mathcal{E}$  E  $\neq$  {}  
 then Fract (vote-count r E) (card (voters- $\mathcal{E}$  E)) else 0)

**fun** *anonymity-homogeneity*<sub>R</sub> :: ('a, 'v) Election set  $\Rightarrow$  ('a, 'v) Election rel **where**  
*anonymity-homogeneity*<sub>R</sub>  $\mathcal{E}$  =  
 {(E, E') | E E'. E  $\in$   $\mathcal{E}$   $\wedge$  E'  $\in$   $\mathcal{E}$   
 $\wedge$  finite (voters- $\mathcal{E}$  E) = finite (voters- $\mathcal{E}$  E')  
 $\wedge$  ( $\forall$  r. *vote-fraction* r E = *vote-fraction* r E')}

**fun** *anonymity-homogeneity*<sub>Q</sub> :: 'a set  $\Rightarrow$  ('a, 'v) Election set set **where**  
*anonymity-homogeneity*<sub>Q</sub> A =  
 quotient (elections-A A) (*anonymity-homogeneity*<sub>R</sub> (elections-A A))

**fun** *vote-fraction*<sub>Q</sub> :: 'a Preference-Relation  $\Rightarrow$  ('a, 'v) Election set  $\Rightarrow$  rat **where**  
*vote-fraction*<sub>Q</sub> p =  $\pi_Q$  (*vote-fraction* p)

**fun** *anonymity-homogeneity-class* :: ('a :: finite, 'v) Election set  $\Rightarrow$   
 (rat, 'a Ordered-Preference) vec **where**  
*anonymity-homogeneity-class*  $\mathcal{E}$  = ( $\chi$  p. *vote-fraction*<sub>Q</sub> (ord2pref p)  $\mathcal{E}$ )

Maps each rational real vector entry to the corresponding rational. If the entry is not rational, the corresponding entry will be undefined.

**fun** *rat-vector* :: real<sup>^b</sup>  $\Rightarrow$  rat<sup>^b</sup> **where**  
*rat-vector* v = ( $\chi$  p. the-inv of-rat (v\$p))

**fun** *rat-vector-set* :: (real<sup>^b</sup>) set  $\Rightarrow$  (rat<sup>^b</sup>) set **where**  
*rat-vector-set* V = *rat-vector* ' {v  $\in$  V.  $\forall$  i. v\$i  $\in$  Q}

**definition** *standard-basis* :: (real<sup>^b</sup>) set **where**  
*standard-basis*  $\equiv$  {v.  $\exists$  b. v\$b = 1  $\wedge$  ( $\forall$  c  $\neq$  b. v\$c = 0)}

The rational points in the simplex.

**definition** *vote-simplex* :: (rat<sup>^b</sup>) set **where**  
*vote-simplex*  $\equiv$   
 insert 0 (*rat-vector-set* (convex hull *standard-basis* :: (real<sup>^b</sup>) set))

### Auxiliary Lemmas

**lemma** *convex-combination-in-convex-hull*:



**fixes**  
 $X :: (\text{real}^b) \text{ set}$  **and**  
 $x :: \text{real}^b$   
**assumes**  $\exists f :: \text{real}^b \Rightarrow \text{real}.$   
 $(\sum y \in X. f y) = 1 \wedge (\forall x \in X. f x \geq 0)$   
 $\wedge x = (\sum x \in X. f x *_R x)$   
**shows**  $x \in \text{convex hull } X$   
**using** *assms*  
**proof** (*induction card X arbitrary: X x*)  
**case** 0  
**fix**  
 $X :: (\text{real}^b) \text{ set}$  **and**  
 $x :: \text{real}^b$   
**assume**  
 $0 = \text{card } X$  **and**  
 $\exists f. (\sum y \in X. f y) = 1 \wedge (\forall x \in X. 0 \leq f x) \wedge x = (\sum x \in X. f x *_R x)$   
**hence**  $(\forall f. (\sum y \in X. f y) = 0) \wedge (\exists f. (\sum y \in X. f y) = 1)$   
**using** *card-0-eq empty-iff sum.infinite sum.neutral zero-neq-one*  
**by** *metis*  
**hence**  $\exists f. (\sum y \in X. f y) = 1 \wedge (\sum y \in X. f y) = 0$   
**by** *metis*  
**hence** *False*  
**using** *zero-neq-one*  
**by** *metis*  
**thus** *?case*  
**by** *simp*  
**next**  
**case** (*Suc n*)  
**fix**  
 $X :: (\text{real}^b) \text{ set}$  **and**  
 $x :: \text{real}^b$  **and**  
 $n :: \text{nat}$   
**assume**  
 $\text{card: } \text{Suc } n = \text{card } X$  **and**  
 $\exists f. (\sum y \in X. f y) = 1 \wedge (\forall x \in X. 0 \leq f x) \wedge x = (\sum x \in X. f x *_R x)$   
**and**  
 $\text{hyp: } \bigwedge (X :: (\text{real}^b) \text{ set}) x. n = \text{card } X$   
 $\implies \exists f. (\sum y \in X. f y) = 1 \wedge (\forall x \in X. 0 \leq f x) \wedge x =$   
 $(\sum x \in X. f x *_R x)$   
 $\implies x \in \text{convex hull } X$   
**then obtain**  $f :: \text{real}^b \Rightarrow \text{real}$  **where**  
 $\text{sum: } (\sum y \in X. f y) = 1$  **and**  
 $\text{nonneg: } \forall x \in X. 0 \leq f x$  **and**  
 $x\text{-sum: } x = (\sum x \in X. f x *_R x)$   
**by** *blast*  
**have**  $\text{card } X > 0$   
**using** *card*  
**by** *linarith*  
**hence** *fin: finite X*

```

using card-gt-0-iff
by blast
have  $n = 0 \longrightarrow \text{card } X = 1$ 
using card
by presburger
hence  $n = 0 \longrightarrow (\exists y. X = \{y\} \wedge f y = 1)$ 
using sum nonneg One-nat-def add.right-neutral card-1-singleton-iff
      empty-iff finite.emptyI sum.insert sum.neutral
by (metis (no-types, opaque-lifting))
hence  $n = 0 \longrightarrow (\exists y. X = \{y\} \wedge x = y)$ 
using x-sum
by fastforce
hence  $n = 0 \longrightarrow x \in X$ 
by blast
moreover have  $n > 0 \longrightarrow x \in \text{convex hull } X$ 
proof (safe)
  assume  $0 < n$ 
  hence card-X-gt-one:  $\text{card } X > 1$ 
    using card
    by simp
  have  $(\forall y \in X. f y \geq 1) \longrightarrow (\sum y \in X. f y) \geq (\sum x \in X. 1)$ 
    using fin sum-mono
    by metis
  moreover have  $(\sum x \in X. 1) = \text{card } X$ 
    by force
  ultimately have  $(\forall y \in X. f y \geq 1) \longrightarrow \text{card } X \leq (\sum y \in X. f y)$ 
    by force
  hence  $(\forall y \in X. f y \geq 1) \longrightarrow 1 < (\sum y \in X. f y)$ 
    using card-X-gt-one
    by linarith
  then obtain  $y :: \text{real}^b$  where
     $y\text{-in-}X: y \in X$  and
     $f\text{-}y\text{-lt-one}: f y < 1$ 
    using sum
    by auto
  hence  $1 - f y \neq 0 \wedge x = f y *_R y + (\sum x \in X - \{y\}. f x *_R x)$ 
    using fin sum.remove x-sum
    by simp
  moreover have
     $\forall \alpha \neq 0. (\sum x \in X - \{y\}. f x *_R x) =$ 
     $\alpha *_R (\sum x \in X - \{y\}. (f x / \alpha) *_R x)$ 
    unfolding scaleR-sum-right
    by simp
  ultimately have convex-comb:
     $x = f y *_R y + (1 - f y) *_R (\sum x \in X - \{y\}. (f x / (1 - f y)) *_R x)$ 
    by simp
  obtain  $f' :: \text{real}^b \Rightarrow \text{real}$  where
     $\text{def}' : f' = (\lambda x. f x / (1 - f y))$ 
    by simp

```

**hence**  $\forall x \in X - \{y\}. f' x \geq 0$   
**using** *nonneg f-y-lt-one*  
**by** *fastforce*  
**moreover have**  
 $(\sum y \in X - \{y\}. f' y) = (\sum x \in X - \{y\}. f x) / (1 - f y)$   
**unfolding** *def' sum-divide-distrib*  
**by** *simp*  
**moreover have**  
 $(\sum x \in X - \{y\}. f x) / (1 - f y) = (1 - f y) / (1 - f y)$   
**using** *sum y-in-X*  
**by** *(simp add: fin sum.remove)*  
**moreover have**  $(1 - f y) / (1 - f y) = 1$   
**using** *f-y-lt-one*  
**by** *simp*  
**ultimately have**  
 $(\sum y \in X - \{y\}. f' y) = 1 \wedge (\forall x \in X - \{y\}. 0 \leq f' x)$   
 $\wedge (\sum x \in X - \{y\}. (f x / (1 - f y)) *_R x) =$   
 $(\sum x \in X - \{y\}. f' x *_R x)$   
**using** *def'*  
**by** *metis*  
**hence**  $\exists f'. (\sum y \in X - \{y\}. f' y) = 1 \wedge (\forall x \in X - \{y\}. 0 \leq f' x)$   
 $\wedge (\sum x \in X - \{y\}. (f x / (1 - f y)) *_R x) =$   
 $(\sum x \in X - \{y\}. f' x *_R x)$   
**by** *metis*  
**moreover have**  $\text{card } (X - \{y\}) = n$   
**using** *card y-in-X*  
**by** *simp*  
**ultimately have**  
 $(\sum x \in X - \{y\}. (f x / (1 - f y)) *_R x) \in \text{convex hull } (X - \{y\})$   
**using** *hyp*  
**by** *blast*  
**hence**  $(\sum x \in X - \{y\}. (f x / (1 - f y)) *_R x) \in \text{convex hull } X$   
**using** *Diff-subset hull-mono in-mono*  
**by** *(metis (no-types, lifting))*  
**moreover have**  $f y \geq 0 \wedge 1 - f y \geq 0$   
**using** *f-y-lt-one nonneg y-in-X*  
**by** *simp*  
**moreover have**  $f y + (1 - f y) \geq 0$   
**by** *simp*  
**moreover have**  $y \in \text{convex hull } X$   
**using** *y-in-X*  
**by** *(simp add: hull-inc)*  
**moreover have**  
 $\forall x y. x \in \text{convex hull } X \wedge y \in \text{convex hull } X \longrightarrow$   
 $(\forall a \geq 0. \forall b \geq 0. a + b = 1 \longrightarrow a *_R x + b *_R y \in \text{convex hull } X)$   
**using** *convex-def convex-convex-hull*  
**by** *(metis (no-types, opaque-lifting))*  
**ultimately show**  $x \in \text{convex hull } X$   
**using** *convex-comb*

by simp  
 qed  
 ultimately show  $x \in \text{convex hull } X$   
 using hull-inc  
 by fastforce  
 qed

**lemma** *standard-simplex-rewrite: convex hull standard-basis =*  
 $\{v :: \text{real}^b. (\forall i. v\$i \geq 0) \wedge (\sum y \in \text{UNIV}. v\$y) = 1\}$   
**proof** (unfold convex-def hull-def, intro equalityI)  
 let ?simplex =  $\{v :: \text{real}^b. (\forall i. v\$i \geq 0) \wedge (\sum y \in \text{UNIV}. v\$y) = 1\}$   
 have  $\forall v :: \text{real}^b \in \text{standard-basis}. \exists b.$   
 $v\$b = 1 \wedge (\forall c. c \neq b \longrightarrow v\$c = 0)$   
 unfolding standard-basis-def  
 by simp  
 then obtain  $\text{one} :: \text{real}^b \Rightarrow ^b$  where  
 $\text{def-map: } \forall v \in \text{standard-basis}. v\$(\text{one } v) = 1 \wedge (\forall i \neq \text{one } v. v\$i = 0)$   
 by metis  
 hence  $\forall v :: \text{real}^b \in \text{standard-basis}. \forall b. v\$b \geq 0$   
 using dual-order.refl zero-less-one-class.zero-le-one  
 by metis  
 moreover have  $\forall v :: \text{real}^b \in \text{standard-basis}.$   
 $(\sum z \in \text{UNIV}. v\$z) = (\sum z \in \text{UNIV} - \{\text{one } v\}. v\$z) + v\$(\text{one } v)$   
 unfolding def-map  
 using add.commute finite insert-UNIV sum.insert-remove  
 by metis  
 moreover have  $\forall v \in \text{standard-basis}.$   
 $(\sum z \in \text{UNIV} - \{\text{one } v\}. v\$z) + v\$(\text{one } v) = 1$   
 using def-map  
 by simp  
 ultimately have  $\text{standard-basis} \subseteq ?\text{simplex}$   
 by force  
 moreover have  $\forall x :: \text{real}^b. \forall y. (\sum z \in \text{UNIV}. (x + y)\$z) =$   
 $(\sum z \in \text{UNIV}. x\$z) + (\sum z \in \text{UNIV}. y\$z)$   
 by (simp add: sum.distrib)  
 hence  $\forall x :: \text{real}^b. \forall y. \forall u v.$   
 $(\sum z \in \text{UNIV}. (u *_R x + v *_R y)\$z) =$   
 $u *_R (\sum z \in \text{UNIV}. x\$z) + v *_R (\sum z \in \text{UNIV}. y\$z)$   
 using scaleR-right.sum sum.cong vector-scaleR-component  
 by (metis (no-types))  
 hence  $\forall x \in ?\text{simplex}. \forall y \in ?\text{simplex}. \forall u v.$   
 $(\sum z \in \text{UNIV}. (u *_R x + v *_R y)\$z) = u *_R 1 + v *_R 1$   
 by simp  
 hence  $\forall x \in ?\text{simplex}. \forall y \in ?\text{simplex}. \forall u \geq 0. \forall v \geq 0.$   
 $u + v = 1 \longrightarrow u *_R x + v *_R y \in ?\text{simplex}$   
 by simp  
 ultimately show  
 $\bigcap \{t. (\forall x \in t. \forall y \in t. \forall u \geq 0. \forall v \geq 0.$   
 $u + v = 1 \longrightarrow u *_R x + v *_R y \in t)\}$

$\wedge \text{standard-basis} \subseteq t\} \subseteq ?\text{simplex}$   
 by *blast*  
 next  
 show  $\{v. (\forall i. 0 \leq v\$i) \wedge (\sum y \in \text{UNIV}. v\$y) = 1\} \subseteq$   
 $\bigcap \{t. (\forall x \in t. \forall y \in t. \forall u \geq 0. \forall v \geq 0.$   
 $u + v = 1 \longrightarrow u *_R x + v *_R y \in t)$   
 $\wedge (\text{standard-basis} :: (\text{real}^b \text{ set}) \subseteq t)\}$   
 proof (intro subsetI)  
 fix  
 $x :: \text{real}^b$  and  
 $X :: \text{real}^b \text{ set}$   
 assume *convex-comb*:  
 $x \in \{v. (\forall i. 0 \leq v\$i) \wedge (\sum y \in \text{UNIV}. v\$y) = 1\}$   
 have  $\forall v \in \text{standard-basis}. \exists b. v\$b = 1 \wedge (\forall b' \neq b. v\$b' = 0)$   
 unfolding *standard-basis-def*  
 by *simp*  
 then obtain  $\text{ind} :: \text{real}^b \Rightarrow 'b$  where  
 $\text{ind-eq-one}: \forall v \in \text{standard-basis}. v\$(\text{ind } v) = 1$  and  
 $\text{ind-eq-zero}: \forall v \in \text{standard-basis}. \forall b \neq (\text{ind } v). v\$b = 0$   
 by *metis*  
 hence  $\forall v \in \text{standard-basis}. \forall v' \in \text{standard-basis}.$   
 $\text{ind } v = \text{ind } v' \longrightarrow (\forall b. v\$b = v'\$b)$   
 by *metis*  
 hence *inj-ind*:  
 $\forall v \in \text{standard-basis}. \forall v' \in \text{standard-basis}.$   
 $\text{ind } v = \text{ind } v' \longrightarrow v = v'$   
 unfolding *vec-eq-iff*  
 by *blast*  
 hence *inj-on ind standard-basis*  
 unfolding *inj-on-def*  
 by *blast*  
 hence *bij-ind-std*: *bij-betw ind standard-basis (ind ` standard-basis)*  
 unfolding *bij-betw-def*  
 by *simp*  
 obtain  $\text{ind-inv} :: 'b \Rightarrow \text{real}^b$  where  
 $\text{char-vec}: \text{ind-inv} = (\lambda b. \chi i. \text{if } i = b \text{ then } 1 \text{ else } 0)$   
 by *blast*  
 hence *in-basis*:  $\forall b. \text{ind-inv } b \in \text{standard-basis}$   
 unfolding *standard-basis-def*  
 by *simp*  
 moreover from *this*  
 have *ind-inv-map*:  $\forall b. \text{ind } (\text{ind-inv } b) = b$   
 using *char-vec ind-eq-zero ind-eq-one axis-def axis-nth zero-neq-one*  
 by *metis*  
 ultimately have  $\forall b. \exists v. v \in \text{standard-basis} \wedge b = \text{ind } v$   
 by *metis*  
 hence *univ*:  $\text{ind ` standard-basis} = \text{UNIV}$   
 by *blast*  
 have *bij-inv*: *bij-betw ind-inv UNIV standard-basis*

**using** *ind-inv-map bij-ind-std bij-betw-byWitness*[*of - ind*] *in-basis inj-ind*  
**unfolding** *image-subset-iff*  
**by** *simp*  
**obtain**  $f :: \text{real}^b \Rightarrow \text{real}$  **where**  
*func*:  $f = (\lambda v. \text{if } v \in \text{standard-basis} \text{ then } x\$(\text{ind } v) \text{ else } 0)$   
**by** *blast*  
**hence**  $(\sum y \in \text{standard-basis}. f y) = (\sum v \in \text{standard-basis}. x\$(\text{ind } v))$   
**by** *simp*  
**also have**  $\dots = (\sum y \in \text{ind} \text{ `standard-basis}. x\$y)$   
**using** *bij-ind-std sum-comp*[*of ind - - (\$) x*]  
**by** *simp*  
**finally have** *sum-eq-one*:  $(\sum y \in \text{standard-basis}. f y) = 1$   
**using** *univ convex-comb*  
**by** *simp*  
**have** *nonneg*:  $\forall v \in \text{standard-basis}. f v \geq 0$   
**using** *func convex-comb*  
**by** *simp*  
**have**  $\forall v \in \text{standard-basis}. (\chi i. x\$(\text{ind } v) * v\$i)$   
 $= (\chi i. \text{if } i = \text{ind } v \text{ then } x\$(\text{ind } v) \text{ else } 0)$   
**using** *ind-eq-one ind-eq-zero*  
**by** *fastforce*  
**hence**  
 $\forall v \in \text{standard-basis}. x\$(\text{ind } v) *_R v = (\chi i. \text{if } i = \text{ind } v \text{ then } x\$(\text{ind } v) \text{ else } 0)$   
**unfolding** *scaleR-vec-def*  
**by** *simp*  
**moreover have**  $(\sum x \in \text{standard-basis}. f x *_R x) =$   
 $(\sum v \in \text{standard-basis}. x\$(\text{ind } v) *_R v)$   
**unfolding** *func*  
**by** *simp*  
**ultimately have**  $(\sum x \in \text{standard-basis}. f x *_R x)$   
 $= (\sum v \in \text{standard-basis}. \chi i. \text{if } i = \text{ind } v \text{ then } x\$(\text{ind } v) \text{ else } 0)$   
**by** *force*  
**also have**  $\dots = (\sum b \in \text{UNIV}. \chi i. \text{if } i = \text{ind } (\text{ind-inv } b) \text{ then } x\$(\text{ind } (\text{ind-inv } b)) \text{ else } 0)$   
**using** *bij-inv sum-comp*  
**unfolding** *comp-def*  
**by** *blast*  
**also have**  $\dots = (\sum b \in \text{UNIV}. \chi i. \text{if } i = b \text{ then } x\$b \text{ else } 0)$   
**using** *ind-inv-map*  
**by** *presburger*  
**finally have**  $(\sum x \in \text{standard-basis}. f x *_R x) =$   
 $(\sum b \in \text{UNIV}. \chi i. \text{if } i = b \text{ then } x\$b \text{ else } 0)$   
**by** *simp*  
**hence**  $(\sum x \in \text{standard-basis}. f x *_R x) = x$   
**unfolding** *vec-eq-iff*  
**by** *simp*  
**hence**  $\exists f :: \text{real}^b \Rightarrow \text{real}.$   
 $(\sum y \in \text{standard-basis}. f y) = 1 \wedge (\forall x \in \text{standard-basis}. f x \geq 0)$

```

       $\wedge x = (\sum x \in \text{standard-basis}. f x *_R x)$ 
    using sum-eq-one nonneg
  by blast
thus  $x \in \bigcap \{t. (\forall x \in t. \forall y \in t. \forall u \geq 0. \forall v \geq 0. \\
u + v = 1 \longrightarrow u *_R x + v *_R y \in t) \\
\wedge (\text{standard-basis} :: (\text{real}^b \text{ set}) \subseteq t)\}$ 
  using convex-combination-in-convex-hull
  unfolding convex-def hull-def
  by blast
qed
qed

lemma fract-distr-helper:
  fixes  $a b c :: \text{int}$ 
  assumes  $c \neq 0$ 
  shows  $\text{Fract } a c + \text{Fract } b c = \text{Fract } (a + b) c$ 
  using add-rat assms mult.commute mult-rat-cancel distrib-right
  by metis

lemma anonymity-homogeneity-is-equivalence:
  fixes  $X :: ('a, 'v) \text{ Election set}$ 
  assumes  $\forall E \in X. \text{finite } (\text{voters-}\mathcal{E} E)$ 
  shows  $\text{equiv } X (\text{anonymity-homogeneity}_{\mathcal{R}} X)$ 
proof (unfold equiv-def, safe)
  show  $\text{refl-on } X (\text{anonymity-homogeneity}_{\mathcal{R}} X)$ 
    unfolding refl-on-def anonymity-homogeneity $_{\mathcal{R}}$ .simps
    by blast
next
  show  $\text{sym } (\text{anonymity-homogeneity}_{\mathcal{R}} X)$ 
    unfolding sym-def anonymity-homogeneity $_{\mathcal{R}}$ .simps
    using sup-commute
    by simp
next
  show  $\text{Relation.trans } (\text{anonymity-homogeneity}_{\mathcal{R}} X)$ 
proof
  fix  $E E' F :: ('a, 'v) \text{ Election}$ 
  assume
     $\text{rel}: (E, E') \in \text{anonymity-homogeneity}_{\mathcal{R}} X$  and
     $\text{rel}': (E', F) \in \text{anonymity-homogeneity}_{\mathcal{R}} X$ 
  hence  $\text{finite } (\text{voters-}\mathcal{E} E')$ 
    unfolding anonymity-homogeneity $_{\mathcal{R}}$ .simps
    using assms
    by fastforce
  from rel rel' have eq-frac:
     $(\forall r. \text{vote-fraction } r E = \text{vote-fraction } r E') \wedge$ 
     $(\forall r. \text{vote-fraction } r E' = \text{vote-fraction } r F)$ 
    unfolding anonymity-homogeneity $_{\mathcal{R}}$ .simps
    by blast
  hence  $\forall r. \text{vote-fraction } r E = \text{vote-fraction } r F$ 

```

```

    by metis
  thus  $(E, F) \in \text{anonymity-homogeneity}_{\mathcal{R}} X$ 
    using rel rel' snd-conv
    unfolding anonymity-homogeneity $_{\mathcal{R}}$ .simps
    by blast
qed
qed

lemma fract-distr:
  fixes
     $A :: 'x \text{ set}$  and
     $f :: 'x \Rightarrow \text{int}$  and
     $b :: \text{int}$ 
  assumes
    finite  $A$  and
     $b \neq 0$ 
  shows  $(\sum a \in A. \text{Fract } (f a) b) = \text{Fract } (\sum x \in A. f x) b$ 
  using assms
proof (induction card  $A$  arbitrary:  $A f b$ )
  case 0
  fix
     $A :: 'x \text{ set}$  and
     $f :: 'x \Rightarrow \text{int}$  and
     $b :: \text{int}$ 
  assume
     $0 = \text{card } A$  and
    finite  $A$  and
     $b \neq 0$ 
  hence  $(\sum a \in A. \text{Fract } (f a) b) = 0 \wedge (\sum y \in A. f y) = 0$ 
    by simp
  thus ?case
    using 0 rat-number-collapse
    by simp
next
  case (Suc  $n$ )
  fix
     $A :: 'x \text{ set}$  and
     $f :: 'x \Rightarrow \text{int}$  and
     $b :: \text{int}$  and
     $n :: \text{nat}$ 
  assume
    card-A:  $\text{Suc } n = \text{card } A$  and
    fin-A: finite  $A$  and
    b-non-zero:  $b \neq 0$  and
    hyp:  $\bigwedge A f b.$ 
       $n = \text{card } (A :: 'x \text{ set}) \implies$ 
      finite  $A \implies b \neq 0 \implies (\sum a \in A. \text{Fract } (f a) b) = \text{Fract } (\sum x \in A. f$ 
 $x) b$ 
  hence  $A \neq \{\}$ 

```



```

    by auto
  then obtain  $c :: 'x$  where
     $c \text{-in-} A: c \in A$ 
    by blast
  hence  $(\sum a \in A. \text{Fract } (f a) b) =$ 
     $(\sum a \in A - \{c\}. \text{Fract } (f a) b) + \text{Fract } (f c) b$ 
    using  $\text{fin-}A$ 
    by ( $\text{simp add: sum-diff1}$ )
  also have  $\dots = \text{Fract } (\sum x \in A - \{c\}. f x) b + \text{Fract } (f c) b$ 
    using  $\text{hyp card-}A \text{ fin-}A \text{ b-non-zero c-in-}A \text{ Diff-empty card-Diff-singleton}$ 
     $\text{diff-Suc-1 finite-Diff-insert}$ 
    by  $\text{metis}$ 
  also have  $\dots = \text{Fract } (\sum x \in A. f x) b$ 
    using  $\text{c-in-}A \text{ fin-}A \text{ b-non-zero fract-distr-helper}$ 
    by ( $\text{simp add: sum-diff1}$ )
  finally show  $(\sum a \in A. \text{Fract } (f a) b) = \text{Fract } (\sum x \in A. f x) b$ 
    by blast
qed

```

## Simplex Bijection

We assume all our elections to consist of a fixed finite set of  $n$  alternatives and finite subsets of an infinite universe of voters. Profiles are linear orders on the alternatives. Then we can work on the standard simplex of dimension  $n!$  instead of the equivalence classes of the equivalence relation for anonymous and homogeneous voting rules: Each dimension corresponds to one possible linear order on the alternative set, i.e., the possible preferences. Each equivalence class of elections corresponds to a vector whose entries denote the fraction of voters per election in that class who vote the respective corresponding preference.

**theorem** *anonymity-homogeneity<sub>Q</sub>-isomorphism:*

**assumes** *infinite* ( $UNIV :: 'v \text{ set}$ )

**shows**

$\text{bij-betw } (\text{anonymity-homogeneity-class} :: ('a :: \text{finite}, 'v) \text{ Election set} \Rightarrow$   
 $\text{rat}^{\sim} a \text{ Ordered-Preference}) (\text{anonymity-homogeneity}_{\mathcal{Q}} (UNIV :: 'a \text{ set}))$   
 $(\text{vote-simplex} :: (\text{rat}^{\sim} a \text{ Ordered-Preference}) \text{ set})$

**proof** ( $\text{unfold bij-betw-def inj-on-def, intro conjI ballI impI}$ )

**fix**  $X Y :: ('a, 'v) \text{ Election set}$

**assume**

$\text{class-}X: X \in \text{anonymity-homogeneity}_{\mathcal{Q}} UNIV$  **and**

$\text{class-}Y: Y \in \text{anonymity-homogeneity}_{\mathcal{Q}} UNIV$

**moreover have** *equiv:*

$\text{equiv } (\text{elections-}\mathcal{A} UNIV) (\text{anonymity-homogeneity}_{\mathcal{R}} (\text{elections-}\mathcal{A} UNIV))$

**using** *anonymity-homogeneity-is-equivalence CollectD IntD1 inf-commute*

**unfolding** *elections-}\mathcal{A}.simps*

**by** (*metis (no-types, lifting)*)

**ultimately have** *subset:*

$X \neq \{\} \wedge X \subseteq \text{elections-}\mathcal{A} UNIV \wedge Y \neq \{\} \wedge Y \subseteq \text{elections-}\mathcal{A} UNIV$

```

using in-quotient-imp-non-empty in-quotient-imp-subset
unfolding anonymity-homogeneityQ.simps
by blast
then obtain  $E\ E' :: ('a, 'v)\ Election$  where
   $E\text{-in-}X: E \in X$  and
   $E'\text{-in-}Y: E' \in Y$ 
by blast
hence class-X-E: anonymity-homogeneityR (elections-A UNIV) “ {E} = X
  using class-X equiv Image-singleton-iff equiv-class-eq quotientE
  unfolding anonymity-homogeneityQ.simps
  by (metis (no-types, opaque-lifting))
hence  $\forall\ F :: ('a, 'v)\ Election \in X. \forall\ p :: 'a\ Preference\text{-}Relation.$ 
   $vote\text{-fraction}\ p\ F = vote\text{-fraction}\ p\ E$ 
  unfolding anonymity-homogeneityR.simps
  by fastforce
hence  $\forall\ p :: 'a\ Preference\text{-}Relation.$ 
   $vote\text{-fraction}\ p\ `X = \{vote\text{-fraction}\ p\ E\}$ 
  using E-in-X
  by blast
hence  $\forall\ p :: 'a\ Preference\text{-}Relation.$ 
   $vote\text{-fraction}_Q\ p\ X = vote\text{-fraction}\ p\ E$ 
  using is-singletonI singleton-set-def-if-card-one the-elem-eq
  unfolding is-singleton-altdef vote-fractionQ.simps  $\pi_Q$ .simps singleton-set.simps
  by metis
hence  $\forall\ p :: 'a\ Ordered\text{-}Preference.$ 
   $(anonymity\text{-}homogeneity\text{-}class\ X)\$p = vote\text{-fraction}\ (ord2pref\ p)\ E$ 
  unfolding anonymity-homogeneity-class.simps
  using vec-lambda-beta
  by metis
moreover assume
   $anonymity\text{-}homogeneity\text{-}class\ X = anonymity\text{-}homogeneity\text{-}class\ Y$ 
moreover have class-Y-E': anonymity-homogeneityR (elections-A UNIV) “ {E'} = Y
  using class-Y equiv E'-in-Y Image-singleton-iff equiv-class-eq quotientE
  unfolding anonymity-homogeneityQ.simps
  by (metis (no-types, opaque-lifting))
hence  $\forall\ F :: ('a, 'v)\ Election \in Y. \forall\ p :: 'a\ Preference\text{-}Relation.$ 
   $vote\text{-fraction}\ p\ E' = vote\text{-fraction}\ p\ F$ 
  unfolding anonymity-homogeneityR.simps
  by blast
hence  $\forall\ p :: 'a\ Preference\text{-}Relation.$ 
   $vote\text{-fraction}\ p\ `Y = \{vote\text{-fraction}\ p\ E'\}$ 
  using E'-in-Y
  by fastforce
hence  $\forall\ p :: 'a\ Preference\text{-}Relation. vote\text{-fraction}_Q\ p\ Y = vote\text{-fraction}\ p\ E'$ 
  using is-singletonI singleton-set-def-if-card-one the-elem-eq
  unfolding is-singleton-altdef vote-fractionQ.simps  $\pi_Q$ .simps singleton-set.simps
  by metis
hence eq-Y-E':

```

$\forall p :: 'a \text{ Ordered-Preference.}$   
 $(\text{anonymity-homogeneity-class } Y) \$ p = \text{vote-fraction } (\text{ord2pref } p) E'$   
**unfolding** *anonymity-homogeneity-class.simps*  
**using** *vec-lambda-beta*  
**by** *metis*  
**ultimately have**  $\forall p :: 'a \text{ Preference-Relation.}$   
 $\text{linear-order } p \longrightarrow \text{vote-fraction } p E = \text{vote-fraction } p E'$   
**using** *mem-Collect-eq pref2ord-inverse*  
**by** *metis*  
**moreover have**  
 $(\forall v :: 'v. v \in \text{voters-}\mathcal{E} E \longrightarrow \text{linear-order } (\text{profile-}\mathcal{E} E v)) \wedge$   
 $(\forall v :: 'v. v \in \text{voters-}\mathcal{E} E' \longrightarrow \text{linear-order } (\text{profile-}\mathcal{E} E' v))$   
**using** *subset E-in-X E'-in-Y*  
**unfolding** *elections- $\mathcal{A}$ .simps well-formed-elections-def profile-def*  
**by** *fastforce*  
**hence**  $\forall p :: 'a \text{ Preference-Relation.}$   
 $\neg \text{linear-order } p \longrightarrow \text{vote-count } p E = 0 \wedge \text{vote-count } p E' = 0$   
**unfolding** *vote-count.simps*  
**using** *card.infinite card-0-eq Collect-empty-eq*  
**by** *(metis (mono-tags, lifting))*  
**hence**  $\forall p :: 'a \text{ Preference-Relation.}$   
 $\neg \text{linear-order } p \longrightarrow \text{vote-fraction } p E = 0 \wedge \text{vote-fraction } p E' = 0$   
**using** *int-ops rat-number-collapse*  
**by** *simp*  
**ultimately have**  $\forall p :: 'a \text{ Preference-Relation.}$   
 $\text{vote-fraction } p E = \text{vote-fraction } p E'$   
**by** *metis*  
**hence**  $(E, E') \in \text{anonymity-homogeneity}_{\mathcal{R}} (\text{elections-}\mathcal{A} \text{ UNIV})$   
**using** *subset E-in-X E'-in-Y elections- $\mathcal{A}$ .simps*  
**unfolding** *anonymity-homogeneity $_{\mathcal{R}}$ .simps*  
**by** *blast*  
**thus**  $X = Y$   
**using** *class-X-E class-Y-E' equiv equiv-class-eq*  
**by** *(metis (no-types, lifting))*  
**next**  
**show**  $(\text{anonymity-homogeneity-class} :: ('a, 'v) \text{ Election set}$   
 $\Rightarrow \text{rat}^{\sim} 'a \text{ Ordered-Preference})$   
 $\text{'anonymity-homogeneity}_{\mathcal{Q}} \text{ UNIV} = \text{vote-simplex}$   
**proof** *(unfold vote-simplex-def, safe)*  
**fix**  $X :: ('a, 'v) \text{ Election set}$   
**assume**  $X \in \text{anonymity-homogeneity}_{\mathcal{Q}} \text{ UNIV}$   
**moreover have**  $\text{equiv } (\text{elections-}\mathcal{A} \text{ UNIV}) (\text{anonymity-homogeneity}_{\mathcal{R}} (\text{elections-}\mathcal{A} \text{ UNIV}))$   
**using** *anonymity-homogeneity-is-equivalence elections- $\mathcal{A}$ .simps*  
**by** *blast*  
**ultimately obtain**  $E :: ('a, 'v) \text{ Election where}$   
 $E \text{-in-} X: E \in X$  **and**  
 $\text{rel: } \forall E' \in X. (E, E') \in \text{anonymity-homogeneity}_{\mathcal{R}} (\text{elections-}\mathcal{A} \text{ UNIV})$   
**using** *anonymity-homogeneity $_{\mathcal{Q}}$ .simps equiv-Eps-in proj-Eps*

**unfolding** *proj-def*  
**by** *blast*  
**hence**  $\forall p :: 'a \text{ Ordered-Preference. } \forall E' \in X.$   
 $\text{vote-fraction } (\text{ord2pref } p) E' = \text{vote-fraction } (\text{ord2pref } p) E$   
**unfolding** *anonymity-homogeneity $\mathcal{R}$ .simps*  
**by** *fastforce*  
**hence**  $\forall p :: 'a \text{ Ordered-Preference.}$   
 $\text{vote-fraction } (\text{ord2pref } p) \text{ ` } X = \{\text{vote-fraction } (\text{ord2pref } p) E\}$   
**using** *E-in-X*  
**by** *blast*  
**hence** *repr:*  $\forall p :: 'a \text{ Ordered-Preference.}$   
 $\text{vote-fraction}_{\mathcal{Q}} (\text{ord2pref } p) X = \text{vote-fraction } (\text{ord2pref } p) E$   
**using** *is-singletonI singleton-set-def-if-card-one the-elem-eq*  
**unfolding** *vote-fraction $\mathcal{Q}$ .simps  $\pi_{\mathcal{Q}}$ .simps is-singleton-altdef*  
**by** *metis*  
**hence**  $\forall p :: 'a \text{ Ordered-Preference. } \text{vote-fraction}_{\mathcal{Q}} (\text{ord2pref } p) X \geq 0$   
**using** *zero-le-Fract-iff Orderings.order-eq-iff card-eq-0-iff*  
 $\text{of-nat-le-0-iff of-nat-less-0-iff linorder-not-less}$   
**unfolding** *vote-fraction.simps card-gt-0-iff*  
**by** *metis*  
**hence** *geq-zero:*  $\forall p :: 'a \text{ Ordered-Preference.}$   
 $\text{real-of-rat } (\text{vote-fraction}_{\mathcal{Q}} (\text{ord2pref } p) X) \geq 0$   
**using** *zero-le-of-rat-iff*  
**by** *blast*  
**have** *zero-case:*  
 $\text{voters-}\mathcal{E} E = \{\} \vee \text{infinite } (\text{voters-}\mathcal{E} E) \longrightarrow$   
 $(\chi p :: 'a \text{ Ordered-Preference.}$   
 $\text{real-of-rat } (\text{vote-fraction}_{\mathcal{Q}} (\text{ord2pref } p) X)) = 0$   
**using** *repr*  
**unfolding** *zero-vec-def*  
**by** *simp*  
**let**  $?vote\text{-sum} = (\sum r :: 'a \text{ Preference-Relation} \in UNIV. \text{vote-count } r E)$   
**have** *finite*  $(UNIV :: 'a \text{ Preference-Relation})$   
**by** *simp*  
**hence** *eq-card:*  $\text{finite } (\text{voters-}\mathcal{E} E) \longrightarrow \text{card } (\text{voters-}\mathcal{E} E) = ?vote\text{-sum}$   
**using** *vote-count-sum*  
**by** *metis*  
**hence** *finite*  $(\text{voters-}\mathcal{E} E) \wedge \text{voters-}\mathcal{E} E \neq \{\} \longrightarrow$   
 $(\sum r :: 'a \text{ Preference-Relation} \in UNIV. \text{vote-fraction } r E) =$   
 $(\sum r :: 'a \text{ Preference-Relation} \in UNIV. \text{Fract } (\text{vote-count } r E) ?vote\text{-sum})$   
**unfolding** *vote-fraction.simps*  
**by** *presburger*  
**moreover** **have** *fin-imp-sum-gt-zero:*  
 $\text{finite } (\text{voters-}\mathcal{E} E) \wedge \text{voters-}\mathcal{E} E \neq \{\} \longrightarrow ?vote\text{-sum} > 0$   
**by** *fastforce*  
**hence** *finite*  $(\text{voters-}\mathcal{E} E) \wedge \text{voters-}\mathcal{E} E \neq \{\} \longrightarrow$   
 $(\sum r :: 'a \text{ Preference-Relation} \in UNIV.$   
 $\text{Fract } (\text{vote-count } r E) ?vote\text{-sum}) = \text{Fract } ?vote\text{-sum } ?vote\text{-sum}$   
**using** *fract-distr[of UNIV ?vote-sum] card-0-eq eq-card of-nat-eq-0-iff*

$\text{finite-class}.\text{finite-UNIV of-nat-sum sum.cong}$   
 by (metis (no-types, lifting))  
 moreover have  
 $\text{finite (voters-}\mathcal{E} E) \wedge \text{voters-}\mathcal{E} E \neq \{\} \longrightarrow \text{Fract ?vote-sum ?vote-sum} = 1$   
 using fin-imp-sum-gt-zero Fract-le-one-iff Fract-less-one-iff  
 of-nat-0-less-iff order-le-less order-less-irrefl  
 by metis  
 ultimately have fin-imp-sum-eq-one:  
 $\text{finite (voters-}\mathcal{E} E) \wedge \text{voters-}\mathcal{E} E \neq \{\} \longrightarrow$   
 $(\sum r :: 'a \text{ Preference-Relation} \in \text{UNIV}. \text{vote-fraction } r E) = 1$   
 by presburger  
 have  $\forall r :: 'a \text{ Preference-Relation}. \neg \text{linear-order } r \longrightarrow \text{vote-count } r E = 0$   
 using E-in-X rel  
 unfolding elections-A.simps well-formed-elections-def profile-def  
 by fastforce  
 hence  $\forall r :: 'a \text{ Preference-Relation}. \neg \text{linear-order } r \longrightarrow \text{vote-fraction } r E = 0$   
 using rat-number-collapse  
 by simp  
 moreover have  $(\sum r :: 'a \text{ Preference-Relation} \in \text{UNIV}. \text{vote-fraction } r E) =$   
 $(\sum r :: 'a \text{ Preference-Relation} \in \{s :: 'a \text{ Preference-Relation}. \text{linear-order } s\}.$   
 $\text{vote-fraction } r E) +$   
 $(\sum r :: 'a \text{ Preference-Relation}$   
 $\in \text{UNIV} - \{s :: 'a \text{ Preference-Relation}. \text{linear-order } s\}.$   
 $\text{vote-fraction } r E)$   
 using finite CollectD Collect-mono UNIV-I add commute  
 sum.subset-diff top-set-def  
 by metis  
 ultimately have  $(\sum r :: 'a \text{ Preference-Relation} \in \text{UNIV}. \text{vote-fraction } r E)$   
 $=$   
 $(\sum r :: 'a \text{ rel} \in \{s :: 'a \text{ Preference-Relation}. \text{linear-order } s\}. \text{vote-fraction } r$   
 $E)$   
 by simp  
 moreover have bij-betw ord2pref UNIV  $\{r :: 'a \text{ Preference-Relation}. \text{lin-}$   
 $\text{ear-order } r\}$   
 using inj-def ord2pref-inject range-ord2pref  
 unfolding bij-betw-def  
 by blast  
 ultimately have  
 $(\sum r :: 'a \text{ Preference-Relation} \in \text{UNIV}. \text{vote-fraction } r E) =$   
 $(\sum r :: 'a \text{ Ordered-Preference} \in \text{UNIV}. \text{vote-fraction (ord2pref } r) E)$   
 using sum-comp  
 by simp  
 hence finite (voters- $\mathcal{E}$  E)  $\wedge \text{voters-}\mathcal{E} E \neq \{\} \longrightarrow$   
 $(\sum p :: 'a \text{ Ordered-Preference} \in \text{UNIV}.$   
 $\text{real-of-rat (vote-fraction (ord2pref } p) E)) = 1$   
 using fin-imp-sum-eq-one of-rat-1 of-rat-sum  
 by metis  
 hence  $(\chi p :: 'a \text{ Ordered-Preference}. \text{real-of-rat (vote-fraction}_{\mathcal{Q}} (\text{ord2pref } p)$   
 $X)) = 0$

$\vee ((\forall p :: 'a \text{ Ordered-Preference. } (\chi q :: 'a \text{ Ordered-Preference.}$   
 $\text{real-of-rat } (\text{vote-fraction}_{\mathbb{Q}} (\text{ord2pref } q) X))\$p \geq 0)$   
 $\wedge (\sum p :: 'a \text{ Ordered-Preference} \in \text{UNIV.}$   
 $(\chi q. \text{real-of-rat } (\text{vote-fraction}_{\mathbb{Q}} (\text{ord2pref } q) X))\$p = 1)$   
**using** *zero-case repr geq-zero*  
**by** *force*  
**moreover have**  
 $\forall p :: 'a \text{ Ordered-Preference.}$   
 $(\chi q :: 'a \text{ Ordered-Preference.}$   
 $\text{real-of-rat } (\text{vote-fraction}_{\mathbb{Q}} (\text{ord2pref } q) X))\$p \in \mathbb{Q}$   
**by** *simp*  
**ultimately have** *simplex-el:*  
 $(\chi p :: 'a \text{ Ordered-Preference. } \text{real-of-rat } (\text{vote-fraction}_{\mathbb{Q}} (\text{ord2pref } p) X))$   
 $\in \{x \in \text{insert } 0 (\text{convex hull standard-basis}).$   
 $\forall p :: 'a \text{ Ordered-Preference. } x\$p \in \mathbb{Q}\}$   
**using** *standard-simplex-rewrite*  
**by** *blast*  
**moreover have**  
 $\forall p :: 'a \text{ Ordered-Preference.}$   
 $(\text{rat-vector } (\chi q :: 'a \text{ Ordered-Preference.}$   
 $\text{of-rat } (\text{vote-fraction}_{\mathbb{Q}} (\text{ord2pref } q) X))\$p =$   
 $\text{the-inv real-of-rat } ((\chi q :: 'a \text{ Ordered-Preference.}$   
 $\text{real-of-rat } (\text{vote-fraction}_{\mathbb{Q}} (\text{ord2pref } q) X))\$p)$   
**unfolding** *rat-vector.simps*  
**using** *vec-lambda-beta*  
**by** *blast*  
**moreover have**  
 $\forall p :: 'a \text{ Ordered-Preference. } \text{the-inv real-of-rat}$   
 $((\chi q :: 'a \text{ Ordered-Preference.}$   
 $\text{real-of-rat } (\text{vote-fraction}_{\mathbb{Q}} (\text{ord2pref } q) X))\$p) =$   
 $\text{the-inv real-of-rat } (\text{real-of-rat } (\text{vote-fraction}_{\mathbb{Q}} (\text{ord2pref } p) X))$   
**by** *simp*  
**moreover have** *inv-of-rat:*  
 $\forall x :: \text{rat} \in \mathbb{Q}. \text{the-inv of-rat } (\text{of-rat } x) = x$   
**using** *the-inv-f-f injI of-rat-eq-iff*  
**by** *metis*  
**hence**  $\forall p :: 'a \text{ Ordered-Preference.}$   
 $\text{the-inv real-of-rat } (\text{real-of-rat } (\text{vote-fraction}_{\mathbb{Q}} (\text{ord2pref } p) X)) =$   
 $\text{vote-fraction}_{\mathbb{Q}} (\text{ord2pref } p) X$   
**using** *Rats-eq-range-nat-to-rat-surj surj-nat-to-rat-surj*  
**by** *blast*  
**moreover have**  
 $\forall p :: 'a \text{ Ordered-Preference.}$   
 $\text{vote-fraction}_{\mathbb{Q}} (\text{ord2pref } p) X = (\text{anonymity-homogeneity-class } X)\$p$   
**by** *simp*  
**ultimately have**  
 $\forall p :: 'a \text{ Ordered-Preference.}$   
 $(\text{rat-vector } (\chi q :: 'a \text{ Ordered-Preference.}$   
 $\text{of-rat } (\text{vote-fraction}_{\mathbb{Q}} (\text{ord2pref } q) X))\$p =$

```

(anonymity-homogeneity-class X)$p
by metis
hence rat-vector
(χ p :: 'a Ordered-Preference. of-rat (vote-fraction_Q (ord2pref p) X)) =
anonymity-homogeneity-class X
by simp
hence ∃ x :: (real, 'a Ordered-Preference) vec
∈ {y :: (real, 'a Ordered-Preference) vec
∈ insert 0 (convex hull standard-basis). ∀ p :: 'a Ordered-Preference.
y$p ∈ Q}.
rat-vector x = anonymity-homogeneity-class X
using simplex-el
by blast
moreover assume
anonymity-homogeneity-class X ∉ rat-vector-set (convex hull standard-basis)
ultimately have rat-vector 0 = anonymity-homogeneity-class X
using image-iff insertE mem-Collect-eq
unfolding rat-vector-set.simps
by (metis (mono-tags, lifting))
thus anonymity-homogeneity-class X = 0
unfolding rat-vector.simps
using Rats-0 inv-of-rat of-rat-0 vec-lambda-unique zero-index
by (metis (no-types, lifting))
next
have all-zero:
∀ r :: 'a Preference-Relation.
∀ (E :: ('a, 'c) Election)
∈ (anonymity-homogeneity_R (elections-A UNIV)) “ {(UNIV, {}, (λ v ::
'c. {}))}.
vote-fraction r E = 0
unfolding Image-def anonymity-homogeneity_R.simps
by fastforce
moreover have (UNIV, {}, λ v :: 'c. {})
∈ (anonymity-homogeneity_R (elections-A UNIV)) “ {(UNIV, {}, λ v :: 'c.
{}))}
unfolding elections-A.simps well-formed-elections-def profile-def
by simp
ultimately have
∀ r :: 'a Preference-Relation. 0 ∈ vote-fraction r
“ (anonymity-homogeneity_R (elections-A UNIV))
“ {(UNIV, {}, (λ v :: 'c. {}))}
using image-eqI
by (metis (mono-tags, lifting))
hence
∀ r :: 'a Preference-Relation. vote-fraction r
“ (anonymity-homogeneity_R (elections-A UNIV))
“ {(UNIV, {}, λ v :: 'c. {}))} = {0}
using all-zero
by blast

```

**hence**  $\forall r :: 'a \text{ Ordered-Preference. } \text{vote-fraction}_{\mathcal{Q}} (\text{ord2pref } r)$   
 $(\text{anonymity-homogeneity}_{\mathcal{R}} (\text{elections-}\mathcal{A} \text{ UNIV})$   
 $\quad \text{"}\{(UNIV, \{\}, \lambda v :: 'c. \{\})\}) = 0$   
**using** *is-singletonI singleton-insert-inj-eq' singleton-set-def-if-card-one*  
**unfolding**  $\text{vote-fraction}_{\mathcal{Q}}.\text{simps } \pi_{\mathcal{Q}}.\text{simps is-singleton-altdef}$   
**by** *metis*  
**hence**  $\forall r :: 'a \text{ Ordered-Preference.}$   
 $(\text{anonymity-homogeneity-class } (\text{anonymity-homogeneity}_{\mathcal{R}} (\text{elections-}\mathcal{A} \text{ UNIV})$   
 $\quad \text{"}\{(UNIV, \{\}, \lambda v :: 'c. \{\})\}))\$r = 0$   
**unfolding**  $\text{anonymity-homogeneity-class.simps}$   
**using** *vec-lambda-beta*  
**by**  $(\text{metis } (\text{no-types}))$   
**moreover have**  $\forall r :: 'a \text{ Ordered-Preference. } 0\$r = 0$   
**by** *simp*  
**ultimately have**  $\text{anonymity-homogeneity-class}$   
 $(\text{anonymity-homogeneity}_{\mathcal{R}} (\text{elections-}\mathcal{A} \text{ UNIV})$   
 $\quad \text{"}\{(UNIV, \{\}, \lambda v :: 'c. \{\})\}) = (0 :: \text{rat}^a \text{ Ordered-Preference})$   
**using** *vec-eq-iff*  
**by**  $(\text{metis } (\text{no-types}))$   
**moreover have**  
 $(UNIV, \{\}, \lambda v :: 'c. \{\}) \in \text{elections-}\mathcal{A} \text{ UNIV}$   
**unfolding**  $\text{elections-}\mathcal{A}.\text{simps well-formed-elections-def profile-def}$   
**by** *simp*  
**hence**  $(\text{anonymity-homogeneity}_{\mathcal{R}} (\text{elections-}\mathcal{A} \text{ UNIV}) \text{"}\{(UNIV, \{\}, \lambda v :: 'c.$   
 $\{\})\})$   
 $\quad \in \text{anonymity-homogeneity}_{\mathcal{Q}} \text{ UNIV}$   
**unfolding**  $\text{anonymity-homogeneity}_{\mathcal{Q}}.\text{simps quotient-def}$   
**by** *blast*  
**ultimately show**  $0 \in \text{anonymity-homogeneity-class 'anonymity-homogeneity}_{\mathcal{Q}}$   
 $\text{UNIV}$   
**using** *image-eqI*  
**by**  $(\text{metis } (\text{no-types}))$   
**next**  
**fix**  $x :: \text{rat}^a \text{ Ordered-Preference}$   
**assume**  $x \in \text{rat-vector-set } (\text{convex hull standard-basis})$   
— The following converts a rational vector  $x$  to real vector  $x'$ .  
**then obtain**  $x' :: \text{real}^a \text{ Ordered-Preference where}$   
 $\text{conv: } (\forall p :: 'a \text{ Ordered-Preference. } 0 \leq x'\$p)$   
 $\quad \wedge (\sum p :: 'a \text{ Ordered-Preference} \in \text{UNIV. } x'\$p) = 1 \text{ and}$   
 $\text{rat-inv: } \forall p :: 'a \text{ Ordered-Preference.}$   
 $\quad x\$p = \text{the-inv real-of-rat } (x'\$p) \wedge x'\$p \in \mathbb{Q}$   
**unfolding**  $\text{rat-vector-set.simps rat-vector.simps}$   
**using** *standard-simplex-rewrite*  
**by** *fastforce*  
**have**  $\forall p :: 'a \text{ Ordered-Preference. } \text{real-of-rat } (x\$p) = x'\$p$   
**using**  $\text{rat-inv f-the-inv-into-f inj-onCI of-rat-eq-iff}$   
**unfolding** *Rats-def*  
**by**  $(\text{metis } (\text{no-types}))$   
**moreover have**



$\forall p :: 'a \text{ Ordered-Preference}. \exists \text{ fract} :: \text{int} \times \text{int}.$   
 $\text{Fract } (\text{fst fract}) (\text{snd fract}) = x\$p \wedge 0 < \text{snd fract}$   
**using** *quotient-of-unique*  
**by** *metis*  
**then obtain**  $\text{fraction}' :: 'a \text{ Ordered-Preference} \Rightarrow (\text{int} \times \text{int})$  **where**  
 $\forall p :: 'a \text{ Ordered-Preference}.$   
 $x\$p = \text{Fract } (\text{fst } (\text{fraction}' p)) (\text{snd } (\text{fraction}' p))$  **and**  
 $\text{pos}': \forall p :: 'a \text{ Ordered-Preference}. 0 < \text{snd } (\text{fraction}' p)$   
**by** *metis*  
**ultimately have**  $\text{fract}'$ :  
 $\forall p :: 'a \text{ Ordered-Preference}. x'\$p = (\text{fst } (\text{fraction}' p)) / (\text{snd } (\text{fraction}' p))$   
**using** *div-by-0 divide-less-cancel of-int-0 of-int-pos of-rat-rat*  
**by** *metis*  
**hence**  $\forall p :: 'a \text{ Ordered-Preference}. (\text{fst } (\text{fraction}' p)) / (\text{snd } (\text{fraction}' p)) \geq 0$   
**using** *conv*  
**by** *fastforce*  
**hence**  $\forall p :: 'a \text{ Ordered-Preference}. \text{fst } (\text{fraction}' p) \in \mathbb{N} \wedge \text{snd } (\text{fraction}' p) \in$   
 $\mathbb{N}$   
**using** *pos' nonneg-int-cases of-nat-in-Nats not-less of-int-0-le-iff*  
*of-int-pos zero-le-divide-iff*  
**by** *metis*  
**hence**  $\forall p :: 'a \text{ Ordered-Preference}. \exists (n :: \text{nat}) (m :: \text{nat}).$   
 $\text{fst } (\text{fraction}' p) = n \wedge \text{snd } (\text{fraction}' p) = m$   
**using** *Nats-cases*  
**by** *metis*  
**hence**  $\forall p :: 'a \text{ Ordered-Preference}. \exists m :: \text{nat} \times \text{nat}.$   
 $\text{fst } (\text{fraction}' p) = \text{int } (\text{fst } m) \wedge \text{snd } (\text{fraction}' p) = \text{int } (\text{snd } m)$   
**by** *simp*  
**then obtain**  $\text{fraction} :: 'a \text{ Ordered-Preference} \Rightarrow (\text{nat} \times \text{nat})$  **where**  
 $\text{eq}: \forall p :: 'a \text{ Ordered-Preference}.$   
 $\text{fst } (\text{fraction}' p) = \text{int } (\text{fst } (\text{fraction } p))$   
 $\wedge \text{snd } (\text{fraction}' p) = \text{int } (\text{snd } (\text{fraction } p))$   
**by** *metis*  
**hence**  $\text{fract}$ :  
 $\forall p :: 'a \text{ Ordered-Preference}. x'\$p = (\text{fst } (\text{fraction } p)) / (\text{snd } (\text{fraction } p))$   
**using**  $\text{fract}'$   
**by** *simp*  
**hence**  $\text{pos}: \forall p :: 'a \text{ Ordered-Preference}. 0 < \text{snd } (\text{fraction } p)$   
**using**  $\text{eq pos}'$   
**by** *simp*  
**let**  $?prod = \prod p :: 'a \text{ Ordered-Preference} \in \text{UNIV}. \text{snd } (\text{fraction } p)$   
**have**  $\text{pos-prod}: ?prod > 0$   
**using** *pos*  
**by** *simp*  
**have**  $\forall p :: 'a \text{ Ordered-Preference}. ?prod \bmod (\text{snd } (\text{fraction } p)) = 0$   
**using** *finite UNIV-I mod-mod-trivial mod-prod-eq mod-self prod-zero*  
**by** *(metis (no-types, lifting))*  
**hence**  $\text{div}: \forall p :: 'a \text{ Ordered-Preference}.$   
 $(?prod \text{ div } (\text{snd } (\text{fraction } p))) * (\text{snd } (\text{fraction } p)) = ?prod$

```

using add.commute add-0 div-mult-mod-eq
by metis
obtain voter-amount :: 'a Ordered-Preference  $\Rightarrow$  nat where
  def-amount:
    voter-amount =
      ( $\lambda$  p :: 'a Ordered-Preference  $\in$  UNIV. (fst (fraction p)) * (?prod div (snd
(fraction p))))
    by blast
  let ?voter-sum =
    ( $\sum$  p :: 'a Ordered-Preference  $\in$  UNIV. (fst (fraction p)) * (?prod div (snd
(fraction p))))
  have rewrite-div:
     $\forall$  p :: 'a Ordered-Preference. ?prod div (snd (fraction p)) = ?prod / (snd
(fraction p))
    using div less-imp-of-nat-less nonzero-mult-div-cancel-right
      of-nat-less-0-iff of-nat-mult pos
    by metis
  hence ?voter-sum =
    ( $\sum$  p :: 'a Ordered-Preference  $\in$  UNIV. fst (fraction p) * (?prod / (snd
(fraction p))))
    using def-amount
    by simp
  hence ?voter-sum =
    ?prod * ( $\sum$  p :: 'a Ordered-Preference  $\in$  UNIV. fst (fraction p) / (snd (fraction
p)))
    using mult-of-nat-commute sum.cong times-divide-eq-right
      vector-space-over-itself.scale-sum-right
    by (metis (mono-tags, lifting))
  hence rewrite-sum: ?voter-sum = ?prod
    using fract conv mult-cancel-left1 of-nat-eq-iff sum.cong
    by (metis (mono-tags, lifting))
obtain V :: 'v set where
  fin-V: finite V and
  card-V-eq-sum: card V = ?voter-sum
  using assms infinite-arbitrarily-large
  by blast
then obtain part :: 'a Ordered-Preference  $\Rightarrow$  'v set where
  partition:  $V = \bigcup \{part\ p \mid p :: 'a\ Ordered-Preference.\ p \in UNIV\}$  and
  disjoint:  $\forall\ p\ p' :: 'a\ Ordered-Preference.$ 
     $p \neq p' \longrightarrow part\ p \cap part\ p' = \{\}$  and
  card:  $\forall\ p :: 'a\ Ordered-Preference.\ card\ (part\ p) = voter-amount\ p$ 
  using def-amount obtain-partition[of V UNIV voter-amount]
  by auto
hence exactly-one-prof:  $\forall\ v :: 'v \in V.\ \exists!p.\ v \in part\ p$ 
  by blast
then obtain prof' :: 'v  $\Rightarrow$  'a Ordered-Preference where
   $\forall\ v :: 'v \in V.\ v \in part\ (prof'\ v)$ 
  by metis
hence  $\forall\ p :: 'a\ Ordered-Preference.\ \{v :: 'v \in V.\ prof'\ v = p\} = part\ p$ 

```

using *partition exactly-one-prof*  
 by *blast*  
 hence  $\forall p :: 'a \text{ Ordered-Preference.}$   
      $\text{card } \{v :: 'v \in V. \text{prof}' v = p\} = \text{voter-amount } p$   
 using *card*  
 by *presburger*  
 moreover obtain  $\text{prof} :: 'v \Rightarrow 'a \text{ Preference-Relation}$  where  
      $\text{prof}: \text{prof} = (\lambda v :: 'v. \text{if } v \in V \text{ then } \text{ord2pref } (\text{prof}' v) \text{ else } \{\})$   
 by *blast*  
 hence  
      $\forall p :: 'a \text{ Ordered-Preference. } \forall v :: 'v.$   
      $(v \in \{v \in V. \text{prof}' v = p\}) = (v \in \{v \in V. \text{prof } v = \text{ord2pref } p\})$   
 by *(simp add: ord2pref-inject)*  
 ultimately have  
      $\forall p :: 'a \text{ Ordered-Preference.}$   
      $\text{vote-fraction } (\text{ord2pref } p) (\text{UNIV}, V, \text{prof}) = \text{Fract } (\text{voter-amount } p) (\text{card } V)$   
 using *rat-number-collapse fin-V*  
 by *simp*  
 moreover have  
      $\forall p. \text{Fract } (\text{voter-amount } p) (\text{card } V) = (\text{voter-amount } p) / (\text{card } V)$   
 unfolding *Fract-of-int-quotient of-rat-divide*  
 by *simp*  
 moreover have  
      $\forall p. (\text{voter-amount } p) / (\text{card } V) = \text{fst } (\text{fraction } p) / \text{snd } (\text{fraction } p)$   
 using *rewrite-div pos-prod def-amount card-V-eq-sum rewrite-sum*  
 by *auto*  
 — The following are the percentages of voters voting for each linearly ordered profile in  $(\text{UNIV}, V, \text{prof})$  that equals the entries of the given vector.  
 ultimately have  
      $\forall p :: 'a \text{ Ordered-Preference. } \text{vote-fraction } (\text{ord2pref } p) (\text{UNIV}, V, \text{prof}) = x\$p$   
 using *fract*  
 by *presburger*  
 moreover have  
      $\forall E \in \text{anonymity-homogeneity}_{\mathcal{R}} (\text{elections-}\mathcal{A} \text{ UNIV}) \text{ “ } \{(UNIV, V, \text{prof})\}.$   
      $\forall p. \text{vote-fraction } (\text{ord2pref } p) E =$   
      $\text{vote-fraction } (\text{ord2pref } p) (\text{UNIV}, V, \text{prof})$   
 unfolding *anonymity-homogeneity<sub>R</sub>.simps*  
 by *fastforce*  
 ultimately have *all-eq-vec*:  
      $\forall p. \forall E \in \text{anonymity-homogeneity}_{\mathcal{R}} (\text{elections-}\mathcal{A} \text{ UNIV})$   
      $\text{“ } \{(UNIV, V, \text{prof})\}. \text{vote-fraction } (\text{ord2pref } p) E = x\$p$   
 using *Re-complex-of-real Re-divide-of-real of-rat.rep-eq of-real-of-int-eq injI of-rat-eq-iff the-inv-f-f rat-inv*  
 by *(metis (mono-tags, opaque-lifting))*  
 moreover have *election*:  $(UNIV, V, \text{prof}) \in \text{elections-}\mathcal{A} \text{ UNIV}$   
 unfolding *elections-}\mathcal{A}.simps* *well-formed-elections-def profile-def*  
 using *fin-V ord2pref prof*

```

    by auto
  hence
     $(UNIV, V, prof) \in \text{anonymity-homogeneity}_{\mathcal{R}} (\text{elections-}\mathcal{A} \text{ } UNIV) \text{ `` } \{(UNIV, V, prof)\}$ 
  unfolding anonymity-homogeneity $_{\mathcal{R}}$ .simps
  by blast
  ultimately have  $\forall p. \text{vote-fraction } (ord2pref p) \text{ `` }$ 
     $\text{anonymity-homogeneity}_{\mathcal{R}} (\text{elections-}\mathcal{A} \text{ } UNIV) \text{ `` } \{(UNIV, V, prof)\} \supseteq \{x\$p\}$ 
  using image-insert insert-iff mk-disjoint-insert singletonD subsetI
  by (metis (no-types, lifting))
  hence  $\forall p. \text{vote-fraction } (ord2pref p) \text{ `` }$ 
     $\text{anonymity-homogeneity}_{\mathcal{R}} (\text{elections-}\mathcal{A} \text{ } UNIV) \text{ `` } \{(UNIV, V, prof)\} = \{x\$p\}$ 
  using all-eq-vec
  by blast
  hence  $x = \text{anonymity-homogeneity-class}$ 
     $(\text{anonymity-homogeneity}_{\mathcal{R}} (\text{elections-}\mathcal{A} \text{ } UNIV) \text{ `` } \{(UNIV, V, prof)\})$ 
  using is-singletonI singleton-inject singleton-set-def-if-card-one vec-lambda-unique
  unfolding anonymity-homogeneity-class.simps is-singleton-altdef
    vote-fraction $_{\mathcal{Q}}$ .simps  $\pi_{\mathcal{Q}}$ .simps
  by (metis (no-types, lifting))
  thus  $x \in (\text{anonymity-homogeneity-class}$ 
     $:: ('a, 'v) \text{ Election set} \Rightarrow \text{rat}^a \text{ Ordered-Preference})$ 
     $\text{ `` } \text{anonymity-homogeneity}_{\mathcal{Q}} \text{ } UNIV$ 
  unfolding anonymity-homogeneity $_{\mathcal{Q}}$ .simps quotient-def
  using election
  by blast
qed
qed
end

```

## Chapter 4

# Component Types

### 4.1 Distance

```
theory Distance
  imports HOL-Library.Extended-Real
           Social-Choice-Types/Voting-Symmetry
begin
```

A general distance on a set  $X$  is a mapping  $d: X \times X \mapsto R \cup \{+\infty\}$  such that for every  $x, y, z$  in  $X$ , the following four conditions are satisfied:

- $d(x, y) \geq 0$  (non-negativity);
- $d(x, y) = 0$  if and only if  $x = y$  (identity of indiscernibles);
- $d(x, y) = d(y, x)$  (symmetry);
- $d(x, y) \leq d(x, z) + d(z, y)$  (triangle inequality).

Moreover, a mapping that satisfies all but the second conditions is called a pseudo-distance, whereas a quasi-distance needs to satisfy the first three conditions (and not necessarily the last one).

#### 4.1.1 Definition

```
type-synonym 'a Distance = 'a  $\Rightarrow$  'a  $\Rightarrow$  ereal
```

The un-curried version of a distance is defined on tuples.

```
fun tup :: 'a Distance  $\Rightarrow$  ('a * 'a  $\Rightarrow$  ereal) where
  tup d = ( $\lambda$  pair. d (fst pair) (snd pair))
```

```
definition distance :: 'a set  $\Rightarrow$  'a Distance  $\Rightarrow$  bool where
  distance S d  $\equiv \forall x y. x \in S \wedge y \in S \longrightarrow d\ x\ x = 0 \wedge 0 \leq d\ x\ y$ 
```

### 4.1.2 Conditions

**definition** *symmetric* :: 'a set  $\Rightarrow$  'a Distance  $\Rightarrow$  bool **where**  
*symmetric*  $S\ d \equiv \forall\ x\ y. x \in S \wedge y \in S \longrightarrow d\ x\ y = d\ y\ x$

**definition** *triangle-ineq* :: 'a set  $\Rightarrow$  'a Distance  $\Rightarrow$  bool **where**  
*triangle-ineq*  $S\ d \equiv \forall\ x\ y\ z. x \in S \wedge y \in S \wedge z \in S \longrightarrow d\ x\ z \leq d\ x\ y + d\ y\ z$

**definition** *eq-if-zero* :: 'a set  $\Rightarrow$  'a Distance  $\Rightarrow$  bool **where**  
*eq-if-zero*  $S\ d \equiv \forall\ x\ y. x \in S \wedge y \in S \longrightarrow d\ x\ y = 0 \longrightarrow x = y$

**definition** *vote-distance* :: ('a Vote set  $\Rightarrow$  'a Vote Distance  $\Rightarrow$  bool)  $\Rightarrow$   
'a Vote Distance  $\Rightarrow$  bool **where**  
*vote-distance*  $\pi\ d \equiv \pi\ \{(A, p). \text{linear-order-on } A\ p \wedge \text{finite } A\}\ d$

**definition** *election-distance* :: (('a, 'v) Election set  $\Rightarrow$   
('a, 'v) Election Distance  $\Rightarrow$  bool)  $\Rightarrow$   
('a, 'v) Election Distance  $\Rightarrow$  bool **where**  
*election-distance*  $\pi\ d \equiv \pi\ \{(A, V, p). \text{finite-profile } V\ A\ p\}\ d$

### 4.1.3 Standard-Distance Property

**definition** *standard* :: ('a, 'v) Election Distance  $\Rightarrow$  bool **where**  
*standard*  $d \equiv$   
 $\forall\ A\ A'\ V\ V'\ p\ p'. A \neq A' \vee V \neq V' \longrightarrow d\ (A, V, p)\ (A', V', p') = \infty$

### 4.1.4 Auxiliary Lemmas

**fun** *arg-min-set* :: ('b  $\Rightarrow$  'a :: ord)  $\Rightarrow$  'b set  $\Rightarrow$  'b set **where**  
*arg-min-set*  $f\ A = \text{Collect } (\text{is-arg-min } f\ (\lambda\ a. a \in A))$

**lemma** *arg-min-subset*:  
**fixes**  
 $B :: 'b\ \text{set}$  **and**  
 $f :: 'b \Rightarrow 'a :: \text{ord}$   
**shows** *arg-min-set*  $f\ B \subseteq B$   
**unfolding** *arg-min-set.simps* *is-arg-min-def*  
**by** *safe*

**lemma** *sum-monotone*:  
**fixes**  
 $A :: 'a\ \text{set}$  **and**  
 $f\ g :: 'a \Rightarrow \text{int}$   
**assumes**  $\forall\ a \in A. f\ a \leq g\ a$   
**shows**  $(\sum\ a \in A. f\ a) \leq (\sum\ a \in A. g\ a)$   
**using** *assms*  
**proof** (*induction*  $A$  *rule: infinite-finite-induct*)  
**case** (*infinite*  $A$ )  
**fix**  $A :: 'a\ \text{set}$   
**show** ?case

```

      using infinite
      by simp
next
  case empty
  show ?case
  by simp
next
  case (insert x F)
  fix
    x :: 'a and
    F :: 'a set
  show ?case
  using insert
  by simp
qed

```

```

lemma distrib:
  fixes
    A :: 'a set and
    f g :: 'a  $\Rightarrow$  int
  shows  $(\sum a \in A. f\ a) + (\sum a \in A. g\ a) = (\sum a \in A. f\ a + g\ a)$ 
  using sum.distrib
  by metis

```

```

lemma distrib-ereal:
  fixes
    A :: 'a set and
    f g :: 'a  $\Rightarrow$  int
  shows  $ereal\ (real-of-int\ ((\sum a \in A. (f :: 'a \Rightarrow int)\ a) + (\sum a \in A. g\ a))) =$ 
 $ereal\ (real-of-int\ (\sum a \in A. f\ a + g\ a))$ 
  using distrib
  by metis

```

```

lemma uneq-ereal:
  fixes x y :: int
  assumes  $x \leq y$ 
  shows  $ereal\ (real-of-int\ x) \leq ereal\ (real-of-int\ y)$ 
  using assms
  by simp

```

#### 4.1.5 Swap Distance

```

fun neq-ord :: 'a Preference-Relation  $\Rightarrow$  'a Preference-Relation  $\Rightarrow$ 
  'a  $\Rightarrow$  'a  $\Rightarrow$  bool where
  neq-ord r s a b =  $((a \preceq_r b \wedge b \preceq_s a) \vee (b \preceq_r a \wedge a \preceq_s b))$ 

```

```

fun pairwise-disagreements :: 'a set  $\Rightarrow$  'a Preference-Relation  $\Rightarrow$ 
  'a Preference-Relation  $\Rightarrow$  ('a  $\times$  'a) set where
  pairwise-disagreements A r s =  $\{(a, b) \in A \times A. a \neq b \wedge neq-ord\ r\ s\ a\ b\}$ 

```

```

fun pairwise-disagreements' :: 'a set  $\Rightarrow$  'a Preference-Relation  $\Rightarrow$ 
  'a Preference-Relation  $\Rightarrow$  ('a  $\times$  'a) set where
  pairwise-disagreements' A r s =
    Set.filter ( $\lambda$  (a, b). a  $\neq$  b  $\wedge$  neq-ord r s a b) (A  $\times$  A)

```

**lemma** set-eq-filter:

```

fixes
  X :: 'a set and
  P :: 'a  $\Rightarrow$  bool
shows {x  $\in$  X. P x} = Set.filter P X
by auto

```

**lemma** pairwise-disagreements-eq[code]: pairwise-disagreements = pairwise-disagreements'

```

unfolding pairwise-disagreements.simps pairwise-disagreements'.simps
by fastforce

```

**fun** swap :: 'a Vote Distance **where**

```

  swap (A, r) (A', r') =
    (if A = A'
     then card (pairwise-disagreements A r r')
     else  $\infty$ )

```

**lemma** swap-case-infinity:

```

fixes x y :: 'a Vote
assumes alts- $\mathcal{V}$  x  $\neq$  alts- $\mathcal{V}$  y
shows swap x y =  $\infty$ 
using assms
by (induction rule: swap.induct, simp)

```

**lemma** swap-case-fin:

```

fixes x y :: 'a Vote
assumes alts- $\mathcal{V}$  x = alts- $\mathcal{V}$  y
shows swap x y = card (pairwise-disagreements (alts- $\mathcal{V}$  x) (pref- $\mathcal{V}$  x) (pref- $\mathcal{V}$  y))
using assms
by (induction rule: swap.induct, simp)

```

#### 4.1.6 Spearman Distance

**fun** spearman :: 'a Vote Distance **where**

```

  spearman (A, x) (A', y) =
    (if A = A'
     then  $\sum a \in A. \text{abs } (\text{int } (\text{rank } x \ a) - \text{int } (\text{rank } y \ a))$ 
     else  $\infty$ )

```

**lemma** spearman-case-inf:

```

fixes x y :: 'a Vote
assumes alts- $\mathcal{V}$  x  $\neq$  alts- $\mathcal{V}$  y
shows spearman x y =  $\infty$ 

```



**using** *assms*  
**by** (*induction rule: spearman.induct, simp*)

**lemma** *spearman-case-fin*:  
**fixes**  $x\ y :: 'a\ Vote$   
**assumes**  $alts\mathcal{V}\ x = alts\mathcal{V}\ y$   
**shows**  $spearman\ x\ y =$   
 $(\sum a \in alts\mathcal{V}\ x. abs\ (int\ (rank\ (pref\mathcal{V}\ x)\ a) - int\ (rank\ (pref\mathcal{V}\ y)\ a)))$   
**using** *assms*  
**by** (*induction rule: spearman.induct, simp*)

#### 4.1.7 Properties

Distances that are invariant under specific relations induce symmetry properties in distance rationalized voting rules.

##### Definitions

**fun**  $total\text{-}invariance_{\mathcal{D}} :: 'x\ Distance \Rightarrow 'x\ rel \Rightarrow bool$  **where**  
 $total\text{-}invariance_{\mathcal{D}}\ d\ rel = is\text{-}symmetry\ (tup\ d)\ (Invariance\ (product\ rel))$

**fun**  $invariance_{\mathcal{D}} :: 'y\ Distance \Rightarrow 'x\ set \Rightarrow 'y\ set \Rightarrow$   
 $('x, 'y)\ binary\text{-}fun \Rightarrow bool$  **where**  
 $invariance_{\mathcal{D}}\ d\ X\ Y\ \varphi = is\text{-}symmetry\ (tup\ d)\ (Invariance\ (equivariance\ X\ Y\ \varphi))$

**definition**  $distance\text{-}anonymity :: ('a, 'v)\ Election\ Distance \Rightarrow bool$  **where**  
 $distance\text{-}anonymity\ d \equiv$   
 $\forall\ A\ A'\ V\ V'\ p\ p'\ \pi :: ('v \Rightarrow 'v).$   
 $(bij\ \pi \longrightarrow$   
 $(d\ (A, V, p)\ (A', V', p')) =$   
 $(d\ (rename\ \pi\ (A, V, p))\ (rename\ \pi\ (A', V', p'))))$

**fun**  $distance\text{-}anonymity' :: ('a, 'v)\ Election\ set \Rightarrow$   
 $('a, 'v)\ Election\ Distance \Rightarrow bool$  **where**  
 $distance\text{-}anonymity'\ X\ d = invariance_{\mathcal{D}}\ d\ (carrier\ bijection_{\mathcal{V}G})\ X\ (\varphi\text{-anon}\ X)$

**fun**  $distance\text{-}neutrality :: ('a, 'v)\ Election\ set \Rightarrow$   
 $('a, 'v)\ Election\ Distance \Rightarrow bool$  **where**  
 $distance\text{-}neutrality\ X\ d = invariance_{\mathcal{D}}\ d\ (carrier\ bijection_{AG})\ X\ (\varphi\text{-neutral}\ X)$

**fun**  $distance\text{-}reversal\text{-}symmetry :: ('a, 'v)\ Election\ set \Rightarrow$   
 $('a, 'v)\ Election\ Distance \Rightarrow bool$  **where**  
 $distance\text{-}reversal\text{-}symmetry\ X\ d =$   
 $invariance_{\mathcal{D}}\ d\ (carrier\ reversal_G)\ X\ (\varphi\text{-reverse}\ X)$

**definition**  $distance\text{-}homogeneity' :: ('a, 'v :: linorder)\ Election\ set \Rightarrow$   
 $('a, 'v)\ Election\ Distance \Rightarrow bool$  **where**  
 $distance\text{-}homogeneity'\ X\ d \equiv total\text{-}invariance_{\mathcal{D}}\ d\ (homogeneity_{\mathcal{R}}'\ X)$

**definition** *distance-homogeneity* :: ('a, 'v) Election set  $\Rightarrow$   
('a, 'v) Election Distance  $\Rightarrow$  bool **where**  
*distance-homogeneity* X d  $\equiv$  *total-invariance* <sub>$\mathcal{D}$</sub>  d (*homogeneity* <sub>$\mathcal{R}$</sub>  X)

## Auxiliary Lemmas

**lemma** *rewrite-total-invariance* <sub>$\mathcal{D}$</sub> :

**fixes**

d :: 'x Distance **and**

r :: 'x rel

**shows** *total-invariance* <sub>$\mathcal{D}$</sub>  d r = ( $\forall$  (x, y)  $\in$  r.  $\forall$  (a, b)  $\in$  r. d a x = d b y)

**proof** (*unfold total-invariance* <sub>$\mathcal{D}$</sub> .*simps is-symmetry.simps product.simps, safe*)

**fix** a b x y :: 'x

**assume**

$\forall$  x y. (x, y)  $\in$  {(p, p')}.

(fst p, fst p')  $\in$  r  $\wedge$  (snd p, snd p')  $\in$  r

$\longrightarrow$  tup d x = tup d y **and**

(a, b)  $\in$  r **and**

(x, y)  $\in$  r

**thus** d a x = d b y

**unfolding** *total-invariance* <sub>$\mathcal{D}$</sub> .*simps is-symmetry.simps*

**by** *simp*

**next**

**fix** a b x y :: 'x

**assume**

$\forall$  (x, y)  $\in$  r.  $\forall$  (a, b)  $\in$  r. d a x = d b y **and**

(fst (x, a), fst (y, b))  $\in$  r **and**

(snd (x, a), snd (y, b))  $\in$  r

**hence** d x a = d y b

**by** *auto*

**thus** tup d (x, a) = tup d (y, b)

**by** *simp*

**qed**

**lemma** *rewrite-invariance* <sub>$\mathcal{D}$</sub> :

**fixes**

d :: 'y Distance **and**

X :: 'x set **and**

Y :: 'y set **and**

$\varphi$  :: ('x, 'y) binary-fun

**shows** *invariance* <sub>$\mathcal{D}$</sub>  d X Y  $\varphi$  =

( $\forall$  x  $\in$  X.  $\forall$  y  $\in$  Y.  $\forall$  z  $\in$  Y. d y z = d ( $\varphi$  x y) ( $\varphi$  x z))

**proof** (*unfold invariance* <sub>$\mathcal{D}$</sub> .*simps is-symmetry.simps equivariance.simps, safe*)

**fix**

x :: 'x **and**

y z :: 'y

**assume**

x  $\in$  X **and**

y  $\in$  Y **and**

```

    z ∈ Y and
    ∀ x y. (x, y) ∈ {(u, v), x, y}. (u, v) ∈ Y × Y
        ∧ (∃ z ∈ X. x = φ z u ∧ y = φ z v)}
        → tup d x = tup d y
  thus d y z = d (φ x y) (φ x z)
    by fastforce
next
fix
  x :: 'x and
  a b :: 'y
assume
  ∀ x ∈ X. ∀ y ∈ Y. ∀ z ∈ Y. d y z = d (φ x y) (φ x z) and
  x ∈ X and
  a ∈ Y and
  b ∈ Y
hence d a b = d (φ x a) (φ x b)
  by blast
thus tup d (a, b) = tup d (φ x a, φ x b)
  by simp
qed

```

**lemma** *invar-dist-image*:

```

fixes
  d :: 'y Distance and
  G :: 'x monoid and
  Y Y' :: 'y set and
  φ :: ('x, 'y) binary-fun and
  y :: 'y and
  g :: 'x
assumes
  invar-d: invarianceD d (carrier G) Y φ and
  Y'-in-Y: Y' ⊆ Y and
  action-φ: group-action G Y φ and
  g-carrier: g ∈ carrier G and
  y-in-Y: y ∈ Y
shows d (φ g y) ' (φ g) ' Y' = d y ' Y'
proof (safe)
  fix y' :: 'y
  assume y'-in-Y': y' ∈ Y'
  hence ((y, y'), ((φ g y), (φ g y'))) ∈ equivariance (carrier G) Y φ
    using Y'-in-Y y-in-Y g-carrier
  unfolding equivariance.simps
  by blast
hence eq-dist: tup d ((φ g y), (φ g y')) = tup d (y, y')
  using invar-d
  unfolding invarianceD.simps
  by fastforce
thus d (φ g y) (φ g y') ∈ d y ' Y'
  using y'-in-Y'

```

```

    by simp
  have  $\varphi \ g \ y' \in \varphi \ g \ ' \ Y'$ 
    using  $y'\text{-in-}Y'$ 
    by simp
  thus  $d \ y \ y' \in d \ (\varphi \ g \ y) \ ' \ \varphi \ g \ ' \ Y'$ 
    using eq-dist
    by (simp add: rev-image-eqI)
qed

lemma swap-neutral: invarianceD swap (carrier bijectionAG)
  UNIV  $(\lambda \ \pi \ (A, q). (\pi \ ' \ A, \text{rel-rename } \pi \ q))$ 
proof (unfold rewrite-invarianceD, safe)
  fix
     $\pi :: 'a \Rightarrow 'a$  and
     $A \ A' :: 'a \text{ set}$  and
     $q \ q' :: 'a \text{ rel}$ 
  assume  $\pi \in \text{carrier bijection}_{AG}$ 
  hence  $\text{bij-}\pi$ :  $\text{bij } \pi$ 
    unfolding bijectionAG-def
    using rewrite-carrier
    by blast
  show swap  $(A, q) \ (A', q') =$ 
    swap  $(\pi \ ' \ A, \text{rel-rename } \pi \ q) \ (\pi \ ' \ A', \text{rel-rename } \pi \ q')$ 
  proof (cases  $A = A'$ )
    let ?f =  $(\lambda \ (a, b). (\pi \ a, \pi \ b))$ 
    let ?swap-set =  $\{(a, b) \in A \times A. a \neq b \wedge \text{neq-ord } q \ q' \ a \ b\}$ 
    let ?swap-set' =
       $\{(a, b) \in \pi \ ' \ A \times \pi \ ' \ A. a \neq b$ 
         $\wedge \text{neq-ord } (\text{rel-rename } \pi \ q) \ (\text{rel-rename } \pi \ q') \ a \ b\}$ 
    let ?rel =  $\{(a, b) \in A \times A. a \neq b \wedge \text{neq-ord } q \ q' \ a \ b\}$ 
    case True
    hence  $\pi \ ' \ A = \pi \ ' \ A'$ 
      by simp
    hence swap  $(\pi \ ' \ A, \text{rel-rename } \pi \ q) \ (\pi \ ' \ A', \text{rel-rename } \pi \ q') = \text{card } ?\text{swap-set}'$ 
      by simp
    moreover have  $\text{bij-betw } ?f \ ?\text{swap-set} \ ?\text{swap-set}'$ 
  proof (unfold bij-betw-def inj-on-def, intro conjI impI ballI)
    fix  $x \ y :: 'a \times 'a$ 
    assume
       $x \in ?\text{swap-set}$  and
       $y \in ?\text{swap-set}$  and
       $?f \ x = ?f \ y$ 
    hence
       $\pi \ (\text{fst } x) = \pi \ (\text{fst } y)$  and
       $\pi \ (\text{snd } x) = \pi \ (\text{snd } y)$ 
      by auto
    hence
       $\text{fst } x = \text{fst } y$  and
       $\text{snd } x = \text{snd } y$ 

```

```

    using bij- $\pi$  bij-pointE
    by (metis, metis)
  thus  $x = y$ 
    using prod.expand
    by metis
next
show ?f ‘ ?swap-set = ?swap-set’
proof
  have  $\forall a b. (a, b) \in A \times A \longrightarrow (\pi a, \pi b) \in \pi ‘ A \times \pi ‘ A$ 
    by simp
  moreover have  $\forall a b. a \neq b \longrightarrow \pi a \neq \pi b$ 
    using bij- $\pi$  bij-pointE
    by metis
  moreover have
     $\forall a b. \text{neg-ord } q \ q' \ a \ b$ 
     $\longrightarrow \text{neg-ord } (\text{rel-rename } \pi \ q) \ (\text{rel-rename } \pi \ q') \ (\pi a) \ (\pi b)$ 
    unfolding neg-ord.simps rel-rename.simps
    by auto
  ultimately show ?f ‘ ?swap-set  $\subseteq$  ?swap-set’
    by auto
next
have  $\forall a b. (a, b) \in (\text{rel-rename } \pi \ q) \longrightarrow (\text{the-inv } \pi \ a, \text{the-inv } \pi \ b) \in q$ 
  unfolding rel-rename.simps
  using bij- $\pi$  bij-is-inj the-inv-f-f
  by fastforce
moreover have
   $\forall a b. (a, b) \in (\text{rel-rename } \pi \ q') \longrightarrow (\text{the-inv } \pi \ a, \text{the-inv } \pi \ b) \in q'$ 
  unfolding rel-rename.simps
  using bij- $\pi$  bij-is-inj the-inv-f-f
  by fastforce
ultimately have
   $\forall a b. \text{neg-ord } (\text{rel-rename } \pi \ q) \ (\text{rel-rename } \pi \ q') \ a \ b$ 
   $\longrightarrow \text{neg-ord } q \ q' \ (\text{the-inv } \pi \ a) \ (\text{the-inv } \pi \ b)$ 
  by simp
moreover have
   $\forall a b. (a, b) \in \pi ‘ A \times \pi ‘ A \longrightarrow (\text{the-inv } \pi \ a, \text{the-inv } \pi \ b) \in A \times A$ 
  using bij- $\pi$  bij-is-inj f-the-inv-into-f inj-image-mem-iff
  by fastforce
moreover have  $\forall a b. a \neq b \longrightarrow \text{the-inv } \pi \ a \neq \text{the-inv } \pi \ b$ 
  using bij- $\pi$  UNIV-I bij-betw-imp-surj bij-is-inj f-the-inv-into-f
  by metis
ultimately have
   $\forall a b. (a, b) \in ?\text{swap-set}' \longrightarrow (\text{the-inv } \pi \ a, \text{the-inv } \pi \ b) \in ?\text{swap-set}$ 
  by blast
moreover have  $\forall a b. (a, b) = ?f \ (\text{the-inv } \pi \ a, \text{the-inv } \pi \ b)$ 
  using f-the-inv-into-f-bij-betw bij- $\pi$ 
  by fastforce
ultimately show ?swap-set'  $\subseteq$  ?f ‘ ?swap-set
  by blast

```

```

    qed
  qed
  moreover have card ?swap-set = swap (A, q) (A', q')
    using True
    by simp
  ultimately show ?thesis
    by (simp add: bij-betw-same-card)
next
case False
hence  $\pi \text{ ` } A \neq \pi \text{ ` } A'$ 
  using bij- $\pi$  bij-is-inj inj-image-eq-iff
  by metis
thus ?thesis
  using False
  by simp
qed
qed
end

```

## 4.2 Votewise Distance

```

theory Votewise-Distance
  imports Social-Choice-Types/Norm
          Distance
begin

```

Votewise distances are a natural class of distances on elections which depend on the submitted votes in a simple and transparent manner. They are formed by using any distance  $d$  on individual orders and combining the components with a norm on  $\mathbb{R}^n$ .

### 4.2.1 Definition

```

fun votewise-distance :: 'a Vote Distance  $\Rightarrow$  Norm  $\Rightarrow$ 
  ('a, 'v :: linorder) Election Distance where
  votewise-distance d n (A, V, p) (A', V', p') =
    (if finite V  $\wedge$  V = V'  $\wedge$  (V  $\neq$  {}  $\vee$  A = A')
     then n (map2 ( $\lambda$  q q'. d (A, q) (A', q')) (to-list V p) (to-list V' p'))
     else  $\infty$ )

```

### 4.2.2 Inference Rules

```

lemma symmetric-norm-inv-under-map-permute:
  fixes
    d :: 'a Vote Distance and

```

```

  n :: Norm and
  A A' :: 'a set and
  φ :: nat ⇒ nat and
  p p' :: 'a Preference-Relation list
assumes
  perm: φ permutes {0 ..< length p} and
  len-eq: length p = length p' and
  sym-n: symmetry n
shows n (map2 (λ q q'. d (A, q) (A', q')) p p') =
  n (map2 (λ q q'. d (A, q) (A', q')) (permute-list φ p) (permute-list φ p'))
proof -
  have length (map2 (λ x y. d (A, x) (A', y)) p p') = length p
  using len-eq
  by simp
  hence n (map2 (λ q q'. d (A, q) (A', q')) p p') =
    n (permute-list φ (map2 (λ x y. d (A, x) (A', y)) p p'))
  using perm sym-n mset-permute-list atLeast-upt
  unfolding symmetry-def
  by fastforce
  thus ?thesis
  using perm len-eq atLeast-upt permute-list-map[of - - λ (q, q'). d (A, q) (A',
q')]
  by (simp add: permute-list-zip)
qed

```

```

lemma permute-invariant-under-map:
  fixes l l' :: 'a list
  assumes l <~~> l'
  shows map f l <~~> map f l'
  using assms
  by simp

```

```

lemma linorder-rank-injective:

```

```

  fixes
    V :: 'v :: linorder set and
    v v' :: 'v

```

```

  assumes
    v-in-V: v ∈ V and
    v'-in-V: v' ∈ V and
    v'-neq-v: v' ≠ v and
    fin-V: finite V

```

```

  shows card {x ∈ V. x < v} ≠ card {x ∈ V. x < v'}

```

```

proof -

```

```

  have v < v' ∨ v' < v
  using v'-neq-v linorder-less-linear
  by metis

```

```

  hence {x ∈ V. x < v} ⊂ {x ∈ V. x < v'} ∨ {x ∈ V. x < v'} ⊂ {x ∈ V. x < v}
  using v-in-V v'-in-V dual-order.strict-trans
  by blast

```

**thus** *?thesis*  
**using** *assms sorted-list-of-set-nth-equals-card*  
**by** (*metis (full-types)*)  
**qed**

**lemma** *permute-invariant-under-coinciding-funs*:  
**fixes**  
 $l :: 'v \text{ list}$  **and**  
 $\pi_1 \pi_2 :: \text{nat} \Rightarrow \text{nat}$   
**assumes**  $\forall i < \text{length } l. \pi_1 i = \pi_2 i$   
**shows** *permute-list*  $\pi_1 l = \text{permute-list } \pi_2 l$   
**using** *assms*  
**unfolding** *permute-list-def*  
**by** *simp*

**lemma** *symmetric-norm-imp-distance-anonymous*:  
**fixes**  
 $d :: 'a \text{ Vote Distance}$  **and**  
 $n :: \text{Norm}$   
**assumes** *symmetry*  $n$   
**shows** *distance-anonymity* (*votewise-distance*  $d n$ )  
**proof** (*unfold distance-anonymity-def, safe*)

**fix**  
 $A A' :: 'a \text{ set}$  **and**  
 $V V' :: 'v :: \text{linorder set}$  **and**  
 $p p' :: ('a, 'v) \text{ Profile}$  **and**  
 $\pi :: 'v \Rightarrow 'v$   
**let**  $?rn1 = \text{rename } \pi (A, V, p)$  **and**  
 $?rn2 = \text{rename } \pi (A', V', p')$  **and**  
 $?rn-V = \pi \text{ ` } V$  **and**  
 $?rn-V' = \pi \text{ ` } V'$  **and**  
 $?rn-p = p \circ (\text{the-inv } \pi)$  **and**  
 $?rn-p' = p' \circ (\text{the-inv } \pi)$  **and**  
 $?len = \text{length } (\text{to-list } V p)$  **and**  
 $?sl-V = \text{sorted-list-of-set } V$

**let**  $?perm = \lambda i. \text{card } \{v \in ?rn-V. v < \pi (?sl-V!i)\}$  **and**  
 — Use a total permutation function in order to apply facts such as *mset-permute-list*.  
 $?perm\text{-total} = \lambda i. \text{if } i < ?len$   
      $\text{then card } \{v \in ?rn-V. v < \pi (?sl-V!i)\}$   
      $\text{else } i$

**assume** *bij- $\pi$* : *bij*  $\pi$

**show** *votewise-distance*  $d n (A, V, p) (A', V', p') =$   
 $\text{votewise-distance } d n ?rn1 ?rn2$

**proof** (*cases finite*  $V \wedge V = V' \wedge (V \neq \{\} \vee A = A')$ )  
**case** *False*

— Case: Both distances are infinite.

**hence** *votewise-distance*  $d n (A, V, p) (A', V', p') = \infty$

**by** *auto*

**moreover have** *infinite*  $V \longrightarrow \text{infinite } ?rn-V$



```

    using bij- $\pi$  bij-betw-finite bij-betw-subset subset-UNIV
    by metis
  moreover have  $V \neq V' \longrightarrow ?rn-V \neq ?rn-V'$ 
    using bij- $\pi$  inj-image-mem-iff subsetI subset-antisym
    unfolding bij-def
    by metis
  ultimately show  $\text{votewise-distance } d \ n \ (A, V, p) \ (A', V', p') =$ 
     $\text{votewise-distance } d \ n \ ?rn1 \ ?rn2$ 
    using False
    by auto
next
case True
  — Case: Both distances are finite.
  have  $\text{lengths-eq: } ?len = \text{length } (\text{to-list } V' \ p')$ 
    using True
    by simp
  have  $rn-V\text{-permutes: } \text{to-list } V \ p = \text{permute-list } ?perm \ (\text{to-list } ?rn-V \ ?rn-p)$ 
    using assms to-list-permutes-under-bij bij- $\pi$  to-list-permutes-under-bij
    unfolding comp-def
    by (metis (no-types))
  hence  $\text{len-}V\text{-}rn-V\text{-eq: } ?len = \text{length } (\text{to-list } ?rn-V \ ?rn-p)$ 
    by simp
  hence  $\text{permute-list } ?perm \ (\text{to-list } ?rn-V \ ?rn-p) =$ 
     $\text{permute-list } ?perm\text{-total } (\text{to-list } ?rn-V \ ?rn-p)$ 
    using permute-invariant-under-coinciding-funs[of to-list ?rn-V ?rn-p]
    by presburger
  hence  $rn\text{-list-perm-list-}V$ :
     $\text{to-list } V \ p = \text{permute-list } ?perm\text{-total } (\text{to-list } ?rn-V \ ?rn-p)$ 
    using  $rn-V\text{-permutes}$ 
    by metis
  have  $\text{to-list } V' \ p' = \text{permute-list } ?perm \ (\text{to-list } ?rn-V' \ ?rn-p')$ 
    unfolding comp-def
    using True bij- $\pi$  to-list-permutes-under-bij
    by (metis (no-types))
  hence  $rn\text{-list-perm-list-}V'$ :
     $\text{to-list } V' \ p' = \text{permute-list } ?perm\text{-total } (\text{to-list } ?rn-V' \ ?rn-p')$ 
    using  $\text{lengths-eq } \text{permute-invariant-under-coinciding-funs}$ [of to-list ?rn-V'
    ?rn-p']
    by fastforce
  have  $?perm\text{-total permutes } \{0 \ ..< \ ?len\}$ 
  proof —
    have  $\forall \ i \ j. \ i < ?len \wedge j < ?len \wedge i \neq j$ 
       $\longrightarrow \pi \ ((\text{sorted-list-of-set } V)!i) \neq \pi \ ((\text{sorted-list-of-set } V)!j)$ 
      using True bij- $\pi$  bij-pointE nth-eq-iff-index-eq length-map
      sorted-list-of-set.distinct-sorted-key-list-of-set to-list.elims
      by (metis (mono-tags, opaque-lifting))
    moreover have  $\text{in-bnds-imp-img-el}$ :
       $\forall \ i. \ i < ?len \longrightarrow \pi \ ((\text{sorted-list-of-set } V)!i) \in \pi \text{ ` } V$ 
      using True image-eqI length-map nth-mem to-list.simps

```

```

      sorted-list-of-set.set-sorted-key-list-of-set
    by (metis (no-types))
  ultimately have
     $\forall i < ?len. \forall j < ?len. ?perm-total\ i = ?perm-total\ j \longrightarrow i = j$ 
    using True linorder-rank-injective Collect-cong finite-imageI
    by (metis (no-types, lifting))
  hence inj: inj-on ?perm-total {0 ..< ?len}
    unfolding inj-on-def
    by simp
  have  $\forall v' \in \pi \text{ ` } V. \text{card } \{v \in \pi \text{ ` } V. v < v'\} < \text{card } (\pi \text{ ` } V)$ 
    using True card-seteq finite-imageI less-irrefl linorder-not-le
      mem-Collect-eq subsetI
    by (metis (no-types, lifting))
  moreover have  $\forall i < ?len. \pi ((sorted-list-of-set\ V)!i) \in \pi \text{ ` } V$ 
    using in-bnds-imp-imp-el
    by simp
  moreover have  $\text{card } (\pi \text{ ` } V) = \text{card } V$ 
    using bij- $\pi$  bij-betw-same-card bij-betw-subset top-greatest
    by metis
  moreover have  $\text{card } V = ?len$ 
    by simp
  ultimately have
     $\forall i. i < ?len \longrightarrow ?perm-total\ i \in \{0 ..< ?len\}$ 
    using atLeast0LessThan lessThan-iff
    by (metis (full-types))
  hence  $?perm-total \text{ ` } \{0 ..< ?len\} \subseteq \{0 ..< ?len\}$ 
    by force
  hence bij-betw  $?perm-total\ \{0 ..< ?len\}\ \{0 ..< ?len\}$ 
    using inj card-image card-subset-eq atLeast0LessThan finite-atLeastLessThan
    unfolding bij-betw-def
    by blast
  thus ?thesis
    using atLeast0LessThan bij-imp-permutes
    by fastforce
qed
hence votewise-distance  $d\ n\ ?rn1\ ?rn2 =$ 
   $n\ (\text{map2 } (\lambda\ q\ q'.\ d\ (A,\ q)\ (A',\ q'))$ 
    (permute-list ?perm-total (to-list ?rn-V ?rn-p))
    (permute-list ?perm-total (to-list ?rn-V' ?rn-p'))))
  using symmetric-norm-inv-under-map-permute[of - to-list ?rn-V ?rn-p]
    True assms len-V-rn-V-eq
  by force
also have  $\dots = n\ (\text{map2 } (\lambda\ q\ q'.\ d\ (A,\ q)\ (A',\ q'))\ (\text{to-list } V\ p)\ (\text{to-list } V'\ p'))$ 
  using rn-list-perm-list-V rn-list-perm-list-V'
  by presburger
finally show
   $\text{votewise-distance } d\ n\ (A,\ V,\ p)\ (A',\ V',\ p') = \text{votewise-distance } d\ n\ ?rn1\ ?rn2$ 
  using True
  by force

```

qed  
qed

**lemma** *neutral-dist-imp-neutral-votewise-dist:*

**fixes**

$d :: 'a \text{ Vote Distance}$  **and**

$n :: \text{Norm}$

**defines** *vote-action*  $\equiv \lambda \pi (A, q). (\pi \text{ ` } A, \text{rel-rename } \pi \text{ } q)$

**assumes** *invariance<sub>D</sub>*  $d (\text{carrier bijection}_{AG}) \text{ UNIV vote-action}$

**shows** *distance-neutrality well-formed-elections (votewise-distance d n)*

**proof** (*unfold distance-neutrality.simps rewrite-invariance<sub>D</sub>, safe*)

**fix**

$A \ A' :: 'a \text{ set}$  **and**

$V \ V' :: 'v :: \text{linorder set}$  **and**

$p \ p' :: ('a, 'v) \text{ Profile}$  **and**

$\pi :: 'a \Rightarrow 'a$

**assume**

*carrier:*  $\pi \in \text{carrier bijection}_{AG}$  **and**

*valid:*  $(A, V, p) \in \text{well-formed-elections}$  **and**

*valid':*  $(A', V', p') \in \text{well-formed-elections}$

**hence** *bij- $\pi$ :* *bij*  $\pi$

**unfolding** *bijection<sub>AG</sub>-def*

**using** *rewrite-carrier*

**by** *blast*

**thus** *votewise-distance d n*  $(A, V, p) (A', V', p') =$

*votewise-distance d n*

*( $\varphi$ -neutral well-formed-elections  $\pi (A, V, p)$ )*

*( $\varphi$ -neutral well-formed-elections  $\pi (A', V', p')$ )*

**proof** (*cases finite  $V \wedge V = V' \wedge (V \neq \{\} \vee A = A')$* )

**case** *True*

**hence** *finite  $V \wedge V = V' \wedge (V \neq \{\} \vee \pi \text{ ` } A = \pi \text{ ` } A')$*

**by** *metis*

**hence** *votewise-distance d n*

*( $\varphi$ -neutral well-formed-elections  $\pi (A, V, p)$ )*

*( $\varphi$ -neutral well-formed-elections  $\pi (A', V', p')$ ) =*

$n (\text{map2 } (\lambda q \ q'. d (\pi \text{ ` } A, q) (\pi \text{ ` } A', q'))$

*(to-list  $V (\text{rel-rename } \pi \circ p)$ ) (to-list  $V' (\text{rel-rename } \pi \circ p')$ )*)

**using** *valid valid'*

**by** *auto*

**also have**

$\dots =$

$n (\text{map2 } (\lambda q \ q'. d (\pi \text{ ` } A, q) (\pi \text{ ` } A', q'))$

*(map (rel-rename  $\pi$ ) (to-list  $V p$ )) (map (rel-rename  $\pi$ ) (to-list  $V' p'))$ )*

**using** *to-list-comp*

**by** *metis*

**also have**

$\dots = n (\text{map2 } (\lambda q \ q'. d (\pi \text{ ` } A, \text{rel-rename } \pi \text{ } q) (\pi \text{ ` } A', \text{rel-rename } \pi \text{ } q'))$

*(to-list  $V p$ ) (to-list  $V' p')$ )*

**unfolding** *map-helper*

```

    by simp
  also have
    ... = (n (map2 (λ q q'. d (A, q) (A', q')) (to-list V p) (to-list V' p')))
    using rewrite-invarianceD[of d - UNIV vote-action] assms carrier
      UNIV-I case-prod-conv
    unfolding vote-action-def
    by (metis (no-types, lifting))
  finally have votewise-distance d n
    (φ-neutral well-formed-elections π (A, V, p))
    (φ-neutral well-formed-elections π (A', V', p')) =
    n (map2 (λ q q'. d (A, q) (A', q')) (to-list V p) (to-list V' p'))
    by simp
  thus ?thesis
    using True
    by auto
next
case False
hence ¬ (finite V ∧ V = V' ∧ (V ≠ {} ∨ π 'A = π 'A'))
  using bij-π bij-is-inj inj-image-eq-iff
  by metis
thus ?thesis
  using False valid valid'
  by force
qed
qed
end

```

## 4.3 Consensus

```

theory Consensus
  imports Social-Choice-Types/Voting-Symmetry
begin

```

An election consisting of a set of alternatives and preferential votes for each voter (a profile) is a consensus if it has an undisputed winner reflecting a certain concept of fairness in the society.

### 4.3.1 Definition

```

type-synonym ('a, 'v) Consensus = ('a, 'v) Election ⇒ bool

```

### 4.3.2 Consensus Conditions

Nonempty alternative set.

```

fun nonempty-setC :: ('a, 'v) Consensus where

```

$nonempty-set_C (A, V, p) = (A \neq \{\})$

Nonempty profile, i.e., nonempty voter set. Note that this is also true if  $p(v) =$  holds for all voters  $v$  in  $V$ .

**fun**  $nonempty-profile_C :: ('a, 'v) Consensus$  **where**  
 $nonempty-profile_C (A, V, p) = (V \neq \{\})$

Equal top ranked alternatives.

**fun**  $equal-top_C' :: 'a \Rightarrow ('a, 'v) Consensus$  **where**  
 $equal-top_C' a (A, V, p) = (a \in A \wedge (\forall v \in V. above (p v) a = \{a\}))$

**fun**  $equal-top_C :: ('a, 'v) Consensus$  **where**  
 $equal-top_C c = (\exists a. equal-top_C' a c)$

Equal votes.

**fun**  $equal-vote_C' :: 'a Preference-Relation \Rightarrow ('a, 'v) Consensus$  **where**  
 $equal-vote_C' r (A, V, p) = (\forall v \in V. (p v) = r)$

**fun**  $equal-vote_C :: ('a, 'v) Consensus$  **where**  
 $equal-vote_C c = (\exists r. equal-vote_C' r c)$

Unanimity condition.

**fun**  $unanimity_C :: ('a, 'v) Consensus$  **where**  
 $unanimity_C c = (nonempty-set_C c \wedge nonempty-profile_C c \wedge equal-top_C c)$

Strong unanimity condition.

**fun**  $strong-unanimity_C :: ('a, 'v) Consensus$  **where**  
 $strong-unanimity_C c = (nonempty-set_C c \wedge nonempty-profile_C c \wedge equal-vote_C c)$

### 4.3.3 Properties

**definition**  $consensus-anonymity :: ('a, 'v) Consensus \Rightarrow bool$  **where**

$consensus-anonymity c \equiv$   
 $(\forall A V p \pi :: ('v \Rightarrow 'v)).$   
 $bij \pi \longrightarrow$   
 $(let (A', V', q) = (rename \pi (A, V, p)) in$   
 $profile V A p \longrightarrow profile V' A' q$   
 $\longrightarrow c (A, V, p) \longrightarrow c (A', V', q)))$

**fun**  $consensus-neutrality :: ('a, 'v) Election set \Rightarrow ('a, 'v) Consensus \Rightarrow bool$  **where**  
 $consensus-neutrality X c = is-symmetry c (Invariance (neutrality_{\mathcal{R}} X))$

### 4.3.4 Auxiliary Lemmas

**lemma**  $cons-anon-conj$ :

**fixes**  $c c' :: ('a, 'v) Consensus$   
**assumes**  
 $consensus-anonymity c$  **and**

$\text{consensus-anonymity } c'$   
**shows**  $\text{consensus-anonymity } (\lambda e. c\ e \wedge c'\ e)$   
**proof** (*unfold consensus-anonymity-def Let-def, clarify*)  
**fix**  
 $A\ A' :: 'a\ \text{set}$  **and**  
 $V\ V' :: 'v\ \text{set}$  **and**  
 $p\ q :: ('a, 'v)\ \text{Profile}$  **and**  
 $\pi :: 'v \Rightarrow 'v$   
**assume**  
 $\text{bij-}\pi$ :  $\text{bij } \pi$  **and**  
 $\text{renamed}$ :  $\text{rename } \pi\ (A, V, p) = (A', V', q)$  **and**  
 $\text{prof}$ :  $\text{profile } V\ A\ p$   
**hence**  $\text{profile } V'\ A'\ q$   
**using**  $\text{rename-sound fst-conv rename.simps}$   
**by** *metis*  
**moreover assume**  
 $c\ (A, V, p)$  **and**  
 $c'\ (A, V, p)$   
**ultimately show**  $c\ (A', V', q) \wedge c'\ (A', V', q)$   
**using**  $\text{bij-}\pi\ \text{renamed assms prof}$   
**unfolding**  $\text{consensus-anonymity-def}$   
**by** *auto*  
**qed**

**theorem**  $\text{cons-conjunction-invariant}$ :  
**fixes**  
 $\mathfrak{C} :: ('a, 'v)\ \text{Consensus set}$  **and**  
 $\text{rel} :: ('a, 'v)\ \text{Election rel}$   
**defines**  $C \equiv \lambda E. \forall C' \in \mathfrak{C}. C' E$   
**assumes**  $\forall C'. C' \in \mathfrak{C} \longrightarrow \text{is-symmetry } C' (\text{Invariance rel})$   
**shows**  $\text{is-symmetry } C (\text{Invariance rel})$   
**proof** (*unfold is-symmetry.simps, intro allI impI*)  
**fix**  $E\ E' :: ('a, 'v)\ \text{Election}$   
**assume**  $(E, E') \in \text{rel}$   
**hence**  $\forall C' \in \mathfrak{C}. C' E = C' E'$   
**using** *assms*  
**unfolding**  $\text{is-symmetry.simps}$   
**by** *blast*  
**thus**  $C E = C E'$   
**unfolding**  $C\text{-def}$   
**by** *blast*  
**qed**

**lemma**  $\text{cons-anon-invariant}$ :  
**fixes**  
 $c :: ('a, 'v)\ \text{Consensus}$  **and**  
 $A\ A' :: 'a\ \text{set}$  **and**  
 $V\ V' :: 'v\ \text{set}$  **and**  
 $p\ q :: ('a, 'v)\ \text{Profile}$  **and**

$\pi :: 'v \Rightarrow 'v$   
**assumes**  
*anon*: *consensus-anonymity* *c* **and**  
*bij- $\pi$* : *bij*  $\pi$  **and**  
*prof-p*: *profile* *V A p* **and**  
*renamed*: *rename*  $\pi (A, V, p) = (A', V', q)$  **and**  
*cond-c*: *c*  $(A, V, p)$   
**shows** *c*  $(A', V', q)$   
**proof** –  
**have** *profile* *V' A' q*  
**using** *rename-sound* *bij- $\pi$*  *renamed* *prof-p*  
**by** *fastforce*  
**thus** *?thesis*  
**using** *anon* *cond-c* *renamed* *rename-finite* *bij- $\pi$*  *prof-p*  
**unfolding** *consensus-anonymity-def* *Let-def*  
**by** *auto*  
**qed**

**lemma** *ex-anon-cons-imp-cons-anonymous*:  
**fixes**  
 $b :: ('a, 'v) \text{ Consensus}$  **and**  
 $b' :: 'b \Rightarrow ('a, 'v) \text{ Consensus}$   
**assumes**  
*general-cond-b*:  $b = (\lambda E. \exists x. b' x E)$  **and**  
*all-cond-anon*:  $\forall x. \text{consensus-anonymity } (b' x)$   
**shows** *consensus-anonymity* *b*  
**proof** (*unfold consensus-anonymity-def* *Let-def*, *safe*)  
**fix**  
 $A A' :: 'a \text{ set}$  **and**  
 $V V' :: 'v \text{ set}$  **and**  
 $p q :: ('a, 'v) \text{ Profile}$  **and**  
 $\pi :: 'v \Rightarrow 'v$   
**assume**  
*bij- $\pi$* : *bij*  $\pi$  **and**  
*cond-b*: *b*  $(A, V, p)$  **and**  
*prof-p*: *profile* *V A p* **and**  
*renamed*: *rename*  $\pi (A, V, p) = (A', V', q)$   
**have**  $\exists x. b' x (A, V, p)$   
**using** *cond-b* *general-cond-b*  
**by** *simp*  
**then obtain**  $x :: 'b$  **where**  
 $b' x (A, V, p)$   
**by** *blast*  
**moreover have** *consensus-anonymity*  $(b' x)$   
**using** *all-cond-anon*  
**by** *simp*  
**moreover have** *profile* *V' A' q*  
**using** *prof-p* *renamed* *bij- $\pi$*  *rename-sound*  
**by** *fastforce*

**ultimately have**  $b' x (A', V', q)$   
**using** *all-cond-anon bij- $\pi$  prof-p renamed*  
**unfolding** *consensus-anonymity-def*  
**by** *auto*  
**hence**  $\exists x. b' x (A', V', q)$   
**by** *metis*  
**thus**  $b (A', V', q)$   
**using** *general-cond-b*  
**by** *simp*  
**qed**

### 4.3.5 Theorems

#### Anonymity

**lemma** *nonempty-set-cons-anonymous: consensus-anonymity nonempty-set<sub>C</sub>*  
**unfolding** *consensus-anonymity-def*  
**by** *simp*

**lemma** *nonempty-profile-cons-anonymous: consensus-anonymity nonempty-profile<sub>C</sub>*

**proof** (*unfold consensus-anonymity-def Let-def, clarify*)

**fix**

$A \ A' :: 'a \text{ set}$  **and**

$V \ V' :: 'v \text{ set}$  **and**

$p \ q :: ('a, 'v) \text{ Profile}$  **and**

$\pi :: 'v \Rightarrow 'v$

**assume**

*bij- $\pi$ : bij  $\pi$*  **and**

*renamed: rename  $\pi (A, V, p) = (A', V', q)$*

**hence**  $\text{card } V = \text{card } V'$

**using** *rename.simps Pair-inject bij-betw-same-card*

*bij-betw-subset top-greatest*

**by** (*metis (mono-tags, lifting)*)

**moreover assume** *nonempty-profile<sub>C</sub> (A, V, p)*

**ultimately show** *nonempty-profile<sub>C</sub> (A', V', q)*

**using** *length-0-conv renamed*

**unfolding** *nonempty-profile<sub>C</sub>.simps*

**by** *auto*

**qed**

**lemma** *equal-top-cons'-anonymous:*

**fixes**  $a :: 'a$

**shows** *consensus-anonymity (equal-top<sub>C</sub> 'a)*

**proof** (*unfold consensus-anonymity-def Let-def, clarify*)

**fix**

$A \ A' :: 'a \text{ set}$  **and**

$V \ V' :: 'v \text{ set}$  **and**

$p \ q :: ('a, 'v) \text{ Profile}$  **and**

$\pi :: 'v \Rightarrow 'v$

**assume**



**bij- $\pi$ :** *bij*  $\pi$  **and**  
**prof- $p$ :** *profile*  $V$   $A$   $p$  **and**  
**renamed:** *rename*  $\pi$   $(A, V, p) = (A', V', q)$  **and**  
**top-cons-a:** *equal-top<sub>C</sub>' a*  $(A, V, p)$   
**have**  $\forall v' \in V'. q\ v' = p\ ((the\text{-}inv\ \pi)\ v')$   
**using** *renamed*  
**by** *auto*  
**moreover have**  $\forall v' \in V'. (the\text{-}inv\ \pi)\ v' \in V$   
**using** *bij- $\pi$  renamed rename.simps bij-is-inj*  
*f-the-inv-into-f-bij-betw inj-image-mem-iff*  
**by** *fastforce*  
**moreover have** *winner:*  $\forall v \in V. above\ (p\ v)\ a = \{a\}$   
**using** *top-cons-a*  
**by** *simp*  
**ultimately have**  $\forall v' \in V'. above\ (q\ v')\ a = \{a\}$   
**by** *simp*  
**moreover have**  $a \in A$   
**using** *top-cons-a*  
**by** *simp*  
**ultimately show** *equal-top<sub>C</sub>' a*  $(A', V', q)$   
**using** *renamed*  
**unfolding** *equal-top<sub>C</sub>'.simps*  
**by** *simp*  
**qed**

**lemma** *eq-top-cons-anon: consensus-anonymity equal-top<sub>C</sub>*  
**using** *equal-top-cons'-anonymous*  
*ex-anon-cons-imp-cons-anonymous[of equal-top<sub>C</sub> equal-top<sub>C</sub>']*  
**by** *fastforce*

**lemma** *eq-vote-cons'-anonymous:*  
**fixes**  $r :: 'a\ Preference\text{-}Relation$   
**shows** *consensus-anonymity*  $(equal\text{-}vote_C'\ r)$   
**proof** *(unfold consensus-anonymity-def Let-def, clarify)*  
**fix**  
 $A\ A' :: 'a\ set$  **and**  
 $V\ V' :: 'v\ set$  **and**  
 $p\ q :: ('a, 'v)\ Profile$  **and**  
 $\pi :: 'v \Rightarrow 'v$   
**assume**  
**bij- $\pi$ :** *bij*  $\pi$  **and**  
**renamed:** *rename*  $\pi$   $(A, V, p) = (A', V', q)$   
**have**  $\forall v' \in V'. (the\text{-}inv\ \pi)\ v' \in V$   
**using** *bij- $\pi$  renamed bij-is-inj inj-image-mem-iff*  
*f-the-inv-into-f-bij-betw*  
**by** *fastforce*  
**moreover assume** *equal-vote<sub>C</sub>' r*  $(A, V, p)$   
**ultimately show** *equal-vote<sub>C</sub>' r*  $(A', V', q)$   
**using** *renamed*

by force  
qed

**lemma** *eq-vote-cons-anonymous: consensus-anonymity equal-vote<sub>C</sub>*  
**unfolding** *equal-vote<sub>C</sub>.sims*  
**using** *eq-vote-cons'-anonymous ex-anon-cons-imp-cons-anonymous*  
**by** *blast*

## Neutrality

**lemma** *nonempty-set<sub>C</sub>-neutral: consensus-neutrality well-formed-elections nonempty-set<sub>C</sub>*  
**unfolding** *well-formed-elections-def*  
**by** *auto*

**lemma** *nonempty-profile<sub>C</sub>-neutral: consensus-neutrality well-formed-elections nonempty-profile<sub>C</sub>*  
**unfolding** *well-formed-elections-def*  
**by** *auto*

**lemma** *equal-vote<sub>C</sub>-neutral: consensus-neutrality well-formed-elections equal-vote<sub>C</sub>*  
**proof** (*unfold well-formed-elections-def consensus-neutrality.sims is-symmetry.sims,*  
*intro allI impI,*  
*unfold split-paired-all neutrality<sub>R</sub>.sims action-induced-rel.sims*  
*voters- $\mathcal{E}$ .sims alternatives- $\mathcal{E}$ .sims profile- $\mathcal{E}$ .sims  $\varphi$ -neutral.sims*  
*extensional-continuation.sims equal-vote<sub>C</sub>.sims equal-vote<sub>C</sub>'.sims*  
*alternatives-rename.sims case-prod-unfold mem-Collect-eq fst-conv*  
*snd-conv mem-Sigma-iff conj-assoc If-def simp-thms, safe)*

**fix**  
 $A \ A' :: 'a \text{ set}$  **and**  
 $V \ V' :: 'v \text{ set}$  **and**  
 $p \ p' :: ('a, 'v) \text{ Profile}$  **and**  
 $\pi :: 'a \Rightarrow 'a$  **and**  
 $r :: 'a \text{ rel}$

**assume**  
 $\text{profile } V \ A \ p$  **and**  
 $(THE \ z. \ (\text{profile } V \ A \ p \longrightarrow z = (\pi \text{ ` } A, V, \text{rel-rename } \pi \circ p)))$   
 $\wedge (\neg \text{profile } V \ A \ p \longrightarrow z = \text{undefined}) = (A', V', p')$

**hence**  
*equal-voters:*  $V' = V$  **and**  
*perm-profile:*  $p' = (\lambda x. \{(\pi \ a, \pi \ b) \mid a \ b. (a, b) \in p \ x\})$   
**unfolding** *comp-def*  
**by** (*simp, simp*)

**have**  
 $(\forall v \in V. p \ v = r)$   
 $\longrightarrow (\exists r'. \forall v \in V. \{(\pi \ a, \pi \ b) \mid a \ b. (a, b) \in p \ v\} = r')$   
**by** *simp*  
**{**  
**moreover assume**  $\forall v' \in V. p \ v' = r$   
**ultimately show**  $\exists r. \forall v \in V'. p' \ v = r$

```

    using equal-voters perm-profile
    by metis
  }
  assume  $\pi \in \text{carrier bijection}_{AG}$ 
  hence  $\text{bij } \pi$ 
    using rewrite-carrier
    unfolding  $\text{bijection}_{AG}\text{-def}$ 
    by blast
  hence  $\forall a. \text{the-inv } \pi (\pi a) = a$ 
    using  $\text{bij-is-inj the-inv-f-f}$ 
    by metis
  moreover have
     $(\forall v \in V. \{(\pi a, \pi b) \mid a b. (a, b) \in p v\} = r) \longrightarrow$ 
     $(\forall v \in V. \{(\text{the-inv } \pi (\pi a), \text{the-inv } \pi (\pi b)) \mid a b. (a, b) \in p v\} =$ 
     $\{(\text{the-inv } \pi a, \text{the-inv } \pi b) \mid a b. (a, b) \in r\})$ 
    by fastforce
  ultimately have
     $(\forall v \in V. \{(\pi a, \pi b) \mid a b. (a, b) \in p v\} = r) \longrightarrow$ 
     $(\forall v \in V. \{(a, b) \mid a b. (a, b) \in p v\} =$ 
     $\{(\text{the-inv } \pi a, \text{the-inv } \pi b) \mid a b. (a, b) \in r\})$ 
    by auto
  hence
     $(\forall v' \in V. \{(\pi a, \pi b) \mid a b. (a, b) \in p v'\} = r)$ 
     $\longrightarrow (\exists r'. \forall v' \in V. p v' = r')$ 
    by simp
  moreover assume  $\forall v' \in V'. p' v' = r$ 
  ultimately show  $\exists r'. \forall v' \in V. p v' = r'$ 
    using equal-voters perm-profile
    by metis
qed

lemma strong-unanimityC-neutral: consensus-neutrality
  well-formed-elections strong-unanimityC
  using nonempty-setC-neutral equal-voteC-neutral nonempty-profileC-neutral
  cons-conjunction-invariant[of
    {nonempty-setC, nonempty-profileC, equal-voteC}
    neutralityR well-formed-elections]
  unfolding strong-unanimityC.simps
  by fastforce

end

```

## 4.4 Electoral Module

```
theory Electoral-Module
  imports Social-Choice-Types/Property-Interpretations
begin
```

Electoral modules are the principal component type of the composable modules voting framework, as they are a generalization of voting rules in the sense of social choice functions. These are only the types used for electoral modules. Further restrictions are encompassed by the electoral-module predicate.

An electoral module does not need to make final decisions for all alternatives, but can instead defer the decision for some or all of them to other modules. Hence, electoral modules partition the received (possibly empty) set of alternatives into elected, rejected and deferred alternatives. In particular, any of those sets, e.g., the set of winning (elected) alternatives, may also be left empty, as long as they collectively still hold all the received alternatives. Just like a voting rule, an electoral module also receives a profile which holds the voters preferences, which, unlike a voting rule, consider only the (sub-)set of alternatives that the module receives.

### 4.4.1 Definition

An electoral module maps an election to a result. To enable currying, the Election type is not used here because that would require tuples.

```
type-synonym ('a, 'v, 'r) Electoral-Module = 'v set  $\Rightarrow$  'a set  $\Rightarrow$ 
  ('a, 'v) Profile  $\Rightarrow$  'r
```

```
fun funE :: ('v set  $\Rightarrow$  'a set  $\Rightarrow$  ('a, 'v) Profile  $\Rightarrow$  'r)  $\Rightarrow$ 
  (('a, 'v) Election  $\Rightarrow$  'r) where
  funE m = ( $\lambda$  E. m (voters- $\mathcal{E}$  E) (alternatives- $\mathcal{E}$  E) (profile- $\mathcal{E}$  E))
```

The next three functions take an electoral module and turn it into a function only outputting the elect, reject, or defer set respectively.

```
abbreviation elect :: ('a, 'v, 'r Result) Electoral-Module  $\Rightarrow$  'v set  $\Rightarrow$  'a set  $\Rightarrow$ 
  ('a, 'v) Profile  $\Rightarrow$  'r where
  elect m V A p  $\equiv$  elect-r (m V A p)
```

```
abbreviation reject :: ('a, 'v, 'r Result) Electoral-Module  $\Rightarrow$  'v set  $\Rightarrow$  'a set  $\Rightarrow$ 
  ('a, 'v) Profile  $\Rightarrow$  'r where
  reject m V A p  $\equiv$  reject-r (m V A p)
```

```
abbreviation defer :: ('a, 'v, 'r Result) Electoral-Module  $\Rightarrow$  'v set  $\Rightarrow$  'a set  $\Rightarrow$ 
  ('a, 'v) Profile  $\Rightarrow$  'r where
  defer m V A p  $\equiv$  defer-r (m V A p)
```

#### 4.4.2 Auxiliary Definitions

Electoral modules partition a given set of alternatives  $A$  into a set of elected alternatives  $e$ , a set of rejected alternatives  $r$ , and a set of deferred alternatives  $d$ , using a profile.  $e$ ,  $r$ , and  $d$  partition  $A$ . Electoral modules can be used as voting rules. They can also be composed in multiple structures to create more complex electoral modules.

**fun** (in result) electoral-module :: ('a, 'v, ('r Result)) Electoral-Module  $\Rightarrow$  bool **where**  
 electoral-module  $m = (\forall A V p. \text{profile } V A p \longrightarrow \text{well-formed } A (m V A p))$

**fun** voters-determine-election :: ('a, 'v, ('r Result)) Electoral-Module  $\Rightarrow$  bool **where**  
 voters-determine-election  $m =$   
 $(\forall A V p p'. (\forall v \in V. p v = p' v) \longrightarrow m V A p = m V A p')$

**lemma** (in result) electoral-modI:  
**fixes**  $m :: ('a, 'v, ('r Result)) \text{ Electoral-Module}$   
**assumes**  $\forall A V p. \text{profile } V A p \longrightarrow \text{well-formed } A (m V A p)$   
**shows** electoral-module  $m$   
**unfolding** electoral-module.simps  
**using** assms  
**by** simp

#### 4.4.3 Auxiliary Properties

We only require voting rules to behave a specific way on admissible elections, i.e., elections that are valid profiles (= votes are linear orders on the alternatives). Note that we do not assume finiteness for the sets of voters or alternatives by default.

**fun** anonymity-in :: ('a, 'v) Election set  $\Rightarrow$  ('a, 'v, 'r) Electoral-Module  $\Rightarrow$  bool **where**  
 anonymity-in  $X m = \text{is-symmetry } (\text{fun}_{\mathcal{E}} m) (\text{Invariance } (\text{anonymity}_{\mathcal{R}} X))$

**fun** homogeneity-in :: ('a, 'v) Election set  $\Rightarrow$   
 ('a, 'v, 'r Result) Electoral-Module  $\Rightarrow$  bool **where**  
 homogeneity-in  $X m = \text{is-symmetry } (\text{fun}_{\mathcal{E}} m) (\text{Invariance } (\text{homogeneity}_{\mathcal{R}} X))$

— This does not require any specific behaviour on infinite voter sets ... It might make sense to extend the definition to that case somehow.

**fun** homogeneity'-in :: ('a, 'v :: linorder) Election set  $\Rightarrow$   
 ('a, 'v, 'b Result) Electoral-Module  $\Rightarrow$  bool **where**  
 homogeneity'-in  $X m = \text{is-symmetry } (\text{fun}_{\mathcal{E}} m) (\text{Invariance } (\text{homogeneity}_{\mathcal{R}}' X))$

**fun** (in result-properties) neutrality-in :: ('a, 'v) Election set  $\Rightarrow$   
 ('a, 'v, 'b Result) Electoral-Module  $\Rightarrow$  bool **where**  
 neutrality-in  $X m =$   
 $\text{is-symmetry } (\text{fun}_{\mathcal{E}} m) (\text{action-induced-equivariance } (\text{carrier bijection}_{AG}) X$   
 $(\varphi\text{-neutral } X) (\text{result-action } \psi))$

#### 4.4.4 Social-Choice Modules

The following results require electoral modules to return social choice results, i.e., sets of elected, rejected and deferred alternatives. In order to export code, we use the hack provided by Locale-Code.

"defers n" is true for all electoral modules that defer exactly n alternatives, whenever there are n or more alternatives.

**definition** *defers* :: nat  $\Rightarrow$  ('a, 'v, 'a Result) Electoral-Module  $\Rightarrow$  bool **where**  
*defers* n m  $\equiv$   
 SCF-result.electoral-module m  $\wedge$   
 ( $\forall$  A V p. (card A  $\geq$  n  $\wedge$  finite A  $\wedge$  profile V A p)  
 $\longrightarrow$  card (defer m V A p) = n)

"rejects n" is true for all electoral modules that reject exactly n alternatives, whenever there are n or more alternatives.

**definition** *rejects* :: nat  $\Rightarrow$  ('a, 'v, 'a Result) Electoral-Module  $\Rightarrow$  bool **where**  
*rejects* n m  $\equiv$   
 SCF-result.electoral-module m  $\wedge$   
 ( $\forall$  A V p. (card A  $\geq$  n  $\wedge$  finite A  $\wedge$  profile V A p)  
 $\longrightarrow$  card (reject m V A p) = n)

As opposed to "rejects", "eliminates" allows to stop rejecting if no alternatives were to remain.

**definition** *eliminates* :: nat  $\Rightarrow$  ('a, 'v, 'a Result) Electoral-Module  $\Rightarrow$  bool **where**  
*eliminates* n m  $\equiv$   
 SCF-result.electoral-module m  $\wedge$   
 ( $\forall$  A V p. (card A > n  $\wedge$  profile V A p)  $\longrightarrow$  card (reject m V A p) = n)

"elects n" is true for all electoral modules that elect exactly n alternatives, whenever there are n or more alternatives.

**definition** *elects* :: nat  $\Rightarrow$  ('a, 'v, 'a Result) Electoral-Module  $\Rightarrow$  bool **where**  
*elects* n m  $\equiv$   
 SCF-result.electoral-module m  $\wedge$   
 ( $\forall$  A V p. (card A  $\geq$  n  $\wedge$  profile V A p)  $\longrightarrow$  card (elect m V A p) = n)

An electoral module is independent of an alternative a iff a's ranking does not influence the outcome.

**definition** *indep-of-alt* :: ('a, 'v, 'a Result) Electoral-Module  $\Rightarrow$  'v set  $\Rightarrow$   
 'a set  $\Rightarrow$  'a  $\Rightarrow$  bool **where**  
*indep-of-alt* m V A a  $\equiv$   
 SCF-result.electoral-module m  
 $\wedge$  ( $\forall$  p q. equiv-prof-except-a V A p q a  $\longrightarrow$  m V A p = m V A q)

**definition** *unique-winner-if-profile-non-empty* :: ('a, 'v, 'a Result)  
 Electoral-Module  $\Rightarrow$  bool **where**  
*unique-winner-if-profile-non-empty* m  $\equiv$

$SCF\text{-}result.electoral\text{-}module\ m \wedge$   
 $(\forall\ A\ V\ p.\ (A \neq \{\}\ \wedge\ V \neq \{\}\ \wedge\ profile\ V\ A\ p) \longrightarrow$   
 $(\exists\ a \in A.\ m\ V\ A\ p = (\{a\},\ A - \{a\},\ \{\})))$

#### 4.4.5 Equivalence Definitions

**definition**  $prof\text{-}contains\text{-}result :: ('a, 'v, 'a\ Result)\ Electoral\text{-}Module \Rightarrow 'v\ set \Rightarrow$   
 $'a\ set \Rightarrow ('a, 'v)\ Profile \Rightarrow ('a, 'v)\ Profile \Rightarrow 'a \Rightarrow bool\ \mathbf{where}$   
 $prof\text{-}contains\text{-}result\ m\ V\ A\ p\ q\ a \equiv$   
 $SCF\text{-}result.electoral\text{-}module\ m \wedge$   
 $profile\ V\ A\ p \wedge profile\ V\ A\ q \wedge a \in A \wedge$   
 $(a \in elect\ m\ V\ A\ p \longrightarrow a \in elect\ m\ V\ A\ q) \wedge$   
 $(a \in reject\ m\ V\ A\ p \longrightarrow a \in reject\ m\ V\ A\ q) \wedge$   
 $(a \in defer\ m\ V\ A\ p \longrightarrow a \in defer\ m\ V\ A\ q)$

**definition**  $prof\text{-}leq\text{-}result :: ('a, 'v, 'a\ Result)\ Electoral\text{-}Module \Rightarrow 'v\ set \Rightarrow$   
 $'a\ set \Rightarrow ('a, 'v)\ Profile \Rightarrow ('a, 'v)\ Profile \Rightarrow 'a \Rightarrow bool\ \mathbf{where}$   
 $prof\text{-}leq\text{-}result\ m\ V\ A\ p\ q\ a \equiv$   
 $SCF\text{-}result.electoral\text{-}module\ m \wedge$   
 $profile\ V\ A\ p \wedge profile\ V\ A\ q \wedge a \in A \wedge$   
 $(a \in reject\ m\ V\ A\ p \longrightarrow a \in reject\ m\ V\ A\ q) \wedge$   
 $(a \in defer\ m\ V\ A\ p \longrightarrow a \notin elect\ m\ V\ A\ q)$

**definition**  $prof\text{-}geq\text{-}result :: ('a, 'v, 'a\ Result)\ Electoral\text{-}Module \Rightarrow 'v\ set \Rightarrow$   
 $'a\ set \Rightarrow ('a, 'v)\ Profile \Rightarrow ('a, 'v)\ Profile \Rightarrow 'a \Rightarrow bool\ \mathbf{where}$   
 $prof\text{-}geq\text{-}result\ m\ V\ A\ p\ q\ a \equiv$   
 $SCF\text{-}result.electoral\text{-}module\ m \wedge$   
 $profile\ V\ A\ p \wedge profile\ V\ A\ q \wedge a \in A \wedge$   
 $(a \in elect\ m\ V\ A\ p \longrightarrow a \in elect\ m\ V\ A\ q) \wedge$   
 $(a \in defer\ m\ V\ A\ p \longrightarrow a \notin reject\ m\ V\ A\ q)$

**definition**  $mod\text{-}contains\text{-}result :: ('a, 'v, 'a\ Result)\ Electoral\text{-}Module \Rightarrow$   
 $('a, 'v, 'a\ Result)\ Electoral\text{-}Module \Rightarrow 'v\ set \Rightarrow 'a\ set \Rightarrow$   
 $('a, 'v)\ Profile \Rightarrow 'a \Rightarrow bool\ \mathbf{where}$   
 $mod\text{-}contains\text{-}result\ m\ n\ V\ A\ p\ a \equiv$   
 $SCF\text{-}result.electoral\text{-}module\ m \wedge$   
 $SCF\text{-}result.electoral\text{-}module\ n \wedge$   
 $profile\ V\ A\ p \wedge a \in A \wedge$   
 $(a \in elect\ m\ V\ A\ p \longrightarrow a \in elect\ n\ V\ A\ p) \wedge$   
 $(a \in reject\ m\ V\ A\ p \longrightarrow a \in reject\ n\ V\ A\ p) \wedge$   
 $(a \in defer\ m\ V\ A\ p \longrightarrow a \in defer\ n\ V\ A\ p)$

**definition**  $mod\text{-}contains\text{-}result\text{-}sym :: ('a, 'v, 'a\ Result)\ Electoral\text{-}Module \Rightarrow$   
 $('a, 'v, 'a\ Result)\ Electoral\text{-}Module \Rightarrow 'v\ set \Rightarrow 'a\ set \Rightarrow$   
 $('a, 'v)\ Profile \Rightarrow 'a \Rightarrow bool\ \mathbf{where}$   
 $mod\text{-}contains\text{-}result\text{-}sym\ m\ n\ V\ A\ p\ a \equiv$   
 $SCF\text{-}result.electoral\text{-}module\ m \wedge$   
 $SCF\text{-}result.electoral\text{-}module\ n \wedge$   
 $profile\ V\ A\ p \wedge a \in A \wedge$

$$(a \in \text{elect } m \ V \ A \ p \longleftrightarrow a \in \text{elect } n \ V \ A \ p) \wedge$$

$$(a \in \text{reject } m \ V \ A \ p \longleftrightarrow a \in \text{reject } n \ V \ A \ p) \wedge$$

$$(a \in \text{defer } m \ V \ A \ p \longleftrightarrow a \in \text{defer } n \ V \ A \ p)$$

#### 4.4.6 Auxiliary Lemmas

**lemma** *elect-rej-def-combination:*

**fixes**

$m :: ('a, 'v, 'a \text{ Result}) \text{ Electoral-Module}$  **and**

$V :: 'v \text{ set}$  **and**

$A :: 'a \text{ set}$  **and**

$p :: ('a, 'v) \text{ Profile}$  **and**

$e \ r \ d :: 'a \text{ set}$

**assumes**

$\text{elect } m \ V \ A \ p = e$  **and**

$\text{reject } m \ V \ A \ p = r$  **and**

$\text{defer } m \ V \ A \ p = d$

**shows**  $m \ V \ A \ p = (e, r, d)$

**using** *assms*

**by** *auto*

**lemma** *par-comp-result-sound:*

**fixes**

$m :: ('a, 'v, 'a \text{ Result}) \text{ Electoral-Module}$  **and**

$A :: 'a \text{ set}$  **and**

$p :: ('a, 'v) \text{ Profile}$

**assumes**

$\text{SCF-result.electoral-module } m$  **and**

$\text{profile } V \ A \ p$

**shows**  $\text{well-formed-SCF } A \ (m \ V \ A \ p)$

**using** *assms*

**by** *simp*

**lemma** *result-presv-alts:*

**fixes**

$m :: ('a, 'v, 'a \text{ Result}) \text{ Electoral-Module}$  **and**

$A :: 'a \text{ set}$  **and**

$V :: 'v \text{ set}$  **and**

$p :: ('a, 'v) \text{ Profile}$

**assumes**

$\text{SCF-result.electoral-module } m$  **and**

$\text{profile } V \ A \ p$

**shows**  $(\text{elect } m \ V \ A \ p) \cup (\text{reject } m \ V \ A \ p) \cup (\text{defer } m \ V \ A \ p) = A$

**proof** (*safe*)

**fix**  $a :: 'a$

**have**

*partition-imp-exist:*

$\forall \ p'. \text{ set-equals-partition } A \ p'$

$\longrightarrow (\exists \ E \ R \ D. p' = (E, R, D) \wedge E \cup R \cup D = A)$  **and**



```

partition-A:
  set-equals-partition A (m V A p)
  using assms
  by (simp, simp)
{
  assume a ∈ elect m V A p
  with partition-imp-exist partition-A
  show a ∈ A
    using UnI1 fstI
    by (metis (no-types))
}
{
  assume a ∈ reject m V A p
  with partition-imp-exist partition-A
  show a ∈ A
    using UnI1 fstI sndI subsetD sup-ge2
    by metis
}
{
  assume a ∈ defer m V A p
  with partition-imp-exist partition-A
  show a ∈ A
    using sndI subsetD sup-ge2
    by metis
}
{
  assume
    a ∈ A and
    a ∉ defer m V A p and
    a ∉ reject m V A p
  with partition-imp-exist partition-A
  show a ∈ elect m V A p
    using fst-conv snd-conv Un-iff
    by metis
}
qed

```

**lemma** *result-disj*:

**fixes**

*m* :: (*'a*, *'v*, *'a Result*) *Electoral-Module* **and**

*A* :: *'a set* **and**

*p* :: (*'a*, *'v*) *Profile* **and**

*V* :: *'v set*

**assumes**

*SCF-result.electoral-module m* **and**

*profile V A p*

**shows**

$(\text{elect } m \ V \ A \ p) \cap (\text{reject } m \ V \ A \ p) = \{\} \wedge$   
 $(\text{elect } m \ V \ A \ p) \cap (\text{defer } m \ V \ A \ p) = \{\} \wedge$

```

      (reject m V A p) ∩ (defer m V A p) = {}
proof (safe)
  fix a :: 'a
  have wf: well-formed-SCF A (m V A p)
    using assms
    unfolding SCF-result.electoral-module.simps
    by metis
  have disj: disjoint3 (m V A p)
    using assms
    by simp
  {
    assume
      a ∈ elect m V A p and
      a ∈ reject m V A p
    with wf disj
    show a ∈ {}
      using prod.exhaust-sel DiffE UnCI result-imp-rej
      by (metis (no-types))
  }
  {
    assume
      elect-a: a ∈ elect m V A p and
      defer-a: a ∈ defer m V A p
    then obtain
      e :: 'a Result ⇒ 'a set and
      r :: 'a Result ⇒ 'a set and
      d :: 'a Result ⇒ 'a set
    where
      m V A p =
        (e (m V A p), r (m V A p), d (m V A p)) ∧
        e (m V A p) ∩ r (m V A p) = {} ∧
        e (m V A p) ∩ d (m V A p) = {} ∧
        r (m V A p) ∩ d (m V A p) = {}
      using IntI emptyE prod.collapse disj disjoint3.simps
      by metis
    hence ((elect m V A p) ∩ (reject m V A p) = {}) ∧
      ((elect m V A p) ∩ (defer m V A p) = {}) ∧
      ((reject m V A p) ∩ (defer m V A p) = {})
      using eq-snd-iff fstI
      by metis
    thus a ∈ {}
      using elect-a defer-a disjoint-iff-not-equal
      by (metis (no-types))
  }
  {
    assume
      a ∈ reject m V A p and
      a ∈ defer m V A p
    with wf disj

```

```

    show  $a \in \{\}$ 
    using prod.exhaust-sel DiffE UnCI result-imp-rej
    by (metis (no-types))
  }
qed

```

```

lemma elect-in-alts:
  fixes
     $m :: ('a, 'v, 'a \text{ Result}) \text{ Electoral-Module}$  and
     $A :: 'a \text{ set}$  and
     $p :: ('a, 'v) \text{ Profile}$ 
  assumes
    SCF-result.electoral-module m and
    profile V A p
  shows elect m V A p  $\subseteq A$ 
  using le-supI1 assms result-presv-alts sup-ge1
  by metis

```

```

lemma reject-in-alts:
  fixes
     $m :: ('a, 'v, 'a \text{ Result}) \text{ Electoral-Module}$  and
     $A :: 'a \text{ set}$  and
     $V :: 'v \text{ set}$  and
     $p :: ('a, 'v) \text{ Profile}$ 
  assumes
    SCF-result.electoral-module m and
    profile V A p
  shows reject m V A p  $\subseteq A$ 
  using le-supI1 assms result-presv-alts sup-ge2
  by metis

```

```

lemma defer-in-alts:
  fixes
     $m :: ('a, 'v, 'a \text{ Result}) \text{ Electoral-Module}$  and
     $A :: 'a \text{ set}$  and
     $V :: 'v \text{ set}$  and
     $p :: ('a, 'v) \text{ Profile}$ 
  assumes
    SCF-result.electoral-module m and
    profile V A p
  shows defer m V A p  $\subseteq A$ 
  using assms result-presv-alts
  by fastforce

```

```

lemma def-presv-prof:
  fixes
     $m :: ('a, 'v, 'a \text{ Result}) \text{ Electoral-Module}$  and
     $A :: 'a \text{ set}$  and
     $p :: ('a, 'v) \text{ Profile}$ 

```

**assumes**  
*SCF-result.electoral-module*  $m$  **and**  
*profile*  $V A p$   
**shows** *let new-A = defer m V A p in profile V new-A (limit-profile new-A p)*  
**using** *defer-in-alts limit-profile-sound assms*  
**by** *metis*

An electoral module can never reject, defer or elect more than  $|A|$  alternatives.

**lemma** *upper-card-bounds-for-result:*  
**fixes**  
 $m :: ('a, 'v, 'a \text{ Result}) \text{ Electoral-Module}$  **and**  
 $A :: 'a \text{ set}$  **and**  
 $V :: 'v \text{ set}$  **and**  
 $p :: ('a, 'v) \text{ Profile}$   
**assumes**  
*SCF-result.electoral-module*  $m$  **and**  
*profile*  $V A p$  **and**  
*finite*  $A$   
**shows**  
*upper-card-bound-for-elect:*  $\text{card } (\text{elect } m V A p) \leq \text{card } A$  **and**  
*upper-card-bound-for-reject:*  $\text{card } (\text{reject } m V A p) \leq \text{card } A$  **and**  
*upper-card-bound-for-defer:*  $\text{card } (\text{defer } m V A p) \leq \text{card } A$   
**using** *assms card-mono*  
**by** (*metis elect-in-alts,*  
*metis reject-in-alts,*  
*metis defer-in-alts*)

**lemma** *reject-not-elected-or-deferred:*  
**fixes**  
 $m :: ('a, 'v, 'a \text{ Result}) \text{ Electoral-Module}$  **and**  
 $A :: 'a \text{ set}$  **and**  
 $V :: 'v \text{ set}$  **and**  
 $p :: ('a, 'v) \text{ Profile}$   
**assumes**  
*SCF-result.electoral-module*  $m$  **and**  
*profile*  $V A p$   
**shows**  $\text{reject } m V A p = A - (\text{elect } m V A p) - (\text{defer } m V A p)$   
**proof** –  
**from** *assms* **have**  $(\text{elect } m V A p) \cup (\text{reject } m V A p) \cup (\text{defer } m V A p) = A$   
**using** *result-presv-alts*  
**by** *blast*  
**with** *assms* **show** *?thesis*  
**using** *result-disj*  
**by** *blast*  
**qed**

**lemma** *elec-and-def-not-rej:*  
**fixes**

$m :: ('a, 'v, 'a \text{ Result}) \text{ Electoral-Module}$  **and**  
 $A :: 'a \text{ set}$  **and**  
 $V :: 'v \text{ set}$  **and**  
 $p :: ('a, 'v) \text{ Profile}$   
**assumes**  
 $SCF\text{-result.electoral-module } m$  **and**  
 $profile\ V\ A\ p$   
**shows**  $elect\ m\ V\ A\ p \cup defer\ m\ V\ A\ p = A - (reject\ m\ V\ A\ p)$   
**proof** –  
**from**  $assms$  **have**  $(elect\ m\ V\ A\ p) \cup (reject\ m\ V\ A\ p) \cup (defer\ m\ V\ A\ p) = A$   
**using**  $result\text{-presv}\text{-alts}$   
**by**  $blast$   
**with**  $assms$  **show**  $?thesis$   
**using**  $result\text{-disj}$   
**by**  $blast$   
**qed**

**lemma**  $defer\text{-not}\text{-elec}\text{-or}\text{-rej}$ :

**fixes**  
 $m :: ('a, 'v, 'a \text{ Result}) \text{ Electoral-Module}$  **and**  
 $A :: 'a \text{ set}$  **and**  
 $p :: ('a, 'v) \text{ Profile}$   
**assumes**  
 $SCF\text{-result.electoral-module } m$  **and**  
 $profile\ V\ A\ p$   
**shows**  $defer\ m\ V\ A\ p = A - (elect\ m\ V\ A\ p) - (reject\ m\ V\ A\ p)$   
**proof** –  
**from**  $assms$  **have**  $(elect\ m\ V\ A\ p) \cup (reject\ m\ V\ A\ p) \cup (defer\ m\ V\ A\ p) = A$   
**using**  $result\text{-presv}\text{-alts}$   
**by**  $simp$   
**with**  $assms$  **show**  $?thesis$   
**using**  $result\text{-disj}$   
**by**  $blast$   
**qed**

**lemma**  $electoral\text{-mod}\text{-defer}\text{-elem}$ :

**fixes**  
 $m :: ('a, 'v, 'a \text{ Result}) \text{ Electoral-Module}$  **and**  
 $A :: 'a \text{ set}$  **and**  
 $V :: 'v \text{ set}$  **and**  
 $p :: ('a, 'v) \text{ Profile}$  **and**  
 $a :: 'a$   
**assumes**  
 $SCF\text{-result.electoral-module } m$  **and**  
 $profile\ V\ A\ p$  **and**  
 $a \in A$  **and**  
 $a \notin elect\ m\ V\ A\ p$  **and**  
 $a \notin reject\ m\ V\ A\ p$   
**shows**  $a \in defer\ m\ V\ A\ p$

```

using DiffI assms reject-not-elected-or-deferred
by metis

lemma mod-contains-result-comm:
  fixes
     $m\ n :: ('a, 'v, 'a\ Result)\ Electoral\ Module$  and
     $A :: 'a\ set$  and
     $V :: 'v\ set$  and
     $p :: ('a, 'v)\ Profile$  and
     $a :: 'a$ 
  assumes mod-contains-result  $m\ n\ V\ A\ p\ a$ 
  shows mod-contains-result  $n\ m\ V\ A\ p\ a$ 
proof (unfold mod-contains-result-def, safe)
  show
    SCF-result.electoral-module  $n$  and
    SCF-result.electoral-module  $m$  and
    profile  $V\ A\ p$  and
     $a \in A$ 
  using assms
  unfolding mod-contains-result-def
  by safe
next
  show
     $a \in elect\ n\ V\ A\ p \implies a \in elect\ m\ V\ A\ p$  and
     $a \in reject\ n\ V\ A\ p \implies a \in reject\ m\ V\ A\ p$  and
     $a \in defer\ n\ V\ A\ p \implies a \in defer\ m\ V\ A\ p$ 
  using assms IntI electoral-mod-defer-elem empty-iff result-disj
  unfolding mod-contains-result-def
  by (metis (mono-tags, lifting),
    metis (mono-tags, lifting),
    metis (mono-tags, lifting))
qed

lemma not-rej-imp-elec-or-defer:
  fixes
     $m :: ('a, 'v, 'a\ Result)\ Electoral\ Module$  and
     $A :: 'a\ set$  and
     $V :: 'v\ set$  and
     $p :: ('a, 'v)\ Profile$  and
     $a :: 'a$ 
  assumes
    SCF-result.electoral-module  $m$  and
    profile  $V\ A\ p$  and
     $a \in A$  and
     $a \notin reject\ m\ V\ A\ p$ 
  shows  $a \in elect\ m\ V\ A\ p \vee a \in defer\ m\ V\ A\ p$ 
  using assms electoral-mod-defer-elem
  by metis

```

**lemma** *single-elim-imp-red-def-set*:  
**fixes**  
 $m :: ('a, 'v, 'a \text{ Result}) \text{ Electoral-Module}$  **and**  
 $A :: 'a \text{ set}$  **and**  
 $V :: 'v \text{ set}$  **and**  
 $p :: ('a, 'v) \text{ Profile}$   
**assumes**  
 $\text{eliminates } 1 \ m$  **and**  
 $\text{card } A > 1$  **and**  
 $\text{profile } V \ A \ p$   
**shows**  $\text{defer } m \ V \ A \ p \subseteq A$   
**using** *Diff-eq-empty-iff Diff-subset card-eq-0-iff defer-in-alts eliminates-def*  
 $\text{eq-iff not-one-le-zero psubsetI reject-not-elected-or-deferred assms}$   
**by** (*metis (no-types, lifting)*)

**lemma** *eq-alts-in-profs-imp-eq-results*:  
**fixes**  
 $m :: ('a, 'v, 'a \text{ Result}) \text{ Electoral-Module}$  **and**  
 $A :: 'a \text{ set}$  **and**  
 $V :: 'v \text{ set}$  **and**  
 $p \ q :: ('a, 'v) \text{ Profile}$   
**assumes**  
 $\text{eq: } \forall a \in A. \text{prof-contains-result } m \ V \ A \ p \ q \ a$  **and**  
 $\text{mod-m: SCF-result.electoral-module } m$  **and**  
 $\text{prof-p: profile } V \ A \ p$  **and**  
 $\text{prof-q: profile } V \ A \ q$   
**shows**  $m \ V \ A \ p = m \ V \ A \ q$   
**proof** –  
**have**  
 $\text{elected-in-A: elect } m \ V \ A \ q \subseteq A$  **and**  
 $\text{rejected-in-A: reject } m \ V \ A \ q \subseteq A$  **and**  
 $\text{deferred-in-A: defer } m \ V \ A \ q \subseteq A$   
**using** *mod-m prof-q*  
**by** (*metis elect-in-alts, metis reject-in-alts, metis defer-in-alts*)  
**have**  
 $\forall a \in \text{elect } m \ V \ A \ p. a \in \text{elect } m \ V \ A \ q$  **and**  
 $\forall a \in \text{reject } m \ V \ A \ p. a \in \text{reject } m \ V \ A \ q$  **and**  
 $\forall a \in \text{defer } m \ V \ A \ p. a \in \text{defer } m \ V \ A \ q$   
**using** *eq mod-m prof-p in-mono*  
**unfolding** *prof-contains-result-def*  
**by** (*metis (no-types, lifting) elect-in-alts,*  
 $\text{metis (no-types, lifting) reject-in-alts,}$   
 $\text{metis (no-types, lifting) defer-in-alts}$ )  
**moreover have**  
 $\forall a \in \text{elect } m \ V \ A \ q. a \in \text{elect } m \ V \ A \ p$  **and**  
 $\forall a \in \text{reject } m \ V \ A \ q. a \in \text{reject } m \ V \ A \ p$  **and**  
 $\forall a \in \text{defer } m \ V \ A \ q. a \in \text{defer } m \ V \ A \ p$   
**proof** (*safe*)  
**fix**  $a :: 'a$

```

assume  $q\text{-elect-}a$ :  $a \in \text{elect } m \ V \ A \ q$ 
hence  $a \in A$ 
  using  $\text{elected-in-}A$ 
  by  $\text{blast}$ 
moreover have
   $a \notin \text{defer } m \ V \ A \ q$  and
   $a \notin \text{reject } m \ V \ A \ q$ 
  using  $q\text{-elect-}a \ \text{prof-}q \ \text{mod-}m \ \text{result-disj} \ \text{disjoint-iff-not-equal}$ 
  by  $(\text{metis}, \text{metis})$ 
ultimately show  $a \in \text{elect } m \ V \ A \ p$ 
  using  $\text{eq electoral-mod-defer-elem}$ 
  unfolding  $\text{prof-contains-result-def}$ 
  by  $\text{metis}$ 
next
  fix  $a :: 'a$ 
  assume  $q\text{-rejects-}a$ :  $a \in \text{reject } m \ V \ A \ q$ 
  hence  $a \in A$ 
    using  $\text{rejected-in-}A$ 
    by  $\text{blast}$ 
  moreover have
     $a \notin \text{defer } m \ V \ A \ q$  and
     $a \notin \text{elect } m \ V \ A \ q$ 
    using  $q\text{-rejects-}a \ \text{prof-}q \ \text{mod-}m \ \text{result-disj} \ \text{disjoint-iff-not-equal}$ 
    by  $(\text{metis}, \text{metis})$ 
  ultimately show  $a \in \text{reject } m \ V \ A \ p$ 
    using  $\text{eq electoral-mod-defer-elem}$ 
    unfolding  $\text{prof-contains-result-def}$ 
    by  $\text{metis}$ 
next
  fix  $a :: 'a$ 
  assume  $q\text{-defers-}a$ :  $a \in \text{defer } m \ V \ A \ q$ 
  moreover have  $a \in A$ 
    using  $q\text{-defers-}a \ \text{deferred-in-}A$ 
    by  $\text{blast}$ 
  moreover have
     $a \notin \text{elect } m \ V \ A \ q$  and
     $a \notin \text{reject } m \ V \ A \ q$ 
    using  $q\text{-defers-}a \ \text{prof-}q \ \text{mod-}m \ \text{result-disj} \ \text{disjoint-iff-not-equal}$ 
    by  $(\text{metis}, \text{metis})$ 
  ultimately show  $a \in \text{defer } m \ V \ A \ p$ 
    using  $\text{eq electoral-mod-defer-elem}$ 
    unfolding  $\text{prof-contains-result-def}$ 
    by  $\text{metis}$ 
qed
ultimately show  $?thesis$ 
  using  $\text{prod.collapse subsetI subset-antisym}$ 
  by  $(\text{metis} \ (\text{no-types}))$ 
qed

```



**lemma** *eq-def-and-elect-imp-eq*:  
**fixes**  
 $m\ n :: ('a, 'v, 'a\ Result)\ Electoral\ Module$  **and**  
 $A :: 'a\ set$  **and**  
 $V :: 'v\ set$  **and**  
 $p\ q :: ('a, 'v)\ Profile$   
**assumes**  
 $mod\text{-}m: SCF\text{-}result.electoral\text{-}module\ m$  **and**  
 $mod\text{-}n: SCF\text{-}result.electoral\text{-}module\ n$  **and**  
 $fin\text{-}p: profile\ V\ A\ p$  **and**  
 $fin\text{-}q: profile\ V\ A\ q$  **and**  
 $elec\text{-}eq: elect\ m\ V\ A\ p = elect\ n\ V\ A\ q$  **and**  
 $def\text{-}eq: defer\ m\ V\ A\ p = defer\ n\ V\ A\ q$   
**shows**  $m\ V\ A\ p = n\ V\ A\ q$   
**proof** –  
**have**  
 $reject\ m\ V\ A\ p = A - ((elect\ m\ V\ A\ p) \cup (defer\ m\ V\ A\ p))$  **and**  
 $reject\ n\ V\ A\ q = A - ((elect\ n\ V\ A\ q) \cup (defer\ n\ V\ A\ q))$   
**using** *elect-rej-def-combination result-imp-rej mod-m mod-n fin-p fin-q*  
**unfolding** *SCF-result.electoral-module.simps*  
**by** (*metis, metis*)  
**thus** *?thesis*  
**using** *prod-eqI elec-eq def-eq*  
**by** *metis*  
**qed**

**lemma** *homogeneity-in-imp-anonymity-in*:  
**fixes**  
 $X :: ('a, 'v)\ Election\ set$  **and**  
 $m :: ('a, 'v, ('r\ Result))\ Electoral\ Module$   
**assumes**  
 $homogeneous\text{-}X\text{-}m: homogeneity\text{-}in\ X\ m$  **and**  
 $finite\text{-}elems\text{-}X: \forall\ E \in X. finite\ (voters\text{-}\mathcal{E}\ E)$   
**shows** *anonymity-in X m*  
**proof** (*unfold anonymity-in.simps is-symmetry.simps, intro allI impI*)  
**fix**  $E\ E' :: ('a, 'v)\ Election$   
**assume**  $rel: (E, E') \in anonymity_{\mathcal{R}}\ X$   
**then obtain**  $\pi :: 'v \Rightarrow 'v$  **where**  
 $bij\text{-}carrier\text{-}\pi: \pi \in carrier\ bijection_{V\mathcal{G}}$  **and**  
 $anon\text{-}action\text{-}E': E' = \varphi\text{-}anon\ X\ \pi\ E$   
**unfolding** *anonymity\_{\mathcal{R}}.simps action-induced-rel.simps*  
**by** *blast*  
**moreover have** *bij \pi*  
**using** *bij-carrier-\pi*  
**unfolding** *bijection\_{V\mathcal{G}}-def rewrite-carrier*  
**by** *simp*  
**moreover have** *in-election-set: E \in X*  
**using** *anon-action-E' rel*  
**unfolding** *anonymity\_{\mathcal{R}}.simps action-induced-rel.simps*

```

  by blast
ultimately have finite (voters- $\mathcal{E}$   $E'$ )
  using finite-elems- $X$  rename.simps rename-finite split-pairs
  unfolding  $\varphi$ -anon.simps extensional-continuation.simps voters- $\mathcal{E}$ .simps
  by metis
moreover have fin- $E$ : finite (voters- $\mathcal{E}$   $E$ )
  using in-election-set finite-elems- $X$ 
  unfolding anonymity $\mathcal{R}$ .simps action-induced-rel.simps
  by blast
moreover have  $\forall r. \text{vote-count } r \ E = 1 * (\text{vote-count } r \ E')$ 
  using fin- $E$  anon-rel-vote-count rel mult-1
  by metis
moreover have alternatives- $\mathcal{E}$   $E = \text{alternatives-}\mathcal{E} \ E'$ 
  using fin- $E$  anon-rel-vote-count rel
  by metis
ultimately show  $\text{fun}_{\mathcal{E}} \ m \ E = \text{fun}_{\mathcal{E}} \ m \ E'$ 
  using homogeneous- $X$ - $m$  in-election-set
  unfolding homogeneity-in.simps is-symmetry.simps homogeneity $\mathcal{R}$ .simps
  by blast
qed

```

#### 4.4.7 Non-Blocking

An electoral module is non-blocking iff this module never rejects all alternatives.

**definition** *non-blocking* ::  $(\text{'a}, \text{'v}, \text{'a Result}) \text{ Electoral-Module} \Rightarrow \text{bool}$  **where**  
*non-blocking*  $m \equiv$   
 $\text{SCF-result.electoral-module } m \wedge$   
 $(\forall A \ V \ p. ((A \neq \{\}) \wedge \text{finite } A \wedge \text{profile } V \ A \ p) \longrightarrow \text{reject } m \ V \ A \ p \neq A))$

#### 4.4.8 Electing

An electoral module is electing iff it always elects at least one alternative.

**definition** *electing* ::  $(\text{'a}, \text{'v}, \text{'a Result}) \text{ Electoral-Module} \Rightarrow \text{bool}$  **where**  
*electing*  $m \equiv$   
 $\text{SCF-result.electoral-module } m \wedge$   
 $(\forall A \ V \ p. (A \neq \{\}) \wedge \text{finite } A \wedge \text{profile } V \ A \ p) \longrightarrow \text{elect } m \ V \ A \ p \neq \{\})$

**lemma** *electing-for-only-alt*:

**fixes**  
 $m :: (\text{'a}, \text{'v}, \text{'a Result}) \text{ Electoral-Module}$  **and**  
 $A :: \text{'a set}$  **and**  
 $V :: \text{'v set}$  **and**  
 $p :: (\text{'a}, \text{'v}) \text{ Profile}$   
**assumes**  
 $\text{one-alt: card } A = 1$  **and**  
 $\text{electing: electing } m$  **and**  
 $\text{prof: profile } V \ A \ p$

```

  shows elect m V A p = A
proof (intro equalityI)
  show elect-in-A: elect m V A p ⊆ A
    using electing prof elect-in-alts
    unfolding electing-def
    by metis
  show A ⊆ elect m V A p
proof (intro subsetI)
  fix a :: 'a
  assume a ∈ A
  thus a ∈ elect m V A p
    using one-alt electing prof elect-in-A IntD2 Int-absorb2 card-1-singletonE
    card-gt-0-iff equals0I zero-less-one singletonD
    unfolding electing-def
    by (metis (no-types))
qed
qed

theorem electing-imp-non-blocking:
  fixes m :: ('a, 'v, 'a Result) Electoral-Module
  assumes electing m
  shows non-blocking m
proof (unfold non-blocking-def, safe)
  show SCF-result.electoral-module m
    using assms
    unfolding electing-def
    by simp
next
fix
  A :: 'a set and
  V :: 'v set and
  p :: ('a, 'v) Profile and
  a :: 'a
assume
  profile V A p and
  finite A and
  reject m V A p = A and
  a ∈ A
moreover have
  SCF-result.electoral-module m ∧
  (∀ A V q. A ≠ {} ∧ finite A ∧ profile V A q ⟶ elect m V A q ≠ {})
  using assms
  unfolding electing-def
  by metis
ultimately show a ∈ {}
  using Diff-cancel Un-empty elec-and-def-not-rej
  by metis
qed

```

#### 4.4.9 Properties

An electoral module is non-electing iff it never elects an alternative.

**definition** *non-electing* :: ('a, 'v, 'a Result) Electoral-Module  $\Rightarrow$  bool **where**  
*non-electing* m  $\equiv$   
 SCF-result.electoral-module m  
 $\wedge (\forall A V p. \text{profile } V A p \longrightarrow \text{elect } m V A p = \{\})$

**lemma** *single-rej-decr-def-card*:

**fixes**  
 m :: ('a, 'v, 'a Result) Electoral-Module **and**  
 A :: 'a set **and**  
 V :: 'v set **and**  
 p :: ('a, 'v) Profile  
**assumes**  
 rejecting: rejects 1 m **and**  
 non-electing: non-electing m **and**  
 f-prof: finite-profile V A p  
**shows** card (defer m V A p) = card A - 1  
**proof** -  
**have** no-elect:  
 SCF-result.electoral-module m  
 $\wedge (\forall V A q. \text{profile } V A q \longrightarrow \text{elect } m V A q = \{\})$   
**using** non-electing  
**unfolding** non-electing-def  
**by** (metis (no-types))  
**hence** reject m V A p  $\subseteq A$   
**using** f-prof reject-in-alts  
**by** metis  
**moreover have** A = A - elect m V A p  
**using** no-elect f-prof  
**by** blast  
**ultimately show** ?thesis  
**using** f-prof no-elect rejecting card-Diff-subset card-gt-0-iff  
 defer-not-elec-or-rej less-one order-less-imp-le Suc-leI  
 bot.extremum-unique card.empty diff-is-0-eq' One-nat-def  
**unfolding** rejects-def  
**by** metis  
**qed**

**lemma** *single-elim-decr-def-card'*:

**fixes**  
 m :: ('a, 'v, 'a Result) Electoral-Module **and**  
 A :: 'a set **and**  
 V :: 'v set **and**  
 p :: ('a, 'v) Profile  
**assumes**  
 eliminating: eliminates 1 m **and**  
 non-electing: non-electing m **and**

```

    not-empty: card A > 1 and
    prof-p: profile V A p
  shows card (defer m V A p) = card A - 1
proof -
  have no-elect:
    SCF-result.electoral-module m
    ∧ (∀ A V q. profile V A q ⟶ elect m V A q = {})
  using non-electing
  unfolding non-electing-def
  by (metis (no-types))
  hence reject m V A p ⊆ A
  using prof-p reject-in-alts
  by metis
  moreover have A = A - elect m V A p
  using no-elect prof-p
  by blast
  ultimately show ?thesis
  using prof-p not-empty no-elect eliminating card-ge-0-finite
    card-Diff-subset defer-not-elec-or-rej zero-less-one
  unfolding eliminates-def
  by (metis (no-types, lifting))
qed

```

An electoral module is defer-deciding iff this module chooses exactly 1 alternative to defer and rejects any other alternative. Note that ‘rejects n-1 m’ can be omitted due to the well-formedness property.

**definition** *defer-deciding* :: ('a, 'v, 'a Result) Electoral-Module  $\Rightarrow$  bool **where**  
*defer-deciding* m  $\equiv$   
 SCF-result.electoral-module m  $\wedge$  non-electing m  $\wedge$  defers 1 m

An electoral module decrements iff this module rejects at least one alternative whenever possible ( $|A| > 1$ ).

**definition** *decrementing* :: ('a, 'v, 'a Result) Electoral-Module  $\Rightarrow$  bool **where**  
*decrementing* m  $\equiv$   
 SCF-result.electoral-module m  $\wedge$   
 $(\forall A V p. \text{profile } V A p \wedge \text{card } A > 1 \longrightarrow \text{card } (\text{reject } m V A p) \geq 1)$

**definition** *defer-condorcet-consistency* :: ('a, 'v, 'a Result) Electoral-Module  $\Rightarrow$  bool **where**  
*defer-condorcet-consistency* m  $\equiv$   
 SCF-result.electoral-module m  $\wedge$   
 $(\forall A V p a. \text{condorcet-winner } V A p a \longrightarrow$   
 $(m V A p = (\{\}, A - (\text{defer } m V A p), \{d \in A. \text{condorcet-winner } V A p d\})))$

**definition** *condorcet-compatibility* :: ('a, 'v, 'a Result) Electoral-Module  $\Rightarrow$  bool **where**  
*condorcet-compatibility* m  $\equiv$   
 SCF-result.electoral-module m  $\wedge$   
 $(\forall A V p a. \text{condorcet-winner } V A p a \longrightarrow$

$$\begin{aligned}
& (a \notin \text{reject } m \ V \ A \ p \wedge \\
& (\forall \ b. \neg \text{condorcet-winner } V \ A \ p \ b \longrightarrow b \notin \text{elect } m \ V \ A \ p) \wedge \\
& (a \in \text{elect } m \ V \ A \ p \longrightarrow \\
& (\forall \ b \in A. \neg \text{condorcet-winner } V \ A \ p \ b \longrightarrow b \in \text{reject } m \ V \ A \ p))))
\end{aligned}$$

An electoral module is defer-monotone iff, when a deferred alternative is lifted, this alternative remains deferred.

**definition** *defer-monotonicity* :: ('a, 'v, 'a Result) Electoral-Module  $\Rightarrow$  bool **where**  
*defer-monotonicity* m  $\equiv$   
*SCF-result.electoral-module* m  $\wedge$   
 $(\forall \ A \ V \ p \ q \ a.$   
 $(a \in \text{defer } m \ V \ A \ p \wedge \text{lifted } V \ A \ p \ q \ a) \longrightarrow a \in \text{defer } m \ V \ A \ q)$

An electoral module is defer-lift-invariant iff lifting a deferred alternative does not affect the outcome.

**definition** *defer-lift-invariance* :: ('a, 'v, 'a Result) Electoral-Module  $\Rightarrow$  bool **where**  
*defer-lift-invariance* m  $\equiv$   
*SCF-result.electoral-module* m  $\wedge$   
 $(\forall \ A \ V \ p \ q \ a. (a \in (\text{defer } m \ V \ A \ p) \wedge \text{lifted } V \ A \ p \ q \ a)$   
 $\longrightarrow m \ V \ A \ p = m \ V \ A \ q)$

**fun** *dli-rel* :: ('a, 'v, 'a Result) Electoral-Module  $\Rightarrow$  ('a, 'v) Election rel **where**  
*dli-rel* m =  $\{((A, V, p), (A, V, q)) \mid A \ V \ p \ q. (\exists \ a \in \text{defer } m \ V \ A \ p. \text{lifted } V \ A \ p \ q \ a)\}$

**lemma** *rewrite-dli-as-invariance*:

**fixes** m :: ('a, 'v, 'a Result) Electoral-Module

**shows**

$$\begin{aligned}
& \text{defer-lift-invariance } m = \\
& (\text{SCF-result.electoral-module } m \\
& \quad \wedge (\text{is-symmetry } (\text{fun}_{\mathcal{E}} \ m) \ (\text{Invariance } (\text{dli-rel } m))))
\end{aligned}$$

**proof** (*unfold is-symmetry.simps, safe*)

**assume** *defer-lift-invariance* m

**thus** *SCF-result.electoral-module* m

**unfolding** *defer-lift-invariance-def*

**by** *blast*

**next**

**fix**

*A A' :: 'a set and*

*V V' :: 'v set and*

*p q :: ('a, 'v) Profile*

**assume**

*invar*: *defer-lift-invariance* m **and**

*rel*:  $((A, V, p), (A', V', q)) \in \text{dli-rel } m$

**then obtain** a :: 'a **where**

*a*  $\in \text{defer } m \ V \ A \ p \wedge \text{lifted } V \ A \ p \ q \ a$

**unfolding** *dli-rel.simps*

**by** *blast*

**moreover with** *rel* **have**  $A = A' \wedge V = V'$

```

    by simp
  ultimately show  $\text{fun}_{\mathcal{E}} m (A, V, p) = \text{fun}_{\mathcal{E}} m (A', V', q)$ 
    using invar fst-eqD snd-eqD profile- $\mathcal{E}$ .simps
    unfolding defer-lift-invariance-def  $\text{fun}_{\mathcal{E}}$ .simps alternatives- $\mathcal{E}$ .simps voters- $\mathcal{E}$ .simps
    by metis
next
assume
  SCF-result.electoral-module m and
   $\forall E E'. (E, E') \in \text{dli-rel } m \longrightarrow \text{fun}_{\mathcal{E}} m E = \text{fun}_{\mathcal{E}} m E'$ 
hence SCF-result.electoral-module m  $\wedge (\forall A V p q.$ 
   $((A, V, p), (A, V, q)) \in \text{dli-rel } m \longrightarrow m V A p = m V A q)$ 
  unfolding  $\text{fun}_{\mathcal{E}}$ .simps alternatives- $\mathcal{E}$ .simps profile- $\mathcal{E}$ .simps voters- $\mathcal{E}$ .simps
  using fst-conv snd-conv
  by metis
moreover have
   $\forall A V p q a. (a \in (\text{defer } m V A p) \wedge \text{lifted } V A p q a) \longrightarrow$ 
     $((A, V, p), (A, V, q)) \in \text{dli-rel } m$ 
  unfolding dli-rel.simps
  by blast
ultimately show defer-lift-invariance m
  unfolding defer-lift-invariance-def
  by blast
qed

```

Two electoral modules are disjoint-compatible if they only make decisions over disjoint sets of alternatives. Electoral modules reject alternatives for which they make no decision.

**definition** *disjoint-compatibility* ::  $('a, 'v, 'a \text{ Result}) \text{ Electoral-Module} \Rightarrow$   
 $('a, 'v, 'a \text{ Result}) \text{ Electoral-Module} \Rightarrow \text{bool}$  **where**  
*disjoint-compatibility* m n  $\equiv$   
 SCF-result.electoral-module m  $\wedge$  SCF-result.electoral-module n  $\wedge$   
 $(\forall V.$   
 $(\forall A.$   
 $(\exists B \subseteq A.$   
 $(\forall a \in B. \text{indep-of-alt } m V A a \wedge$   
 $(\forall p. \text{profile } V A p \longrightarrow a \in \text{reject } m V A p)) \wedge$   
 $(\forall a \in A - B. \text{indep-of-alt } n V A a \wedge$   
 $(\forall p. \text{profile } V A p \longrightarrow a \in \text{reject } n V A p))))))$

Lifting an elected alternative a from an invariant-monotone electoral module either does not change the elect set, or makes a the only elected alternative.

**definition** *invariant-monotonicity* ::  $('a, 'v, 'a \text{ Result})$   
*Electoral-Module*  $\Rightarrow \text{bool}$  **where**  
*invariant-monotonicity* m  $\equiv$   
 SCF-result.electoral-module m  $\wedge$   
 $(\forall A V p q a. (a \in \text{elect } m V A p \wedge \text{lifted } V A p q a) \longrightarrow$   
 $(\text{elect } m V A q = \text{elect } m V A p \vee \text{elect } m V A q = \{a\}))$

Lifting a deferred alternative a from a defer-invariant-monotone electoral

module either does not change the defer set, or makes a the only deferred alternative.

**definition** *defer-invariant-monotonicity* :: ('a, 'v, 'a Result)  
*Electoral-Module*  $\Rightarrow$  bool **where**  
*defer-invariant-monotonicity* m  $\equiv$   
*SCF-result.electoral-module* m  $\wedge$  *non-electing* m  $\wedge$   
 $(\forall A V p q a. (a \in \text{defer } m \ V \ A \ p \wedge \text{lifted } V \ A \ p \ q \ a) \longrightarrow$   
 $(\text{defer } m \ V \ A \ q = \text{defer } m \ V \ A \ p \vee \text{defer } m \ V \ A \ q = \{a\}))$

#### 4.4.10 Inference Rules

**lemma** *ccomp-and-dd-imp-def-only-winner*:

**fixes**

*m* :: ('a, 'v, 'a Result) *Electoral-Module* **and**  
*A* :: 'a set **and**  
*V* :: 'v set **and**  
*p* :: ('a, 'v) *Profile* **and**  
*a* :: 'a

**assumes**

*ccomp*: *condorcet-compatibility* m **and**  
*dd*: *defer-deciding* m **and**  
*winner*: *condorcet-winner* V A p a

**shows** *defer* m V A p = {a}

**proof** (rule *ccontr*)

**assume** *defer* m V A p  $\neq$  {a}

**moreover have** *def-one*: *defers* 1 m

**using** *dd*

**unfolding** *defer-deciding-def*

**by** *metis*

**hence** *c-win*: *finite-profile* V A p  $\wedge$  a  $\in$  A  $\wedge$   $(\forall b \in A - \{a\}. \text{wins } V \ a \ p \ b)$

**using** *winner*

**by** *auto*

**ultimately have**  $\exists b \in A. b \neq a \wedge \text{defer } m \ V \ A \ p = \{b\}$

**using** *Suc-leI card-gt-0-iff def-one equals0D card-1-singletonE*

*defer-in-alts insert-subset*

**unfolding** *defer-deciding-def One-nat-def defers-def*

**by** *metis*

**hence** a  $\notin$  *defer* m V A p

**by** *force*

**hence** a  $\in$  *reject* m V A p

**using** *ccomp c-win electoral-mod-defer-elem dd equals0D*

**unfolding** *defer-deciding-def non-electing-def condorcet-compatibility-def*

**by** *metis*

**moreover have** a  $\notin$  *reject* m V A p

**using** *ccomp c-win winner*

**unfolding** *condorcet-compatibility-def*

**by** *simp*

**ultimately show** *False*

**by** *simp*



qed

**theorem** *ccomp-and-dd-imp-dcc[simp]*:  
**fixes**  $m :: ('a, 'v, 'a \text{ Result}) \text{ Electoral-Module}$   
**assumes**  
     *ccomp*: *condorcet-compatibility m* **and**  
     *dd*: *defer-deciding m*  
**shows** *defer-condorcet-consistency m*  
**proof** (*unfold defer-condorcet-consistency-def, safe*)  
   **show** *SCF-result.electoral-module m*  
     **using** *dd*  
     **unfolding** *defer-deciding-def*  
     **by** *metis*  
**next**  
**fix**  
    $A :: 'a \text{ set}$  **and**  
    $V :: 'v \text{ set}$  **and**  
    $p :: ('a, 'v) \text{ Profile}$  **and**  
    $a :: 'a$   
**assume** *c-winner*: *condorcet-winner V A p a*  
**hence** *elect m V A p = {}*  
   **using** *dd*  
   **unfolding** *defer-deciding-def non-electing-def*  
   **by** *simp*  
**moreover have** *defer m V A p = {a}*  
   **using** *c-winner dd ccomp ccomp-and-dd-imp-def-only-winner*  
   **by** *simp*  
**ultimately have**  $m \ V \ A \ p = (\{\}, A - \text{defer } m \ V \ A \ p, \{a\})$   
   **using** *c-winner reject-not-elected-or-deferred*  
     *elect-rej-def-combination Diff-empty dd*  
   **unfolding** *defer-deciding-def condorcet-winner.simps*  
   **by** *metis*  
**moreover have**  $\{a\} = \{c \in A. \text{condorcet-winner } V \ A \ p \ c\}$   
   **using** *c-winner cond-winner-unique*  
   **by** *metis*  
**ultimately show**  
    $m \ V \ A \ p = (\{\}, A - \text{defer } m \ V \ A \ p, \{c \in A. \text{condorcet-winner } V \ A \ p \ c\})$   
   **by** *simp*  
 qed

If  $m$  and  $n$  are disjoint compatible, so are  $n$  and  $m$ .

**theorem** *disj-compat-comm[simp]*:  
**fixes**  $m \ n :: ('a, 'v, 'a \text{ Result}) \text{ Electoral-Module}$   
**assumes** *disjoint-compatibility m n*  
**shows** *disjoint-compatibility n m*  
**proof** (*unfold disjoint-compatibility-def, safe*)  
**show**  
   *SCF-result.electoral-module m* **and**  
   *SCF-result.electoral-module n*

```

    using assms
    unfolding disjoint-compatibility-def
    by safe
next
fix
  A :: 'a set and
  V :: 'v set
obtain B :: 'a set where
  B ⊆ A ∧
  (∀ a ∈ B.
    indep-of-alt m V A a ∧ (∀ p. profile V A p ⟶ a ∈ reject m V A p)) ∧
  (∀ a ∈ A - B.
    indep-of-alt n V A a ∧ (∀ p. profile V A p ⟶ a ∈ reject n V A p))
  using assms
  unfolding disjoint-compatibility-def
  by metis
hence
  ∃ B ⊆ A.
  (∀ a ∈ A - B.
    indep-of-alt n V A a ∧ (∀ p. profile V A p ⟶ a ∈ reject n V A p)) ∧
  (∀ a ∈ B.
    indep-of-alt m V A a ∧ (∀ p. profile V A p ⟶ a ∈ reject m V A p))
  by blast
thus ∃ B ⊆ A.
  (∀ a ∈ B.
    indep-of-alt n V A a ∧ (∀ p. profile V A p ⟶ a ∈ reject n V A p)) ∧
  (∀ a ∈ A - B.
    indep-of-alt m V A a ∧ (∀ p. profile V A p ⟶ a ∈ reject m V A p))
  by fastforce
qed

```

Every electoral module which is defer-lift-invariant is also defer-monotone.

```

theorem dl-inv-imp-def-mono[simp]:
  fixes m :: ('a, 'v, 'a Result) Electoral-Module
  assumes defer-lift-invariance m
  shows defer-monotonicity m
  using assms
  unfolding defer-monotonicity-def defer-lift-invariance-def
  by metis

```

#### 4.4.11 Social-Choice Properties

##### Condorcet Consistency

```

definition condorcet-consistency :: ('a, 'v, 'a Result) Electoral-Module ⟹
  bool where
  condorcet-consistency m ≡
    SCF-result.electoral-module m ∧
    (∀ A V p a. condorcet-winner V A p a ⟶
      (m V A p = ({e ∈ A. condorcet-winner V A p e}, A - (elect m V A p), {})))

```

## Anonymity

An electoral module is anonymous iff the result is invariant under renamings of voters, i.e., any permutation of the voter set that does not change the preferences leads to an identical result.

**definition** (*in result*)  $\text{anonymity} :: ('a, 'v, ('r \text{ Result})) \text{ Electoral-Module} \Rightarrow \text{bool}$  **where**  
 $\text{anonymity } m \equiv$   
 $\text{electoral-module } m \wedge$   
 $(\forall A \ V \ p \ \pi :: ('v \Rightarrow 'v)).$   
 $\text{bij } \pi \longrightarrow (\text{let } (A', V', q) = (\text{rename } \pi \ (A, V, p)) \text{ in}$   
 $\text{profile } V \ A \ p \wedge \text{profile } V' \ A' \ q \longrightarrow m \ V \ A \ p = m \ V' \ A' \ q))$

Anonymity can alternatively be described as invariance under the voter permutation group acting on elections via the rename function.

**fun**  $\text{anonymity-finite}' :: ('a, 'v, 'r) \text{ Electoral-Module} \Rightarrow \text{bool}$  **where**  
 $\text{anonymity-finite}' m = \text{anonymity-in well-formed-finite-}\mathcal{V}\text{-elections } m$

**fun**  $\text{anonymity}' :: ('a, 'v, 'r) \text{ Electoral-Module} \Rightarrow \text{bool}$  **where**  
 $\text{anonymity}' m = \text{anonymity-in well-formed-elections } m$

## Homogeneity

A voting rule is homogeneous if copying an election does not change the result. For ordered voter types and finite elections, we use the notion of copying ballot lists to define copying an election. The more general definition of homogeneity for unordered voter types already implies anonymity.

**fun**  $\text{homogeneity} :: ('a, 'v, 'b \text{ Result}) \text{ Electoral-Module} \Rightarrow \text{bool}$  **where**  
 $\text{homogeneity } m = \text{homogeneity-in well-formed-finite-}\mathcal{V}\text{-elections } m$

**fun**  $\text{homogeneity}' :: ('a, 'v :: \text{linorder}, 'b \text{ Result}) \text{ Electoral-Module} \Rightarrow \text{bool}$  **where**  
 $\text{homogeneity}' m = \text{homogeneity'-in well-formed-finite-}\mathcal{V}\text{-elections } m$

**fun**  $\text{homogeneity-inf} :: ('a, 'v, 'b \text{ Result}) \text{ Electoral-Module} \Rightarrow \text{bool}$  **where**  
 $\text{homogeneity-inf } m = \text{homogeneity-in well-formed-elections } m$

**fun**  $\text{homogeneity-inf}' :: ('a, 'v :: \text{linorder}, 'b \text{ Result}) \text{ Electoral-Module} \Rightarrow \text{bool}$  **where**  
 $\text{homogeneity-inf}' m = \text{homogeneity'-in well-formed-elections } m$

## Neutrality

Neutrality is equivariance under consistent renaming of candidates in the candidate set and election results.

**fun** (*in result-properties*)  $\text{neutrality} :: ('a, 'v, 'b \text{ Result}) \text{ Electoral-Module} \Rightarrow \text{bool}$  **where**  
 $\text{neutrality } m = \text{neutrality-in well-formed-elections } m$

### (Weak) Monotonicity

An electoral module is monotone iff when an elected alternative is lifted, this alternative remains elected.

**definition** *monotonicity* :: ('a, 'v, 'a Result) Electoral-Module  $\Rightarrow$  bool **where**  
*monotonicity*  $m \equiv$   
 $SCF\text{-}result.\text{electoral-module } m \wedge$   
 $(\forall A V p q a. a \in \text{elect } m V A p \wedge \text{lifted } V A p q a \longrightarrow a \in \text{elect } m V A q)$

### 4.4.12 Social-Welfare Properties

#### Reversal Symmetry

A social welfare rule is reversal symmetric if reversing all voters' preferences reverses the result rankings as well.

**definition** *reversal-symmetry-in* :: ('a, 'v) Election set  $\Rightarrow$   
('a, 'v, 'a rel Result) Electoral-Module  $\Rightarrow$  bool **where**  
*reversal-symmetry-in*  $X m \equiv$   
 $is\text{-}symmetry (\text{fun}_E m) (\text{action-induced-equivariance } (\text{carrier reversal}_G) X$   
 $(\varphi\text{-reverse } X) (\text{result-action } \psi\text{-reverse}))$

**fun** *reversal-symmetry* :: ('a, 'v, 'a rel Result) Electoral-Module  $\Rightarrow$  bool **where**  
*reversal-symmetry*  $m = \text{reversal-symmetry-in well-formed-elections } m$

### 4.4.13 Property Relations

**lemma** *condorcet-consistency-equiv*:

**fixes**  $m :: ('a, 'v, 'a Result) \text{ Electoral-Module}$

**shows** *condorcet-consistency*  $m =$

$(SCF\text{-}result.\text{electoral-module } m \wedge$   
 $(\forall A V p a. \text{condorcet-winner } V A p a \longrightarrow$   
 $(m V A p = (\{a\}, A - (\text{elect } m V A p), \{ \}))))$

**proof** (*safe*)

**assume** *condorcet-consistency*  $m$

**thus**  $SCF\text{-}result.\text{electoral-module } m$

**unfolding** *condorcet-consistency-def*

**by** (*metis* (*mono-tags*, *lifting*))

**next**

**fix**

$A :: 'a \text{ set}$  **and**

$V :: 'v \text{ set}$  **and**

$p :: ('a, 'v) \text{ Profile}$  **and**

$a :: 'a$

**assume**

*condorcet-consistency*  $m$  **and**

*condorcet-winner*  $V A p a$

**thus**  $m V A p = (\{a\}, A - \text{elect } m V A p, \{ \})$

**using** *cond-winner-unique*

**unfolding** *condorcet-consistency-def*

```

    by (metis (mono-tags, lifting))
next
  assume
    SCF-result.electoral-module m and
     $\forall A V p a. \text{condorcet-winner } V A p a$ 
     $\longrightarrow m V A p = (\{a\}, A - \text{elect } m V A p, \{\})$ 
  thus condorcet-consistency m
  using cond-winner-unique
  unfolding condorcet-consistency-def
  by (metis (mono-tags, lifting))
qed

lemma condorcet-consistency-equiv':
  fixes m :: ('a, 'v, 'a Result) Electoral-Module
  shows condorcet-consistency m =
    (SCF-result.electoral-module m  $\wedge$ 
     ( $\forall A V p a. \text{condorcet-winner } V A p a \longrightarrow m V A p = (\{a\}, A - \{a\}, \{\})$ ))
proof (unfold condorcet-consistency-equiv, safe)
  fix
    A :: 'a set and
    V :: 'v set and
    p :: ('a, 'v) Profile and
    a :: 'a
  assume condorcet-winner V A p a
  {
    moreover assume
       $\forall A V p a'. \text{condorcet-winner } V A p a'$ 
       $\longrightarrow m V A p = (\{a'\}, A - \text{elect } m V A p, \{\})$ 
    ultimately show m V A p = ( $\{a\}$ , A -  $\{a\}$ ,  $\{\}$ )
    using fst-conv
    by metis
  }
  {
    moreover assume
       $\forall A V p a'. \text{condorcet-winner } V A p a'$ 
       $\longrightarrow m V A p = (\{a'\}, A - \{a'\}, \{\})$ 
    ultimately show m V A p = ( $\{a\}$ , A - elect m V A p,  $\{\}$ )
    using fst-conv
    by metis
  }
}
qed

lemma (in result) homogeneity-imp-anonymity-finite:
  fixes m :: ('a, 'v, ('r Result)) Electoral-Module
  assumes homogeneity m
  shows anonymity-finite' m
proof (unfold homogeneity.simps anonymity-finite'.simps)
  obtain Y :: ('a, 'v) Election set where

```

```

homogeneous-Y-imp-anonymous-Y:
homogeneity-in Y m  $\longrightarrow$  ( $\forall E \in Y. \text{finite } (\text{voters-}\mathcal{E} \ E)$ )  $\longrightarrow$  anonymity-in Y
m and
wf-and-finite-Y: Y = well-formed-finite- $\mathcal{V}$ -elections
using homogeneity-in-imp-anonymity-in
by metis
have homogeneity-in Y m
using assms wf-and-finite-Y
unfolding homogeneity.simps
by safe
moreover have  $\forall E \in Y. \text{finite } (\text{voters-}\mathcal{E} \ E)$ 
using wf-and-finite-Y
unfolding finite- $\mathcal{V}$ -elections-def well-formed-finite- $\mathcal{V}$ -elections-def
by safe
ultimately show anonymity-in well-formed-finite- $\mathcal{V}$ -elections m
using homogeneous-Y-imp-anonymous-Y wf-and-finite-Y
by safe
qed
end

```

## 4.5 Electoral Module on Election Quotients

```

theory Quotient-Module
imports Quotients/Relation-Quotients
        Electoral-Module
begin

lemma invariance-is-congruence:
fixes
  m :: ('a, 'v, 'r) Electoral-Module and
  r :: ('a, 'v) Election rel
shows is-symmetry (fun $\mathcal{E}$  m) (Invariance r) = fun $\mathcal{E}$  m respects r
unfolding is-symmetry.simps congruent-def
by blast

lemma invariance-is-congruence':
fixes
  f :: 'x  $\Rightarrow$  'y and
  r :: 'x rel
shows is-symmetry f (Invariance r) = f respects r
unfolding is-symmetry.simps congruent-def
by blast

theorem pass-to-election-quotient:
fixes
  m :: ('a, 'v, 'r) Electoral-Module and

```

```

    r :: ('a, 'v) Election rel and
    X :: ('a, 'v) Election set
assumes
    equiv X r and
    is-symmetry (funE m) (Invariance r)
shows  $\forall A \in X // r. \forall E \in A. \pi_Q (\text{fun}_E m) A = \text{fun}_E m E$ 
using invariance-is-congruence pass-to-quotient assms
by blast

end

```

## 4.6 Evaluation Function

```

theory Evaluation-Function
imports Social-Choice-Types/Profile
begin

```

This is the evaluation function. From a set of currently eligible alternatives, the evaluation function computes a numerical value that is then to be used for further (s)election, e.g., by the elimination module.

### 4.6.1 Definition

```

type-synonym ('a, 'v) Evaluation-Function =
    'v set  $\Rightarrow$  'a  $\Rightarrow$  'a set  $\Rightarrow$  ('a, 'v) Profile  $\Rightarrow$  enat

```

### 4.6.2 Property

An Evaluation function is a Condorcet-rating iff the following holds: If a Condorcet Winner  $w$  exists,  $w$  and only  $w$  has the highest value.

```

definition condorcet-rating :: ('a, 'v) Evaluation-Function  $\Rightarrow$  bool where
    condorcet-rating f  $\equiv$ 
     $\forall A V p w . \text{condorcet-winner } V A p w \longrightarrow$ 
     $(\forall l \in A . l \neq w \longrightarrow f V l A p < f V w A p)$ 

```

An Evaluation function is dependent only on the participating voters iff it is invariant under profile changes that only impact non-voters.

```

fun voters-determine-evaluation :: ('a, 'v) Evaluation-Function  $\Rightarrow$  bool where
    voters-determine-evaluation f =
     $(\forall A V p p' . (\forall v \in V . p v = p' v) \longrightarrow (\forall a \in A . f V a A p = f V a A p'))$ 

```

### 4.6.3 Theorems

If  $e$  is Condorcet-rating, the following holds: If a Condorcet winner  $w$  exists,  $w$  has the maximum evaluation value.

**theorem** *cond-winner-imp-max-eval-val*:

**fixes**

$e :: ('a, 'v)$  *Evaluation-Function* **and**

$A :: 'a$  *set* **and**

$V :: 'v$  *set* **and**

$p :: ('a, 'v)$  *Profile* **and**

$a :: 'a$

**assumes**

*rating*: *condorcet-rating*  $e$  **and**

*f-prof*: *finite-profile*  $V$   $A$   $p$  **and**

*winner*: *condorcet-winner*  $V$   $A$   $p$   $a$

**shows**  $e$   $V$   $a$   $A$   $p$   $=$   $\text{Max } \{e$   $V$   $b$   $A$   $p$   $\mid b. b \in A\}$

**proof**  $-$

**let**  $?set = \{e$   $V$   $b$   $A$   $p$   $\mid b. b \in A\}$  **and**

$?eMax = \text{Max } \{e$   $V$   $b$   $A$   $p$   $\mid b. b \in A\}$  **and**

$?eW = e$   $V$   $a$   $A$   $p$

**have**  $?eW \in ?set$

**using** *CollectI winner*

**unfolding** *condorcet-winner.simps*

**by** (*metis (mono-tags, lifting)*)

**moreover have**  $\forall e \in ?set. e \leq ?eW$

**proof** (*safe*)

**fix**  $b :: 'a$

**assume**  $b \in A$

**thus**  $e$   $V$   $b$   $A$   $p \leq e$   $V$   $a$   $A$   $p$

**using** *less-imp-le rating winner order-refl*

**unfolding** *condorcet-rating-def*

**by** *metis*

**qed**

**moreover have** *finite*  $?set$

**using** *f-prof*

**by** *simp*

**moreover have**  $?set \neq \{\}$

**using** *winner*

**unfolding** *condorcet-winner.simps*

**by** *fastforce*

**ultimately show** *?thesis*

**using** *Max-eq-iff*

**by** (*metis (no-types, lifting)*)

**qed**

If  $e$  is Condorcet-rating, the following holds: If a Condorcet Winner  $w$  exists, a non-Condorcet winner has a value lower than the maximum evaluation value.

**theorem** *non-cond-winner-not-max-eval*:

**fixes**

$e :: ('a, 'v)$  *Evaluation-Function* **and**

$A :: 'a$  *set* **and**

$V :: 'v$  *set* **and**



```

    p :: ('a, 'v) Profile and
    a b :: 'a
assumes
    rating: condorcet-rating e and
    f-prof: finite-profile V A p and
    winner: condorcet-winner V A p a and
    lin-A: b ∈ A and
    loser: a ≠ b
shows e V b A p < Max {e V c A p | c. c ∈ A}
proof -
  have e V b A p < e V a A p
    using lin-A loser rating winner
    unfolding condorcet-rating-def
    by metis
  also have ... = Max {e V c A p | c. c ∈ A}
    using cond-winner-imp-max-eval-val f-prof rating winner
    by fastforce
  finally show ?thesis
    by simp
qed

end

```

## 4.7 Elimination Module

```

theory Elimination-Module
  imports Evaluation-Function
    Electoral-Module
begin

```

This is the elimination module. It rejects a set of alternatives only if these are not all alternatives. The alternatives potentially to be rejected are put in a so-called elimination set. These are all alternatives that score below a preset threshold value that depends on the specific voting rule.

### 4.7.1 General Definitions

```

type-synonym Threshold-Value = enat
type-synonym Threshold-Relation = enat ⇒ enat ⇒ bool
type-synonym ('a, 'v) Electoral-Set = 'v set ⇒ 'a set ⇒ ('a, 'v) Profile ⇒ 'a set
fun elimination-set :: ('a, 'v) Evaluation-Function ⇒ Threshold-Value ⇒
    Threshold-Relation ⇒ ('a, 'v) Electoral-Set where

```

*elimination-set*  $e \ t \ r \ V \ A \ p = (\text{if finite } A \text{ then } \{a \in A . r \ (e \ V \ a \ A \ p) \ t\} \text{ else } \{\})$

**fun** *average* :: (*'a*, *'v*) *Evaluation-Function*  $\Rightarrow$  *'v set*  $\Rightarrow$  *'a set*  $\Rightarrow$  (*'a*, *'v*) *Profile*  $\Rightarrow$  *Threshold-Value* **where**  
*average*  $e \ V \ A \ p = (\text{let sum-eval} = (\sum x \in A. e \ V \ x \ A \ p) \text{ in}$   
*if*  $\text{sum-eval} = \infty \text{ then } \infty \text{ else the-enat sum-eval div card } A)$

#### 4.7.2 Social-Choice Definitions

**fun** *elimination-module* :: (*'a*, *'v*) *Evaluation-Function*  $\Rightarrow$  *Threshold-Value*  $\Rightarrow$  *Threshold-Relation*  $\Rightarrow$  (*'a*, *'v*, *'a Result*) *Electoral-Module* **where**  
*elimination-module*  $e \ t \ r \ V \ A \ p =$   
*(if* *elimination-set*  $e \ t \ r \ V \ A \ p \neq A$   
*then*  $(\{\}, \text{elimination-set } e \ t \ r \ V \ A \ p, A - \text{elimination-set } e \ t \ r \ V \ A \ p)$   
*else*  $(\{\}, \{\}, A))$

#### 4.7.3 Social-Choice Eliminators

**fun** *less-eliminator* :: (*'a*, *'v*) *Evaluation-Function*  $\Rightarrow$  *Threshold-Value*  $\Rightarrow$  (*'a*, *'v*, *'a Result*) *Electoral-Module* **where**  
*less-eliminator*  $e \ t \ V \ A \ p = \text{elimination-module } e \ t \ (<) \ V \ A \ p$

**fun** *max-eliminator* :: (*'a*, *'v*) *Evaluation-Function*  $\Rightarrow$  (*'a*, *'v*, *'a Result*) *Electoral-Module* **where**  
*max-eliminator*  $e \ V \ A \ p =$   
*less-eliminator*  $e \ (\text{Max } \{e \ V \ x \ A \ p \mid x. x \in A\}) \ V \ A \ p$

**fun** *leq-eliminator* :: (*'a*, *'v*) *Evaluation-Function*  $\Rightarrow$  *Threshold-Value*  $\Rightarrow$  (*'a*, *'v*, *'a Result*) *Electoral-Module* **where**  
*leq-eliminator*  $e \ t \ V \ A \ p = \text{elimination-module } e \ t \ (\leq) \ V \ A \ p$

**fun** *min-eliminator* :: (*'a*, *'v*) *Evaluation-Function*  $\Rightarrow$  (*'a*, *'v*, *'a Result*) *Electoral-Module* **where**  
*min-eliminator*  $e \ V \ A \ p =$   
*leq-eliminator*  $e \ (\text{Min } \{e \ V \ x \ A \ p \mid x. x \in A\}) \ V \ A \ p$

**fun** *less-average-eliminator* :: (*'a*, *'v*) *Evaluation-Function*  $\Rightarrow$  (*'a*, *'v*, *'a Result*) *Electoral-Module* **where**  
*less-average-eliminator*  $e \ V \ A \ p = \text{less-eliminator } e \ (\text{average } e \ V \ A \ p) \ V \ A \ p$

**fun** *leq-average-eliminator* :: (*'a*, *'v*) *Evaluation-Function*  $\Rightarrow$  (*'a*, *'v*, *'a Result*) *Electoral-Module* **where**  
*leq-average-eliminator*  $e \ V \ A \ p = \text{leq-eliminator } e \ (\text{average } e \ V \ A \ p) \ V \ A \ p$

#### 4.7.4 Soundness

**lemma** *elim-mod-sound[simp]*:  
**fixes**  
*e* :: (*'a*, *'v*) *Evaluation-Function* **and**  
*t* :: *Threshold-Value* **and**

```

    r :: Threshold-Relation
  shows SCF-result.electoral-module (elimination-module e t r)
  unfolding SCF-result.electoral-module.simps
  by auto

lemma less-elim-sound[simp]:
  fixes
    e :: ('a, 'v) Evaluation-Function and
    t :: Threshold-Value
  shows SCF-result.electoral-module (less-eliminator e t)
  unfolding SCF-result.electoral-module.simps
  by auto

lemma leq-elim-sound[simp]:
  fixes
    e :: ('a, 'v) Evaluation-Function and
    t :: Threshold-Value
  shows SCF-result.electoral-module (leq-eliminator e t)
  unfolding SCF-result.electoral-module.simps
  by auto

lemma max-elim-sound[simp]:
  fixes e :: ('a, 'v) Evaluation-Function
  shows SCF-result.electoral-module (max-eliminator e)
  unfolding SCF-result.electoral-module.simps
  by auto

lemma min-elim-sound[simp]:
  fixes e :: ('a, 'v) Evaluation-Function
  shows SCF-result.electoral-module (min-eliminator e)
  unfolding SCF-result.electoral-module.simps
  by auto

lemma less-avg-elim-sound[simp]:
  fixes e :: ('a, 'v) Evaluation-Function
  shows SCF-result.electoral-module (less-average-eliminator e)
  unfolding SCF-result.electoral-module.simps
  by auto

lemma leq-avg-elim-sound[simp]:
  fixes e :: ('a, 'v) Evaluation-Function
  shows SCF-result.electoral-module (leq-average-eliminator e)
  unfolding SCF-result.electoral-module.simps
  by auto

```

#### 4.7.5 Independence of Non-Voters

```

lemma voters-determine-elim-mod[simp]:
  fixes

```

```

    e :: ('a, 'v) Evaluation-Function and
    t :: Threshold-Value and
    r :: Threshold-Relation
  assumes voters-determine-evaluation e
  shows voters-determine-election (elimination-module e t r)
proof (unfold voters-determine-election.simps elimination-module.simps, safe)
  fix
    A :: 'a set and
    V :: 'v set and
    p p' :: ('a, 'v) Profile
  assume  $\forall v \in V. p\ v = p'\ v$ 
  hence  $\forall a \in A. (e\ V\ a\ A\ p) = (e\ V\ a\ A\ p')$ 
    using assms
    unfolding voters-determine-election.simps
    by simp
  hence  $\{a \in A. r\ (e\ V\ a\ A\ p)\ t\} = \{a \in A. r\ (e\ V\ a\ A\ p')\ t\}$ 
    by metis
  hence elimination-set e t r V A p = elimination-set e t r V A p'
    unfolding elimination-set.simps
    by presburger
  thus (if elimination-set e t r V A p  $\neq$  A
    then ( $\{\}$ , elimination-set e t r V A p, A - elimination-set e t r V A p)
    else ( $\{\}$ ,  $\{\}$ , A)) =
    (if elimination-set e t r V A p'  $\neq$  A
    then ( $\{\}$ , elimination-set e t r V A p', A - elimination-set e t r V A p')
    else ( $\{\}$ ,  $\{\}$ , A))
    by presburger
qed

```

```

lemma voters-determine-less-elim[simp]:
  fixes
    e :: ('a, 'v) Evaluation-Function and
    t :: Threshold-Value
  assumes voters-determine-evaluation e
  shows voters-determine-election (less-eliminator e t)
  using assms voters-determine-elim-mod
  unfolding less-eliminator.simps voters-determine-election.simps
  by (metis (full-types))

```

```

lemma voters-determine-leq-elim[simp]:
  fixes
    e :: ('a, 'v) Evaluation-Function and
    t :: Threshold-Value
  assumes voters-determine-evaluation e
  shows voters-determine-election (leq-eliminator e t)
  using assms voters-determine-elim-mod
  unfolding leq-eliminator.simps voters-determine-election.simps
  by (metis (full-types))

```

```

lemma voters-determine-max-elim[simp]:
  fixes e :: ('a, 'v) Evaluation-Function
  assumes voters-determine-evaluation e
  shows voters-determine-election (max-eliminator e)
proof (unfold max-eliminator.simps voters-determine-election.simps, safe)
  fix
    A :: 'a set and
    V :: 'v set and
    p p' :: ('a, 'v) Profile
  assume coinciding:  $\forall v \in V. p\ v = p'\ v$ 
  hence  $\forall x \in A. e\ V\ x\ A\ p = e\ V\ x\ A\ p'$ 
    using assms
    unfolding voters-determine-evaluation.simps
    by simp
  hence  $\text{Max } \{e\ V\ x\ A\ p \mid x. x \in A\} = \text{Max } \{e\ V\ x\ A\ p' \mid x. x \in A\}$ 
    by metis
  thus less-eliminator e (Max {e V x A p | x. x ∈ A}) V A p =
    less-eliminator e (Max {e V x A p' | x. x ∈ A}) V A p'
    using coinciding assms voters-determine-less-elim
    unfolding voters-determine-election.simps
    by (metis (no-types, lifting))
qed

```

```

lemma voters-determine-min-elim[simp]:
  fixes e :: ('a, 'v) Evaluation-Function
  assumes voters-determine-evaluation e
  shows voters-determine-election (min-eliminator e)
proof (unfold min-eliminator.simps voters-determine-election.simps, safe)
  fix
    A :: 'a set and
    V :: 'v set and
    p p' :: ('a, 'v) Profile
  assume coinciding:  $\forall v \in V. p\ v = p'\ v$ 
  hence  $\forall x \in A. e\ V\ x\ A\ p = e\ V\ x\ A\ p'$ 
    using assms
    unfolding voters-determine-election.simps
    by simp
  hence  $\text{Min } \{e\ V\ x\ A\ p \mid x. x \in A\} = \text{Min } \{e\ V\ x\ A\ p' \mid x. x \in A\}$ 
    by metis
  thus leq-eliminator e (Min {e V x A p | x. x ∈ A}) V A p =
    leq-eliminator e (Min {e V x A p' | x. x ∈ A}) V A p'
    using coinciding assms voters-determine-leq-elim
    unfolding voters-determine-election.simps
    by (metis (no-types, lifting))
qed

```

```

lemma voters-determine-less-avg-elim[simp]:
  fixes e :: ('a, 'v) Evaluation-Function
  assumes voters-determine-evaluation e

```

**shows** *voters-determine-election* (*less-average-eliminator e*)  
**proof** (*unfold less-average-eliminator.simps voters-determine-election.simps, safe*)  
**fix**  
 $A :: 'a \text{ set}$  **and**  
 $V :: 'v \text{ set}$  **and**  
 $p \ p' :: ('a, 'v) \text{ Profile}$   
**assume** *coinciding*:  $\forall v \in V. p \ v = p' \ v$   
**hence**  $\forall x \in A. e \ V \ x \ A \ p = e \ V \ x \ A \ p'$   
**using** *assms*  
**unfolding** *voters-determine-election.simps*  
**by** *simp*  
**hence**  $\text{average } e \ V \ A \ p = \text{average } e \ V \ A \ p'$   
**unfolding** *average.simps*  
**by** *auto*  
**thus**  $\text{less-eliminator } e \ (\text{average } e \ V \ A \ p) \ V \ A \ p =$   
 $\text{less-eliminator } e \ (\text{average } e \ V \ A \ p') \ V \ A \ p'$   
**using** *coinciding assms voters-determine-less-elim*  
**unfolding** *voters-determine-election.simps*  
**by** (*metis (no-types, lifting)*)  
**qed**

**lemma** *voters-determine-leq-avg-elim*[*simp*]:  
**fixes**  $e :: ('a, 'v) \text{ Evaluation-Function}$   
**assumes** *voters-determine-evaluation e*  
**shows** *voters-determine-election* (*leq-average-eliminator e*)  
**proof** (*unfold leq-average-eliminator.simps voters-determine-election.simps, safe*)  
**fix**  
 $A :: 'a \text{ set}$  **and**  
 $V :: 'v \text{ set}$  **and**  
 $p \ p' :: ('a, 'v) \text{ Profile}$   
**assume** *coinciding*:  $\forall v \in V. p \ v = p' \ v$   
**hence**  $\forall x \in A. e \ V \ x \ A \ p = e \ V \ x \ A \ p'$   
**using** *assms*  
**unfolding** *voters-determine-election.simps*  
**by** *simp*  
**hence**  $\text{average } e \ V \ A \ p = \text{average } e \ V \ A \ p'$   
**unfolding** *average.simps*  
**by** *auto*  
**thus**  $\text{leq-eliminator } e \ (\text{average } e \ V \ A \ p) \ V \ A \ p =$   
 $\text{leq-eliminator } e \ (\text{average } e \ V \ A \ p') \ V \ A \ p'$   
**using** *coinciding assms voters-determine-leq-elim*  
**unfolding** *voters-determine-election.simps*  
**by** (*metis (no-types, lifting)*)  
**qed**

#### 4.7.6 Non-Blocking

**lemma** *elim-mod-non-blocking*:  
**fixes**

```

    e :: ('a, 'v) Evaluation-Function and
    t :: Threshold-Value and
    r :: Threshold-Relation
  shows non-blocking (elimination-module e t r)
  unfolding non-blocking-def
  by auto

lemma less-elim-non-blocking:
  fixes
    e :: ('a, 'v) Evaluation-Function and
    t :: Threshold-Value
  shows non-blocking (less-eliminator e t)
  unfolding less-eliminator.simps
  using elim-mod-non-blocking
  by auto

lemma leq-elim-non-blocking:
  fixes
    e :: ('a, 'v) Evaluation-Function and
    t :: Threshold-Value
  shows non-blocking (leq-eliminator e t)
  unfolding leq-eliminator.simps
  using elim-mod-non-blocking
  by auto

lemma max-elim-non-blocking:
  fixes e :: ('a, 'v) Evaluation-Function
  shows non-blocking (max-eliminator e)
  unfolding non-blocking-def
  using SCF-result.electoral-module.simps
  by auto

lemma min-elim-non-blocking:
  fixes e :: ('a, 'v) Evaluation-Function
  shows non-blocking (min-eliminator e)
  unfolding non-blocking-def
  using SCF-result.electoral-module.simps
  by auto

lemma less-avg-elim-non-blocking:
  fixes e :: ('a, 'v) Evaluation-Function
  shows non-blocking (less-average-eliminator e)
  unfolding non-blocking-def
  using SCF-result.electoral-module.simps
  by auto

lemma leq-avg-elim-non-blocking:
  fixes e :: ('a, 'v) Evaluation-Function
  shows non-blocking (leq-average-eliminator e)

```

```

unfolding non-blocking-def
using SCF-result.electoral-module.simps
by auto

```

#### 4.7.7 Non-Electing

```

lemma elim-mod-non-electing:
  fixes
     $e :: ('a, 'v)$  Evaluation-Function and
     $t ::$  Threshold-Value and
     $r ::$  Threshold-Relation
  shows non-electing (elimination-module  $e$   $t$   $r$ )
  unfolding non-electing-def
  by force

```

```

lemma less-elim-non-electing:
  fixes
     $e :: ('a, 'v)$  Evaluation-Function and
     $t ::$  Threshold-Value
  shows non-electing (less-eliminator  $e$   $t$ )
  using elim-mod-non-electing less-elim-sound
  unfolding non-electing-def
  by force

```

```

lemma leq-elim-non-electing:
  fixes
     $e :: ('a, 'v)$  Evaluation-Function and
     $t ::$  Threshold-Value
  shows non-electing (leq-eliminator  $e$   $t$ )
  unfolding non-electing-def
  by force

```

```

lemma max-elim-non-electing:
  fixes  $e :: ('a, 'v)$  Evaluation-Function
  shows non-electing (max-eliminator  $e$ )
  unfolding non-electing-def
  by force

```

```

lemma min-elim-non-electing:
  fixes  $e :: ('a, 'v)$  Evaluation-Function
  shows non-electing (min-eliminator  $e$ )
  unfolding non-electing-def
  by force

```

```

lemma less-avg-elim-non-electing:
  fixes  $e :: ('a, 'v)$  Evaluation-Function
  shows non-electing (less-average-eliminator  $e$ )
  unfolding non-electing-def
  by auto

```



**lemma** *leq-avg-elim-non-electing*:  
**fixes**  $e :: ('a, 'v)$  *Evaluation-Function*  
**shows** *non-electing* (*leq-average-eliminator*  $e$ )  
**unfolding** *non-electing-def*  
**by** *force*

#### 4.7.8 Inference Rules

If the used evaluation function is Condorcet rating, max-eliminator is Condorcet compatible.

**theorem** *cr-eval-imp-ccomp-max-elim[simp]*:  
**fixes**  $e :: ('a, 'v)$  *Evaluation-Function*  
**assumes** *condorcet-rating*  $e$   
**shows** *condorcet-compatibility* (*max-eliminator*  $e$ )  
**proof** (*unfold condorcet-compatibility-def, safe*)  
**show** *SCF-result.electoral-module* (*max-eliminator*  $e$ )  
**by** *force*  
**next**  
**fix**  
 $A :: 'a$  *set* **and**  
 $V :: 'v$  *set* **and**  
 $p :: ('a, 'v)$  *Profile* **and**  
 $a :: 'a$   
**assume**  
 $c\text{-win}: \text{condorcet-winner } V A p a$  **and**  
 $rej\text{-}a: a \in \text{reject } (\text{max-eliminator } e) V A p$   
**have**  $e V a A p = \text{Max } \{e V b A p \mid b. b \in A\}$   
**using**  $c\text{-win cond-winner-imp-max-eval-val assms}$   
**by** *fastforce*  
**hence**  $a \notin \text{reject } (\text{max-eliminator } e) V A p$   
**by** *simp*  
**thus** *False*  
**using**  $rej\text{-}a$   
**by** *linarith*  
**next**  
**fix**  
 $A :: 'a$  *set* **and**  
 $V :: 'v$  *set* **and**  
 $p :: ('a, 'v)$  *Profile* **and**  
 $a :: 'a$   
**assume**  $a \in \text{elect } (\text{max-eliminator } e) V A p$   
**moreover have**  $a \notin \text{elect } (\text{max-eliminator } e) V A p$   
**by** *simp*  
**ultimately show** *False*  
**by** *linarith*  
**next**  
**fix**  
 $A :: 'a$  *set* **and**

```

  V :: 'v set and
  p :: ('a, 'v) Profile and
  a a' :: 'a
assume
  condorcet-winner V A p a and
  a ∈ elect (max-eliminator e) V A p
thus a' ∈ reject (max-eliminator e) V A p
  using empty-iff max-elim-non-electing
  unfolding condorcet-winner.simps non-electing-def
  by metis
qed

```

If the used evaluation function is Condorcet rating, max-eliminator is defer-Condorcet-consistent.

```

theorem cr-eval-imp-dcc-max-elim[simp]:
  fixes e :: ('a, 'v) Evaluation-Function
  assumes condorcet-rating e
  shows defer-condorcet-consistency (max-eliminator e)
proof (unfold defer-condorcet-consistency-def, safe)
  show SCF-result.electoral-module (max-eliminator e)
    using max-elim-sound
    by metis
next
  fix
    A :: 'a set and
    V :: 'v set and
    p :: ('a, 'v) Profile and
    a :: 'a
  assume winner: condorcet-winner V A p a
  hence f-prof: finite-profile V A p
    by simp
  let ?trsh = Max {e V b A p | b. b ∈ A}
  show
    max-eliminator e V A p =
      ({},
        A - defer (max-eliminator e) V A p,
        {b ∈ A. condorcet-winner V A p b})
proof (cases elimination-set e (?trsh) (<) V A p ≠ A)
  have e V a A p = Max {e V x A p | x. x ∈ A}
    using winner assms cond-winner-imp-max-eval-val
    by fastforce
  hence ∀ b ∈ A. b ≠ a
    ⟷ b ∈ {c ∈ A. e V c A p < Max {e V b A p | b. b ∈ A}}
    using winner assms mem-Collect-eq linorder-neq-iff
    unfolding condorcet-rating-def
    by (metis (mono-tags, lifting))
  hence elim-set: elimination-set e ?trsh (<) V A p = A - {a}
    unfolding elimination-set.simps
    using f-prof

```

```

    by fastforce
  case True
  hence
    max-eliminator e V A p =
      ({},
        elimination-set e ?trsh (<) V A p,
        A - elimination-set e ?trsh (<) V A p)
    by simp
  also have ... = ({}, A - defer (max-eliminator e) V A p, {a})
    using elim-set winner
    by auto
  also have
    ... = ({},
      A - defer (max-eliminator e) V A p,
      {b ∈ A. condorcet-winner V A p b})
    using cond-winner-unique winner Collect-cong
    by (metis (no-types, lifting))
  finally show ?thesis
    using winner
    by metis
next
case False
moreover have ?trsh = e V a A p
  using assms winner cond-winner-imp-max-eval-val
  by fastforce
ultimately show ?thesis
  using winner
  by auto
qed
qed
end

```

## 4.8 Aggregator

```

theory Aggregator
  imports Social-Choice-Types/Social-Choice-Result
begin

```

An aggregator gets two partitions (results of electoral modules) as input and output another partition. They are used to aggregate results of parallel composed electoral modules. They are commutative, i.e., the order of the aggregated modules does not affect the resulting aggregation. Moreover, they are conservative in the sense that the resulting decisions are subsets of

the two given partitions' decisions.

#### 4.8.1 Definition

**type-synonym** *'a Aggregator* = *'a set*  $\Rightarrow$  *'a Result*  $\Rightarrow$  *'a Result*  $\Rightarrow$  *'a Result*

**definition** *aggregator* :: *'a Aggregator*  $\Rightarrow$  *bool* **where**

*aggregator agg*  $\equiv$   
 $\forall A e e' d d' r r'.$   
 $(\text{well-formed-SCF } A (e, r, d) \wedge \text{well-formed-SCF } A (e', r', d')) \longrightarrow$   
 $\text{well-formed-SCF } A (\text{agg } A (e, r, d) (e', r', d'))$

#### 4.8.2 Properties

**definition** *agg-commutative* :: *'a Aggregator*  $\Rightarrow$  *bool* **where**

*agg-commutative agg*  $\equiv$   
 $\text{aggregator } \text{agg} \wedge (\forall A e e' d d' r r'.$   
 $\text{agg } A (e, r, d) (e', r', d') = \text{agg } A (e', r', d') (e, r, d))$

**definition** *agg-conservative* :: *'a Aggregator*  $\Rightarrow$  *bool* **where**

*agg-conservative agg*  $\equiv$   
 $\text{aggregator } \text{agg} \wedge$   
 $(\forall A e e' d d' r r'.$   
 $((\text{well-formed-SCF } A (e, r, d) \wedge \text{well-formed-SCF } A (e', r', d')) \longrightarrow$   
 $\text{elect-r } (\text{agg } A (e, r, d) (e', r', d')) \subseteq (e \cup e') \wedge$   
 $\text{reject-r } (\text{agg } A (e, r, d) (e', r', d')) \subseteq (r \cup r') \wedge$   
 $\text{defer-r } (\text{agg } A (e, r, d) (e', r', d')) \subseteq (d \cup d')))$

**end**

### 4.9 Maximum Aggregator

**theory** *Maximum-Aggregator*

**imports** *Aggregator*

**begin**

The max(imum) aggregator takes two partitions of an alternative set A as input. It returns a partition where every alternative receives the maximum result of the two input partitions.

#### 4.9.1 Definition

**fun** *max-aggregator* :: *'a Aggregator* **where**

*max-aggregator A* (e, r, d) (e', r', d') =

$(e \cup e',$   
 $A - (e \cup e' \cup d \cup d'),$   
 $(d \cup d') - (e \cup e'))$

#### 4.9.2 Auxiliary Lemma

**lemma** *max-agg-rej-set*:

**fixes**

$A \ e \ e' \ d \ d' \ r \ r' :: 'a \ \text{set}$  **and**

$a :: 'a$

**assumes**

*wf-first-mod*: *well-formed-SCF*  $A \ (e, r, d)$  **and**

*wf-second-mod*: *well-formed-SCF*  $A \ (e', r', d')$

**shows** *reject-r* (*max-aggregator*  $A \ (e, r, d) \ (e', r', d')$ ) =  $r \cap r'$

**proof** –

**have**  $A - (e \cup d) = r$

**using** *wf-first-mod result-imp-rej*

**by** *metis*

**moreover have**  $A - (e' \cup d') = r'$

**using** *wf-second-mod result-imp-rej*

**by** *metis*

**ultimately have**  $A - (e \cup e' \cup d \cup d') = r \cap r'$

**by** *blast*

**moreover have**  $\{l \in A. l \notin e \cup e' \cup d \cup d'\} = A - (e \cup e' \cup d \cup d')$

**unfolding** *set-diff-eq*

**by** *simp*

**ultimately show** *reject-r* (*max-aggregator*  $A \ (e, r, d) \ (e', r', d')$ ) =  $r \cap r'$

**by** *simp*

**qed**

#### 4.9.3 Soundness

**theorem** *max-agg-sound*[*simp*]: *aggregator max-aggregator*

**proof** (*unfold aggregator-def max-aggregator.simps well-formed-SCF.simps disjoint3.simps*  
*set-equals-partition.simps, safe*)

**fix**

$A \ e \ e' \ d \ d' \ r \ r' :: 'a \ \text{set}$  **and**

$a :: 'a$

**assume**

$e' \cup r' \cup d' = e \cup r \cup d$  **and**

$a \notin d$  **and**

$a \notin r$  **and**

$a \in e'$

**thus**  $a \in e$

**by** *auto*

**next**

**fix**

$A \ e \ e' \ d \ d' \ r \ r' :: 'a \ \text{set}$  **and**

$a :: 'a$

**assume**

```

     $e' \cup r' \cup d' = e \cup r \cup d$  and
     $a \notin d$  and
     $a \notin r$  and
     $a \in d'$ 
  thus  $a \in e$ 
  by auto
qed

```

#### 4.9.4 Properties

The max-aggregator is conservative.

**theorem** *max-agg-consv[simp]: agg-conservative max-aggregator*

**proof** (*unfold agg-conservative-def, safe*)

**show** *aggregator max-aggregator*

**using** *max-agg-sound*

**by** *metis*

**next**

**fix**

$A \ e \ e' \ d \ d' \ r \ r' :: 'a \ \text{set}$  and

$a :: 'a$

**assume**

*elect-a*:  $a \in \text{elect-}r \ (\text{max-aggregator } A \ (e, r, d) \ (e', r', d'))$  and

*a-not-in-e'*:  $a \notin e'$

**have**  $a \in e \cup e'$

**using** *elect-a*

**by** *simp*

**thus**  $a \in e$

**using** *a-not-in-e'*

**by** *simp*

**next**

**fix**

$A \ e \ e' \ d \ d' \ r \ r' :: 'a \ \text{set}$  and

$a :: 'a$

**assume**

*wf-result*: *well-formed-SCF*  $A \ (e', r', d')$  and

*reject-a*:  $a \in \text{reject-}r \ (\text{max-aggregator } A \ (e, r, d) \ (e', r', d'))$  and

*a-not-in-r'*:  $a \notin r'$

**have**  $a \in r \cup r'$

**using** *wf-result reject-a*

**by** *force*

**thus**  $a \in r$

**using** *a-not-in-r'*

**by** *simp*

**next**

**fix**

$A \ e \ e' \ d \ d' \ r \ r' :: 'a \ \text{set}$  and

$a :: 'a$

**assume**

*defer-a*:  $a \in \text{defer-}r \ (\text{max-aggregator } A \ (e, r, d) \ (e', r', d'))$  and

```

    a-not-in-d':  $a \notin d'$ 
have  $a \in d \cup d'$ 
    using defer-a
    by force
thus  $a \in d$ 
    using a-not-in-d'
    by simp
qed

```

The max-aggregator is commutative.

```

theorem max-agg-comm[simp]: agg-commutative max-aggregator
    unfolding agg-commutative-def
    by auto

end

```

## 4.10 Termination Condition

```

theory Termination-Condition
    imports Social-Choice-Types/Result
begin

```

The termination condition is used in loops. It decides whether or not to terminate the loop after each iteration, depending on the current state of the loop.

```

type-synonym 'r Termination-Condition = 'r Result  $\Rightarrow$  bool

end

```

## 4.11 Defer Equal Condition

```

theory Defer-Equal-Condition
    imports Termination-Condition
begin

```

This is a family of termination conditions. For a natural number  $n$ , the according defer-equal condition is true if and only if the given result's defer-set contains exactly  $n$  elements.

```

fun defer-equal-condition :: nat  $\Rightarrow$  'a Termination-Condition where

```

*defer-equal-condition*  $n(e, r, d) = (\text{card } d = n)$

**end**



## Chapter 5

# Basic Modules

### 5.1 Defer Module

```
theory Defer-Module
  imports Component-Types/Electoral-Module
begin
```

The defer module is not concerned about the voter's ballots, and simply defers all alternatives. It is primarily used for defining an empty loop.

#### 5.1.1 Definition

```
fun defer-module :: ('a, 'v, 'a Result) Electoral-Module where
  defer-module V A p = ({}, {}, A)
```

#### 5.1.2 Soundness

```
theorem def-mod-sound[simp]: SCF-result.electoral-module defer-module
  unfolding SCF-result.electoral-module.simps
  by simp
```

#### 5.1.3 Properties

```
theorem def-mod-non-electing: non-electing defer-module
  unfolding non-electing-def
  by simp
```

```
theorem def-mod-def-lift-inv: defer-lift-invariance defer-module
  unfolding defer-lift-invariance-def
  by simp
```

```
end
```

## 5.2 Elect-First Module

```

theory Elect-First-Module
  imports Component-Types/Electoral-Module
begin

```

The elect first module elects the alternative that is most preferred on the first ballot and rejects all other alternatives.

### 5.2.1 Definition

```

fun least :: 'v :: wellorder set  $\Rightarrow$  'v where
  least V = (Least ( $\lambda$  v. v  $\in$  V))

```

```

fun elect-first-module :: ('a, 'v :: wellorder, 'a Result) Electoral-Module where
  elect-first-module V A p =
    ({a  $\in$  A. above (p (least V)) a = {a}},
     {a  $\in$  A. above (p (least V)) a  $\neq$  {a}},
     {})

```

### 5.2.2 Soundness

**theorem** *elect-first-mod-sound*: *SCF-result.electoral-module elect-first-module*

**proof** (*intro SCF-result.electoral-modI allI impI*)

```

  fix
    A :: 'a set and
    V :: 'v :: wellorder set and
    p :: ('a, 'v) Profile
  have {a  $\in$  A. above (p (least V)) a = {a}}
     $\cup$  {a  $\in$  A. above (p (least V)) a  $\neq$  {a}} = A
  by blast
  hence set-equals-partition A (elect-first-module V A p)
  by simp
  moreover have
     $\forall$  a  $\in$  A. (a  $\notin$  {a'  $\in$  A. above (p (least V)) a' = {a'}}  $\vee$ 
              a  $\notin$  {a'  $\in$  A. above (p (least V)) a'  $\neq$  {a'}})
  by simp
  hence {a  $\in$  A. above (p (least V)) a = {a}}
     $\cap$  {a  $\in$  A. above (p (least V)) a  $\neq$  {a}} = {}
  by blast
  hence disjoint3 (elect-first-module V A p)
  by simp
  ultimately show well-formed-SCF A (elect-first-module V A p)
  by simp
qed
end

```

## 5.3 Consensus Class

```

theory Consensus-Class
  imports Consensus
           ../Defer-Module
           ../Elect-First-Module
begin

```

A consensus class is a pair of a set of elections and a mapping that assigns a unique alternative to each election in that set (of elections). This alternative is then called the consensus alternative (winner). Here, we model the mapping by an electoral module that defers alternatives which are not in the consensus.

### 5.3.1 Definition

```

type-synonym ('a, 'v, 'r) Consensus-Class =
  ('a, 'v) Consensus × ('a, 'v, 'r) Electoral-Module

fun consensus-K :: ('a, 'v, 'r) Consensus-Class ⇒ ('a, 'v) Consensus where
  consensus-K K = fst K

fun rule-K :: ('a, 'v, 'r) Consensus-Class ⇒ ('a, 'v, 'r) Electoral-Module where
  rule-K K = snd K

```

### 5.3.2 Consensus Choice

Returns those consensus elections on a given alternative and voter set from a given consensus that are mapped to the given unique winner by a given consensus rule.

```

fun  $\mathcal{K}_E$  :: ('a, 'v, 'r Result) Consensus-Class ⇒ 'r ⇒ ('a, 'v) Election set where
   $\mathcal{K}_E$  K w =
    {(A, V, p) | A V p. (consensus-K K) (A, V, p) ∧ finite-profile V A p
      ∧ elect (rule-K K) V A p = {w}}

fun elections-K :: ('a, 'v, 'r Result) Consensus-Class ⇒ ('a, 'v) Election set where
  elections-K K =  $\bigcup ((\mathcal{K}_E K) \text{ 'UNIV})$ 

```

A consensus class is deemed well-formed if the result of its mapping is completely determined by its consensus, the elected set of the electoral module's result.

```

definition well-formed :: ('a, 'v) Consensus ⇒ ('a, 'v, 'r) Electoral-Module ⇒
  bool where
  well-formed c m ≡
    ∀ A V V' p p'.
      profile V A p ∧ profile V' A p' ∧ c (A, V, p) ∧ c (A, V', p')
        ⟶ m V A p = m V' A p'

```

A sensible social choice rule for a given arbitrary consensus and social choice rule  $r$  is the one that chooses the result of  $r$  for all consensus elections and defers all candidates otherwise.

```
fun consensus-choice :: ('a, 'v) Consensus  $\Rightarrow$ 
  ('a, 'v, 'a Result) Electoral-Module  $\Rightarrow$ 
  ('a, 'v, 'a Result) Consensus-Class where
  consensus-choice c m =
    (let
      w = ( $\lambda$  V A p. if c (A, V, p) then m V A p else defer-module V A p)
    in (c, w))
```

### 5.3.3 Auxiliary Lemmas

**lemma** unanimity'-consensus-imp-elect-fst-mod-well-formed:

**fixes** a :: 'a

**shows** well-formed

( $\lambda$  c. nonempty-set<sub>C</sub> c  $\wedge$  nonempty-profile<sub>C</sub> c  
 $\wedge$  equal-top<sub>C</sub>' a c) elect-first-module

**proof** (unfold well-formed-def, safe)

**fix**

a :: 'a **and**

A :: 'a set **and**

V V' :: 'v :: wellorder set **and**

p p' :: ('a, 'v) Profile

**let** ?cond =  $\lambda$  c. nonempty-set<sub>C</sub> c  $\wedge$  nonempty-profile<sub>C</sub> c  $\wedge$  equal-top<sub>C</sub>' a c

**assume**

prof-p: profile V A p **and**

prof-p': profile V' A p' **and**

eq-top-p: equal-top<sub>C</sub>' a (A, V, p) **and**

eq-top-p': equal-top<sub>C</sub>' a (A, V', p') **and**

not-empty-A: nonempty-set<sub>C</sub> (A, V, p) **and**

not-empty-A': nonempty-set<sub>C</sub> (A, V', p') **and**

not-empty-p: nonempty-profile<sub>C</sub> (A, V, p) **and**

not-empty-p': nonempty-profile<sub>C</sub> (A, V', p')

**hence**

cond-Ap: ?cond (A, V, p) **and**

cond-Ap': ?cond (A, V', p')

**by** simp-all

**have**  $\forall$  a'  $\in$  A.

((above (p (least V)) a' = {a'}) = (above (p' (least V')) a' = {a'}))

**proof**

**fix** a' :: 'a

**assume** a'-in-A: a'  $\in$  A

**show** (above (p (least V)) a' = {a'}) = (above (p' (least V')) a' = {a'})

**proof** (cases)

**assume** a' = a

**thus** ?thesis

**using** cond-Ap cond-Ap' Collect-mem-eq LeastI empty-Collect-eq equal-top<sub>C</sub>'.simps  
 nonempty-profile<sub>C</sub>.simps least.simps

```

    by (metis (no-types, lifting))
next
  assume a'-neq-a:  $a' \neq a$ 
  have non-empty:  $V \neq \{\}$   $\wedge$   $V' \neq \{\}$ 
    using not-empty-p not-empty-p'
    by simp
  hence  $A \neq \{\}$   $\wedge$  linear-order-on  $A$  (p (least V))
     $\wedge$  linear-order-on  $A$  (p' (least V'))
  using not-empty-A not-empty-A' prof-p prof-p' enumerate-0
    a'-in-A card.remove enumerate-in-set finite-enumerate-in-set
    least.elims all-not-in-conv zero-less-Suc
  unfolding profile-def
  by metis
  hence ( $a \in \text{above } (p \text{ (least V)})$   $a' \vee a' \in \text{above } (p \text{ (least V)})$   $a$ )
     $\wedge$  ( $a \in \text{above } (p' \text{ (least V')})$   $a' \vee a' \in \text{above } (p' \text{ (least V')})$   $a$ )
  using a'-in-A a'-neq-a eq-top-p
  unfolding above-def linear-order-on-def total-on-def
  by auto
  hence
    ( $\text{above } (p \text{ (least V)})$   $a = \{a\} \wedge \text{above } (p \text{ (least V)})$   $a' = \{a'\}$ 
       $\longrightarrow a = a'$ )
     $\wedge$  ( $\text{above } (p' \text{ (least V')})$   $a = \{a\} \wedge \text{above } (p' \text{ (least V')})$   $a' = \{a'\}$ 
       $\longrightarrow a = a'$ )
  by auto
  thus ?thesis
    using bot-nat-0.not-eq-extremum card-0-eq cond-Ap cond-Ap'
      enumerate-0 enumerate-in-set equal-topC'.simps
      finite-enumerate-in-set non-empty least.simps
    by metis
qed
qed
thus elect-first-module  $V$   $A$   $p = \text{elect-first-module } V' A p'$ 
  by auto
qed

lemma strong-unanimity'consensus-imp-elect-fst-mod-completely-determined:
  fixes  $r :: 'a \text{ Preference-Relation}$ 
  shows well-formed
    ( $\lambda c. \text{nonempty-set}_C c \wedge \text{nonempty-profile}_C c \wedge \text{equal-vote}_C' r c$ ) elect-first-module
proof (unfold well-formed-def, clarify)
fix
   $a :: 'a$  and
   $A :: 'a \text{ set}$  and
   $V V' :: 'v :: \text{wellorder set}$  and
   $p p' :: ('a, 'v) \text{ Profile}$ 
let ?cond =  $\lambda c. \text{nonempty-set}_C c \wedge \text{nonempty-profile}_C c \wedge \text{equal-vote}_C' r c$ 
assume
  prof-p: profile  $V$   $A$   $p$  and
  prof-p': profile  $V'$   $A$   $p'$  and

```

$eq\text{-}vote\text{-}p$ :  $equal\text{-}vote_C' r (A, V, p)$  **and**  
 $eq\text{-}vote\text{-}p'$ :  $equal\text{-}vote_C' r (A, V', p')$  **and**  
 $not\text{-}empty\text{-}A$ :  $nonempty\text{-}set_C (A, V, p)$  **and**  
 $not\text{-}empty\text{-}A'$ :  $nonempty\text{-}set_C (A, V', p')$  **and**  
 $not\text{-}empty\text{-}p$ :  $nonempty\text{-}profile_C (A, V, p)$  **and**  
 $not\text{-}empty\text{-}p'$ :  $nonempty\text{-}profile_C (A, V', p')$   
**hence**  
 $cond\text{-}Ap$ :  $?cond (A, V, p)$  **and**  
 $cond\text{-}Ap'$ :  $?cond (A, V', p')$   
**by** *simp-all*  
**have**  $p (\text{least } V) = r \wedge p' (\text{least } V') = r$   
**using**  $eq\text{-}vote\text{-}p$   $eq\text{-}vote\text{-}p'$   $not\text{-}empty\text{-}p$   $not\text{-}empty\text{-}p'$   
 $bot\text{-}nat\text{-}0.not\text{-}eq\text{-}extremum$   $card\text{-}0\text{-}eq$   $enumerate\text{-}0$   
 $enumerate\text{-}in\text{-}set$   $equal\text{-}vote_C'.simps$   $finite\text{-}enumerate\text{-}in\text{-}set$   
 $nonempty\text{-}profile_C.simps$   $least.elims$   
**by** (*metis* (*no-types*, *lifting*))  
**thus**  $elect\text{-}first\text{-}module\ V\ A\ p = elect\text{-}first\text{-}module\ V'\ A\ p'$   
**by** *auto*  
**qed**

**lemma** *strong-unanimity'consensus-imp-elect-fst-mod-well-formed*:  
**fixes**  $r :: 'a\ \text{Preference-Relation}$   
**shows** *well-formed*  
 $(\lambda\ c. nonempty\text{-}set_C\ c \wedge nonempty\text{-}profile_C\ c$   
 $\wedge equal\text{-}vote_C' r\ c) elect\text{-}first\text{-}module$   
**using** *strong-unanimity'consensus-imp-elect-fst-mod-completely-determined*  
**by** *blast*

**lemma** *cons-domain-well-formed*:  
**fixes**  $C :: ('a, 'v, 'r\ \text{Result})\ \text{Consensus-Class}$   
**shows**  $elections\text{-}\mathcal{K}\ C \subseteq well\text{-}formed\text{-}elections$   
**proof**  
**fix**  $E :: ('a, 'v)\ \text{Election}$   
**assume**  $E \in elections\text{-}\mathcal{K}\ C$   
**hence**  $fun_{\mathcal{E}}\ profile\ E$   
**unfolding**  $\mathcal{K}_{\mathcal{E}}.simps$   
**by** *force*  
**thus**  $E \in well\text{-}formed\text{-}elections$   
**unfolding** *well-formed-elections-def*  
**by** *simp*  
**qed**

**lemma** *cons-domain-finite*:  
**fixes**  $C :: ('a, 'v, 'r\ \text{Result})\ \text{Consensus-Class}$   
**shows**  
 $finite$ :  $elections\text{-}\mathcal{K}\ C \subseteq finite\text{-}elections$  **and**  
 $finite\text{-}voters$ :  $elections\text{-}\mathcal{K}\ C \subseteq finite\text{-}\mathcal{V}\text{-}elections$   
**proof** –  
**have**  $\forall\ E \in elections\text{-}\mathcal{K}\ C.$

```

    funE profile  $E \wedge$  finite (alternatives- $\mathcal{E}$   $E$ )  $\wedge$  finite (voters- $\mathcal{E}$   $E$ )
  unfolding  $\mathcal{K}_{\mathcal{E}}.simps$ 
  by force
  thus elections- $\mathcal{K}$   $C \subseteq$  finite-elections
    unfolding finite-elections-def funE.simps
    by blast
  thus elections- $\mathcal{K}$   $C \subseteq$  finite- $\mathcal{V}$ -elections
    unfolding finite-elections-def finite- $\mathcal{V}$ -elections-def
    by blast
qed

```

### 5.3.4 Consensus Rules

**definition** *non-empty-set* :: ( $'a$ ,  $'v$ ,  $'r$ ) Consensus-Class  $\Rightarrow$  bool **where**  
*non-empty-set*  $c \equiv \exists K. \text{consensus-}\mathcal{K} \ c \ K$

Unanimity condition.

**definition** *unanimity* :: ( $'a$ ,  $'v :: \text{wellorder}$ ,  $'a \text{ Result}$ ) Consensus-Class **where**  
*unanimity*  $\equiv \text{consensus-choice unanimity}_{\mathcal{C}} \text{ elect-first-module}$

Strong unanimity condition.

**definition** *strong-unanimity* :: ( $'a$ ,  $'v :: \text{wellorder}$ ,  $'a \text{ Result}$ ) Consensus-Class **where**  
*strong-unanimity*  $\equiv \text{consensus-choice strong-unanimity}_{\mathcal{C}} \text{ elect-first-module}$

### 5.3.5 Properties

**definition** *consensus-rule-anonymity* :: ( $'a$ ,  $'v$ ,  $'r$ ) Consensus-Class  $\Rightarrow$  bool **where**  
*consensus-rule-anonymity*  $c \equiv$   
 $(\forall A \ V \ p \ \pi :: ('v \Rightarrow 'v).$   
 $\text{bij } \pi \longrightarrow$   
 $(\text{let } (A', V', q) = (\text{rename } \pi \ (A, V, p)) \text{ in}$   
 $\text{profile } V \ A \ p \longrightarrow \text{profile } V' \ A' \ q$   
 $\longrightarrow \text{consensus-}\mathcal{K} \ c \ (A, V, p)$   
 $\longrightarrow (\text{consensus-}\mathcal{K} \ c \ (A', V', q) \wedge (\text{rule-}\mathcal{K} \ c \ V \ A \ p = \text{rule-}\mathcal{K} \ c \ V' \ A' \ q))))$

**fun** *consensus-rule-anonymity'* :: ( $'a$ ,  $'v$ ) Election set  $\Rightarrow$   
 $( 'a, 'v, 'r \text{ Result}) \text{ Consensus-Class} \Rightarrow$  bool **where**  
*consensus-rule-anonymity'*  $X \ C =$   
 $\text{is-symmetry } (\text{elect-r} \circ \text{fun}_{\mathcal{E}} \ (\text{rule-}\mathcal{K} \ C)) \ (\text{Invariance } (\text{anonymity}_{\mathcal{R}} \ X))$

**fun** (in result-properties) *consensus-rule-neutrality* :: ( $'a$ ,  $'v$ ) Election set  $\Rightarrow$   
 $( 'a, 'v, 'b \text{ Result}) \text{ Consensus-Class} \Rightarrow$  bool **where**  
*consensus-rule-neutrality*  $X \ C =$   
 $\text{is-symmetry } (\text{elect-r} \circ \text{fun}_{\mathcal{E}} \ (\text{rule-}\mathcal{K} \ C))$   
 $(\text{action-induced-equivariance } (\text{carrier bijection}_{\mathcal{AG}}) \ X \ (\varphi\text{-neutral } X) \ (\text{set-action } \psi))$

**fun** *consensus-rule-reversal-symmetry* :: ( $'a$ ,  $'v$ ) Election set  $\Rightarrow$

$(\text{'a}, \text{'v}, \text{'a rel Result}) \text{ Consensus-Class} \Rightarrow \text{bool}$  **where**  
 $\text{consensus-rule-reversal-symmetry } X \ C = \text{is-symmetry } (\text{elect-r} \circ \text{fun}_{\mathcal{E}} (\text{rule-}\mathcal{K} \ C))$   
 $(\text{action-induced-equivariance } (\text{carrier reversal}_G) \ X \ (\varphi\text{-reverse } X) \ (\text{set-action } \psi\text{-reverse}))$

### 5.3.6 Inference Rules

**lemma** *if-else-cons-equivar*:

**fixes**

$m \ n :: (\text{'a}, \text{'v}, \text{'a Result}) \text{ Electoral-Module}$  **and**  
 $c :: (\text{'a}, \text{'v}) \text{ Consensus}$  **and**  
 $G :: \text{'b set}$  **and**  
 $X :: (\text{'a}, \text{'v}) \text{ Election set}$  **and**  
 $\varphi :: (\text{'b}, (\text{'a}, \text{'v}) \text{ Election}) \text{ binary-fun}$  **and**  
 $\psi :: (\text{'b}, \text{'a}) \text{ binary-fun}$  **and**  
 $f :: \text{'a Result} \Rightarrow \text{'a set}$

**defines**

$\text{equivar} \equiv \text{action-induced-equivariance } G \ X \ \varphi \ (\text{set-action } \psi)$  **and**  
 $\text{if-else-cons} \equiv (c, (\lambda \ V \ A \ p. \text{if } c \ (A, \ V, \ p) \text{ then } m \ V \ A \ p \text{ else } n \ V \ A \ p))$

**assumes**

$\text{equivar-m}: \text{is-symmetry } (f \circ \text{fun}_{\mathcal{E}} \ m)$  **equivar** **and**  
 $\text{equivar-n}: \text{is-symmetry } (f \circ \text{fun}_{\mathcal{E}} \ n)$  **equivar** **and**  
 $\text{invar-cons}: \text{is-symmetry } c \ (\text{Invariance } (\text{action-induced-rel } G \ X \ \varphi))$

**shows**  $\text{is-symmetry } (f \circ \text{fun}_{\mathcal{E}} \ (\text{rule-}\mathcal{K} \ \text{if-else-cons}))$

$(\text{action-induced-equivariance } G \ X \ \varphi \ (\text{set-action } \psi))$

**proof**  $(\text{unfold rewrite-equivariance, intro ballI impI})$

**fix**

$E :: (\text{'a}, \text{'v}) \text{ Election}$  **and**  
 $g :: \text{'b}$

**assume**

$g\text{-in-}G: g \in G$  **and**  
 $E\text{-in-}X: E \in X$

**show**  $(f \circ \text{fun}_{\mathcal{E}} \ (\text{rule-}\mathcal{K} \ \text{if-else-cons})) \ (\varphi \ g \ E) =$

$\text{set-action } \psi \ g \ ((f \circ \text{fun}_{\mathcal{E}} \ (\text{rule-}\mathcal{K} \ \text{if-else-cons})) \ E)$

**proof**  $(\text{cases } c \ E)$

**case** *True*

**hence**  $c \ (\varphi \ g \ E)$

**using** *invar-cons rewrite-invar-ind-by-act g-in-G E-in-X*

**by** *metis*

**hence**  $(f \circ \text{fun}_{\mathcal{E}} \ (\text{rule-}\mathcal{K} \ \text{if-else-cons})) \ (\varphi \ g \ E) =$

$(f \circ \text{fun}_{\mathcal{E}} \ m) \ (\varphi \ g \ E)$

**unfolding** *if-else-cons-def*

**by** *simp*

**also have**  $(f \circ \text{fun}_{\mathcal{E}} \ m) \ (\varphi \ g \ E) =$

$\text{set-action } \psi \ g \ ((f \circ \text{fun}_{\mathcal{E}} \ m) \ E)$

**using** *equivar-m E-in-X g-in-G rewrite-equivariance*

**unfolding** *equivar-def*

**by**  $(\text{metis } (\text{mono-tags, lifting}))$

**also have**  $(f \circ \text{fun}_{\mathcal{E}} \ m) \ E =$



```

      (f ∘ funε (rule- $\mathcal{K}$  if-else-cons)) E
    using True E-in-X g-in-G invar-cons if-else-cons-def
    by simp
  finally show ?thesis
    by simp
next
  case False
  hence ¬ c (φ g E)
    using invar-cons rewrite-invar-ind-by-act g-in-G E-in-X
    by metis
  hence (f ∘ funε (rule- $\mathcal{K}$  if-else-cons)) (φ g E) =
    (f ∘ funε n) (φ g E)
    unfolding if-else-cons-def
    by simp
  also have (f ∘ funε n) (φ g E) =
    set-action ψ g ((f ∘ funε n) E)
    using equivar-n E-in-X g-in-G rewrite-equivariance
    unfolding equivar-def
    by (metis (mono-tags, lifting))
  also have (f ∘ funε n) E =
    (f ∘ funε (rule- $\mathcal{K}$  if-else-cons)) E
    using False E-in-X g-in-G invar-cons
    unfolding if-else-cons-def
    by simp
  finally show ?thesis
    by simp
qed
qed

lemma consensus-choice-anonymous:
  fixes
    α β :: ('a, 'v) Consensus and
    m :: ('a, 'v, 'a Result) Electoral-Module and
    β' :: 'b ⇒ ('a, 'v) Consensus
  assumes
    beta-sat: β = (λ E. ∃ a. β' a E) and
    beta'-anon: ∀ x. consensus-anonymity (β' x) and
    anon-cons-cond: consensus-anonymity α and
    conditions-univ: ∀ x. well-formed (λ E. α E ∧ β' x E) m
  shows consensus-rule-anonymity (consensus-choice (λ E. α E ∧ β E) m)
proof (unfold consensus-rule-anonymity-def Let-def, safe)
  fix
    A A' :: 'a set and
    V V' :: 'v set and
    p q :: ('a, 'v) Profile and
    π :: 'v ⇒ 'v
  assume
    bij-π: bij π and
    prof-p: profile V A p and

```

*prof-q*: profile  $V' A' q$  **and**  
*renamed*: rename  $\pi (A, V, p) = (A', V', q)$  **and**  
*consensus-cond*:  
 $\text{consensus-}\mathcal{K} (\text{consensus-choice } (\lambda E. \alpha E \wedge \beta E) m) (A, V, p)$   
**hence**  $(\lambda E. \alpha E \wedge \beta E) (A, V, p)$   
**by** *simp*  
**hence**  
 $\text{alpha-}Ap: \alpha (A, V, p)$  **and**  
 $\text{beta-}Ap: \beta (A, V, p)$   
**by** *simp-all*  
**have**  $\text{alpha-}A\text{-perm-}p: \alpha (A', V', q)$   
**using** *anon-cons-cond alpha-Ap bij- $\pi$  prof-p prof-q renamed*  
**unfolding** *consensus-anonymity-def*  
**by** *fastforce*  
**moreover have**  $\beta (A', V', q)$   
**using** *beta'-anon beta-Ap beta-sat*  
 $\text{ex-anon-cons-imp-cons-anonymous}[of \ \beta'] \text{ bij-}\pi$   
 $\text{prof-p renamed beta'-anon cons-anon-invariant}[of \ \beta]$   
**unfolding** *consensus-anonymity-def*  
**by** *blast*  
**ultimately show** *em-cond-perm*:  
 $\text{consensus-}\mathcal{K} (\text{consensus-choice } (\lambda E. \alpha E \wedge \beta E) m) (A', V', q)$   
**using** *beta-Ap beta-sat ex-anon-cons-imp-cons-anonymous bij- $\pi$*   
 $\text{prof-p prof-q}$   
**by** *simp*  
**have**  $\exists x. \beta' x (A, V, p)$   
**using** *beta-Ap beta-sat*  
**by** *simp*  
**then obtain**  $x :: 'b$  **where**  
 $\text{beta'-}x\text{-}Ap: \beta' x (A, V, p)$   
**by** *metis*  
**hence**  $\text{beta'-}x\text{-}A\text{-perm-}p: \beta' x (A', V', q)$   
**using** *beta'-anon bij- $\pi$  prof-p renamed*  
 $\text{cons-anon-invariant prof-q}$   
**unfolding** *consensus-anonymity-def*  
**by** *blast*  
**have**  $m \ V \ A \ p = m \ V' \ A' \ q$   
**using** *alpha-Ap alpha-A-perm-p beta'-x-Ap beta'-x-A-perm-p*  
 $\text{conditions-univ prof-p prof-q rename.simps prod.inject renamed}$   
**unfolding** *well-formed-def*  
**by** *metis*  
**thus**  $\text{rule-}\mathcal{K} (\text{consensus-choice } (\lambda E. \alpha E \wedge \beta E) m) \ V \ A \ p =$   
 $\text{rule-}\mathcal{K} (\text{consensus-choice } (\lambda E. \alpha E \wedge \beta E) m) \ V' \ A' \ q$   
**using** *consensus-cond em-cond-perm*  
**by** *simp*  
**qed**

### 5.3.7 Theorems

#### Anonymity

**lemma** *unanimity-anonymous: consensus-rule-anonymity unanimity*

**proof** (*unfold unanimity-def*)

**let** *?ne-cond* = ( $\lambda c. \text{nonempty-set}_C c \wedge \text{nonempty-profile}_C c$ )

**have** *consensus-anonymity ?ne-cond*

**using** *nonempty-set-cons-anonymous nonempty-profile-cons-anonymous cons-anon-conj*  
**by** *auto*

**moreover have** *equal-top<sub>C</sub>* = ( $\lambda c. \exists a. \text{equal-top}_C' a c$ )

**by** *fastforce*

**ultimately have** *consensus-rule-anonymity*

(*consensus-choice*

( $\lambda c. \text{nonempty-set}_C c \wedge \text{nonempty-profile}_C c \wedge \text{equal-top}_C c$ ) *elect-first-module*)

**using** *consensus-choice-anonymous[of equal-top<sub>C</sub>] equal-top-cons'-anonymous*  
*unanimity'-consensus-imp-elect-fst-mod-well-formed*

**by** *fastforce*

**moreover have** *consensus-choice*

( $\lambda c. \text{nonempty-set}_C c \wedge \text{nonempty-profile}_C c \wedge \text{equal-top}_C c$ )

*elect-first-module* =

*consensus-choice unanimity<sub>C</sub> elect-first-module*

**using** *unanimity<sub>C</sub>.simps*

**by** *metis*

**ultimately show** *consensus-rule-anonymity (consensus-choice unanimity<sub>C</sub> elect-first-module)*

**by** (*metis (no-types)*)

**qed**

**lemma** *strong-unanimity-anonymous: consensus-rule-anonymity strong-unanimity*

**proof** (*unfold strong-unanimity-def*)

**have** *consensus-anonymity* ( $\lambda c. \text{nonempty-set}_C c \wedge \text{nonempty-profile}_C c$ )

**using** *nonempty-set-cons-anonymous nonempty-profile-cons-anonymous cons-anon-conj*

**unfolding** *consensus-anonymity-def*

**by** *simp*

**moreover have** *equal-vote<sub>C</sub>* = ( $\lambda c. \exists v. \text{equal-vote}_C' v c$ )

**by** *fastforce*

**ultimately have** *consensus-rule-anonymity*

(*consensus-choice*

( $\lambda c. \text{nonempty-set}_C c \wedge \text{nonempty-profile}_C c \wedge \text{equal-vote}_C c$ ) *elect-first-module*)

**using** *consensus-choice-anonymous[of equal-vote<sub>C</sub>] nonempty-set-cons-anonymous*  
*nonempty-profile-cons-anonymous eq-vote-cons'-anonymous*  
*strong-unanimity'consensus-imp-elect-fst-mod-well-formed*

**by** *fastforce*

**moreover have**

*consensus-choice* ( $\lambda c. \text{nonempty-set}_C c \wedge \text{nonempty-profile}_C c \wedge \text{equal-vote}_C c$ )

*elect-first-module* =

*consensus-choice strong-unanimity<sub>C</sub> elect-first-module*

**unfolding** *strong-unanimity<sub>C</sub>.simps*

**by** *metis*

**ultimately show**

$\text{consensus-rule-anonymity } (\text{consensus-choice strong-unanimity}_C \text{ elect-first-module})$   
 by (metis (no-types))  
 qed

## Neutrality

**lemma** *defer-winners-equivariant:*

**fixes**  
 $G :: 'b \text{ set}$  **and**  
 $E :: ('a, 'v) \text{ Election set}$  **and**  
 $\varphi :: ('b, ('a, 'v) \text{ Election}) \text{ binary-fun}$  **and**  
 $\psi :: ('b, 'a) \text{ binary-fun}$   
**shows**  $\text{is-symmetry } (\text{elect-r} \circ \text{fun}_E \text{ defer-module})$   
 $(\text{action-induced-equivariance } G \ E \ \varphi \ (\text{set-action } \psi))$   
**using** *rewrite-equivariance*  
**by** *fastforce*

**lemma** *elect-first-winners-neutral: is-symmetry*  $(\text{elect-r} \circ \text{fun}_E \text{ elect-first-module})$   
 $(\text{action-induced-equivariance } (\text{carrier bijection}_{AG}))$   
 $\text{well-formed-elections } (\varphi\text{-neutral well-formed-elections})$   
 $(\text{set-action } \psi\text{-neutral}_c))$

**proof** (*unfold rewrite-equivariance, clarify*)

**fix**  
 $A :: 'a \text{ set}$  **and**  
 $V :: 'v :: \text{wellorder set}$  **and**  
 $p :: ('a, 'v) \text{ Profile}$  **and**  
 $\pi :: 'a \Rightarrow 'a$

**assume**  
 $\text{bij-carrier-}\pi: \pi \in \text{carrier bijection}_{AG}$  **and**  
 $\text{valid: } (A, V, p) \in \text{well-formed-elections}$

**hence**  $\text{bijective-}\pi: \text{bij } \pi$   
**unfolding**  $\text{bijection}_{AG}\text{-def}$   
**using** *rewrite-carrier*  
**by** *blast*

**hence**  $\text{inv: } \forall a. a = \pi (\text{the-inv } \pi \ a)$   
**by** (*simp add: f-the-inv-into-f-bij-betw*)

**from**  $\text{bij-carrier-}\pi \text{ valid}$  **have**  
 $(\text{elect-r} \circ \text{fun}_E \text{ elect-first-module})$   
 $(\varphi\text{-neutral well-formed-elections } \pi \ (A, V, p)) =$   
 $\{a \in \pi \text{ ' } A. \text{ above } (\text{rel-rename } \pi \ (p \ (\text{least } V))) \ a = \{a\}\}$   
**by** *simp*

**moreover have**  
 $\{a \in \pi \text{ ' } A. \text{ above } (\text{rel-rename } \pi \ (p \ (\text{least } V))) \ a = \{a\}\} =$   
 $\{a \in \pi \text{ ' } A. \{b. (a, b) \in \{(\pi \ a, \pi \ b) \mid a \ b. (a, b) \in p \ (\text{least } V)\}\} = \{a\}\}$   
**unfolding** *above-def*  
**by** *simp*

**ultimately have** *elect-simp:*  
 $(\text{elect-r} \circ \text{fun}_E \text{ elect-first-module})$   
 $(\varphi\text{-neutral well-formed-elections } \pi \ (A, V, p)) =$

$\{a \in \pi \text{ ' } A. \{b. (a, b) \in \{(\pi a, \pi b) \mid a b. (a, b) \in p \text{ (least } V)\}\} = \{a\}\}$   
**by simp**  
**have**  $\forall a \in \pi \text{ ' } A. \{b. (a, b) \in \{(\pi x, \pi y) \mid x y. (x, y) \in p \text{ (least } V)\}\} =$   
 $\{\pi b \mid b. (a, \pi b) \in \{(\pi x, \pi y) \mid x y. (x, y) \in p \text{ (least } V)\}\}$   
**by blast**  
**moreover have**  $\forall a \in \pi \text{ ' } A.$   
 $\{\pi b \mid b. (a, \pi b) \in \{(\pi x, \pi y) \mid x y. (x, y) \in p \text{ (least } V)\}\} =$   
 $\{\pi b \mid b. (\pi (\text{the-inv } \pi a), \pi b) \in \{(\pi x, \pi y) \mid x y. (x, y) \in p \text{ (least } V)\}\}$   
**using bijective- $\pi$**   
**by (simp add: f-the-inv-into-f-bij-betw)**  
**moreover have**  $\forall a \in \pi \text{ ' } A. \forall b.$   
 $((\pi (\text{the-inv } \pi a), \pi b) \in \{(\pi x, \pi y) \mid x y. (x, y) \in p \text{ (least } V)\}) =$   
 $((\text{the-inv } \pi a, b) \in \{(x, y) \mid x y. (x, y) \in p \text{ (least } V)\})$   
**using bijective- $\pi$  rel-rename-helper[ $\text{of } \pi$ ]**  
**by auto**  
**moreover have**  $\{(x, y) \mid x y. (x, y) \in p \text{ (least } V)\} = p \text{ (least } V)$   
**by simp**  
**ultimately have**  
 $\forall a \in \pi \text{ ' } A. (\{b. (a, b) \in \{(\pi a, \pi b) \mid a b. (a, b) \in p \text{ (least } V)\}\} = \{a\}) =$   
 $(\{\pi b \mid b. (\text{the-inv } \pi a, b) \in p \text{ (least } V)\} = \{a\})$   
**by force**  
**hence**  $\{a \in \pi \text{ ' } A.$   
 $\{b. (a, b) \in \{(\pi a, \pi b) \mid a b. (a, b) \in p \text{ (least } V)\}\} = \{a\}\} =$   
 $\{a \in \pi \text{ ' } A. \{\pi b \mid b. (\text{the-inv } \pi a, b) \in p \text{ (least } V)\} = \{a\}\}$   
**by blast**  
**hence**  $(\text{elect-r} \circ \text{fun}_{\mathcal{E}} \text{ elect-first-module})$   
 $(\varphi\text{-neutral well-formed-elections } \pi (A, V, p)) =$   
 $\{a \in \pi \text{ ' } A. \{\pi b \mid b. (\text{the-inv } \pi a, b) \in p \text{ (least } V)\} = \{a\}\}$   
**using elect-simp**  
**by simp**  
**also have**  $\dots = \pi \text{ ' } \{a \in A. \pi \text{ ' } \{b \mid b. (a, b) \in p \text{ (least } V)\} = \pi \text{ ' } \{a\}\}$   
**using bijective- $\pi$  inv bij-is-inj the-inv-f-f**  
**by fastforce**  
**finally have**  
 $(\text{elect-r} \circ \text{fun}_{\mathcal{E}} \text{ elect-first-module})$   
 $(\varphi\text{-neutral well-formed-elections } \pi (A, V, p)) =$   
 $\pi \text{ ' } \{a \in A. \pi \text{ ' } (\text{above } (p \text{ (least } V)) a) = \pi \text{ ' } \{a\}\}$   
**unfolding above-def**  
**by simp**  
**moreover have**  
 $\forall a. (\pi \text{ ' } (\text{above } (p \text{ (least } V)) a) = \pi \text{ ' } \{a\}) =$   
 $(\text{the-inv } \pi \text{ ' } \pi \text{ ' } \text{above } (p \text{ (least } V)) a = \text{the-inv } \pi \text{ ' } \pi \text{ ' } \{a\})$   
**using bijective- $\pi$  bij-betw-the-inv-into bij-def inj-image-eq-iff**  
**by metis**  
**moreover have**  
 $\forall a. (\text{the-inv } \pi \text{ ' } \pi \text{ ' } \text{above } (p \text{ (least } V)) a = \text{the-inv } \pi \text{ ' } \pi \text{ ' } \{a\}) =$   
 $(\text{above } (p \text{ (least } V)) a = \{a\})$   
**using bijective- $\pi$  bij-betw-imp-inj-on bij-betw-the-inv-into inj-image-eq-iff**  
**by metis**

**ultimately have**  
 $(\text{elect-r} \circ \text{fun}_{\mathcal{E}} \text{ elect-first-module})$   
 $(\varphi\text{-neutral well-formed-elections } \pi (A, V, p)) =$   
 $\pi \text{ ' } \{a \in A. \text{ above } (p (\text{least } V)) a = \{a\}\}$   
**by** *presburger*  
**moreover have**  
 $\text{elect elect-first-module } V A p = \{a \in A. \text{ above } (p (\text{least } V)) a = \{a\}\}$   
**by** *simp*  
**moreover have** *set-action*  $\psi\text{-neutral}_c \pi$   
 $((\text{elect-r} \circ \text{fun}_{\mathcal{E}} \text{ elect-first-module}) (A, V, p)) =$   
 $\pi \text{ ' } (\text{elect elect-first-module } V A p)$   
**by** *auto*  
**ultimately show**  
 $(\text{elect-r} \circ \text{fun}_{\mathcal{E}} \text{ elect-first-module})$   
 $(\varphi\text{-neutral well-formed-elections } \pi (A, V, p)) =$   
 $\text{set-action } \psi\text{-neutral}_c \pi$   
 $((\text{elect-r} \circ \text{fun}_{\mathcal{E}} \text{ elect-first-module}) (A, V, p))$   
**by** *blast*  
**qed**

**lemma** *strong-unanimity-neutral*:  
**defines**  $\text{domain} \equiv \text{well-formed-elections} \cap \text{Collect strong-unanimity}_c$   
 — We want to show neutrality on a set as general as possible, as this implies subset neutrality.  
**shows** *SCF-properties.consensus-rule-neutrality domain strong-unanimity*  
**proof** —  
**have** *coincides*:  
 $\forall \pi. \forall E \in \text{domain}. \varphi\text{-neutral domain } \pi E =$   
 $\varphi\text{-neutral well-formed-elections } \pi E$   
**unfolding** *domain-def*  $\varphi\text{-neutral.simps}$   
**by** *auto*  
**hence**  $\text{neutrality}_{\mathcal{R}} \text{ domain} \subseteq \text{neutrality}_{\mathcal{R}} \text{ well-formed-elections}$   
**unfolding** *neutrality<sub>R</sub>.simps action-induced-rel.simps*  
**using** *domain-def*  
**by** *auto*  
**hence** *consensus-neutrality domain strong-unanimity<sub>c</sub>*  
**using** *strong-unanimity<sub>c</sub>-neutral invar-under-subset-rel*  
**unfolding** *consensus-neutrality.simps*  
**by** *blast*  
**hence** *is-symmetry strong-unanimity<sub>c</sub>*  
 $(\text{Invariance } (\text{action-induced-rel } (\text{carrier bijection}_{\mathcal{AG}})$   
 $\text{domain } (\varphi\text{-neutral well-formed-elections})))$   
**unfolding** *consensus-neutrality.simps neutrality<sub>R</sub>.simps*  
**using** *coincides coinciding-actions-ind-equal-rel*  
**by** *metis*  
**moreover have** *is-symmetry*  $(\text{elect-r} \circ \text{fun}_{\mathcal{E}} \text{ elect-first-module})$   
 $(\text{action-induced-equivariance } (\text{carrier bijection}_{\mathcal{AG}})$   
 $\text{domain } (\varphi\text{-neutral well-formed-elections}) (\text{set-action } \psi\text{-neutral}_c))$   
**using** *elect-first-winners-neutral*

**unfolding** *domain-def action-induced-equivariance-def*  
**using** *equivar-under-subset*  
**by** *blast*  
**ultimately have** *is-symmetry (elect-r  $\circ$  fun <sub>$\mathcal{E}$</sub>  (rule- $\mathcal{K}$  strong-unanimity))*  
*(action-induced-equivariance (carrier bijection <sub>$\mathcal{AG}$</sub> ) domain*  
*( $\varphi$ -neutral well-formed-elections) (set-action  $\psi$ -neutral <sub>$\mathcal{C}$</sub> ))*  
**using** *defer-winners-equivariant[of - domain -  $\psi$ -neutral <sub>$\mathcal{C}$</sub> ]*  
*if-else-cons-equivar[of - - domain -  $\psi$ -neutral <sub>$\mathcal{C}$</sub>  - strong-unanimity <sub>$\mathcal{C}$</sub> ]*  
**unfolding** *strong-unanimity-def*  
**by** *fastforce*  
**thus** *?thesis*  
**unfolding** *SCF-properties.consensus-rule-neutrality.simps*  
**using** *coincides equivar-ind-by-act-coincide*  
**by** *(metis (no-types, lifting))*  
**qed**

**lemma** *strong-unanimity-neutral': SCF-properties.consensus-rule-neutrality*  
*(elections- $\mathcal{K}$  strong-unanimity) strong-unanimity*  
**proof** –  
**have** *elections- $\mathcal{K}$  strong-unanimity  $\subseteq$  well-formed-elections  $\cap$  Collect strong-unanimity <sub>$\mathcal{C}$</sub>*   
**unfolding** *well-formed-elections-def  $\mathcal{K}_{\mathcal{E}}$ .simps strong-unanimity-def*  
**by** *force*  
**moreover from this have** *coincide:*  
 $\forall \pi. \forall E \in \text{elections-}\mathcal{K} \text{ strong-unanimity.}$   
 $\varphi\text{-neutral (well-formed-elections} \cap \text{Collect strong-unanimity}_{\mathcal{C}}) \pi E =$   
 $\varphi\text{-neutral (elections-}\mathcal{K} \text{ strong-unanimity)} \pi E$   
**unfolding**  *$\varphi$ -neutral.simps*  
**using** *extensional-continuation-subset*  
**by** *(metis (no-types, lifting))*  
**ultimately have**  
*is-symmetry (elect-r  $\circ$  fun <sub>$\mathcal{E}$</sub>  (rule- $\mathcal{K}$  strong-unanimity))*  
*(action-induced-equivariance (carrier bijection <sub>$\mathcal{AG}$</sub> ) (elections- $\mathcal{K}$  strong-unanimity)*  
*( $\varphi$ -neutral (well-formed-elections  $\cap$  Collect strong-unanimity <sub>$\mathcal{C}$</sub> ))*  
*(set-action  $\psi$ -neutral <sub>$\mathcal{C}$</sub> ))*  
**using** *strong-unanimity-neutral equivar-under-subset*  
**unfolding** *action-induced-equivariance-def SCF-properties.consensus-rule-neutrality.simps*  
**by** *blast*  
**thus** *?thesis*  
**unfolding** *SCF-properties.consensus-rule-neutrality.simps*  
**using** *coincide equivar-ind-by-act-coincide*  
**by** *(metis (no-types))*  
**qed**

**lemma** *strong-unanimity-closed-under-neutrality: closed-restricted-rel*  
*(neutrality <sub>$\mathcal{R}$</sub>  well-formed-elections) well-formed-elections*  
*(elections- $\mathcal{K}$  strong-unanimity)*  
**proof** *(unfold closed-restricted-rel.simps restricted-rel.simps neutrality <sub>$\mathcal{R}$</sub> .simps*  
*action-induced-rel.simps elections- $\mathcal{K}$ .simps, safe)*  
**fix**

$A \ A' :: 'a \text{ set}$  **and**  
 $V \ V' :: 'b \text{ set}$  **and**  
 $p \ p' :: ('a, 'b) \text{ Profile}$  **and**  
 $\pi :: 'a \Rightarrow 'a$  **and**  
 $a :: 'a$   
**assume**  
 $\text{prof}: (A, V, p) \in \text{well-formed-elections}$  **and**  
 $\text{cons}: (A, V, p) \in \mathcal{K}_{\mathcal{E}} \text{ strong-unanimity } a$  **and**  
 $\text{bij-carrier-}\pi: \pi \in \text{carrier bijection}_{\mathcal{AG}}$  **and**  
 $\text{img}: \varphi\text{-neutral well-formed-elections } \pi \ (A, V, p) = (A', V', p')$   
**hence**  $\text{fin}: (A, V, p) \in \text{finite-elections}$   
**unfolding**  $\mathcal{K}_{\mathcal{E}}.\text{sims finite-elections-def}$   
**by**  $\text{simp}$   
**hence**  $\text{valid}': (A', V', p') \in \text{well-formed-elections}$   
**using**  $\text{bij-carrier-}\pi \ \text{img } \varphi\text{-neutral-action.group-action-axioms}$   
 $\text{group-action.element-image prof}$   
**unfolding**  $\text{finite-elections-def}$   
**by**  $(\text{metis (mono-tags, lifting)})$   
**moreover have**  $V' = V \wedge A' = \pi \ `A$   
**using**  $\text{img fin alternatives-rename.elims fstI prof sndI}$   
**unfolding**  $\text{extensional-continuation.sims } \varphi\text{-neutral.sims}$   
 $\text{alternatives-}\mathcal{E}.\text{sims voters-}\mathcal{E}.\text{sims}$   
**by**  $(\text{metis (no-types, lifting)})$   
**ultimately have**  $\text{prof}': \text{finite-profile } V' \ A' \ p'$   
**using**  $\text{fin bij-carrier-}\pi \ \text{CollectD finite-imageI fst-eqD snd-eqD}$   
**unfolding**  $\text{finite-elections-def well-formed-elections-def alternatives-}\mathcal{E}.\text{sims}$   
 $\text{voters-}\mathcal{E}.\text{sims profile-}\mathcal{E}.\text{sims}$   
**by**  $(\text{metis (no-types, lifting)})$   
**let**  $?domain = \text{well-formed-elections} \cap \text{Collect strong-unanimity}_{\mathcal{C}}$   
**have**  $((A, V, p), (A', V', p')) \in \text{neutrality}_{\mathcal{R}} \text{ well-formed-elections}$   
**using**  $\text{bij-carrier-}\pi \ \text{img fin valid'}$   
**unfolding**  $\text{neutrality}_{\mathcal{R}}.\text{sims action-induced-rel.sims}$   
 $\text{finite-elections-def well-formed-elections-def}$   
**by**  $\text{blast}$   
**moreover have**  $\text{unanimous}: (A, V, p) \in ?domain$   
**using**  $\text{cons fin}$   
**unfolding**  $\mathcal{K}_{\mathcal{E}}.\text{sims strong-unanimity-def well-formed-elections-def}$   
**by**  $\text{simp}$   
**ultimately have**  $\text{unanimous}': (A', V', p') \in ?domain$   
**using**  $\text{strong-unanimity}_{\mathcal{C}}\text{-neutral valid'}$   
**unfolding**  $\text{consensus-neutrality.sims}$   
**by**  $\text{force}$   
**have**  $\text{rewrite}: \forall \ \pi \in \text{carrier bijection}_{\mathcal{AG}}.$   
 $\varphi\text{-neutral } ?domain \ \pi \ (A, V, p) \in ?domain$   
 $\longrightarrow (\text{elect-r} \circ \text{fun}_{\mathcal{E}} \ (\text{rule-}\mathcal{K} \ \text{strong-unanimity}))$   
 $(\varphi\text{-neutral } ?domain \ \pi \ (A, V, p)) =$   
 $\text{set-action } \psi\text{-neutral}_{\mathcal{C}} \ \pi$   
 $((\text{elect-r} \circ \text{fun}_{\mathcal{E}} \ (\text{rule-}\mathcal{K} \ \text{strong-unanimity})) \ (A, V, p))$   
**using**  $\text{strong-unanimity-neutral unanimous}$



```

      rewrite-equivariance[of elect-r  $\circ$  fun $_{\mathcal{E}}$  (rule- $\mathcal{K}$  strong-unanimity) carrier
bijection $_{\mathcal{AG}}$ ]
  unfolding SCF-properties.consensus-rule-neutrality.simps
  by metis
  have img':  $\varphi$ -neutral ?domain  $\pi$  (A, V, p) = (A', V', p')
  using img unanimous
  by simp
  hence elect (rule- $\mathcal{K}$  strong-unanimity) V' A' p' =
    (elect-r  $\circ$  fun $_{\mathcal{E}}$  (rule- $\mathcal{K}$  strong-unanimity))
    ( $\varphi$ -neutral ?domain  $\pi$  (A, V, p))
  by simp
  also have
    ... = set-action  $\psi$ -neutral $_c$   $\pi$ 
      ((elect-r  $\circ$  fun $_{\mathcal{E}}$  (rule- $\mathcal{K}$  strong-unanimity)) (A, V, p))
  using bij-carrier- $\pi$  img' unanimous' rewrite
  by metis
  also have ... = set-action  $\psi$ -neutral $_c$   $\pi$  {a}
  using cons
  unfolding  $\mathcal{K}_{\mathcal{E}}$ .simps
  by simp
  finally have (A', V', p')  $\in$  elections- $\mathcal{K}$  strong-unanimity
  unfolding  $\mathcal{K}_{\mathcal{E}}$ .simps strong-unanimity-def consensus-choice.simps
  using unanimous' prof'
  by simp
  hence ((A, V, p), (A', V', p'))
     $\in \bigcup$  (range ( $\mathcal{K}_{\mathcal{E}}$  strong-unanimity))  $\times \bigcup$  (range ( $\mathcal{K}_{\mathcal{E}}$  strong-unanimity))
  unfolding elections- $\mathcal{K}$ .simps
  using cons
  by blast
  moreover have
     $\exists \pi \in$  carrier bijection $_{\mathcal{AG}}$ .
       $\varphi$ -neutral well-formed-elections  $\pi$  (A, V, p) = (A', V', p')
  using img bij-carrier- $\pi$ 
  unfolding bijection $_{\mathcal{AG}}$ -def
  by blast
  ultimately show (A', V', p')  $\in \bigcup$  (range ( $\mathcal{K}_{\mathcal{E}}$  strong-unanimity))
  by blast
qed
end

```

## 5.4 Distance Rationalization

```

theory Distance-Rationalization
  imports Social-Choice-Types/Refined-Types/Preference-List
          Consensus-Class
          Distance

```

**begin**

A distance rationalization of a voting rule is its interpretation as a procedure that elects an uncontroversial winner if there is one, and otherwise elects the alternatives that are as close to becoming an uncontroversial winner as possible. Within general distance rationalization, a voting rule is characterized by a distance on profiles and a consensus class.

### 5.4.1 Definitions

Returns the distance of an election to the preimage of a unique winner under the given consensus elections and consensus rule.

**fun** *score* :: ('a, 'v) Election Distance  $\Rightarrow$  ('a, 'v, 'r Result) Consensus-Class  $\Rightarrow$  ('a, 'v) Election  $\Rightarrow$  'r  $\Rightarrow$  ereal **where**  
*score* *d* *K* *E* *w* = Inf (*d* *E* ' ( $\mathcal{K}_E$  *K* *w*))

**fun** (**in** *result*)  $\mathcal{R}_W$  :: ('a, 'v) Election Distance  $\Rightarrow$  ('a, 'v, 'r Result) Consensus-Class  $\Rightarrow$  'v set  $\Rightarrow$  'a set  $\Rightarrow$  ('a, 'v) Profile  $\Rightarrow$  'r set **where**  
 $\mathcal{R}_W$  *d* *K* *V* *A* *p* = arg-min-set (*score* *d* *K* (*A*, *V*, *p*)) (limit *A* UNIV)

**fun** (**in** *result*) *distance-R* :: ('a, 'v) Election Distance  $\Rightarrow$  ('a, 'v, 'r Result) Consensus-Class  $\Rightarrow$  ('a, 'v, 'r Result) Electoral-Module **where**  
*distance-R* *d* *K* *V* *A* *p* =  
( $\mathcal{R}_W$  *d* *K* *V* *A* *p*, (limit *A* UNIV) -  $\mathcal{R}_W$  *d* *K* *V* *A* *p*, {})

### 5.4.2 Standard Definitions

**definition** *standard* :: ('a, 'v) Election Distance  $\Rightarrow$  bool **where**  
*standard* *d*  $\equiv$   
 $\forall A A' V V' p p'. (V \neq V' \vee A \neq A') \longrightarrow d(A, V, p)(A', V', p') = \infty$

**definition** *voters-determine-distance* :: ('a, 'v) Election Distance  $\Rightarrow$  bool **where**  
*voters-determine-distance* *d*  $\equiv$   
 $\forall A A' V V' p q p'.$   
 $(\forall v \in V. p v = q v)$   
 $\longrightarrow (d(A, V, p)(A', V', p') = d(A, V, q)(A', V', p')$   
 $\wedge (d(A', V', p')(A, V, p) = d(A', V', p')(A, V, q)))$

Creates a set of all possible profiles on a finite alternative set that are empty everywhere outside of a given finite voter set.

**fun** *profiles* :: 'v set  $\Rightarrow$  'a set  $\Rightarrow$  (('a, 'v) Profile) set **where**  
*profiles* *V* *A* =  
(if infinite *A*  $\vee$  infinite *V*  
then {} else {*p*. *p* ' *V*  $\subseteq$  pl- $\alpha$  ' permutations-of-set *A*})

**fun**  $\mathcal{K}_E$ -std :: ('a, 'v, 'r Result) Consensus-Class  $\Rightarrow$  'r  $\Rightarrow$  'a set  $\Rightarrow$  'v set  $\Rightarrow$

```

      ('a, 'v) Election set where
     $\mathcal{K}_{\mathcal{E}}\text{-std } K \ w \ A \ V =$ 
      ( $\lambda p. (A, V, p)$ ) ‘ Set.filter
      ( $\lambda p. \text{consensus-}\mathcal{K} \ K \ (A, V, p) \wedge \text{elect} \ (\text{rule-}\mathcal{K} \ K) \ V \ A \ p = \{w\}$ )
      (profiles  $V \ A$ )

```

Returns those consensus elections on a given alternative and voter set from a given consensus that are mapped to the given unique winner by a given consensus rule.

```

fun score-std :: ('a, 'v) Election Distance  $\Rightarrow$  ('a, 'v, 'r Result) Consensus-Class  $\Rightarrow$ 
      ('a, 'v) Election  $\Rightarrow$  'r  $\Rightarrow$  ereal where
    score-std  $d \ K \ E \ w =$ 
      (if  $\mathcal{K}_{\mathcal{E}}\text{-std } K \ w \ (\text{alternatives-}\mathcal{E} \ E) \ (\text{voters-}\mathcal{E} \ E) = \{\}$ 
        then  $\infty$  else Min ( $d \ E$  ‘ ( $\mathcal{K}_{\mathcal{E}}\text{-std } K \ w \ (\text{alternatives-}\mathcal{E} \ E) \ (\text{voters-}\mathcal{E} \ E)$ )))

```

```

fun (in result)  $\mathcal{R}_{\mathcal{W}}\text{-std}$  :: ('a, 'v) Election Distance  $\Rightarrow$ 
      ('a, 'v, 'r Result) Consensus-Class  $\Rightarrow$  'v set  $\Rightarrow$  'a set  $\Rightarrow$  ('a, 'v) Profile  $\Rightarrow$ 
      'r set where
     $\mathcal{R}_{\mathcal{W}}\text{-std } d \ K \ V \ A \ p = \text{arg-min-set} \ (\text{score-std } d \ K \ (A, V, p)) \ (\text{limit } A \ \text{UNIV})$ 

```

```

fun (in result) distance-}\mathcal{R}\text{-std} :: ('a, 'v) Election Distance  $\Rightarrow$ 
      ('a, 'v, 'r Result) Consensus-Class  $\Rightarrow$ 
      ('a, 'v, 'r Result) Electoral-Module where
    distance-}\mathcal{R}\text{-std } d \ K \ V \ A \ p =
      ( $\mathcal{R}_{\mathcal{W}}\text{-std } d \ K \ V \ A \ p, (\text{limit } A \ \text{UNIV}) - \mathcal{R}_{\mathcal{W}}\text{-std } d \ K \ V \ A \ p, \{\}$ )

```

### 5.4.3 Auxiliary Lemmas

```

lemma fin-}\mathcal{K}_{\mathcal{E}}:
  fixes  $C :: ('a, 'v, 'r Result) \text{Consensus-Class}$ 
  shows  $\text{elections-}\mathcal{K} \ C \subseteq \text{finite-elections}$ 
proof
  fix  $E :: ('a, 'v) \text{Election}$ 
  assume  $E \in \text{elections-}\mathcal{K} \ C$ 
  hence finite-election  $E$ 
    unfolding  $\mathcal{K}_{\mathcal{E}}.\text{sims}$ 
    by force
  thus  $E \in \text{finite-elections}$ 
    unfolding finite-elections-def
    by simp
qed

```

```

lemma univ-}\mathcal{K}_{\mathcal{E}}:
  fixes  $C :: ('a, 'v, 'r Result) \text{Consensus-Class}$ 
  shows  $\text{elections-}\mathcal{K} \ C \subseteq \text{UNIV}$ 
  by simp

```

```

lemma listset-finiteness:
  fixes  $l :: 'a \text{ set list}$ 

```

```

assumes  $\forall i :: \text{nat}. i < \text{length } l \longrightarrow \text{finite } (!i)$ 
shows  $\text{finite } (\text{listset } l)$ 
using assms
proof (induct l)
  case Nil
  show  $\text{finite } (\text{listset } [])$ 
  by simp
next
  case (Cons a l)
  fix
     $a :: 'a \text{ set}$  and
     $l :: 'a \text{ set list}$ 
  assume  $\forall i :: \text{nat} < \text{length } (a \# l). \text{finite } ((a \# l)!i)$ 
  hence
     $\text{finite } a$  and
     $\forall i < \text{length } l. \text{finite } (!i)$ 
  by auto
  moreover assume
     $\forall i :: \text{nat} < \text{length } l. \text{finite } (!i) \implies \text{finite } (\text{listset } l)$ 
  ultimately have  $\text{finite } \{a' \# l' \mid a' l'. a' \in a \wedge l' \in (\text{listset } l)\}$ 
  using list-cons-presv-finiteness
  by blast
  thus  $\text{finite } (\text{listset } (a \# l))$ 
  by (simp add: set-Cons-def)
qed

lemma ls-entries-empty-imp-ls-set-empty:
  fixes  $l :: 'a \text{ set list}$ 
  assumes
     $0 < \text{length } l$  and
     $\forall i :: \text{nat}. i < \text{length } l \longrightarrow !i = \{\}$ 
  shows  $\text{listset } l = \{\}$ 
  using assms
proof (induct l)
  case Nil
  thus  $\text{listset } [] = \{\}$ 
  by simp
next
  case (Cons a l)
  fix
     $a :: 'a \text{ set}$  and
     $l :: 'a \text{ set list}$  and
     $l' :: 'a \text{ list}$ 
  assume all-elems-empty:  $\forall i :: \text{nat} < \text{length } (a \# l). (a \# l)!i = \{\}$ 
  hence  $a = \{\}$ 
  by auto
  moreover from all-elems-empty
  have  $\forall i < \text{length } l. !i = \{\}$ 
  by auto

```

ultimately have  $\{a' \# l' \mid a' l'. a' \in a \wedge l' \in (\text{listset } l)\} = \{\}$   
 by *simp*  
 thus  $\text{listset } (a \# l) = \{\}$   
 by (*simp add: set-Cons-def*)  
 qed

**lemma** *all-ls-elems-same-len*:  
 fixes  $l :: 'a \text{ set list}$   
 shows  $\forall l' :: 'a \text{ list}. l' \in \text{listset } l \longrightarrow \text{length } l' = \text{length } l$   
**proof** (*induct l, safe*)  
 case *Nil*  
 fix  $l :: 'a \text{ list}$   
 assume  $l \in \text{listset } []$   
 thus  $\text{length } l = \text{length } []$   
 by *simp*  
**next**  
 case (*Cons a l*)  
 fix  
    $a :: 'a \text{ set}$  and  
    $l :: 'a \text{ set list}$  and  
    $l' :: 'a \text{ list}$   
 assume  
    $\forall l'. l' \in \text{listset } l \longrightarrow \text{length } l' = \text{length } l$  and  
    $l' \in \text{listset } (a \# l)$   
 moreover have  
    $\forall a' l' :: 'a \text{ set list}.$   
      $\text{listset } (a' \# l') = \{b \# m \mid b m. b \in a' \wedge m \in \text{listset } l'\}$   
   by (*simp add: set-Cons-def*)  
 ultimately show  $\text{length } l' = \text{length } (a \# l)$   
   using *local.Cons*  
   by *fastforce*  
 qed

**lemma** *fin-all-profs*:  
 fixes  
    $A :: 'a \text{ set}$  and  
    $V :: 'v \text{ set}$  and  
    $x :: 'a \text{ Preference-Relation}$   
 assumes  
    $\text{fin-}A$ : *finite A* and  
    $\text{fin-}V$ : *finite V*  
 shows *finite (profiles V A  $\cap \{p. \forall v. v \notin V \longrightarrow p v = x\})$*   
**proof** (*cases A = {}*)  
 let  $?profs = \text{profiles } V A \cap \{p. \forall v. v \notin V \longrightarrow p v = x\}$   
 case *True*  
 hence *permutations-of-set A = {}*  
   unfolding *permutations-of-set-def*  
   by *fastforce*  
 hence  $\text{pl-}\alpha \text{ 'permutations-of-set } A = \{\{\}\}$

```

    unfolding pl- $\alpha$ -def
  by simp
  hence  $\forall p \in \text{profiles } V A. \forall v. v \in V \longrightarrow p v = \{\}$ 
  by (simp add: image-subset-iff)
  hence  $\forall p \in ?\text{profs}. (\forall v. v \in V \longrightarrow p v = \{\}) \wedge (\forall v. v \notin V \longrightarrow p v = x)$ 
  by simp
  hence  $\forall p \in ?\text{profs}. p = (\lambda v. \text{if } v \in V \text{ then } \{\} \text{ else } x)$ 
  by (metis (no-types, lifting))
  hence  $?\text{profs} \subseteq \{\lambda v. \text{if } v \in V \text{ then } \{\} \text{ else } x\}$ 
  by blast
  thus finite ?profs
    using finite.emptyI finite-insert finite-subset
    by (metis (no-types, lifting))
next
  let ?profs = profiles V A  $\cap \{p. \forall v. v \notin V \longrightarrow p v = x\}$ 
  case False
  from fin-V obtain ord :: 'v rel where
    linear-order-on V ord
  using finite-list lin-ord-equiv lin-order-equiv-list-of-alts
  by metis
  then obtain list-V :: 'v list where
    len: length list-V = card V and
    pl: ord = pl- $\alpha$  list-V and
    perm: list-V  $\in$  permutations-of-set V
  using lin-order-pl- $\alpha$  fin-V image-iff length-finite-permutations-of-set
  by metis
  let ?map =  $\lambda p :: ('a, 'v) \text{Profile}. \text{map } p \text{ list-V}$ 
  have  $\forall p \in \text{profiles } V A. \forall v \in V. p v \in (\text{pl-}\alpha \text{ 'permutations-of-set } A)$ 
  by (simp add: image-subset-iff)
  hence  $\forall p \in \text{profiles } V A. (\forall v \in V. \text{linear-order-on } A (p v))$ 
  using pl- $\alpha$ -lin-order fin-A False
  by metis
  moreover have  $\forall p \in ?\text{profs}. \forall i < \text{length } (?map p). (?map p)!i = p (\text{list-V}!i)$ 
  by simp
  moreover have  $\forall i < \text{length list-V}. \text{list-V}!i \in V$ 
  using perm nth-mem
  unfolding permutations-of-set-def
  by safe
  moreover have lens-eq:  $\forall p \in ?\text{profs}. \text{length } (?map p) = \text{length list-V}$ 
  by simp
  ultimately have
     $\forall p \in ?\text{profs}. \forall i < \text{length } (?map p). \text{linear-order-on } A ((?map p)!i)$ 
  by simp
  hence subset-map-profs:  $?\text{map} \text{ ' } ?\text{profs} \subseteq \{xs. \text{length } xs = \text{card } V \wedge$ 
     $(\forall i < \text{length } xs. \text{linear-order-on } A (xs!i))\}$ 
  using len lens-eq
  by fastforce
  have  $\forall p1 p2. p1 \in ?\text{profs} \wedge p2 \in ?\text{profs} \wedge p1 \neq p2 \longrightarrow (\exists v \in V. p1 v \neq p2 v)$ 

```

by *fastforce*  
 hence  $\forall p1\ p2.$   
    $p1 \in ?profs \wedge p2 \in ?profs \wedge p1 \neq p2$   
    $\longrightarrow (\exists v \in \text{set list-}V. p1\ v \neq p2\ v)$   
 using *perm*  
 unfolding *permutations-of-set-def*  
 by *simp*  
 hence  $\forall p1\ p2. p1 \in ?profs \wedge p2 \in ?profs \wedge p1 \neq p2 \longrightarrow ?map\ p1 \neq ?map\ p2$   
 by *simp*  
 hence *inj-on*  $?map\ ?profs$   
 unfolding *inj-on-def*  
 by *blast*  
 moreover have  
    $\text{finite } \{xs. \text{length } xs = \text{card } V \wedge (\forall i < \text{length } xs. \text{linear-order-on } A\ (xs!i))\}$   
 proof –  
   have  $\text{finite } \{r. \text{linear-order-on } A\ r\}$   
   using *fin-A*  
   unfolding *linear-order-on-def partial-order-on-def preorder-on-def refl-on-def*  
   by *simp*  
   hence *fin-supset*:  
    $\forall n. \text{finite } \{xs. \text{length } xs = n \wedge \text{set } xs \subseteq \{r. \text{linear-order-on } A\ r\}\}$   
   using *Collect-mono finite-lists-length-eq rev-finite-subset*  
   by (*metis (no-types, lifting)*)  
   have  $\forall l \in \{xs. \text{length } xs = \text{card } V \wedge$   
      $(\forall i < \text{length } xs. \text{linear-order-on } A\ (xs!i))\}.$   
      $\text{set } l \subseteq \{r. \text{linear-order-on } A\ r\}$   
   using *in-set-conv-nth mem-Collect-eq subsetI*  
   by (*metis (no-types, lifting)*)  
   hence  $\{xs. \text{length } xs = \text{card } V \wedge$   
      $(\forall i < \text{length } xs. \text{linear-order-on } A\ (xs!i))\}$   
      $\subseteq \{xs. \text{length } xs = \text{card } V \wedge \text{set } xs \subseteq \{r. \text{linear-order-on } A\ r\}\}$   
   by *blast*  
   thus *?thesis*  
   using *fin-supset rev-finite-subset*  
   by *blast*  
 qed  
 moreover have  $\forall f\ X\ Y. \text{inj-on } f\ X \wedge \text{finite } Y \wedge f\ `X \subseteq Y \longrightarrow \text{finite } X$   
 using *finite-imageD finite-subset*  
 by *metis*  
 ultimately show *finite ?profs*  
 using *subset-map-profs*  
 by *blast*  
 qed  
  
 lemma *profile-permutation-set*:  
   fixes  
      $A :: 'a\ \text{set}$  and  
      $V :: 'v\ \text{set}$   
   shows  $\text{profiles } V\ A = \{p :: ('a, 'v)\ \text{Profile}. \text{finite-profile } V\ A\ p\}$

```

proof (cases finite A ∧ finite V ∧ A ≠ {})
  case True
    assume finite A ∧ finite V ∧ A ≠ {}
    hence
      fin-A: finite A and
      fin-V: finite V and
      non-empty: A ≠ {}
      by safe
    show profiles V A = {p'. finite-profile V A p'}
    proof (standard, clarify)
      fix p :: 'v ⇒ 'a Preference-Relation
      assume p ∈ profiles V A
      hence  $\forall v \in V. p\ v \in \text{pl-}\alpha\ \text{' permutations-of-set } A$ 
        using fin-A fin-V
        by auto
      hence  $\forall v \in V. \text{linear-order-on } A\ (p\ v)$ 
        using fin-A pl-}\alpha\ \text{lin-order non-empty}
        by metis
      thus finite-profile V A p
        unfolding profile-def
        using fin-A fin-V
        by blast
    next
      show  $\{p. \text{finite-profile } V\ A\ p\} \subseteq \text{profiles } V\ A$ 
      proof (standard, clarify)
        fix p :: ('a, 'v) Profile
        assume prof: profile V A p
        have  $p \in \{p. p\ \text{' } V \subseteq (\text{pl-}\alpha\ \text{' permutations-of-set } A)\}$ 
          using fin-A lin-order-pl-}\alpha\ prof
          unfolding profile-def
          by blast
        thus  $p \in \text{profiles } V\ A$ 
          using fin-A fin-V
          unfolding profiles.simps
          by metis
      qed
    qed
  next
    case False
    assume not-fin-empty: ¬ (finite A ∧ finite V ∧ A ≠ {})
    have  $\text{finite } A \wedge \text{finite } V \wedge A = \{\} \longrightarrow \text{permutations-of-set } A = \{\{\}\}$ 
      unfolding permutations-of-set-def
      by fastforce
    hence pl-empty:
       $\text{finite } A \wedge \text{finite } V \wedge A = \{\} \longrightarrow \text{pl-}\alpha\ \text{' permutations-of-set } A = \{\{\}\}$ 
      unfolding pl-}\alpha\ \text{def}
      by simp
    hence  $\text{finite } A \wedge \text{finite } V \wedge A = \{\} \longrightarrow$ 
       $(\forall \pi \in \{\pi. \pi\ \text{' } V \subseteq (\text{pl-}\alpha\ \text{' permutations-of-set } A)\}. \forall v \in V. \pi\ v = \{\})$ 

```



by *fastforce*  
**hence**  $\text{finite } A \wedge \text{finite } V \wedge A = \{\}$   $\longrightarrow$   
 $\{\pi. \pi \text{ ' } V \subseteq (\text{pl-}\alpha \text{ ' permutations-of-set } A)\} = \{\pi. \forall v \in V. \pi v = \{\}\}$   
 using *image-subset-iff singletonD singletonI pl-empty*  
 by *fastforce*  
**moreover have**  $\text{finite } A \wedge \text{finite } V \wedge A = \{\}$   
 $\longrightarrow \text{profiles } V A = \{\pi. \pi \text{ ' } V \subseteq (\text{pl-}\alpha \text{ ' permutations-of-set } A)\}$   
 by *simp*  
**ultimately have** *all-prof-eq*:  $\text{finite } A \wedge \text{finite } V \wedge A = \{\}$   
 $\longrightarrow \text{profiles } V A = \{\pi. \forall v \in V. \pi v = \{\}\}$   
 by *simp*  
**have**  $\text{finite } A \wedge \text{finite } V \wedge A = \{\}$   
 $\longrightarrow (\forall p \in \{p. \text{finite-profile } V A p \wedge (\forall v. v \notin V \longrightarrow p v = \{\})\}.$   
 $(\forall v \in V. \text{linear-order-on } \{\} (p v)))$   
 unfolding *profile-def*  
 by *simp*  
**moreover have**  $\forall r. \text{linear-order-on } \{\} r \longrightarrow r = \{\}$   
 using *lin-ord-not-empty*  
 by *metis*  
**ultimately have** *non-voters*:  
 $\text{finite } A \wedge \text{finite } V \wedge A = \{\}$   
 $\longrightarrow (\forall p \in \{p. \text{finite-profile } V A p \wedge (\forall v. v \notin V \longrightarrow p v = \{\})\}.$   
 $\forall v. p v = \{\})$   
 by *blast*  
**hence**  $(\forall p. \text{profile } V \{\} p \wedge (\forall v. v \notin V \longrightarrow p v = \{\}))$   
 $\longrightarrow (\forall v. p v = \{\})) \longrightarrow \text{finite } V \longrightarrow A = \{\}$   
 $\longrightarrow \{p. \text{profile } V \{\} p\} = \{p. \forall v \in V. p v = \{\}\}$   
 unfolding *profile-def*  
 using *lin-ord-not-empty*  
 by *auto*  
**hence**  $\text{finite } A \wedge \text{finite } V \wedge A = \{\}$   
 $\longrightarrow \{p. \text{finite-profile } V A p\} = \{p. \forall v \in V. p v = \{\}\}$   
 using *non-voters*  
 by *blast*  
**hence**  $\text{finite } A \wedge \text{finite } V \wedge A = \{\}$   
 $\longrightarrow \text{profiles } V A = \{p. \text{finite-profile } V A p\}$   
 using *all-prof-eq*  
 by *simp*  
**moreover have**  $\text{infinite } A \vee \text{infinite } V \longrightarrow \text{profiles } V A = \{\}$   
 by *simp*  
**moreover have**  $\text{infinite } A \vee \text{infinite } V \longrightarrow$   
 $\{p. \text{finite-profile } V A p \wedge (\forall v. v \notin V \longrightarrow p v = \{\})\} = \{\}$   
 by *auto*  
**moreover have**  $\text{infinite } A \vee \text{infinite } V \vee A = \{\}$   
 using *not-fin-empty*  
 by *simp*  
**ultimately show**  $\text{profiles } V A = \{p. \text{finite-profile } V A p\}$   
 by *blast*  
**qed**

#### 5.4.4 Soundness

**lemma** (in result)  *$\mathcal{R}$ -sound:*

```

fixes
   $K :: ('a, 'v, 'r \text{ Result}) \text{ Consensus-Class}$  and
   $d :: ('a, 'v) \text{ Election Distance}$ 
shows electoral-module ( $\text{distance-}\mathcal{R} \ d \ K$ )
proof (unfold electoral-module.simps, safe)
fix
   $A :: 'a \text{ set}$  and
   $V :: 'v \text{ set}$  and
   $p :: ('a, 'v) \text{ Profile}$ 
have  $\mathcal{R}_{\mathcal{W}} \ d \ K \ V \ A \ p \subseteq (\text{limit } A \ \text{UNIV})$ 
  using  $\mathcal{R}_{\mathcal{W}}.\text{simps}$  arg-min-subset
  by metis
hence set-equals-partition ( $\text{limit } A \ \text{UNIV}$ ) ( $\text{distance-}\mathcal{R} \ d \ K \ V \ A \ p$ )
  by auto
moreover have disjoint3 ( $\text{distance-}\mathcal{R} \ d \ K \ V \ A \ p$ )
  by simp
ultimately show well-formed  $A$  ( $\text{distance-}\mathcal{R} \ d \ K \ V \ A \ p$ )
  using result-axioms
  unfolding result-def
  by simp
qed

```

#### 5.4.5 Properties

```

fun distance-decisiveness ::  $('a, 'v) \text{ Election set} \Rightarrow ('a, 'v) \text{ Election Distance} \Rightarrow$ 
   $('a, 'v, 'r \text{ Result}) \text{ Electoral-Module} \Rightarrow \text{bool}$  where
  distance-decisiveness  $X \ d \ m =$ 
     $(\nexists \ E. E \in X$ 
       $\wedge (\exists \ \delta > 0. \forall \ E' \in X. d \ E \ E' < \delta \longrightarrow \text{card } (\text{elect-r } (\text{fun}_{\mathcal{E}} \ m \ E')) > 1))$ 

```

#### 5.4.6 Inference Rules

**lemma** (in result) *standard-distance-imp-equal-score:*

```

fixes
   $d :: ('a, 'v) \text{ Election Distance}$  and
   $K :: ('a, 'v, 'r \text{ Result}) \text{ Consensus-Class}$  and
   $A :: 'a \text{ set}$  and
   $V :: 'v \text{ set}$  and
   $p :: ('a, 'v) \text{ Profile}$  and
   $w :: 'r$ 
assumes
  irr-non-V: voters-determine-distance  $d$  and
  std: standard  $d$ 
shows  $\text{score } d \ K \ (A, V, p) \ w = \text{score-std } d \ K \ (A, V, p) \ w$ 
proof –
  have profile-perm-set:
    profiles  $V \ A =$ 

```

```

    {p' :: ('a, 'v) Profile. finite-profile V A p'}
  using profile-permutation-set
  by metis
hence eq-intersect:  $\mathcal{K}_\mathcal{E}$ -std  $K w A V =$ 
     $\mathcal{K}_\mathcal{E} K w \cap \text{Pair } A \text{ ' Pair } V \text{ ' } \{p' :: ('a, 'v) \text{ Profile. finite-profile } V A p'\}$ 
  by force
have  $\mathcal{K}_\mathcal{E} K w \cap \text{Pair } A \text{ ' Pair } V \text{ ' } \{p' :: ('a, 'v) \text{ Profile. finite-profile } V A p'\}$ 
     $\subseteq \mathcal{K}_\mathcal{E} K w$ 
  by simp
hence  $\text{Inf } (d (A, V, p) \text{ ' } (\mathcal{K}_\mathcal{E} K w)) \leq$ 
     $\text{Inf } (d (A, V, p) \text{ ' } (\mathcal{K}_\mathcal{E} K w \cap$ 
     $\text{Pair } A \text{ ' Pair } V \text{ ' } \{p' :: ('a, 'v) \text{ Profile. finite-profile } V A p'\}))$ 
  using INF-superset-mono dual-order.refl
  by metis
moreover have  $\text{Inf } (d (A, V, p) \text{ ' } (\mathcal{K}_\mathcal{E} K w)) \geq$ 
     $\text{Inf } (d (A, V, p) \text{ ' } (\mathcal{K}_\mathcal{E} K w \cap$ 
     $\text{Pair } A \text{ ' Pair } V \text{ ' } \{p' :: ('a, 'v) \text{ Profile. finite-profile } V A p'\}))$ 
  proof (rule INF-greatest)
    let ?inf =  $\text{Inf } (d (A, V, p) \text{ ' } (\mathcal{K}_\mathcal{E} K w \cap \text{Pair } A \text{ ' Pair } V \text{ ' } \{p'. \text{finite-profile } V A p'\}))$ 
    let ?compl =  $\mathcal{K}_\mathcal{E} K w -$ 
     $\mathcal{K}_\mathcal{E} K w \cap \text{Pair } A \text{ ' Pair } V \text{ ' } \{p'. \text{finite-profile } V A p'\}$ 
    fix i :: ('a, 'v) Election
    assume el:  $i \in \mathcal{K}_\mathcal{E} K w$ 
    have in-intersect:
       $i \in (\mathcal{K}_\mathcal{E} K w \cap \text{Pair } A \text{ ' Pair } V \text{ ' } \{p'. \text{finite-profile } V A p'\})$ 
       $\longrightarrow ?inf \leq d (A, V, p) i$ 
    using Complete-Lattices.complete-lattice-class.INF-lower
    by metis
    have compl-imp-neither-voter-nor-alt-nor-infinite-prof:
       $i \in ?compl \longrightarrow (V \neq \text{fst } (\text{snd } i)$ 
       $\vee A \neq \text{fst } i$ 
       $\vee \neg \text{finite-profile } V A (\text{snd } (\text{snd } i)))$ 
    by fastforce
    moreover have not-voters-imp-infty:  $V \neq \text{fst } (\text{snd } i) \longrightarrow d (A, V, p) i = \infty$ 
    using std prod.collapse
    unfolding standard-def
    by metis
    moreover have not-alt-imp-infty:  $A \neq \text{fst } i \longrightarrow d (A, V, p) i = \infty$ 
    using std prod.collapse
    unfolding standard-def
    by metis
    moreover have  $V = \text{fst } (\text{snd } i) \wedge A = \text{fst } i$ 
       $\wedge \neg \text{finite-profile } V A (\text{snd } (\text{snd } i)) \longrightarrow \text{False}$ 
    using el
    by fastforce
  hence  $i \in ?compl \longrightarrow d (A, V, p) i = \infty$ 
    using not-alt-imp-infty not-voters-imp-infty
    compl-imp-neither-voter-nor-alt-nor-infinite-prof

```

```

    by fastforce
  ultimately have
     $i \in ?compl$ 
     $\longrightarrow \text{Inf } (d \ (A, V, p)$ 
       $\quad '(\mathcal{K}_\mathcal{E} \ K \ w \cap \text{Pair } A \ ' \text{Pair } V \ ' \{p'. \text{finite-profile } V \ A \ p'\}))$ 
       $\leq d \ (A, V, p) \ i$ 
    using ereal-less-eq
    by (metis (no-types, lifting))
  thus  $\text{Inf } (d \ (A, V, p) \ '(\mathcal{K}_\mathcal{E} \ K \ w \cap$ 
     $\quad \text{Pair } A \ ' \text{Pair } V \ ' \{p'. \text{finite-profile } V \ A \ p'\}))$ 
     $\leq d \ (A, V, p) \ i$ 
    using in-intersect el
    by blast
qed
ultimately have  $\text{Inf } (d \ (A, V, p) \ ' \mathcal{K}_\mathcal{E} \ K \ w) =$ 
   $\text{Inf } (d \ (A, V, p) \ '(\mathcal{K}_\mathcal{E} \ K \ w \cap \text{Pair } A \ ' \text{Pair } V \ ' \{p'. \text{finite-profile } V \ A \ p'\}))$ 
  using order-antisym
  by simp
also have  $\text{inf-eq-min-for-std-cons: } \dots = \text{score-std } d \ K \ (A, V, p) \ w$ 
proof (cases  $\mathcal{K}_\mathcal{E}\text{-std } K \ w \ A \ V = \{\}$ )
  case True
  hence  $\text{Inf } (d \ (A, V, p) \ '(\mathcal{K}_\mathcal{E} \ K \ w \cap \text{Pair } A \ ' \text{Pair } V \ ' \{p'. \text{finite-profile } V \ A \ p'\})) = \infty$ 
  using eq-intersect top-ereal-def
  by simp
  also have  $\text{score-std } d \ K \ (A, V, p) \ w = \infty$ 
  using True
  unfolding Let-def
  by simp
  finally show ?thesis
  by simp
next
  case False
  hence  $\text{fin: } \text{finite } A \wedge \text{finite } V$ 
  using eq-intersect
  by blast
  have  $\mathcal{K}_\mathcal{E}\text{-std } K \ w \ A \ V =$ 
     $(\mathcal{K}_\mathcal{E} \ K \ w) \cap \{(A, V, p') \mid p'. \text{finite-profile } V \ A \ p'\}$ 
  using eq-intersect
  by blast
  hence  $\text{subset-dist-}\mathcal{K}_\mathcal{E}\text{-std:}$ 
     $d \ (A, V, p) \ '(\mathcal{K}_\mathcal{E}\text{-std } K \ w \ A \ V) \subseteq$ 
     $d \ (A, V, p) \ ' \{(A, V, p') \mid p'. \text{finite-profile } V \ A \ p'\}$ 
  by blast
  let ?finite-prof =  $\lambda p' v. \text{if } v \in V \text{ then } p' \ v \text{ else } \{\}$ 
  have  $\forall p'. \text{finite-profile } V \ A \ p' \longrightarrow$ 

```

$\text{finite-profile } V \ A \ (\text{?finite-prof } p')$   
**unfolding** *If-def profile-def*  
**by** *simp*  
**moreover have**  $\forall p'. (\forall v. v \notin V \longrightarrow \text{?finite-prof } p' \ v = \{\})$   
**by** *simp*  
**ultimately have**  
 $\forall (A', V', p') \in \{(A', V', p'). A' = A \wedge V' = V \wedge \text{finite-profile } V \ A \ p'\}.$   
 $(A', V', \text{?finite-prof } p') \in \{(A, V, p') \mid p'. \text{finite-profile } V \ A \ p'\}$   
**by** *force*  
**moreover have**  
 $\forall p'. d \ (A, V, p) \ (A, V, p') = d \ (A, V, p) \ (A, V, \text{?finite-prof } p')$   
**using** *irr-non-V*  
**unfolding** *voters-determine-distance-def*  
**by** *simp*  
**ultimately have**  
 $\forall (A', V', p') \in \{(A, V, p') \mid p'. \text{finite-profile } V \ A \ p'\}.$   
 $(\exists (X, Y, z) \in \{(A, V, p') \mid p'. \text{finite-profile } V \ A \ p' \wedge (\forall v. v \notin V \longrightarrow p' \ v = \{\})\}.$   
 $d \ (A, V, p) \ (A', V', p') = d \ (A, V, p) \ (X, Y, z))$   
**by** *fastforce*  
**hence**  
 $\forall (A', V', p')$   
 $\in \{(A', V', p'). A' = A \wedge V' = V \wedge \text{finite-profile } V \ A \ p'\}.$   
 $d \ (A, V, p) \ (A', V', p') \in$   
 $d \ (A, V, p) \ ' \{(A, V, p') \mid p'. \text{finite-profile } V \ A \ p' \wedge (\forall v. v \notin V \longrightarrow p' \ v = \{\})\}$   
**by** *fastforce*  
**hence** *subset-dist-restrict-non-voters:*  
 $d \ (A, V, p) \ ' \{(A, V, p') \mid p'. \text{finite-profile } V \ A \ p'\}$   
 $\subseteq d \ (A, V, p) \ ' \{(A, V, p') \mid p'. \text{finite-profile } V \ A \ p' \wedge (\forall v. v \notin V \longrightarrow p' \ v = \{\})\}$   
**by** *fastforce*  
**have**  $\forall (A', V', p') \in \{(A, V, p') \mid p'. \text{finite-profile } V \ A \ p' \wedge (\forall v. v \notin V \longrightarrow p' \ v = \{\})\}.$   
 $(\forall v \in V. \text{linear-order-on } A \ (p' \ v))$   
 $\wedge (\forall v. v \notin V \longrightarrow p' \ v = \{\})$   
**using** *fin*  
**unfolding** *profile-def*  
**by** *simp*  
**hence** *subset-lin-ord:*  
 $\{(A, V, p') \mid p'. \text{finite-profile } V \ A \ p' \wedge (\forall v. v \notin V \longrightarrow p' \ v = \{\})\}$   
 $\subseteq \{(A, V, p') \mid p'. p' \in \{p'. (\forall v \in V. \text{linear-order-on } A \ (p' \ v)) \wedge (\forall v. v \notin V \longrightarrow p' \ v = \{\})\}\}$   
**by** *blast*  
**have**  $\{p'. (\forall v \in V. \text{linear-order-on } A \ (p' \ v))$   
 $\wedge (\forall v. v \notin V \longrightarrow p' \ v = \{\})\}$   
 $\subseteq \text{profiles } V \ A \cap \{p. \forall v. v \notin V \longrightarrow p \ v = \{\}\}$   
**using** *lin-order-pl- $\alpha$  fin*  
**by** *fastforce*

**moreover have** *finite* (*profiles*  $V \ A \cap \{p. \forall v. v \notin V \longrightarrow p \ v = \{\}\}$ )  
**using** *fin fin-all-profs*  
**by** *blast*  
**ultimately have**  
*finite*  $\{p'. (\forall v \in V. \text{linear-order-on } A \ (p' \ v)) \wedge (\forall v. v \notin V \longrightarrow p' \ v = \{\})\}$   
**using** *rev-finite-subset*  
**by** *blast*  
**hence** *finite*  $\{(A, V, p^\wedge) \mid p'. p' \in \{p'. (\forall v \in V. \text{linear-order-on } A \ (p' \ v)) \wedge (\forall v. v \notin V \longrightarrow p' \ v = \{\})\}\}$   
**by** *simp*  
**hence** *finite*  $\{(A, V, p^\wedge) \mid p'. \text{finite-profile } V \ A \ p' \wedge (\forall v. v \notin V \longrightarrow p' \ v = \{\})\}$   
**using** *subset-lin-ord rev-finite-subset*  
**by** *simp*  
**hence** *finite*  $(d \ (A, V, p) \text{ ‘ } \{(A, V, p^\wedge) \mid p'. \text{finite-profile } V \ A \ p' \wedge (\forall v. v \notin V \longrightarrow p' \ v = \{\})\})$   
**by** *simp*  
**hence** *finite*  $(d \ (A, V, p) \text{ ‘ } \{(A, V, p^\wedge) \mid p'. \text{finite-profile } V \ A \ p'\})$   
**using** *subset-dist-restrict-non-voters rev-finite-subset*  
**by** *simp*  
**hence** *finite*  $(d \ (A, V, p) \text{ ‘ } (\mathcal{K}_{\mathcal{E}}\text{-std } K \ w \ A \ V))$   
**using** *subset-dist- $\mathcal{K}_{\mathcal{E}}$ -std rev-finite-subset*  
**by** *blast*  
**moreover have**  $d \ (A, V, p) \text{ ‘ } (\mathcal{K}_{\mathcal{E}}\text{-std } K \ w \ A \ V) \neq \{\}$   
**using** *False*  
**by** *simp*  
**ultimately have**  
 $\text{Inf } (d \ (A, V, p) \text{ ‘ } (\mathcal{K}_{\mathcal{E}}\text{-std } K \ w \ A \ V)) =$   
 $\text{Min } (d \ (A, V, p) \text{ ‘ } (\mathcal{K}_{\mathcal{E}}\text{-std } K \ w \ A \ V))$   
**using** *Min-Inf False*  
**by** *metis*  
**also have**  $\dots = \text{score-std } d \ K \ (A, V, p) \ w$   
**using** *False*  
**by** *simp*  
**also have**  $\text{Inf } (d \ (A, V, p) \text{ ‘ } (\mathcal{K}_{\mathcal{E}}\text{-std } K \ w \ A \ V)) =$   
 $\text{Inf } (d \ (A, V, p) \text{ ‘ } (\mathcal{K}_{\mathcal{E}} \ K \ w \cap \text{Pair } A \text{ ‘ } \text{Pair } V \text{ ‘ } \{p'. \text{finite-profile } V \ A \ p'\}))$   
**using** *eq-intersect*  
**by** *simp*  
**ultimately show** *?thesis*  
**by** *simp*  
**qed**  
**finally show**  $\text{score } d \ K \ (A, V, p) \ w = \text{score-std } d \ K \ (A, V, p) \ w$   
**by** *simp*  
**qed**

**lemma** (*in result*) *anonymous-distance-and-consensus-imp-rule-anonymity*:  
**fixes**

$d :: ('a, 'v)$  Election Distance **and**  
 $K :: ('a, 'v, 'r)$  Result Consensus-Class  
**assumes**  
 $d\text{-anon}$ : distance-anonymity  $d$  **and**  
 $K\text{-anon}$ : consensus-rule-anonymity  $K$   
**shows** anonymity (distance- $\mathcal{R}$   $d$   $K$ )  
**proof** (unfold anonymity-def Let-def, safe)  
**show** electoral-module (distance- $\mathcal{R}$   $d$   $K$ )  
**using**  $\mathcal{R}$ -sound  
**by** metis  
**next**  
**fix**  
 $A\ A' :: 'a$  set **and**  
 $V\ V' :: 'v$  set **and**  
 $p\ q :: ('a, 'v)$  Profile **and**  
 $\pi :: 'v \Rightarrow 'v$   
**assume**  
bijective: bij  $\pi$  **and**  
renamed: rename  $\pi$   $(A, V, p) = (A', V', q)$   
**hence** eq-univ: limit  $A$  UNIV = limit  $A'$  UNIV  
**by** simp  
**have** dist-rename-inv:  
 $\forall E :: ('a, 'v)$  Election.  $d(A, V, p)\ E = d(A', V', q)\ (\text{rename } \pi\ E)$   
**using**  $d\text{-anon}$  bijective renamed surj-pair  
**unfolding** distance-anonymity-def  
**by** metis  
**hence**  $\forall S :: ('a, 'v)$  Election set.  
 $(d(A, V, p)\ 'S) \subseteq (d(A', V', q)\ '(\text{rename } \pi\ 'S))$   
**by** blast  
**moreover have**  
 $\forall S :: ('a, 'v)$  Election set.  
 $((d(A', V', q)\ '(\text{rename } \pi\ 'S)) \subseteq (d(A, V, p)\ 'S))$   
**proof** (clarify)  
**fix**  
 $S :: ('a, 'v)$  Election set **and**  
 $X\ X' :: 'a$  set **and**  
 $Y\ Y' :: 'v$  set **and**  
 $z\ z' :: ('a, 'v)$  Profile  
**assume**  $(X', Y', z') = \text{rename } \pi\ (X, Y, z)$   
**hence**  $d(A', V', q)\ (X', Y', z') = d(A, V, p)\ (X, Y, z)$   
**using** dist-rename-inv  
**by** metis  
**moreover assume**  $(X, Y, z) \in S$   
**ultimately show**  $d(A', V', q)\ (X', Y', z') \in d(A, V, p)\ 'S$   
**by** simp  
**qed**  
**ultimately have** eq-range:  
 $\forall S :: ('a, 'v)$  Election set.  
 $(d(A, V, p)\ 'S) = (d(A', V', q)\ '(\text{rename } \pi\ 'S))$

by *blast*  
 have  $\forall w. \text{rename } \pi \text{ ' } (\mathcal{K}_\mathcal{E} K w) \subseteq (\mathcal{K}_\mathcal{E} K w)$   
 proof (*clarify*)  
 fix  
    $w :: 'r$  and  
    $A A' :: 'a \text{ set}$  and  
    $V V' :: 'v \text{ set}$  and  
    $p p' :: ('a, 'v) \text{ Profile}$   
 assume  $(A, V, p) \in \mathcal{K}_\mathcal{E} K w$   
 hence *cons*:  
    $(\text{consensus-}\mathcal{K} K) (A, V, p) \wedge \text{finite-profile } V A p$   
    $\wedge \text{elect } (\text{rule-}\mathcal{K} K) V A p = \{w\}$   
 by *simp*  
 moreover assume *renamed*:  $(A', V', p') = \text{rename } \pi (A, V, p)$   
 ultimately have *finite-profile*  $V' A' p'$   
   using *bijective fst-conv rename-finite rename-prof*  
   unfolding *rename.simps*  
 by *metis*  
 moreover from *this* have *cons-img*:  
    $\text{consensus-}\mathcal{K} K (A', V', p') \wedge (\text{rule-}\mathcal{K} K V A p = \text{rule-}\mathcal{K} K V' A' p')$   
   using *K-anon renamed bijective cons*  
   unfolding *consensus-rule-anonymity-def Let-def*  
 by *simp*  
 ultimately show  $(A', V', p') \in \mathcal{K}_\mathcal{E} K w$   
   using *cons*  
   by *simp*  
 qed  
 moreover have  $\forall w. (\mathcal{K}_\mathcal{E} K w) \subseteq \text{rename } \pi \text{ ' } (\mathcal{K}_\mathcal{E} K w)$   
 proof (*clarify*)  
 fix  
    $w :: 'r$  and  
    $A :: 'a \text{ set}$  and  
    $V :: 'v \text{ set}$  and  
    $p :: ('a, 'v) \text{ Profile}$   
 assume  $(A, V, p) \in \mathcal{K}_\mathcal{E} K w$   
 hence *cons*:  
    $(\text{consensus-}\mathcal{K} K) (A, V, p) \wedge \text{finite-profile } V A p$   
    $\wedge \text{elect } (\text{rule-}\mathcal{K} K) V A p = \{w\}$   
 by *simp*  
 let  $?inv = \text{rename } (\text{the-inv } \pi) (A, V, p)$   
 have *inv-inv-id*:  $\text{the-inv } (\text{the-inv } \pi) = \pi$   
   using *the-inv-f-f bijective bij-betw-imp-inj-on bij-betw-imp-surj*  
   *inj-on-the-inv-into surj-imp-inv-eq the-inv-into-onto*  
   by (*metis (no-types, opaque-lifting)*)  
 hence  $?inv = (A, ((\text{the-inv } \pi) \text{ ' } V), p \circ (\text{the-inv } (\text{the-inv } \pi)))$   
   by *simp*  
 moreover have  $p \circ \text{the-inv } (\text{the-inv } \pi) \circ \text{the-inv } \pi = p$   
   using *bijective inv-inv-id*  
   unfolding *bij-betw-def comp-def*



by (*simp add: f-the-inv-into-f*)  
 moreover have  $\pi \text{ ‘ (the-inv } \pi) \text{ ‘ } V = V$   
 using *bijjective the-inv-f-f image-inv-into-cancel top-greatest*  
   *surj-imp-inv-eq*  
 unfolding *bij-betw-def*  
 by (*metis (no-types, opaque-lifting)*)  
 ultimately have *preimg: rename  $\pi$  ?inv = (A, V, p)*  
 unfolding *Let-def*  
 by *simp*  
 have *bij (the-inv  $\pi$ )*  
 using *bijjective bij-betw-the-inv-into*  
 by *metis*  
 moreover from *this* have *fin-preimg:*  
   *finite-profile (fst (snd ?inv)) (fst ?inv) (snd (snd ?inv))*  
 using *rename-prof cons*  
 by *fastforce*  
 ultimately have  
   *consensus- $\mathcal{K}$  K ?inv  $\wedge$*   
   *(rule- $\mathcal{K}$  K V A p =*  
     *rule- $\mathcal{K}$  K (fst (snd ?inv)) (fst ?inv) (snd (snd ?inv)))*  
 using *K-anon renamed bijjective cons*  
 unfolding *consensus-rule-anonymity-def Let-def*  
 by *simp*  
 moreover from *this* have  
   *elect (rule- $\mathcal{K}$  K) (fst (snd ?inv)) (fst ?inv) (snd (snd ?inv)) = {w}*  
 using *cons*  
 by *simp*  
 ultimately have *?inv  $\in \mathcal{K}_{\mathcal{E}}$  K w*  
 using *fin-preimg*  
 by *simp*  
 thus  $(A, V, p) \in \text{rename } \pi \text{ ‘ } \mathcal{K}_{\mathcal{E}} K w$   
 using *preimg image-eqI*  
 by *metis*  
 qed  
 ultimately have  $\forall w. (\mathcal{K}_{\mathcal{E}} K w) = \text{rename } \pi \text{ ‘ } (\mathcal{K}_{\mathcal{E}} K w)$   
 by *blast*  
 hence  $\forall w. \text{score } d K (A, V, p) w = \text{score } d K (A', V', q) w$   
 using *eq-range*  
 by *simp*  
 hence *arg-min-set (score d K (A, V, p)) (limit A UNIV) =*  
   *arg-min-set (score d K (A', V', q)) (limit A' UNIV)*  
 using *eq-univ*  
 by *presburger*  
 hence  $\mathcal{R}_{\mathcal{W}} d K V A p = \mathcal{R}_{\mathcal{W}} d K V' A' q$   
 by *simp*  
 thus *distance- $\mathcal{R}$  d K V A p = distance- $\mathcal{R}$  d K V' A' q*  
 using *eq-univ*  
 by *simp*  
 qed

end

## 5.5 Votewise Distance Rationalization

```

theory Votewise-Distance-Rationalization
  imports Distance-Rationalization
           Votewise-Distance
begin

```

A votewise distance rationalization of a voting rule is its distance rationalization with a distance function that depends on the submitted votes in a simple and a transparent manner by using a distance on individual orders and combining the components with a norm on  $\mathbb{R}^n$ .

### 5.5.1 Common Rationalizations

```

fun swap- $\mathcal{R}$  :: ('a, 'v :: linorder, 'a Result) Consensus-Class  $\Rightarrow$ 
      ('a, 'v, 'a Result) Electoral-Module where
  swap- $\mathcal{R}$  K = SCF-result.distance- $\mathcal{R}$  (votewise-distance swap l-one) K

```

### 5.5.2 Theorems

```

lemma votewise-non-voters-irrelevant:
  fixes
    d :: 'a Vote Distance and
    N :: Norm
  shows voters-determine-distance (votewise-distance d N)
proof (unfold voters-determine-distance-def, clarify)
  fix
    A A' :: 'a set and
    V V' :: 'v :: linorder set and
    p p' q :: ('a, 'v) Profile
  assume coincide:  $\forall v \in V. p\ v = q\ v$ 
  have  $\forall i < \text{length}(\text{sorted-list-of-set } V). (\text{sorted-list-of-set } V)!i \in V$ 
  using card-eq-0-iff not-less-zero nth-mem
        sorted-list-of-set.length-sorted-key-list-of-set
        sorted-list-of-set.set-sorted-key-list-of-set
  by metis
  hence  $(\text{to-list } V\ p) = (\text{to-list } V\ q)$ 
  using coincide length-map nth-equalityI to-list.simps
  by auto
  thus votewise-distance d N (A, V, p) (A', V', p') =
    votewise-distance d N (A, V, q) (A', V', p')  $\wedge$ 
    votewise-distance d N (A', V', p') (A, V, p) =
    votewise-distance d N (A', V', p') (A, V, q)

```

```

    unfolding votewise-distance.simps
    by presburger
qed

lemma swap-standard: standard (votewise-distance swap l-one)
proof (unfold standard-def, clarify)
  fix
    A A' :: 'a set and
    V V' :: 'v :: linorder set and
    p p' :: ('a, 'v) Profile
  assume assms: V ≠ V' ∨ A ≠ A'
  let ?l = (λ l1 l2. (map2 (λ q q'. swap (A, q) (A', q')) l1 l2))
  have A ≠ A' ∧ V = V' ∧ V ≠ {} ∧ finite V ⟶
    (∀ l1 l2. l1 ≠ [] ∧ l2 ≠ [] ⟶ (∀ i < length (?l l1 l2). (?l l1 l2)!i = ∞))
  by simp
  moreover have
    V = V' ∧ V ≠ {} ∧ finite V ⟶ (to-list V p) ≠ [] ∧ (to-list V' p') ≠ []
  using sorted-list-of-set.sorted-key-list-of-set-eq-Nil-iff
    to-list.simps Nil-is-map-conv
  by (metis (no-types))
  moreover have ∀ l. (∃ i < length l. !i = ∞) ⟶ l-one l = ∞
proof (safe)
  fix
    l :: ereal list and
    i :: nat
  assume
    i < length l and
    l ! i = ∞
  hence (∑ j < length l. |l[j]|) = ∞
  using sum-Pinfy finite-lessThan lessThan-iff abs-ereal.simps
  by metis
  thus l-one l = ∞
  by auto
qed
ultimately have A ≠ A' ∧ V = V' ∧ V ≠ {} ∧ finite V
  ⟶ l-one (?l (to-list V p) (to-list V' p')) = ∞
  using length-greater-0-conv map-is-Nil-conv zip-eq-Nil-iff
  by metis
hence A ≠ A' ∧ V = V' ∧ V ≠ {} ∧ finite V ⟶
  votewise-distance swap l-one (A, V, p) (A', V', p') = ∞
  by force
moreover have
  V ≠ V'
  ⟶ votewise-distance swap l-one (A, V, p) (A', V', p') = ∞
  by simp
moreover have
  A ≠ A' ∧ V = {}
  ⟶ votewise-distance swap l-one (A, V, p) (A', V', p') = ∞
  by simp

```

**moreover have**  
 $(A \neq A' \wedge V = V' \wedge V \neq \{\} \wedge \text{finite } V)$   
 $\vee \text{infinite } V \vee (A \neq A' \wedge V = \{\}) \vee V \neq V'$   
**using** *assms*  
**by** *blast*  
**ultimately show** *votewise-distance swap l-one*  $(A, V, p) (A', V', p') = \infty$   
**by** *fastforce*  
**qed**

### 5.5.3 Equivalence Lemmas

**type-synonym**  $(\text{'a}, \text{'v}) \text{ score-type} = (\text{'a}, \text{'v}) \text{ Election Distance} \Rightarrow$   
 $(\text{'a}, \text{'v}, \text{'a Result}) \text{ Consensus-Class} \Rightarrow (\text{'a}, \text{'v}) \text{ Election} \Rightarrow \text{'a} \Rightarrow \text{ereal}$

**type-synonym**  $(\text{'a}, \text{'v}) \text{ dist-rat-type} = (\text{'a}, \text{'v}) \text{ Election Distance} \Rightarrow$   
 $(\text{'a}, \text{'v}, \text{'a Result}) \text{ Consensus-Class} \Rightarrow \text{'v set} \Rightarrow \text{'a set} \Rightarrow (\text{'a}, \text{'v}) \text{ Profile} \Rightarrow \text{'a set}$

**type-synonym**  $(\text{'a}, \text{'v}) \text{ dist-rat-std-type} = (\text{'a}, \text{'v}) \text{ Election Distance} \Rightarrow$   
 $(\text{'a}, \text{'v}, \text{'a Result}) \text{ Consensus-Class} \Rightarrow (\text{'a}, \text{'v}, \text{'a Result}) \text{ Electoral-Module}$

**type-synonym**  $(\text{'a}, \text{'v}) \text{ dist-type} = (\text{'a}, \text{'v}) \text{ Election Distance} \Rightarrow$   
 $(\text{'a}, \text{'v}, \text{'a Result}) \text{ Consensus-Class} \Rightarrow (\text{'a}, \text{'v}, \text{'a Result}) \text{ Electoral-Module}$

**lemma** *equal-score-swap*:  $(\text{score} :: (\text{'a}, \text{'v} :: \text{linorder}) \text{ score-type})$   
 $(\text{votewise-distance swap l-one}) = \text{score-std} (\text{votewise-distance swap l-one})$   
**using** *votewise-non-voters-irrelevant swap-standard*  
 $\text{SCF-result.standard-distance-imp-equal-score}$   
**by** *fast*

**lemma** *swap- $\mathcal{R}$ -code*[code]:  $\text{swap-}\mathcal{R} =$   
 $(\text{SCF-result.distance-}\mathcal{R}\text{-std} :: (\text{'a}, \text{'v} :: \text{linorder}) \text{ dist-rat-std-type})$   
 $(\text{votewise-distance swap l-one})$

**unfolding**  $\text{swap-}\mathcal{R}.\text{sims} \text{ SCF-result.distance-}\mathcal{R}.\text{sims} \text{ SCF-result.distance-}\mathcal{R}\text{-std.sims}$   
 $\text{SCF-result.}\mathcal{R}_{\mathcal{W}}.\text{sims} \text{ SCF-result.}\mathcal{R}_{\mathcal{W}}\text{-std.sims equal-score-swap}$   
**by** *safe*

**end**

## 5.6 Symmetry in Distance-Rationalizable Rules

**theory** *Distance-Rationalization-Symmetry*  
**imports** *Distance-Rationalization*  
**begin**

### 5.6.1 Minimizer Function

**fun** *distance-infimum* ::  $\text{'a Distance} \Rightarrow \text{'a set} \Rightarrow \text{'a} \Rightarrow \text{ereal}$  **where**

```

distance-infimum d A a = Inf (d a ‘ A)

fun closest-preimg-distance :: ('a ⇒ 'b) ⇒ 'a set ⇒ 'a Distance ⇒
    'a ⇒ 'b ⇒ ereal where
    closest-preimg-distance f domainf d a b = distance-infimum d (preimg f domainf
b) a

fun minimizer :: ('a ⇒ 'b) ⇒ 'a set ⇒ 'a Distance ⇒ 'b set ⇒ 'a ⇒ 'b set where
    minimizer f domainf d A a = arg-min-set (closest-preimg-distance f domainf d
a) A

```

### Auxiliary Lemmas

```

lemma rewrite-arg-min-set:
  fixes
    f :: 'a ⇒ 'b :: linorder and
    A :: 'a set
  shows arg-min-set f A = ⋃ (preimg f A ‘ {y ∈ f ‘ A. ∀ z ∈ f ‘ A. y ≤ z})
proof (safe)
  fix x :: 'a
  assume x ∈ arg-min-set f A
  thus x ∈ ⋃ (preimg f A ‘ {y ∈ f ‘ A. ∀ z ∈ f ‘ A. y ≤ z})
    by (simp add: is-arg-min-linorder)
next
  fix x y :: 'a
  assume
    x ∈ preimg f A (f y) and
    ∀ z ∈ f ‘ A. f y ≤ z
  thus x ∈ arg-min-set f A
    by (simp add: is-arg-min-linorder)
qed

```

### Equivariance

```

abbreviation Restrp :: 'a rel ⇒ 'a set ⇒ 'a rel where
    Restrp r A ≡ r Int (A × UNIV)

lemma restr-induced-rel:
  fixes
    A :: 'a set and
    B B' :: 'b set and
    φ :: ('a, 'b) binary-fun
  assumes B' ⊆ B
  shows Restrp (action-induced-rel A B φ) B' = action-induced-rel A B' φ
  using assms
  by force

theorem group-action-invar-dist-and-equivar-f-imp-equivar-minimizer:
  fixes
    f :: 'a ⇒ 'b and

```

```

domain_f X :: 'a set and
d :: 'a Distance and
well-formed-img :: 'a ⇒ 'b set and
G :: 'c monoid and
φ :: ('c, 'a) binary-fun and
ψ :: ('c, 'b) binary-fun
defines equivar-prop-set-valued ≡
  action-induced-equivariance (carrier G) X φ (set-action ψ)
assumes
  action-φ: group-action G X φ and
  group-action-res: group-action G UNIV ψ and
  dom-in-X: domain_f ⊆ X and
  closed-domain:
    closed-restricted-rel (action-induced-rel (carrier G) X φ) X domain_f and
  equivar-img: is-symmetry well-formed-img equivar-prop-set-valued and
  invar-d: invariance_D d (carrier G) X φ and
  equivar-f:
    is-symmetry f (action-induced-equivariance (carrier G) domain_f φ ψ)
shows is-symmetry (λ x. minimizer f domain_f d (well-formed-img x) x) equivar-prop-set-valued
proof (unfold action-induced-equivariance-def equivar-prop-set-valued-def is-symmetry.simps
  set-action.simps minimizer.simps, clarify)
fix
  x :: 'a and
  g :: 'c
assume
  group-elem: g ∈ carrier G and
  x-in-X: x ∈ X
hence img-X: φ g x ∈ X
  using action-φ group-action.element-image
  by metis
let ?x' = φ g x
let ?c = closest-preimg-distance f domain_f d x and
  ?c' = closest-preimg-distance f domain_f d ?x'
have ∀ y. preimg f domain_f y ⊆ X
  using dom-in-X
  by fastforce
hence ∀ y. d x ' (preimg f domain_f y) = d ?x' ' (φ g ' (preimg f domain_f y))
  using x-in-X group-elem invar-dist-image invar-d action-φ
  by metis
hence ∀ y. Inf (d ?x' ' preimg f domain_f (ψ g y)) =
  Inf (d x ' preimg f domain_f y)
  using assms group-action-equivar-f-imp-equivar-preimg[of G] group-elem
  by metis
hence comp:
  closest-preimg-distance f domain_f d x =
    (closest-preimg-distance f domain_f d ?x') ∘ (ψ g)
  by auto
hence ∀ Y A. {preimg ?c' (ψ g ' Y) α | α. α ∈ A} =
  {ψ g ' preimg ?c Y α | α. α ∈ A}

```

```

    using preimg-comp
    by auto
  moreover have
     $\forall Y A. \{\psi g \text{ ' } preimg \text{ ?c } Y \alpha \mid \alpha. \alpha \in A\} = \{\psi g \text{ ' } \beta \mid \beta. \beta \in preimg \text{ ?c } Y \text{ ' } A\}$ 
    by blast
  moreover have
     $\forall Y A. preimg \text{ ?c' } (\psi g \text{ ' } Y) \text{ ' } A = \{preimg \text{ ?c' } (\psi g \text{ ' } Y) \alpha \mid \alpha. \alpha \in A\}$ 
    by blast
  ultimately have
     $\forall Y A. \bigcup (preimg \text{ ?c' } (\psi g \text{ ' } Y) \text{ ' } A) = \bigcup \{\psi g \text{ ' } \alpha \mid \alpha. \alpha \in preimg \text{ ?c } Y \text{ ' } A\}$ 
    by simp
  moreover have
     $\forall Y A. \bigcup \{\psi g \text{ ' } \alpha \mid \alpha. \alpha \in preimg \text{ ?c } Y \text{ ' } A\} = \psi g \text{ ' } \bigcup (preimg \text{ ?c } Y \text{ ' } A)$ 
    by blast
  ultimately have  $\forall Y. arg\text{-min}\text{-set } (closest\text{-preimg}\text{-distance } f \text{ domain}_f \text{ d } ?x') (\psi g \text{ ' } Y) =$ 
     $(\psi g) \text{ ' } (arg\text{-min}\text{-set } (closest\text{-preimg}\text{-distance } f \text{ domain}_f \text{ d } x) Y)$ 
    using rewrite-arg-min-set[of ?c'] rewrite-arg-min-set[of ?c] comp
    by auto
  moreover have  $well\text{-formed}\text{-img } (\varphi g x) = \psi g \text{ ' } well\text{-formed}\text{-img } x$ 
    using equivar-img x-in-X group-elem img-X rewrite-equivariance
    unfolding equivar-prop-set-valued-def set-action.simps
    by metis
  ultimately show
     $arg\text{-min}\text{-set } (closest\text{-preimg}\text{-distance } f \text{ domain}_f \text{ d } (\varphi g x))$ 
     $(well\text{-formed}\text{-img } (\varphi g x)) =$ 
     $\psi g \text{ ' } arg\text{-min}\text{-set } (closest\text{-preimg}\text{-distance } f \text{ domain}_f \text{ d } x)$ 
     $(well\text{-formed}\text{-img } x)$ 
    by presburger
qed

```

## Invariance

**lemma** *closest-dist-invar-under-refl-rel-and-tot-invar-dist:*

**fixes**

$f :: 'a \Rightarrow 'b$  **and**  
 $domain_f :: 'a \text{ set}$  **and**  
 $d :: 'a \text{ Distance}$  **and**  
 $rel :: 'a \text{ rel}$

**assumes**

$reflp\text{-on'} \text{ domain}_f \text{ (Restrp } rel \text{ domain}_f)$  **and**  
 $total\text{-invariance}_{\mathcal{D}} \text{ d } rel$

**shows** *is-symmetry*  $(closest\text{-preimg}\text{-distance } f \text{ domain}_f \text{ d}) \text{ (Invariance } rel)$

**proof**  $(unfold \text{ is-symmetry.simps, intro allI impI ext})$

**fix**

$a \text{ b} :: 'a$  **and**  
 $y :: 'b$

**assume**  $(a, b) \in rel$

**hence**  $\forall c \in domain_f. d \ a \ c = d \ b \ c$

```

using assms
unfolding reflp-on'-def reflp-on-def rewrite-total-invarianceD
by blast
thus closest-preimg-distance f domainf d a y =
      closest-preimg-distance f domainf d b y
by simp
qed

```

**lemma** *refl-rel-and-tot-invar-dist-imp-invar-minimizer:*

```

fixes
  f :: 'a  $\Rightarrow$  'b and
  domainf :: 'a set and
  d :: 'a Distance and
  rel :: 'a rel and
  img :: 'b set
assumes
  reflp-on' domainf (Restrp rel domainf) and
  total-invarianceD d rel
shows is-symmetry (minimizer f domainf d img) (Invariance rel)
proof –
  have is-symmetry (closest-preimg-distance f domainf d) (Invariance rel)
    using assms closest-dist-invar-under-refl-rel-and-tot-invar-dist
    by metis
  thus ?thesis
    by simp
qed

```

**theorem** *group-act-invar-dist-and-invar-f-imp-invar-minimizer:*

```

fixes
  f :: 'a  $\Rightarrow$  'b and
  domainf A :: 'a set and
  d :: 'a Distance and
  img :: 'b set and
  G :: 'c monoid and
   $\varphi$  :: ('c, 'a) binary-fun
defines
  rel  $\equiv$  action-induced-rel (carrier G) A  $\varphi$  and
  rel'  $\equiv$  action-induced-rel (carrier G) domainf  $\varphi$ 
assumes
  action- $\varphi$ : group-action G A  $\varphi$  and
  dom-in-A: domainf  $\subseteq$  A and
  closed-domain: closed-restricted-rel rel A domainf and
  invar-d: invarianceD d (carrier G) A  $\varphi$  and
  invar-f: is-symmetry f (Invariance rel')
shows is-symmetry (minimizer f domainf d img) (Invariance rel)
proof –
  let
    ? $\psi$  =  $\lambda$  g. id and
    ?img =  $\lambda$  x. img

```



```

have is-symmetry f (action-induced-equivariance (carrier G) domainf φ ?ψ)
  using invar-f rewrite-invar-as-equivar
  unfolding rel'-def
  by blast
moreover have group-action G UNIV ?ψ
  using const-id-is-group-action action-φ
  unfolding group-action-def group-hom-def
  by blast
moreover have
  is-symmetry ?img (action-induced-equivariance (carrier G) A φ (set-action ?ψ))
  unfolding action-induced-equivariance-def
  by fastforce
ultimately have
  is-symmetry ( $\lambda x. \text{minimizer } f \text{ domain}_f d \text{ } (?img \ x) \ x$ )
    (action-induced-equivariance (carrier G) A φ (set-action ?ψ))
  using group-action-invar-dist-and-equivar-f-imp-equivar-minimizer[of
    - - - - ?img] assms
  by blast
thus ?thesis
  unfolding rel-def set-action.simps
  using rewrite-invar-as-equivar image-id
  by metis
qed

```

### 5.6.2 Minimizer Translation

**lemma** *K<sub>ε</sub>-is-preimg*:

```

fixes
  d :: ('a, 'v) Election Distance and
  C :: ('a, 'v, 'r Result) Consensus-Class and
  E :: ('a, 'v) Election and
  w :: 'r
shows preimg (elect-r  $\circ$  funε (rule-K C)) (elections-K C) {w} = Kε C w
proof -
have preimg (elect-r  $\circ$  funε (rule-K C)) (elections-K C) {w} =
  {E  $\in$  elections-K C.
    elect (rule-K C) (voters-ε E) (alternatives-ε E) (profile-ε E) = {w}}
  by simp
also have ... =
  elections-K C
     $\cap$  {E. elect (rule-K C) (voters-ε E) (alternatives-ε E) (profile-ε E) = {w}}
  by blast
finally show preimg (elect-r  $\circ$  funε (rule-K C)) (elections-K C) {w} = Kε C w
  by force
qed

```

**lemma** *score-is-closest-preimg-dist*:

```

fixes
  d :: ('a, 'v) Election Distance and

```

$C :: ('a, 'v, 'r \text{ Result}) \text{ Consensus-Class}$  **and**  
 $E :: ('a, 'v) \text{ Election}$  **and**  
 $w :: 'r$   
**shows**  $\text{score } d \ C \ E \ w =$   
 $\text{closest-preimg-distance } (\text{elect-r} \circ \text{fun}_{\mathcal{E}} (\text{rule-}\mathcal{K} \ C)) (\text{elections-}\mathcal{K} \ C) \ d \ E \ \{w\}$   
**proof** –  
**have**  $\text{score } d \ C \ E \ w = \text{Inf } (d \ E \ ' (\mathcal{K}_{\mathcal{E}} \ C \ w))$   
**by** *simp*  
**moreover** **have**  $\mathcal{K}_{\mathcal{E}} \ C \ w = \text{preimg } (\text{elect-r} \circ \text{fun}_{\mathcal{E}} (\text{rule-}\mathcal{K} \ C)) (\text{elections-}\mathcal{K} \ C) \ \{w\}$   
**using**  $\mathcal{K}_{\mathcal{E}}\text{-is-preimg}$   
**by** *metis*  
**moreover** **have**  
 $\text{Inf } (d \ E \ ' (\text{preimg } (\text{elect-r} \circ \text{fun}_{\mathcal{E}} (\text{rule-}\mathcal{K} \ C)) (\text{elections-}\mathcal{K} \ C) \ \{w\})) =$   
 $\text{closest-preimg-distance } (\text{elect-r} \circ \text{fun}_{\mathcal{E}} (\text{rule-}\mathcal{K} \ C)) (\text{elections-}\mathcal{K} \ C) \ d \ E \ \{w\}$   
**by** *simp*  
**ultimately show** *?thesis*  
**by** *simp*  
**qed**

**lemma** (*in result*)  $\mathcal{R}_{\mathcal{W}}\text{-is-minimizer}$ :  
**fixes**  
 $d :: ('a, 'v) \text{ Election Distance}$  **and**  
 $C :: ('a, 'v, 'r \text{ Result}) \text{ Consensus-Class}$   
**shows**  $\text{fun}_{\mathcal{E}} (\mathcal{R}_{\mathcal{W}} \ d \ C) =$   
 $(\lambda \ E. \bigcup (\text{minimizer } (\text{elect-r} \circ \text{fun}_{\mathcal{E}} (\text{rule-}\mathcal{K} \ C)) (\text{elections-}\mathcal{K} \ C) \ d$   
 $\quad (\text{singleton-set-system } (\text{limit } (\text{alternatives-}\mathcal{E} \ E) \ \text{UNIV})) \ E))$   
**proof**  
**fix**  $E :: ('a, 'v) \text{ Election}$   
**let**  $?min = (\text{minimizer } (\text{elect-r} \circ \text{fun}_{\mathcal{E}} (\text{rule-}\mathcal{K} \ C)) (\text{elections-}\mathcal{K} \ C) \ d$   
 $\quad (\text{singleton-set-system } (\text{limit } (\text{alternatives-}\mathcal{E} \ E) \ \text{UNIV})) \ E)$   
**have**  $?min =$   
 $\text{arg-min-set}$   
 $(\text{closest-preimg-distance } (\text{elect-r} \circ \text{fun}_{\mathcal{E}} (\text{rule-}\mathcal{K} \ C)) (\text{elections-}\mathcal{K} \ C) \ d \ E)$   
 $(\text{singleton-set-system } (\text{limit } (\text{alternatives-}\mathcal{E} \ E) \ \text{UNIV}))$   
**by** *simp*  
**also** **have**  
 $\dots = \text{singleton-set-system}$   
 $(\text{arg-min-set } (\text{score } d \ C \ E) (\text{limit } (\text{alternatives-}\mathcal{E} \ E) \ \text{UNIV}))$   
**proof** (*safe*)  
**fix**  $R :: 'r \text{ set}$   
**assume**  
 $\text{min: } R \in \text{arg-min-set}$   
 $(\text{closest-preimg-distance}$   
 $(\text{elect-r} \circ \text{fun}_{\mathcal{E}} (\text{rule-}\mathcal{K} \ C)) (\text{elections-}\mathcal{K} \ C) \ d \ E)$   
 $(\text{singleton-set-system } (\text{limit } (\text{alternatives-}\mathcal{E} \ E) \ \text{UNIV}))$   
**hence**  $R \in \text{singleton-set-system } (\text{limit } (\text{alternatives-}\mathcal{E} \ E) \ \text{UNIV})$   
**using** *arg-min-subset subsetD*  
**by** (*metis* *(no-types, lifting)*)

**then obtain**  $r :: 'r$  **where**  
*res-singleton*:  $R = \{r\}$  **and**  
*r-in-lim-set*:  $r \in \text{limit } (\text{alternatives-}\mathcal{E} \ E) \ UNIV$   
**by auto**  
**have**  $\nexists R'. R' \in \text{singleton-set-system } (\text{limit } (\text{alternatives-}\mathcal{E} \ E) \ UNIV)$   
 $\wedge \text{closest-preimg-distance}$   
 $(\text{elect-}r \circ \text{fun}_{\mathcal{E}} (\text{rule-}\mathcal{K} \ C)) (\text{elections-}\mathcal{K} \ C) \ d \ E \ R'$   
 $< \text{closest-preimg-distance}$   
 $(\text{elect-}r \circ \text{fun}_{\mathcal{E}} (\text{rule-}\mathcal{K} \ C)) (\text{elections-}\mathcal{K} \ C) \ d \ E \ R$   
**using** *min arg-min-set.simps is-arg-min-def CollectD*  
**by** (*metis (mono-tags, lifting)*)  
**hence**  $\nexists r'. r' \in \text{limit } (\text{alternatives-}\mathcal{E} \ E) \ UNIV$   
 $\wedge \text{closest-preimg-distance}$   
 $(\text{elect-}r \circ \text{fun}_{\mathcal{E}} (\text{rule-}\mathcal{K} \ C)) (\text{elections-}\mathcal{K} \ C) \ d \ E \ \{r'\}$   
 $< \text{closest-preimg-distance}$   
 $(\text{elect-}r \circ \text{fun}_{\mathcal{E}} (\text{rule-}\mathcal{K} \ C)) (\text{elections-}\mathcal{K} \ C) \ d \ E \ \{r\}$   
**using** *res-singleton*  
**by auto**  
**hence**  $r \in \text{arg-min-set } (\text{score } d \ C \ E) (\text{limit } (\text{alternatives-}\mathcal{E} \ E) \ UNIV)$   
**using** *score-is-closest-preimg-dist r-in-lim-set CollectI*  
 $\text{arg-min-set.simps is-arg-min-def}$   
**by metis**  
**thus**  $R \in \text{singleton-set-system}$   
 $(\text{arg-min-set } (\text{score } d \ C \ E) (\text{limit } (\text{alternatives-}\mathcal{E} \ E) \ UNIV))$   
**using** *res-singleton*  
**by simp**  
**next**  
**fix**  $R :: 'r \text{ set}$   
**assume**  
 $R \in \text{singleton-set-system}$   
 $(\text{arg-min-set } (\text{score } d \ C \ E) (\text{limit } (\text{alternatives-}\mathcal{E} \ E) \ UNIV))$   
**then obtain**  $r :: 'r$  **where**  
*res-singleton*:  $R = \{r\}$  **and**  
*r-min-lim-set*:  
 $r \in \text{arg-min-set } (\text{score } d \ C \ E) (\text{limit } (\text{alternatives-}\mathcal{E} \ E) \ UNIV)$   
**by auto**  
**hence**  $\nexists r'. r' \in \text{limit } (\text{alternatives-}\mathcal{E} \ E) \ UNIV$   
 $\wedge \text{score } d \ C \ E \ r' < \text{score } d \ C \ E \ r$   
**using** *CollectD arg-min-set.simps is-arg-min-def*  
**by metis**  
**hence**  
 $\nexists r'. r' \in \text{limit } (\text{alternatives-}\mathcal{E} \ E) \ UNIV$   
 $\wedge \text{closest-preimg-distance}$   
 $(\text{elect-}r \circ \text{fun}_{\mathcal{E}} (\text{rule-}\mathcal{K} \ C)) (\text{elections-}\mathcal{K} \ C) \ d \ E \ \{r'\}$   
 $< \text{closest-preimg-distance}$   
 $(\text{elect-}r \circ \text{fun}_{\mathcal{E}} (\text{rule-}\mathcal{K} \ C)) (\text{elections-}\mathcal{K} \ C) \ d \ E \ \{r\}$   
**using** *score-is-closest-preimg-dist*  
**by metis**  
**moreover have**

$\forall R' \in \text{singleton-set-system } (\text{limit } (\text{alternatives-}\mathcal{E} \ E) \ \text{UNIV}).$   
 $\exists r' \in \text{limit } (\text{alternatives-}\mathcal{E} \ E) \ \text{UNIV}. R' = \{r'\}$   
**by auto**  
**ultimately have**  
 $\nexists R'. R' \in \text{singleton-set-system } (\text{limit } (\text{alternatives-}\mathcal{E} \ E) \ \text{UNIV})$   
 $\wedge \text{closest-preimg-distance}$   
 $(\text{elect-}r \circ \text{fun}_{\mathcal{E}} (\text{rule-}\mathcal{K} \ C)) (\text{elections-}\mathcal{K} \ C) \ d \ E \ R'$   
 $< \text{closest-preimg-distance}$   
 $(\text{elect-}r \circ \text{fun}_{\mathcal{E}} (\text{rule-}\mathcal{K} \ C)) (\text{elections-}\mathcal{K} \ C) \ d \ E \ R$   
**using** *res-singleton*  
**by auto**  
**moreover have**  
 $R \in \text{singleton-set-system } (\text{limit } (\text{alternatives-}\mathcal{E} \ E) \ \text{UNIV})$   
**using** *r-min-lim-set res-singleton arg-min-subset*  
**by fastforce**  
**ultimately show**  
 $R \in \text{arg-min-set}$   
 $(\text{closest-preimg-distance}$   
 $(\text{elect-}r \circ \text{fun}_{\mathcal{E}} (\text{rule-}\mathcal{K} \ C)) (\text{elections-}\mathcal{K} \ C) \ d \ E)$   
 $(\text{singleton-set-system } (\text{limit } (\text{alternatives-}\mathcal{E} \ E) \ \text{UNIV})))$   
**using** *arg-min-set.simps is-arg-min-def CollectI*  
**by** (*metis (mono-tags, lifting)*)  
**qed**  
**also have**  
 $(\text{arg-min-set } (\text{score } d \ C \ E) (\text{limit } (\text{alternatives-}\mathcal{E} \ E) \ \text{UNIV})) =$   
 $\text{fun}_{\mathcal{E}} (\mathcal{R}_{\mathcal{W}} \ d \ C) \ E$   
**by simp**  
**finally have**  $\bigcup \ ?min = \bigcup (\text{singleton-set-system } (\text{fun}_{\mathcal{E}} (\mathcal{R}_{\mathcal{W}} \ d \ C) \ E))$   
**by presburger**  
**thus**  $\text{fun}_{\mathcal{E}} (\mathcal{R}_{\mathcal{W}} \ d \ C) \ E = \bigcup \ ?min$   
**using** *un-left-inv-singleton-set-system*  
**by auto**  
**qed**

## Invariance

**theorem** (*in result*) *tot-invar-dist-imp-invar-dr-rule:*

**fixes**

$d :: ('a, 'v) \text{ Election Distance}$  **and**

$C :: ('a, 'v, 'r \text{ Result}) \text{ Consensus-Class}$  **and**

$\text{rel} :: ('a, 'v) \text{ Election rel}$

**assumes**

*r-refl*: *reflp-on'* (*elections- $\mathcal{K}$*  *C*) (*Restrp rel* (*elections- $\mathcal{K}$*  *C*)) **and**

*tot-invar-d*: *total-invariance $_{\mathcal{D}}$*  *d rel* **and**

*invar-res*:

*is-symmetry* ( $\lambda E. \text{limit } (\text{alternatives-}\mathcal{E} \ E) \ \text{UNIV}$ ) (*Invariance rel*)

**shows** *is-symmetry* ( $\text{fun}_{\mathcal{E}} (\text{distance-}\mathcal{R} \ d \ C)$ ) (*Invariance rel*)

**proof** –

**let** *?min* =

$\lambda E. \bigcup \circ (\text{minimizer } (\text{elect-r} \circ \text{fun}_{\mathcal{E}} (\text{rule-}\mathcal{K} \ C)) (\text{elections-}\mathcal{K} \ C) \ d$   
 $(\text{singleton-set-system } (\text{limit } (\text{alternatives-}\mathcal{E} \ E) \ \text{UNIV})))$   
**have**  $\forall E. \text{is-symmetry } (?min \ E) \ (\text{Invariance rel})$   
**using**  $r\text{-refl tot-invar-d invar-comp}$   
 $\text{refl-rel-and-tot-invar-dist-imp-invar-minimizer}$   
**by** *blast*  
**moreover have**  $\text{is-symmetry } ?min \ (\text{Invariance rel})$   
**using** *invar-res*  
**by** *auto*  
**ultimately have**  $\text{is-symmetry } (\lambda E. ?min \ E \ E) \ (\text{Invariance rel})$   
**using** *invar-parameterized-fun[of ?min]*  
**by** *blast*  
**also have**  $(\lambda E. ?min \ E \ E) = \text{fun}_{\mathcal{E}} (\mathcal{R}_{\mathcal{W}} \ d \ C)$   
**using**  *$\mathcal{R}_{\mathcal{W}}$ -is-minimizer*  
**unfolding** *comp-def fun $_{\mathcal{E}}$ .simps*  
**by** *metis*  
**finally have**  $\text{invar-}\mathcal{R}_{\mathcal{W}}: \text{is-symmetry } (\text{fun}_{\mathcal{E}} (\mathcal{R}_{\mathcal{W}} \ d \ C)) \ (\text{Invariance rel})$   
**by** *simp*  
**hence**  
 $\text{is-symmetry } (\lambda E. \text{limit } (\text{alternatives-}\mathcal{E} \ E) \ \text{UNIV} - \text{fun}_{\mathcal{E}} (\mathcal{R}_{\mathcal{W}} \ d \ C) \ E)$   
 $(\text{Invariance rel})$   
**using** *invar-res*  
**by** *fastforce*  
**thus**  $\text{is-symmetry } (\text{fun}_{\mathcal{E}} (\text{distance-}\mathcal{R} \ d \ C)) \ (\text{Invariance rel})$   
**using** *invar-}\mathcal{R}\_{\mathcal{W}}*  
**by** *auto*  
**qed**

**theorem** (*in result*) *invar-dist-cons-imp-invar-dr-rule:*  
**fixes**  
 $d :: ('a, 'v) \text{ Election Distance}$  **and**  
 $C :: ('a, 'v, 'r \text{ Result}) \text{ Consensus-Class}$  **and**  
 $G :: 'b \text{ monoid}$  **and**  
 $\varphi :: ('b, ('a, 'v) \text{ Election}) \text{ binary-fun}$  **and**  
 $B :: ('a, 'v) \text{ Election set}$   
**defines**  
 $\text{rel} \equiv \text{action-induced-rel } (\text{carrier } G) \ B \ \varphi$  **and**  
 $\text{rel}' \equiv \text{action-induced-rel } (\text{carrier } G) \ (\text{elections-}\mathcal{K} \ C) \ \varphi$   
**assumes**  
 $\text{action-}\varphi: \text{group-action } G \ B \ \varphi$  **and**  
 $\text{consensus-}C\text{-in-}B: \text{elections-}\mathcal{K} \ C \subseteq B$  **and**  
*closed-domain:*  
 $\text{closed-restricted-rel rel } B \ (\text{elections-}\mathcal{K} \ C)$  **and**  
*invar-res:*  
 $\text{is-symmetry } (\lambda E. \text{limit } (\text{alternatives-}\mathcal{E} \ E) \ \text{UNIV}) \ (\text{Invariance rel})$  **and**  
 $\text{invar-d: invariance}_{\mathcal{D}} \ d \ (\text{carrier } G) \ B \ \varphi$  **and**  
 $\text{invar-C-winners: is-symmetry } (\text{elect-r} \circ \text{fun}_{\mathcal{E}} (\text{rule-}\mathcal{K} \ C)) \ (\text{Invariance rel})$   
**shows**  $\text{is-symmetry } (\text{fun}_{\mathcal{E}} (\text{distance-}\mathcal{R} \ d \ C)) \ (\text{Invariance rel})$   
**proof** –

**let**  $?min =$   
 $\lambda E. \bigcup \circ (\text{minimizer } (\text{elect-}r \circ \text{fun}_{\mathcal{E}} (\text{rule-}\mathcal{K} \ C)) (\text{elections-}\mathcal{K} \ C) \ d$   
 $\quad (\text{singleton-set-system } (\text{limit } (\text{alternatives-}\mathcal{E} \ E) \ \text{UNIV})))$   
**have**  $\forall E. \text{is-symmetry } (?min \ E) \ (\text{Invariance rel})$   
**using**  $\text{action-}\varphi \ \text{closed-domain} \ \text{consensus-}C\text{-in-}B \ \text{invar-}d \ \text{invar-}C\text{-winners}$   
 $\text{group-act-invar-dist-and-invar-f-imp-invar-minimizer rel-def}$   
 $\text{rel'-def invar-comp}$   
**by**  $(\text{metis } (\text{no-types, lifting}))$   
**moreover have**  $\text{is-symmetry } ?min \ (\text{Invariance rel})$   
**using**  $\text{invar-res}$   
**by**  $\text{auto}$   
**ultimately have**  $\text{is-symmetry } (\lambda E. ?min \ E \ E) \ (\text{Invariance rel})$   
**using**  $\text{invar-parameterized-fun}[of \ ?min]$   
**by**  $\text{blast}$   
**also have**  $(\lambda E. ?min \ E \ E) = \text{fun}_{\mathcal{E}} (\mathcal{R}_{\mathcal{W}} \ d \ C)$   
**using**  $\mathcal{R}_{\mathcal{W}}\text{-is-minimizer}$   
**unfolding**  $\text{comp-def fun}_{\mathcal{E}}.\text{simps}$   
**by**  $\text{metis}$   
**finally have**  $\text{invar-}\mathcal{R}_{\mathcal{W}}:$   
 $\text{is-symmetry } (\text{fun}_{\mathcal{E}} (\mathcal{R}_{\mathcal{W}} \ d \ C)) \ (\text{Invariance rel})$   
**by**  $\text{simp}$   
**hence**  $\text{is-symmetry } (\lambda E. \text{limit } (\text{alternatives-}\mathcal{E} \ E) \ \text{UNIV} -$   
 $\text{fun}_{\mathcal{E}} (\mathcal{R}_{\mathcal{W}} \ d \ C) \ E) \ (\text{Invariance rel})$   
**using**  $\text{invar-res}$   
**by**  $\text{fastforce}$   
**thus**  $\text{is-symmetry } (\text{fun}_{\mathcal{E}} (\text{distance-}\mathcal{R} \ d \ C)) \ (\text{Invariance rel})$   
**using**  $\text{invar-}\mathcal{R}_{\mathcal{W}}$   
**by**  $\text{simp}$   
**qed**

## Equivariance

**theorem** (**in result**)  $\text{invar-dist-equivar-cons-imp-equivar-dr-rule:}$

**fixes**

$d :: ('a, 'v) \text{ Election Distance}$  **and**  
 $C :: ('a, 'v, 'r) \text{ Result Consensus-Class}$  **and**  
 $G :: 'b \text{ monoid}$  **and**  
 $\varphi :: ('b, ('a, 'v) \text{ Election}) \text{ binary-fun}$  **and**  
 $\psi :: ('b, 'r) \text{ binary-fun}$  **and**  
 $B :: ('a, 'v) \text{ Election set}$

**defines**

$\text{rel} \equiv \text{action-induced-rel } (\text{carrier } G) \ B \ \varphi$  **and**  
 $\text{rel}' \equiv \text{action-induced-rel } (\text{carrier } G) \ (\text{elections-}\mathcal{K} \ C) \ \varphi$  **and**  
 $\text{equivar-prop} \equiv$   
 $\text{action-induced-equivariance } (\text{carrier } G) \ (\text{elections-}\mathcal{K} \ C)$   
 $\varphi \ (\text{set-action } \psi)$  **and**  
 $\text{equivar-prop-global-set-valued} \equiv$   
 $\text{action-induced-equivariance } (\text{carrier } G) \ B \ \varphi \ (\text{set-action } \psi)$  **and**  
 $\text{equivar-prop-global-result-valued} \equiv$

*action-induced-equivariance* (*carrier*  $G$ )  $B$   $\varphi$  (*result-action*  $\psi$ )  
**assumes**  
*action- $\varphi$* : *group-action*  $G$   $B$   $\varphi$  **and**  
*group-act-res*: *group-action*  $G$   $UNIV$   $\psi$  **and**  
*cons-elect-set*: *elections- $\mathcal{K}$*   $C \subseteq B$  **and**  
*closed-domain*: *closed-restricted-rel*  $rel$   $B$  (*elections- $\mathcal{K}$*   $C$ ) **and**  
*equivar-res*:  
*is-symmetry* ( $\lambda E. \text{limit } (\text{alternatives-}\mathcal{E} \ E) \ UNIV$ )  
*equivar-prop-global-set-valued* **and**  
*invar-d*: *invariance<sub>D</sub>*  $d$  (*carrier*  $G$ )  $B$   $\varphi$  **and**  
*equivar- $C$ -winners*: *is-symmetry* (*elect-r*  $\circ$  *fun<sub>E</sub>* (*rule- $\mathcal{K}$*   $C$ )) *equivar-prop*  
**shows** *is-symmetry* (*fun<sub>E</sub>* (*distance- $\mathcal{R}$*   $d$   $C$ )) *equivar-prop-global-result-valued*  
**proof** –  
**let**  $?min-E =$   
 $\lambda E. \text{minimizer } (\text{elect-r} \circ \text{fun}_E (\text{rule-}\mathcal{K} \ C)) (\text{elections-}\mathcal{K} \ C) \ d$   
 $(\text{singleton-set-system } (\text{limit } (\text{alternatives-}\mathcal{E} \ E) \ UNIV)) \ E$   
**let**  $?min =$   
 $\lambda E. \bigcup \circ (\text{minimizer } (\text{elect-r} \circ \text{fun}_E (\text{rule-}\mathcal{K} \ C)) (\text{elections-}\mathcal{K} \ C) \ d$   
 $(\text{singleton-set-system } (\text{limit } (\text{alternatives-}\mathcal{E} \ E) \ UNIV)))$   
**let**  $? \psi' = \text{set-action } (\text{set-action } \psi)$   
**let**  $?equivar-prop-global-set-valued' =$   
*action-induced-equivariance* (*carrier*  $G$ )  $B$   $\varphi$   $? \psi'$   
**have**  $\forall E \ g. g \in \text{carrier } G \longrightarrow E \in B \longrightarrow$   
 $\text{singleton-set-system } (\text{limit } (\text{alternatives-}\mathcal{E} \ (\varphi \ g \ E)) \ UNIV) =$   
 $\{\{r\} \mid r. r \in \text{limit } (\text{alternatives-}\mathcal{E} \ (\varphi \ g \ E)) \ UNIV\}$   
**by** *simp*  
**moreover have**  
 $\forall E \ g. g \in \text{carrier } G \longrightarrow E \in B \longrightarrow$   
 $\text{limit } (\text{alternatives-}\mathcal{E} \ (\varphi \ g \ E)) \ UNIV =$   
 $\psi \ g \ ' (\text{limit } (\text{alternatives-}\mathcal{E} \ E) \ UNIV)$   
**using** *equivar-res action- $\varphi$  group-action.element-image*  
**unfolding** *equivar-prop-global-set-valued-def action-induced-equivariance-def*  
**by** *fastforce*  
**ultimately have**  $\forall E \ g. g \in \text{carrier } G \longrightarrow E \in B \longrightarrow$   
 $\text{singleton-set-system } (\text{limit } (\text{alternatives-}\mathcal{E} \ (\varphi \ g \ E)) \ UNIV) =$   
 $\{\{r\} \mid r. r \in \psi \ g \ ' (\text{limit } (\text{alternatives-}\mathcal{E} \ E) \ UNIV)\}$   
**by** *simp*  
**moreover have**  
 $\forall E \ g. \{\{r\} \mid r. r \in \psi \ g \ ' (\text{limit } (\text{alternatives-}\mathcal{E} \ E) \ UNIV)\} =$   
 $\{\psi \ g \ ' \{r\} \mid r. r \in \text{limit } (\text{alternatives-}\mathcal{E} \ E) \ UNIV\}$   
**by** *blast*  
**moreover have**  
 $\forall E \ g. \{\psi \ g \ ' \{r\} \mid r. r \in \text{limit } (\text{alternatives-}\mathcal{E} \ E) \ UNIV\} =$   
 $? \psi' \ g \ \{\{r\} \mid r. r \in \text{limit } (\text{alternatives-}\mathcal{E} \ E) \ UNIV\}$   
**unfolding** *set-action.simps*  
**by** *blast*  
**ultimately have**  
*is-symmetry* ( $\lambda E. \text{singleton-set-system } (\text{limit } (\text{alternatives-}\mathcal{E} \ E) \ UNIV)$ )  
 $?equivar-prop-global-set-valued'$

**using** *rewrite-equivariance*[of  
 $\lambda E. \text{ singleton-set-system } (\text{limit } (\text{alternatives-}\mathcal{E} \ E) \ \text{UNIV})$   
 $\text{carrier } G \ B \ \varphi \ ?\psi]$   
**by** *force*  
**moreover have** *group-action*  $G \ \text{UNIV} \ (\text{set-action } \psi)$   
**unfolding** *set-action.simps*  
**using** *group-act-induces-set-group-act*[of -  $\text{UNIV}$ ] *group-act-res*  
**by** *simp*  
**ultimately have** *is-symmetry*  $?min\text{-}E \ ?\text{equivar-prop-global-set-valued}'$   
**using** *action- $\varphi$  invar-d cons-elect-set closed-domain equivar- $C$ -winners*  
*group-action-invar-dist-and-equivar-f-imp-equivar-minimizer*[of  
 $G \ B \ \varphi \ \text{set-action } \psi \ \text{elections-}\mathcal{K} \ C$   
 $\lambda E. \text{ singleton-set-system } (\text{limit } (\text{alternatives-}\mathcal{E} \ E) \ \text{UNIV})$   
 $d \ \text{elect-r} \circ \text{fun}_{\mathcal{E}} \ (\text{rule-}\mathcal{K} \ C)]$   
**unfolding** *rel'-def rel-def equivar-prop-def*  
**by** *metis*  
**moreover have**  
*is-symmetry*  
 $\bigcup \ (\text{action-induced-equivariance}$   
 $(\text{carrier } G) \ \text{UNIV} \ ?\psi' \ (\text{set-action } \psi))$   
**using** *equivar-union-under-image-action*[of -  $\psi$ ]  
**by** *simp*  
**ultimately have** *is-symmetry*  $(\bigcup \circ ?min\text{-}E) \ \text{equivar-prop-global-set-valued}$   
**unfolding** *equivar-prop-global-set-valued-def*  
**using** *equivar-ind-by-action-comp*[of -  $\text{UNIV}$ ]  
**by** *simp*  
**moreover have**  $(\lambda E. \ ?min \ E \ E) = \bigcup \circ ?min\text{-}E$   
**unfolding** *comp-def*  
**by** *simp*  
**ultimately have**  
*is-symmetry*  $(\lambda E. \ ?min \ E \ E) \ \text{equivar-prop-global-set-valued}$   
**by** *simp*  
**moreover have**  $(\lambda E. \ ?min \ E \ E) = \text{fun}_{\mathcal{E}} \ (\mathcal{R}_{\mathcal{W}} \ d \ C)$   
**using**  *$\mathcal{R}_{\mathcal{W}}$ -is-minimizer*  
**unfolding** *comp-def fun $_{\mathcal{E}}$ .simps*  
**by** *metis*  
**ultimately have** *equivar- $\mathcal{R}_{\mathcal{W}}$ :*  
*is-symmetry*  $(\text{fun}_{\mathcal{E}} \ (\mathcal{R}_{\mathcal{W}} \ d \ C)) \ \text{equivar-prop-global-set-valued}$   
**by** *simp*  
**moreover have**  $\forall \ g \in \text{carrier } G. \ \text{bij } (\psi \ g)$   
**using** *group-act-res*  
**unfolding** *bij-betw-def*  
**by** (*simp add: group-action.inj-prop group-action.surj-prop*)  
**ultimately have**  
*is-symmetry*  $(\lambda E. \ \text{limit } (\text{alternatives-}\mathcal{E} \ E) \ \text{UNIV} - \text{fun}_{\mathcal{E}} \ (\mathcal{R}_{\mathcal{W}} \ d \ C) \ E)$   
*equivar-prop-global-set-valued*  
**using** *equivar-res equivar-set-minus*  
**unfolding** *action-induced-equivariance-def set-action.simps*  
*equivar-prop-global-set-valued-def*



by *blast*  
**thus** *is-symmetry* (*fun<sub>E</sub>* (*distance- $\mathcal{R}$*  *d C*)) *equivar-prop-global-result-valued*  
 using *equivar- $\mathcal{R}_W$*   
**unfolding** *equivar-prop-global-result-valued-def*  
           *equivar-prop-global-set-valued-def*  
           *rewrite-equivariance*  
 by *simp*  
**qed**

### 5.6.3 Inference Rules

**theorem** (*in result*) *anon-dist-and-cons-imp-anon-dr*:  
 fixes  
   *d* :: ('a, 'v) *Election Distance* **and**  
   *C* :: ('a, 'v, 'r *Result*) *Consensus-Class*  
 assumes  
   *anon-d*: *distance-anonymity'* *well-formed-elections d* **and**  
   *anon-C*: *consensus-rule-anonymity'* (*elections- $\mathcal{K}$*  *C*) *C* **and**  
   *closed-C*: *closed-restricted-rel* (*anonymity<sub>R</sub>* *well-formed-elections*)  
           *well-formed-elections* (*elections- $\mathcal{K}$*  *C*)  
 shows *anonymity'* (*distance- $\mathcal{R}$*  *d C*)  
**proof** –  
 have  $\forall \pi. \forall E \in \text{elections-}\mathcal{K} \ C.$   
    $\varphi\text{-anon } (\text{elections-}\mathcal{K} \ C) \ \pi \ E = \varphi\text{-anon well-formed-elections } \pi \ E$   
**using** *cons-domain-well-formed extensional-continuation-subset*  
**unfolding**  *$\varphi\text{-anon.simps}$*   
 by *metis*  
**hence** *action-induced-rel* (*carrier bijection<sub>VG</sub>*) (*elections- $\mathcal{K}$*  *C*)  
   ( $\varphi\text{-anon well-formed-elections}$ ) =  
   *action-induced-rel* (*carrier bijection<sub>VG</sub>*) (*elections- $\mathcal{K}$*  *C*)  
   ( $\varphi\text{-anon } (\text{elections-}\mathcal{K} \ C)$ )  
**using** *coinciding-actions-ind-equal-rel*  
 by *metis*  
**hence** *is-symmetry* (*elect-r*  $\circ$  *fun<sub>E</sub>* (*rule- $\mathcal{K}$*  *C*))  
   (*Invariance* (*action-induced-rel*  
     (*carrier bijection<sub>VG</sub>*) (*elections- $\mathcal{K}$*  *C*) ( $\varphi\text{-anon well-formed-elections}$ )))  
**using** *anon-C*  
**unfolding** *consensus-rule-anonymity'.simps* *anonymity<sub>R</sub>.simps*  
 by *presburger*  
**thus** *?thesis*  
**using** *anon-d closed-C cons-domain-well-formed anonymity-action-presv-symmetry*  
   *anonymous-group-action.group-action-axioms invar-dist-cons-imp-invar-dr-rule*  
**unfolding** *distance-anonymity'.simps* *anonymity<sub>R</sub>.simps* *anonymity'.simps*  
   *anonymity-in.simps*  
 by *blast*  
**qed**

**theorem** (*in result-properties*) *neutr-dist-and-cons-imp-neutr-dr*:  
 fixes

$d :: ('a, 'v)$  Election Distance **and**  
 $C :: ('a, 'v, 'b \text{ Result})$  Consensus-Class  
**assumes**  
 $\text{neutral-d: distance-neutrality well-formed-elections } d$  **and**  
 $\text{neutral-C: consensus-rule-neutrality (elections-}\mathcal{K}\text{ } C) C$  **and**  
 $\text{closed-C: closed-restricted-rel (neutrality}_{\mathcal{R}} \text{ well-formed-elections)}$   
 $\text{well-formed-elections (elections-}\mathcal{K}\text{ } C)$   
**shows**  $\text{neutrality (distance-}\mathcal{R}\text{ } d C)$   
**proof** –  
**have**  $\forall \pi. \forall E \in \text{elections-}\mathcal{K}\text{ } C.$   
 $\varphi\text{-neutral well-formed-elections } \pi E = \varphi\text{-neutral (elections-}\mathcal{K}\text{ } C) \pi E$   
**using**  $\text{cons-domain-well-formed extensional-continuation-subset}$   
**unfolding**  $\varphi\text{-neutral.simps}$   
**by** *metis*  
**hence**  $\text{is-symmetry (elect-r } \circ \text{ fun}_{\mathcal{E}} \text{ (rule-}\mathcal{K}\text{ } C))}$   
 $\text{(action-induced-equivariance (carrier bijection}_{\mathcal{AG}}) \text{ (elections-}\mathcal{K}\text{ } C))}$   
 $\text{(\varphi-neutral well-formed-elections) (set-action } \psi))$   
**using**  $\text{neutral-C equivar-ind-by-act-coincide}$   
**unfolding**  $\text{consensus-rule-neutrality.simps}$   
**by**  $(\text{metis (no-types, lifting)})$   
**thus** *?thesis*  
**using**  $\text{neutral-d closed-C } \varphi\text{-neutral-action.group-action-axioms}$   
 $\text{neutrality action-neutral cons-domain-well-formed[of } C]$   
 $\text{invar-dist-equivar-cons-imp-equivar-dr-rule[of}$   
 $\text{- } \varphi\text{-neutral well-formed-elections]}$   
**by** *simp*  
**qed**

**theorem** *reversal-sym-dist-and-cons-imp-reversal-sym-dr:*  
**fixes**  
 $d :: ('a, 'c)$  Election Distance **and**  
 $C :: ('a, 'c, 'a \text{ rel Result})$  Consensus-Class  
**assumes**  
 $\text{reverse-sym-d: distance-reversal-symmetry well-formed-elections } d$  **and**  
 $\text{reverse-sym-C: consensus-rule-reversal-symmetry (elections-}\mathcal{K}\text{ } C) C$  **and**  
 $\text{closed-C: closed-restricted-rel (reversal}_{\mathcal{R}} \text{ well-formed-elections)}$   
 $\text{well-formed-elections (elections-}\mathcal{K}\text{ } C)$   
**shows**  $\text{reversal-symmetry (SWF-result.distance-}\mathcal{R}\text{ } d C)$   
**proof** –  
**have**  $\forall \pi. \forall E \in \text{elections-}\mathcal{K}\text{ } C.$   
 $\varphi\text{-reverse well-formed-elections } \pi E = \varphi\text{-reverse (elections-}\mathcal{K}\text{ } C) \pi E$   
**using**  $\text{cons-domain-well-formed extensional-continuation-subset}$   
**unfolding**  $\varphi\text{-reverse.simps}$   
**by** *metis*  
**hence**  $\text{is-symmetry (elect-r } \circ \text{ fun}_{\mathcal{E}} \text{ (rule-}\mathcal{K}\text{ } C))}$   
 $\text{(action-induced-equivariance (carrier reversal}_{\mathcal{G}}) \text{ (elections-}\mathcal{K}\text{ } C))}$   
 $\text{(\varphi-reverse well-formed-elections) (set-action } \psi\text{-reverse))}$   
**using**  $\text{reverse-sym-C equivar-ind-by-act-coincide}$   
**unfolding**  $\text{consensus-rule-reversal-symmetry.simps}$

by (*metis* (*no-types*, *lifting*))  
 thus ?thesis  
 using reverse-sym-d closed-C reversal-symm-act-presv-symmetry  
     SWF-result.invar-dist-equivar-cons-imp-equivar-dr-rule  
      $\varphi$ -reverse-action.group-action-axioms cons-domain-well-formed  
      $\psi$ -reverse-action.group-action-axioms  
 unfolding reversal-symmetry.simps reversal-symmetry-in-def  
     reversal $\mathcal{R}$ .simps distance-reversal-symmetry.simps  
 by metis  
 qed

**theorem** (in result) distance-homogeneity-imp-distance- $\mathcal{R}$ -homogeneity:  
 fixes  
    $d :: ('a, \text{nat}) \text{ Election Distance}$  and  
    $C :: ('a, \text{nat}, 'r \text{ Result}) \text{ Consensus-Class}$   
 assumes distance-homogeneity well-formed-finite- $\mathcal{V}$ -elections  $d$   
 shows homogeneity (distance- $\mathcal{R}$   $d$   $C$ )  
 proof –  
 have Restr $p$  (homogeneity $\mathcal{R}$  well-formed-finite- $\mathcal{V}$ -elections) (elections- $\mathcal{K}$   $C$ ) =  
     homogeneity $\mathcal{R}$  (elections- $\mathcal{K}$   $C$ )  
 using cons-domain-finite cons-domain-well-formed well-formed-and-finite- $\mathcal{V}$ -elections  
 unfolding homogeneity $\mathcal{R}$ .simps  
 by blast  
 hence refl $p$ -on' (elections- $\mathcal{K}$   $C$ )  
   (Restr $p$  (homogeneity $\mathcal{R}$  well-formed-finite- $\mathcal{V}$ -elections) (elections- $\mathcal{K}$   $C$ ))  
 using refl-homogeneity $\mathcal{R}$ [of elections- $\mathcal{K}$   $C$ ] cons-domain-finite[of  $C$ ]  
 by presburger  
 moreover have  
   is-symmetry ( $\lambda E. \text{limit} (\text{alternatives-}\mathcal{E} \ E) \ \text{UNIV}$ )  
   (Invariance (homogeneity $\mathcal{R}$  well-formed-finite- $\mathcal{V}$ -elections))  
 using homogeneity-action-presv-symmetry  
 by simp  
 ultimately show ?thesis  
   using assms tot-invar-dist-imp-invar-dr-rule  
   unfolding distance-homogeneity-def homogeneity.simps homogeneity-in.simps  
   by blast  
 qed

**theorem** (in result) distance-homogeneity'-imp-distance- $\mathcal{R}$ -homogeneity':  
 fixes  
    $d :: ('a, 'v :: \text{linorder}) \text{ Election Distance}$  and  
    $C :: ('a, 'v, 'r \text{ Result}) \text{ Consensus-Class}$   
 assumes distance-homogeneity' well-formed-finite- $\mathcal{V}$ -elections  $d$   
 shows homogeneity' (distance- $\mathcal{R}$   $d$   $C$ )  
 proof (unfold homogeneity'.simps homogeneity'-in.simps)  
 have Restr $p$  (homogeneity $\mathcal{R}$ ' well-formed-finite- $\mathcal{V}$ -elections) (elections- $\mathcal{K}$   $C$ ) =  
     homogeneity $\mathcal{R}$ ' (elections- $\mathcal{K}$   $C$ )  
 using cons-domain-finite cons-domain-well-formed well-formed-and-finite- $\mathcal{V}$ -elections  
 unfolding homogeneity $\mathcal{R}$ '.simps

```

    by blast
  hence reflp-on' (elections- $\mathcal{K}$  C)
    (Restrp (homogeneity $\mathcal{R}$ ' well-formed-finite- $\mathcal{V}$ -elections) (elections- $\mathcal{K}$  C))
  using refl-homogeneity $\mathcal{R}$ '[of elections- $\mathcal{K}$  C] cons-domain-finite[of C]
  by presburger
  moreover have
    is-symmetry ( $\lambda$  E. limit (alternatives- $\mathcal{E}$  E) UNIV)
      (Invariance (homogeneity $\mathcal{R}$ ' well-formed-finite- $\mathcal{V}$ -elections))
  using homogeneity'-action-presv-symmetry
  by simp
  ultimately show
    is-symmetry (fun $\mathcal{E}$  (distance- $\mathcal{R}$  d C))
      (Invariance (homogeneity $\mathcal{R}$ ' well-formed-finite- $\mathcal{V}$ -elections))
  using assms tot-invar-dist-imp-invar-dr-rule
  unfolding distance-homogeneity'-def
  by blast
qed
end

```

## 5.7 Distance Rationalization on Election Quotients

```

theory Quotient-Distance-Rationalization
  imports Quotient-Module
          Distance-Rationalization-Symmetry
begin

```

### 5.7.1 Distances

```

fun distance $\mathcal{Q}$  :: 'x Distance  $\Rightarrow$  'x set Distance where
  distance $\mathcal{Q}$  d A B = (if A = {}  $\wedge$  B = {} then 0 else
    (if A = {}  $\vee$  B = {} then  $\infty$  else
       $\pi_{\mathcal{Q}}$  (tup d) (A  $\times$  B)))

fun relation-paths :: 'x rel  $\Rightarrow$  'x list set where
  relation-paths r =
    {p.  $\exists$  k. length p = 2 * k  $\wedge$  ( $\forall$  i < k. (p!(2 * i), p!(2 * i + 1))  $\in$  r)}

fun admissible-paths :: 'x rel  $\Rightarrow$  'x set  $\Rightarrow$  'x set  $\Rightarrow$  'x list set where
  admissible-paths r X Y =
    {x#p@[y] | x y p. x  $\in$  X  $\wedge$  y  $\in$  Y  $\wedge$  p  $\in$  relation-paths r}

fun path-length :: 'x list  $\Rightarrow$  'x Distance  $\Rightarrow$  ereal where
  path-length [] d = 0 |
  path-length [x] d = 0 |
  path-length (x#y#xs) d = d x y + path-length xs d

```

**fun** *quotient-dist* :: 'x rel  $\Rightarrow$  'x Distance  $\Rightarrow$  'x set Distance **where**  
*quotient-dist* r d A B =  
 Inf ( $\bigcup \{ \{ \text{path-length } p \ d \mid p. p \in \text{admissible-paths } r \ A \ B \} \}$ )

**fun** *distance-infimum*<sub>Q</sub> :: 'x Distance  $\Rightarrow$  'x set Distance **where**  
*distance-infimum*<sub>Q</sub> d A B = Inf {d a b | a b. a  $\in$  A  $\wedge$  b  $\in$  B}

**fun** *simple* :: 'x rel  $\Rightarrow$  'x set  $\Rightarrow$  'x Distance  $\Rightarrow$  bool **where**  
*simple* r X d =  
 ( $\forall A \in X \ // \ r.$   
 $\exists a \in A. \forall B \in X \ // \ r.$   
*distance-infimum*<sub>Q</sub> d A B = Inf {d a b | b. b  $\in$  B})

— We call a distance simple with respect to a relation if for all relation classes, there is an  $a$  in  $A$  that minimizes the infimum distance between  $A$  and all  $B$  such that the infimum distance between these sets coincides with the infimum distance over all  $b$  in  $B$  for a fixed  $a$ .

**fun** *product'* :: 'x rel  $\Rightarrow$  ('x \* 'x) rel **where**  
*product'* r = {( $p_1, p_2$ ). ( $\text{fst } p_1, \text{fst } p_2$ )  $\in$  r  $\wedge$   $\text{snd } p_1 = \text{snd } p_2$ )  
 $\vee$  ( $\text{snd } p_1, \text{snd } p_2$ )  $\in$  r  $\wedge$   $\text{fst } p_1 = \text{fst } p_2$ }

## Auxiliary Lemmas

**lemma** *tot-dist-invariance-is-congruence*:

**fixes**

$d :: 'x \text{ Distance}$  **and**

$r :: 'x \text{ rel}$

**shows** ( $\text{total-invariance}_{\mathcal{D}} \ d \ r$ ) = ( $\text{tup } d \text{ respects } (\text{product } r)$ )

**unfolding**  $\text{total-invariance}_{\mathcal{D}}.\text{simps}$  *is-symmetry.simps* *congruent-def*

**by** *blast*

**lemma** *product-helper*:

**fixes**

$r :: 'x \text{ rel}$  **and**

$X :: 'x \text{ set}$

**shows**

$\text{trans-imp: Relation.trans } r \longrightarrow \text{Relation.trans } (\text{product } r)$  **and**

$\text{refl-imp: refl-on } X \ r \longrightarrow \text{refl-on } (X \times X) \ (\text{product } r)$  **and**

$\text{sym: sym-on } X \ r \longrightarrow \text{sym-on } (X \times X) \ (\text{product } r)$

**unfolding**  $\text{Relation.trans-def}$   $\text{refl-on-def}$   $\text{sym-on-def}$   $\text{product.simps}$

**by** *auto*

**theorem** *dist-pass-to-quotient*:

**fixes**

$d :: 'x \text{ Distance}$  **and**

$r :: 'x \text{ rel}$  **and**

$X :: 'x \text{ set}$

**assumes**

$\text{equiv-X-r: equiv } X \ r$  **and**

*tot-inv-dist-d-r: total-invariance<sub>D</sub> d r*  
**shows**  $\forall A B. A \in X // r \wedge B \in X // r$   
 $\longrightarrow (\forall a b. a \in A \wedge b \in B \longrightarrow \text{distance}_{\mathcal{Q}} d A B = d a b)$   
**proof** (*safe*)  
**fix**  
 $A B :: 'x \text{ set}$  **and**  
 $a b :: 'x$   
**assume**  
 $a\text{-in-}A: a \in A$  **and**  
 $A \in X // r$   
**moreover with** *equiv-X-r quotient-eq-iff*  
**have**  $(a, a) \in r$   
**by** *metis*  
**moreover with** *equiv-X-r*  
**have**  $a\text{-in-}X: a \in X$   
**using** *equiv-class-eq-iff*  
**by** *metis*  
**ultimately have**  $A\text{-eq-r-}a: A = r `` \{a\}$   
**using** *equiv-X-r quotient-eq-iff quotientI*  
**by** *fast*  
**assume**  
 $b\text{-in-}B: b \in B$  **and**  
 $B \in X // r$   
**moreover with** *equiv-X-r quotient-eq-iff*  
**have**  $(b, b) \in r$   
**by** *metis*  
**moreover with** *equiv-X-r*  
**have**  $b\text{-in-}X: b \in X$   
**using** *equiv-class-eq-iff*  
**by** *metis*  
**ultimately have**  $B\text{-eq-r-}b: B = r `` \{b\}$   
**using** *equiv-X-r quotient-eq-iff quotientI*  
**by** *fast*  
**from**  $A\text{-eq-r-}a$   $B\text{-eq-r-}b$   $a\text{-in-}X$   $b\text{-in-}X$   
**have**  $A \times B \in (X \times X) // (\text{product } r)$   
**unfolding** *quotient-def*  
**by** *fastforce*  
**moreover have** *equiv*  $(X \times X)$   $(\text{product } r)$   
**using** *equiv-X-r product-helper UNIV-Times-UNIV equivE equivI*  
**by** *metis*  
**moreover have** *tup d respects*  $(\text{product } r)$   
**using** *tot-inv-dist-d-r tot-dist-invariance-is-congruence*  
**by** *metis*  
**ultimately show**  $\text{distance}_{\mathcal{Q}} d A B = d a b$   
**unfolding** *distance<sub>Q</sub>.simps*  
**using** *pass-to-quotient a-in-A b-in-B*  
**by** *fastforce*  
**qed**

```

lemma relation-paths-subset:
  fixes
     $n :: \text{'x nat}$  and
     $p :: \text{'x list}$  and
     $r :: \text{'x rel}$  and
     $X :: \text{'x set}$ 
  assumes  $r \subseteq X \times X$ 
  shows  $\forall p. p \in \text{relation-paths } r \longrightarrow (\forall i < \text{length } p. p!i \in X)$ 
proof (safe)
  fix
     $p :: \text{'x list}$  and
     $i :: \text{nat}$ 
  assume  $p \in \text{relation-paths } r$ 
  then obtain  $k :: \text{nat}$  where
     $\text{len-}p: \text{length } p = 2 * k$  and
     $\text{rel}: \forall i < k. (p!(2 * i), p!(2 * i + 1)) \in r$ 
  by auto
  moreover obtain  $k' :: \text{nat}$  where
     $i\text{-cases}: i = 2 * k' \vee i = 2 * k' + 1$ 
  using diff-Suc-1 even-Suc oddE odd-two-times-div-two-nat
  by metis
  moreover assume  $i < \text{length } p$ 
  ultimately have  $k' < k$ 
  by linarith
  thus  $p!i \in X$ 
  using assms rel i-cases
  by blast
qed

lemma admissible-path-len:
  fixes
     $d :: \text{'x Distance}$  and
     $r :: \text{'x rel}$  and
     $X :: \text{'x set}$  and
     $a\ b :: \text{'x}$  and
     $p :: \text{'x list}$ 
  assumes refl-on X r
  shows triangle-ineq  $X\ d \wedge p \in \text{relation-paths } r \wedge \text{total-invariance}_{\mathcal{D}}\ d\ r$ 
     $\wedge a \in X \wedge b \in X \longrightarrow \text{path-length } (a\#p@[b])\ d \geq d\ a\ b$ 
proof (clarify, induction p d arbitrary: a b rule: path-length.induct)
  case (1  $d$ )
    show  $d\ a\ b \leq \text{path-length } (a\#\ []@[b])\ d$ 
    by simp
  next
    case (2  $x\ d$ )
    thus  $d\ a\ b \leq \text{path-length } (a\#[x]@[b])\ d$ 
    by simp
  next
    case (3  $x\ y\ xs\ d$ )

```

```

assume
  ineq: triangle-ineq  $X$   $d$  and
  a-in-X:  $a \in X$  and
  b-in-X:  $b \in X$  and
  rel:  $x\#y\#xs \in \text{relation-paths } r$  and
  invar: total-invariance $\mathcal{D}$   $d$   $r$  and
  hyp:
     $\bigwedge a\ b.\ \text{triangle-ineq } X\ d \implies xs \in \text{relation-paths } r$ 
     $\implies \text{total-invariance}_{\mathcal{D}}\ d\ r \implies a \in X \implies b \in X$ 
     $\implies d\ a\ b \leq \text{path-length } (a\#xs@[b])\ d$ 
then obtain  $k :: \text{nat}$  where
  len: length  $(x\#y\#xs) = 2 * k$ 
  by auto
moreover have  $\forall\ i < k - 1.\ (xs!(2 * i), xs!(2 * i + 1)) =$ 
   $((x\#y\#xs)!(2 * (i + 1)), (x\#y\#xs)!(2 * (i + 1) + 1))$ 
  by simp
ultimately have  $\forall\ i < k - 1.\ (xs!(2 * i), xs!(2 * i + 1)) \in r$ 
  using rel less-diff-conv
  unfolding relation-paths.simps
  by fastforce
moreover have length  $xs = 2 * (k - 1)$ 
  using len
  by simp
ultimately have  $xs \in \text{relation-paths } r$ 
  by simp
hence  $\forall\ x\ y.\ x \in X \wedge y \in X \longrightarrow d\ x\ y \leq \text{path-length } (x\#xs@[y])\ d$ 
  using ineq invar hyp
  by blast
moreover have
  path-length  $(a\#(x\#y\#xs)@[b])\ d = d\ a\ x + \text{path-length } (y\#xs@[b])\ d$ 
  by simp
moreover have  $x\text{-rel-}y: (x, y) \in r$ 
  using rel
  unfolding relation-paths.simps
  by fastforce
ultimately have path-length  $(a\#(x\#y\#xs)@[b])\ d \geq d\ a\ x + d\ y\ b$ 
  using assms add-left-mono assms refl-onD2 b-in-X
  unfolding refl-on-def
  by metis
moreover have  $d\ y\ b = d\ x\ b$ 
  using invar x-rel-y rewrite-total-invarianceD assms b-in-X
  unfolding refl-on-def
  by fastforce
moreover have  $d\ a\ x + d\ x\ b \geq d\ a\ b$ 
  using a-in-X b-in-X x-rel-y assms ineq
  unfolding refl-on-def triangle-ineq-def
  by auto
ultimately show  $d\ a\ b \leq \text{path-length } (a\#(x\#y\#xs)@[b])\ d$ 
  by simp

```



qed

**lemma** *quotient-dist-coincides-with-dist<sub>Q</sub>*:

**fixes**

$d :: 'x \text{ Distance}$  **and**

$r :: 'x \text{ rel}$  **and**

$X :: 'x \text{ set}$

**assumes**

*equiv*:  $\text{equiv } X \ r$  **and**

*tri*:  $\text{triangle-ineq } X \ d$  **and**

*invar*:  $\text{total-invariance}_{\mathcal{D}} \ d \ r$

**shows**  $\forall A \in X \ // \ r. \ \forall B \in X \ // \ r. \ \text{quotient-dist } r \ d \ A \ B = \text{distance}_{\mathcal{Q}} \ d \ A \ B$

**proof** (*clarify*)

**fix**  $A \ B :: 'x \text{ set}$

**assume**

*A-in-quot-X*:  $A \in X \ // \ r$  **and**

*B-in-quot-X*:  $B \in X \ // \ r$

**then obtain**

$a \ b :: 'x$  **where**

*el*:  $a \in A \wedge b \in B$  **and**

*def-dist*:  $\text{distance}_{\mathcal{Q}} \ d \ A \ B = d \ a \ b$

**using** *dist-pass-to-quotient* *assms* *in-quotient-imp-non-empty* *ex-in-conv*

**by** (*metis* (*full-types*))

**have**  $b \in X$

**using** *B-in-quot-X* *el* *equiv* *quotient-eq-iff* *equiv* *equiv-class-eq-iff*

**by** *metis*

**hence**  $B = r \ \text{``} \{b\}$

**using** *equiv-class-self* *B-in-quot-X* *el* *equiv* *quotientI* *quotient-eq-iff*

**by** *metis*

**moreover have**  $a \in X$

**using** *A-in-quot-X* *el* *equiv* *quotient-eq-iff* *equiv* *equiv-class-eq-iff*

**by** *metis*

**ultimately have** *equiv-class*:  $A = r \ \text{``} \{a\} \wedge B = r \ \text{``} \{b\}$

**using** *A-in-quot-X* *el* *equiv* *quotientI* *quotient-eq-iff*

**by** *slow*

**have**  $\forall p \in \text{admissible-paths } r \ A \ B.$

$\exists p' \ x \ y. \ x \in A \wedge y \in B \wedge p' \in \text{relation-paths } r \wedge p = x \# p' @ [y]$

**unfolding** *admissible-paths.simps*

**by** *blast*

**moreover have**  $\forall x \ y. \ x \in A \wedge y \in B \longrightarrow d \ x \ y = d \ a \ b$

**using** *invar* *equiv-class*

**by** *auto*

**moreover have** *refl-on*  $X \ r$

**using** *equiv*

**unfolding** *equiv-def*

**by** *blast*

**moreover have**  $r \subseteq X \times X \wedge A \subseteq X \wedge B \subseteq X$

**using** *assms* *A-in-quot-X* *B-in-quot-X* *Union-quotient* *Union-upper*

**unfolding** *equiv-def* *refl-on-def*

by *metis*  
**ultimately have**  $\forall p. p \in \text{admissible-paths } r \ A \ B \longrightarrow \text{path-length } p \ d \geq d \ a \ b$   
 using *admissible-path-len[of X r d] tri el invar in-mono*  
 by *metis*  
**hence**  $\forall l. l \in \bigcup \{ \{ \text{path-length } p \ d \mid p. p \in \text{admissible-paths } r \ A \ B \} \}$   
 $\longrightarrow l \geq d \ a \ b$   
 by *blast*  
**hence** *geq: quotient-dist r d A B  $\geq$  distance<sub>Q</sub> d A B*  
 unfolding *quotient-dist.simps le-Inf-iff*  
 using *def-dist*  
 by *simp*  
**have**  $[a, b] \in \text{admissible-paths } r \ A \ B$   
 using *el*  
 by *simp*  
**moreover have**  $\text{path-length } [a, b] \ d = d \ a \ b$   
 by *simp*  
**ultimately have**  $\text{quotient-dist } r \ d \ A \ B \leq d \ a \ b$   
 unfolding *quotient-dist.simps*  
 using *CollectI Inf-lower ccpo-Sup-singleton*  
 by (*metis (mono-tags, lifting)*)  
**thus**  $\text{quotient-dist } r \ d \ A \ B = \text{distance}_Q \ d \ A \ B$   
 using *geq def-dist nle-le*  
 by *metis*  
**qed**

**lemma** *inf-dist-coincides-with-dist<sub>Q</sub>:*  
**fixes**  
 $d :: 'x \ \text{Distance}$  **and**  
 $r :: 'x \ \text{rel}$  **and**  
 $X :: 'x \ \text{set}$   
**assumes**  
*equiv-X-r: equiv X r* **and**  
*tot-inv-d-r: total-invariance<sub>D</sub> d r*  
**shows**  $\forall A \in X \ // \ r. \ \forall B \in X \ // \ r.$   
 $\text{distance-infimum}_Q \ d \ A \ B = \text{distance}_Q \ d \ A \ B$   
**proof** (*clarify*)  
**fix**  $A \ B :: 'x \ \text{set}$   
**assume**  
 $A\text{-in-quot-}X: A \in X \ // \ r$  **and**  
 $B\text{-in-quot-}X: B \in X \ // \ r$   
**then obtain**  
 $a \ b :: 'x$  **where**  
 $el: a \in A \wedge b \in B$  **and**  
 $def\text{-}dist: \text{distance}_Q \ d \ A \ B = d \ a \ b$   
 using *dist-pass-to-quotient equiv-X-r tot-inv-d-r*  
*in-quotient-imp-non-empty ex-in-conv*  
 by (*metis (full-types)*)  
**from** *def-dist equiv-X-r tot-inv-d-r*  
**have**  $\forall x \ y. x \in A \wedge y \in B \longrightarrow d \ x \ y = d \ a \ b$

```

    using dist-pass-to-quotient A-in-quot-X B-in-quot-X
    by force
  hence  $\{d\ x\ y \mid x\ y.\ x \in A \wedge y \in B\} = \{d\ a\ b\}$ 
    using el
    by blast
  thus  $\text{distance-infimum}_{\mathcal{Q}}\ d\ A\ B = \text{distance}_{\mathcal{Q}}\ d\ A\ B$ 
    unfolding distance-infimumQ.simps
    using def-dist
    by simp
qed

lemma inf-helper:
  fixes
     $A\ B :: 'x\ \text{set}$  and
     $d :: 'x\ \text{Distance}$ 
  shows  $\text{Inf}\ \{d\ a\ b \mid a\ b.\ a \in A \wedge b \in B\} =$ 
     $\text{Inf}\ \{\text{Inf}\ \{d\ a\ b \mid b.\ b \in B\} \mid a.\ a \in A\}$ 
  proof -
    have  $\forall\ a\ b.\ a \in A \wedge b \in B \longrightarrow \text{Inf}\ \{d\ a\ b \mid b.\ b \in B\} \leq d\ a\ b$ 
      using INF-lower Setcompr-eq-image
      by metis
    hence  $\forall\ \alpha \in \{d\ a\ b \mid a\ b.\ a \in A \wedge b \in B\}.$ 
       $\exists\ \beta \in \{\text{Inf}\ \{d\ a\ b \mid b.\ b \in B\} \mid a.\ a \in A\}.\ \beta \leq \alpha$ 
      by blast
    hence  $\text{Inf}\ \{\text{Inf}\ \{d\ a\ b \mid b.\ b \in B\} \mid a.\ a \in A\}$ 
       $\leq \text{Inf}\ \{d\ a\ b \mid a\ b.\ a \in A \wedge b \in B\}$ 
      using Inf-mono
      by (metis (no-types, lifting))
    moreover have
       $\neg \text{Inf}\ \{\text{Inf}\ \{d\ a\ b \mid b.\ b \in B\} \mid a.\ a \in A\}$ 
       $< \text{Inf}\ \{d\ a\ b \mid a\ b.\ a \in A \wedge b \in B\}$ 
    proof (rule ccontr, safe)
      assume  $\text{Inf}\ \{\text{Inf}\ \{d\ a\ b \mid b.\ b \in B\} \mid a.\ a \in A\}$ 
         $< \text{Inf}\ \{d\ a\ b \mid a\ b.\ a \in A \wedge b \in B\}$ 
      then obtain  $\alpha :: \text{ereal}$  where
        inf:  $\alpha \in \{\text{Inf}\ \{d\ a\ b \mid b.\ b \in B\} \mid a.\ a \in A\}$  and
        less:  $\alpha < \text{Inf}\ \{d\ a\ b \mid a\ b.\ a \in A \wedge b \in B\}$ 
        using Inf-less-iff
        by (metis (no-types, lifting))
      then obtain  $a :: 'x$  where
        a-in-A:  $a \in A$  and
         $\alpha = \text{Inf}\ \{d\ a\ b \mid b.\ b \in B\}$ 
        by blast
      with less
      have inf-less:  $\text{Inf}\ \{d\ a\ b \mid b.\ b \in B\} < \text{Inf}\ \{d\ a\ b \mid a\ b.\ a \in A \wedge b \in B\}$ 
        by blast
      have  $\{d\ a\ b \mid b.\ b \in B\} \subseteq \{d\ a\ b \mid a\ b.\ a \in A \wedge b \in B\}$ 
        using a-in-A
        by blast

```

```

hence  $\text{Inf } \{d \ a \ b \mid a \ b. \ a \in A \wedge b \in B\} \leq \text{Inf } \{d \ a \ b \mid b. \ b \in B\}$ 
using Inf-superset-mono
by (metis (no-types, lifting))
with inf-less
show False
using linorder-not-less
by simp
qed
ultimately show ?thesis
by simp
qed

lemma invar-dist-simple:
fixes
   $d :: 'y \text{ Distance}$  and
   $G :: 'x \text{ monoid}$  and
   $Y :: 'y \text{ set}$  and
   $\varphi :: ('x, 'y) \text{ binary-fun}$ 
assumes
  action- $\varphi$ : group-action  $G \ Y \ \varphi$  and
  invar: invariance $_{\mathcal{D}}$   $d \ (\text{carrier } G) \ Y \ \varphi$ 
shows simple (action-induced-rel (carrier  $G$ )  $Y \ \varphi$ )  $Y \ d$ 
proof (unfold simple.simps, safe)
fix  $A :: 'y \text{ set}$ 
assume class $_Y$ :  $A \in Y \ // \text{ action-induced-rel (carrier } G) \ Y \ \varphi$ 
moreover have equiv-rel:
  equiv  $Y \ (\text{action-induced-rel (carrier } G) \ Y \ \varphi)$ 
using assms rel-ind-by-group-act-equiv
by blast
ultimately obtain  $a :: 'y$  where
  a-in- $A$ :  $a \in A$ 
using equiv-Eps-in
by blast
have subset:  $\forall B \in Y \ // \text{ action-induced-rel (carrier } G) \ Y \ \varphi. B \subseteq Y$ 
using equiv-rel in-quotient-imp-subset
by blast
hence  $\forall B \in Y \ // \text{ action-induced-rel (carrier } G) \ Y \ \varphi.$ 
   $\forall B' \in Y \ // \text{ action-induced-rel (carrier } G) \ Y \ \varphi.$ 
   $\forall b \in B. \forall c \in B'. b \in Y \wedge c \in Y$ 
using class $_Y$ 
by blast
hence eq-dist:
   $\forall B \in Y \ // \text{ action-induced-rel (carrier } G) \ Y \ \varphi.$ 
   $\forall B' \in Y \ // \text{ action-induced-rel (carrier } G) \ Y \ \varphi.$ 
   $\forall b \in B. \forall c \in B'. \forall g \in \text{carrier } G.$ 
   $d \ (\varphi \ g \ c) \ (\varphi \ g \ b) = d \ c \ b$ 
using invar rewrite-invariance $_{\mathcal{D}}$  class $_Y$ 
by metis
have  $\forall b \in Y. \forall g \in \text{carrier } G.$ 

```

$(b, \varphi g b) \in \text{action-induced-rel } (\text{carrier } G) Y \varphi$   
**unfolding** *action-induced-rel.simps*  
**using** *group-action.element-image action-φ*  
**by** *fastforce*  
**hence**  $\forall b \in Y. \forall g \in \text{carrier } G.$   
 $\varphi g b \in \text{action-induced-rel } (\text{carrier } G) Y \varphi \text{ “ } \{b\}$   
**unfolding** *Image-def*  
**by** *blast*  
**moreover have** *equiv-class*:  
 $\forall B. B \in Y // \text{action-induced-rel } (\text{carrier } G) Y \varphi \longrightarrow$   
 $(\forall b \in B. B = \text{action-induced-rel } (\text{carrier } G) Y \varphi \text{ “ } \{b\})$   
**using** *Image-singleton-iff equiv-class-eq-iff equiv-rel*  
*quotientI quotient-eq-iff*  
**by** *meson*  
**ultimately have** *closed-class*:  
 $\forall B \in Y // \text{action-induced-rel } (\text{carrier } G) Y \varphi.$   
 $\forall b \in B. \forall g \in \text{carrier } G. \varphi g b \in B$   
**using** *equiv-rel subset*  
**by** *blast*  
**with** *eq-dist class<sub>Y</sub>*  
**have** *a-subset-A*:  
 $\forall B \in Y // \text{action-induced-rel } (\text{carrier } G) Y \varphi.$   
 $\{d a b \mid b. b \in B\} \subseteq \{d a b \mid a b. a \in A \wedge b \in B\}$   
**using** *a-in-A*  
**by** *blast*  
**have**  $\forall a' \in A. A = \text{action-induced-rel } (\text{carrier } G) Y \varphi \text{ “ } \{a'\}$   
**using** *class<sub>Y</sub> equiv-rel equiv-class*  
**by** *presburger*  
**hence**  $\forall a' \in A. (a', a) \in \text{action-induced-rel } (\text{carrier } G) Y \varphi$   
**using** *a-in-A*  
**by** *blast*  
**hence**  $\forall a' \in A. \exists g \in \text{carrier } G. \varphi g a' = a$   
**by** *simp*  
**hence**  $\forall B \in Y // \text{action-induced-rel } (\text{carrier } G) Y \varphi.$   
 $\forall a' b. a' \in A \wedge b \in B \longrightarrow (\exists g \in \text{carrier } G. d a' b = d a (\varphi g b))$   
**using** *eq-dist class<sub>Y</sub>*  
**by** *metis*  
**hence**  $\forall B \in Y // \text{action-induced-rel } (\text{carrier } G) Y \varphi.$   
 $\forall a' b. a' \in A \wedge b \in B \longrightarrow d a' b \in \{d a b \mid b. b \in B\}$   
**using** *closed-class mem-Collect-eq*  
**by** *fastforce*  
**hence**  $\forall B \in Y // \text{action-induced-rel } (\text{carrier } G) Y \varphi.$   
 $\{d a b \mid b. b \in B\} \supseteq \{d a b \mid a b. a \in A \wedge b \in B\}$   
**using** *closed-class*  
**by** *blast*  
**with** *a-subset-A*  
**have**  $\forall B \in Y // \text{action-induced-rel } (\text{carrier } G) Y \varphi.$   
 $\text{distance-infimum}_{\mathcal{Q}} d A B = \text{Inf } \{d a b \mid b. b \in B\}$   
**unfolding** *distance-infimum<sub>Q</sub>.simps*

```

    by fastforce
  thus  $\exists a \in A. \forall B \in Y // \text{action-induced-rel } (\text{carrier } G) Y \varphi.$ 
    distance-infimumQ  $d A B = \text{Inf } \{d a b \mid b. b \in B\}$ 
    using a-in-A
    by blast
qed

lemma tot-invar-dist-simple:
  fixes
     $d :: 'x \text{ Distance}$  and
     $r :: 'x \text{ rel}$  and
     $X :: 'x \text{ set}$ 
  assumes
    equiv-on-X:  $\text{equiv } X r$  and
    invar:  $\text{total-invariance}_{\mathcal{D}} d r$ 
  shows  $\text{simple } r X d$ 
proof (unfold simple.simps, safe)
  fix  $A :: 'x \text{ set}$ 
  assume A-quot-X:  $A \in X // r$ 
  then obtain  $a :: 'x$  where
    a-in-A:  $a \in A$ 
    using equiv-on-X equiv-Eps-in
    by blast
  have  $\forall a \in A. A = r `` \{a\}$ 
    using A-quot-X Image-singleton-iff equiv-class-eq equiv-on-X quotientE
    by metis
  hence  $\forall a a'. a \in A \wedge a' \in A \longrightarrow (a, a') \in r$ 
    by blast
  moreover have  $\forall B \in X // r. \forall b \in B. (b, b) \in r$ 
    using equiv-on-X quotient-eq-iff
    by metis
  ultimately have
     $\forall B \in X // r. \forall a a' b. a \in A \wedge a' \in A \wedge b \in B \longrightarrow d a b = d a' b$ 
    using invar rewrite-total-invarianceD
    by simp
  hence  $\forall B \in X // r.$ 
     $\{d a b \mid a b. a \in A \wedge b \in B\} = \{d a b \mid a' b. a' \in A \wedge b \in B\}$ 
    using a-in-A
    by blast
  moreover have
     $\forall B \in X // r. \{d a b \mid a' b. a' \in A \wedge b \in B\} =$ 
     $\{d a b \mid b. b \in B\}$ 
    using a-in-A
    by blast
  ultimately have
     $\forall B \in X // r. \text{Inf } \{d a b \mid a b. a \in A \wedge b \in B\} =$ 
     $\text{Inf } \{d a b \mid b. b \in B\}$ 
    by simp
  hence  $\forall B \in X // r. \text{distance-infimum}_Q d A B =$ 

```

```

      Inf {d a b | b. b ∈ B}
    by simp
  thus ∃ a ∈ A. ∀ B ∈ X // r.
      distance-infimum_Q d A B = Inf {d a b | b. b ∈ B}
    using a-in-A
    by blast
qed

```

### 5.7.2 Consensus and Results

```

fun elections- $\mathcal{K}_Q :: ('a, 'v)$  Election rel  $\Rightarrow ('a, 'v, 'r$  Result) Consensus-Class  $\Rightarrow$ 
      ('a, 'v) Election set set where
      elections- $\mathcal{K}_Q$  r C = (elections- $\mathcal{K}$  C) // r

```

```

fun (in result) limit_Q :: ('a, 'v) Election set  $\Rightarrow 'r$  set  $\Rightarrow 'r$  set where
      limit_Q X res =  $\bigcap \{ \text{limit (alternatives-}\mathcal{E} \ E) \ res \mid E. E \in X \}$ 

```

#### Auxiliary Lemmas

```

lemma closed-under-equiv-rel-subset:
  fixes
    X Y Z :: 'x set and
    r :: 'x rel
  assumes
    equiv X r and
    Y  $\subseteq$  X and
    Z  $\subseteq$  X and
    Z  $\in$  Y // r and
    closed-restricted-rel r X Y
  shows Z  $\subseteq$  Y
proof (safe)
  fix z :: 'x
  assume z  $\in$  Z
  then obtain y :: 'x where
    y  $\in$  Y and
    (y, z)  $\in$  r
  using assms
  unfolding quotient-def Image-def
  by blast
  hence (y, z)  $\in$  r  $\cap$  Y  $\times$  X
  using assms
  unfolding equiv-def refl-on-def
  by blast
  hence z  $\in$  {z.  $\exists y \in Y. (y, z) \in r \cap Y \times X$ }
  by blast
  thus z  $\in$  Y
  using assms
  unfolding closed-restricted-rel.simps restricted-rel.simps
  by blast
qed

```

**lemma** (in result) *limit-invar*:

**fixes**

$d :: ('a, 'v)$  Election Distance **and**

$r :: ('a, 'v)$  Election rel **and**

$C :: ('a, 'v, 'r)$  Result Consensus-Class **and**

$X A :: ('a, 'v)$  Election set

**assumes**

*quot-class*:  $A \in X // r$  **and**

*equiv-rel*:  $\text{equiv } X \ r$  **and**

*cons-subset*:  $\text{elections-}\mathcal{K} \ C \subseteq X$  **and**

*invar-res*:  $\text{is-symmetry } (\lambda E. \text{limit } (\text{alternatives-}\mathcal{E} \ E) \ \text{UNIV})$  (Invariance  $r$ )

**shows**  $\forall a \in A. \text{limit } (\text{alternatives-}\mathcal{E} \ a) \ \text{UNIV} = \text{limit}_Q A \ \text{UNIV}$

**proof**

**fix**  $a :: ('a, 'v)$  Election

**assume**  $a\text{-in-}A$ :  $a \in A$

**hence**  $\forall b \in A. (a, b) \in r$

**using** *quot-class equiv-rel quotient-eq-iff*

**by** *metis*

**hence**  $\forall b \in A.$

$\text{limit } (\text{alternatives-}\mathcal{E} \ b) \ \text{UNIV} = \text{limit } (\text{alternatives-}\mathcal{E} \ a) \ \text{UNIV}$

**using** *invar-res*

**unfolding** *is-symmetry.simps*

**by** (*metis (mono-tags, lifting)*)

**hence**  $\text{limit}_Q A \ \text{UNIV} = \bigcap \{ \text{limit } (\text{alternatives-}\mathcal{E} \ a) \ \text{UNIV} \}$

**unfolding** *limit\_Q.simps*

**using**  $a\text{-in-}A$

**by** *blast*

**thus**  $\text{limit } (\text{alternatives-}\mathcal{E} \ a) \ \text{UNIV} = \text{limit}_Q A \ \text{UNIV}$

**by** *simp*

**qed**

**lemma** (in result) *preimg-invar*:

**fixes**

$f :: 'x \Rightarrow 'y$  **and**

$\text{domain}_f \ X :: 'x \text{ set}$  **and**

$d :: 'x$  Distance **and**

$r :: 'x$  rel

**assumes**

*equiv-rel*:  $\text{equiv } X \ r$  **and**

*cons-subset*:  $\text{domain}_f \subseteq X$  **and**

*closed-domain*:  $\text{closed-restricted-rel } r \ X \ \text{domain}_f$  **and**

*invar-f*:  $\text{is-symmetry } f$  (Invariance ( $\text{Restr } r \ \text{domain}_f$ ))

**shows**  $\forall y. (\text{preimg } f \ \text{domain}_f \ y) // r = \text{preimg } (\pi_Q f) (\text{domain}_f // r) \ y$

**proof** (*safe*)

**fix**

$A :: 'x \text{ set}$  **and**

$y :: 'y$

**assume** *preimg-quot*:  $A \in \text{preimg } f \ \text{domain}_f \ y // r$



hence  $A\text{-in-dom}$ :  $A \in \text{domain}_f // r$   
 unfolding *preimg.simps quotient-def*  
 by *blast*  
 obtain  $x :: 'x$  where  
 $x \in \text{preimg } f \text{ domain}_f y$  and  
 $A\text{-eq-img-singleton-r}$ :  $A = r `` \{x\}$   
 using *equiv-rel preimg-quot quotientE*  
 unfolding *quotient-def*  
 by *blast*  
 hence  $x\text{-in-dom-and-f-x-y}$ :  $x \in \text{domain}_f \wedge f x = y$   
 unfolding *preimg.simps*  
 by *blast*  
 moreover have  $r `` \{x\} \subseteq X$   
 using *equiv-rel equiv-type*  
 by *fastforce*  
 ultimately have  $r `` \{x\} \subseteq \text{domain}_f$   
 using *closed-domain A-eq-img-singleton-r A-in-dom*  
 by *fastforce*  
 hence  $\forall x' \in r `` \{x\}. (x, x') \in \text{Restr } r \text{ domain}_f$   
 using *x-in-dom-and-f-x-y in-mono*  
 by *blast*  
 hence  $\forall x' \in r `` \{x\}. f x' = y$   
 using *invar-f x-in-dom-and-f-x-y*  
 unfolding *is-symmetry.simps*  
 by *metis*  
 moreover have  $x \in A$   
 using *equiv-rel cons-subset equiv-class-self in-mono*  
 $A\text{-eq-img-singleton-r } x\text{-in-dom-and-f-x-y}$   
 by *metis*  
 ultimately have  $f ` A = \{y\}$   
 using *A-eq-img-singleton-r*  
 by *auto*  
 hence  $\pi_Q f A = y$   
 unfolding  *$\pi_Q$ .simps singleton-set.simps*  
 using *insert-absorb insert-iff insert-not-empty singleton-set-def-if-card-one*  
 $\text{is-singletonI is-singleton-altdef singleton-set.simps}$   
 by *metis*  
 thus  $A \in \text{preimg } (\pi_Q f) (\text{domain}_f // r) y$   
 using *A-in-dom*  
 unfolding *preimg.simps*  
 by *blast*  
 next  
 fix  
 $A :: 'x \text{ set}$  and  
 $y :: 'y$   
 assume *quot-preimg*:  $A \in \text{preimg } (\pi_Q f) (\text{domain}_f // r) y$   
 hence  $A\text{-in-dom-rel-r}$ :  $A \in \text{domain}_f // r$   
 using *cons-subset equiv-rel*  
 by *auto*

hence  $A \subseteq X$   
 using *equiv-rel cons-subset Image-subset equiv-type quotientE*  
 by *metis*  
 hence  $A\text{-in-dom}: A \subseteq \text{domain}_f$   
 using *closed-under-equiv-rel-subset*  
     *closed-domain cons-subset A-in-dom-rel-r equiv-rel*  
 by *blast*  
 moreover obtain  $x :: 'x$  where  
      $x\text{-in-}A: x \in A$  and  
      $A\text{-eq-}r\text{-img-single-}x: A = r `` \{x\}$   
 using *A-in-dom-rel-r equiv-rel cons-subset equiv-class-self in-mono quotientE*  
 by *metis*  
 ultimately have  $\forall x' \in A. (x, x') \in \text{Restr } r \text{ domain}_f$   
 by *blast*  
 hence  $\forall x' \in A. f x' = f x$   
 using *invar-f*  
 by *fastforce*  
 hence  $f ` A = \{f x\}$   
 using *x-in-A*  
 by *blast*  
 hence  $\pi_Q f A = f x$   
 unfolding  *$\pi_Q.\text{simps singleton-set.simps}$*   
 using *is-singleton-altdef singleton-set-def-if-card-one*  
 by *fastforce*  
 also have  $\pi_Q f A = y$   
 using *quot-preimg*  
 unfolding *preimg.simps*  
 by *blast*  
 finally have  $f x = y$   
 by *simp*  
 moreover have  $x \in \text{domain}_f$   
 using *x-in-A A-in-dom*  
 by *blast*  
 ultimately have  $x \in \text{preimg } f \text{ domain}_f y$   
 by *simp*  
 thus  $A \in \text{preimg } f \text{ domain}_f y // r$   
 using *A-eq-r-img-single-x*  
 unfolding *quotient-def*  
 by *blast*  
 qed

lemma *minimizer-helper*:

fixes  
      $f :: 'x \Rightarrow 'y$  and  
      $\text{domain}_f :: 'x \text{ set}$  and  
      $d :: 'x \text{ Distance}$  and  
      $Y :: 'y \text{ set}$  and  
      $x :: 'x$  and  
      $y :: 'y$

**shows**  $y \in \text{minimizer } f \text{ domain}_f \text{ d } Y \text{ x} =$   
 $(y \in Y \wedge (\forall y' \in Y.$   
 $\quad \text{Inf } (d \text{ x } ' (\text{preimg } f \text{ domain}_f y)) \leq \text{Inf } (d \text{ x } ' (\text{preimg } f \text{ domain}_f y'))))$   
**unfolding** *is-arg-min-def minimizer.simps arg-min-set.simps*  
**by** *auto*

**lemma** *rewr-singleton-set-system-union:*

**fixes**  
 $Y :: 'x \text{ set set}$  **and**  
 $X :: 'x \text{ set}$   
**assumes**  $Y \subseteq \text{singleton-set-system } X$   
**shows**  
 $\text{singleton-set-union: } x \in \bigcup Y \longleftrightarrow \{x\} \in Y$  **and**  
 $\text{obtain-singleton: } A \in \text{singleton-set-system } X \longleftrightarrow (\exists x \in X. A = \{x\})$   
**unfolding** *singleton-set-system.simps*  
**using** *assms*  
**by** *auto*

**lemma** *union-inf:*

**fixes**  $X :: \text{ereal set set}$   
**shows**  $\text{Inf } \{\text{Inf } A \mid A. A \in X\} = \text{Inf } (\bigcup X)$   
**proof** –  
**let**  $?inf = \text{Inf } \{\text{Inf } A \mid A. A \in X\}$   
**have**  $\forall A \in X. \forall x \in A. ?inf \leq x$   
**using** *INF-lower2 Inf-lower Setcompr-eq-image*  
**by** *metis*  
**hence**  $\forall x \in \bigcup X. ?inf \leq x$   
**by** *simp*  
**hence** *le:*  $?inf \leq \text{Inf } (\bigcup X)$   
**using** *Inf-greatest*  
**by** *blast*  
**have**  $\forall A \in X. \text{Inf } (\bigcup X) \leq \text{Inf } A$   
**using** *Inf-superset-mono Union-upper*  
**by** *metis*  
**hence**  $\text{Inf } (\bigcup X) \leq \text{Inf } \{\text{Inf } A \mid A. A \in X\}$   
**using** *le-Inf-iff*  
**by** *auto*  
**thus** *?thesis*  
**using** *le*  
**by** *simp*  
**qed**

### 5.7.3 Distance Rationalization

**fun** (in *result*)  $\mathcal{R}_{\mathcal{Q}} :: ('a, 'v) \text{ Election rel} \Rightarrow ('a, 'v) \text{ Election Distance} \Rightarrow$   
 $('a, 'v, 'r \text{ Result}) \text{ Consensus-Class} \Rightarrow ('a, 'v) \text{ Election set} \Rightarrow 'r \text{ set}$  **where**  
 $\mathcal{R}_{\mathcal{Q}} \text{ r d } C \text{ A} =$   
 $\bigcup (\text{minimizer } (\pi_{\mathcal{Q}} (\text{elect-r} \circ \text{fun}_{\mathcal{E}} (\text{rule-}\mathcal{K} \text{ C}))) (\text{elections-}\mathcal{K}_{\mathcal{Q}} \text{ r } C)$   
 $\quad (\text{distance-infimum}_{\mathcal{Q}} \text{ d}) (\text{singleton-set-system } (\text{limit}_{\mathcal{Q}} \text{ A UNIV})) \text{ A})$

**fun** (in result) distance- $\mathcal{R}_Q :: ('a, 'v)$  Election rel  $\Rightarrow ('a, 'v)$  Election Distance  $\Rightarrow$   
 ('a, 'v, 'r Result) Consensus-Class  $\Rightarrow ('a, 'v)$  Election set  $\Rightarrow$  'r Result **where**  
 distance- $\mathcal{R}_Q$  r d C A =  
 ( $\mathcal{R}_Q$  r d C A,  
 $\pi_Q (\lambda E. \text{limit} (\text{alternatives-}\mathcal{E} E) \text{UNIV}) A - \mathcal{R}_Q$  r d C A,  
 {})

Proposition 4.17 by Hadjibeyli and Wilson [3].

**theorem** (in result) invar-dr-simple-dist-imp-quotient-dr-winners:

**fixes**

d :: ('a, 'v) Election Distance **and**  
 C :: ('a, 'v, 'r Result) Consensus-Class **and**  
 r :: ('a, 'v) Election rel **and**  
 X A :: ('a, 'v) Election set

**assumes**

simple: simple r X d **and**  
 closed-domain: closed-restricted-rel r X (elections- $\mathcal{K}$  C) **and**  
 invar-res:  
 is-symmetry ( $\lambda E. \text{limit} (\text{alternatives-}\mathcal{E} E) \text{UNIV}$ ) (Invariance r) **and**  
 invar-C: is-symmetry (elect-r  $\circ$  fun $_{\mathcal{E}}$  (rule- $\mathcal{K}$  C))  
 (Invariance (Restr r (elections- $\mathcal{K}$  C))) **and**  
 invar-dr: is-symmetry (fun $_{\mathcal{E}}$  ( $\mathcal{R}_W$  d C)) (Invariance r) **and**  
 quot-class: A  $\in$  X // r **and**  
 equiv-rel: equiv X r **and**  
 cons-subset: elections- $\mathcal{K}$  C  $\subseteq$  X

**shows**  $\pi_Q$  (fun $_{\mathcal{E}}$  ( $\mathcal{R}_W$  d C)) A =  $\mathcal{R}_Q$  r d C A

**proof** –

**have** preimg-img-imp-cls:

$\forall y B. B \in \text{preimg} (\pi_Q (\text{elect-r} \circ \text{fun}_{\mathcal{E}} (\text{rule-}\mathcal{K} C))) (\text{elections-}\mathcal{K}_Q r C) y$   
 $\longrightarrow B \in (\text{elections-}\mathcal{K} C) // r$

**by** simp

**have**  $\forall y. \forall E$

$\in \text{preimg} (\text{elect-r} \circ \text{fun}_{\mathcal{E}} (\text{rule-}\mathcal{K} C)) (\text{elections-}\mathcal{K} C) y. E \in r \text{ “ } \{E\}$

**using** equiv-rel cons-subset equiv-class-self equiv-rel in-mono

**unfolding** equiv-def preimg.simps

**by** fastforce

**hence**  $\forall y.$

$\bigcup (\text{preimg} (\text{elect-r} \circ \text{fun}_{\mathcal{E}} (\text{rule-}\mathcal{K} C)) (\text{elections-}\mathcal{K} C) y // r) \supseteq$   
 $\text{preimg} (\text{elect-r} \circ \text{fun}_{\mathcal{E}} (\text{rule-}\mathcal{K} C)) (\text{elections-}\mathcal{K} C) y$

**unfolding** quotient-def

**by** blast

**moreover** **have**  $\forall y.$

$\bigcup (\text{preimg} (\text{elect-r} \circ \text{fun}_{\mathcal{E}} (\text{rule-}\mathcal{K} C)) (\text{elections-}\mathcal{K} C) y // r) \subseteq$   
 $\text{preimg} (\text{elect-r} \circ \text{fun}_{\mathcal{E}} (\text{rule-}\mathcal{K} C)) (\text{elections-}\mathcal{K} C) y$

**proof** (intro allI subsetI)

**fix**

Y :: 'r set **and**

E :: ('a, 'v) Election

**assume**  $E \in \bigcup (\text{preimg } (\text{elect-}r \circ \text{fun}_{\mathcal{E}} (\text{rule-}\mathcal{K} \ C)) (\text{elections-}\mathcal{K} \ C) \ Y \ // \ r)$   
**then obtain**  $B :: ('a, 'v) \text{ Election set}$  **where**  
 $E\text{-in-}B$ :  $E \in B$  **and**  
 $B \in \text{preimg } (\text{elect-}r \circ \text{fun}_{\mathcal{E}} (\text{rule-}\mathcal{K} \ C)) (\text{elections-}\mathcal{K} \ C) \ Y \ // \ r$   
**by** *blast*  
**then obtain**  $E' :: ('a, 'v) \text{ Election}$  **where**  
 $B = r \text{ `` } \{E'\}$  **and**  
 $\text{map-to-}Y$ :  $E' \in \text{preimg } (\text{elect-}r \circ \text{fun}_{\mathcal{E}} (\text{rule-}\mathcal{K} \ C)) (\text{elections-}\mathcal{K} \ C) \ Y$   
**using** *quotientE*  
**by** *blast*  
**hence** *in-restr-rel*:  $(E', E) \in r \cap (\text{elections-}\mathcal{K} \ C) \times X$   
**using** *E-in-B equiv-rel*  
**unfolding** *preimg.simps equiv-def refl-on-def*  
**by** *blast*  
**hence**  $E \in \text{elections-}\mathcal{K} \ C$   
**using** *closed-domain*  
**unfolding** *closed-restricted-rel.simps restricted-rel.simps Image-def*  
**by** *blast*  
**hence** *rel-cons-els*:  $(E', E) \in \text{Restr } r (\text{elections-}\mathcal{K} \ C)$   
**using** *in-restr-rel*  
**by** *blast*  
**hence**  $(\text{elect-}r \circ \text{fun}_{\mathcal{E}} (\text{rule-}\mathcal{K} \ C)) \ E = (\text{elect-}r \circ \text{fun}_{\mathcal{E}} (\text{rule-}\mathcal{K} \ C)) \ E'$   
**using** *invar-C*  
**unfolding** *is-symmetry.simps*  
**by** *blast*  
**hence**  $(\text{elect-}r \circ \text{fun}_{\mathcal{E}} (\text{rule-}\mathcal{K} \ C)) \ E = Y$   
**using** *map-to-Y*  
**by** *simp*  
**thus**  $E \in \text{preimg } (\text{elect-}r \circ \text{fun}_{\mathcal{E}} (\text{rule-}\mathcal{K} \ C)) (\text{elections-}\mathcal{K} \ C) \ Y$   
**unfolding** *preimg.simps*  
**using** *rel-cons-els*  
**by** *blast*  
**qed**  
**ultimately have** *preimg-partition*:  $\forall \ y.$   
 $\bigcup (\text{preimg } (\text{elect-}r \circ \text{fun}_{\mathcal{E}} (\text{rule-}\mathcal{K} \ C)) (\text{elections-}\mathcal{K} \ C) \ y \ // \ r) =$   
 $\text{preimg } (\text{elect-}r \circ \text{fun}_{\mathcal{E}} (\text{rule-}\mathcal{K} \ C)) (\text{elections-}\mathcal{K} \ C) \ y$   
**by** *blast*  
**have** *quot-classes-subset*:  $(\text{elections-}\mathcal{K} \ C) \ // \ r \subseteq X \ // \ r$   
**using** *cons-subset*  
**unfolding** *quotient-def*  
**by** *blast*  
**obtain**  $a :: ('a, 'v) \text{ Election}$  **where**  
 $a\text{-in-}A$ :  $a \in A$  **and**  
 $a\text{-def-inf-dist}$ :  
 $\forall \ B \in X \ // \ r.$   
 $\text{distance-infimum}_{\mathcal{Q}} \ d \ A \ B = \text{Inf } \{d \ a \ b \mid b. b \in B\}$   
**using** *simple quot-class*  
**unfolding** *simple.simps*  
**by** *blast*

**hence** *inf-dist-preimg-sets*:

$$\begin{aligned} & \forall y \ B. B \in \text{preimg} (\pi_Q (\text{elect-r} \circ \text{fun}_{\mathcal{E}} (\text{rule-}\mathcal{K} \ C))) (\text{elections-}\mathcal{K}_Q \ r \ C) \ y \\ & \longrightarrow \text{distance-infimum}_Q \ d \ A \ B = \text{Inf} \ {d \ a \ b \mid b. b \in B} \end{aligned}$$

**using** *preimg-img-imp-cls quot-classes-subset*

**by** *blast*

**have** *wf-res-eq*:  $\text{singleton-set-system} (\text{limit} (\text{alternatives-}\mathcal{E} \ a) \ UNIV) = \text{singleton-set-system} (\text{limit}_Q \ A \ UNIV)$

**using** *invar-res a-in-A quot-class cons-subset equiv-rel limit-invar*

**by** *metis*

**have** *inf-le-iff*:  $\forall x.$

$$\begin{aligned} & (\forall y \in \text{singleton-set-system} (\text{limit} (\text{alternatives-}\mathcal{E} \ a) \ UNIV). \\ & \quad \text{Inf} (d \ a \ ' \text{preimg} (\text{elect-r} \circ \text{fun}_{\mathcal{E}} (\text{rule-}\mathcal{K} \ C)) (\text{elections-}\mathcal{K} \ C) \ \{x\}) \\ & \quad \leq \text{Inf} (d \ a \ ' \text{preimg} (\text{elect-r} \circ \text{fun}_{\mathcal{E}} (\text{rule-}\mathcal{K} \ C)) (\text{elections-}\mathcal{K} \ C) \ y)) \\ & = (\forall y \in \text{singleton-set-system} (\text{limit}_Q \ A \ UNIV). \\ & \quad \text{Inf} (\text{distance-infimum}_Q \ d \ A \ ' \text{preimg} (\pi_Q (\text{elect-r} \circ \text{fun}_{\mathcal{E}} (\text{rule-}\mathcal{K} \ C))) \\ & \quad \quad (\text{elections-}\mathcal{K}_Q \ r \ C) \ \{x\}) \\ & \quad \leq \text{Inf} (\text{distance-infimum}_Q \ d \ A \ ' \text{preimg} (\pi_Q (\text{elect-r} \circ \text{fun}_{\mathcal{E}} (\text{rule-}\mathcal{K} \ C))) \\ & \quad \quad (\text{elections-}\mathcal{K}_Q \ r \ C) \ y)) \end{aligned}$$

**proof** –

**have** *preimg-partition-dist*:  $\forall y.$

$$\begin{aligned} & \text{Inf} \ {d \ a \ b \mid b. b \in} \\ & \quad \bigcup (\text{preimg} (\text{elect-r} \circ \text{fun}_{\mathcal{E}} (\text{rule-}\mathcal{K} \ C)) (\text{elections-}\mathcal{K} \ C) \ y \ // \ r) \} = \\ & \text{Inf} (d \ a \ ' \text{preimg} (\text{elect-r} \circ \text{fun}_{\mathcal{E}} (\text{rule-}\mathcal{K} \ C)) (\text{elections-}\mathcal{K} \ C) \ y) \end{aligned}$$

**using** *Setcompr-eq-image preimg-partition*

**by** *metis*

**have**  $\forall y.$

$$\begin{aligned} & \{\text{Inf} \ {d \ a \ b \mid b. b \in B} \\ & \quad \mid B. B \in \text{preimg} (\text{elect-r} \circ \text{fun}_{\mathcal{E}} (\text{rule-}\mathcal{K} \ C)) (\text{elections-}\mathcal{K} \ C) \ y \ // \ r\} \\ & = \{\text{Inf} \ E \mid E. E \in \{\{d \ a \ b \mid b. b \in B\} \\ & \quad \mid B. B \in \text{preimg} (\text{elect-r} \circ \text{fun}_{\mathcal{E}} (\text{rule-}\mathcal{K} \ C)) (\text{elections-}\mathcal{K} \ C) \ y \ // \ r\}\} \end{aligned}$$

**by** *blast*

**hence**  $\forall y.$

$$\begin{aligned} & \text{Inf} \ {\text{Inf} \ {d \ a \ b \mid b. b \in B} \mid B.} \\ & \quad B \in \text{preimg} (\text{elect-r} \circ \text{fun}_{\mathcal{E}} (\text{rule-}\mathcal{K} \ C)) (\text{elections-}\mathcal{K} \ C) \ y \ // \ r\} = \\ & \text{Inf} (\bigcup \ {\{d \ a \ b \mid b. b \in B\} \mid B.} \\ & \quad B \in (\text{preimg} (\text{elect-r} \circ \text{fun}_{\mathcal{E}} (\text{rule-}\mathcal{K} \ C)) (\text{elections-}\mathcal{K} \ C) \ y \ // \ r)\}) \end{aligned}$$

**using** *union-inf*

**by** *presburger*

**moreover have**

$\forall y.$

$$\begin{aligned} & \{d \ a \ b \mid b. b \in \bigcup \\ & \quad (\text{preimg} (\text{elect-r} \circ \text{fun}_{\mathcal{E}} (\text{rule-}\mathcal{K} \ C)) \\ & \quad \quad (\text{elections-}\mathcal{K} \ C) \ y \ // \ r)\} = \\ & \bigcup \ {\{d \ a \ b \mid b. b \in B\} \mid B.} \\ & \quad B \in (\text{preimg} (\text{elect-r} \circ \text{fun}_{\mathcal{E}} (\text{rule-}\mathcal{K} \ C)) \\ & \quad \quad (\text{elections-}\mathcal{K} \ C) \ y \ // \ r)\} \end{aligned}$$

**by** *blast*

**ultimately have** *rewrite-inf-dist*:

$$\forall y. \text{Inf} \ {\text{Inf} \ {d \ a \ b \mid b. b \in B}}$$

```

    | B. B ∈ preimg
      (elect-r ∘ funℰ (rule-ℳ C)) (elections-ℳ C) y // r} =
  Inf {d a b
    | b. b ∈ ⋃ (preimg
      (elect-r ∘ funℰ (rule-ℳ C)) (elections-ℳ C) y // r)}
  by presburger
have ∀ y. distance-infimumQ d A ‘ preimg (πQ (elect-r ∘ funℰ (rule-ℳ C)))
      (elections-ℳQ r C) y =
  {Inf {d a b | b. b ∈ B}
    | B. B ∈ preimg (πQ (elect-r ∘ funℰ (rule-ℳ C))) (elections-ℳQ r C) y}
  using inf-dist-preimg-sets
  unfolding Image-def
  by auto
moreover have ∀ y.
  {Inf {d a b | b. b ∈ B} | B.
    B ∈ preimg (πQ (elect-r ∘ funℰ (rule-ℳ C))) (elections-ℳQ r C) y} =
  {Inf {d a b | b. b ∈ B} | B.
    B ∈ (preimg (elect-r ∘ funℰ (rule-ℳ C)) (elections-ℳ C) y) // r}
  unfolding elections-ℳQ.simps
  using preimg-invar closed-domain cons-subset equiv-rel invar-C
  by blast
ultimately have
  ∀ y. Inf (distance-infimumQ d A ‘ preimg (πQ (elect-r ∘ funℰ (rule-ℳ C)))
      (elections-ℳQ r C) y) =
  Inf {Inf {d a b | b. b ∈ B}
    | B. B ∈ preimg (elect-r ∘ funℰ (rule-ℳ C)) (elections-ℳ C) y // r}
  by simp
thus ?thesis
  using wf-res-eq rewrite-inf-dist preimg-partition-dist
  by presburger
qed
from a-in-A
have πQ (funℰ (ℳW d C)) A = funℰ (ℳW d C) a
  using invar-dr equiv-rel quot-class pass-to-quotient invariance-is-congruence
  by blast
moreover have ∀ x. x ∈ funℰ (ℳW d C) a ⟷ x ∈ ℳQ r d C A
proof
  fix x :: 'r
  have x ∈ funℰ (ℳW d C) a =
    (x ∈ ⋃ (minimizer (elect-r ∘ funℰ (rule-ℳ C)) (elections-ℳ C) d
      (singleton-set-system (limit (alternatives-ℰ a) UNIV)) a))
    using ℳW-is-minimizer
    by metis
  also have ... =
    ({x} ∈ minimizer (elect-r ∘ funℰ (rule-ℳ C)) (elections-ℳ C) d
      (singleton-set-system (limit (alternatives-ℰ a) UNIV)) a)
    using singleton-set-union
    unfolding minimizer.simps arg-min-set.simps is-arg-min-def
    by auto

```

**also have** ... =  $(\{x\} \in \text{singleton-set-system } (\text{limit } (\text{alternatives-}\mathcal{E} \ a) \ UNIV)$   
 $\wedge (\forall \ y \in \text{singleton-set-system } (\text{limit } (\text{alternatives-}\mathcal{E} \ a) \ UNIV).$   
 $\text{Inf } (d \ a \ ' \text{preimg } (\text{elect-r} \circ \text{fun}_{\mathcal{E}} \ (\text{rule-}\mathcal{K} \ C)) \ (\text{elections-}\mathcal{K} \ C) \ \{x\}))$   
 $\leq \text{Inf } (d \ a \ ' \text{preimg } (\text{elect-r} \circ \text{fun}_{\mathcal{E}} \ (\text{rule-}\mathcal{K} \ C)) \ (\text{elections-}\mathcal{K} \ C) \ y)))$   
**using** *minimizer-helper*  
**by** *(metis (no-types, lifting))*  
**also have** ... =  $(\{x\} \in \text{singleton-set-system } (\text{limit}_{\mathcal{Q}} \ A \ UNIV)$   
 $\wedge (\forall \ y \in \text{singleton-set-system } (\text{limit}_{\mathcal{Q}} \ A \ UNIV).$   
 $\text{Inf } (\text{distance-infimum}_{\mathcal{Q}} \ d \ A \ ' \text{preimg } (\pi_{\mathcal{Q}} \ (\text{elect-r} \circ \text{fun}_{\mathcal{E}} \ (\text{rule-}\mathcal{K} \ C)))$   
 $(\text{elections-}\mathcal{K}_{\mathcal{Q}} \ r \ C) \ \{x\}))$   
 $\leq \text{Inf } (\text{distance-infimum}_{\mathcal{Q}} \ d \ A \ ' \text{preimg } (\pi_{\mathcal{Q}} \ (\text{elect-r} \circ \text{fun}_{\mathcal{E}} \ (\text{rule-}\mathcal{K} \ C)))$   
 $(\text{elections-}\mathcal{K}_{\mathcal{Q}} \ r \ C) \ y)))$   
**using** *wf-res-eq inf-le-iff*  
**by** *blast*  
**also have** ... =  
 $(\{x\} \in \text{minimizer}$   
 $(\pi_{\mathcal{Q}} \ (\text{elect-r} \circ \text{fun}_{\mathcal{E}} \ (\text{rule-}\mathcal{K} \ C))) \ (\text{elections-}\mathcal{K}_{\mathcal{Q}} \ r \ C)$   
 $(\text{distance-infimum}_{\mathcal{Q}} \ d)$   
 $(\text{singleton-set-system } (\text{limit}_{\mathcal{Q}} \ A \ UNIV)) \ A)$   
**using** *minimizer-helper*  
**by** *(metis (no-types, lifting))*  
**also have** ... =  
 $(x \in \bigcup \ (\text{minimizer}$   
 $(\pi_{\mathcal{Q}} \ (\text{elect-r} \circ \text{fun}_{\mathcal{E}} \ (\text{rule-}\mathcal{K} \ C))) \ (\text{elections-}\mathcal{K}_{\mathcal{Q}} \ r \ C)$   
 $(\text{distance-infimum}_{\mathcal{Q}} \ d)$   
 $(\text{singleton-set-system } (\text{limit}_{\mathcal{Q}} \ A \ UNIV)) \ A))$   
**using** *singleton-set-union*  
**unfolding** *minimizer.simps arg-min-set.simps is-arg-min-def*  
**by** *auto*  
**finally show**  $x \in \text{fun}_{\mathcal{E}} \ (\mathcal{R}_{\mathcal{W}} \ d \ C) \ a = (x \in \mathcal{R}_{\mathcal{Q}} \ r \ d \ C \ A)$   
**unfolding**  *$\mathcal{R}_{\mathcal{Q}}$ .simps*  
**by** *safe*  
**qed**  
**ultimately show**  $\pi_{\mathcal{Q}} \ (\text{fun}_{\mathcal{E}} \ (\mathcal{R}_{\mathcal{W}} \ d \ C)) \ A = \mathcal{R}_{\mathcal{Q}} \ r \ d \ C \ A$   
**by** *blast*  
**qed**

**theorem** (*in result*) *invar-dr-simple-dist-imp-quotient-dr:*

**fixes**

$d :: ('a, 'v) \text{ Election Distance}$  **and**  
 $C :: ('a, 'v, 'r \text{ Result}) \text{ Consensus-Class}$  **and**  
 $r :: ('a, 'v) \text{ Election rel}$  **and**  
 $X \ A :: ('a, 'v) \text{ Election set}$

**assumes**

*simple: simple*  $r \ X \ d$  **and**  
*closed-domain: closed-restricted-rel*  $r \ X \ (\text{elections-}\mathcal{K} \ C)$  **and**  
*invar-res:*  
*is-symmetry*  $(\lambda \ E. \text{limit } (\text{alternatives-}\mathcal{E} \ E) \ UNIV) \ (\text{Invariance } r)$  **and**  
*invar-C: is-symmetry*  $(\text{elect-r} \circ \text{fun}_{\mathcal{E}} \ (\text{rule-}\mathcal{K} \ C))$



(Invariance (Restr  $r$  (elections- $\mathcal{K}$   $C$ ))) and  
 invar-dr: is-symmetry ( $\text{fun}_{\mathcal{E}}$  ( $\mathcal{R}_{\mathcal{W}}$   $d$   $C$ )) (Invariance  $r$ ) and  
 quot-class:  $A \in X // r$  and  
 equiv-rel: equiv  $X$   $r$  and  
 cons-subset: elections- $\mathcal{K}$   $C \subseteq X$   
 shows  $\pi_{\mathcal{Q}}$  ( $\text{fun}_{\mathcal{E}}$  ( $\text{distance-}\mathcal{R}$   $d$   $C$ ))  $A = \text{distance-}\mathcal{R}_{\mathcal{Q}}$   $r$   $d$   $C$   $A$   
**proof** –  
 have  $\forall E. \text{fun}_{\mathcal{E}}$  ( $\text{distance-}\mathcal{R}$   $d$   $C$ )  $E =$   
     ( $\text{fun}_{\mathcal{E}}$  ( $\mathcal{R}_{\mathcal{W}}$   $d$   $C$ )  $E$ ,  
     limit (alternatives- $\mathcal{E}$   $E$ ) UNIV –  $\text{fun}_{\mathcal{E}}$  ( $\mathcal{R}_{\mathcal{W}}$   $d$   $C$ )  $E$ ,  
     { })  
 by simp  
 moreover have  $\forall E \in A. \text{fun}_{\mathcal{E}}$  ( $\mathcal{R}_{\mathcal{W}}$   $d$   $C$ )  $E = \pi_{\mathcal{Q}}$  ( $\text{fun}_{\mathcal{E}}$  ( $\mathcal{R}_{\mathcal{W}}$   $d$   $C$ ))  $A$   
 using invar-dr invariance-is-congruence pass-to-quotient quot-class equiv-rel  
 by blast  
 moreover have  $\pi_{\mathcal{Q}}$  ( $\text{fun}_{\mathcal{E}}$  ( $\mathcal{R}_{\mathcal{W}}$   $d$   $C$ ))  $A = \mathcal{R}_{\mathcal{Q}}$   $r$   $d$   $C$   $A$   
 using invar-dr-simple-dist-imp-quotient-dr-winners assms  
 by blast  
 moreover have  
      $\forall E \in A. \text{limit}$  (alternatives- $\mathcal{E}$   $E$ ) UNIV =  
      $\pi_{\mathcal{Q}}$  ( $\lambda E. \text{limit}$  (alternatives- $\mathcal{E}$   $E$ ) UNIV)  $A$   
 using invar-res invariance-is-congruence' pass-to-quotient quot-class equiv-rel  
 by blast  
 ultimately have all-eq:  
      $\forall E \in A. \text{fun}_{\mathcal{E}}$  ( $\text{distance-}\mathcal{R}$   $d$   $C$ )  $E =$   
     ( $\mathcal{R}_{\mathcal{Q}}$   $r$   $d$   $C$   $A$ ,  
      $\pi_{\mathcal{Q}}$  ( $\lambda E. \text{limit}$  (alternatives- $\mathcal{E}$   $E$ ) UNIV)  $A - \mathcal{R}_{\mathcal{Q}}$   $r$   $d$   $C$   $A$ ,  
     { })  
 by fastforce  
 hence  
      $\text{fun}_{\mathcal{E}}$  ( $\text{distance-}\mathcal{R}$   $d$   $C$ ) ‘  $A \subseteq$   
     { ( $\mathcal{R}_{\mathcal{Q}}$   $r$   $d$   $C$   $A$ ,  
      $\pi_{\mathcal{Q}}$  ( $\lambda E. \text{limit}$  (alternatives- $\mathcal{E}$   $E$ ) UNIV)  $A - \mathcal{R}_{\mathcal{Q}}$   $r$   $d$   $C$   $A$ ,  
     { }) }  
 by blast  
 moreover have  $A \neq \{ \}$   
 using quot-class equiv-rel in-quotient-imp-non-empty  
 by metis  
 ultimately have single-img:  
     { ( $\mathcal{R}_{\mathcal{Q}}$   $r$   $d$   $C$   $A$ ,  
      $\pi_{\mathcal{Q}}$  ( $\lambda E. \text{limit}$  (alternatives- $\mathcal{E}$   $E$ ) UNIV)  $A - \mathcal{R}_{\mathcal{Q}}$   $r$   $d$   $C$   $A$ ,  
     { }) } =  
      $\text{fun}_{\mathcal{E}}$  ( $\text{distance-}\mathcal{R}$   $d$   $C$ ) ‘  $A$   
 using empty-is-image subset-singletonD  
 by (metis (no-types, lifting))  
 hence card ( $\text{fun}_{\mathcal{E}}$  ( $\text{distance-}\mathcal{R}$   $d$   $C$ ) ‘  $A$ ) = 1  
 using is-singleton-altdef is-singletonI  
 by (metis (no-types, lifting))  
 moreover from this

```

have the-inv ( $\lambda x. \{x\}$ ) (fun $\mathcal{E}$  (distance- $\mathcal{R}$  d C) ‘A) =
  (RQ r d C A,
     $\pi_Q$  ( $\lambda E. \text{limit } (\text{alternatives-}\mathcal{E} \ E) \ \text{UNIV}$ ) A – RQ r d C A,
    {} )
using single-img singleton-insert-inj-eq singleton-set.elims
      singleton-set-def-if-card-one
by (metis (no-types))
ultimately show ?thesis
  unfolding distance- $\mathcal{R}_Q$ .simps  $\pi_Q$ .simps singleton-set.simps
  by presburger
qed

end

```

## 5.8 Code Generation Interpretations for Results and Properties

```

theory Interpretation-Code
  imports Electoral-Module
          Distance-Rationalization
begin
setup Locale-Code.open-block

```

### 5.8.1 Code Lemmas

Lemmas stating the explicit instantiations of interpreted abstract functions from locales.

```

lemma electoral-module-SCF-code-lemma:
  fixes m :: ('a, 'v, 'a Result) Electoral-Module
  shows SCF-result.electoral-module m =
    ( $\forall A \ V \ p. \text{profile } V \ A \ p \longrightarrow \text{well-formed-SCF } A \ (m \ V \ A \ p)$ )
  unfolding SCF-result.electoral-module.simps
  by safe

```

```

lemma RW-SCF-code-lemma:
  fixes
    d :: ('a, 'v) Election Distance and
    K :: ('a, 'v, 'a Result) Consensus-Class and
    V :: 'v set and
    A :: 'a set and
    p :: ('a, 'v) Profile
  shows SCF-result.RW d K V A p =
    arg-min-set (score d K (A, V, p)) (limit-SCF A UNIV)
  unfolding SCF-result.RW.simps
  by safe

```

**lemma** *distance- $\mathcal{R}$ -SCF-code-lemma*:  
**fixes**  
 $d :: ('a, 'v)$  *Election Distance* **and**  
 $K :: ('a, 'v, 'a \text{ Result})$  *Consensus-Class* **and**  
 $V :: 'v \text{ set}$  **and**  
 $A :: 'a \text{ set}$  **and**  
 $p :: ('a, 'v)$  *Profile*  
**shows**  $\text{SCF-result.distance-}\mathcal{R} \ d \ K \ V \ A \ p =$   
 $(\text{SCF-result.}\mathcal{R}_{\mathcal{W}} \ d \ K \ V \ A \ p,$   
 $(\text{limit-SCF } A \ \text{UNIV}) - \text{SCF-result.}\mathcal{R}_{\mathcal{W}} \ d \ K \ V \ A \ p,$   
 $\{\})$   
**unfolding**  $\text{SCF-result.distance-}\mathcal{R}.\text{simps}$   
**by** *safe*

**lemma**  *$\mathcal{R}_{\mathcal{W}}$ -std-SCF-code-lemma*:  
**fixes**  
 $d :: ('a, 'v)$  *Election Distance* **and**  
 $K :: ('a, 'v, 'a \text{ Result})$  *Consensus-Class* **and**  
 $V :: 'v \text{ set}$  **and**  
 $A :: 'a \text{ set}$  **and**  
 $p :: ('a, 'v)$  *Profile*  
**shows**  $\text{SCF-result.}\mathcal{R}_{\mathcal{W}}\text{-std} \ d \ K \ V \ A \ p =$   
 $\text{arg-min-set } (\text{score-std} \ d \ K \ (A, \ V, \ p)) \ (\text{limit-SCF } A \ \text{UNIV})$   
**unfolding**  $\text{SCF-result.}\mathcal{R}_{\mathcal{W}}\text{-std.simps}$   
**by** *safe*

**lemma** *distance- $\mathcal{R}$ -std-SCF-code-lemma*:  
**fixes**  
 $d :: ('a, 'v)$  *Election Distance* **and**  
 $K :: ('a, 'v, 'a \text{ Result})$  *Consensus-Class* **and**  
 $V :: 'v \text{ set}$  **and**  
 $A :: 'a \text{ set}$  **and**  
 $p :: ('a, 'v)$  *Profile*  
**shows**  $\text{SCF-result.distance-}\mathcal{R}\text{-std} \ d \ K \ V \ A \ p =$   
 $(\text{SCF-result.}\mathcal{R}_{\mathcal{W}}\text{-std} \ d \ K \ V \ A \ p,$   
 $(\text{limit-SCF } A \ \text{UNIV}) - \text{SCF-result.}\mathcal{R}_{\mathcal{W}}\text{-std} \ d \ K \ V \ A \ p,$   
 $\{\})$   
**unfolding**  $\text{SCF-result.distance-}\mathcal{R}\text{-std.simps}$   
**by** *safe*

**lemma** *anonymity-SCF-code-lemma*:  $\text{SCF-result.anonymity} =$   
 $(\lambda \ m :: ('a, 'v, 'a \text{ Result}) \ \text{Electoral-Module}.$   
 $\text{SCF-result.electoral-module } m \wedge$   
 $(\forall \ A \ V \ p \ \pi :: ('v \Rightarrow 'v).$   
 $\text{bij } \pi \longrightarrow (\text{let } (A', V', q) = (\text{rename } \pi \ (A, V, p)) \text{ in}$   
 $\text{profile } V \ A \ p \wedge \text{profile } V' \ A' \ q \longrightarrow m \ V \ A \ p = m \ V' \ A' \ q)))$   
**unfolding**  $\text{SCF-result.anonymity-def}$   
**by** *simp*

## 5.8.2 Interpretation Declarations and Constants

Declarations for replacing interpreted abstract functions from locales by their explicit instantiations.

```
declare [[lc-add SCF-result.electoral-module electoral-module-SCF-code-lemma]]
declare [[lc-add SCF-result.RW RW-SCF-code-lemma]]
declare [[lc-add SCF-result.RW-std RW-std-SCF-code-lemma]]
declare [[lc-add SCF-result.distance-R distance-R-SCF-code-lemma]]
declare [[lc-add SCF-result.distance-R-std distance-R-std-SCF-code-lemma]]
declare [[lc-add SCF-result.anonymity anonymity-SCF-code-lemma]]
```

Constant aliases to use instead of the interpreted functions.

```
definition RW-SCF-code  $\equiv$  SCF-result.RW
definition RW-std-SCF-code  $\equiv$  SCF-result.RW-std
definition distance-R-SCF-code  $\equiv$  SCF-result.distance-R
definition distance-R-std-SCF-code  $\equiv$  SCF-result.distance-R-std
definition electoral-module-SCF-code  $\equiv$  SCF-result.electoral-module
definition anonymity-SCF-code  $\equiv$  SCF-result.anonymity
```

```
setup Locale-Code.close-block
```

```
end
```

## 5.9 Drop Module

```
theory Drop-Module
  imports Component-Types/Electoral-Module
           Component-Types/Social-Choice-Types/Result
begin
```

This is a family of electoral modules. For a natural number  $n$  and a lexicon (linear order)  $r$  of all alternatives, the according drop module rejects the lexicographically first  $n$  alternatives (from  $A$ ) and defers the rest. It is primarily used as counterpart to the pass module in a parallel composition, in order to segment the alternatives into two groups.

### 5.9.1 Definition

```
fun drop-module :: nat  $\Rightarrow$  'a Preference-Relation  $\Rightarrow$ 
    ('a, 'v, 'a Result) Electoral-Module where
  drop-module n r V A p =
    ({},
     {a  $\in$  A. rank (limit A r) a  $\leq$  n},
     {a  $\in$  A. rank (limit A r) a  $>$  n})
```

### 5.9.2 Soundness

**theorem** *drop-mod-sound*[simp]:

**fixes**

$r :: 'a$  *Preference-Relation* **and**

$n :: \text{nat}$

**shows** *SCF-result.electoral-module* (*drop-module*  $n$   $r$ )

**proof** (*unfold SCF-result.electoral-module.simps, safe*)

**fix**

$A :: 'a$  *set* **and**

$V :: 'v$  *set* **and**

$p :: ('a, 'v)$  *Profile*

**assume** *profile*  $V$   $A$   $p$

**let**  $?mod = \text{drop-module } n \ r$

**have**  $\forall a \in A. a \in \{x \in A. \text{rank } (\text{limit } A \ r) \ x \leq n\} \vee$   
 $a \in \{x \in A. \text{rank } (\text{limit } A \ r) \ x > n\}$

**by** *auto*

**hence**  $\{a \in A. \text{rank } (\text{limit } A \ r) \ a \leq n\} \cup \{a \in A. \text{rank } (\text{limit } A \ r) \ a > n\} = A$

**by** *blast*

**hence** *set-partition: set-equals-partition*  $A$  (*drop-module*  $n$   $r$   $V$   $A$   $p$ )

**by** *simp*

**have**  $\forall a \in A.$

$\neg (a \in \{x \in A. \text{rank } (\text{limit } A \ r) \ x \leq n\} \wedge$   
 $a \in \{x \in A. \text{rank } (\text{limit } A \ r) \ x > n\})$

**by** *simp*

**hence**  $\{a \in A. \text{rank } (\text{limit } A \ r) \ a \leq n\} \cap \{a \in A. \text{rank } (\text{limit } A \ r) \ a > n\} = \{\}$

**by** *blast*

**thus** *well-formed-SCF*  $A$  ( $?mod$   $V$   $A$   $p$ )

**using** *set-partition*

**by** *simp*

**qed**

**lemma** *voters-determine-drop-mod*:

**fixes**

$r :: 'a$  *Preference-Relation* **and**

$n :: \text{nat}$

**shows** *voters-determine-election* (*drop-module*  $n$   $r$ )

**unfolding** *voters-determine-election.simps*

**by** *simp*

### 5.9.3 Non-Electing

The drop module is non-electing.

**theorem** *drop-mod-non-electing*[simp]:

**fixes**

$r :: 'a$  *Preference-Relation* **and**

$n :: \text{nat}$

**shows** *non-electing* (*drop-module*  $n$   $r$ )

**unfolding** *non-electing-def*

by *auto*

#### 5.9.4 Properties

The drop module is strictly defer-monotone.

```
theorem drop-mod-def-lift-inv[simp]:
  fixes
    r :: 'a Preference-Relation and
    n :: nat
  shows defer-lift-invariance (drop-module n r)
  unfolding defer-lift-invariance-def
  by force

end
```

### 5.10 Pass Module

```
theory Pass-Module
  imports Component-Types/Electoral-Module
begin
```

This is a family of electoral modules. For a natural number  $n$  and a lexicon (linear order)  $r$  of all alternatives, the according pass module defers the lexicographically first  $n$  alternatives (from  $A$ ) and rejects the rest. It is primarily used as counterpart to the drop module in a parallel composition in order to segment the alternatives into two groups.

#### 5.10.1 Definition

```
fun pass-module :: nat  $\Rightarrow$  'a Preference-Relation  $\Rightarrow$ 
  ('a, 'v, 'a Result) Electoral-Module where
  pass-module n r V A p =
    ({},
     {a  $\in$  A. rank (limit A r) a > n},
     {a  $\in$  A. rank (limit A r) a  $\leq$  n})
```

#### 5.10.2 Soundness

```
theorem pass-mod-sound[simp]:
  fixes
    r :: 'a Preference-Relation and
    n :: nat
  shows SCF-result.electoral-module (pass-module n r)
proof (unfold SCF-result.electoral-module.simps, safe)
```

```

fix
   $A :: 'a \text{ set}$  and
   $V :: 'v \text{ set}$  and
   $p :: ('a, 'v) \text{ Profile}$ 
let  $?mod = \text{pass-module } n \ r$ 
have  $\forall a \in A. a \in \{x \in A. \text{rank } (\text{limit } A \ r) \ x > n\} \vee$ 
    $a \in \{x \in A. \text{rank } (\text{limit } A \ r) \ x \leq n\}$ 
  using  $\text{CollectI not-less}$ 
  by  $\text{metis}$ 
hence  $\{a \in A. \text{rank } (\text{limit } A \ r) \ a > n\} \cup \{a \in A. \text{rank } (\text{limit } A \ r) \ a \leq n\} = A$ 
  by  $\text{blast}$ 
hence  $\text{set-equals-partition } A \ (\text{pass-module } n \ r \ V \ A \ p)$ 
  by  $\text{simp}$ 
moreover have
   $\forall a \in A.$ 
    $\neg (a \in \{x \in A. \text{rank } (\text{limit } A \ r) \ x > n\} \wedge$ 
     $a \in \{x \in A. \text{rank } (\text{limit } A \ r) \ x \leq n\})$ 
  by  $\text{simp}$ 
hence  $\{a \in A. \text{rank } (\text{limit } A \ r) \ a > n\} \cap \{a \in A. \text{rank } (\text{limit } A \ r) \ a \leq n\} = \{\}$ 
  by  $\text{blast}$ 
ultimately show  $\text{well-formed-SCF } A \ (?mod \ V \ A \ p)$ 
  by  $\text{simp}$ 
qed

```

```

lemma  $\text{voters-determine-pass-mod:}$ 
  fixes
     $r :: 'a \text{ Preference-Relation}$  and
     $n :: \text{nat}$ 
  shows  $\text{voters-determine-election } (\text{pass-module } n \ r)$ 
  unfolding  $\text{voters-determine-election.simps pass-module.simps}$ 
  by  $\text{blast}$ 

```

### 5.10.3 Non-Blocking

The pass module is non-blocking.

```

theorem  $\text{pass-mod-non-blocking[simp]:}$ 
  fixes
     $r :: 'a \text{ Preference-Relation}$  and
     $n :: \text{nat}$ 
  assumes
     $\text{order: linear-order } r$  and
     $\text{greater-zero: } n > 0$ 
  shows  $\text{non-blocking } (\text{pass-module } n \ r)$ 
proof  $(\text{unfold non-blocking-def, safe})$ 
  show  $\text{SCF-result.electoral-module } (\text{pass-module } n \ r)$ 
  using  $\text{pass-mod-sound}$ 
  by  $\text{metis}$ 
next
  fix

```

```

  A :: 'a set and
  V :: 'v set and
  p :: ('a, 'v) Profile and
  a :: 'a
assume
  fin-A: finite A and
  rej-pass-A: reject (pass-module n r) V A p = A and
  a-in-A: a ∈ A
moreover have lin: linear-order-on A (limit A r)
  using limit-presv-lin-ord order top-greatest
  by metis
moreover have
  ∃ b ∈ A. above (limit A r) b = {b}
  ∧ (∀ c ∈ A. above (limit A r) c = {c} ⟶ c = b)
  using fin-A a-in-A lin above-one
  by blast
moreover have {b ∈ A. rank (limit A r) b > n} ≠ A
  using Suc-leI greater-zero leD mem-Collect-eq above-rank calculation
  unfolding One-nat-def
  by (metis (no-types, lifting))
hence reject (pass-module n r) V A p ≠ A
  by simp
thus a ∈ {}
  using rej-pass-A
  by simp
qed

```

#### 5.10.4 Non-Electing

The pass module is non-electing.

```

theorem pass-mod-non-electing[simp]:
  fixes
    r :: 'a Preference-Relation and
    n :: nat
  assumes linear-order r
  shows non-electing (pass-module n r)
  unfolding non-electing-def
  using assms
  by force

```

#### 5.10.5 Properties

The pass module is strictly defer-monotone.

```

theorem pass-mod-dl-inv[simp]:
  fixes
    r :: 'a Preference-Relation and
    n :: nat
  assumes linear-order r

```



```

shows defer-lift-invariance (pass-module n r)
unfolding defer-lift-invariance-def
using assms pass-mod-sound
by simp

theorem pass-zero-mod-def-zero[simp]:
  fixes r :: 'a Preference-Relation
  assumes linear-order r
  shows defers 0 (pass-module 0 r)
proof (unfold defers-def, safe)
  show SCF-result.electoral-module (pass-module 0 r)
    using pass-mod-sound assms
    by metis
next
fix
  A :: 'a set and
  V :: 'v set and
  p :: ('a, 'v) Profile
assume
  card-pos: 0 ≤ card A and
  finite-A: finite A and
  prof-A: profile V A p
have linear-order-on A (limit A r)
  using assms limit-presv-lin-ord
  by blast
hence limit-is-connex: connex A (limit A r)
  using lin-ord-imp-connex
  by simp
have ∀ n. (n :: nat) ≤ 0 → n = 0
  by blast
hence ∀ a A'. a ∈ A' ∧ a ∈ A → connex A' (limit A r) →
  ¬ rank (limit A r) a ≤ 0
  using above-connex above-presv-limit card-eq-0-iff equals0D finite-A
  assms rev-finite-subset
  unfolding rank.simps
  by (metis (no-types))
hence {a ∈ A. rank (limit A r) a ≤ 0} = {}
  using limit-is-connex
  by simp
hence card {a ∈ A. rank (limit A r) a ≤ 0} = 0
  using card.empty
  by metis
thus card (defer (pass-module 0 r) V A p) = 0
  by simp
qed

```

For any natural number *n* and any linear order, the according pass module defers *n* alternatives (if there are *n* alternatives). NOTE: The induction proof is still missing. The following are the proofs for *n*=1 and *n*=2.

```

theorem pass-one-mod-def-one[simp]:
  fixes  $r :: 'a \text{ Preference-Relation}$ 
  assumes linear-order  $r$ 
  shows defers 1 (pass-module 1 r)
proof (unfold defers-def, safe)
  show SCF-result.electoral-module (pass-module 1 r)
    using pass-mod-sound assms
    by simp
next
fix
   $A :: 'a \text{ set}$  and
   $V :: 'v \text{ set}$  and
   $p :: ('a, 'v) \text{ Profile}$ 
assume
  card-pos: 1 ≤ card A and
  finite-A: finite A and
  prof-A: profile V A p
show card (defer (pass-module 1 r) V A p) = 1
proof –
  have  $A \neq \{\}$ 
    using card-pos
    by auto
moreover have lin-ord-on-A: linear-order-on A (limit A r)
    using assms limit-presv-lin-ord
    by blast
ultimately have winner-exists:
   $\exists a \in A. \text{above } (\text{limit } A \ r) \ a = \{a\} \wedge$ 
   $(\forall b \in A. \text{above } (\text{limit } A \ r) \ b = \{b\} \longrightarrow b = a)$ 
    using finite-A above-one
    by simp
then obtain  $w :: 'a$  where
  w-unique-top:
   $\text{above } (\text{limit } A \ r) \ w = \{w\} \wedge$ 
   $(\forall a \in A. \text{above } (\text{limit } A \ r) \ a = \{a\} \longrightarrow a = w)$ 
    using above-one
    by auto
hence  $\{a \in A. \text{rank } (\text{limit } A \ r) \ a \leq 1\} = \{w\}$ 
proof
  assume
  w-top: above (limit A r) w = {w} and
  w-unique:  $\forall a \in A. \text{above } (\text{limit } A \ r) \ a = \{a\} \longrightarrow a = w$ 
have rank (limit A r) w ≤ 1
    using w-top
    by auto
hence  $\{w\} \subseteq \{a \in A. \text{rank } (\text{limit } A \ r) \ a \leq 1\}$ 
    using winner-exists w-unique-top
    by blast
moreover have  $\{a \in A. \text{rank } (\text{limit } A \ r) \ a \leq 1\} \subseteq \{w\}$ 
proof

```

```

fix a :: 'a
assume a-in-winner-set: a ∈ {b ∈ A. rank (limit A r) b ≤ 1}
hence a-in-A: a ∈ A
  by auto
hence connex-limit: connex A (limit A r)
  using lin-ord-imp-connex lin-ord-on-A
  by simp
hence let q = limit A r in a ≼q a
  using connex-limit above-connex pref-imp-in-above a-in-A
  by metis
hence (a, a) ∈ limit A r
  by simp
hence a-above-a: a ∈ above (limit A r) a
  unfolding above-def
  by simp
have above (limit A r) a ⊆ A
  using above-presv-limit assms
  by fastforce
hence above-finite: finite (above (limit A r) a)
  using finite-A finite-subset
  by simp
have rank (limit A r) a ≤ 1
  using a-in-winner-set
  by simp
moreover have rank (limit A r) a ≥ 1
  using Suc-leI above-finite card-eq-0-iff equals0D neq0-conv a-above-a
  unfolding rank.simps One-nat-def
  by metis
ultimately have rank (limit A r) a = 1
  by simp
hence {a} = above (limit A r) a
  using a-above-a lin-ord-on-A rank-one-imp-above-one
  by metis
hence a = w
  using w-unique a-in-A
  by simp
thus a ∈ {w}
  by simp
qed
ultimately have {w} = {a ∈ A. rank (limit A r) a ≤ 1}
  by auto
thus ?thesis
  by simp
qed
thus card (defer (pass-module 1 r) V A p) = 1
  by simp
qed
qed

```

```

theorem pass-two-mod-def-two:
  fixes  $r :: 'a \text{ Preference-Relation}$ 
  assumes linear-order  $r$ 
  shows defers 2 (pass-module 2 r)
proof (unfold defers-def, safe)
  show SCF-result.electoral-module (pass-module 2 r)
    using assms pass-mod-sound
    by metis
next
fix
   $A :: 'a \text{ set}$  and
   $V :: 'v \text{ set}$  and
   $p :: ('a, 'v) \text{ Profile}$ 
assume
  min-card-two:  $2 \leq \text{card } A$  and
  fin-A: finite  $A$  and
  prof-A: profile  $V \ A \ p$ 
from min-card-two
have not-empty-A:  $A \neq \{\}$ 
  by auto
moreover have limit-A-order: linear-order-on  $A \ (\text{limit } A \ r)$ 
  using limit-presv-lin-ord assms
  by auto
ultimately obtain  $a :: 'a$  where
  above  $(\text{limit } A \ r) \ a = \{a\}$ 
  using above-one min-card-two fin-A prof-A
  by blast
hence  $\forall b \in A. \text{let } q = \text{limit } A \ r \text{ in } (b \preceq_q a)$ 
  using limit-A-order pref-imp-in-above empty-iff lin-ord-imp-connex
    insert-iff insert-subset above-presv-limit assms
  unfolding connex-def
  by metis
hence a-best:  $\forall b \in A. (b, a) \in \text{limit } A \ r$ 
  by simp
hence a-above:  $\forall b \in A. a \in \text{above } (\text{limit } A \ r) \ b$ 
  unfolding above-def
  by simp
hence  $a \in \{a \in A. \text{rank } (\text{limit } A \ r) \ a \leq 2\}$ 
  using CollectI not-empty-A empty-iff fin-A insert-iff limit-A-order
    above-one above-rank one-le-numeral
  by (metis (no-types, lifting))
hence a-in-defer:  $a \in \text{defer } (\text{pass-module } 2 \ r) \ V \ A \ p$ 
  by simp
have finite  $(A - \{a\})$ 
  using fin-A
  by simp
moreover have A-not-only-a:  $A - \{a\} \neq \{\}$ 
  using Diff-empty Diff-idemp Diff-insert0 not-empty-A insert-Diff finite.emptyI
    card.insert-remove card.empty min-card-two Suc-n-not-le-n numeral-2-eq-2

```

by *metis*  
**moreover have** *limit-A-without-a-order*:  
   *linear-order-on*  $(A - \{a\})$   $(\text{limit } (A - \{a\}) \ r)$   
   **using** *limit-presv-lin-ord* *assms* *top-greatest*  
   by *blast*  
**ultimately obtain**  $b :: 'a$  **where**  
   *top-b*: *above*  $(\text{limit } (A - \{a\}) \ r)$   $b = \{b\}$   
   **using** *above-one*  
   by *metis*  
**hence**  $\forall \ c \in A - \{a\}. \text{let } q = \text{limit } (A - \{a\}) \ r \text{ in } (c \preceq_q b)$   
   **using** *limit-A-without-a-order* *pref-imp-in-above* *empty-iff* *lin-ord-imp-connex*  
     *insert-iff* *insert-subset* *above-presv-limit* *assms*  
   **unfolding** *connex-def*  
   by *metis*  
**hence** *b-in-limit*:  $\forall \ c \in A - \{a\}. (c, b) \in \text{limit } (A - \{a\}) \ r$   
   by *simp*  
**hence** *b-best*:  $\forall \ c \in A - \{a\}. (c, b) \in \text{limit } A \ r$   
   by *auto*  
**hence**  $\forall \ c \in A - \{a, b\}. c \notin \text{above } (\text{limit } A \ r) \ b$   
   **using** *top-b* *Diff-iff* *Diff-insert2* *above-presv-limit* *insert-subset*  
     *assms* *limit-presv-above* *limit-rel-presv-above*  
   by *metis*  
**moreover have** *above-subset*:  $\text{above } (\text{limit } A \ r) \ b \subseteq A$   
   **using** *above-presv-limit* *assms*  
   by *metis*  
**moreover have** *b-above-b*:  $b \in \text{above } (\text{limit } A \ r) \ b$   
   **using** *top-b* *b-best* *above-presv-limit* *mem-Collect-eq* *assms* *insert-subset*  
   **unfolding** *above-def*  
   by *metis*  
**ultimately have** *above-b-eq-ab*:  $\text{above } (\text{limit } A \ r) \ b = \{a, b\}$   
   **using** *a-above*  
   by *auto*  
**hence** *card-above-b-eq-two*:  $\text{rank } (\text{limit } A \ r) \ b = 2$   
   **using** *A-not-only-a* *b-in-limit*  
   by *auto*  
**hence** *b-in-defer*:  $b \in \text{defer } (\text{pass-module } 2 \ r) \ V \ A \ p$   
   **using** *b-above-b* *above-subset*  
   by *auto*  
**have** *b-above*:  $\forall \ c \in A - \{a\}. b \in \text{above } (\text{limit } A \ r) \ c$   
   **using** *b-best* *mem-Collect-eq*  
   **unfolding** *above-def*  
   by *metis*  
**have** *connex A*  $(\text{limit } A \ r)$   
   **using** *limit-A-order* *lin-ord-imp-connex*  
   by *auto*  
**hence**  $\forall \ c \in A. c \in \text{above } (\text{limit } A \ r) \ c$   
   **using** *above-connex*  
   by *metis*  
**hence**  $\forall \ c \in A - \{a, b\}. \{a, b, c\} \subseteq \text{above } (\text{limit } A \ r) \ c$

```

    using a-above b-above
    by auto
  moreover have  $\forall c \in A - \{a, b\}. \text{card } \{a, b, c\} = 3$ 
    using DiffE Suc-1 above-b-eq-ab card-above-b-eq-two above-subset fin-A
      card-insert-disjoint finite-subset insert-commute numeral-3-eq-3
    unfolding One-nat-def rank.simps
    by metis
  ultimately have  $\forall c \in A - \{a, b\}. \text{rank } (\text{limit } A \ r) \ c \geq 3$ 
    using card-mono fin-A finite-subset above-presv-limit assms
    unfolding rank.simps
    by metis
  hence  $\forall c \in A - \{a, b\}. \text{rank } (\text{limit } A \ r) \ c > 2$ 
    using Suc-le-eq Suc-1 numeral-3-eq-3
    unfolding One-nat-def
    by metis
  hence  $\forall c \in A - \{a, b\}. c \notin \text{defer } (\text{pass-module } 2 \ r) \ V \ A \ p$ 
    by (simp add: not-le)
  moreover have  $\text{defer } (\text{pass-module } 2 \ r) \ V \ A \ p \subseteq A$ 
    by auto
  ultimately have  $\text{defer } (\text{pass-module } 2 \ r) \ V \ A \ p \subseteq \{a, b\}$ 
    by blast
  hence  $\text{defer } (\text{pass-module } 2 \ r) \ V \ A \ p = \{a, b\}$ 
    using a-in-defer b-in-defer
    by fastforce
  thus  $\text{card } (\text{defer } (\text{pass-module } 2 \ r) \ V \ A \ p) = 2$ 
    using above-b-eq-ab card-above-b-eq-two
    unfolding rank.simps
    by presburger
qed
end

```

## 5.11 Elect Module

```

theory Elect-Module
  imports Component-Types/Electoral-Module
begin

```

The elect module is not concerned about the voter's ballots, and just elects all alternatives. It is primarily used in sequence after an electoral module that only defers alternatives to finalize the decision, thereby inducing a proper voting rule in the social choice sense.

### 5.11.1 Definition

**fun** *elect-module* :: ('a, 'v, 'a Result) *Electoral-Module* **where**  
*elect-module* *V A p* = (*A*, {}, {})

### 5.11.2 Soundness

**theorem** *elect-mod-sound[simp]*: *SCF-result.electoral-module elect-module*  
**by** *simp*

**lemma** *elect-mod-only-voters: voters-determine-election elect-module*  
**by** *simp*

### 5.11.3 Electing

**theorem** *elect-mod-electing[simp]*: *electing elect-module*  
**unfolding** *electing-def*  
**by** *simp*

**end**

## 5.12 Plurality Module

**theory** *Plurality-Module*  
**imports** *Component-Types/Elimination-Module*  
**begin**

The plurality module implements the plurality voting rule. The plurality rule elects all modules with the maximum amount of top preferences among all alternatives, and rejects all the other alternatives. It is electing and induces the classical plurality (voting) rule from social-choice theory.

### 5.12.1 Definition

**fun** *plurality-score* :: ('a, 'v) *Evaluation-Function* **where**  
*plurality-score* *V x A p* = *win-count V p x*

**fun** *plurality* :: ('a, 'v, 'a Result) *Electoral-Module* **where**  
*plurality* *V A p* = *max-eliminator plurality-score V A p*

**fun** *plurality'* :: ('a, 'v, 'a Result) *Electoral-Module* **where**  
*plurality'* *V A p* =  
 (if *finite A*  
 then {},  
 {*a* ∈ *A*. ∃ *x* ∈ *A*. *win-count V p x* > *win-count V p a*},

$\{a \in A. \forall x \in A. \text{win-count } V p x \leq \text{win-count } V p a\}$   
 else  $(\{\}, \{\}, A)$ )

**lemma** *enat-leq-enat-set-max*:

**fixes**  
 $x :: \text{enat}$  **and**  
 $X :: \text{enat set}$   
**assumes**  
 $x \in X$  **and**  
*finite*  $X$   
**shows**  $x \leq \text{Max } X$   
**using** *assms*  
**by** *simp*

**lemma** *plurality-mod-equiv*:

**fixes**  
 $A :: 'a \text{ set}$  **and**  
 $V :: 'v \text{ set}$  **and**  
 $p :: ('a, 'v) \text{ Profile}$   
**shows**  $\text{plurality } V A p = \text{plurality}' V A p$   
**proof** (*unfold plurality'.simps*)  
**have** *no-winners-or-in-domain*:  
 $\text{finite } \{\text{win-count } V p a \mid a. a \in A\} \longrightarrow$   
 $\{\text{win-count } V p a \mid a. a \in A\} = \{\} \vee$   
 $\text{Max } \{\text{win-count } V p a \mid a. a \in A\} \in \{\text{win-count } V p a \mid a. a \in A\}$   
**using** *Max-in*  
**by** *blast*  
**moreover have** *only-one-max*:  
 $\text{finite } A \longrightarrow$   
 $\{a \in A. \exists x \in A. \text{win-count } V p a < \text{win-count } V p x\} =$   
 $\{a \in A. \text{win-count } V p a < \text{Max } \{\text{win-count } V p x \mid x. x \in A\}\}$   
**proof**  
**assume** *fin-A*: *finite*  $A$   
**hence** *finite*  $\{\text{win-count } V p x \mid x. x \in A\}$   
**by** *simp*  
**hence**  
 $\forall a \in A. \forall b \in A. \text{win-count } V p a < \text{win-count } V p b \longrightarrow$   
 $\text{win-count } V p a < \text{Max } \{\text{win-count } V p x \mid x. x \in A\}$   
**using** *CollectI Max-gr-iff empty-Collect-eq*  
**by** (*metis (mono-tags, lifting)*)  
**hence**  
 $\{a \in A. \exists x \in A. \text{win-count } V p a < \text{win-count } V p x\}$   
 $\subseteq \{a \in A. \text{win-count } V p a < \text{Max } \{\text{win-count } V p x \mid x. x \in A\}\}$   
**by** *blast*  
**moreover have**  
 $\{a \in A. \text{win-count } V p a < \text{Max } \{\text{win-count } V p x \mid x. x \in A\}\}$   
 $\subseteq \{a \in A. \exists x \in A. \text{win-count } V p a < \text{win-count } V p x\}$   
**using** *fin-A no-winners-or-in-domain*  
**by** *fastforce*



**ultimately show**  
 $\{a \in A. \exists x \in A. \text{win-count } V p a < \text{win-count } V p x\} =$   
 $\{a \in A. \text{win-count } V p a < \text{Max } \{\text{win-count } V p x \mid x. x \in A\}\}$   
**by fastforce**  
**qed**  
**ultimately have**  
 $\text{finite } A \longrightarrow$   
 $\text{reject plurality } V A p = \{a \in A. \exists x \in A. \text{win-count } V p a < \text{win-count } V p$   
 $x\}$   
**by force**  
**moreover have**  
 $\text{finite } A \longrightarrow$   
 $\text{defer plurality } V A p = \{a \in A. \forall b \in A. \text{win-count } V p b \leq \text{win-count } V p$   
 $a\}$   
**proof**  
**assume fin-A:**  $\text{finite } A$   
**have**  $\{a \in A. \exists x \in A. \text{win-count } V p x > \text{win-count } V p a\}$   
 $\cap \{a \in A. \forall x \in A. \text{win-count } V p x \leq \text{win-count } V p a\} = \{\}$   
**by force**  
**moreover have**  
 $\{a \in A. \exists x \in A. \text{win-count } V p x > \text{win-count } V p a\}$   
 $\cup \{a \in A. \forall x \in A. \text{win-count } V p x \leq \text{win-count } V p a\} = A$   
**by force**  
**ultimately have**  
 $\{a \in A. \forall b \in A. \text{win-count } V p b \leq \text{win-count } V p a\} =$   
 $A - \{a \in A. \text{win-count } V p a < \text{Max } \{\text{win-count } V p x \mid x. x \in A\}\}$   
**using** *fin-A only-one-max Diff-cancel Int-Diff-Un Un-Diff inf-commute*  
**by** (*metis (no-types, lifting)*)  
**moreover have**  
 $\{a \in A. \text{win-count } V p a < \text{Max } \{\text{win-count } V p x \mid x. x \in A\}\} = A \longrightarrow$   
 $\{a \in A. \forall b \in A. \text{win-count } V p b \leq \text{win-count } V p a\} = A$   
**using** *fin-A no-winners-or-in-domain*  
**by fastforce**  
**ultimately show**  
 $\text{defer plurality } V A p = \{a \in A. \forall b \in A. \text{win-count } V p b \leq \text{win-count } V p$   
 $a\}$   
**using** *fin-A*  
**by force**  
**qed**  
**moreover have** *elect plurality*  $V A p = \{\}$   
**unfolding** *max-eliminator.simps less-eliminator.simps elimination-module.simps*  
**by force**  
**ultimately have**  
 $\text{finite } A \longrightarrow$   
 $\text{plurality } V A p =$   
 $(\{\}, \{a \in A. \exists x \in A. \text{win-count } V p a < \text{win-count } V p x\},$   
 $\{a \in A. \forall x \in A. \text{win-count } V p x \leq \text{win-count } V p a\})$   
**using** *split-pairs*  
**by** (*metis (no-types, lifting)*)

```

thus plurality  $V A p =$ 
  (if finite  $A$ 
    then ( $\{\}, \{a \in A. \exists x \in A. \text{win-count } V p a < \text{win-count } V p x\},$ 
       $\{a \in A. \forall x \in A. \text{win-count } V p x \leq \text{win-count } V p a\}$ )
    else ( $\{\}, \{\}, A$ ))
  by force
qed

```

### 5.12.2 Soundness

```

theorem plurality-sound[simp]: SCF-result.electoral-module plurality
  unfolding plurality.simps
  using max-elim-sound
  by metis

```

```

theorem plurality'-sound[simp]: SCF-result.electoral-module plurality'

```

```

proof (unfold SCF-result.electoral-module.simps, safe)
  fix
     $A :: 'a \text{ set}$  and
     $V :: 'v \text{ set}$  and
     $p :: ('a, 'v) \text{ Profile}$ 
  have disjoint3 (
     $\{\},$ 
     $\{a \in A. \exists a' \in A. \text{win-count } V p a < \text{win-count } V p a'\},$ 
     $\{a \in A. \forall a' \in A. \text{win-count } V p a' \leq \text{win-count } V p a\}$ )
  by auto
  moreover have
     $\{a \in A. \exists x \in A. \text{win-count } V p a < \text{win-count } V p x\} \cup$ 
     $\{a \in A. \forall x \in A. \text{win-count } V p x \leq \text{win-count } V p a\} = A$ 
  using not-le-imp-less
  by blast
  ultimately show well-formed-SCF  $A (plurality' V A p)$ 
  by simp
qed

```

```

lemma voters-determine-plurality-score: voters-determine-evaluation plurality-score

```

```

proof (unfold plurality-score.simps voters-determine-evaluation.simps, safe)

```

```

  fix
     $A :: 'b \text{ set}$  and
     $V :: 'a \text{ set}$  and
     $p p' :: ('b, 'a) \text{ Profile}$  and
     $a :: 'b$ 

```

```

  assume
     $\forall v \in V. p v = p' v$  and
     $a \in A$ 

```

```

  hence finite  $V \longrightarrow$ 
     $\text{card } \{v \in V. \text{above } (p v) a = \{a\}\} = \text{card } \{v \in V. \text{above } (p' v) a = \{a\}\}$ 
  using Collect-cong
  by (metis (no-types, lifting))

```

```

thus win-count  $V$   $p$   $a$  = win-count  $V$   $p'$   $a$ 
  unfolding win-count.simps
  by presburger
qed

lemma voters-determine-plurality: voters-determine-election plurality
  unfolding plurality.simps
  using voters-determine-max-elim voters-determine-plurality-score
  by blast

lemma voters-determine-plurality': voters-determine-election plurality'
proof (unfold voters-determine-election.simps, safe)
  fix
     $A :: 'k$  set and
     $V :: 'v$  set and
     $p$   $p' :: ('k, 'v)$  Profile
  assume  $\forall v \in V. p\ v = p'\ v$ 
  thus plurality'  $V$   $A$   $p$  = plurality'  $V$   $A$   $p'$ 
    using voters-determine-plurality plurality-mod-equiv
    unfolding voters-determine-election.simps
    by (metis (full-types))
qed

```

### 5.12.3 Non-Blocking

The plurality module is non-blocking.

```

theorem plurality-mod-non-blocking[simp]: non-blocking plurality
  unfolding plurality.simps
  using max-elim-non-blocking
  by metis

theorem plurality'-mod-non-blocking[simp]: non-blocking plurality'
  using plurality-mod-non-blocking plurality-mod-equiv plurality'-sound
  unfolding non-blocking-def
  by metis

```

### 5.12.4 Non-Electing

The plurality module is non-electing.

```

theorem plurality-non-electing[simp]: non-electing plurality
  using max-elim-non-electing
  unfolding plurality.simps non-electing-def
  by metis

theorem plurality'-non-electing[simp]: non-electing plurality'
  unfolding non-electing-def
  using plurality'-sound
  by simp

```

### 5.12.5 Property

**lemma** *plurality-def-inv-mono-alts*:

**fixes**

$A :: 'a \text{ set}$  **and**

$V :: 'v \text{ set}$  **and**

$p \ q :: ('a, 'v) \text{ Profile}$  **and**

$a :: 'a$

**assumes**

*defer-a*:  $a \in \text{defer plurality } V \ A \ p$  **and**

*lift-a*:  $\text{lifted } V \ A \ p \ q \ a$

**shows**  $\text{defer plurality } V \ A \ q = \text{defer plurality } V \ A \ p$   
 $\vee \text{defer plurality } V \ A \ q = \{a\}$

**proof** –

**have** *set-disj*:  $\forall \ b \ c. \ b \notin \{c\} \vee b = c$

**by** *blast*

**have** *lifted-winner*:  $\forall \ b \in A. \forall \ i \in V.$

$\text{above } (p \ i) \ b = \{b\} \longrightarrow (\text{above } (q \ i) \ b = \{b\} \vee \text{above } (q \ i) \ a = \{a\})$

**using** *lift-a lifted-above-winner-alts*

**unfolding** *Profile.lifted-def*

**by** *metis*

**hence**  $\forall \ i \in V. (\text{above } (p \ i) \ a = \{a\} \longrightarrow \text{above } (q \ i) \ a = \{a\})$

**using** *defer-a lift-a*

**unfolding** *Profile.lifted-def*

**by** *metis*

**hence** *a-win-subset*:

$\{i \in V. \text{above } (p \ i) \ a = \{a\}\} \subseteq \{i \in V. \text{above } (q \ i) \ a = \{a\}\}$

**by** *blast*

**moreover have** *lifted-prof*:  $\text{profile } V \ A \ q$

**using** *lift-a*

**unfolding** *Profile.lifted-def*

**by** *metis*

**ultimately have** *win-count-a*:  $\text{win-count } V \ p \ a \leq \text{win-count } V \ q \ a$

**by** (*simp add: card-mono*)

**have** *fin-A*:  $\text{finite } A$

**using** *lift-a*

**unfolding** *Profile.lifted-def*

**by** *blast*

**hence**  $\forall \ b \in A - \{a\}.$

$\forall \ i \in V. (\text{above } (q \ i) \ a = \{a\} \longrightarrow \text{above } (q \ i) \ b \neq \{b\})$

**using** *DiffE above-one lift-a insertCI insert-absorb insert-not-empty*

**unfolding** *Profile.lifted-def profile-def*

**by** *metis*

**with** *lifted-winner*

**have** *above-QtoP*:

$\forall \ b \in A - \{a\}.$

$\forall \ i \in V. (\text{above } (q \ i) \ b = \{b\} \longrightarrow \text{above } (p \ i) \ b = \{b\})$

**using** *lifted-above-winner-other lift-a*

**unfolding** *Profile.lifted-def*

**by** *metis*

hence  $\forall b \in A - \{a\}$ .  
 $\{i \in V. \text{above } (q \ i) \ b = \{b\}\} \subseteq \{i \in V. \text{above } (p \ i) \ b = \{b\}\}$   
 by (*simp add: Collect-mono*)  
 hence *win-count-other*:  $\forall b \in A - \{a\}. \text{win-count } V \ p \ b \geq \text{win-count } V \ q \ b$   
 by (*simp add: card-mono*)  
 show *defer plurality*  $V \ A \ q = \text{defer plurality } V \ A \ p$   
 $\vee \text{defer plurality } V \ A \ q = \{a\}$   
 proof (*cases*)  
 assume *win-count*  $V \ p \ a = \text{win-count } V \ q \ a$   
 hence *card*  $\{i \in V. \text{above } (p \ i) \ a = \{a\}\} = \text{card } \{i \in V. \text{above } (q \ i) \ a = \{a\}\}$   
 using *win-count.simps Profile.lifted-def enat.inject lift-a*  
 by (*metis (mono-tags, lifting)*)  
 moreover have *finite*  $\{i \in V. \text{above } (q \ i) \ a = \{a\}\}$   
 using *Collect-mem-eq Profile.lifted-def finite-Collect-conjI lift-a*  
 by (*metis (mono-tags)*)  
 ultimately have  $\{i \in V. \text{above } (p \ i) \ a = \{a\}\} = \{i \in V. \text{above } (q \ i) \ a = \{a\}\}$   
 using *a-win-subset*  
 by (*simp add: card-subset-eq*)  
 hence *above-pq*:  $\forall i \in V. (\text{above } (p \ i) \ a = \{a\}) = (\text{above } (q \ i) \ a = \{a\})$   
 by *blast*  
 moreover have  
 $\forall b \in A - \{a\}. \forall i \in V.$   
 $(\text{above } (p \ i) \ b = \{b\}) \longrightarrow (\text{above } (q \ i) \ b = \{b\} \vee \text{above } (q \ i) \ a = \{a\})$   
 using *lifted-winner*  
 by *auto*  
 moreover have  
 $\forall b \in A - \{a\}. \forall i \in V. (\text{above } (p \ i) \ b = \{b\}) \longrightarrow \text{above } (p \ i) \ a \neq \{a\}$   
 proof (*intro ballI impI, safe*)  
 fix  
 $b :: 'a$  and  
 $i :: 'v$   
 assume  
 $b \in A$  and  
 $i \in V$   
 moreover from *this* have *A-not-empty*:  $A \neq \{\}$   
 by *blast*  
 ultimately have *linear-order-on*  $A \ (p \ i)$   
 using *lift-a*  
 unfolding *lifted-def profile-def*  
 by *metis*  
 moreover assume  
 $b \neq a$ :  $b \neq a$  and  
 $abv\text{-}b$ :  $\text{above } (p \ i) \ b = \{b\}$  and  
 $abv\text{-}a$ :  $\text{above } (p \ i) \ a = \{a\}$   
 ultimately show *False*  
 using *above-one-eq A-not-empty fin-A*  
 by (*metis (no-types)*)  
 qed  
 ultimately have *above-PtoQ*:

$\forall b \in A - \{a\}. \forall i \in V. (\text{above } (p \ i) \ b = \{b\} \longrightarrow \text{above } (q \ i) \ b = \{b\})$   
 by *simp*  
 hence  $\forall b \in A.$   
 $\text{card } \{i \in V. \text{above } (p \ i) \ b = \{b\}\} =$   
 $\text{card } \{i \in V. \text{above } (q \ i) \ b = \{b\}\}$   
 proof (*safe*)  
 fix  $b :: 'a$   
 assume  $b \in A$   
 thus  $\text{card } \{i \in V. \text{above } (p \ i) \ b = \{b\}\} =$   
 $\text{card } \{i \in V. \text{above } (q \ i) \ b = \{b\}\}$   
 using *DiffI set-disj above-PtoQ above-QtoP above-pq*  
 by (*metis (no-types, lifting)*)  
 qed  
 hence  $\{b \in A. \forall c \in A. \text{win-count } V \ p \ c \leq \text{win-count } V \ p \ b\} =$   
 $\{b \in A. \forall c \in A. \text{win-count } V \ q \ c \leq \text{win-count } V \ q \ b\}$   
 by *auto*  
 hence  $\text{defer plurality}' \ V \ A \ q = \text{defer plurality}' \ V \ A \ p$   
 $\vee \text{defer plurality}' \ V \ A \ q = \{a\}$   
 by *simp*  
 hence  $\text{defer plurality } V \ A \ q = \text{defer plurality } V \ A \ p$   
 $\vee \text{defer plurality } V \ A \ q = \{a\}$   
 using *plurality-mod-equiv lift-a*  
 unfolding *Profile.lifted-def*  
 by (*metis (no-types, opaque-lifting)*)  
 thus *?thesis*  
 by *simp*  
 next  
 assume  $\text{win-count } V \ p \ a \neq \text{win-count } V \ q \ a$   
 hence *strict-less*:  $\text{win-count } V \ p \ a < \text{win-count } V \ q \ a$   
 using *win-count-a*  
 by *simp*  
 have  $a \in \text{defer plurality } V \ A \ p$   
 using *defer-a plurality.elims*  
 by (*metis (no-types)*)  
 moreover have *non-empty-A*:  $A \neq \{\}$   
 using *lift-a equals0D equiv-prof-except-a-def*  
 $\text{lifted-imp-equiv-prof-except-a}$   
 by *metis*  
 moreover have *fin-A*: *finite-profile*  $V \ A \ p$   
 using *lift-a*  
 unfolding *Profile.lifted-def*  
 by *simp*  
 ultimately have  $a \in \text{defer plurality}' \ V \ A \ p$   
 using *plurality-mod-equiv*  
 by *metis*  
 hence *a-in-win-p*:  
 $a \in \{b \in A. \forall c \in A. \text{win-count } V \ p \ c \leq \text{win-count } V \ p \ b\}$   
 using *fin-A*  
 by *simp*

**hence**  $\forall b \in A. \text{win-count } V p b \leq \text{win-count } V p a$   
**by** *simp*  
**hence** *less*:  $\forall b \in A - \{a\}. \text{win-count } V q b < \text{win-count } V q a$   
**using** *DiffD1 antisym dual-order.trans not-le-imp-less*  
*win-count-a strict-less win-count-other*  
**by** *metis*  
**hence**  $\forall b \in A - \{a\}. \neg (\forall c \in A. \text{win-count } V q c \leq \text{win-count } V q b)$   
**using** *lift-a not-le*  
**unfolding** *Profile.lifted-def*  
**by** *metis*  
**hence**  $\forall b \in A - \{a\}. b \notin \{c \in A. \forall b \in A. \text{win-count } V q b \leq \text{win-count } V q c\}$   
**by** *blast*  
**hence**  $\forall b \in A - \{a\}. b \notin \text{defer plurality}' V A q$   
**using** *fin-A*  
**by** *simp*  
**hence**  $\forall b \in A - \{a\}. b \notin \text{defer plurality } V A q$   
**using** *lift-a non-empty-A plurality-mod-equiv*  
**unfolding** *Profile.lifted-def*  
**by** (*metis (no-types, lifting)*)  
**hence**  $\forall b \in A - \{a\}. b \notin \text{defer plurality } V A q$   
**by** *simp*  
**moreover have**  $a \in \text{defer plurality } V A q$   
**proof** –  
**have**  $\forall b \in A - \{a\}. \text{win-count } V q b \leq \text{win-count } V q a$   
**using** *less less-imp-le*  
**by** *metis*  
**moreover have**  $\text{win-count } V q a \leq \text{win-count } V q a$   
**by** *simp*  
**ultimately have**  $\forall b \in A. \text{win-count } V q b \leq \text{win-count } V q a$   
**by** *auto*  
**moreover have**  $a \in A$   
**using** *a-in-win-p*  
**by** *simp*  
**ultimately have**  
 $a \in \{b \in A. \forall c \in A. \text{win-count } V q c \leq \text{win-count } V q b\}$   
**by** *simp*  
**hence**  $a \in \text{defer plurality}' V A q$   
**by** *simp*  
**hence**  $a \in \text{defer plurality } V A q$   
**using** *plurality-mod-equiv non-empty-A fin-A lift-a non-empty-A*  
**unfolding** *Profile.lifted-def*  
**by** (*metis (no-types)*)  
**thus** *?thesis*  
**by** *simp*  
**qed**  
**moreover have**  $\text{defer plurality } V A q \subseteq A$   
**by** *simp*  
**ultimately show** *?thesis*

by blast  
qed  
qed

**lemma** *plurality'-def-inv-mono-alts*:

**fixes**

$A :: 'a \text{ set}$  **and**

$V :: 'v \text{ set}$  **and**

$p \ q :: ('a, 'v) \text{ Profile}$  **and**

$a :: 'a$

**assumes**

$a \in \text{defer plurality}' V A p$  **and**

*lifted*  $V A p \ q \ a$

**shows**  $\text{defer plurality}' V A q = \text{defer plurality}' V A p$

$\vee \text{defer plurality}' V A q = \{a\}$

**using** *assms plurality-def-inv-mono-alts plurality-mod-equiv*

**by** (*metis (no-types)*)

The plurality rule is invariant-monotone.

**theorem** *plurality-mod-def-inv-mono[simp]: defer-invariant-monotonicity plurality*

**proof** (*unfold defer-invariant-monotonicity-def, intro conjI impI allI*)

**show** *SCF-result.electoral-module plurality*

**using** *plurality-sound*

**by** *metis*

**next**

**show** *non-electing plurality*

**by** *simp*

**next**

**fix**

$A :: 'b \text{ set}$  **and**

$V :: 'a \text{ set}$  **and**

$p \ q :: ('b, 'a) \text{ Profile}$  **and**

$a :: 'b$

**assume**  $a \in \text{defer plurality } V A p \wedge \text{Profile.lifted } V A p \ q \ a$

**hence**  $\text{defer plurality } V A q = \text{defer plurality } V A p$

$\vee \text{defer plurality } V A q = \{a\}$

**using** *plurality-def-inv-mono-alts*

**by** *metis*

**thus**  $\text{defer plurality } V A q = \text{defer plurality } V A p$

$\vee \text{defer plurality } V A q = \{a\}$

**by** *simp*

**qed**

**theorem** *plurality'-mod-def-inv-mono[simp]: defer-invariant-monotonicity plurality'*

**using** *plurality-mod-def-inv-mono plurality-mod-equiv*

*plurality'-non-electing plurality'-sound*

**unfolding** *defer-invariant-monotonicity-def*

**by** *metis*



end

## 5.13 Borda Module

**theory** *Borda-Module*  
**imports** *Component-Types/Elimination-Module*  
**begin**

This is the Borda module used by the Borda rule. The Borda rule is a voting rule, where on each ballot, each alternative is assigned a score that depends on how many alternatives are ranked below. The sum of all such scores for an alternative is hence called their Borda score. The alternative with the highest Borda score is elected. The module implemented herein only rejects the alternatives not elected by the voting rule, and defers the alternatives that would be elected by the full voting rule.

### 5.13.1 Definition

**fun** *borda-score* :: ('a, 'v) *Evaluation-Function* **where**  
*borda-score* *V x A p* = ( $\sum y \in A. (\text{prefer-count } V p x y)$ )

**fun** *borda* :: ('a, 'v, 'a *Result*) *Electoral-Module* **where**  
*borda* *V A p* = *max-eliminator* *borda-score* *V A p*

### 5.13.2 Soundness

**theorem** *borda-sound*: *SCF-result.electoral-module* *borda*  
**unfolding** *borda.simps*  
**using** *max-elim-sound*  
**by** *metis*

### 5.13.3 Non-Blocking

The Borda module is non-blocking.

**theorem** *borda-mod-non-blocking[simp]*: *non-blocking* *borda*  
**unfolding** *borda.simps*  
**using** *max-elim-non-blocking*  
**by** *metis*

### 5.13.4 Non-Electing

The Borda module is non-electing.

**theorem** *borda-mod-non-electing[simp]*: *non-electing* *borda*

```

using max-elim-non-electing
unfolding borda.simps non-electing-def
by metis

end

```

## 5.14 Condorcet Module

```

theory Condorcet-Module
  imports Component-Types/Elimination-Module
begin

```

This is the Condorcet module used by the Condorcet (voting) rule. The Condorcet rule is a voting rule that implements the Condorcet criterion, i.e., it elects the Condorcet winner if it exists, otherwise a tie remains between all alternatives. The module implemented herein only rejects the alternatives not elected by the voting rule, and defers the alternatives that would be elected by the full voting rule.

### 5.14.1 Definition

```

fun condorcet-score :: ('a, 'v) Evaluation-Function where
  condorcet-score V x A p = (if condorcet-winner V A p x then 1 else 0)

fun condorcet :: ('a, 'v, 'a Result) Electoral-Module where
  condorcet V A p = (max-eliminator condorcet-score) V A p

```

### 5.14.2 Soundness

```

theorem condorcet-sound: SCF-result.electoral-module condorcet
  unfolding condorcet.simps
  using max-elim-sound
  by metis

```

### 5.14.3 Property

```

theorem condorcet-score-is-condorcet-rating: condorcet-rating condorcet-score
proof (unfold condorcet-rating-def, safe)
  fix
    A :: 'b set and
    V :: 'a set and
    p :: ('b, 'a) Profile and
    w l :: 'b
  assume
    c-win: condorcet-winner V A p w and

```

```

    l-neq-w:  $l \neq w$ 
  have  $\neg \text{condorcet-winner } V \ A \ p \ l$ 
    using cond-winner-unique-eq c-win l-neq-w
    by metis
  thus  $\text{condorcet-score } V \ l \ A \ p < \text{condorcet-score } V \ w \ A \ p$ 
    using c-win zero-less-one
    unfolding condorcet-score.simps
    by (metis (full-types))
qed

theorem condorcet-is-dcc: defer-condorcet-consistency condorcet
proof (unfold defer-condorcet-consistency-def SCF-result.electoral-module.simps,
  safe)
  fix
     $A :: 'b \text{ set}$  and
     $V :: 'a \text{ set}$  and
     $p :: ('b, 'a) \text{ Profile}$ 
  assume profile  $V \ A \ p$ 
  hence well-formed-SCF  $A \ (\text{max-eliminator condorcet-score } V \ A \ p)$ 
    using max-elim-sound
    unfolding SCF-result.electoral-module.simps
    by metis
  thus well-formed-SCF  $A \ (\text{condorcet } V \ A \ p)$ 
    by simp
next
  fix
     $A :: 'b \text{ set}$  and
     $V :: 'a \text{ set}$  and
     $p :: ('b, 'a) \text{ Profile}$  and
     $a :: 'b$ 
  assume c-win-w:  $\text{condorcet-winner } V \ A \ p \ a$ 
  let  $?m = (\text{max-eliminator condorcet-score}) :: ('b, 'a, 'b \text{ Result}) \text{ Electoral-Module}$ 
  have defer-condorcet-consistency  $?m$ 
    using cr-eval-imp-dcc-max-elim condorcet-score-is-condorcet-rating
    by metis
  hence  $?m \ V \ A \ p =$ 
    ( $\{\}, A - \text{defer } ?m \ V \ A \ p, \{b \in A. \text{condorcet-winner } V \ A \ p \ b\}$ )
    using c-win-w
    unfolding defer-condorcet-consistency-def
    by (metis (no-types))
  thus  $\text{condorcet } V \ A \ p =$ 
    ( $\{\},$ 
     $A - \text{defer condorcet } V \ A \ p,$ 
     $\{d \in A. \text{condorcet-winner } V \ A \ p \ d\}$ )
    by simp
qed

end

```

## 5.15 Copeland Module

```
theory Copeland-Module
  imports Component-Types/Elimination-Module
begin
```

This is the Copeland module used by the Copeland voting rule. The Copeland rule elects the alternatives with the highest difference between the amount of simple-majority wins and the amount of simple-majority losses. The module implemented herein only rejects the alternatives not elected by the voting rule, and defers the alternatives that would be elected by the full voting rule.

### 5.15.1 Definition

```
fun copeland-score :: ('a, 'v) Evaluation-Function where
  copeland-score V x A p =
    card {y ∈ A . wins V x p y} - card {y ∈ A . wins V y p x}

fun copeland :: ('a, 'v, 'a Result) Electoral-Module where
  copeland V A p = max-eliminator copeland-score V A p
```

### 5.15.2 Soundness

```
theorem copeland-sound: SCF-result.electoral-module copeland
  unfolding copeland.simps
  using max-elim-sound
  by metis
```

### 5.15.3 Lemmas

```
lemma voters-determine-copeland-score: voters-determine-evaluation copeland-score
proof (unfold copeland-score.simps voters-determine-evaluation.simps, safe)
  fix
    A :: 'b set and
    V :: 'a set and
    p p' :: ('b, 'a) Profile and
    a :: 'b
  assume
    ∀ v ∈ V. p v = p' v and
    a ∈ A
  hence ∀ x y. {v ∈ V. (x, y) ∈ p v} = {v ∈ V. (x, y) ∈ p' v}
    by blast
  hence ∀ x y.
    card {y ∈ A. wins V x p y} = card {y ∈ A. wins V x p' y}
```

$\wedge \text{card } \{x \in A. \text{ wins } V x p y\} = \text{card } \{x \in A. \text{ wins } V x p' y\}$   
 by *simp*  
 thus  $\text{card } \{y \in A. \text{ wins } V a p y\} - \text{card } \{y \in A. \text{ wins } V y p a\} =$   
 $\text{card } \{y \in A. \text{ wins } V a p' y\} - \text{card } \{y \in A. \text{ wins } V y p' a\}$   
 by *presburger*  
 qed

**theorem** *voters-determine-copeland: voters-determine-election copeland*  
**unfolding** *copeland.simps*  
**using** *voters-determine-max-elim voters-determine-election.simps*  
*voters-determine-copeland-score*  
**by** *blast*

For a Condorcet winner  $w$ , we have: " $|\{y \in A. \text{ wins } V w p y\}| = |A| - 1$ ".

**lemma** *cond-winner-imp-win-count:*

**fixes**  
 $A :: 'a \text{ set}$  **and**  
 $V :: 'v \text{ set}$  **and**  
 $p :: ('a, 'v) \text{ Profile}$  **and**  
 $w :: 'a$   
**assumes** *condorcet-winner*  $V A p w$   
**shows**  $\text{card } \{a \in A. \text{ wins } V w p a\} = \text{card } A - 1$   
**proof** –  
**have**  $\forall a \in A - \{w\}. \text{ wins } V w p a$   
**using** *assms*  
**by** *auto*  
**hence**  $\{a \in A - \{w\}. \text{ wins } V w p a\} = A - \{w\}$   
**by** *blast*  
**hence** *winner-wins-against-all-others:*  
 $\text{card } \{a \in A - \{w\}. \text{ wins } V w p a\} = \text{card } (A - \{w\})$   
**by** *simp*  
**have**  $w \in A$   
**using** *assms*  
**by** *simp*  
**hence**  $\text{card } (A - \{w\}) = \text{card } A - 1$   
**using** *card-Diff-singleton assms*  
**by** *metis*  
**hence** *winner-amount-one:*  $\text{card } \{a \in A - \{w\}. \text{ wins } V w p a\} = \text{card } (A) - 1$   
**using** *winner-wins-against-all-others*  
**by** *linarith*  
**have** *win-for-winner-not-reflexive:*  $\forall a \in \{w\}. \neg \text{ wins } V a p a$   
**by** (*simp add: wins-irreflex*)  
**hence**  $\{a \in \{w\}. \text{ wins } V w p a\} = \{\}$   
**by** *blast*  
**hence** *winner-amount-zero:*  $\text{card } \{a \in \{w\}. \text{ wins } V w p a\} = 0$   
**by** *simp*  
**have** *union:*  
 $\{a \in A - \{w\}. \text{ wins } V w p a\} \cup \{x \in \{w\}. \text{ wins } V w p x\} =$   
 $\{a \in A. \text{ wins } V w p a\}$

```

using win-for-winner-not-reflexive
by blast
have finite-defeated: finite  $\{a \in A - \{w\}. \text{wins } V w p a\}$ 
using assms
by simp
have finite  $\{a \in \{w\}. \text{wins } V w p a\}$ 
by simp
hence card  $(\{a \in A - \{w\}. \text{wins } V w p a\} \cup \{a \in \{w\}. \text{wins } V w p a\}) =$ 
  card  $\{a \in A - \{w\}. \text{wins } V w p a\} + \text{card } \{a \in \{w\}. \text{wins } V w p a\}$ 
using finite-defeated card-Un-disjoint
by blast
hence card  $\{a \in A. \text{wins } V w p a\} =$ 
  card  $\{a \in A - \{w\}. \text{wins } V w p a\} + \text{card } \{a \in \{w\}. \text{wins } V w p a\}$ 
using union
by simp
thus ?thesis
using winner-amount-one winner-amount-zero
by linarith
qed

```

For a Condorcet winner  $w$ , we have: " $|\{y \in A . \text{wins } V y p w\}| = 0$ ".

**lemma** cond-winner-imp-loss-count:

```

fixes
  A :: 'a set and
  V :: 'v set and
  p :: ('a, 'v) Profile and
  w :: 'a
assumes condorcet-winner V A p w
shows card  $\{a \in A. \text{wins } V a p w\} = 0$ 
using Collect-empty-eq card-eq-0-iff insert-Diff insert-iff wins-antisym assms
unfolding condorcet-winner.simps
by (metis (no-types, lifting))

```

Copeland score of a Condorcet winner.

**lemma** cond-winner-imp-copeland-score:

```

fixes
  A :: 'a set and
  V :: 'v set and
  p :: ('a, 'v) Profile and
  w :: 'a
assumes condorcet-winner V A p w
shows copeland-score V w A p = card A - 1
proof (unfold copeland-score.simps)
have card  $\{a \in A. \text{wins } V w p a\} = \text{card } A - 1$ 
using cond-winner-imp-win-count assms
by metis
moreover have card  $\{a \in A. \text{wins } V a p w\} = 0$ 
using cond-winner-imp-loss-count assms
by (metis (no-types))

```

ultimately show  
 $enat (card \{a \in A. wins V w p a\} - card \{a \in A. wins V a p w\}) = enat (card A - 1)$   
 by *simp*  
 qed

For a non-Condorcet winner  $l$ , we have: " $|\{y \in A . wins V l p y\}| = |A| - 2$ ".

**lemma** *non-cond-winner-imp-win-count*:

**fixes**  
 $A :: 'a \text{ set}$  **and**  
 $V :: 'v \text{ set}$  **and**  
 $p :: ('a, 'v) \text{ Profile}$  **and**  
 $w l :: 'a$   
**assumes**  
 $winner: condorcet-winner V A p w$  **and**  
 $loser: l \neq w$  **and**  
 $l-in-A: l \in A$   
**shows**  $card \{a \in A . wins V l p a\} \leq card A - 2$   
**proof** –  
**have**  $wins V w p l$   
**using** *assms*  
**by** *auto*  
**hence**  $\neg wins V l p w$   
**using** *wins-antisym*  
**by** *simp*  
**moreover have**  $\neg wins V l p l$   
**using** *wins-irreflex*  
**by** *simp*  
**ultimately have** *wins-of-loser-eq-without-winner*:  
 $\{y \in A . wins V l p y\} = \{y \in A - \{l, w\} . wins V l p y\}$   
**by** *blast*  
**have**  $\forall M f. finite M \longrightarrow card \{x \in M . f x\} \leq card M$   
**by** (*simp add: card-mono*)  
**moreover have**  $finite (A - \{l, w\})$   
**using** *finite-Diff winner*  
**by** *simp*  
**ultimately have**  $card \{y \in A - \{l, w\} . wins V l p y\} \leq card (A - \{l, w\})$   
**using** *winner*  
**by** (*metis (full-types)*)  
**thus** *?thesis*  
**using** *assms wins-of-loser-eq-without-winner*  
**by** *simp*  
 qed

#### 5.15.4 Property

The Copeland score is Condorcet rating.

**theorem** *copeland-score-is-cr: condorcet-rating copeland-score*

**proof** (*unfold condorcet-rating-def, unfold copeland-score.simps, safe*)  
**fix**  
 $A :: 'b \text{ set}$  **and**  
 $V :: 'v \text{ set}$  **and**  
 $p :: ('b, 'v) \text{ Profile}$  **and**  
 $w l :: 'b$   
**assume**  
 $\text{winner: condorcet-winner } V A p w$  **and**  
 $l\text{-in-}A: l \in A$  **and**  
 $l\text{-neg-}w: l \neq w$   
**hence**  $\text{card } \{y \in A. \text{wins } V l p y\} \leq \text{card } A - 2$   
**using** *non-cond-winner-imp-win-count*  
**by** (*metis (mono-tags, lifting)*)  
**hence**  $\text{card } \{y \in A. \text{wins } V l p y\} - \text{card } \{y \in A. \text{wins } V y p l\} \leq \text{card } A - 2$   
**using** *diff-le-self order.trans*  
**by** *simp*  
**moreover have**  $\text{card } A - 2 < \text{card } A - 1$   
**using** *card-0-eq diff-less-mono2 empty-iff l-in-A l-neg-w neg0-conv less-one*  
 $\text{Suc-1 zero-less-diff add-diff-cancel-left' diff-is-0-eq Suc-eq-plus1}$   
 $\text{card-1-singleton-iff order-less-le singletonD le-zero-eq winner}$   
**unfolding** *condorcet-winner.simps*  
**by** *metis*  
**ultimately have**  
 $\text{card } \{y \in A. \text{wins } V l p y\} - \text{card } \{y \in A. \text{wins } V y p l\} < \text{card } A - 1$   
**using** *order-le-less-trans*  
**by** *fastforce*  
**moreover have**  $\text{card } \{a \in A. \text{wins } V a p w\} = 0$   
**using** *cond-winner-imp-loss-count winner*  
**by** *metis*  
**moreover have**  $\text{card } A - 1 = \text{card } \{a \in A. \text{wins } V w p a\}$   
**using** *cond-winner-imp-win-count winner*  
**by** (*metis (full-types)*)  
**ultimately show**  
 $\text{enat } (\text{card } \{y \in A. \text{wins } V l p y\} - \text{card } \{y \in A. \text{wins } V y p l\}) <$   
 $\text{enat } (\text{card } \{y \in A. \text{wins } V w p y\} - \text{card } \{y \in A. \text{wins } V y p w\})$   
**using** *enat-ord-simps diff-zero*  
**by** (*metis (no-types, lifting)*)  
**qed**

**theorem** *copeland-is-dcc: defer-condorcet-consistency copeland*

**proof** (*unfold defer-condorcet-consistency-def SCF-result.electoral-module.simps, safe*)

**fix**  
 $A :: 'b \text{ set}$  **and**  
 $V :: 'a \text{ set}$  **and**  
 $p :: ('b, 'a) \text{ Profile}$   
**assume** *profile*  $V A p$   
**moreover from this**  
**have** *well-formed-SCF*  $A$  (*max-eliminator copeland-score*  $V A p$ )



```

    using max-elim-sound
    unfolding SCF-result.electoral-module.simps
    by metis
  ultimately show well-formed-SCF A (copeland V A p)
    using copeland-sound
    unfolding SCF-result.electoral-module.simps
    by metis
next
fix
  A :: 'b set and
  V :: 'v set and
  p :: ('b, 'v) Profile and
  w :: 'b
assume condorcet-winner V A p w
moreover have defer-condorcet-consistency (max-eliminator copeland-score)
  by (simp add: copeland-score-is-cr)
ultimately have
  max-eliminator copeland-score V A p =
    ({},
     A - defer (max-eliminator copeland-score) V A p,
     {d ∈ A. condorcet-winner V A p d})
  unfolding defer-condorcet-consistency-def
  by (metis (no-types))
moreover have copeland V A p = max-eliminator copeland-score V A p
  unfolding copeland.simps
  by safe
ultimately show
  copeland V A p =
    ({}, A - defer copeland V A p, {d ∈ A. condorcet-winner V A p d})
  by metis
qed

end

```

## 5.16 Minimax Module

```

theory Minimax-Module
  imports Component-Types/Elimination-Module
begin

```

This is the Minimax module used by the Minimax voting rule. The Minimax rule elects the alternatives with the highest Minimax score. The module implemented herein only rejects the alternatives not elected by the voting rule, and defers the alternatives that would be elected by the full voting rule.

### 5.16.1 Definition

**fun** *minimax-score* :: ('a, 'v) *Evaluation-Function* **where**  
*minimax-score*  $V\ x\ A\ p =$   
 $\text{Min } \{\text{prefer-count } V\ p\ x\ y \mid y. y \in A - \{x\}\}$

**fun** *minimax* :: ('a, 'v, 'a *Result*) *Electoral-Module* **where**  
*minimax*  $A\ p = \text{max-eliminator } \text{minimax-score } A\ p$

### 5.16.2 Soundness

**theorem** *minimax-sound*: *SCF-result.electoral-module minimax*  
**unfolding** *minimax.simps*  
**using** *max-elim-sound*  
**by** *metis*

### 5.16.3 Lemma

**lemma** *non-cond-winner-minimax-score*:  
**fixes**  
 $A :: 'a\ \text{set}$  **and**  
 $V :: 'v\ \text{set}$  **and**  
 $p :: ('a, 'v)\ \text{Profile}$  **and**  
 $w\ l :: 'a$   
**assumes**  
 $\text{prof: profile } V\ A\ p$  **and**  
 $\text{winner: condorcet-winner } V\ A\ p\ w$  **and**  
 $\text{l-in-A: } l \in A$  **and**  
 $\text{l-neq-w: } l \neq w$   
**shows**  $\text{minimax-score } V\ l\ A\ p \leq \text{prefer-count } V\ p\ l\ w$   
**proof** (*unfold minimax-score.simps, intro Min-le*)  
**have** *finite V*  
**using** *winner*  
**by** *simp*  
**moreover have**  $\forall\ E\ n. \text{infinite } E \longrightarrow (\exists\ e. \neg e \leq \text{enat } n \wedge e \in E)$   
**using** *finite-enat-bounded*  
**by** *blast*  
**ultimately show**  $\text{finite } \{\text{prefer-count } V\ p\ l\ y \mid y. y \in A - \{l\}\}$   
**using** *pref-count-voter-set-card*  
**by** *fastforce*  
**next**  
**have**  $w \in A$   
**using** *winner*  
**by** *simp*  
**thus**  $\text{prefer-count } V\ p\ l\ w \in \{\text{prefer-count } V\ p\ l\ y \mid y. y \in A - \{l\}\}$   
**using** *l-neq-w*  
**by** *blast*  
**qed**

### 5.16.4 Property

**theorem** *minimax-score-cond-rating: condorcet-rating minimax-score*

**proof** (*unfold condorcet-rating-def minimax-score.simps prefer-count.simps,*  
*safe, rule ccontr*)

**fix**

$A :: 'b$  set **and**  
 $V :: 'a$  set **and**  
 $p :: ('b, 'a)$  Profile **and**  
 $w l :: 'b$

**assume**

*winner: condorcet-winner*  $V A p w$  **and**

*l-in-A:  $l \in A$*  **and**

*l-neq-w:  $l \neq w$*  **and**

*min-leq:*

$\neg \text{Min } \{ \text{if finite } V$   
 $\quad \text{then enat } (\text{card } \{v \in V. \text{ let } r = p \ v \text{ in } y \preceq_r l\})$   
 $\quad \text{else } \infty \mid y. y \in A - \{l\} \}$   
 $< \text{Min } \{ \text{if finite } V$   
 $\quad \text{then enat } (\text{card } \{v \in V. \text{ let } r = p \ v \text{ in } y \preceq_r w\})$   
 $\quad \text{else } \infty \mid y. y \in A - \{w\} \}$

**hence** *min-count-ineq:*

$\text{Min } \{ \text{prefer-count } V p l y \mid y. y \in A - \{l\} \} \geq$   
 $\text{Min } \{ \text{prefer-count } V p w y \mid y. y \in A - \{w\} \}$

**by** *simp*

**have** *pref-count-gte-min:*

$\text{prefer-count } V p l w \geq \text{Min } \{ \text{prefer-count } V p l y \mid y. y \in A - \{l\} \}$

**using** *l-in-A l-neq-w condorcet-winner.simps winner non-cond-winner-minimax-score*  
*minimax-score.simps*

**by** *metis*

**have** *l-in-A-without-w:  $l \in A - \{w\}$*

**using** *l-in-A l-neq-w*

**by** *simp*

**hence** *pref-counts-non-empty:  $\{ \text{prefer-count } V p w y \mid y. y \in A - \{w\} \} \neq \{ \}$*

**by** *blast*

**have** *finite  $(A - \{w\})$*

**using** *condorcet-winner.simps winner finite-Diff*

**by** *metis*

**hence** *finite  $\{ \text{prefer-count } V p w y \mid y. y \in A - \{w\} \}$*

**by** *simp*

**hence**  $\exists n \in A - \{w\}. \text{prefer-count } V p w n =$

$\text{Min } \{ \text{prefer-count } V p w y \mid y. y \in A - \{w\} \}$

**using** *pref-counts-non-empty Min-in*

**by** *fastforce*

**then obtain**  $n :: 'b$  **where**

*pref-count-eq-min:*

$\text{prefer-count } V p w n =$

$\text{Min } \{ \text{prefer-count } V p w y \mid y. y \in A - \{w\} \}$  **and**

*n-not-w:  $n \in A - \{w\}$*

**by** *metis*

```

hence n-in-A:  $n \in A$ 
  using DiffE
  by metis
have n-neq-w:  $n \neq w$ 
  using n-not-w
  by simp
have w-in-A:  $w \in A$ 
  using winner
  by simp
have pref-count-n-w-ineq:  $\text{prefer-count } V \ p \ w \ n > \text{prefer-count } V \ p \ n \ w$ 
  using n-not-w winner
  by auto
have pref-count-l-w-n-ineq:  $\text{prefer-count } V \ p \ l \ w \geq \text{prefer-count } V \ p \ w \ n$ 
  using pref-count-gte-min min-count-ineq pref-count-eq-min
  by auto
hence  $\text{prefer-count } V \ p \ n \ w \geq \text{prefer-count } V \ p \ w \ l$ 
  using n-in-A w-in-A l-in-A n-neq-w l-neq-w pref-count-sym winner
  unfolding condorcet-winner.simps
  by metis
hence  $\text{prefer-count } V \ p \ l \ w > \text{prefer-count } V \ p \ w \ l$ 
  using n-in-A w-in-A l-in-A n-neq-w l-neq-w pref-count-sym winner
  pref-count-n-w-ineq pref-count-l-w-n-ineq
  unfolding condorcet-winner.simps
  by auto
hence wins  $V \ l \ p \ w$ 
  by simp
thus False
  using l-in-A-without-w wins-antisym winner
  unfolding condorcet-winner.simps
  by metis
qed

theorem minimax-is-dcc: defer-condorcet-consistency minimax
proof (unfold defer-condorcet-consistency-def SCF-result.electoral-module.simps,
  safe)
  fix
     $A :: 'b \text{ set}$  and
     $V :: 'a \text{ set}$  and
     $p :: ('b, 'a) \text{ Profile}$ 
  assume profile  $V \ A \ p$ 
  hence well-formed-SCF  $A \ (\text{max-eliminator minimax-score } V \ A \ p)$ 
  using max-elim-sound par-comp-result-sound
  by metis
  thus well-formed-SCF  $A \ (\text{minimax } V \ A \ p)$ 
  by simp
next
  fix
     $A :: 'b \text{ set}$  and
     $V :: 'a \text{ set}$  and

```

```

     $p :: ('b, 'a) \text{ Profile}$  and
     $w :: 'b$ 
assume  $cwin-w: \text{condorcet-winner } V \ A \ p \ w$ 
have  $max-mmaxscore-dcc:$ 
     $defer\text{-}condorcet\text{-}consistency \ ((max\text{-}eliminator \ minimax\text{-}score)$ 
     $:: ('b, 'a, 'b \text{ Result}) \text{ Electoral-Module})$ 
using  $cr\text{-}eval\text{-}imp\text{-}dcc\text{-}max\text{-}elim \ minimax\text{-}score\text{-}cond\text{-}rating$ 
by  $metis$ 
hence
     $max\text{-}eliminator \ minimax\text{-}score \ V \ A \ p =$ 
     $(\{\},$ 
     $A - defer \ (max\text{-}eliminator \ minimax\text{-}score) \ V \ A \ p,$ 
     $\{a \in A. \text{condorcet-winner } V \ A \ p \ a\})$ 
using  $cwin-w$ 
unfolding  $defer\text{-}condorcet\text{-}consistency\text{-}def$ 
by  $blast$ 
thus
     $minimax \ V \ A \ p =$ 
     $(\{\},$ 
     $A - defer \ minimax \ V \ A \ p,$ 
     $\{d \in A. \text{condorcet-winner } V \ A \ p \ d\})$ 
by  $simp$ 
qed

end

```

## Chapter 6

# Compositional Structures

### 6.1 Drop- and Pass-Compatibility

```
theory Drop-And-Pass-Compatibility
imports Basic-Modules/Drop-Module
        Basic-Modules/Pass-Module
begin
```

This is a collection of properties about the interplay and compatibility of both the drop module and the pass module.

```
theorem drop-zero-mod-rej-zero[simp]:
  fixes  $r :: 'a \text{ Preference-Relation}$ 
  assumes  $\text{linear-order } r$ 
  shows  $\text{rejects } 0 \ (\text{drop-module } 0 \ r)$ 
proof (unfold rejects-def, safe)
  show  $\text{SCF-result.electoral-module } (\text{drop-module } 0 \ r)$ 
    using  $\text{assms drop-mod-sound}$ 
    by  $\text{metis}$ 
next
fix
   $A :: 'a \text{ set}$  and
   $V :: 'v \text{ set}$  and
   $p :: ('a, 'v) \text{ Profile}$ 
assume
   $\text{fin-}A: \text{finite } A$  and
   $\text{prof-}A: \text{profile } V \ A \ p$ 
have  $\text{connex UNIV } r$ 
  using  $\text{assms lin-ord-imp-connex}$ 
  by  $\text{auto}$ 
hence  $\text{connex: connex } A \ (\text{limit } A \ r)$ 
  using  $\text{limit-presv-connex subset-UNIV}$ 
  by  $\text{metis}$ 
have  $\forall B \ a. B \neq \{\} \vee (a :: 'a) \notin B$ 
  by  $\text{simp}$ 
hence  $\forall a \ B. a \in A \wedge a \in B \longrightarrow \text{connex } B \ (\text{limit } A \ r) \longrightarrow$ 
```

```

      ¬ card (above (limit A r) a) ≤ 0
    using above-connex above-presv-limit card-eq-0-iff
      fin-A finite-subset le-0-eq assms
    by (metis (no-types))
  hence {a ∈ A. card (above (limit A r) a) ≤ 0} = {}
    using connex
    by auto
  hence card {a ∈ A. card (above (limit A r) a) ≤ 0} = 0
    using card.empty
    by (metis (full-types))
  thus card (reject (drop-module 0 r) V A p) = 0
    by simp
qed

```

The drop module rejects  $n$  alternatives (if there are at least  $n$  alternatives).

```

theorem drop-two-mod-rej-n[simp]:
  fixes r :: 'a Preference-Relation
  assumes linear-order r
  shows rejects n (drop-module n r)
proof (unfold rejects-def, safe)
  show SCF-result.electoral-module (drop-module n r)
    using drop-mod-sound
    by metis
next
  fix
    A :: 'a set and
    V :: 'v set and
    p :: ('a, 'v) Profile
  assume
    card-n: n ≤ card A and
    fin-A: finite A and
    prof: profile V A p
  let ?inv-rank = the-inv-into A (rank (limit A r))
  have lin-ord-limit: linear-order-on A (limit A r)
    using assms limit-presv-lin-ord
    by auto
  hence (limit A r) ⊆ A × A
    unfolding linear-order-on-def partial-order-on-def preorder-on-def refl-on-def
    by simp
  hence ∀ a ∈ A. (above (limit A r) a) ⊆ A
    unfolding above-def
    by auto
  hence leq: ∀ a ∈ A. rank (limit A r) a ≤ card A
    using fin-A
    by (simp add: card-mono)
  have ∀ a ∈ A. {a} ⊆ (above (limit A r) a)
    using lin-ord-limit
    unfolding linear-order-on-def partial-order-on-def
      preorder-on-def refl-on-def above-def

```

by *auto*  
 hence  $\forall a \in A. \text{card } \{a\} \leq \text{card } (\text{above } (\text{limit } A \ r) \ a)$   
 using *card-mono fin-A rev-finite-subset above-presv-limit*  
 by *metis*  
 hence *rank-geq-one*:  $\forall a \in A. 1 \leq \text{rank } (\text{limit } A \ r) \ a$   
 by *simp*  
 with *leq* have  $\forall a \in A. \text{rank } (\text{limit } A \ r) \ a \in \{1 \ .. \ \text{card } A\}$   
 by *simp*  
 hence  $\text{rank } (\text{limit } A \ r) \ 'A \subseteq \{1 \ .. \ \text{card } A\}$   
 by *auto*  
 moreover have *inj*:  $\text{inj-on } (\text{rank } (\text{limit } A \ r)) \ A$   
 using *fin-A inj-onI rank-unique lin-ord-limit*  
 by *metis*  
 ultimately have *bij-A*:  $\text{bij-betw } (\text{rank } (\text{limit } A \ r)) \ A \ \{1 \ .. \ \text{card } A\}$   
 using *bij-betw-def bij-betw-finite bij-betw-iff-card card-seteq*  
     *dual-order.refl ex-bij-betw-nat-finite-1 fin-A*  
 by *metis*  
 hence *bij-inv*:  $\text{bij-betw } ?\text{inv-rank } \{1 \ .. \ \text{card } A\} \ A$   
 using *bij-betw-the-inv-into*  
 by *blast*  
 hence  $\forall S \subseteq \{1 \ .. \ \text{card } A\}. \text{card } (? \text{inv-rank } 'S) = \text{card } S$   
 using *fin-A bij-betw-same-card bij-betw-subset*  
 by *metis*  
 moreover have *subset*:  $\{1 \ .. \ n\} \subseteq \{1 \ .. \ \text{card } A\}$   
 using *card-n*  
 by *simp*  
 ultimately have  $\text{card } (? \text{inv-rank } ' \{1 \ .. \ n\}) = n$   
 using *numeral-One numeral-eq-iff card-atLeastAtMost diff-Suc-1*  
 by *presburger*  
 also have  $? \text{inv-rank } ' \{1 \ .. \ n\} = \{a \in A. \text{rank } (\text{limit } A \ r) \ a \in \{1 \ .. \ n\}\}$   
 proof  
   show  $? \text{inv-rank } ' \{1 \ .. \ n\} \subseteq \{a \in A. \text{rank } (\text{limit } A \ r) \ a \in \{1 \ .. \ n\}\}$   
   proof  
     fix  $a :: 'a$   
     assume  $a \in ? \text{inv-rank } ' \{1 \ .. \ n\}$   
     then obtain  $b :: \text{nat}$  where  
        $b \text{-img}: b \in \{1 \ .. \ n\} \wedge ? \text{inv-rank } b = a$   
     by *auto*  
     hence  $\text{rank } (\text{limit } A \ r) \ a = b$   
     using *subset f-the-inv-into-f-bij-betw subsetD bij-A*  
     by *metis*  
     hence  $\text{rank } (\text{limit } A \ r) \ a \in \{1 \ .. \ n\}$   
     using *b-img*  
     by *simp*  
   moreover have  $a \in A$   
   using *b-img bij-inv bij-betwE subset*  
   by *blast*  
   ultimately show  $a \in \{a \in A. \text{rank } (\text{limit } A \ r) \ a \in \{1 \ .. \ n\}\}$   
   by *blast*



```

qed
next
show  $\{a \in A. \text{rank } (\text{limit } A \ r) \ a \in \{1 \ .. \ n\}\}$ 
 $\subseteq \text{the-inv-into } A \ (\text{rank } (\text{limit } A \ r)) \ ' \{1 \ .. \ n\}$ 
proof
  fix a :: 'a
  assume el:  $a \in \{a \in A. \text{rank } (\text{limit } A \ r) \ a \in \{1 \ .. \ n\}\}$ 
  then obtain b :: nat where
    b-img:  $b \in \{1..n\} \wedge \text{rank } (\text{limit } A \ r) \ a = b$ 
  by auto
  moreover have  $a \in A$ 
  using el
  by simp
  ultimately have ?inv-rank b = a
  using inj the-inv-into-f-f
  by metis
  thus  $a \in ?inv\text{-rank } ' \{1 \ .. \ n\}$ 
  using b-img
  by auto
qed
qed
finally have  $\text{card } \{a \in A. \text{rank } (\text{limit } A \ r) \ a \in \{1 \ .. \ n\}\} = n$ 
  by blast
also have  $\{a \in A. \text{rank } (\text{limit } A \ r) \ a \in \{1 \ .. \ n\}\} =$ 
 $\{a \in A. \text{rank } (\text{limit } A \ r) \ a \leq n\}$ 
  using rank-geq-one
  by auto
also have  $\dots = \text{reject } (\text{drop-module } n \ r) \ V \ A \ p$ 
  by simp
finally show  $\text{card } (\text{reject } (\text{drop-module } n \ r) \ V \ A \ p) = n$ 
  by blast
qed

```

The pass and drop module are (disjoint-)compatible.

```

theorem drop-pass-disj-compat[simp]:
  fixes
    r :: 'a Preference-Relation and
    n :: nat
  assumes linear-order r
  shows disjoint-compatibility (drop-module n r) (pass-module n r)
proof (unfold disjoint-compatibility-def, safe)
  show SCF-result.electoral-module (drop-module n r)
    using assms drop-mod-sound
    by simp
next
  show SCF-result.electoral-module (pass-module n r)
    using assms pass-mod-sound
    by simp
next

```

```

fix
   $A :: 'a \text{ set}$  and
   $V :: 'b \text{ set}$ 
have  $\text{linear-order-on } A \text{ (limit } A \text{ } r)$ 
  using  $\text{assms limit-presv-lin-ord}$ 
  by  $\text{blast}$ 
hence  $\text{profile } V \text{ } A \text{ } (\lambda v. \text{limit } A \text{ } r)$ 
  using  $\text{profile-def}$ 
  by  $\text{blast}$ 
then obtain  $p :: ('a, 'b) \text{ Profile}$  where
   $\text{profile } V \text{ } A \text{ } p$ 
  by  $\text{blast}$ 
show  $\exists B \subseteq A. (\forall a \in B. \text{indep-of-alt (drop-module } n \text{ } r) \text{ } V \text{ } A \text{ } a \wedge$ 
   $(\forall p. \text{profile } V \text{ } A \text{ } p \longrightarrow a \in \text{reject (drop-module } n \text{ } r) \text{ } V \text{ } A \text{ } p)) \wedge$ 
   $(\forall a \in A - B. \text{indep-of-alt (pass-module } n \text{ } r) \text{ } V \text{ } A \text{ } a \wedge$ 
   $(\forall p. \text{profile } V \text{ } A \text{ } p \longrightarrow a \in \text{reject (pass-module } n \text{ } r) \text{ } V \text{ } A \text{ } p)))$ 
proof
  have  $\text{same-}A$ :
     $\forall p \ q. (\text{profile } V \text{ } A \text{ } p \wedge \text{profile } V \text{ } A \text{ } q) \longrightarrow$ 
     $\text{reject (drop-module } n \text{ } r) \text{ } V \text{ } A \text{ } p = \text{reject (drop-module } n \text{ } r) \text{ } V \text{ } A \text{ } q$ 
    by  $\text{auto}$ 
  let  $?A = \text{reject (drop-module } n \text{ } r) \text{ } V \text{ } A \text{ } p$ 
  have  $?A \subseteq A$ 
    by  $\text{auto}$ 
  moreover have  $\forall a \in ?A. \text{indep-of-alt (drop-module } n \text{ } r) \text{ } V \text{ } A \text{ } a$ 
    using  $\text{assms drop-mod-sound}$ 
    unfolding  $\text{drop-module.simps indep-of-alt-def}$ 
    by  $(\text{metis (mono-tags, lifting)})$ 
  moreover have
     $\forall a \in ?A. \forall p. \text{profile } V \text{ } A \text{ } p$ 
     $\longrightarrow a \in \text{reject (drop-module } n \text{ } r) \text{ } V \text{ } A \text{ } p$ 
    by  $\text{auto}$ 
  moreover have  $\forall a \in A - ?A. \text{indep-of-alt (pass-module } n \text{ } r) \text{ } V \text{ } A \text{ } a$ 
    using  $\text{assms pass-mod-sound}$ 
    unfolding  $\text{pass-module.simps indep-of-alt-def}$ 
    by  $\text{metis}$ 
  moreover have
     $\forall a \in A - ?A. \forall p.$ 
     $\text{profile } V \text{ } A \text{ } p \longrightarrow a \in \text{reject (pass-module } n \text{ } r) \text{ } V \text{ } A \text{ } p$ 
    by  $\text{auto}$ 
  ultimately show  $?A \subseteq A \wedge$ 
     $(\forall a \in ?A. \text{indep-of-alt (drop-module } n \text{ } r) \text{ } V \text{ } A \text{ } a \wedge$ 
     $(\forall p. \text{profile } V \text{ } A \text{ } p \longrightarrow a \in \text{reject (drop-module } n \text{ } r) \text{ } V \text{ } A \text{ } p)) \wedge$ 
     $(\forall a \in A - ?A. \text{indep-of-alt (pass-module } n \text{ } r) \text{ } V \text{ } A \text{ } a \wedge$ 
     $(\forall p. \text{profile } V \text{ } A \text{ } p \longrightarrow a \in \text{reject (pass-module } n \text{ } r) \text{ } V \text{ } A \text{ } p)))$ 
    by  $\text{simp}$ 
qed
qed

```

end

## 6.2 Revision Composition

**theory** *Revision-Composition*  
**imports** *Basic-Modules/Component-Types/Electoral-Module*  
**begin**

A revised electoral module rejects all originally rejected or deferred alternatives, and defers the originally elected alternatives. It does not elect any alternatives.

### 6.2.1 Definition

**fun** *revision-composition* :: ('a, 'v, 'a Result) Electoral-Module  $\Rightarrow$   
 ('a, 'v, 'a Result) Electoral-Module **where**  
*revision-composition* m V A p = ({}, A - elect m V A p, elect m V A p)

**abbreviation** *rev* :: ('a, 'v, 'a Result) Electoral-Module  $\Rightarrow$   
 ('a, 'v, 'a Result) Electoral-Module ( $\downarrow$  50) **where**  
*m* $\downarrow$   $\equiv$  *revision-composition* m

### 6.2.2 Soundness

**theorem** *rev-comp-sound[simp]*:  
**fixes** m :: ('a, 'v, 'a Result) Electoral-Module  
**assumes** *SCF-result.electoral-module* m  
**shows** *SCF-result.electoral-module* (*revision-composition* m)  
**proof** -  
**from** *assms*  
**have**  $\forall$  A V p. *profile* V A p  $\longrightarrow$  *elect* m V A p  $\subseteq$  A  
**using** *elect-in-alts*  
**by** *metis*  
**hence**  $\forall$  A V p. *profile* V A p  $\longrightarrow$  (A - *elect* m V A p)  $\cup$  *elect* m V A p = A  
**by** *blast*  
**hence**  $\forall$  A V p. *profile* V A p  $\longrightarrow$   
*set-equals-partition* A (*revision-composition* m V A p)  
**by** *simp*  
**moreover** **have**  $\forall$  A V p. *profile* V A p  $\longrightarrow$  (A - *elect* m V A p)  $\cap$  *elect* m V  
A p = {}  
**by** *blast*  
**hence**  $\forall$  A V p. *profile* V A p  $\longrightarrow$  *disjoint3* (*revision-composition* m V A p)  
**by** *simp*  
**ultimately show** *?thesis*  
**by** *simp*

qed

**lemma** *voters-determine-rev-comp*:  
  **fixes**  $m :: ('a, 'v, 'a \text{ Result}) \text{ Electoral-Module}$   
  **assumes** *voters-determine-election*  $m$   
  **shows** *voters-determine-election* (*revision-composition*  $m$ )  
  **using** *assms*  
  **unfolding** *voters-determine-election.simps* *revision-composition.simps*  
  **by** *presburger*

### 6.2.3 Composition Rules

An electoral module received by revision is never electing.

**theorem** *rev-comp-non-electing[simp]*:  
  **fixes**  $m :: ('a, 'v, 'a \text{ Result}) \text{ Electoral-Module}$   
  **assumes** *SCF-result.electoral-module*  $m$   
  **shows** *non-electing* ( $m \downarrow$ )  
  **using** *assms fstI rev-comp-sound revision-composition.simps*  
  **using** *non-electing-def*  
  **by** *metis*

Revising an electing electoral module results in a non-blocking electoral module.

**theorem** *rev-comp-non-blocking[simp]*:  
  **fixes**  $m :: ('a, 'v, 'a \text{ Result}) \text{ Electoral-Module}$   
  **assumes** *electing*  $m$   
  **shows** *non-blocking* ( $m \downarrow$ )  
**proof** (*unfold non-blocking-def, safe*)  
  **show** *SCF-result.electoral-module* ( $m \downarrow$ )  
    **using** *assms rev-comp-sound*  
    **unfolding** *electing-def*  
    **by** (*metis (no-types, lifting)*)  
**next**  
  **fix**  
     $A :: 'a \text{ set}$  **and**  
     $V :: 'v \text{ set}$  **and**  
     $p :: ('a, 'v) \text{ Profile}$  **and**  
     $x :: 'a$   
  **assume**  
     $\text{fin-}A$ : *finite*  $A$  **and**  
     $\text{prof-}A$ : *profile*  $V A p$  **and**  
     $\text{reject-}A$ : *reject* ( $m \downarrow$ )  $V A p = A$  **and**  
     $\text{x-in-}A$ :  $x \in A$   
  **hence** *non-electing*  $m$   
    **using** *assms empty-iff Diff-disjoint Int-absorb2*  
      *elect-in-alts prod.collapse prod.inject*  
    **unfolding** *electing-def* *revision-composition.simps*  
    **by** (*metis (no-types, lifting)*)

```

thus  $x \in \{\}$ 
  using assms fin-A prof-A x-in-A
  unfolding electing-def non-electing-def
  by (metis (no-types, lifting))
qed

```

Revising an invariant monotone electoral module results in a defer-invariant-monotone electoral module.

```

theorem rev-comp-def-inv-mono[simp]:
  fixes  $m :: ('a, 'v, 'a \text{ Result}) \text{ Electoral-Module}$ 
  assumes invariant-monotonicity m
  shows defer-invariant-monotonicity (m↓)
proof (unfold defer-invariant-monotonicity-def, safe)
  show SCF-result.electoral-module (m↓)
    using assms rev-comp-sound
    unfolding invariant-monotonicity-def
    by metis
next
  show non-electing (m↓)
    using assms rev-comp-non-electing
    unfolding invariant-monotonicity-def
    by simp
next
  fix
     $A :: 'a \text{ set}$  and
     $V :: 'v \text{ set}$  and
     $p \ q :: ('a, 'v) \text{ Profile}$  and
     $a \ x \ x' :: 'a$ 
  assume
    rev-p-defer-a: a ∈ defer (m↓) V A p and
    a-lifted: lifted V A p q a and
    rev-q-defer-x: x ∈ defer (m↓) V A q and
    x-non-eq-a: x ≠ a and
    rev-q-defer-x': x' ∈ defer (m↓) V A q
  from rev-p-defer-a
  have elect-a-in-p: a ∈ elect m V A p
    by simp
  from rev-q-defer-x x-non-eq-a
  have elect-no-unique-a-in-q: elect m V A q ≠ {a}
    by force
  from assms
  have elect m V A q = elect m V A p
    using a-lifted elect-a-in-p elect-no-unique-a-in-q
    unfolding invariant-monotonicity-def
    by (metis (no-types))
  thus  $x' \in \text{defer } (m\downarrow) \ V \ A \ p$ 
    using rev-q-defer-x'
    by simp
next

```

```

fix
   $A :: 'a \text{ set}$  and
   $V :: 'v \text{ set}$  and
   $p \ q :: ('a, 'v) \text{ Profile}$  and
   $a \ x \ x' :: 'a$ 
assume
   $\text{rev-p-defer-a}: a \in \text{defer } (m\downarrow) \ V \ A \ p$  and
   $\text{a-lifted}: \text{lifted } V \ A \ p \ q \ a$  and
   $\text{rev-q-defer-x}: x \in \text{defer } (m\downarrow) \ V \ A \ q$  and
   $\text{x-non-eq-a}: x \neq a$  and
   $\text{rev-p-defer-x'}: x' \in \text{defer } (m\downarrow) \ V \ A \ p$ 
have  $\text{reject-and-defer}:$ 
   $(A - \text{elect } m \ V \ A \ q, \text{elect } m \ V \ A \ q) = \text{snd } ((m\downarrow) \ V \ A \ q)$ 
by  $\text{force}$ 
have  $\text{elect-p-eq-defer-rev-p}: \text{elect } m \ V \ A \ p = \text{defer } (m\downarrow) \ V \ A \ p$ 
by  $\text{simp}$ 
hence  $\text{elect-a-in-p}: a \in \text{elect } m \ V \ A \ p$ 
using  $\text{rev-p-defer-a}$ 
by  $\text{presburger}$ 
have  $\text{elect } m \ V \ A \ q \neq \{a\}$ 
using  $\text{rev-q-defer-x} \ \text{x-non-eq-a}$ 
by  $\text{force}$ 
with  $\text{assms}$ 
show  $x' \in \text{defer } (m\downarrow) \ V \ A \ q$ 
using  $\text{a-lifted} \ \text{rev-p-defer-x'} \ \text{snd-conv} \ \text{elect-a-in-p}$ 
   $\text{elect-p-eq-defer-rev-p} \ \text{reject-and-defer}$ 
unfolding  $\text{invariant-monotonicity-def}$ 
by  $(\text{metis } (\text{no-types}))$ 
next
fix
   $A :: 'a \text{ set}$  and
   $V :: 'v \text{ set}$  and
   $p \ q :: ('a, 'v) \text{ Profile}$  and
   $a \ x \ x' :: 'a$ 
assume
   $a \in \text{defer } (m\downarrow) \ V \ A \ p$  and
   $\text{lifted } V \ A \ p \ q \ a$  and
   $x' \in \text{defer } (m\downarrow) \ V \ A \ q$ 
with  $\text{assms}$ 
show  $x' \in \text{defer } (m\downarrow) \ V \ A \ p$ 
using  $\text{empty-iff} \ \text{insertE} \ \text{snd-conv} \ \text{revision-composition.elims}$ 
unfolding  $\text{invariant-monotonicity-def}$ 
by  $\text{metis}$ 
next
fix
   $A :: 'a \text{ set}$  and
   $V :: 'v \text{ set}$  and
   $p \ q :: ('a, 'v) \text{ Profile}$  and
   $a \ x \ x' :: 'a$ 

```

```

assume
  rev-p-defer-a:  $a \in \text{defer } (m \downarrow) \ V \ A \ p$  and
  a-lifted:  $\text{lifted } V \ A \ p \ q \ a$  and
  rev-q-not-defer-a:  $a \notin \text{defer } (m \downarrow) \ V \ A \ q$ 
moreover from assms
have lifted-inv:
   $\forall \ A \ V \ p \ q \ a. \ a \in \text{elect } m \ V \ A \ p \wedge \text{lifted } V \ A \ p \ q \ a \longrightarrow$ 
   $\text{elect } m \ V \ A \ q = \text{elect } m \ V \ A \ p \vee \text{elect } m \ V \ A \ q = \{a\}$ 
  unfolding invariant-monotonicity-def
  by (metis (no-types))
moreover have p-defer-rev-eq-elect:  $\text{defer } (m \downarrow) \ V \ A \ p = \text{elect } m \ V \ A \ p$ 
  by simp
moreover have defer (m down) V A q = elect m V A q
  by simp
ultimately show  $x' \in \text{defer } (m \downarrow) \ V \ A \ q$ 
  using rev-p-defer-a rev-q-not-defer-a
  by blast
qed

end

```

## 6.3 Sequential Composition

```

theory Sequential-Composition
imports Basic-Modules/Component-Types/Electoral-Module
begin

```

The sequential composition creates a new electoral module from two electoral modules. In a sequential composition, the second electoral module makes decisions over alternatives deferred by the first electoral module.

### 6.3.1 Definition

```

fun sequential-composition :: ('a, 'v, 'a Result) Electoral-Module  $\Rightarrow$ 
  ('a, 'v, 'a Result) Electoral-Module  $\Rightarrow$ 
  ('a, 'v, 'a Result) Electoral-Module where
  sequential-composition m n V A p =
    (let new-A = defer m V A p;
     new-p = limit-profile new-A p in (
       (elect m V A p)  $\cup$  (elect n V new-A new-p),
       (reject m V A p)  $\cup$  (reject n V new-A new-p),
       defer n V new-A new-p))

abbreviation sequence :: ('a, 'v, 'a Result) Electoral-Module  $\Rightarrow$ 

```

```

      ('a, 'v, 'a Result) Electoral-Module  $\Rightarrow$  ('a, 'v, 'a Result) Electoral-Module
    (infix  $\triangleright$  50) where
      m  $\triangleright$  n  $\equiv$  sequential-composition m n

fun sequential-composition' :: ('a, 'v, 'a Result) Electoral-Module  $\Rightarrow$ 
      ('a, 'v, 'a Result) Electoral-Module  $\Rightarrow$ 
      ('a, 'v, 'a Result) Electoral-Module where
      sequential-composition' m n V A p =
        (let (m-e, m-r, m-d) = m V A p; new-A = m-d;
            new-p = limit-profile new-A p;
            (n-e, n-r, n-d) = n V new-A new-p in
          (m-e  $\cup$  n-e, m-r  $\cup$  n-r, n-d))

lemma voters-determine-seq-comp:
  fixes m n :: ('a, 'v, 'a Result) Electoral-Module
  assumes voters-determine-election m  $\wedge$  voters-determine-election n
  shows voters-determine-election (m  $\triangleright$  n)
proof (unfold voters-determine-election.simps, clarify)
  fix
    A :: 'a set and
    V :: 'v set and
    p p' :: ('a, 'v) Profile
  assume coincide:  $\forall v \in V. p v = p' v$ 
  hence eq: m V A p = m V A p'  $\wedge$  n V A p = n V A p'
    using assms
    unfolding voters-determine-election.simps
    by blast
  hence coincide-limit:
     $\forall v \in V. \text{limit-profile } (\text{defer } m \text{ V A } p) p v =$ 
       $\text{limit-profile } (\text{defer } m \text{ V A } p') p' v$ 
    using coincide
    by simp
  moreover have
    elect m V A p
       $\cup$  elect n V (defer m V A p) (limit-profile (defer m V A p) p) =
    elect m V A p'
       $\cup$  elect n V (defer m V A p') (limit-profile (defer m V A p') p')
    using assms eq coincide-limit
    unfolding voters-determine-election.simps
    by metis
  moreover have
    reject m V A p
       $\cup$  reject n V (defer m V A p) (limit-profile (defer m V A p) p) =
    reject m V A p'
       $\cup$  reject n V (defer m V A p') (limit-profile (defer m V A p') p')
    using assms eq coincide-limit
    unfolding voters-determine-election.simps
    by metis
  moreover have

```



```

    defer n V (defer m V A p) (limit-profile (defer m V A p) p) =
    defer n V (defer m V A p') (limit-profile (defer m V A p') p')
  using assms eq coincide-limit
  unfolding voters-determine-election.simps
  by metis
ultimately show (m ▷ n) V A p = (m ▷ n) V A p'
  unfolding sequential-composition.simps
  by metis
qed

lemma seq-comp-presv-disj:
  fixes
    m n :: ('a, 'v, 'a Result) Electoral-Module and
    A :: 'a set and
    V :: 'v set and
    p :: ('a, 'v) Profile
  assumes
    module-m: SCF-result.electoral-module m and
    module-n: SCF-result.electoral-module n and
    prof: profile V A p
  shows disjoint3 ((m ▷ n) V A p)
proof -
  let ?new-A = defer m V A p
  let ?new-p = limit-profile ?new-A p
  have prof-def-lim: profile V (defer m V A p) (limit-profile (defer m V A p) p)
    using def-presv-prof prof module-m
    by metis
  have defer-in-A:
    ∀ A' V' p' m' a.
      (profile V' A' p' ∧
       SCF-result.electoral-module m' ∧
       a ∈ defer m' V' A' p') →
      a ∈ A'
    using UnCI result-presv-alts
    by (metis (mono-tags))
  from module-m prof
  have disjoint-m: disjoint3 (m V A p)
    unfolding SCF-result.electoral-module.simps well-formed-SCF.simps
    by blast
  from module-m module-n def-presv-prof prof
  have disjoint-n: disjoint3 (n V ?new-A ?new-p)
    unfolding SCF-result.electoral-module.simps well-formed-SCF.simps
    by metis
  have disj-n:
    elect m V A p ∩ reject m V A p = {} ∧
    elect m V A p ∩ defer m V A p = {} ∧
    reject m V A p ∩ defer m V A p = {}
    using prof module-m
    by (simp add: result-disj)

```

```

have reject n V (defer m V A p)
  (limit-profile (defer m V A p) p)
   $\subseteq$  defer m V A p
using def-presv-prof reject-in-alts prof module-m module-n
by metis
with disjoint-m module-m module-n prof
have elect-reject-diff: elect m V A p  $\cap$  reject n V ?new-A ?new-p = {}
  using disj-n
  by blast
from prof module-m module-n
have elec-n-in-def-m:
  elect n V (defer m V A p) (limit-profile (defer m V A p) p)  $\subseteq$  defer m V A p
  using def-presv-prof elect-in-alts
  by metis
have elect-defer-diff: elect m V A p  $\cap$  defer n V ?new-A ?new-p = {}
proof -
  obtain f :: 'a set  $\Rightarrow$  'a set  $\Rightarrow$  'a where
     $\forall B B'.$ 
     $(\exists a b. a \in B' \wedge b \in B \wedge a = b) =$ 
     $(f B B' \in B' \wedge (\exists a. a \in B \wedge f B B' = a))$ 
    using disjoint-iff
    by metis
  then obtain g :: 'a set  $\Rightarrow$  'a set  $\Rightarrow$  'a where
     $\forall B B'.$ 
     $(B \cap B' = \{\})$ 
     $\longrightarrow (\forall a b. a \in B \wedge b \in B' \longrightarrow a \neq b)) \wedge$ 
     $(B \cap B' \neq \{\})$ 
     $\longrightarrow f B B' \in B \wedge g B B' \in B' \wedge f B B' = g B B')$ 
    by auto
  thus ?thesis
  using defer-in-A disj-n module-n prof-def-lim prof
  by (metis (no-types, opaque-lifting))
qed
have rej-intersect-new-elect-empty:
  reject m V A p  $\cap$  elect n V ?new-A ?new-p = {}
  using disj-n disjoint-m disjoint-n def-presv-prof prof
  module-m module-n elec-n-in-def-m
  by blast
have (elect m V A p  $\cup$  elect n V ?new-A ?new-p)  $\cap$ 
  (reject m V A p  $\cup$  reject n V ?new-A ?new-p) = {}
proof (safe)
  fix x :: 'a
  assume
    x  $\in$  elect m V A p and
    x  $\in$  reject m V A p
  hence x  $\in$  elect m V A p  $\cap$  reject m V A p
  by simp
  thus x  $\in$  {}
  using disj-n

```

```

    by simp
next
  fix x :: 'a
  assume
    x ∈ elect m V A p and
    x ∈ reject n V (defer m V A p)
    (limit-profile (defer m V A p) p)
  thus x ∈ {}
  using elect-reject-diff
  by blast
next
  fix x :: 'a
  assume
    x ∈ elect n V (defer m V A p)
    (limit-profile (defer m V A p) p) and
    x ∈ reject m V A p
  thus x ∈ {}
  using rej-intersect-new-elect-empty
  by blast
next
  fix x :: 'a
  assume
    x ∈ elect n V (defer m V A p)
    (limit-profile (defer m V A p) p) and
    x ∈ reject n V (defer m V A p)
    (limit-profile (defer m V A p) p)
  thus x ∈ {}
  using disjoint-iff-not-equal module-n prof-def-lim result-disj prof
  by metis
qed
moreover have
  (elect m V A p ∪ elect n V ?new-A ?new-p)
  ∩ (defer n V ?new-A ?new-p) = {}
  using Int-Un-distrib2 Un-empty elect-defer-diff module-n
  prof-def-lim result-disj prof
  by (metis (no-types))
moreover have
  (reject m V A p ∪ reject n V ?new-A ?new-p)
  ∩ (defer n V ?new-A ?new-p) = {}
proof (safe)
  fix x :: 'a
  assume x ∈ defer n V (defer m V A p) (limit-profile (defer m V A p) p)
  hence x ∈ defer m V A p
  using defer-in-A module-n prof-def-lim prof
  by metis
moreover assume x ∈ reject m V A p
ultimately have x ∈ reject m V A p ∩ defer m V A p
  by fastforce
thus x ∈ {}

```

```

    using disj-n
    by blast
next
fix  $x :: 'a$ 
assume
 $x \in \text{defer } n \ V \ (\text{defer } m \ V \ A \ p) \ (\text{limit-profile } (\text{defer } m \ V \ A \ p) \ p)$  and
 $x \in \text{reject } n \ V \ (\text{defer } m \ V \ A \ p) \ (\text{limit-profile } (\text{defer } m \ V \ A \ p) \ p)$ 
thus  $x \in \{\}$ 
    using module-n prof-def-lim reject-not-elected-or-deferred
    by blast
qed
ultimately have
    disjoint3 ( $\text{elect } m \ V \ A \ p \cup \text{elect } n \ V \ ?\text{new-A } ?\text{new-p}$ ,
         $\text{reject } m \ V \ A \ p \cup \text{reject } n \ V \ ?\text{new-A } ?\text{new-p}$ ,
         $\text{defer } n \ V \ ?\text{new-A } ?\text{new-p}$ )
    by simp
thus ?thesis
    unfolding sequential-composition.simps
    by metis
qed

lemma seq-comp-presv-alts:
fixes
 $m \ n :: ('a, 'v, 'a \text{ Result}) \text{ Electoral-Module}$  and
 $A :: 'a \text{ set}$  and
 $V :: 'v \text{ set}$  and
 $p :: ('a, 'v) \text{ Profile}$ 
assumes
    module-m: SCF-result.electoral-module  $m$  and
    module-n: SCF-result.electoral-module  $n$  and
    prof: profile  $V \ A \ p$ 
shows set-equals-partition  $A \ ((m \triangleright n) \ V \ A \ p)$ 
proof -
let  $?new-A = \text{defer } m \ V \ A \ p$ 
let  $?new-p = \text{limit-profile } ?new-A \ p$ 
have elect-reject-diff:  $\text{elect } m \ V \ A \ p \cup \text{reject } m \ V \ A \ p \cup ?new-A = A$ 
    using module-m prof
    by (simp add: result-presv-alts)
have  $\text{elect } n \ V \ ?new-A \ ?new-p \cup$ 
     $\text{reject } n \ V \ ?new-A \ ?new-p \cup$ 
     $\text{defer } n \ V \ ?new-A \ ?new-p = ?new-A$ 
    using module-m module-n prof def-presv-prof result-presv-alts
    by metis
hence  $(\text{elect } m \ V \ A \ p \cup \text{elect } n \ V \ ?new-A \ ?new-p) \cup$ 
     $(\text{reject } m \ V \ A \ p \cup \text{reject } n \ V \ ?new-A \ ?new-p) \cup$ 
     $\text{defer } n \ V \ ?new-A \ ?new-p = A$ 
    using elect-reject-diff
    by blast
hence set-equals-partition  $A$ 

```

```

      (elect m V A p  $\cup$  elect n V ?new-A ?new-p,
       reject m V A p  $\cup$  reject n V ?new-A ?new-p,
       defer n V ?new-A ?new-p)
    by simp
  thus ?thesis
    unfolding sequential-composition.simps
    by metis
qed

lemma seq-comp-alt-eq[fundef-cong, code]: sequential-composition = sequential-composition'
proof (unfold sequential-composition'.simps sequential-composition.simps)
  have  $\forall m n V A E.$ 
    (case m V A E of (e, r, d)  $\Rightarrow$ 
     case n V d (limit-profile d E) of (e', r', d')  $\Rightarrow$ 
     (e  $\cup$  e', r  $\cup$  r', d')) =
    (elect m V A E
      $\cup$  elect n V (defer m V A E) (limit-profile (defer m V A E) E),
     reject m V A E
      $\cup$  reject n V (defer m V A E) (limit-profile (defer m V A E) E),
     defer n V (defer m V A E) (limit-profile (defer m V A E) E))
  using case-prod-beta'
  by (metis (no-types, lifting))
  thus
    ( $\lambda m n V A p.$ 
     let A' = defer m V A p; p' = limit-profile A' p in
     (elect m V A p  $\cup$  elect n V A' p',
      reject m V A p  $\cup$  reject n V A' p',
      defer n V A' p')) =
    ( $\lambda m n V A pr.$ 
     let (e, r, d) = m V A pr; A' = d; p' = limit-profile A' pr;
     (e', r', d') = n V A' p' in
     (e  $\cup$  e', r  $\cup$  r', d'))
  by metis
qed

```

### 6.3.2 Soundness

```

theorem seq-comp-sound[simp]:
  fixes m n :: ('a, 'v, 'a Result) Electoral-Module
  assumes
    SCF-result.electoral-module m and
    SCF-result.electoral-module n
  shows SCF-result.electoral-module (m  $\triangleright$  n)
proof (unfold SCF-result.electoral-module.simps, safe)
  fix
    A :: 'a set and
    V :: 'v set and
    p :: ('a, 'v) Profile
  assume profile V A p

```

**moreover have**  $\forall r. \text{well-formed-SCF } (A :: 'a \text{ set}) \ r =$   
 $(\text{disjoint3 } r \wedge \text{set-equals-partition } A \ r)$   
**by** *simp*  
**ultimately show**  $\text{well-formed-SCF } A \ ((m \triangleright n) \ V \ A \ p)$   
**using** *assms seq-comp-presv-disj seq-comp-presv-alts*  
**by** *metis*  
**qed**

### 6.3.3 Lemmas

**lemma** *seq-comp-decrease-only-defer*:

**fixes**  
 $m \ n :: ('a, 'v, 'a \text{ Result}) \text{ Electoral-Module}$  **and**  
 $A :: 'a \text{ set}$  **and**  
 $V :: 'v \text{ set}$  **and**  
 $p :: ('a, 'v) \text{ Profile}$   
**assumes**  
 $\text{module-}m: \text{SCF-result.electoral-module } m$  **and**  
 $\text{module-}n: \text{SCF-result.electoral-module } n$  **and**  
 $\text{prof: profile } V \ A \ p$  **and**  
 $\text{empty-defer: defer } m \ V \ A \ p = \{\}$   
**shows**  $(m \triangleright n) \ V \ A \ p = m \ V \ A \ p$   
**proof** –  
**have**  $\forall m' \ A' \ V' \ p'.$   
 $(\text{SCF-result.electoral-module } m' \wedge \text{profile } V' \ A' \ p') \longrightarrow$   
 $\text{profile } V' \ (\text{defer } m' \ V' \ A' \ p') \ (\text{limit-profile } (\text{defer } m' \ V' \ A' \ p') \ p')$   
**using** *def-presv-prof prof*  
**by** *metis*  
**hence**  $\text{prof-no-alt: profile } V \ \{\} \ (\text{limit-profile } (\text{defer } m \ V \ A \ p) \ p)$   
**using** *empty-defer prof module-m*  
**by** *metis*  
**show** *?thesis*  
**proof**  
**have**  $(\text{elect } m \ V \ A \ p)$   
 $\cup (\text{elect } n \ V \ (\text{defer } m \ V \ A \ p) \ (\text{limit-profile } (\text{defer } m \ V \ A \ p) \ p)) =$   
 $\text{elect } m \ V \ A \ p$   
**using** *elect-in-alts[of - - limit-profile (defer m V A p) p]*  
 $\text{empty-defer module-n prof prof-no-alt}$   
**by** *auto*  
**thus**  $\text{elect } (m \triangleright n) \ V \ A \ p = \text{elect } m \ V \ A \ p$   
**using** *fst-conv*  
**unfolding** *sequential-composition.simps*  
**by** *metis*  
**next**  
**have** *rej-empty*:  
 $\forall m' \ V' \ p'.$   
 $(\text{SCF-result.electoral-module } m'$   
 $\wedge \text{profile } V' \ \{\} \ p') \longrightarrow \text{reject } m' \ V' \ \{\} \ p' = \{\}$   
**using** *bot.extremum-uniqueI reject-in-alts*

```

    by metis
  have (reject m V A p, defer n V {} (limit-profile {} p)) = snd (m V A p)
    using bot.extremum-uniqueI defer-in-alts empty-defer
      module-n prod.collapse prof-no-alt
    by (metis (no-types))
  thus snd ((m ▷ n) V A p) = snd (m V A p)
    unfolding sequential-composition.simps
    using rej-empty empty-defer module-n prof-no-alt prof sndI sup-bot-right
    by metis
qed
qed

lemma seq-comp-def-then-elect:
  fixes
    m n :: ('a, 'v, 'a Result) Electoral-Module and
    A :: 'a set and
    V :: 'v set and
    p :: ('a, 'v) Profile
  assumes
    n-electing-m: non-electing m and
    def-one-m: defers 1 m and
    electing-n: electing n and
    f-prof: finite-profile V A p
  shows elect (m ▷ n) V A p = defer m V A p
proof (cases)
  assume A = {}
  with electing-n n-electing-m f-prof
  show ?thesis
    using bot.extremum-uniqueI defer-in-alts elect-in-alts seq-comp-sound
    unfolding electing-def non-electing-def
    by metis
next
  assume non-empty-A: A ≠ {}
  from n-electing-m f-prof
  have ele: elect m V A p = {}
    unfolding non-electing-def
    by simp
  from non-empty-A def-one-m f-prof finite
  have def-card: card (defer m V A p) = 1
    unfolding defers-def
    by (simp add: Suc-leI card-gt-0-iff)
  with n-electing-m f-prof
  have def: ∃ a ∈ A. defer m V A p = {a}
    using card-1-singletonE defer-in-alts singletonI subsetCE
    unfolding non-electing-def
    by metis
  from ele def n-electing-m
  have rej: ∃ a ∈ A. reject m V A p = A - {a}
    using Diff-empty def-one-m f-prof reject-not-elected-or-deferred

```

```

    unfolding defers-def
  by metis
from ele rej def n-electing-m f-prof
have res-m:  $\exists a \in A. m \vee A p = (\{\}, A - \{a\}, \{a\})$ 
  using Diff-empty elect-rej-def-combination reject-not-elected-or-deferred
  unfolding non-electing-def
  by metis
hence  $\exists a \in A. \text{elect } (m \triangleright n) \vee A p = \text{elect } n \vee \{a\} \text{ (limit-profile } \{a\} p)$ 
  using prod.sel sup-bot.left-neutral
  unfolding sequential-composition.simps
  by metis
with def-card def electing-n n-electing-m f-prof
have  $\exists a \in A. \text{elect } (m \triangleright n) \vee A p = \{a\}$ 
  using electing-for-only-alt fst-conv def-presv-prof sup-bot.left-neutral
  unfolding non-electing-def sequential-composition.simps
  by metis
with def def-card electing-n n-electing-m f-prof res-m
show ?thesis
  using def-presv-prof electing-for-only-alt fst-conv sup-bot.left-neutral
  unfolding non-electing-def sequential-composition.simps
  by metis
qed

```

**lemma** *seq-comp-def-card-bounded*:

```

fixes
  m n :: ('a, 'v, 'a Result) Electoral-Module and
  A :: 'a set and
  V :: 'v set and
  p :: ('a, 'v) Profile
assumes
  SCF-result.electoral-module m and
  SCF-result.electoral-module n and
  finite-profile V A p
shows card (defer (m  $\triangleright$  n) V A p)  $\leq$  card (defer m V A p)
  using card-mono defer-in-alts assms def-presv-prof snd-conv finite-subset
  unfolding sequential-composition.simps
  by metis

```

**lemma** *seq-comp-def-set-bounded*:

```

fixes
  m n :: ('a, 'v, 'a Result) Electoral-Module and
  A :: 'a set and
  V :: 'v set and
  p :: ('a, 'v) Profile
assumes
  SCF-result.electoral-module m and
  SCF-result.electoral-module n and
  profile V A p
shows defer (m  $\triangleright$  n) V A p  $\subseteq$  defer m V A p

```



**using** *defer-in-alts assms snd-conv def-presv-prof*  
**unfolding** *sequential-composition.simps*  
**by** *metis*

**lemma** *seq-comp-defers-def-set:*

**fixes**  
 $m\ n :: ('a, 'v, 'a\ Result)\ Electoral\ Module$  **and**  
 $A :: 'a\ set$  **and**  
 $V :: 'v\ set$  **and**  
 $p :: ('a, 'v)\ Profile$   
**shows**  $defer\ (m \triangleright n)\ V\ A\ p =$   
 $defer\ n\ V\ (defer\ m\ V\ A\ p)\ (limit\ profile\ (defer\ m\ V\ A\ p)\ p)$   
**using** *snd-conv*  
**unfolding** *sequential-composition.simps*  
**by** *metis*

**lemma** *seq-comp-def-then-elect-elec-set:*

**fixes**  
 $m\ n :: ('a, 'v, 'a\ Result)\ Electoral\ Module$  **and**  
 $A :: 'a\ set$  **and**  
 $V :: 'v\ set$  **and**  
 $p :: ('a, 'v)\ Profile$   
**shows**  $elect\ (m \triangleright n)\ V\ A\ p =$   
 $elect\ n\ V\ (defer\ m\ V\ A\ p)$   
 $(limit\ profile\ (defer\ m\ V\ A\ p)\ p) \cup (elect\ m\ V\ A\ p)$   
**using** *Un-commute fst-conv*  
**unfolding** *sequential-composition.simps*  
**by** *metis*

**lemma** *seq-comp-elim-one-red-def-set:*

**fixes**  
 $m\ n :: ('a, 'v, 'a\ Result)\ Electoral\ Module$  **and**  
 $A :: 'a\ set$  **and**  
 $V :: 'v\ set$  **and**  
 $p :: ('a, 'v)\ Profile$   
**assumes**  
 $SCF\ result.electoral\ module\ m$  **and**  
 $eliminates\ 1\ n$  **and**  
 $profile\ V\ A\ p$  **and**  
 $card\ (defer\ m\ V\ A\ p) > 1$   
**shows**  $defer\ (m \triangleright n)\ V\ A\ p \subset defer\ m\ V\ A\ p$   
**using** *assms snd-conv def-presv-prof single-elim-imp-red-def-set*  
**unfolding** *sequential-composition.simps*  
**by** *metis*

**lemma** *seq-comp-def-set-trans:*

**fixes**  
 $m\ n :: ('a, 'v, 'a\ Result)\ Electoral\ Module$  **and**  
 $A :: 'a\ set$  **and**

$V :: 'v \text{ set}$  **and**  
 $p :: ('a, 'v) \text{ Profile}$  **and**  
 $a :: 'a$   
**assumes**  
 $a \in (\text{defer } (m \triangleright n) \ V \ A \ p)$  **and**  
 $\text{SCF-result.electoral-module } m \wedge \text{SCF-result.electoral-module } n$  **and**  
 $\text{profile } V \ A \ p$   
**shows**  $a \in \text{defer } n \ V \ (\text{defer } m \ V \ A \ p) \ (\text{limit-profile } (\text{defer } m \ V \ A \ p) \ p) \wedge$   
 $a \in \text{defer } m \ V \ A \ p$   
**using** *seq-comp-def-set-bounded assms in-mono seq-comp-defers-def-set*  
**by** (*metis (no-types, opaque-lifting)*)

### 6.3.4 Composition Rules

The sequential composition preserves the non-blocking property.

**theorem** *seq-comp-presv-non-blocking[simp]*:  
**fixes**  $m \ n :: ('a, 'v, 'a \text{ Result}) \text{ Electoral-Module}$   
**assumes**  
 $\text{non-blocking-m: non-blocking } m$  **and**  
 $\text{non-blocking-n: non-blocking } n$   
**shows**  $\text{non-blocking } (m \triangleright n)$   
**proof** –  
**fix**  
 $A :: 'a \text{ set}$  **and**  
 $V :: 'v \text{ set}$  **and**  
 $p :: ('a, 'v) \text{ Profile}$   
**let**  $?input\text{-sound} = A \neq \{\} \wedge \text{finite-profile } V \ A \ p$   
**from**  $\text{non-blocking-m}$   
**have**  $?input\text{-sound} \longrightarrow \text{reject } m \ V \ A \ p \neq A$   
**unfolding**  $\text{non-blocking-def}$   
**by** *simp*  
**with**  $\text{non-blocking-m}$   
**have**  $A\text{-reject-diff: } ?input\text{-sound} \longrightarrow A - \text{reject } m \ V \ A \ p \neq \{\}$   
**using** *Diff-eq-empty-iff reject-in-alts subset-antisym*  
**unfolding**  $\text{non-blocking-def}$   
**by** *metis*  
**from**  $\text{non-blocking-m}$   
**have**  $?input\text{-sound} \longrightarrow \text{well-formed-SCF } A \ (m \ V \ A \ p)$   
**unfolding**  $\text{SCF-result.electoral-module.simps non-blocking-def}$   
**by** *simp*  
**hence**  $?input\text{-sound} \longrightarrow \text{elect } m \ V \ A \ p \cup \text{defer } m \ V \ A \ p = A - \text{reject } m \ V \ A \ p$   
**using**  $\text{non-blocking-m elec-and-def-not-rej}$   
**unfolding**  $\text{non-blocking-def}$   
**by** *metis*  
**with**  $A\text{-reject-diff}$   
**have**  $?input\text{-sound} \longrightarrow \text{elect } m \ V \ A \ p \cup \text{defer } m \ V \ A \ p \neq \{\}$   
**by** *simp*  
**hence**  $?input\text{-sound} \longrightarrow (\text{elect } m \ V \ A \ p \neq \{\} \vee \text{defer } m \ V \ A \ p \neq \{\})$   
**by** *simp*

```

with non-blocking-m non-blocking-n
show ?thesis
proof (unfold non-blocking-def)
  assume
    emod-reject-m:
    SCF-result.electoral-module m
     $\wedge (\forall A V p. A \neq \{\} \wedge \text{finite } A \wedge \text{profile } V A p$ 
       $\longrightarrow \text{reject } m V A p \neq A)$  and
    emod-reject-n:
    SCF-result.electoral-module n
     $\wedge (\forall A V p. A \neq \{\} \wedge \text{finite } A \wedge \text{profile } V A p$ 
       $\longrightarrow \text{reject } n V A p \neq A)$ 
  show
    SCF-result.electoral-module (m  $\triangleright$  n)
     $\wedge (\forall A V p. A \neq \{\} \wedge \text{finite } A \wedge \text{profile } V A p$ 
       $\longrightarrow \text{reject } (m \triangleright n) V A p \neq A)$ 
  proof (safe)
    show SCF-result.electoral-module (m  $\triangleright$  n)
      using emod-reject-m emod-reject-n seq-comp-sound
      by metis
  next
  fix
    A :: 'a set and
    V :: 'v set and
    p :: ('a, 'v) Profile and
    x :: 'a
  assume
    fin-A: finite A and
    prof-A: profile V A p and
    rej-mn: reject (m  $\triangleright$  n) V A p = A and
    x-in-A: x  $\in$  A
  from emod-reject-m fin-A prof-A
  have fin-defer:
    finite (defer m V A p)
     $\wedge \text{profile } V (\text{defer } m V A p) (\text{limit-profile } (\text{defer } m V A p) p)$ 
    using def-presv-prof defer-in-alts finite-subset
    by (metis (no-types))
  from emod-reject-m emod-reject-n fin-A prof-A
  have seq-elect:
    elect (m  $\triangleright$  n) V A p =
    elect n V (defer m V A p)
     $(\text{limit-profile } (\text{defer } m V A p) p) \cup \text{elect } m V A p$ 
    using seq-comp-def-then-elect-elec-set
    by metis
  from emod-reject-n emod-reject-m fin-A prof-A
  have def-limit:
    defer (m  $\triangleright$  n) V A p =
    defer n V (defer m V A p) (limit-profile (defer m V A p) p)
    using seq-comp-defers-def-set

```

```

    by metis
  from emod-reject-n emod-reject-m fin-A prof-A
  have elect (m ▷ n) V A p ∪ defer (m ▷ n) V A p =
    A - reject (m ▷ n) V A p
    using elec-and-def-not-rej seq-comp-sound
    by metis
  hence elect-def-disj:
    elect n V (defer m V A p) (limit-profile (defer m V A p) p) ∪
    elect m V A p ∪
    defer n V (defer m V A p) (limit-profile (defer m V A p) p) = {}
    using def-limit seq-elect Diff-cancel rej-mn
    by auto
  have rej-def-eq-set:
    defer n V (defer m V A p) (limit-profile (defer m V A p) p) -
    defer n V (defer m V A p) (limit-profile (defer m V A p) p) = {} →
    reject n V (defer m V A p) (limit-profile (defer m V A p) p) =
    defer m V A p
    using elect-def-disj emod-reject-n fin-defer
    by (simp add: reject-not-elected-or-deferred)
  have
    defer n V (defer m V A p) (limit-profile (defer m V A p) p) -
    defer n V (defer m V A p) (limit-profile (defer m V A p) p) = {} →
    elect m V A p = elect m V A p ∩ defer m V A p
    using elect-def-disj
    by blast
  thus x ∈ {}
    using rej-def-eq-set result-disj fin-defer Diff-cancel Diff-empty fin-A prof-A
    emod-reject-m emod-reject-n reject-not-elected-or-deferred x-in-A
    by metis
qed
qed
qed

```

Sequential composition preserves the non-electing property.

```

theorem seq-comp-presv-non-electing[simp]:
  fixes m n :: ('a, 'v, 'a Result) Electoral-Module
  assumes
    non-electing m and
    non-electing n
  shows non-electing (m ▷ n)
proof (unfold non-electing-def, safe)
  have SCF-result.electoral-module m ∧ SCF-result.electoral-module n
    using assms
    unfolding non-electing-def
    by blast
  thus SCF-result.electoral-module (m ▷ n)
    using seq-comp-sound
    by metis
next

```

```

fix
   $A :: 'a \text{ set}$  and
   $V :: 'v \text{ set}$  and
   $p :: ('a, 'v) \text{ Profile}$  and
   $x :: 'a$ 
assume
   $\text{profile } V \ A \ p$  and
   $x \in \text{elect } (m \triangleright n) \ V \ A \ p$ 
thus  $x \in \{\}$ 
using assms
unfolding non-electing-def
using seq-comp-def-then-elect-elec-set def-presv-prof Diff-empty Diff-partition
  empty-subsetI
by metis
qed

```

Composing an electoral module that defers exactly 1 alternative in sequence after an electoral module that is electing results (still) in an electing electoral module.

```

theorem seq-comp-electing[simp]:
  fixes  $m \ n :: ('a, 'v, 'a \text{ Result}) \text{ Electoral-Module}$ 
  assumes
     $\text{def-one-}m$ :  $\text{defers } 1 \ m$  and
     $\text{electing-}n$ :  $\text{electing } n$ 
  shows  $\text{electing } (m \triangleright n)$ 
proof –
  have defer-card-eq-one:
     $\forall \ A \ V \ p. (\text{card } A \geq 1 \wedge \text{finite } A \wedge \text{profile } V \ A \ p) \longrightarrow \text{card } (\text{defer } m \ V \ A \ p) = 1$ 
    using def-one-m
    unfolding defers-def
    by metis
  hence def-m-not-empty:
     $\forall \ A \ V \ p. (A \neq \{\} \wedge \text{finite } A \wedge \text{profile } V \ A \ p) \longrightarrow \text{defer } m \ V \ A \ p \neq \{\}$ 
    using One-nat-def Suc-leI card-eq-0-iff card-gt-0-iff zero-neq-one
    by metis
  thus ?thesis
proof –
  have  $\forall \ m'.$ 
     $(\neg \text{electing } m' \vee \text{SCF-result.electoral-module } m'$ 
     $\wedge (\forall \ A' \ V' \ p'. (A' \neq \{\} \wedge \text{finite } A' \wedge \text{profile } V' \ A' \ p') \longrightarrow \text{elect } m' \ V' \ A' \ p' \neq \{\}))$ 
     $\wedge (\text{electing } m' \vee \neg \text{SCF-result.electoral-module } m' \vee$ 
     $(\exists \ A \ V \ p. (A \neq \{\} \wedge \text{finite } A \wedge \text{profile } V \ A \ p \wedge \text{elect } m' \ V \ A \ p = \{\})))$ 
    unfolding electing-def
    by blast
  hence  $\forall \ m'.$ 
     $(\neg \text{electing } m' \vee \text{SCF-result.electoral-module } m'$ 
     $\wedge (\forall \ A' \ V' \ p'. (A' \neq \{\} \wedge \text{finite } A' \wedge \text{profile } V' \ A' \ p'))$ 

```

$\longrightarrow \text{elect } m' \ V' \ A' \ p' \neq \{\})$   
 $\wedge (\exists \ A \ V \ p. (\text{electing } m' \vee \neg \text{SCF-result.electoral-module } m' \vee A \neq \{}$   
 $\wedge \text{finite } A \wedge \text{profile } V \ A \ p \wedge \text{elect } m' \ V \ A \ p = \{\}))$   
**by simp**  
**then obtain**  
 $A :: ('a, 'v, 'a \text{ Result}) \text{ Electoral-Module} \Rightarrow 'a \text{ set}$  **and**  
 $V :: ('a, 'v, 'a \text{ Result}) \text{ Electoral-Module} \Rightarrow 'v \text{ set}$  **and**  
 $p :: ('a, 'v, 'a \text{ Result}) \text{ Electoral-Module} \Rightarrow ('a, 'v) \text{ Profile}$  **where**  
*f-mod:*  
 $\forall \ m' :: ('a, 'v, 'a \text{ Result}) \text{ Electoral-Module.}$   
 $(\neg \text{electing } m' \vee \neg \text{SCF-result.electoral-module } m' \wedge$   
 $(\forall \ A' \ V' \ p'. (A' \neq \{ \} \wedge \text{finite } A' \wedge \text{profile } V' \ A' \ p'))$   
 $\longrightarrow \text{elect } m' \ V' \ A' \ p' \neq \{\}))$   
 $\wedge (\text{electing } m' \vee \neg \text{SCF-result.electoral-module } m' \vee A \ m' \neq \{ \}$   
 $\wedge \text{finite } (A \ m') \wedge \text{profile } (V \ m') \ (A \ m') \ (p \ m')$   
 $\wedge \text{elect } m' \ (V \ m') \ (A \ m') \ (p \ m') = \{\})$   
**by metis**  
**hence f-elect:**  
 $\text{SCF-result.electoral-module } n \wedge$   
 $(\forall \ A \ V \ p. (A \neq \{ \} \wedge \text{finite } A \wedge \text{profile } V \ A \ p) \longrightarrow \text{elect } n \ V \ A \ p \neq \{\})$   
**using electing-n**  
**unfolding electing-def**  
**by metis**  
**have def-card-one:**  
 $\text{SCF-result.electoral-module } m$   
 $\wedge (\forall \ A \ V \ p. (1 \leq \text{card } A \wedge \text{finite } A \wedge \text{profile } V \ A \ p)$   
 $\longrightarrow \text{card } (\text{defer } m \ V \ A \ p) = 1)$   
**using def-one-m defer-card-eq-one**  
**unfolding defers-def**  
**by blast**  
**hence SCF-result.electoral-module**  $(m \triangleright n)$   
**using f-elect seq-comp-sound**  
**by metis**  
**with f-mod f-elect def-card-one**  
**show ?thesis**  
**using seq-comp-def-then-elect-elec-set def-presv-prof defer-in-alts**  
 $\text{def-m-not-empty bot-eq-sup-iff finite-subset}$   
**unfolding electing-def**  
**by metis**  
**qed**  
**qed**  
**lemma def-lift-inv-seq-comp-help:**  
**fixes**  
 $m \ n :: ('a, 'v, 'a \text{ Result}) \text{ Electoral-Module}$  **and**  
 $A :: 'a \text{ set}$  **and**  
 $V :: 'v \text{ set}$  **and**  
 $p \ q :: ('a, 'v) \text{ Profile}$  **and**  
 $a :: 'a$

**assumes**  
*monotone-m: defer-lift-invariance m and*  
*monotone-n: defer-lift-invariance n and*  
*voters-determine-n: voters-determine-election n and*  
*def-and-lifted:  $a \in (\text{defer } (m \triangleright n) \ V \ A \ p) \wedge \text{lifted } V \ A \ p \ q \ a$*   
**shows**  $(m \triangleright n) \ V \ A \ p = (m \triangleright n) \ V \ A \ q$   
**proof** –  
**let**  $?new\text{-}Ap = \text{defer } m \ V \ A \ p$   
**let**  $?new\text{-}Aq = \text{defer } m \ V \ A \ q$   
**let**  $?new\text{-}p = \text{limit-profile } ?new\text{-}Ap \ p$   
**let**  $?new\text{-}q = \text{limit-profile } ?new\text{-}Aq \ q$   
**from** *monotone-m monotone-n*  
**have** *modules: SCF-result.electoral-module m  $\wedge$  SCF-result.electoral-module n*  
**unfolding** *defer-lift-invariance-def*  
**by** *simp*  
**hence**  $\text{profile } V \ A \ p \longrightarrow \text{defer } (m \triangleright n) \ V \ A \ p \subseteq \text{defer } m \ V \ A \ p$   
**using** *seq-comp-def-set-bounded*  
**by** *metis*  
**moreover** **have** *profile-p: lifted V A p q a  $\longrightarrow$  finite-profile V A p*  
**unfolding** *lifted-def*  
**by** *simp*  
**ultimately** **have** *defer-subset: defer (m  $\triangleright$  n) V A p  $\subseteq$  defer m V A p*  
**using** *def-and-lifted*  
**by** *blast*  
**hence** *mono-m: m V A p = m V A q*  
**using** *monotone-m def-and-lifted modules profile-p*  
*seq-comp-def-set-trans*  
**unfolding** *defer-lift-invariance-def*  
**by** *metis*  
**hence** *new-A-eq: ?new-Ap = ?new-Aq*  
**by** *presburger*  
**have** *defer-eq: defer (m  $\triangleright$  n) V A p = defer n V ?new-Ap ?new-p*  
**using** *snd-conv*  
**unfolding** *sequential-composition.simps*  
**by** *metis*  
**have** *mono-n: n V ?new-Ap ?new-p = n V ?new-Aq ?new-q*  
**proof** (*cases*)  
**assume** *lifted V ?new-Ap ?new-p ?new-q a*  
**thus** *?thesis*  
**using** *defer-eq mono-m monotone-n def-and-lifted*  
**unfolding** *defer-lift-invariance-def*  
**by** (*metis (no-types, lifting)*)  
**next**  
**assume** *unlifted-a:  $\neg \text{lifted } V \ ?new\text{-}Ap \ ?new\text{-}p \ ?new\text{-}q \ a$*   
**from** *def-and-lifted*  
**have** *finite-profile V A q*  
**unfolding** *lifted-def*  
**by** *simp*  
**with** *modules new-A-eq*

```

have prof-p: profile V ?new-Ap ?new-q
  using def-presv-prof
  by (metis (no-types))
moreover from modules profile-p def-and-lifted
have prof-q: profile V ?new-Ap ?new-p
  using def-presv-prof
  by (metis (no-types))
moreover from defer-subset def-and-lifted
have a ∈ ?new-Ap
  by blast
ultimately have lifted-stmt:
  (∃ v ∈ V.
    Preference-Relation.lifted ?new-Ap (?new-p v) (?new-q v) a) →
  (∃ v ∈ V.
    ¬ Preference-Relation.lifted ?new-Ap (?new-p v) (?new-q v) a ∧
    (?new-p v) ≠ (?new-q v))
  using unlifted-a def-and-lifted defer-in-alts infinite-super modules profile-p
  unfolding lifted-def
  by metis
from def-and-lifted modules
have ∀ v ∈ V. (Preference-Relation.lifted A (p v) (q v) a ∨ (p v) = (q v))
  unfolding Profile.lifted-def
  by metis
with def-and-lifted modules mono-m
have ∀ v ∈ V.
  (Preference-Relation.lifted ?new-Ap (?new-p v) (?new-q v) a ∨
   (?new-p v) = (?new-q v))
  using limit-lifted-imp-eq-or-lifted defer-in-alts
  unfolding Profile.lifted-def limit-profile.simps
  by (metis (no-types, lifting))
with lifted-stmt
have ∀ v ∈ V. (?new-p v) = (?new-q v)
  by blast
with mono-m
show ?thesis
  using leI not-less-zero nth-equalityI voters-determine-n
  unfolding voters-determine-election.simps
  by presburger
qed
from mono-m mono-n
show ?thesis
  unfolding sequential-composition.simps
  by (metis (full-types))
qed

```

Sequential composition preserves the property defer-lift-invariance.

```

theorem seq-comp-presv-def-lift-inv[simp]:
  fixes m n :: ('a, 'v, 'a Result) Electoral-Module
  assumes

```



```

    defer-lift-invariance m and
    defer-lift-invariance n and
    voters-determine-election n
  shows defer-lift-invariance (m ▷ n)
proof (unfold defer-lift-invariance-def, safe)
  show SCF-result.electoral-module (m ▷ n)
    using assms seq-comp-sound
    unfolding defer-lift-invariance-def
    by blast
next
fix
  A :: 'a set and
  V :: 'v set and
  p q :: ('a, 'v) Profile and
  a :: 'a
assume
  a ∈ defer (m ▷ n) V A p and
  Profile.lifted V A p q a
thus (m ▷ n) V A p = (m ▷ n) V A q
  unfolding defer-lift-invariance-def
  using assms def-lift-inv-seq-comp-help
  by metis
qed

```

Composing a non-blocking, non-electing electoral module in sequence with an electoral module that defers exactly one alternative results in an electoral module that defers exactly one alternative.

```

theorem seq-comp-def-one[simp]:
  fixes m n :: ('a, 'v, 'a Result) Electoral-Module
  assumes
    non-blocking-m: non-blocking m and
    non-electing-m: non-electing m and
    def-one-n: defers 1 n
  shows defers 1 (m ▷ n)
proof (unfold defers-def, safe)
  have SCF-result.electoral-module m
    using non-electing-m
    unfolding non-electing-def
    by simp
  moreover have SCF-result.electoral-module n
    using def-one-n
    unfolding defers-def
    by simp
  ultimately show SCF-result.electoral-module (m ▷ n)
    using seq-comp-sound
    by metis
next
fix
  A :: 'a set and

```

```

  V :: 'v set and
  p :: ('a, 'v) Profile
assume
  pos-card: 1 ≤ card A and
  fin-A: finite A and
  prof-A: profile V A p
from pos-card
have A ≠ {}
  by auto
with fin-A prof-A
have reject m V A p ≠ A
  using non-blocking-m
  unfolding non-blocking-def
  by simp
hence ∃ a. a ∈ A ∧ a ∉ reject m V A p
  using non-electing-m reject-in-alts fin-A prof-A
  card-seteq infinite-super subsetI upper-card-bound-for-reject
  unfolding non-electing-def
  by metis
hence defer m V A p ≠ {}
  using electoral-mod-defer-elem empty-iff non-electing-m fin-A prof-A
  unfolding non-electing-def
  by (metis (no-types))
hence card (defer m V A p) ≥ 1
  using Suc-leI card-gt-0-iff fin-A prof-A
  non-blocking-m defer-in-alts infinite-super
  unfolding One-nat-def non-blocking-def
  by metis
moreover have
  ∀ i m'. defers i m' =
    (SCF-result.electoral-module m' ∧
     (∀ A' V' p'. (i ≤ card A' ∧ finite A' ∧ profile V' A' p') →
      card (defer m' V' A' p') = i))
  unfolding defers-def
  by simp
ultimately have
  card (defer n V (defer m V A p) (limit-profile (defer m V A p) p)) = 1
  using def-one-n fin-A prof-A non-blocking-m def-presv-prof
  card.infinite not-one-le-zero
  unfolding non-blocking-def
  by metis
moreover have
  defer (m ▷ n) V A p =
    defer n V (defer m V A p) (limit-profile (defer m V A p) p)
  using seq-comp-defers-def-set
  by (metis (no-types, opaque-lifting))
ultimately show card (defer (m ▷ n) V A p) = 1
  by simp
qed

```

Composing a defer-lift invariant and a non-electing electoral module that defers exactly one alternative in sequence with an electing electoral module results in a monotone electoral module.

**theorem** *disj-compat-seq[simp]*:  
**fixes**  $m\ m'\ n :: ('a, 'v, 'a\ Result)\ Electoral\ Module$   
**assumes**  
     *compatible: disjoint-compatibility*  $m\ n$  **and**  
     *module-m': SCF-result.electoral-module*  $m'$  **and**  
     *voters-determine-m': voters-determine-election*  $m'$   
**shows** *disjoint-compatibility*  $(m \triangleright m')\ n$   
**proof** (*unfold disjoint-compatibility-def, safe*)  
**show** *SCF-result.electoral-module*  $(m \triangleright m')$   
     **using** *compatible module-m' seq-comp-sound*  
     **unfolding** *disjoint-compatibility-def*  
     **by** *metis*  
**next**  
**show** *SCF-result.electoral-module*  $n$   
     **using** *compatible*  
     **unfolding** *disjoint-compatibility-def*  
     **by** *metis*  
**next**  
**fix**  
      $S :: 'a\ set$  **and**  
      $V :: 'v\ set$   
**have** *modules:*  
     *SCF-result.electoral-module*  $(m \triangleright m') \wedge$  *SCF-result.electoral-module*  $n$   
     **using** *compatible module-m' seq-comp-sound*  
     **unfolding** *disjoint-compatibility-def*  
     **by** *metis*  
**obtain**  $A :: 'a\ set$  **where**  
     *rej-A:*  
      $A \subseteq S \wedge$   
      $(\forall\ a \in A.$   
         *indep-of-alt*  $m\ V\ S\ a \wedge (\forall\ p.\ profile\ V\ S\ p \longrightarrow a \in reject\ m\ V\ S\ p)) \wedge$   
      $(\forall\ a \in S - A.$   
         *indep-of-alt*  $n\ V\ S\ a \wedge (\forall\ p.\ profile\ V\ S\ p \longrightarrow a \in reject\ n\ V\ S\ p))$   
     **using** *compatible*  
     **unfolding** *disjoint-compatibility-def*  
     **by** (*metis (no-types, lifting)*)  
**show**  
      $\exists\ A \subseteq S.$   
      $(\forall\ a \in A.\ i\!n\!d\!e\!p\!-\!o\!f\!-\!a\!l\!t\ (m \triangleright m')\ V\ S\ a \wedge$   
          $(\forall\ p.\ profile\ V\ S\ p \longrightarrow a \in reject\ (m \triangleright m')\ V\ S\ p)) \wedge$   
      $(\forall\ a \in S - A.$   
         *indep-of-alt*  $n\ V\ S\ a \wedge (\forall\ p.\ profile\ V\ S\ p \longrightarrow a \in reject\ n\ V\ S\ p))$   
**proof**  
     **have**  $\forall\ a\ p\ q.\ a \in A \wedge equiv\text{-}prof\text{-}except\text{-}a\ V\ S\ p\ q\ a \longrightarrow$   
          $(m \triangleright m')\ V\ S\ p = (m \triangleright m')\ V\ S\ q$   
     **proof** (*safe*)

```

fix
  a :: 'a and
  p q :: ('a, 'v) Profile
assume
  a-in-A: a ∈ A and
  lifting-equiv-p-q: equiv-prof-except-a V S p q a
hence eq-defer: defer m V S p = defer m V S q
  using rej-A
  unfolding indep-of-alt-def
  by metis
have profiles: profile V S p ∧ profile V S q
  using lifting-equiv-p-q
  unfolding equiv-prof-except-a-def
  by simp
hence (defer m V S p) ⊆ S
  using compatible defer-in-alts
  unfolding disjoint-compatibility-def
  by metis
moreover have a ∉ defer m V S q
  using a-in-A compatible profiles rej-A IntI emptyE result-disj
  unfolding disjoint-compatibility-def
  by metis
ultimately have
  ∀ v ∈ V. limit-profile (defer m V S p) p v =
    limit-profile (defer m V S q) q v
  using lifting-equiv-p-q negl-diff-imp-eq-limit-prof[of - S]
  unfolding eq-defer limit-profile.simps
  by blast
hence m' V (defer m V S p) (limit-profile (defer m V S p) p) =
  m' V (defer m V S q) (limit-profile (defer m V S q) q)
  using eq-defer voters-determine-m'
  by simp
moreover have m V S p = m V S q
  using rej-A a-in-A lifting-equiv-p-q
  unfolding indep-of-alt-def
  by metis
ultimately show (m ▷ m') V S p = (m ▷ m') V S q
  unfolding sequential-composition.simps
  by (metis (full-types))
qed
moreover have ∀ a' ∈ A. ∀ p'. profile V S p' ⟶ a' ∈ reject (m ▷ m') V S p'
  using rej-A UnI1 prod.sel
  unfolding sequential-composition.simps
  by metis
ultimately show A ⊆ S ∧
  (∀ a' ∈ A. indep-of-alt (m ▷ m') V S a' ∧
    (∀ p'. profile V S p' ⟶ a' ∈ reject (m ▷ m') V S p')) ∧
  (∀ a' ∈ S - A. indep-of-alt n V S a' ∧
    (∀ p'. profile V S p' ⟶ a' ∈ reject n V S p'))

```

```

    using rej-A indep-of-alt-def modules
    by (metis (no-types, lifting))
qed
qed

theorem seq-comp-cond-compat[simp]:
  fixes m n :: ('a, 'v, 'a Result) Electoral-Module
  assumes
    dcc-m: defer-condorcet-consistency m and
    nb-n: non-blocking n and
    ne-n: non-electing n
  shows condorcet-compatibility (m ▷ n)
proof (unfold condorcet-compatibility-def, safe)
  have SCF-result.electoral-module m
    using dcc-m
    unfolding defer-condorcet-consistency-def
    by presburger
  moreover have SCF-result.electoral-module n
    using nb-n
    unfolding non-blocking-def
    by presburger
  ultimately have SCF-result.electoral-module (m ▷ n)
    using seq-comp-sound
    by metis
  thus SCF-result.electoral-module (m ▷ n)
    by presburger
next
fix
  A :: 'a set and
  V :: 'v set and
  p :: ('a, 'v) Profile and
  a :: 'a
assume
  cw-a: condorcet-winner V A p a and
  a-in-rej-seq-m-n: a ∈ reject (m ▷ n) V A p
hence  $\exists a'. \text{defer-condorcet-consistency } m \wedge \text{condorcet-winner } V A p a'$ 
  using dcc-m
  by blast
hence  $m \ V A \ p = (\{\}, A - (\text{defer } m \ V A \ p), \{a\})$ 
  using defer-condorcet-consistency-def cw-a cond-winner-unique
  by (metis (no-types, lifting))
have sound-m: SCF-result.electoral-module m
  using dcc-m
  unfolding defer-condorcet-consistency-def
  by presburger
moreover have SCF-result.electoral-module n
  using nb-n
  unfolding non-blocking-def
  by presburger

```

**ultimately have** *sound-seq-m-n*: *SCF-result.electoral-module* ( $m \triangleright n$ )  
**using** *seq-comp-sound*  
**by** *metis*  
**have** *def-m*:  $\text{defer } m \ V \ A \ p = \{a\}$   
**using** *cw-a cond-winner-unique dcc-m snd-conv*  
**unfolding** *defer-condorcet-consistency-def*  
**by** (*metis* (*mono-tags*, *lifting*))  
**have** *rej-m*:  $\text{reject } m \ V \ A \ p = A - \{a\}$   
**using** *cw-a cond-winner-unique dcc-m prod.sel*  
**unfolding** *defer-condorcet-consistency-def*  
**by** (*metis* (*mono-tags*, *lifting*))  
**have** *elect-m*:  $\text{elect } m \ V \ A \ p = \{\}$   
**using** *cw-a def-m rej-m dcc-m fst-conv*  
**unfolding** *defer-condorcet-consistency-def*  
**by** (*metis* (*mono-tags*, *lifting*))  
**hence** *diff-elect-m*:  $A - \text{elect } m \ V \ A \ p = A$   
**using** *Diff-empty*  
**by** (*metis* (*full-types*))  
**have** *cond-win*:  
 $\text{finite } A \wedge \text{finite } V \wedge \text{profile } V \ A \ p$   
 $\wedge a \in A \wedge (\forall a'. a' \in A - \{a\} \longrightarrow \text{wins } V \ a \ p \ a')$   
**using** *cw-a condorcet-winner.simps DiffD2 singletonI*  
**by** (*metis* (*no-types*))  
**have**  $\forall a' A'. (a' :: 'a) \in A' \longrightarrow \text{insert } a' (A' - \{a'\}) = A'$   
**by** *blast*  
**have** *nb-n-full*:  
 $\text{SCF-result.electoral-module } n \wedge$   
 $(\forall A' V' p'. A' \neq \{\} \wedge \text{finite } A' \wedge \text{finite } V' \wedge \text{profile } V' \ A' \ p'$   
 $\longrightarrow \text{reject } n \ V' \ A' \ p' \neq A')$   
**using** *nb-n non-blocking-def*  
**by** *metis*  
**have** *def-seq-diff*:  
 $\text{defer } (m \triangleright n) \ V \ A \ p = A - \text{elect } (m \triangleright n) \ V \ A \ p - \text{reject } (m \triangleright n) \ V \ A \ p$   
**using** *defer-not-elec-or-rej cond-win sound-seq-m-n*  
**by** *metis*  
**have** *set-ins*:  $\forall a' A'. (a' :: 'a) \in A' \longrightarrow \text{insert } a' (A' - \{a'\}) = A'$   
**by** *fastforce*  
**have**  $\forall p' A' p''. p' = (A' :: 'a \text{ set}, p'' :: 'a \text{ set} \times 'a \text{ set}) \longrightarrow \text{snd } p' = p''$   
**by** *simp*  
**hence**  
 $\text{snd } (\text{elect } m \ V \ A \ p$   
 $\cup \text{elect } n \ V \ (\text{defer } m \ V \ A \ p) \ (\text{limit-profile } (\text{defer } m \ V \ A \ p) \ p),$   
 $\text{reject } m \ V \ A \ p$   
 $\cup \text{reject } n \ V \ (\text{defer } m \ V \ A \ p) \ (\text{limit-profile } (\text{defer } m \ V \ A \ p) \ p),$   
 $\text{defer } n \ V \ (\text{defer } m \ V \ A \ p) \ (\text{limit-profile } (\text{defer } m \ V \ A \ p) \ p)) =$   
 $(\text{reject } m \ V \ A \ p$   
 $\cup \text{reject } n \ V \ (\text{defer } m \ V \ A \ p) \ (\text{limit-profile } (\text{defer } m \ V \ A \ p) \ p),$   
 $\text{defer } n \ V \ (\text{defer } m \ V \ A \ p) \ (\text{limit-profile } (\text{defer } m \ V \ A \ p) \ p))$

**by** *blast*  
**hence** *seq-snd-simplified*:  
 $snd ((m \triangleright n) \vee A p) =$   
 $(reject\ m\ \vee\ A\ p$   
 $\cup reject\ n\ \vee\ (defer\ m\ \vee\ A\ p)\ (limit-profile\ (defer\ m\ \vee\ A\ p)\ p),$   
 $defer\ n\ \vee\ (defer\ m\ \vee\ A\ p)\ (limit-profile\ (defer\ m\ \vee\ A\ p)\ p))$   
**using** *sequential-composition.simps*  
**by** *metis*  
**hence** *seq-rej-union-eq-rej*:  
 $reject\ m\ \vee\ A\ p$   
 $\cup reject\ n\ \vee\ (defer\ m\ \vee\ A\ p)\ (limit-profile\ (defer\ m\ \vee\ A\ p)\ p) =$   
 $reject\ (m \triangleright n) \vee A p$   
**by** *simp*  
**hence** *seq-rej-union-subset-A*:  
 $reject\ m\ \vee\ A\ p$   
 $\cup reject\ n\ \vee\ (defer\ m\ \vee\ A\ p)\ (limit-profile\ (defer\ m\ \vee\ A\ p)\ p) \subseteq A$   
**using** *sound-seq-m-n cond-win reject-in-alts*  
**by** (*metis* (*no-types*))  
**hence**  $A - \{a\} = reject\ (m \triangleright n) \vee A p - \{a\}$   
**using** *seq-rej-union-eq-rej defer-not-elec-or-rej cond-win def-m diff-elect-m*  
*double-diff rej-m sound-m sup-ge1*  
**by** (*metis* (*no-types*))  
**hence**  $reject\ (m \triangleright n) \vee A p \subseteq A - \{a\}$   
**using** *seq-rej-union-subset-A seq-snd-simplified set-ins def-seq-diff nb-n-full*  
*cond-win fst-conv Diff-empty Diff-eq-empty-iff a-in-rej-seq-m-n def-m*  
*def-presv-prof sound-m ne-n diff-elect-m insert-not-empty defer-in-alts*  
*reject-not-elected-or-deferred seq-comp-def-then-elect-elec-set finite-subset*  
*seq-comp-defers-def-set sup-bot.left-neutral*  
**unfolding** *non-electing-def*  
**by** (*metis* (*no-types*, *lifting*))  
**thus** *False*  
**using** *a-in-rej-seq-m-n*  
**by** *blast*  
**next**  
**fix**  
 $A :: 'a\ set$  **and**  
 $V :: 'v\ set$  **and**  
 $p :: ('a, 'v)\ Profile$  **and**  
 $a\ a' :: 'a$   
**assume**  
 $cw-a: condorcet-winner\ V\ A\ p\ a$  **and**  
 $not-cw-a': \neg condorcet-winner\ V\ A\ p\ a'$  **and**  
 $a'-in-elect-seq-m-n: a' \in elect\ (m \triangleright n) \vee A p$   
**hence**  $\exists\ a''. defer-condorcet-consistency\ m \wedge condorcet-winner\ V\ A\ p\ a''$   
**using** *dcc-m*  
**by** *blast*  
**hence** *result-m*:  $m\ \vee\ A\ p = (\{\}, A - (defer\ m\ \vee\ A\ p), \{a\})$   
**using** *defer-condorcet-consistency-def cw-a cond-winner-unique*  
**by** (*metis* (*no-types*, *lifting*))

**have** *sound-m*: *SCF-result.electoral-module m*  
**using** *dcc-m*  
**unfolding** *defer-condorcet-consistency-def*  
**by** *presburger*  
**moreover have** *SCF-result.electoral-module n*  
**using** *nb-n*  
**unfolding** *non-blocking-def*  
**by** *presburger*  
**ultimately have** *sound-seq-m-n*: *SCF-result.electoral-module (m ▷ n)*  
**using** *seq-comp-sound*  
**by** *metis*  
**have** *reject m V A p = A - {a}*  
**using** *cw-a dcc-m prod.sel result-m*  
**unfolding** *defer-condorcet-consistency-def*  
**by** (*metis (mono-tags, lifting)*)  
**hence** *a'-in-rej*: *a' ∈ reject m V A p*  
**using** *Diff-iff cw-a not-cw-a' a'-in-elect-seq-m-n subset-iff*  
*elect-in-alts singleton-iff sound-seq-m-n*  
**unfolding** *condorcet-winner.simps*  
**by** (*metis (no-types, lifting)*)  
**have**  $\forall p' A' p''. p' = (A' :: 'a \text{ set}, p'' :: 'a \text{ set} \times 'a \text{ set}) \longrightarrow \text{snd } p' = p''$   
**by** *simp*  
**hence** *m-seq-n*:  

$$\begin{aligned} & \text{snd } (\text{elect } m \text{ V } A \text{ p} \\ & \cup \text{elect } n \text{ V } (\text{defer } m \text{ V } A \text{ p}) (\text{limit-profile } (\text{defer } m \text{ V } A \text{ p}) \text{ p}), \\ & \text{reject } m \text{ V } A \text{ p} \\ & \cup \text{reject } n \text{ V } (\text{defer } m \text{ V } A \text{ p}) (\text{limit-profile } (\text{defer } m \text{ V } A \text{ p}) \text{ p}), \\ & \text{defer } n \text{ V } (\text{defer } m \text{ V } A \text{ p}) (\text{limit-profile } (\text{defer } m \text{ V } A \text{ p}) \text{ p})) = \\ & (\text{reject } m \text{ V } A \text{ p} \\ & \cup \text{reject } n \text{ V } (\text{defer } m \text{ V } A \text{ p}) (\text{limit-profile } (\text{defer } m \text{ V } A \text{ p}) \text{ p}), \\ & \text{defer } n \text{ V } (\text{defer } m \text{ V } A \text{ p}) (\text{limit-profile } (\text{defer } m \text{ V } A \text{ p}) \text{ p})) \end{aligned}$$
**by** *blast*  
**have** *a' ∈ elect m V A p*  
**using** *a'-in-elect-seq-m-n condorcet-winner.simps cw-a def-presv-prof ne-n*  
*seq-comp-def-then-elect-elec-set sound-m sup-bot.left-neutral*  
**unfolding** *non-electing-def*  
**by** (*metis (no-types)*)  
**hence** *a-in-rej-union*:  

$$\begin{aligned} & a \in \text{reject } m \text{ V } A \text{ p} \\ & \cup \text{reject } n \text{ V } (\text{defer } m \text{ V } A \text{ p}) (\text{limit-profile } (\text{defer } m \text{ V } A \text{ p}) \text{ p}) \end{aligned}$$
**using** *Diff-iff a'-in-rej condorcet-winner.simps cw-a*  
*reject-not-elected-or-deferred sound-m*  
**by** (*metis (no-types)*)  
**have** *m-seq-n-full*:  

$$\begin{aligned} & (m \triangleright n) \text{ V } A \text{ p} = \\ & (\text{elect } m \text{ V } A \text{ p} \\ & \cup \text{elect } n \text{ V } (\text{defer } m \text{ V } A \text{ p}) (\text{limit-profile } (\text{defer } m \text{ V } A \text{ p}) \text{ p}), \\ & \text{reject } m \text{ V } A \text{ p} \\ & \cup \text{reject } n \text{ V } (\text{defer } m \text{ V } A \text{ p}) (\text{limit-profile } (\text{defer } m \text{ V } A \text{ p}) \text{ p}), \end{aligned}$$



```

    defer n V (defer m V A p) (limit-profile (defer m V A p) p))
  unfolding sequential-composition.simps
  by metis
have  $\forall A' A''. (A' :: 'a \text{ set}) = \text{fst } (A', A'' :: 'a \text{ set})$ 
  by simp
hence  $a \in \text{reject } (m \triangleright n) V A p$ 
  using a-in-rej-union m-seq-n m-seq-n-full
  by presburger
moreover have
  finite A  $\wedge$  finite V  $\wedge$  profile V A p
 $\wedge a \in A \wedge (\forall a''. a'' \in A - \{a\} \longrightarrow \text{wins } V a p a'')$ 
  using cw-a m-seq-n-full a'-in-elect-seq-m-n a'-in-rej ne-n sound-m
  unfolding condorcet-winner.simps
  by metis
ultimately show False
  using a'-in-elect-seq-m-n IntI empty-iff result-disj sound-seq-m-n a'-in-rej def-presv-prof
    fst-conv m-seq-n-full ne-n non-electing-def sound-m sup-bot.right-neutral
  by metis
next
fix
  A :: 'a set and
  V :: 'v set and
  p :: ('a, 'v) Profile and
  a a' :: 'a
assume
  cw-a: condorcet-winner V A p a and
  a'-in-A:  $a' \in A$  and
  not-cw-a':  $\neg \text{condorcet-winner } V A p a'$ 
have  $\text{reject } m V A p = A - \{a\}$ 
  using cw-a cond-winner-unique dcc-m prod.sel
  unfolding defer-condorcet-consistency-def
  by (metis (mono-tags, lifting))
moreover have  $a \neq a'$ 
  using cw-a not-cw-a'
  by safe
ultimately have  $a' \in \text{reject } m V A p$ 
  using DiffI a'-in-A singletonD
  by (metis (no-types))
hence  $a' \in \text{reject } m V A p$ 
   $\cup \text{reject } n V (defer m V A p) (limit-profile (defer m V A p) p)$ 
  by blast
moreover have
   $(m \triangleright n) V A p =$ 
   $(\text{elect } m V A p$ 
   $\cup \text{elect } n V (defer m V A p) (limit-profile (defer m V A p) p),$ 
   $\text{reject } m V A p$ 
   $\cup \text{reject } n V (defer m V A p) (limit-profile (defer m V A p) p),$ 
   $\text{defer } n V (defer m V A p) (limit-profile (defer m V A p) p))$ 
  unfolding sequential-composition.simps

```

```

  by metis
moreover have
  snd (elect m V A p
    ∪ elect n V (defer m V A p) (limit-profile (defer m V A p) p),
    reject m V A p
    ∪ reject n V (defer m V A p) (limit-profile (defer m V A p) p),
    defer n V (defer m V A p) (limit-profile (defer m V A p) p)) =
    (reject m V A p
    ∪ reject n V (defer m V A p) (limit-profile (defer m V A p) p),
    defer n V (defer m V A p) (limit-profile (defer m V A p) p))
  using snd-conv
  by metis
ultimately show  $a' \in \text{reject } (m \triangleright n) V A p$ 
  using fst-eqD
  by (metis (no-types))
qed

```

Composing a defer-condorcet-consistent electoral module in sequence with a non-blocking and non-electing electoral module results in a defer-condorcet-consistent module.

```

theorem seq-comp-dcc[simp]:
  fixes  $m\ n :: ('a, 'v, 'a\ Result)\ Electoral\ Module$ 
  assumes
    dcc-m: defer-condorcet-consistency m and
    nb-n: non-blocking n and
    ne-n: non-electing n
  shows defer-condorcet-consistency  $(m \triangleright n)$ 
proof (unfold defer-condorcet-consistency-def, safe)
  have SCF-result.electoral-module m
    using dcc-m
    unfolding defer-condorcet-consistency-def
    by metis
  thus SCF-result.electoral-module  $(m \triangleright n)$ 
    using ne-n seq-comp-sound
    unfolding non-electing-def
    by metis
next
fix
  A :: 'a set and
  V :: 'v set and
  p :: ('a, 'v) Profile and
  a :: 'a
  assume cw-a: condorcet-winner V A p a
  hence  $\exists\ a'. \text{defer-condorcet-consistency } m \wedge \text{condorcet-winner } V A p a'$ 
    using dcc-m
    by blast
  hence result-m:  $m\ V\ A\ p = (\{\}, A - (\text{defer } m\ V\ A\ p), \{a\})$ 
    using defer-condorcet-consistency-def cw-a cond-winner-unique
    by (metis (no-types, lifting))

```

```

hence elect-m-empty: elect  $m \ V \ A \ p = \{\}$ 
  using eq-fst-iff
  by metis
have sound-m: SCF-result.electoral-module  $m$ 
  using dcc-m
  unfolding defer-condorcet-consistency-def
  by metis
hence sound-seq-m-n: SCF-result.electoral-module  $(m \triangleright n)$ 
  using ne-n seq-comp-sound
  unfolding non-electing-def
  by metis
have defer-eq-a: defer  $(m \triangleright n) \ V \ A \ p = \{a\}$ 
proof (safe)
  fix  $a' :: 'a$ 
  assume a'-in-def-seq-m-n:  $a' \in \text{defer } (m \triangleright n) \ V \ A \ p$ 
  have  $\{a\} = \{a \in A. \text{condorcet-winner } V \ A \ p \ a\}$ 
    using cond-winner-unique cw-a
    by metis
  moreover have defer-condorcet-consistency  $m \longrightarrow$ 
     $m \ V \ A \ p = (\{\}, A - \text{defer } m \ V \ A \ p, \{a \in A. \text{condorcet-winner } V \ A \ p \ a\})$ 
    using cw-a defer-condorcet-consistency-def
    by (metis (no-types))
  ultimately have defer  $m \ V \ A \ p = \{a\}$ 
    using dcc-m snd-conv
    by (metis (no-types, lifting))
  hence defer  $(m \triangleright n) \ V \ A \ p = \{a\}$ 
    using cw-a a'-in-def-seq-m-n empty-iff sound-m nb-n
    seq-comp-def-set-bounded subset-singletonD
    unfolding condorcet-winner.simps non-blocking-def
    by metis
  thus  $a' = a$ 
    using a'-in-def-seq-m-n
    by blast
next
  have  $\exists \ a'. \text{defer-condorcet-consistency } m \wedge \text{condorcet-winner } V \ A \ p \ a'$ 
    using cw-a dcc-m
    by blast
  hence  $m \ V \ A \ p = (\{\}, A - (\text{defer } m \ V \ A \ p), \{a\})$ 
    using defer-condorcet-consistency-def cw-a cond-winner-unique
    by (metis (no-types, lifting))
  hence elect-m-empty: elect  $m \ V \ A \ p = \{\}$ 
    using eq-fst-iff
    by metis
  have profile  $V \ (\text{defer } m \ V \ A \ p) \ (\text{limit-profile } (\text{defer } m \ V \ A \ p) \ p)$ 
    using condorcet-winner.simps cw-a def-presv-prof sound-m
    by (metis (no-types))
  hence elect  $n \ V \ (\text{defer } m \ V \ A \ p) \ (\text{limit-profile } (\text{defer } m \ V \ A \ p) \ p) = \{\}$ 
    using ne-n non-electing-def
    by metis

```

**hence**  $\text{elect } (m \triangleright n) \ V \ A \ p = \{\}$   
**using** *elect-m-empty seq-comp-def-then-elect-elec-set sup-bot.right-neutral*  
**by** (*metis (no-types)*)  
**moreover have** *condorcet-compatibility*  $(m \triangleright n)$   
**using** *dcc-m nb-n ne-n*  
**by** *simp*  
**hence**  $a \notin \text{reject } (m \triangleright n) \ V \ A \ p$   
**unfolding** *condorcet-compatibility-def*  
**using** *cw-a*  
**by** *metis*  
**ultimately show**  $a \in \text{defer } (m \triangleright n) \ V \ A \ p$   
**using** *cw-a electoral-mod-defer-elem empty-iff*  
*sound-seq-m-n condorcet-winner.simps*  
**by** *metis*  
**qed**  
**have** *profile*  $V \ (\text{defer } m \ V \ A \ p) \ (\text{limit-profile } (\text{defer } m \ V \ A \ p) \ p)$   
**using** *condorcet-winner.simps cw-a def-presv-prof sound-m*  
**by** (*metis (no-types)*)  
**hence**  $\text{elect } n \ V \ (\text{defer } m \ V \ A \ p) \ (\text{limit-profile } (\text{defer } m \ V \ A \ p) \ p) = \{\}$   
**using** *ne-n*  
**unfolding** *non-electing-def*  
**by** *metis*  
**hence**  $\text{elect } (m \triangleright n) \ V \ A \ p = \{\}$   
**using** *elect-m-empty seq-comp-def-then-elect-elec-set sup-bot.right-neutral*  
**by** (*metis (no-types)*)  
**moreover have** *def-seq-m-n-eq-a*:  $\text{defer } (m \triangleright n) \ V \ A \ p = \{a\}$   
**using** *cw-a defer-eq-a*  
**by** (*metis (no-types)*)  
**ultimately have**  $(m \triangleright n) \ V \ A \ p = (\{\}, A - \{a\}, \{a\})$   
**using** *Diff-empty cw-a elect-rej-def-combination*  
*reject-not-elected-or-deferred sound-seq-m-n condorcet-winner.simps*  
**by** (*metis (no-types)*)  
**moreover have**  $\{a' \in A. \text{condorcet-winner } V \ A \ p \ a'\} = \{a\}$   
**using** *cw-a cond-winner-unique*  
**by** *metis*  
**ultimately show**  $(m \triangleright n) \ V \ A \ p$   
 $= (\{\}, A - \text{defer } (m \triangleright n) \ V \ A \ p, \{a' \in A. \text{condorcet-winner } V \ A \ p \ a'\})$   
**using** *def-seq-m-n-eq-a*  
**by** *metis*  
**qed**

Composing a defer-lift invariant and a non-electing electoral module that defers exactly one alternative in sequence with an electing electoral module results in a monotone electoral module.

**theorem** *seq-comp-mono[simp]*:  
**fixes**  $m \ n :: ('a, 'v, 'a \text{ Result}) \text{Electoral-Module}$   
**assumes**  
*def-monotone-m: defer-lift-invariance m* **and**  
*non-ele-m: non-electing m* **and**

```

    def-one-m: defers 1 m and
    electing-n: electing n
  shows monotonicity (m ▷ n)
proof (unfold monotonicity-def, safe)
  have SCF-result.electoral-module m
    using non-ele-m
    unfolding non-electing-def
    by simp
  moreover have SCF-result.electoral-module n
    using electing-n
    unfolding electing-def
    by simp
  ultimately show SCF-result.electoral-module (m ▷ n)
    using seq-comp-sound
    by metis
next
fix
  A :: 'a set and
  V :: 'v set and
  p q :: ('a, 'v) Profile and
  w :: 'a
assume
  elect-w-in-p: w ∈ elect (m ▷ n) V A p and
  lifted-w: Profile.lifted V A p q w
thus w ∈ elect (m ▷ n) V A q
  unfolding lifted-def
  using seq-comp-def-then-elect lifted-w assms
  unfolding defer-lift-invariance-def
  by metis
qed

```

Composing a defer-invariant-monotone electoral module in sequence before a non-electing, defer-monotone electoral module that defers exactly 1 alternative results in a defer-lift-invariant electoral module.

```

theorem def-inv-mono-imp-def-lift-inv[simp]:
  fixes m n :: ('a, 'v, 'a Result) Electoral-Module
  assumes
    strong-def-mon-m: defer-invariant-monotonicity m and
    non-electing-n: non-electing n and
    defers-one: defers 1 n and
    defer-monotone-n: defer-monotonicity n and
    voters-determine-n: voters-determine-election n
  shows defer-lift-invariance (m ▷ n)
proof (unfold defer-lift-invariance-def, safe)
  have SCF-result.electoral-module m
    using strong-def-mon-m
    unfolding defer-invariant-monotonicity-def
    by metis
  moreover have SCF-result.electoral-module n

```

```

    using defers-one
    unfolding defers-def
    by metis
ultimately show SCF-result.electoral-module ( $m \triangleright n$ )
    using seq-comp-sound
    by metis
next
fix
  A :: 'a set and
  V :: 'v set and
  p q :: ('a, 'v) Profile and
  a :: 'a
assume
  defer-a-p:  $a \in \text{defer } (m \triangleright n) \ V \ A \ p$  and
  lifted-a:  $\text{Profile.lifted } V \ A \ p \ q \ a$ 
have non-electing-m: non-electing m
    using strong-def-mon-m
    unfolding defer-invariant-monotonicity-def
    by simp
have electoral-mod-m: SCF-result.electoral-module m
    using strong-def-mon-m
    unfolding defer-invariant-monotonicity-def
    by metis
have electoral-mod-n: SCF-result.electoral-module n
    using defers-one
    unfolding defers-def
    by metis
have finite-profile-p: finite-profile V A p
    using lifted-a
    unfolding Profile.lifted-def
    by simp
have finite-profile-q: finite-profile V A q
    using lifted-a
    unfolding Profile.lifted-def
    by simp
have 1 ≤ card A
    using Profile.lifted-def card-eq-0-iff emptyE less-one lifted-a linorder-le-less-linear
    by metis
hence n-defers-exactly-one-p:  $\text{card } (\text{defer } n \ V \ A \ p) = 1$ 
    using finite-profile-p defers-one
    unfolding defers-def
    by (metis (no-types))
have fin-prof-def-m-q:
  profile V (defer m V A q) (limit-profile (defer m V A q) q)
    using def-presv-prof electoral-mod-m finite-profile-q
    by (metis (no-types))
have def-seq-m-n-q:
  defer (m  $\triangleright$  n) V A q =
    defer n V (defer m V A q) (limit-profile (defer m V A q) q)

```

```

using seq-comp-defers-def-set
by simp
have prof-def-m:  $\text{profile } V (\text{defer } m \ V \ A \ p) (\text{limit-profile } (\text{defer } m \ V \ A \ p) \ p)$ 
  using def-presv-prof electoral-mod-m finite-profile-p
  by (metis (no-types))
hence prof-seq-comp-m-n:
   $\text{profile } V (\text{defer } n \ V (\text{defer } m \ V \ A \ p) (\text{limit-profile } (\text{defer } m \ V \ A \ p) \ p))$ 
     $(\text{limit-profile } (\text{defer } n \ V (\text{defer } m \ V \ A \ p) (\text{limit-profile } (\text{defer } m \ V \ A \ p) \ p)))$ 
     $(\text{limit-profile } (\text{defer } m \ V \ A \ p) \ p))$ 
  using def-presv-prof electoral-mod-n
  by (metis (no-types))
have a-non-empty:  $a \notin \{\}$ 
  by simp
have def-seq-m-n:
   $\text{defer } (m \triangleright n) \ V \ A \ p =$ 
     $\text{defer } n \ V (\text{defer } m \ V \ A \ p) (\text{limit-profile } (\text{defer } m \ V \ A \ p) \ p)$ 
  using seq-comp-defers-def-set
  by simp
have  $1 \leq \text{card } (\text{defer } n \ V (\text{defer } m \ V \ A \ p) (\text{limit-profile } (\text{defer } m \ V \ A \ p) \ p))$ 
  using a-non-empty card-gt-0-iff defer-a-p electoral-mod-n prof-def-m
    seq-comp-defers-def-set One-nat-def Suc-leI defer-in-alts
    electoral-mod-m finite-profile-p finite-subset
  by (metis (mono-tags))
hence  $\text{card } (\text{defer } n \ V (\text{defer } n \ V (\text{defer } m \ V \ A \ p)$ 
   $(\text{limit-profile } (\text{defer } m \ V \ A \ p) \ p))$ 
   $(\text{limit-profile } (\text{defer } n \ V (\text{defer } m \ V \ A \ p)$ 
   $(\text{limit-profile } (\text{defer } m \ V \ A \ p) \ p))$ 
   $(\text{limit-profile } (\text{defer } m \ V \ A \ p) \ p))) = 1$ 
  using n-defers-exactly-one-p prof-seq-comp-m-n defers-one defer-in-alts
    electoral-mod-m finite-profile-p finite-subset prof-def-m
  unfolding defers-def
  by metis
hence defer-seq-m-n-eq-one:  $\text{card } (\text{defer } (m \triangleright n) \ V \ A \ p) = 1$ 
  using One-nat-def Suc-leI a-non-empty card-gt-0-iff def-seq-m-n defer-a-p
    defers-one electoral-mod-m prof-def-m finite-profile-p
    seq-comp-def-set-trans defer-in-alts rev-finite-subset
  unfolding defers-def
  by metis
hence def-seq-m-n-eq-a:  $\text{defer } (m \triangleright n) \ V \ A \ p = \{a\}$ 
  using defer-a-p is-singleton-altdef is-singleton-the-elem singletonD
  by (metis (no-types))
show  $(m \triangleright n) \ V \ A \ p = (m \triangleright n) \ V \ A \ q$ 
proof (cases)
  assume  $\text{defer } m \ V \ A \ q \neq \text{defer } m \ V \ A \ p$ 
  hence  $\text{defer } m \ V \ A \ q = \{a\}$ 
  using defer-a-p electoral-mod-n finite-profile-p lifted-a seq-comp-def-set-trans
    strong-def-mon-m
  unfolding defer-invariant-monotonicity-def
  by (metis (no-types))

```

**moreover from** *this*  
**have**  $(a \in \text{defer } m \ V \ A \ p) \longrightarrow \text{card } (\text{defer } (m \triangleright n) \ V \ A \ q) = 1$   
**using** *card-eq-0-iff card-insert-disjoint defers-one electoral-mod-m empty-iff*  
*order-refl finite.emptyI seq-comp-defers-def-set def-presv-prof*  
*finite-profile-q finite.insertI*  
**unfolding** *One-nat-def defers-def*  
**by** *metis*  
**moreover have**  $a \in \text{defer } m \ V \ A \ p$   
**using** *electoral-mod-m electoral-mod-n defer-a-p seq-comp-def-set-bounded*  
*finite-profile-p finite-profile-q*  
**by** *blast*  
**ultimately have**  $\text{defer } (m \triangleright n) \ V \ A \ q = \{a\}$   
**using** *Collect-mem-eq card-1-singletonE empty-Collect-eq insertCI subset-singletonD*  
*def-seq-m-n-q defer-in-alts electoral-mod-n fin-prof-def-m-q*  
**by** *(metis (no-types, lifting))*  
**hence**  $\text{defer } (m \triangleright n) \ V \ A \ p = \text{defer } (m \triangleright n) \ V \ A \ q$   
**using** *def-seq-m-n-eq-a*  
**by** *presburger*  
**moreover have**  $\text{elect } (m \triangleright n) \ V \ A \ p = \text{elect } (m \triangleright n) \ V \ A \ q$   
**using** *prof-def-m fin-prof-def-m-q finite-profile-p finite-profile-q non-electing-def*  
*non-electing-m non-electing-n seq-comp-def-then-elect-elec-set*  
**by** *metis*  
**ultimately show** *?thesis*  
**using** *electoral-mod-m electoral-mod-n eq-def-and-elect-imp-eq*  
*finite-profile-p finite-profile-q seq-comp-sound*  
**by** *(metis (no-types))*  
**next**  
**assume**  $\neg (\text{defer } m \ V \ A \ q \neq \text{defer } m \ V \ A \ p)$   
**hence** *def-eq: defer m V A q = defer m V A p*  
**by** *presburger*  
**have**  $\text{elect } m \ V \ A \ p = \{\}$   
**using** *finite-profile-p non-electing-m*  
**unfolding** *non-electing-def*  
**by** *simp*  
**moreover have**  $\text{elect } m \ V \ A \ q = \{\}$   
**using** *finite-profile-q non-electing-m*  
**unfolding** *non-electing-def*  
**by** *simp*  
**ultimately have** *elect-m-equal:*  
 $\text{elect } m \ V \ A \ p = \text{elect } m \ V \ A \ q$   
**by** *simp*  
**have**  $(\forall v \in V. (\text{limit-profile } (\text{defer } m \ V \ A \ p) \ p) \ v =$   
 $\quad (\text{limit-profile } (\text{defer } m \ V \ A \ q) \ q) \ v)$   
 $\vee \text{lifted } V \ (\text{defer } m \ V \ A \ q) \ (\text{limit-profile } (\text{defer } m \ V \ A \ p) \ p)$   
 $\quad (\text{limit-profile } (\text{defer } m \ V \ A \ p) \ q) \ a$   
**using** *def-eq defer-in-alts electoral-mod-m lifted-a finite-profile-q*  
*limit-prof-eq-or-lifted*  
**by** *metis*  
**moreover have**



$(\forall v \in V. (\text{limit-profile } (\text{defer } m \ V \ A \ p) \ p) \ v =$   
 $\quad (\text{limit-profile } (\text{defer } m \ V \ A \ p) \ q) \ v)$   
 $\longrightarrow n \ V (\text{defer } m \ V \ A \ p) (\text{limit-profile } (\text{defer } m \ V \ A \ p) \ p) =$   
 $\quad n \ V (\text{defer } m \ V \ A \ q) (\text{limit-profile } (\text{defer } m \ V \ A \ q) \ q)$   
**using** *voters-determine-n def-eq*  
**unfolding** *voters-determine-election.simps*  
**by** *presburger*  
**moreover have**  
 $\text{lifted } V (\text{defer } m \ V \ A \ q) (\text{limit-profile } (\text{defer } m \ V \ A \ p) \ p)$   
 $\quad (\text{limit-profile } (\text{defer } m \ V \ A \ p) \ q) \ a$   
 $\longrightarrow \text{defer } n \ V (\text{defer } m \ V \ A \ p) (\text{limit-profile } (\text{defer } m \ V \ A \ p) \ p) =$   
 $\quad \text{defer } n \ V (\text{defer } m \ V \ A \ q) (\text{limit-profile } (\text{defer } m \ V \ A \ q) \ q)$   
**proof** (*intro impI*)  
**assume** *lifted*:  
 $\text{Profile.lifted } V (\text{defer } m \ V \ A \ q) (\text{limit-profile } (\text{defer } m \ V \ A \ p) \ p)$   
 $\quad (\text{limit-profile } (\text{defer } m \ V \ A \ p) \ q) \ a$   
**hence**  $a \in \text{defer } n \ V (\text{defer } m \ V \ A \ q) (\text{limit-profile } (\text{defer } m \ V \ A \ q) \ q)$   
**using** *lifted-a def-seq-m-n defer-a-p defer-monotone-n*  
 $\text{fin-prof-def-m-q def-eq}$   
**unfolding** *defer-monotonicity-def*  
**by** *metis*  
**hence**  $a \in \text{defer } (m \triangleright n) \ V \ A \ q$   
**using** *def-seq-m-n-q*  
**by** *simp*  
**moreover have**  $\text{card } (\text{defer } (m \triangleright n) \ V \ A \ q) = 1$   
**using** *def-seq-m-n-q defers-one def-eq defer-seq-m-n-eq-one defers-def lifted*  
 $\text{electoral-mod-m fin-prof-def-m-q finite-profile-p seq-comp-def-card-bounded}$   
 $\text{Profile.lifted-def}$   
**by** (*metis (no-types, lifting)*)  
**ultimately have**  $\text{defer } (m \triangleright n) \ V \ A \ q = \{a\}$   
**using** *a-non-empty card-1-singletonE insertE*  
**by** *metis*  
**thus**  $\text{defer } n \ V (\text{defer } m \ V \ A \ p) (\text{limit-profile } (\text{defer } m \ V \ A \ p) \ p)$   
 $= \text{defer } n \ V (\text{defer } m \ V \ A \ q) (\text{limit-profile } (\text{defer } m \ V \ A \ q) \ q)$   
**using** *def-seq-m-n-eq-a def-seq-m-n-q def-seq-m-n*  
**by** *presburger*  
**qed**  
**ultimately have**  $\text{defer } (m \triangleright n) \ V \ A \ p = \text{defer } (m \triangleright n) \ V \ A \ q$   
**using** *def-seq-m-n def-seq-m-n-q*  
**by** *presburger*  
**hence**  $\text{defer } (m \triangleright n) \ V \ A \ p = \text{defer } (m \triangleright n) \ V \ A \ q$   
**using** *a-non-empty def-eq def-seq-m-n def-seq-m-n-q*  
 $\text{defer-a-p defer-monotone-n finite-profile-p}$   
 $\text{defer-seq-m-n-eq-one defers-one electoral-mod-m}$   
 $\text{fin-prof-def-m-q}$   
**unfolding** *defers-def*  
**by** (*metis (no-types, lifting)*)  
**moreover from** *this*  
**have**  $\text{reject } (m \triangleright n) \ V \ A \ p = \text{reject } (m \triangleright n) \ V \ A \ q$

```

using electoral-mod-m electoral-mod-n finite-profile-p finite-profile-q non-electing-def
      non-electing-m non-electing-n eq-def-and-elect-imp-eq seq-comp-presv-non-electing
by (metis (no-types))
ultimately have  $\text{snd } ((m \triangleright n) \ V \ A \ p) = \text{snd } ((m \triangleright n) \ V \ A \ q)$ 
using prod-eqI
by metis
moreover have  $\text{elect } (m \triangleright n) \ V \ A \ p = \text{elect } (m \triangleright n) \ V \ A \ q$ 
using prof-def-m fin-prof-def-m-q non-electing-n finite-profile-p finite-profile-q
      non-electing-def def-eq elect-m-equal fst-conv
unfolding sequential-composition.simps
by (metis (no-types))
ultimately show  $(m \triangleright n) \ V \ A \ p = (m \triangleright n) \ V \ A \ q$ 
using prod-eqI
by metis
qed
qed
end

```

## 6.4 Parallel Composition

```

theory Parallel-Composition
imports Basic-Modules/Component-Types/Aggregator
        Basic-Modules/Component-Types/Electoral-Module
begin

```

The parallel composition composes a new electoral module from two electoral modules combined with an aggregator. Therein, the two modules each make a decision and the aggregator combines them to a single (aggregated) result.

### 6.4.1 Definition

```

fun parallel-composition :: ('a, 'v, 'a Result) Electoral-Module  $\Rightarrow$ 
    ('a, 'v, 'a Result) Electoral-Module  $\Rightarrow$  'a Aggregator  $\Rightarrow$ 
    ('a, 'v, 'a Result) Electoral-Module where
    parallel-composition m n agg V A p = agg A (m V A p) (n V A p)

abbreviation parallel :: ('a, 'v, 'a Result) Electoral-Module  $\Rightarrow$  'a Aggregator  $\Rightarrow$ 
    ('a, 'v, 'a Result) Electoral-Module  $\Rightarrow$  ('a, 'v, 'a Result) Electoral-Module
    (- ||- - [50, 1000, 51] 50) where
     $m \parallel_a n \equiv \text{parallel-composition } m \ n \ a$ 

```

### 6.4.2 Soundness

```

theorem par-comp-sound[simp]:

```

**fixes**  
 $m\ n :: ('a, 'v, 'a\ Result)\ \text{Electoral-Module}$  **and**  
 $a :: 'a\ \text{Aggregator}$   
**assumes**  
 $SCF\text{-result.electoral-module}\ m$  **and**  
 $SCF\text{-result.electoral-module}\ n$  **and**  
 $aggregator\ a$   
**shows**  $SCF\text{-result.electoral-module}\ (m \parallel_a n)$   
**proof** (*unfold*  $SCF\text{-result.electoral-module.simps}$ , *safe*)  
**fix**  
 $A :: 'a\ set$  **and**  
 $V :: 'v\ set$  **and**  
 $p :: ('a, 'v)\ Profile$   
**assume**  $profile\ V\ A\ p$   
**moreover have**  
 $\forall\ a'. aggregator\ a' =$   
 $(\forall\ A'\ e\ r\ d\ e'\ r'\ d'.$   
 $(well\text{-formed}\text{-}SCF\ (A' :: 'a\ set)\ (e, r', d)$   
 $\wedge\ well\text{-formed}\text{-}SCF\ A'\ (r, d', e'))$   
 $\longrightarrow well\text{-formed}\text{-}SCF\ A'\ (a'\ A'\ (e, r', d)\ (r, d', e')))$   
**unfolding**  $aggregator\text{-}def$   
**by** *blast*  
**moreover have**  
 $\forall\ m'\ V'\ A'\ p'.$   
 $(SCF\text{-result.electoral-module}\ m' \wedge\ finite\ (A' :: 'a\ set)$   
 $\wedge\ finite\ (V' :: 'v\ set) \wedge\ profile\ V'\ A'\ p')$   
 $\longrightarrow well\text{-formed}\text{-}SCF\ A'\ (m'\ V'\ A'\ p')$   
**using** *par-comp-result-sound*  
**by** (*metis* (*no-types*))  
**ultimately have**  $well\text{-formed}\text{-}SCF\ A\ (a\ A\ (m\ V\ A\ p)\ (n\ V\ A\ p))$   
**using** *elect-rej-def-combination assms*  
**by** (*metis* *par-comp-result-sound*)  
**thus**  $well\text{-formed}\text{-}SCF\ A\ ((m \parallel_a n)\ V\ A\ p)$   
**by** *simp*  
**qed**

### 6.4.3 Composition Rule

Using a conservative aggregator, the parallel composition preserves the property non-electing.

**theorem** *conserv-agg-presv-non-electing[simp]*:

**fixes**  
 $m\ n :: ('a, 'v, 'a\ Result)\ \text{Electoral-Module}$  **and**  
 $a :: 'a\ \text{Aggregator}$   
**assumes**  
 $non\text{-electing}\text{-}m: non\text{-electing}\ m$  **and**  
 $non\text{-electing}\text{-}n: non\text{-electing}\ n$  **and**  
 $conservative: agg\text{-}conservative\ a$   
**shows**  $non\text{-electing}\ (m \parallel_a n)$

```

proof (unfold non-electing-def, safe)
  have SCF-result.electoral-module m
    using non-electing-m
    unfolding non-electing-def
    by simp
  moreover have SCF-result.electoral-module n
    using non-electing-n
    unfolding non-electing-def
    by simp
  moreover have aggregator a
    using conservative
    unfolding agg-conservative-def
    by simp
  ultimately show SCF-result.electoral-module (m  $\parallel_a$  n)
    using par-comp-sound
    by simp
next
fix
  A :: 'a set and
  V :: 'v set and
  p :: ('a, 'v) Profile and
  w :: 'a
assume
  prof-A: profile V A p and
  w-wins: w  $\in$  elect (m  $\parallel_a$  n) V A p
have emod-m: SCF-result.electoral-module m
  using non-electing-m
  unfolding non-electing-def
  by simp
have emod-n: SCF-result.electoral-module n
  using non-electing-n
  unfolding non-electing-def
  by simp
have  $\forall r r' d d' e e' A' f.$ 
  ((well-formed-SCF (A' :: 'a set) (e', r', d')  $\wedge$ 
    well-formed-SCF A' (e, r, d))  $\longrightarrow$ 
    elect-r (f A' (e', r', d') (e, r, d))  $\subseteq$  e'  $\cup$  e  $\wedge$ 
    reject-r (f A' (e', r', d') (e, r, d))  $\subseteq$  r'  $\cup$  r  $\wedge$ 
    defer-r (f A' (e', r', d') (e, r, d))  $\subseteq$  d'  $\cup$  d) =
    ((well-formed-SCF A' (e', r', d')  $\wedge$ 
    well-formed-SCF A' (e, r, d))  $\longrightarrow$ 
    elect-r (f A' (e', r', d') (e, r, d))  $\subseteq$  e'  $\cup$  e  $\wedge$ 
    reject-r (f A' (e', r', d') (e, r, d))  $\subseteq$  r'  $\cup$  r  $\wedge$ 
    defer-r (f A' (e', r', d') (e, r, d))  $\subseteq$  d'  $\cup$  d)
  by linarith
hence  $\forall a'. \text{agg-conservative } a' =$ 
  (aggregator a'  $\wedge$ 
    ( $\forall A' e e' d d' r r'.$ 
      (well-formed-SCF (A' :: 'a set) (e, r, d)  $\wedge$ 

```

```

    well-formed-SCF A' (e', r', d') →
    elect-r (a' A' (e, r, d) (e', r', d')) ⊆ e ∪ e' ∧
    reject-r (a' A' (e, r, d) (e', r', d')) ⊆ r ∪ r' ∧
    defer-r (a' A' (e, r, d) (e', r', d')) ⊆ d ∪ d')
  unfolding agg-conservative-def
  by simp
  hence aggregator a ∧
    (∀ A' e e' d d' r r'.
      (well-formed-SCF A' (e, r, d) ∧
        well-formed-SCF A' (e', r', d')) →
        elect-r (a A' (e, r, d) (e', r', d')) ⊆ e ∪ e' ∧
        reject-r (a A' (e, r, d) (e', r', d')) ⊆ r ∪ r' ∧
        defer-r (a A' (e, r, d) (e', r', d')) ⊆ d ∪ d')
    using conservative
    by presburger
  hence let c = (a A (m V A p) (n V A p)) in
    (elect-r c ⊆ ((elect m V A p) ∪ (elect n V A p)))
    using emod-m emod-n par-comp-result-sound
    prod.collapse prof-A
    by metis
  hence w ∈ ((elect m V A p) ∪ (elect n V A p))
    using w-wins
    by auto
  thus w ∈ {}
    using sup-bot-right prof-A
    non-electing-m non-electing-n
    unfolding non-electing-def
    by (metis (no-types, lifting))
qed
end

```

## 6.5 Loop Composition

```

theory Loop-Composition
  imports Basic-Modules/Component-Types/Termination-Condition
         Basic-Modules/Defer-Module
         Sequential-Composition
begin

```

The loop composition uses the same module in sequence, combined with a termination condition, until either

- the termination condition is met or

- no new decisions are made (i.e., a fixed point is reached).

### 6.5.1 Definition

**lemma** *loop-termination-helper*:

**fixes**

$m \text{ acc} :: ('a, 'v, 'a \text{ Result}) \text{ Electoral-Module}$  **and**

$t :: 'a \text{ Termination-Condition}$  **and**

$A :: 'a \text{ set}$  **and**

$V :: 'v \text{ set}$  **and**

$p :: ('a, 'v) \text{ Profile}$

**assumes**

$\neg t (acc \triangleright V A p)$  **and**

$defer (acc \triangleright m) V A p \subset defer acc V A p$  **and**

$finite (defer acc V A p)$

**shows**  $((acc \triangleright m, m, t, V, A, p), (acc, m, t, V, A, p)) \in$

$measure (\lambda (acc, m, t, V, A, p). card (defer acc V A p))$

**using** *assms psubset-card-mono*

**by** *simp*

This function handles the accumulator for the following loop composition function.

**function** *loop-comp-helper*  $:: ('a, 'v, 'a \text{ Result}) \text{ Electoral-Module} \Rightarrow$

$(('a, 'v, 'a \text{ Result}) \text{ Electoral-Module} \Rightarrow 'a \text{ Termination-Condition} \Rightarrow$

$('a, 'v, 'a \text{ Result}) \text{ Electoral-Module}$  **where**

*loop-comp-helper-finite*:

$finite (defer acc V A p) \wedge (defer (acc \triangleright m) V A p) \subset (defer acc V A p)$

$\longrightarrow t (acc V A p) \Longrightarrow$

$loop-comp-helper acc m t V A p = acc V A p \mid$

*loop-comp-helper-infinite*:

$\neg (finite (defer acc V A p) \wedge (defer (acc \triangleright m) V A p) \subset (defer acc V A p))$

$\longrightarrow t (acc V A p) \Longrightarrow$

$loop-comp-helper acc m t V A p = loop-comp-helper (acc \triangleright m) m t V A p$

**proof** –

**fix**

$P :: bool$  **and**

$accum ::$

$(('a, 'v, 'a \text{ Result}) \text{ Electoral-Module} \times ('a, 'v, 'a \text{ Result}) \text{ Electoral-Module}$

$\times 'a \text{ Termination-Condition} \times 'v \text{ set} \times 'a \text{ set} \times ('a, 'v) \text{ Profile}$

**have** *accum-exists*:  $\exists m n t V A p. (m, n, t, V, A, p) = accum$

**using** *prod-cases5*

**by** *metis*

**assume**

$\bigwedge acc V A p m t.$

$finite (defer acc V A p) \wedge defer (acc \triangleright m) V A p \subset defer acc V A p$

$\longrightarrow t (acc V A p) \Longrightarrow accum = (acc, m, t, V, A, p) \Longrightarrow P$  **and**

$\bigwedge acc V A p m t.$

$\neg (finite (defer acc V A p) \wedge defer (acc \triangleright m) V A p \subset defer acc V A p)$

```

       $\longrightarrow t (acc \ V \ A \ p)) \Longrightarrow accum = (acc, m, t, V, A, p) \Longrightarrow P$ 
thus  $P$ 
  using accum-exists
  by metis
next
fix
   $t \ t' :: 'a \ Termination-Condition$  and
   $acc \ acc' :: ('a, 'v, 'a \ Result) \ Electoral-Module$  and
   $A \ A' :: 'a \ set$  and
   $V \ V' :: 'v \ set$  and
   $p \ p' :: ('a, 'v) \ Profile$  and
   $m \ m' :: ('a, 'v, 'a \ Result) \ Electoral-Module$ 
assume
   $finite \ (defer \ acc \ V \ A \ p)$ 
   $\wedge \ defer \ (acc \triangleright m) \ V \ A \ p \subset defer \ acc \ V \ A \ p$ 
   $\longrightarrow t \ (acc \ V \ A \ p)$  and
   $finite \ (defer \ acc' \ V' \ A' \ p')$ 
   $\wedge \ defer \ (acc' \triangleright m') \ V' \ A' \ p' \subset defer \ acc' \ V' \ A' \ p'$ 
   $\longrightarrow t' \ (acc' \ V' \ A' \ p')$  and
   $(acc, m, t, V, A, p) = (acc', m', t', V', A', p')$ 
thus  $acc \ V \ A \ p = acc' \ V' \ A' \ p'$ 
  by fastforce
next
fix
   $t \ t' :: 'a \ Termination-Condition$  and
   $acc \ acc' :: ('a, 'v, 'a \ Result) \ Electoral-Module$  and
   $A \ A' :: 'a \ set$  and
   $V \ V' :: 'v \ set$  and
   $p \ p' :: ('a, 'v) \ Profile$  and
   $m \ m' :: ('a, 'v, 'a \ Result) \ Electoral-Module$ 
assume
   $finite \ (defer \ acc \ V \ A \ p)$ 
   $\wedge \ defer \ (acc \triangleright m) \ V \ A \ p \subset defer \ acc \ V \ A \ p$ 
   $\longrightarrow t \ (acc \ V \ A \ p)$  and
   $\neg \ (finite \ (defer \ acc' \ V' \ A' \ p'))$ 
   $\wedge \ defer \ (acc' \triangleright m') \ V' \ A' \ p' \subset defer \ acc' \ V' \ A' \ p'$ 
   $\longrightarrow t' \ (acc' \ V' \ A' \ p')$  and
   $(acc, m, t, V, A, p) = (acc', m', t', V', A', p')$ 
thus  $acc \ V \ A \ p = loop-comp-helper-sumC \ (acc' \triangleright m', m', t', V', A', p')$ 
  by force
next
fix
   $t \ t' :: 'a \ Termination-Condition$  and
   $acc \ acc' :: ('a, 'v, 'a \ Result) \ Electoral-Module$  and
   $A \ A' :: 'a \ set$  and
   $V \ V' :: 'v \ set$  and
   $p \ p' :: ('a, 'v) \ Profile$  and
   $m \ m' :: ('a, 'v, 'a \ Result) \ Electoral-Module$ 
assume

```

$\neg$  (*finite* (*defer* *acc* *V* *A* *p*)  
 $\wedge$  *defer* (*acc*  $\triangleright$  *m*) *V* *A* *p*  $\subset$  *defer* *acc* *V* *A* *p*  
 $\longrightarrow$  *t* (*acc* *V* *A* *p*)) **and**  
 $\neg$  (*finite* (*defer* *acc'* *V'* *A'* *p'*)  
 $\wedge$  *defer* (*acc'*  $\triangleright$  *m'*) *V'* *A'* *p'*  $\subset$  *defer* *acc'* *V'* *A'* *p'*  
 $\longrightarrow$  *t'* (*acc'* *V'* *A'* *p'*)) **and**  
(*acc*, *m*, *t*, *V*, *A*, *p*) = (*acc'*, *m'*, *t'*, *V'*, *A'*, *p'*)  
**thus** *loop-comp-helper-sumC* (*acc*  $\triangleright$  *m*, *m*, *t*, *V*, *A*, *p*) =  
*loop-comp-helper-sumC* (*acc'*  $\triangleright$  *m'*, *m'*, *t'*, *V'*, *A'*, *p'*)

**by** *force*

**qed**

**termination**

**proof** (*safe*)

**fix**

*m* *n* :: ('b, 'a, 'b *Result*) *Electoral-Module* **and**  
*t* :: 'b *Termination-Condition* **and**  
*A* :: 'b *set* **and**  
*V* :: 'a *set* **and**  
*p* :: ('b, 'a) *Profile*

**have** *term-rel*:

$\exists$  *R*. *wf* *R*  $\wedge$   
(*finite* (*defer* *m* *V* *A* *p*)  
 $\wedge$  *defer* (*m*  $\triangleright$  *n*) *V* *A* *p*  $\subset$  *defer* *m* *V* *A* *p*  
 $\longrightarrow$  *t* (*m* *V* *A* *p*)  
 $\vee$  ((*m*  $\triangleright$  *n*, *n*, *t*, *V*, *A*, *p*), (*m*, *n*, *t*, *V*, *A*, *p*))  $\in$  *R*)

**using** *loop-termination-helper wf-measure termination*

**by** (*metis* (*no-types*))

**obtain**

*R* :: (((('b, 'a, 'b *Result*) *Electoral-Module*  
 $\times$  ('b, 'a, 'b *Result*) *Electoral-Module*  
 $\times$  ('b *Termination-Condition*)  $\times$  'a *set*  $\times$  'b *set*  
 $\times$  ('b, 'a) *Profile*)  
 $\times$  ('b, 'a, 'b *Result*) *Electoral-Module*  
 $\times$  ('b, 'a, 'b *Result*) *Electoral-Module*  
 $\times$  ('b *Termination-Condition*)  $\times$  'a *set*  $\times$  'b *set*  
 $\times$  ('b, 'a) *Profile*) *set* **where**

*wf* *R*  $\wedge$

(*finite* (*defer* *m* *V* *A* *p*)  
 $\wedge$  *defer* (*m*  $\triangleright$  *n*) *V* *A* *p*  $\subset$  *defer* *m* *V* *A* *p*  
 $\longrightarrow$  *t* (*m* *V* *A* *p*)  
 $\vee$  ((*m*  $\triangleright$  *n*, *n*, *t*, *V*, *A*, *p*), *m*, *n*, *t*, *V*, *A*, *p*)  $\in$  *R*)

**using** *term-rel*

**by** *presburger*

**have**  $\forall$  *R'*.

*All* (*loop-comp-helper-dom* ::

('b, 'a, 'b *Result*) *Electoral-Module*  $\times$  ('b, 'a, 'b *Result*) *Electoral-Module*  
 $\times$  'b *Termination-Condition*  $\times$  'a *set*  $\times$  'b *set*  $\times$  ('b, 'a) *Profile*  $\Rightarrow$  *bool*)  $\vee$   
( $\exists$  *t'* *m'* *A'* *V'* *p'* *n'*. *wf* *R'*  $\longrightarrow$   
((*m'*  $\triangleright$  *n'*, *n'*, *t'*, *V'* :: 'a *set*, *A'* :: 'b *set*, *p'*), *m'*, *n'*, *t'*, *V'*, *A'*, *p'*)  $\notin$  *R'*)



```

       $\wedge \text{finite } (\text{defer } m' \ V' \ A' \ p') \wedge \text{defer } (m' \triangleright n') \ V' \ A' \ p' \subset \text{defer } m' \ V' \ A' \ p'$ 
       $\wedge \neg t' (m' \ V' \ A' \ p')$ 
    using termination
    by metis
  thus loop-comp-helper-dom (m, n, t, V, A, p)
    using loop-termination-helper wf-measure
    by metis
qed

```

```

lemma loop-comp-code-helper[code]:
  fixes
    m acc :: ('a, 'v, 'a Result) Electoral-Module and
    t :: 'a Termination-Condition and
    A :: 'a set and
    V :: 'v set and
    p :: ('a, 'v) Profile
  shows
    loop-comp-helper acc m t V A p =
      (if t (acc V A p)  $\vee \neg \text{defer } (acc \triangleright m) \ V \ A \ p \subset \text{defer } acc \ V \ A \ p$ 
        $\vee \text{infinite } (\text{defer } acc \ V \ A \ p)$ 
       then acc V A p else loop-comp-helper (acc  $\triangleright m$ ) m t V A p)
    using loop-comp-helper.simps
    by (metis (no-types))

function loop-composition :: ('a, 'v, 'a Result) Electoral-Module  $\Rightarrow$ 
  'a Termination-Condition  $\Rightarrow$  ('a, 'v, 'a Result) Electoral-Module where
  t ({}, {}, A)
     $\Rightarrow$  loop-composition m t V A p = defer-module V A p |
     $\neg(t \{ \}, \{ \}, A)$ 
     $\Rightarrow$  loop-composition m t V A p = (loop-comp-helper m m t) V A p
  by (fastforce, simp-all)

termination
  using termination wf-empty
  by blast

```

```

abbreviation loop :: ('a, 'v, 'a Result) Electoral-Module  $\Rightarrow$ 
  'a Termination-Condition  $\Rightarrow$  ('a, 'v, 'a Result) Electoral-Module
  (-  $\odot$  50) where
  m  $\odot_t$   $\equiv$  loop-composition m t

```

```

lemma loop-comp-code[code]:
  fixes
    m :: ('a, 'v, 'a Result) Electoral-Module and
    t :: 'a Termination-Condition and
    A :: 'a set and
    V :: 'v set and
    p :: ('a, 'v) Profile
  shows loop-composition m t V A p =
    (if t ({}, {}, A)

```

$\text{then defer-module } V \ A \ p \ \text{else } (\text{loop-comp-helper } m \ m \ t) \ V \ A \ p)$   
**by** *simp*

**lemma** *loop-comp-helper-imp-partit*:  
**fixes**  
 $m \ acc :: ('a, 'v, 'a \ \text{Result}) \ \text{Electoral-Module} \ \text{and}$   
 $t :: 'a \ \text{Termination-Condition} \ \text{and}$   
 $A :: 'a \ \text{set} \ \text{and}$   
 $V :: 'v \ \text{set} \ \text{and}$   
 $p :: ('a, 'v) \ \text{Profile} \ \text{and}$   
 $n :: \text{nat}$   
**assumes**  
 $\text{module-}m: \text{SCF-result.electoral-module } m \ \text{and}$   
 $\text{profile: profile } V \ A \ p \ \text{and}$   
 $\text{module-acc: SCF-result.electoral-module } acc \ \text{and}$   
 $\text{defer-card-}n: n = \text{card } (\text{defer } acc \ V \ A \ p)$   
**shows**  $\text{well-formed-SCF } A \ (\text{loop-comp-helper } acc \ m \ t \ V \ A \ p)$   
**using** *assms*  
**proof** (*induct arbitrary: acc rule: less-induct*)  
**case** (*less*)  
**have**  $\forall \ m' \ n'.$   
 $(\text{SCF-result.electoral-module } m' \wedge \text{SCF-result.electoral-module } n')$   
 $\longrightarrow \text{SCF-result.electoral-module } (m' \triangleright n')$   
**using** *seq-comp-sound*  
**by** *metis*  
**hence**  $\text{SCF-result.electoral-module } (acc \triangleright m)$   
**using** *less.premis module-m*  
**by** *blast*  
**hence**  $\neg t \ (acc \ V \ A \ p) \wedge \text{defer } (acc \triangleright m) \ V \ A \ p \subset \text{defer } acc \ V \ A \ p \wedge$   
 $\text{finite } (\text{defer } acc \ V \ A \ p) \longrightarrow$   
 $\text{well-formed-SCF } A \ (\text{loop-comp-helper } acc \ m \ t \ V \ A \ p)$   
**using** *less.hyps less.premis loop-comp-helper-infinite*  
 $\text{psubset-card-mono}$   
**by** *metis*  
**moreover have**  $\text{well-formed-SCF } A \ (acc \ V \ A \ p)$   
**using** *less.premis profile*  
**unfolding** *SCF-result.electoral-module.simps*  
**by** *metis*  
**ultimately show** *?case*  
**using** *loop-comp-code-helper*  
**by** (*metis (no-types)*)  
**qed**

### 6.5.2 Soundness

**theorem** *loop-comp-sound*:  
**fixes**  
 $m :: ('a, 'v, 'a \ \text{Result}) \ \text{Electoral-Module} \ \text{and}$   
 $t :: 'a \ \text{Termination-Condition}$

```

assumes SCF-result.electoral-module m
shows SCF-result.electoral-module (m  $\odot_t$ )
using def-mod-sound loop-composition.simps
      loop-comp-helper-imp-partit assms
unfolding SCF-result.electoral-module.simps
by metis

lemma loop-comp-helper-imp-no-def-incr:
fixes
  m acc :: ('a, 'v, 'a Result) Electoral-Module and
  t :: 'a Termination-Condition and
  A :: 'a set and
  V :: 'v set and
  p :: ('a, 'v) Profile and
  n :: nat
assumes
  module-m: SCF-result.electoral-module m and
  profile: profile V A p and
  mod-acc: SCF-result.electoral-module acc and
  card-n-defer-acc: n = card (defer acc V A p)
shows defer (loop-comp-helper acc m t) V A p  $\subseteq$  defer acc V A p
using assms
proof (induct arbitrary: acc rule: less-induct)
case (less)
have emod-acc-m: SCF-result.electoral-module (acc  $\triangleright$  m)
  using less.prems module-m seq-comp-sound
by blast
have  $\forall A A'. (finite\ A \wedge A' \subset A) \longrightarrow card\ A' < card\ A$ 
  using psubset-card-mono
by metis
hence  $\neg t\ (acc\ V\ A\ p) \wedge defer\ (acc\ \triangleright\ m)\ V\ A\ p \subset defer\ acc\ V\ A\ p \wedge$ 
  finite (defer acc V A p)  $\longrightarrow$ 
  defer (loop-comp-helper (acc  $\triangleright$  m) m t) V A p  $\subseteq$  defer acc V A p
using emod-acc-m less.hyps less.prems
by blast
hence  $\neg t\ (acc\ V\ A\ p) \wedge defer\ (acc\ \triangleright\ m)\ V\ A\ p \subset defer\ acc\ V\ A\ p \wedge$ 
  finite (defer acc V A p)  $\longrightarrow$ 
  defer (loop-comp-helper acc m t) V A p  $\subseteq$  defer acc V A p
using loop-comp-helper-infinite
by (metis (no-types))
thus ?case
  using eq-iff loop-comp-code-helper
  by (metis (no-types))
qed

```

### 6.5.3 Lemmas

```

lemma loop-comp-helper-def-lift-inv-helper:
fixes

```

```

m acc :: ('a, 'v, 'a Result) Electoral-Module and
t :: 'a Termination-Condition and
A :: 'a set and
V :: 'v set and
p :: ('a, 'v) Profile and
n :: nat
assumes
  monotone-m: defer-lift-invariance m and
  prof: profile V A p and
  dli-acc: defer-lift-invariance acc and
  card-n-defer: n = card (defer acc V A p) and
  defer-finite: finite (defer acc V A p) and
  voters-determine-m: voters-determine-election m
shows
   $\forall q\ a. a \in (\text{defer } (\text{loop-comp-helper } acc\ m\ t)\ V\ A\ p) \wedge \text{lifted } V\ A\ p\ q\ a \longrightarrow$ 
     $(\text{loop-comp-helper } acc\ m\ t)\ V\ A\ p = (\text{loop-comp-helper } acc\ m\ t)\ V\ A\ q$ 
using assms
proof (induct n arbitrary: acc rule: less-induct)
case (less n)
have defer-card-comp:
  defer-lift-invariance acc  $\longrightarrow$ 
     $(\forall q\ a. a \in (\text{defer } (acc \triangleright m)\ V\ A\ p) \wedge \text{lifted } V\ A\ p\ q\ a \longrightarrow$ 
       $\text{card } (\text{defer } (acc \triangleright m)\ V\ A\ p) = \text{card } (\text{defer } (acc \triangleright m)\ V\ A\ q))$ 
using monotone-m def-lift-inv-seq-comp-help voters-determine-m
by metis
have defer-lift-invariance acc  $\longrightarrow$ 
     $(\forall q\ a. a \in (\text{defer } acc\ V\ A\ p) \wedge \text{lifted } V\ A\ p\ q\ a \longrightarrow$ 
       $\text{card } (\text{defer } acc\ V\ A\ p) = \text{card } (\text{defer } acc\ V\ A\ q))$ 
unfolding defer-lift-invariance-def
by simp
hence defer-card-acc:
  defer-lift-invariance acc  $\longrightarrow$ 
     $(\forall q\ a. (a \in (\text{defer } (acc \triangleright m)\ V\ A\ p) \wedge \text{lifted } V\ A\ p\ q\ a) \longrightarrow$ 
       $\text{card } (\text{defer } acc\ V\ A\ p) = \text{card } (\text{defer } acc\ V\ A\ q))$ 
using assms seq-comp-def-set-trans
unfolding defer-lift-invariance-def
by metis
thus ?case
proof (cases)
assume card-unchanged:
  card (defer (acc  $\triangleright$  m) V A p) = card (defer acc V A p)
have defer-lift-invariance acc  $\longrightarrow$ 
     $(\forall q\ a. a \in (\text{defer } acc\ V\ A\ p) \wedge \text{lifted } V\ A\ p\ q\ a \longrightarrow$ 
       $(\text{loop-comp-helper } acc\ m\ t)\ V\ A\ q = acc\ V\ A\ q)$ 
proof (safe)
fix
  q :: ('a, 'v) Profile and
  a :: 'a
assume

```

*dli-acc*: *defer-lift-invariance acc* **and**  
*a-in-def-acc*:  $a \in \text{defer } acc \ V \ A \ p$  **and**  
*lifted-A*: *Profile.lifted V A p q a*  
**moreover have** *SCF-result.electoral-module m*  
**using** *monotone-m*  
**unfolding** *defer-lift-invariance-def*  
**by** *simp*  
**moreover have** *emod-acc: SCF-result.electoral-module acc*  
**using** *dli-acc*  
**unfolding** *defer-lift-invariance-def*  
**by** *simp*  
**moreover have** *acc-eq-pq: acc V A q = acc V A p*  
**using** *a-in-def-acc dli-acc lifted-A*  
**unfolding** *defer-lift-invariance-def*  
**by** (*metis (full-types)*)  
**ultimately have** *finite (defer acc V A p)*  
 $\longrightarrow \text{loop-comp-helper } acc \ m \ t \ V \ A \ q = acc \ V \ A \ q$   
**using** *card-unchanged defer-card-comp prof loop-comp-code-helper*  
*psubset-card-mono dual-order.strict-iff-order*  
*seq-comp-def-set-bounded less*  
**by** (*metis (mono-tags, lifting)*)  
**thus** *loop-comp-helper acc m t V A q = acc V A q*  
**using** *acc-eq-pq loop-comp-code-helper*  
**by** (*metis (full-types)*)  
**qed**  
**moreover from** *card-unchanged*  
**have** (*loop-comp-helper acc m t V A p = acc V A p*)  
**using** *loop-comp-code-helper order.strict-iff-order psubset-card-mono*  
**by** *metis*  
**ultimately have**  
*defer-lift-invariance (acc  $\triangleright$  m)  $\wedge$  defer-lift-invariance acc*  
 $\longrightarrow (\forall \ q \ a. \ a \in (\text{defer } (\text{loop-comp-helper } acc \ m \ t) \ V \ A \ p) \wedge \text{lifted } V \ A \ p \ q \ a)$   
 $\longrightarrow (\text{loop-comp-helper } acc \ m \ t) \ V \ A \ p =$   
 $(\text{loop-comp-helper } acc \ m \ t) \ V \ A \ q)$   
**unfolding** *defer-lift-invariance-def*  
**by** *metis*  
**moreover have** *defer-lift-invariance (acc  $\triangleright$  m)*  
**using** *less monotone-m seq-comp-presv-def-lift-inv*  
**by** *safe*  
**ultimately show** *?thesis*  
**using** *less monotone-m*  
**by** *metis*  
**next**  
**assume** *card-changed:*  
 $\neg (\text{card } (\text{defer } (acc \triangleright m) \ V \ A \ p) = \text{card } (\text{defer } acc \ V \ A \ p))$   
**with** *prof*  
**have** *card-smaller-for-p:*  
 $SCF\text{-result.electoral-module } acc \wedge \text{finite } A \longrightarrow$

```

    card (defer (acc ▷ m) V A p) < card (defer acc V A p)
using monotone-m order.not-eq-order-implies-strict
    card-mono less.premis seq-comp-def-set-bounded
unfolding defer-lift-invariance-def
by metis
with defer-card-acc defer-card-comp
have card-changed-for-q:
  defer-lift-invariance acc →
    (∀ q a. a ∈ (defer (acc ▷ m) V A p) ∧ lifted V A p q a →
      card (defer (acc ▷ m) V A q) < card (defer acc V A q))
using lifted-def less
unfolding defer-lift-invariance-def
by (metis (no-types, lifting))
thus ?thesis
proof (cases)
  assume t-not-satisfied-for-p: ¬ t (acc V A p)
  hence t-not-satisfied-for-q:
    defer-lift-invariance acc →
      (∀ q a. a ∈ (defer (acc ▷ m) V A p) ∧ lifted V A p q a
        → ¬ t (acc V A q))
  using monotone-m prof seq-comp-def-set-trans
  unfolding defer-lift-invariance-def
  by metis
have dli-card-defer:
  defer-lift-invariance (acc ▷ m) ∧ defer-lift-invariance acc
    → (∀ q a. a ∈ (defer (acc ▷ m) V A p) ∧ Profile.lifted V A p q a
      → card (defer (acc ▷ m) V A q) ≠ (card (defer acc V A q)))
proof –
  have
    ∀ m'.
      (¬ defer-lift-invariance m' ∧ SCF-result.electoral-module m'
        → (∃ V' A' p' q' a.
          m' V' A' p' ≠ m' V' A' q' ∧ lifted V' A' p' q' a
            ∧ a ∈ defer m' V' A' p'))
      ∧ (defer-lift-invariance m'
        → SCF-result.electoral-module m'
          ∧ (∀ V' A' p' q' a.
            m' V' A' p' ≠ m' V' A' q'
              → lifted V' A' p' q' a → a ∉ defer m' V' A' p'))
  unfolding defer-lift-invariance-def
  by blast
thus ?thesis
  using card-changed monotone-m prof seq-comp-def-set-trans
  by (metis (no-types, opaque-lifting))
qed
hence dli-def-subset:
  defer-lift-invariance (acc ▷ m) ∧ defer-lift-invariance acc
    → (∀ p' a. a ∈ (defer (acc ▷ m) V A p) ∧ lifted V A p p' a
      → defer (acc ▷ m) V A p' ⊂ defer acc V A p')

```

```

using Profile.lifted-def dli-card-defer defer-lift-invariance-def
    monotone-m psubsetI seq-comp-def-set-bounded
by (metis (no-types, opaque-lifting))
with t-not-satisfied-for-p
have rec-step-q:
  defer-lift-invariance (acc  $\triangleright$  m)  $\wedge$  defer-lift-invariance acc
   $\longrightarrow$  ( $\forall$  q a. a  $\in$  (defer (acc  $\triangleright$  m) V A p)  $\wedge$  lifted V A p q a
     $\longrightarrow$  loop-comp-helper acc m t V A q =
      loop-comp-helper (acc  $\triangleright$  m) m t V A q)
proof (safe)
  fix
    q :: ('a, 'v) Profile and
    a :: 'a
  assume
    a-in-def-imp-def-subset:
     $\forall$  q' a'. a'  $\in$  defer (acc  $\triangleright$  m) V A p  $\wedge$  lifted V A p q' a'  $\longrightarrow$ 
      defer (acc  $\triangleright$  m) V A q'  $\subseteq$  defer acc V A q' and
    dli-acc: defer-lift-invariance acc and
    a-in-def-seq-acc-m: a  $\in$  defer (acc  $\triangleright$  m) V A p and
    lifted-pq-a: lifted V A p q a
  hence defer (acc  $\triangleright$  m) V A q  $\subseteq$  defer acc V A q
    by metis
  moreover have SCF-result.electoral-module acc
    using dli-acc
    unfolding defer-lift-invariance-def
    by simp
  moreover have  $\neg$  t (acc V A q)
    using dli-acc a-in-def-seq-acc-m lifted-pq-a t-not-satisfied-for-q
    by metis
  ultimately show loop-comp-helper acc m t V A q
    = loop-comp-helper (acc  $\triangleright$  m) m t V A q
    using loop-comp-code-helper defer-in-alts finite-subset lifted-pq-a
    unfolding lifted-def
    by (metis (mono-tags, lifting))
qed
have rec-step-p:
  SCF-result.electoral-module acc  $\longrightarrow$ 
    loop-comp-helper acc m t V A p = loop-comp-helper (acc  $\triangleright$  m) m t V A p
proof (safe)
  assume emod-acc: SCF-result.electoral-module acc
  have sound-imp-def-subset:
    SCF-result.electoral-module m
     $\longrightarrow$  defer (acc  $\triangleright$  m) V A p  $\subseteq$  defer acc V A p
    using emod-acc prof seq-comp-def-set-bounded
    by blast
  hence card-ineq: card (defer (acc  $\triangleright$  m) V A p) < card (defer acc V A p)
    using card-changed card-mono less order-neq-le-trans
    unfolding defer-lift-invariance-def
    by metis

```

```

have def-limited-acc:
  profile V (defer acc V A p) (limit-profile (defer acc V A p) p)
  using def-presv-prof emod-acc prof
  by metis
have defer (acc ▷ m) V A p ⊆ defer acc V A p
  using sound-imp-defer-subset defer-lift-invariance-def monotone-m
  by blast
hence defer (acc ▷ m) V A p ⊂ defer acc V A p
  using def-limited-acc card-ineq card-psubset less
  by metis
with def-limited-acc
show loop-comp-helper acc m t V A p =
  loop-comp-helper (acc ▷ m) m t V A p
  using loop-comp-code-helper t-not-satisfied-for-p less
  by (metis (no-types))
qed
show ?thesis
proof (safe)
  fix
    q :: ('a, 'v) Profile and
    a :: 'a
  assume
    a-in-defer-lch: a ∈ defer (loop-comp-helper acc m t) V A p and
    a-lifted: Profile.lifted V A p q a
  have mod-acc: SCF-result.electoral-module acc
    using less.premis
    unfolding defer-lift-invariance-def
    by simp
  hence loop-comp-equiv:
    loop-comp-helper acc m t V A p = loop-comp-helper (acc ▷ m) m t V A p
    using rec-step-p
    by blast
  hence a ∈ defer (loop-comp-helper (acc ▷ m) m t) V A p
    using a-in-defer-lch
    by presburger
  moreover have l-inv: defer-lift-invariance (acc ▷ m)
    using less.premis monotone-m voters-determine-m
    seq-comp-presv-def-lift-inv
    by blast
  ultimately have a ∈ defer (acc ▷ m) V A p
    using prof monotone-m in-mono loop-comp-helper-imp-no-def-incr
    unfolding defer-lift-invariance-def
    by (metis (no-types, lifting))
  with l-inv loop-comp-equiv show
    loop-comp-helper acc m t V A p = loop-comp-helper acc m t V A q
  proof –
    assume
      dli-acc-seq-m: defer-lift-invariance (acc ▷ m) and
      a-in-def-seq: a ∈ defer (acc ▷ m) V A p

```



```

moreover from this have SCF-result.electoral-module (acc  $\triangleright$  m)
  unfolding defer-lift-invariance-def
  by blast
moreover have a  $\in$  defer (loop-comp-helper (acc  $\triangleright$  m) m t) V A p
  using loop-comp-equiv a-in-defer-lch
  by presburger
ultimately have
  loop-comp-helper (acc  $\triangleright$  m) m t V A p
    = loop-comp-helper (acc  $\triangleright$  m) m t V A q
  using monotone-m mod-acc less a-lifted card-smaller-for-p
    defer-in-altis infinite-super less
  unfolding lifted-def
  by (metis (no-types))
moreover have loop-comp-helper acc m t V A q
    = loop-comp-helper (acc  $\triangleright$  m) m t V A q
  using dli-acc-seq-m a-in-def-seq less a-lifted rec-step-q
  by blast
ultimately show ?thesis
  using loop-comp-equiv
  by presburger
qed
qed
next
assume  $\neg \neg t$  (acc V A p)
thus ?thesis
  using loop-comp-code-helper less
  unfolding defer-lift-invariance-def
  by metis
qed
qed
qed

lemma loop-comp-helper-def-lift-inv:
fixes
  m acc :: ('a, 'v, 'a Result) Electoral-Module and
  t :: 'a Termination-Condition and
  A :: 'a set and
  V :: 'v set and
  p q :: ('a, 'v) Profile and
  a :: 'a
assumes
  defer-lift-invariance m and
  voters-determine-election m and
  defer-lift-invariance acc and
  profile V A p and
  lifted V A p q a and
  a  $\in$  defer (loop-comp-helper acc m t) V A p
shows (loop-comp-helper acc m t) V A p = (loop-comp-helper acc m t) V A q
using assms loop-comp-helper-def-lift-inv-helper lifted-def

```

```

    defer-in-alts defer-lift-invariance-def finite-subset
  by metis

lemma lifted-imp-fin-prof:
  fixes
    A :: 'a set and
    V :: 'v set and
    p q :: ('a, 'v) Profile and
    a :: 'a
  assumes lifted V A p q a
  shows finite-profile V A p
  using assms
  unfolding lifted-def
  by simp

lemma loop-comp-helper-presv-def-lift-inv:
  fixes
    m acc :: ('a, 'v, 'a Result) Electoral-Module and
    t :: 'a Termination-Condition
  assumes
    defer-lift-invariance m and
    voters-determine-election m and
    defer-lift-invariance acc
  shows defer-lift-invariance (loop-comp-helper acc m t)
proof (unfold defer-lift-invariance-def, safe)
  show SCF-result.electoral-module (loop-comp-helper acc m t)
    using loop-comp-helper-imp-partit assms
    unfolding SCF-result.electoral-module.simps
    defer-lift-invariance-def
  by metis
next
fix
  A :: 'a set and
  V :: 'v set and
  p q :: ('a, 'v) Profile and
  a :: 'a
assume
  a ∈ defer (loop-comp-helper acc m t) V A p and
  lifted V A p q a
thus loop-comp-helper acc m t V A p = loop-comp-helper acc m t V A q
  using lifted-imp-fin-prof loop-comp-helper-def-lift-inv assms
  by metis
qed

lemma loop-comp-presv-non-electing-helper:
  fixes
    m acc :: ('a, 'v, 'a Result) Electoral-Module and
    t :: 'a Termination-Condition and
    A :: 'a set and

```

$V :: 'v \text{ set}$  **and**  
 $p :: ('a, 'v) \text{ Profile}$  **and**  
 $n :: \text{nat}$   
**assumes**  
 $\text{non-electing-m: non-electing } m$  **and**  
 $\text{non-electing-acc: non-electing } acc$  **and**  
 $\text{prof: profile } V \ A \ p$  **and**  
 $\text{acc-defer-card: } n = \text{card } (\text{defer } acc \ V \ A \ p)$   
**shows**  $\text{elect } (\text{loop-comp-helper } acc \ m \ t) \ V \ A \ p = \{\}$   
**using**  $\text{acc-defer-card non-electing-acc}$   
**proof** ( $\text{induct } n \text{ arbitrary: acc rule: less-induct}$ )  
**case** ( $\text{less } n$ )  
**thus**  $?case$   
**proof** ( $\text{safe}$ )  
**fix**  $x :: 'a$   
**assume**  
 $\text{acc-no-elect:}$   
 $\bigwedge i \ acc'. i < \text{card } (\text{defer } acc \ V \ A \ p) \implies$   
 $i = \text{card } (\text{defer } acc' \ V \ A \ p) \implies \text{non-electing } acc' \implies$   
 $\text{elect } (\text{loop-comp-helper } acc' \ m \ t) \ V \ A \ p = \{\}$  **and**  
 $\text{acc-non-elect: non-electing } acc$  **and**  
 $\text{x-in-acc-elect: } x \in \text{elect } (\text{loop-comp-helper } acc \ m \ t) \ V \ A \ p$   
**have**  $\forall m' \ n'. \text{non-electing } m' \wedge \text{non-electing } n' \longrightarrow \text{non-electing } (m' \triangleright n')$   
**by**  $\text{simp}$   
**hence**  $\text{seq-acc-m-non-elect: non-electing } (acc \triangleright m)$   
**using**  $\text{acc-non-elect non-electing-m}$   
**by**  $\text{blast}$   
**have**  $\forall i \ m'.$   
 $i < \text{card } (\text{defer } acc \ V \ A \ p) \wedge i = \text{card } (\text{defer } m' \ V \ A \ p) \wedge$   
 $\text{non-electing } m' \longrightarrow$   
 $\text{elect } (\text{loop-comp-helper } m' \ m \ t) \ V \ A \ p = \{\}$   
**using**  $\text{acc-no-elect}$   
**by**  $\text{blast}$   
**hence**  $\forall m'.$   
 $\text{finite } (\text{defer } acc \ V \ A \ p) \wedge \text{defer } m' \ V \ A \ p \subset \text{defer } acc \ V \ A \ p \wedge$   
 $\text{non-electing } m' \longrightarrow$   
 $\text{elect } (\text{loop-comp-helper } m' \ m \ t) \ V \ A \ p = \{\}$   
**using**  $\text{psubset-card-mono}$   
**by**  $\text{metis}$   
**hence**  $\neg t \ (acc \ V \ A \ p) \wedge \text{defer } (acc \triangleright m) \ V \ A \ p \subset \text{defer } acc \ V \ A \ p \wedge$   
 $\text{finite } (\text{defer } acc \ V \ A \ p) \longrightarrow$   
 $\text{elect } (\text{loop-comp-helper } acc \ m \ t) \ V \ A \ p = \{\}$   
**using**  $\text{loop-comp-code-helper seq-acc-m-non-elect}$   
**by** ( $\text{metis (no-types)}$ )  
**moreover have**  $\text{elect } acc \ V \ A \ p = \{\}$   
**using**  $\text{acc-non-elect prof non-electing-def}$   
**by**  $\text{blast}$   
**ultimately show**  $x \in \{\}$   
**using**  $\text{loop-comp-code-helper x-in-acc-elect}$

by (metis (no-types))  
qed  
qed

**lemma** *loop-comp-helper-iter-elim-def-n-helper:*

**fixes**

*m acc* :: ('a, 'v, 'a Result) *Electoral-Module* **and**

*t* :: 'a *Termination-Condition* **and**

*A* :: 'a *set* **and**

*V* :: 'v *set* **and**

*p* :: ('a, 'v) *Profile* **and**

*n x* :: nat

**assumes**

*non-electing-m*: *non-electing m* **and**

*single-elimination*: *eliminates 1 m* **and**

*terminate-if-n-left*:  $\forall r. t\ r = (\text{card } (\text{defer-r } r) = x)$  **and**

*x-greater-zero*:  $x > 0$  **and**

*prof*: *profile V A p* **and**

*n-acc-defer-card*:  $n = \text{card } (\text{defer } \text{acc } V\ A\ p)$  **and**

*n-ge-x*:  $n \geq x$  **and**

*def-card-gt-one*:  $\text{card } (\text{defer } \text{acc } V\ A\ p) > 1$  **and**

*acc-nonelect*: *non-electing acc*

**shows**  $\text{card } (\text{defer } (\text{loop-comp-helper } \text{acc } m\ t)\ V\ A\ p) = x$

**using** *n-ge-x def-card-gt-one acc-nonelect n-acc-defer-card*

**proof** (*induct n arbitrary: acc rule: less-induct*)

**case** (*less n*)

**have** *mod-acc*: *SCF-result.electoral-module acc*

**using** *less*

**unfolding** *non-electing-def*

**by** *metis*

**hence** *step-reduces-defer-set*:  $\text{defer } (\text{acc } \triangleright m)\ V\ A\ p \subset \text{defer } \text{acc } V\ A\ p$

**using** *seq-comp-elim-one-red-def-set single-elimination prof less*

**by** *metis*

**thus** *?case*

**proof** (*cases t (acc V A p)*)

**case** *True*

**assume** *term-satisfied*:  $t\ (\text{acc } V\ A\ p)$

**thus**  $\text{card } (\text{defer-r } (\text{loop-comp-helper } \text{acc } m\ t\ V\ A\ p)) = x$

**using** *loop-comp-code-helper term-satisfied terminate-if-n-left*

**by** *metis*

**next**

**case** *False*

**hence** *card-not-eq-x*:  $\text{card } (\text{defer } \text{acc } V\ A\ p) \neq x$

**using** *terminate-if-n-left*

**by** *metis*

**have** *fin-def-acc*: *finite (defer acc V A p)*

**using** *prof mod-acc less card.infinite not-one-less-zero*

**by** *metis*

```

hence rec-step:
  loop-comp-helper acc m t V A p = loop-comp-helper (acc ▷ m) m t V A p
  using False step-reduces-defer-set
  by simp
have card-too-big: card (defer acc V A p) > x
  using card-not-eq-x dual-order.order-iff-strict less
  by simp
hence enough-leftover: card (defer acc V A p) > 1
  using x-greater-zero
  by simp
obtain k :: nat where
  new-card-k: k = card (defer (acc ▷ m) V A p)
  by metis
have defer acc V A p ⊆ A
  using defer-in-alts prof mod-acc
  by metis
hence step-profile:
  profile V (defer acc V A p) (limit-profile (defer acc V A p) p)
  using prof limit-profile-sound
  by metis
hence
  card (defer m V (defer acc V A p) (limit-profile (defer acc V A p) p)) =
    card (defer acc V A p) − 1
  using enough-leftover non-electing-m
    single-elimination single-elim-decr-def-card'
  by blast
hence k-card: k = card (defer acc V A p) − 1
  using mod-acc prof new-card-k non-electing-m seq-comp-defers-def-set
  by metis
hence new-card-still-big-enough: x ≤ k
  using card-too-big
  by linarith
show ?thesis
proof (cases x < k)
  case True
  hence 1 < card (defer (acc ▷ m) V A p)
  using new-card-k x-greater-zero
  by linarith
  moreover have k < n
  using step-reduces-defer-set step-profile psubset-card-mono
    new-card-k less fin-def-acc
  by metis
  moreover have SCF-result.electoral-module (acc ▷ m)
  using mod-acc eliminates-def seq-comp-sound single-elimination
  by metis
  moreover have non-electing (acc ▷ m)
  using less non-electing-m
  by simp
  ultimately have card (defer (loop-comp-helper (acc ▷ m) m t) V A p) = x

```

```

    using new-card-k new-card-still-big-enough less
    by metis
  thus ?thesis
    using rec-step
    by presburger
next
case False
thus ?thesis
  using dual-order.strict-iff-order new-card-k
    new-card-still-big-enough rec-step
    terminate-if-n-left
  by simp
qed
qed
qed

```

**lemma** *loop-comp-helper-iter-elim-def-n:*

```

fixes
  m acc :: ('a, 'v, 'a Result) Electoral-Module and
  t :: 'a Termination-Condition and
  A :: 'a set and
  V :: 'v set and
  p :: ('a, 'v) Profile and
  x :: nat

```

**assumes**

```

  non-electing m and
  eliminates 1 m and
   $\forall r. (t\ r) = (\text{card } (\text{defer-r } r) = x)$  and
   $x > 0$  and
  profile V A p and
   $\text{card } (\text{defer acc } V\ A\ p) \geq x$  and
  non-electing acc

```

**shows**  $\text{card } (\text{defer } (\text{loop-comp-helper acc } m\ t)\ V\ A\ p) = x$

**using** *assms gr-implies-not0 le-neq-implies-less less-one linorder-neqE-nat nat-neq-iff less-le loop-comp-helper-iter-elim-def-n-helper loop-comp-code-helper*

**by** (*metis (no-types, lifting)*)

**lemma** *iter-elim-def-n-helper:*

```

fixes
  m :: ('a, 'v, 'a Result) Electoral-Module and
  t :: 'a Termination-Condition and
  A :: 'a set and
  V :: 'v set and
  p :: ('a, 'v) Profile and
  x :: nat

```

**assumes**

```

  non-electing-m: non-electing m and
  single-elimination: eliminates 1 m and
  terminate-if-n-left:  $\forall r. (t\ r) = (\text{card } (\text{defer-r } r) = x)$  and

```

```

    x-greater-zero:  $x > 0$  and
    prof: profile  $V A p$  and
    enough-alternatives:  $\text{card } A \geq x$ 
shows  $\text{card } (\text{defer } (m \circ_t) V A p) = x$ 
proof (cases)
  assume  $\text{card } A = x$ 
  thus ?thesis
    using terminate-if-n-left
    by simp
next
  assume card-not-x:  $\neg \text{card } A = x$ 
  thus ?thesis
proof (cases)
  assume  $\text{card } A < x$ 
  thus ?thesis
    using enough-alternatives not-le
    by blast
next
  assume  $\neg \text{card } A < x$ 
  hence  $\text{card } A > x$ 
    using card-not-x
    by linarith
  moreover from this
  have  $\text{card } (\text{defer } m V A p) = \text{card } A - 1$ 
    using non-electing-m single-elimination single-elim-decr-def-card'
    prof x-greater-zero
    by fastforce
  ultimately have  $\text{card } (\text{defer } m V A p) \geq x$ 
    by linarith
  moreover have  $(m \circ_t) V A p = (\text{loop-comp-helper } m m t) V A p$ 
    using card-not-x terminate-if-n-left
    by simp
  ultimately show ?thesis
    using non-electing-m prof single-elimination terminate-if-n-left x-greater-zero
    loop-comp-helper-iter-elim-def-n
    by metis
qed
qed

```

#### 6.5.4 Composition Rules

The loop composition preserves defer-lift-invariance.

```

theorem loop-comp-presv-def-lift-inv[simp]:
  fixes
     $m :: ('a, 'v, 'a \text{ Result}) \text{ Electoral-Module}$  and
     $t :: 'a \text{ Termination-Condition}$ 
  assumes
    defer-lift-invariance m and
    voters-determine-election m

```

```

shows defer-lift-invariance ( $m \circ_t$ )
proof (unfold defer-lift-invariance-def, safe)
  have SCF-result.electoral-module  $m$ 
    using assms
    unfolding defer-lift-invariance-def
    by simp
  thus SCF-result.electoral-module ( $m \circ_t$ )
    using loop-comp-sound
    by blast
next
fix
   $A :: 'a \text{ set}$  and
   $V :: 'v \text{ set}$  and
   $p \ q :: ('a, 'v) \text{ Profile}$  and
   $a :: 'a$ 
assume
   $a \in \text{defer } (m \circ_t) \ V \ A \ p$  and
  lifted  $V \ A \ p \ q \ a$ 
moreover have
   $\forall \ p' \ q' \ a'. \ a' \in (\text{defer } (m \circ_t) \ V \ A \ p') \wedge \text{lifted } V \ A \ p' \ q' \ a' \longrightarrow$ 
     $(m \circ_t) \ V \ A \ p' = (m \circ_t) \ V \ A \ q'$ 
  using assms lifted-imp-fin-prof loop-comp-helper-def-lift-inv
    loop-composition.simps defer-module.simps
  by (metis (full-types))
ultimately show  $(m \circ_t) \ V \ A \ p = (m \circ_t) \ V \ A \ q$ 
  by metis
qed

```

The loop composition preserves the property non-electing.

```

theorem loop-comp-presv-non-electing[simp]:
  fixes
     $m :: ('a, 'v, 'a \text{ Result}) \text{ Electoral-Module}$  and
     $t :: 'a \text{ Termination-Condition}$ 
  assumes non-electing  $m$ 
  shows non-electing ( $m \circ_t$ )
proof (unfold non-electing-def, safe)
  show SCF-result.electoral-module ( $m \circ_t$ )
    using loop-comp-sound assms
    unfolding non-electing-def
    by metis
next
fix
   $A :: 'a \text{ set}$  and
   $V :: 'v \text{ set}$  and
   $p :: ('a, 'v) \text{ Profile}$  and
   $a :: 'a$ 
assume
  profile  $V \ A \ p$  and
   $a \in \text{elect } (m \circ_t) \ V \ A \ p$ 

```



```

thus  $a \in \{\}$ 
  using def-mod-non-electing loop-comp-presv-non-electing-helper
    assms empty-iff loop-comp-code
  unfolding non-electing-def
  by (metis (no-types, lifting))
qed

theorem iter-elim-def-n[simp]:
  fixes
     $m :: ('a, 'v, 'a \text{ Result}) \text{ Electoral-Module}$  and
     $t :: 'a \text{ Termination-Condition}$  and
     $n :: \text{nat}$ 
  assumes
    non-electing-m: non-electing m and
    single-elimination: eliminates 1 m and
    terminate-if-n-left:  $\forall r. t\ r = (\text{card} (\text{defer-r } r) = n)$  and
    x-greater-zero:  $n > 0$ 
  shows defers n (m  $\circ_t$ )
proof (unfold defers-def, safe)
  show SCF-result.electoral-module (m  $\circ_t$ )
    using loop-comp-sound non-electing-m
    unfolding non-electing-def
    by metis
next
  fix
     $A :: 'a \text{ set}$  and
     $V :: 'v \text{ set}$  and
     $p :: ('a, 'v) \text{ Profile}$ 
  assume
     $n \leq \text{card } A$  and
    profile V A p
  thus  $\text{card} (\text{defer } (m \circ_t) V A p) = n$ 
    using iter-elim-def-n-helper assms
    by metis
qed

end

```

## 6.6 Maximum Parallel Composition

```

theory Maximum-Parallel-Composition
  imports Basic-Modules/Component-Types/Maximum-Aggregator
    Parallel-Composition
begin

```

This is a family of parallel compositions. It composes a new electoral module from two electoral modules combined with the maximum aggregator. Therein, the two modules each make a decision and then a partition is returned where every alternative receives the maximum result of the two input partitions. This means that, if any alternative is elected by at least one of the modules, then it gets elected, if any non-elected alternative is deferred by at least one of the modules, then it gets deferred, only alternatives rejected by both modules get rejected.

### 6.6.1 Definition

**fun** *maximum-parallel-composition* :: ('a, 'v, 'a Result) Electoral-Module  $\Rightarrow$   
     ('a, 'v, 'a Result) Electoral-Module  $\Rightarrow$   
     ('a, 'v, 'a Result) Electoral-Module **where**  
     *maximum-parallel-composition* *m n* =  
     (*let* *a* = *max-aggregator* *in* (*m*  $\parallel_a$  *n*))

**abbreviation** *max-parallel* :: ('a, 'v, 'a Result) Electoral-Module  $\Rightarrow$   
     ('a, 'v, 'a Result) Electoral-Module  $\Rightarrow$   
     ('a, 'v, 'a Result) Electoral-Module (**infix**  $\parallel_{\uparrow}$  50) **where**  
     *m*  $\parallel_{\uparrow}$  *n*  $\equiv$  *maximum-parallel-composition* *m n*

### 6.6.2 Soundness

**theorem** *max-par-comp-sound*:  
     **fixes** *m n* :: ('a, 'v, 'a Result) Electoral-Module  
     **assumes**  
         *SCF-result.electoral-module m* **and**  
         *SCF-result.electoral-module n*  
     **shows** *SCF-result.electoral-module* (*m*  $\parallel_{\uparrow}$  *n*)  
     **using** *assms max-agg-sound par-comp-sound*  
     **unfolding** *maximum-parallel-composition.simps*  
     **by** *metis*

**lemma** *voters-determine-max-par-comp*:  
     **fixes** *m n* :: ('a, 'v, 'a Result) Electoral-Module  
     **assumes**  
         *voters-determine-election m* **and**  
         *voters-determine-election n*  
     **shows** *voters-determine-election* (*m*  $\parallel_{\uparrow}$  *n*)  
     **using** *max-aggregator.simps assms*  
     **unfolding** *Let-def maximum-parallel-composition.simps*  
         *parallel-composition.simps*  
         *voters-determine-election.simps*  
     **by** *presburger*

### 6.6.3 Lemmas

**lemma** *max-agg-eq-result*:

**fixes**  
 $m\ n :: ('a, 'v, 'a\ Result)\ \textit{Electoral-Module}$  **and**  
 $A :: 'a\ set$  **and**  
 $V :: 'v\ set$  **and**  
 $p :: ('a, 'v)\ \textit{Profile}$  **and**  
 $a :: 'a$   
**assumes**  
 $module\text{-}m: SCF\text{-}result.electoral\text{-}module\ m$  **and**  
 $module\text{-}n: SCF\text{-}result.electoral\text{-}module\ n$  **and**  
 $prof\text{-}p: profile\ V\ A\ p$  **and**  
 $a\text{-in}\text{-}A: a \in A$   
**shows**  $mod\text{-}contains\text{-}result\ (m \parallel_{\uparrow} n)\ m\ V\ A\ p\ a \vee$   
 $mod\text{-}contains\text{-}result\ (m \parallel_{\uparrow} n)\ n\ V\ A\ p\ a$   
**proof** (cases)  
**assume**  $a\text{-elect}: a \in elect\ (m \parallel_{\uparrow} n)\ V\ A\ p$   
**hence**  $let\ (e, r, d) = m\ V\ A\ p;$   
 $(e', r', d') = n\ V\ A\ p\ in$   
 $a \in e \cup e'$   
**by** *auto*  
**hence**  $a \in (elect\ m\ V\ A\ p) \cup (elect\ n\ V\ A\ p)$   
**by** *auto*  
**moreover have**  
 $\forall\ m'\ n'\ V'\ A'\ p'\ a'.$   
 $mod\text{-}contains\text{-}result\ m'\ n'\ V'\ A'\ p'\ (a' :: 'a) =$   
 $(SCF\text{-}result.electoral\text{-}module\ m'$   
 $\wedge\ SCF\text{-}result.electoral\text{-}module\ n'$   
 $\wedge\ profile\ V'\ A'\ p' \wedge a' \in A'$   
 $\wedge\ (a' \notin elect\ m'\ V'\ A'\ p' \vee a' \in elect\ n'\ V'\ A'\ p')$   
 $\wedge\ (a' \notin reject\ m'\ V'\ A'\ p' \vee a' \in reject\ n'\ V'\ A'\ p')$   
 $\wedge\ (a' \notin defer\ m'\ V'\ A'\ p' \vee a' \in defer\ n'\ V'\ A'\ p'))$   
**unfolding**  $mod\text{-}contains\text{-}result\text{-}def$   
**by** *simp*  
**moreover have**  $module\text{-}mn: SCF\text{-}result.electoral\text{-}module\ (m \parallel_{\uparrow} n)$   
**using**  $module\text{-}m\ module\text{-}n\ max\text{-}par\text{-}comp\text{-}sound$   
**by** *metis*  
**moreover have**  $a \notin defer\ (m \parallel_{\uparrow} n)\ V\ A\ p$   
**using**  $module\text{-}mn\ IntI\ a\text{-elect}\ empty\text{-}iff\ prof\text{-}p\ result\text{-}disj$   
**by** (*metis* (*no-types*))  
**moreover have**  $a \notin reject\ (m \parallel_{\uparrow} n)\ V\ A\ p$   
**using**  $module\text{-}mn\ IntI\ a\text{-elect}\ empty\text{-}iff\ prof\text{-}p\ result\text{-}disj$   
**by** (*metis* (*no-types*))  
**ultimately show** *?thesis*  
**using** *assms*  
**by** *blast*  
**next**  
**assume**  $not\text{-}a\text{-elect}: a \notin elect\ (m \parallel_{\uparrow} n)\ V\ A\ p$   
**thus** *?thesis*  
**proof** (cases)  
**assume**  $a\text{-in}\text{-}defer: a \in defer\ (m \parallel_{\uparrow} n)\ V\ A\ p$

```

thus ?thesis
proof (safe)
  assume not-mod-cont-mn:  $\neg \text{mod-contains-result } (m \parallel_{\uparrow} n) \ n \ V \ A \ p \ a$ 
  have par-emod:  $\forall \ m' \ n'.$ 
    SCF-result.electoral-module  $m' \wedge$ 
    SCF-result.electoral-module  $n' \longrightarrow$ 
    SCF-result.electoral-module  $(m' \parallel_{\uparrow} n')$ 
  using max-par-comp-sound
  by blast
  have set-intersect:  $\forall \ a' \ A' \ A''. (a' \in A' \cap A'') = (a' \in A' \wedge a' \in A'')$ 
  by blast
  have wf-n: well-formed-SCF  $A \ (n \ V \ A \ p)$ 
  using prof-p module-n
  unfolding SCF-result.electoral-module.simps
  by blast
  have wf-m: well-formed-SCF  $A \ (m \ V \ A \ p)$ 
  using prof-p module-m
  unfolding SCF-result.electoral-module.simps
  by blast
  have e-mod-par: SCF-result.electoral-module  $(m \parallel_{\uparrow} n)$ 
  using par-emod module-m module-n
  by blast
  hence SCF-result.electoral-module  $(m \parallel_{\text{max-aggregator}} n)$ 
  by simp
  hence result-disj-max:
    elect  $(m \parallel_{\text{max-aggregator}} n) \ V \ A \ p \cap$ 
    reject  $(m \parallel_{\text{max-aggregator}} n) \ V \ A \ p = \{\}$   $\wedge$ 
    elect  $(m \parallel_{\text{max-aggregator}} n) \ V \ A \ p \cap$ 
    defer  $(m \parallel_{\text{max-aggregator}} n) \ V \ A \ p = \{\}$   $\wedge$ 
    reject  $(m \parallel_{\text{max-aggregator}} n) \ V \ A \ p \cap$ 
    defer  $(m \parallel_{\text{max-aggregator}} n) \ V \ A \ p = \{\}$ 
  using prof-p result-disj
  by metis
  have a-not-elect:  $a \notin \text{elect } (m \parallel_{\text{max-aggregator}} n) \ V \ A \ p$ 
  using result-disj-max a-in-defer
  by force
  have result-m:  $(\text{elect } m \ V \ A \ p, \text{reject } m \ V \ A \ p, \text{defer } m \ V \ A \ p) = m \ V \ A \ p$ 
  by auto
  have result-n:  $(\text{elect } n \ V \ A \ p, \text{reject } n \ V \ A \ p, \text{defer } n \ V \ A \ p) = n \ V \ A \ p$ 
  by auto
  have max-pq:
     $\forall \ (A' :: 'a \text{ set}) \ m' \ n'.$ 
    elect-r  $(\text{max-aggregator } A' \ m' \ n') = \text{elect-r } m' \cup \text{elect-r } n'$ 
  by force
  have a  $\notin \text{elect } (m \parallel_{\text{max-aggregator}} n) \ V \ A \ p$ 
  using a-not-elect
  by blast
  hence a  $\notin \text{elect } m \ V \ A \ p \cup \text{elect } n \ V \ A \ p$ 
  using max-pq

```

by *simp*  
 hence *a-not-elect-mn*:  $a \notin \text{elect } m \ V \ A \ p \wedge a \notin \text{elect } n \ V \ A \ p$   
 by *blast*  
 have *a-not-mpar-rej*:  $a \notin \text{reject } (m \parallel_{\uparrow} n) \ V \ A \ p$   
 using *result-disj-max a-in-defer*  
 by *fastforce*  
 have *mod-cont-res-fg*:  
 $\forall m' n' A' V' p' (a' :: 'a).$   
 $\text{mod-contains-result } m' n' V' A' p' a' =$   
 $(\text{SCF-result.electoral-module } m'$   
 $\wedge \text{SCF-result.electoral-module } n'$   
 $\wedge \text{profile } V' A' p' \wedge a' \in A'$   
 $\wedge (a' \in \text{elect } m' V' A' p' \longrightarrow a' \in \text{elect } n' V' A' p')$   
 $\wedge (a' \in \text{reject } m' V' A' p' \longrightarrow a' \in \text{reject } n' V' A' p')$   
 $\wedge (a' \in \text{defer } m' V' A' p' \longrightarrow a' \in \text{defer } n' V' A' p'))$   
 unfolding *mod-contains-result-def*  
 by *simp*  
 have *max-agg-res*:  
 $\text{max-aggregator } A \ (\text{elect } m \ V \ A \ p, \text{reject } m \ V \ A \ p, \text{defer } m \ V \ A \ p)$   
 $(\text{elect } n \ V \ A \ p, \text{reject } n \ V \ A \ p, \text{defer } n \ V \ A \ p) =$   
 $(m \parallel_{\text{max-aggregator}} n) \ V \ A \ p$   
 by *simp*  
 have *well-f-max*:  
 $\forall r' r'' e' e'' d' d'' A'.$   
 $\text{well-formed-SCF } A' (e', r', d') \wedge$   
 $\text{well-formed-SCF } A' (e'', r'', d'') \longrightarrow$   
 $\text{reject-r } (\text{max-aggregator } A' (e', r', d') (e'', r'', d'')) =$   
 $r' \cap r''$   
 using *max-agg-rej-set*  
 by *metis*  
 have *e-mod-disj*:  
 $\forall m' (V' :: 'v \text{ set}) (A' :: 'a \text{ set}) p'.$   
 $\text{SCF-result.electoral-module } m' \wedge \text{profile } V' A' p'$   
 $\longrightarrow \text{elect } m' V' A' p' \cup \text{reject } m' V' A' p' \cup \text{defer } m' V' A' p' = A'$   
 using *result-presv-alts*  
 by *blast*  
 hence *e-mod-disj-n*:  $\text{elect } n \ V \ A \ p \cup \text{reject } n \ V \ A \ p \cup \text{defer } n \ V \ A \ p = A$   
 using *prof-p module-n*  
 by *metis*  
 have  $\forall m' n' A' V' p' (b :: 'a).$   
 $\text{mod-contains-result } m' n' V' A' p' b =$   
 $(\text{SCF-result.electoral-module } m'$   
 $\wedge \text{SCF-result.electoral-module } n'$   
 $\wedge \text{profile } V' A' p' \wedge b \in A'$   
 $\wedge (b \in \text{elect } m' V' A' p' \longrightarrow b \in \text{elect } n' V' A' p')$   
 $\wedge (b \in \text{reject } m' V' A' p' \longrightarrow b \in \text{reject } n' V' A' p')$   
 $\wedge (b \in \text{defer } m' V' A' p' \longrightarrow b \in \text{defer } n' V' A' p'))$   
 unfolding *mod-contains-result-def*  
 by *simp*

**hence**  $a \notin \text{defer } n \ V \ A \ p$   
**using**  $a\text{-not-mpar-rej } a\text{-in-}A \ e\text{-mod-par } \text{module-}n \ \text{not-}a\text{-elect}$   
 $\text{not-mod-cont-mn } \text{prof-}p$   
**by** *blast*  
**hence**  $a \in \text{reject } n \ V \ A \ p$   
**using**  $a\text{-in-}A \ a\text{-not-elect-mn } \text{module-}n \ \text{not-rej-imp-elec-or-defer } \text{prof-}p$   
**by** *metis*  
**hence**  $a \notin \text{reject } m \ V \ A \ p$   
**using**  $\text{well-f-max } \text{max-agg-res } \text{result-}m \ \text{result-}n \ \text{set-intersect}$   
 $\text{wf-}m \ \text{wf-}n \ a\text{-not-mpar-rej}$   
**unfolding**  $\text{maximum-parallel-composition.simps}$   
**by**  $(\text{metis } (\text{no-types}))$   
**hence**  $a \notin \text{defer } (m \parallel_{\uparrow} n) \ V \ A \ p \vee a \in \text{defer } m \ V \ A \ p$   
**using**  $e\text{-mod-disj } \text{prof-}p \ a\text{-in-}A \ \text{module-}m \ a\text{-not-elect-mn}$   
**by** *blast*  
**thus**  $\text{mod-contains-result } (m \parallel_{\uparrow} n) \ m \ V \ A \ p \ a$   
**using**  $a\text{-not-mpar-rej } \text{mod-cont-res-fg } e\text{-mod-par } \text{prof-}p \ a\text{-in-}A$   
 $\text{module-}m \ a\text{-not-elect}$   
**unfolding**  $\text{maximum-parallel-composition.simps}$   
**by** *metis*  
**qed**  
**next**  
**assume**  $\text{not-}a\text{-defer}: a \notin \text{defer } (m \parallel_{\uparrow} n) \ V \ A \ p$   
**have**  $\text{el-rej-defer}: (\text{elect } m \ V \ A \ p, \text{reject } m \ V \ A \ p, \text{defer } m \ V \ A \ p) = m \ V \ A \ p$   
**by** *auto*  
**from**  $\text{not-}a\text{-elect } \text{not-}a\text{-defer}$   
**have**  $a\text{-reject}: a \in \text{reject } (m \parallel_{\uparrow} n) \ V \ A \ p$   
**using**  $\text{electoral-mod-defer-elem } a\text{-in-}A \ \text{module-}m$   
 $\text{module-}n \ \text{prof-}p \ \text{max-par-comp-sound}$   
**by** *metis*  
**hence**  $\text{case } \text{snd } (m \ V \ A \ p) \text{ of } (r, d) \Rightarrow$   
 $\text{case } n \ V \ A \ p \text{ of } (e', r', d') \Rightarrow$   
 $a \in \text{reject-}r \ (\text{max-aggregator } A \ (\text{elect } m \ V \ A \ p, r, d) \ (e', r', d'))$   
**using**  $\text{el-rej-defer}$   
**by** *force*  
**hence**  $\text{let } (e, r, d) = m \ V \ A \ p;$   
 $(e', r', d') = n \ V \ A \ p \text{ in}$   
 $a \in \text{reject-}r \ (\text{max-aggregator } A \ (e, r, d) \ (e', r', d'))$   
**unfolding**  $\text{case-prod-unfold}$   
**by** *simp*  
**hence**  $\text{let } (e, r, d) = m \ V \ A \ p;$   
 $(e', r', d') = n \ V \ A \ p \text{ in}$   
 $a \in A - (e \cup e' \cup d \cup d')$   
**by** *simp*  
**hence**  $a \notin \text{elect } m \ V \ A \ p \cup (\text{defer } n \ V \ A \ p \cup \text{defer } m \ V \ A \ p)$   
**by** *force*  
**thus**  $?thesis$   
**using**  $\text{mod-contains-result-comm } \text{mod-contains-result-def } \text{Un-iff}$   
 $a\text{-reject } \text{prof-}p \ a\text{-in-}A \ \text{module-}m \ \text{module-}n \ \text{max-par-comp-sound}$

by (*metis* (*no-types*))  
 qed  
 qed

**lemma** *max-agg-rej-iff-both-reject*:  
 fixes  
 $m\ n :: ('a, 'v, 'a\ Result)\ Electoral\ Module$  and  
 $A :: 'a\ set$  and  
 $V :: 'v\ set$  and  
 $p :: ('a, 'v)\ Profile$  and  
 $a :: 'a$   
 assumes  
*finite-profile*  $V\ A\ p$  and  
*SCF-result.electoral-module*  $m$  and  
*SCF-result.electoral-module*  $n$   
 shows  $(a \in reject\ (m \parallel_{\uparrow} n)\ V\ A\ p) =$   
 $(a \in reject\ m\ V\ A\ p \wedge a \in reject\ n\ V\ A\ p)$

**proof**  
 assume *rej-a*:  $a \in reject\ (m \parallel_{\uparrow} n)\ V\ A\ p$   
 hence *case n*  $V\ A\ p$  of  $(e, r, d) \Rightarrow$   
 $a \in reject\text{-}r\ (max\text{-}aggregator\ A$   
 $(elect\ m\ V\ A\ p, reject\ m\ V\ A\ p, defer\ m\ V\ A\ p)\ (e, r, d))$   
 by *auto*  
 hence *case snd*  $(m\ V\ A\ p)$  of  $(r, d) \Rightarrow$   
 $case\ n\ V\ A\ p$  of  $(e', r', d') \Rightarrow$   
 $a \in reject\text{-}r\ (max\text{-}aggregator\ A\ (elect\ m\ V\ A\ p, r, d)\ (e', r', d'))$   
 by *force*  
 with *rej-a*  
 have *let*  $(e, r, d) = m\ V\ A\ p;$   
 $(e', r', d') = n\ V\ A\ p$  in  
 $a \in reject\text{-}r\ (max\text{-}aggregator\ A\ (e, r, d)\ (e', r', d'))$   
 unfolding *prod.case-eq-if*  
 by *simp*  
 hence *let*  $(e, r, d) = m\ V\ A\ p;$   
 $(e', r', d') = n\ V\ A\ p$  in  
 $a \in A - (e \cup e' \cup d \cup d')$   
 by *simp*  
 hence  
 $a \in A - (elect\ m\ V\ A\ p \cup elect\ n\ V\ A\ p \cup defer\ m\ V\ A\ p \cup defer\ n\ V\ A\ p)$   
 by *auto*  
 thus  $a \in reject\ m\ V\ A\ p \wedge a \in reject\ n\ V\ A\ p$   
 using *Diff-iff Un-iff electoral-mod-defer-elem assms*  
 by *metis*

**next**  
 assume  $a \in reject\ m\ V\ A\ p \wedge a \in reject\ n\ V\ A\ p$   
 moreover from *this*  
 have  $a \notin elect\ m\ V\ A\ p \wedge a \notin defer\ m\ V\ A\ p$   
 $\wedge a \notin elect\ n\ V\ A\ p \wedge a \notin defer\ n\ V\ A\ p$   
 using *IntI empty-iff assms result-disj*

```

    by metis
  ultimately show  $a \in \text{reject } (m \parallel_{\uparrow} n) \ V \ A \ p$ 
  using DiffD1 max-agg-eq-result mod-contains-result-comm mod-contains-result-def
    reject-not-elected-or-deferred assms
  by (metis (no-types))
qed

lemma max-agg-rej-fst-imp-seq-contained:
  fixes
     $m \ n :: ('a, 'v, 'a \text{ Result}) \text{ Electoral-Module}$  and
     $A :: 'a \text{ set}$  and
     $V :: 'v \text{ set}$  and
     $p :: ('a, 'v) \text{ Profile}$  and
     $a :: 'a$ 
  assumes
     $f\text{-prof}: \text{finite-profile } V \ A \ p$  and
     $\text{module-}m: \text{SCF-result.electoral-module } m$  and
     $\text{module-}n: \text{SCF-result.electoral-module } n$  and
     $\text{rejected}: a \in \text{reject } n \ V \ A \ p$ 
  shows  $\text{mod-contains-result } m \ (m \parallel_{\uparrow} n) \ V \ A \ p \ a$ 
  using assms
proof (unfold mod-contains-result-def, safe)
  show  $\text{SCF-result.electoral-module } (m \parallel_{\uparrow} n)$ 
  using module-m module-n max-par-comp-sound
  by metis
next
  show  $a \in A$ 
  using  $f\text{-prof}$  module-n rejected reject-in-alts
  by blast
next
  assume  $a\text{-in-elect}: a \in \text{elect } m \ V \ A \ p$ 
  hence  $a\text{-not-reject}: a \notin \text{reject } m \ V \ A \ p$ 
  using disjoint-iff-not-equal  $f\text{-prof}$  module-m result-disj
  by metis
  have  $\text{reject } n \ V \ A \ p \subseteq A$ 
  using  $f\text{-prof}$  module-n
  by (simp add: reject-in-alts)
  hence  $a \in A$ 
  using in-mono rejected
  by metis
  with  $a\text{-in-elect}$   $a\text{-not-reject}$ 
  show  $a \in \text{elect } (m \parallel_{\uparrow} n) \ V \ A \ p$ 
  using  $f\text{-prof}$  max-agg-eq-result module-m module-n rejected
    max-agg-rej-iff-both-reject mod-contains-result-comm
    mod-contains-result-def
  by metis
next
  assume  $a \in \text{reject } m \ V \ A \ p$ 
  hence  $a \in \text{reject } m \ V \ A \ p \wedge a \in \text{reject } n \ V \ A \ p$ 

```



```

    using rejected
    by simp
  thus  $a \in \text{reject } (m \parallel_{\uparrow} n) \ V \ A \ p$ 
    using f-prof max-agg-rej-iff-both-reject module-m module-n
    by (metis (no-types))
next
  assume a-in-defer:  $a \in \text{defer } m \ V \ A \ p$ 
  then obtain  $d :: 'a$  where
    defer-a:  $a = d \wedge d \in \text{defer } m \ V \ A \ p$ 
    by metis
  have a-not-rej:  $a \notin \text{reject } m \ V \ A \ p$ 
    using disjoint-iff-not-equal f-prof defer-a module-m result-disj
    by (metis (no-types))
  have
     $\forall m' A' V' p'. \text{SCF-result.electoral-module } m' \wedge \text{finite } A' \wedge \text{finite } V' \wedge \text{profile } V' \ A' \ p' \longrightarrow \text{elect } m' \ V' \ A' \ p' \cup \text{reject } m' \ V' \ A' \ p' \cup \text{defer } m' \ V' \ A' \ p' = A'$ 
    using result-presv-alts
    by metis
  hence  $a \in A$ 
    using a-in-defer f-prof module-m
    by blast
  with defer-a a-not-rej
  show  $a \in \text{defer } (m \parallel_{\uparrow} n) \ V \ A \ p$ 
    using f-prof max-agg-eq-result max-agg-rej-iff-both-reject
      mod-contains-result-comm mod-contains-result-def
      module-m module-n rejected
    by metis
qed

```

**lemma** *max-agg-rej-fst-equiv-seq-contained:*

```

  fixes
     $m \ n :: ('a, 'v, 'a \text{ Result}) \text{ Electoral-Module}$  and
     $A :: 'a \text{ set}$  and
     $V :: 'v \text{ set}$  and
     $p :: ('a, 'v) \text{ Profile}$  and
     $a :: 'a$ 
  assumes
    finite-profile  $V \ A \ p$  and
    SCF-result.electoral-module  $m$  and
    SCF-result.electoral-module  $n$  and
     $a \in \text{reject } n \ V \ A \ p$ 
  shows mod-contains-result-sym  $(m \parallel_{\uparrow} n) \ m \ V \ A \ p \ a$ 
    using assms
  proof (unfold mod-contains-result-sym-def, safe)
    assume  $a \in \text{reject } (m \parallel_{\uparrow} n) \ V \ A \ p$ 
    thus  $a \in \text{reject } m \ V \ A \ p$ 
      using assms max-agg-rej-iff-both-reject
      by (metis (no-types))
  qed

```

```

next
  have mod-contains-result  $m \ (m \parallel_{\uparrow} n) \ V \ A \ p \ a$ 
    using assms max-agg-rej-fst-imp-seq-contained
    by (metis (full-types))
  thus
     $a \in \text{elect } (m \parallel_{\uparrow} n) \ V \ A \ p \implies a \in \text{elect } m \ V \ A \ p$  and
     $a \in \text{defer } (m \parallel_{\uparrow} n) \ V \ A \ p \implies a \in \text{defer } m \ V \ A \ p$ 
    using mod-contains-result-comm
    unfolding mod-contains-result-def
    by (metis (full-types), metis (full-types))
next
  show
    SCF-result.electoral-module  $(m \parallel_{\uparrow} n)$  and
     $a \in A$ 
    using assms max-agg-rej-fst-imp-seq-contained
    unfolding mod-contains-result-def
    by (metis (full-types), metis (full-types))
next
  show
     $a \in \text{elect } m \ V \ A \ p \implies a \in \text{elect } (m \parallel_{\uparrow} n) \ V \ A \ p$  and
     $a \in \text{reject } m \ V \ A \ p \implies a \in \text{reject } (m \parallel_{\uparrow} n) \ V \ A \ p$  and
     $a \in \text{defer } m \ V \ A \ p \implies a \in \text{defer } (m \parallel_{\uparrow} n) \ V \ A \ p$ 
    using assms max-agg-rej-fst-imp-seq-contained
    unfolding mod-contains-result-def
    by (metis (no-types), metis (no-types), metis (no-types))
qed

lemma max-agg-rej-snd-imp-seq-contained:
  fixes
     $m \ n :: ('a, 'v, 'a \text{ Result}) \text{ Electoral-Module}$  and
     $A :: 'a \text{ set}$  and
     $V :: 'v \text{ set}$  and
     $p :: ('a, 'v) \text{ Profile}$  and
     $a :: 'a$ 
  assumes
    f-prof: finite-profile  $V \ A \ p$  and
    module-m: SCF-result.electoral-module  $m$  and
    module-n: SCF-result.electoral-module  $n$  and
    rejected: a \in reject m V A p
  shows mod-contains-result  $n \ (m \parallel_{\uparrow} n) \ V \ A \ p \ a$ 
  using assms
proof (unfold mod-contains-result-def, safe)
  show SCF-result.electoral-module  $(m \parallel_{\uparrow} n)$ 
    using module-m module-n max-par-comp-sound
    by metis
next
  show  $a \in A$ 
    using f-prof in-mono module-m reject-in-alts rejected
    by (metis (no-types))

```

```

next
  assume  $a \in \text{elect } n \ V \ A \ p$ 
  thus  $a \in \text{elect } (m \parallel_{\uparrow} n) \ V \ A \ p$ 
  using  $\text{max-aggregator.simps[of}$ 
    -  $\text{elect } m \ V \ A \ p \ \text{reject } m \ V \ A \ p \ \text{defer } m \ V \ A \ p$ 
    -  $\text{elect } n \ V \ A \ p \ \text{reject } n \ V \ A \ p \ \text{defer } n \ V \ A \ p]$ 
  by  $\text{simp}$ 
next
  assume  $a \in \text{reject } n \ V \ A \ p$ 
  thus  $a \in \text{reject } (m \parallel_{\uparrow} n) \ V \ A \ p$ 
  using  $\text{f-prof max-agg-rej-iff-both-reject module-m module-n rejected}$ 
  by  $\text{metis}$ 
next
  assume  $a \in \text{defer } n \ V \ A \ p$ 
  moreover have  $a \in A$ 
  using  $\text{f-prof max-agg-rej-fst-imp-seq-contained module-m rejected}$ 
  unfolding  $\text{mod-contains-result-def}$ 
  by  $\text{metis}$ 
  ultimately show  $a \in \text{defer } (m \parallel_{\uparrow} n) \ V \ A \ p$ 
  using  $\text{disjoint-iff-not-equal max-agg-eq-result max-agg-rej-iff-both-reject}$ 
     $\text{f-prof mod-contains-result-comm mod-contains-result-def}$ 
     $\text{module-m module-n rejected result-disj}$ 
  by  $(\text{metis } (\text{no-types}, \text{opaque-lifting}))$ 
qed

lemma  $\text{max-agg-rej-snd-equiv-seq-contained}$ :
  fixes
     $m \ n :: ('a, 'v, 'a \ \text{Result}) \ \text{Electoral-Module}$  and
     $A :: 'a \ \text{set}$  and
     $V :: 'v \ \text{set}$  and
     $p :: ('a, 'v) \ \text{Profile}$  and
     $a :: 'a$ 
  assumes
     $\text{finite-profile } V \ A \ p$  and
     $\text{SCF-result.electoral-module } m$  and
     $\text{SCF-result.electoral-module } n$  and
     $a \in \text{reject } m \ V \ A \ p$ 
  shows  $\text{mod-contains-result-sym } (m \parallel_{\uparrow} n) \ n \ V \ A \ p \ a$ 
  using  $\text{assms}$ 
proof (unfold  $\text{mod-contains-result-sym-def}$ , safe)
  assume  $a \in \text{reject } (m \parallel_{\uparrow} n) \ V \ A \ p$ 
  thus  $a \in \text{reject } n \ V \ A \ p$ 
  using  $\text{assms max-agg-rej-iff-both-reject}$ 
  by  $(\text{metis } (\text{no-types}))$ 
next
  have  $\text{mod-contains-result } n \ (m \parallel_{\uparrow} n) \ V \ A \ p \ a$ 
  using  $\text{assms max-agg-rej-snd-imp-seq-contained}$ 
  by  $(\text{metis } (\text{full-types}))$ 
  thus

```

```

    a ∈ elect (m ||↑ n) V A p ⇒ a ∈ elect n V A p and
    a ∈ defer (m ||↑ n) V A p ⇒ a ∈ defer n V A p
using mod-contains-result-comm
unfolding mod-contains-result-def
by (metis (full-types), metis (full-types))
next
show
  SCF-result.electoral-module (m ||↑ n) and
  a ∈ A
using assms max-agg-rej-snd-imp-seq-contained
unfolding mod-contains-result-def
by (metis (full-types), metis (full-types))
next
show
  a ∈ elect n V A p ⇒ a ∈ elect (m ||↑ n) V A p and
  a ∈ reject n V A p ⇒ a ∈ reject (m ||↑ n) V A p and
  a ∈ defer n V A p ⇒ a ∈ defer (m ||↑ n) V A p
using assms max-agg-rej-snd-imp-seq-contained
unfolding mod-contains-result-def
by (metis (no-types), metis (no-types), metis (no-types))
qed

lemma max-agg-rej-intersect:
fixes
  m n :: ('a, 'v, 'a Result) Electoral-Module and
  A :: 'a set and
  V :: 'v set and
  p :: ('a, 'v) Profile
assumes
  SCF-result.electoral-module m and
  SCF-result.electoral-module n and
  profile V A p and
  finite A
shows reject (m ||↑ n) V A p = (reject m V A p) ∩ (reject n V A p)
proof –
have A = (elect m V A p) ∪ (reject m V A p) ∪ (defer m V A p)
  ∧ A = (elect n V A p) ∪ (reject n V A p) ∪ (defer n V A p)
using assms result-presv-alts
by metis
hence A – ((elect m V A p) ∪ (defer m V A p)) = (reject m V A p)
  ∧ A – ((elect n V A p) ∪ (defer n V A p)) = (reject n V A p)
using assms reject-not-elected-or-deferred
by fastforce
hence
  A – ((elect m V A p) ∪ (elect n V A p)
    ∪ (defer m V A p) ∪ (defer n V A p)) =
  (reject m V A p) ∩ (reject n V A p)
by blast
hence let (e, r, d) = m V A p;

```

```

      (e', r', d') = n V A p in
      A - (e ∪ e' ∪ d ∪ d') = r ∩ r'
    by fastforce
  thus ?thesis
    by auto
qed

lemma dcompat-dec-by-one-mod:
  fixes
    m n :: ('a, 'v, 'a Result) Electoral-Module and
    A :: 'a set and
    V :: 'v set and
    a :: 'a
  assumes
    disjoint-compatibility m n and
    a ∈ A
  shows
    (∀ p. finite-profile V A p ⟶ mod-contains-result m (m ||↑ n) V A p a)
    ∨ (∀ p. finite-profile V A p ⟶ mod-contains-result n (m ||↑ n) V A p a)
  using DiffI assms max-agg-rej-fst-imp-seq-contained max-agg-rej-snd-imp-seq-contained
  unfolding disjoint-compatibility-def
  by metis

```

#### 6.6.4 Composition Rules

Using a conservative aggregator, the parallel composition preserves the property non-electing.

```

theorem conserv-max-agg-presv-non-electing[simp]:
  fixes m n :: ('a, 'v, 'a Result) Electoral-Module
  assumes
    non-electing m and
    non-electing n
  shows non-electing (m ||↑ n)
  using assms
  by simp

```

Using the max aggregator, composing two compatible electoral modules in parallel preserves defer-lift-invariance.

```

theorem par-comp-def-lift-inv[simp]:
  fixes m n :: ('a, 'v, 'a Result) Electoral-Module
  assumes
    compatible: disjoint-compatibility m n and
    monotone-m: defer-lift-invariance m and
    monotone-n: defer-lift-invariance n
  shows defer-lift-invariance (m ||↑ n)
proof (unfold defer-lift-invariance-def, safe)
  have mod-m: SCF-result.electoral-module m
  using monotone-m

```

```

    unfolding defer-lift-invariance-def
  by simp
moreover have mod-n: SCF-result.electoral-module n
  using monotone-n
  unfolding defer-lift-invariance-def
  by simp
ultimately show SCF-result.electoral-module (m ||↑ n)
  using max-par-comp-sound
  by metis
fix
  A :: 'a set and
  V :: 'v set and
  p q :: ('a, 'v) Profile and
  a :: 'a
assume
  defer-a: a ∈ defer (m ||↑ n) V A p and
  lifted-a: Profile.lifted V A p q a
hence f-profs: finite-profile V A p ∧ finite-profile V A q
  unfolding lifted-def
  by simp
from compatible
obtain B :: 'a set where
  alts: B ⊆ A
    ∧ (∀ b ∈ B. indep-of-alt m V A b ∧
      (∀ p'. finite-profile V A p' ⟶ b ∈ reject m V A p'))
    ∧ (∀ b ∈ A - B. indep-of-alt n V A b ∧
      (∀ p'. finite-profile V A p' ⟶ b ∈ reject n V A p'))
  using f-profs
  unfolding disjoint-compatibility-def
  by (metis (no-types, lifting))
have ∀ b ∈ A. prof-contains-result (m ||↑ n) V A p q b
proof (cases)
  assume a-in-B: a ∈ B
  hence a ∈ reject m V A p
    using alts f-profs
    by blast
  with defer-a
  have defer-n: a ∈ defer n V A p
    using compatible f-profs max-agg-rej-snd-equiv-seq-contained
    unfolding disjoint-compatibility-def mod-contains-result-sym-def
    by metis
  have ∀ b ∈ B. mod-contains-result-sym (m ||↑ n) n V A p b
    using alts compatible max-agg-rej-snd-equiv-seq-contained f-profs
    unfolding disjoint-compatibility-def
    by metis
  moreover have ∀ b ∈ A. prof-contains-result n V A p q b
proof (unfold prof-contains-result-def, clarify)
  fix b :: 'a
  assume b-in-A: b ∈ A

```

```

show SCF-result.electoral-module  $n \wedge \text{profile } V A p$ 
   $\wedge \text{profile } V A q \wedge b \in A \wedge$ 
   $(b \in \text{elect } n V A p \longrightarrow b \in \text{elect } n V A q) \wedge$ 
   $(b \in \text{reject } n V A p \longrightarrow b \in \text{reject } n V A q) \wedge$ 
   $(b \in \text{defer } n V A p \longrightarrow b \in \text{defer } n V A q)$ 
proof (safe)
  show SCF-result.electoral-module  $n$ 
    using monotone-n
    unfolding defer-lift-invariance-def
    by metis
next
show
  profile  $V A p$  and
  profile  $V A q$  and
   $b \in A$ 
  using f-profs b-in-A
  by (simp, simp, simp)
next
show
   $b \in \text{elect } n V A p \implies b \in \text{elect } n V A q$  and
   $b \in \text{reject } n V A p \implies b \in \text{reject } n V A q$  and
   $b \in \text{defer } n V A p \implies b \in \text{defer } n V A q$ 
  using defer-n lifted-a monotone-n f-profs
  unfolding defer-lift-invariance-def
  by (metis, metis, metis)
qed
qed
moreover have  $\forall b \in B. \text{mod-contains-result } n (m \parallel_{\uparrow} n) V A q b$ 
  using alts compatible max-agg-rej-snd-imp-seq-contained f-profs
  unfolding disjoint-compatibility-def
  by metis
ultimately have prof-contains-result-of-comps-for-elems-in-B:
   $\forall b \in B. \text{prof-contains-result } (m \parallel_{\uparrow} n) V A p q b$ 
  unfolding mod-contains-result-def mod-contains-result-sym-def
  prof-contains-result-def
  by simp
have  $\forall b \in A - B. \text{mod-contains-result-sym } (m \parallel_{\uparrow} n) m V A p b$ 
  using alts max-agg-rej-fst-equiv-seq-contained monotone-m monotone-n f-profs
  unfolding defer-lift-invariance-def
  by metis
moreover have  $\forall b \in A. \text{prof-contains-result } m V A p q b$ 
proof (unfold prof-contains-result-def, clarify)
  fix  $b :: 'a$ 
  assume b-in-A: b ∈ A
  show SCF-result.electoral-module  $m \wedge \text{profile } V A p \wedge$ 
    profile  $V A q \wedge b \in A \wedge$ 
     $(b \in \text{elect } m V A p \longrightarrow b \in \text{elect } m V A q) \wedge$ 
     $(b \in \text{reject } m V A p \longrightarrow b \in \text{reject } m V A q) \wedge$ 
     $(b \in \text{defer } m V A p \longrightarrow b \in \text{defer } m V A q)$ 

```

```

proof (safe)
  show SCF-result.electoral-module m
    using monotone-m
    unfolding defer-lift-invariance-def
    by metis
next
  show
    profile V A p and
    profile V A q and
    b ∈ A
    using f-profs b-in-A
    by (simp, simp, simp)
next
  show
    b ∈ elect m V A p ⇒ b ∈ elect m V A q and
    b ∈ reject m V A p ⇒ b ∈ reject m V A q and
    b ∈ defer m V A p ⇒ b ∈ defer m V A q
    using alts a-in-B lifted-a lifted-imp-equiv-prof-except-a
    unfolding indep-of-alt-def
    by (metis, metis, metis)
qed
qed
moreover have  $\forall b \in A - B. \text{mod-contains-result } m (m \parallel_{\uparrow} n) V A q b$ 
  using alts max-agg-rej-fst-imp-seq-contained monotone-m monotone-n f-profs
  unfolding defer-lift-invariance-def
  by metis
ultimately have  $\forall b \in A - B. \text{prof-contains-result } (m \parallel_{\uparrow} n) V A p q b$ 
  unfolding mod-contains-result-def mod-contains-result-sym-def
    prof-contains-result-def
  by simp
thus ?thesis
  using prof-contains-result-of-comps-for-elems-in-B
  by blast
next
  assume  $a \notin B$ 
  hence a-in-set-diff: a ∈ A - B
    using DiffI lifted-a compatible f-profs
    unfolding Profile.lifted-def
    by (metis (no-types, lifting))
  hence reject-n: a ∈ reject n V A p
    using alts f-profs
    by blast
  hence defer-m: a ∈ defer m V A p
    using mod-m mod-n defer-a f-profs max-agg-rej-fst-equiv-seq-contained
    unfolding mod-contains-result-sym-def
    by (metis (no-types))
  have  $\forall b \in B. \text{mod-contains-result } (m \parallel_{\uparrow} n) n V A p b$ 
  using alts compatible f-profs max-agg-rej-snd-imp-seq-contained mod-contains-result-comm
  unfolding disjoint-compatibility-def

```



by *metis*  
 have  $\forall b \in B. \text{mod-contains-result-sym } (m \parallel_{\uparrow} n) \ n \ V \ A \ p \ b$   
 using *alts max-agg-rej-snd-equiv-seq-contained monotone-m monotone-n f-profs*  
 unfolding *defer-lift-invariance-def*  
 by *metis*  
 moreover have  $\forall b \in A. \text{prof-contains-result } n \ V \ A \ p \ q \ b$   
 proof (unfold *prof-contains-result-def*, clarify)  
 fix  $b :: 'a$   
 assume *b-in-A*:  $b \in A$   
 show *SCF-result.electoral-module*  $n \wedge \text{profile } V \ A \ p \wedge$   
    $\text{profile } V \ A \ q \wedge b \in A \wedge$   
    $(b \in \text{elect } n \ V \ A \ p \longrightarrow b \in \text{elect } n \ V \ A \ q) \wedge$   
    $(b \in \text{reject } n \ V \ A \ p \longrightarrow b \in \text{reject } n \ V \ A \ q) \wedge$   
    $(b \in \text{defer } n \ V \ A \ p \longrightarrow b \in \text{defer } n \ V \ A \ q)$   
 proof (safe)  
 show *SCF-result.electoral-module*  $n$   
 using *monotone-n*  
 unfolding *defer-lift-invariance-def*  
 by *metis*  
 next  
 show  
    $\text{profile } V \ A \ p$  and  
    $\text{profile } V \ A \ q$  and  
    $b \in A$   
 using *f-profs b-in-A*  
 by (*simp, simp, simp*)  
 next  
 show  
    $b \in \text{elect } n \ V \ A \ p \implies b \in \text{elect } n \ V \ A \ q$  and  
    $b \in \text{reject } n \ V \ A \ p \implies b \in \text{reject } n \ V \ A \ q$  and  
    $b \in \text{defer } n \ V \ A \ p \implies b \in \text{defer } n \ V \ A \ q$   
 using *alts a-in-set-diff lifted-a lifted-imp-equiv-prof-except-a*  
 unfolding *indep-of-alt-def*  
 by (*metis, metis, metis*)  
 qed  
 qed  
 moreover have  $\forall b \in B. \text{mod-contains-result } n \ (m \parallel_{\uparrow} n) \ V \ A \ q \ b$   
 using *alts compatible max-agg-rej-snd-imp-seq-contained f-profs*  
 unfolding *disjoint-compatibility-def*  
 by *metis*  
 ultimately have *prof-contains-result-of-comps-for-elems-in-B*:  
    $\forall b \in B. \text{prof-contains-result } (m \parallel_{\uparrow} n) \ V \ A \ p \ q \ b$   
 unfolding *mod-contains-result-def mod-contains-result-sym-def*  
   *prof-contains-result-def*  
 by *simp*  
 have  $\forall b \in A - B. \text{mod-contains-result-sym } (m \parallel_{\uparrow} n) \ m \ V \ A \ p \ b$   
 using *alts max-agg-rej-fst-equiv-seq-contained monotone-m monotone-n f-profs*  
 unfolding *defer-lift-invariance-def*  
 by *metis*

```

moreover have  $\forall b \in A. \text{prof-contains-result } m \ V \ A \ p \ q \ b$ 
proof (unfold prof-contains-result-def, clarify)
  fix  $b :: 'a$ 
  assume  $b\text{-in-}A: b \in A$ 
  show  $SCF\text{-result.electoral-module } m \wedge \text{profile } V \ A \ p$ 
     $\wedge \text{profile } V \ A \ q \wedge b \in A$ 
     $\wedge (b \in \text{elect } m \ V \ A \ p \longrightarrow b \in \text{elect } m \ V \ A \ q)$ 
     $\wedge (b \in \text{reject } m \ V \ A \ p \longrightarrow b \in \text{reject } m \ V \ A \ q)$ 
     $\wedge (b \in \text{defer } m \ V \ A \ p \longrightarrow b \in \text{defer } m \ V \ A \ q)$ 
  proof (safe)
    show  $SCF\text{-result.electoral-module } m$ 
      using monotone-m
      unfolding defer-lift-invariance-def
      by simp
    next
      show
         $\text{profile } V \ A \ p$  and
         $\text{profile } V \ A \ q$  and
         $b \in A$ 
        using f-profs b-in-A
        by (simp, simp, simp)
      next
        show
           $b \in \text{elect } m \ V \ A \ p \Longrightarrow b \in \text{elect } m \ V \ A \ q$  and
           $b \in \text{reject } m \ V \ A \ p \Longrightarrow b \in \text{reject } m \ V \ A \ q$  and
           $b \in \text{defer } m \ V \ A \ p \Longrightarrow b \in \text{defer } m \ V \ A \ q$ 
          using defer-m lifted-a monotone-m
          unfolding defer-lift-invariance-def
          by (metis, metis, metis)
        qed
      qed
    moreover have  $\forall x \in A - B. \text{mod-contains-result } m \ (m \parallel_{\uparrow} n) \ V \ A \ q \ x$ 
      using alts max-agg-rej-fst-imp-seq-contained monotone-m monotone-n f-profs
      unfolding defer-lift-invariance-def
      by metis
    ultimately have  $\forall x \in A - B. \text{prof-contains-result } (m \parallel_{\uparrow} n) \ V \ A \ p \ q \ x$ 
      unfolding mod-contains-result-def mod-contains-result-sym-def
        prof-contains-result-def
      by simp
    thus ?thesis
      using prof-contains-result-of-comps-for-elems-in-B
      by blast
    qed
  thus  $(m \parallel_{\uparrow} n) \ V \ A \ p = (m \parallel_{\uparrow} n) \ V \ A \ q$ 
    using compatible f-profs eq-alts-in-profs-imp-eq-results max-par-comp-sound
    unfolding disjoint-compatibility-def
    by metis
  qed

```

**lemma** *par-comp-rej-card*:  
**fixes**  
 $m\ n :: ('a, 'v, 'a\ Result)\ Electoral\ Module$  **and**  
 $A :: 'a\ set$  **and**  
 $V :: 'v\ set$  **and**  
 $p :: ('a, 'v)\ Profile$  **and**  
 $c :: nat$   
**assumes**  
 $compatible: disjoint-compatibility\ m\ n$  **and**  
 $prof: profile\ V\ A\ p$  **and**  
 $fin-A: finite\ A$  **and**  
 $reject-sum: card\ (reject\ m\ V\ A\ p) + card\ (reject\ n\ V\ A\ p) = card\ A + c$   
**shows**  $card\ (reject\ (m\ ||_{\uparrow}\ n)\ V\ A\ p) = c$   
**proof** –  
**obtain**  $B :: 'a\ set$  **where**  
 $alt-set: B \subseteq A$   
 $\wedge (\forall a \in B. indep-of-alt\ m\ V\ A\ a \wedge$   
 $(\forall q. profile\ V\ A\ q \longrightarrow a \in reject\ m\ V\ A\ q))$   
 $\wedge (\forall a \in A - B. indep-of-alt\ n\ V\ A\ a \wedge$   
 $(\forall q. profile\ V\ A\ q \longrightarrow a \in reject\ n\ V\ A\ q))$   
**using** *compatible prof*  
**unfolding** *disjoint-compatibility-def*  
**by** *metis*  
**have** *reject-representation*:  
 $reject\ (m\ ||_{\uparrow}\ n)\ V\ A\ p = (reject\ m\ V\ A\ p) \cap (reject\ n\ V\ A\ p)$   
**using** *prof fin-A compatible max-agg-rej-intersect*  
**unfolding** *disjoint-compatibility-def*  
**by** *metis*  
**have** *SCF-result.electoral-module m*  $\wedge$  *SCF-result.electoral-module n*  
**using** *compatible*  
**unfolding** *disjoint-compatibility-def*  
**by** *simp*  
**hence** *subsets*:  $(reject\ m\ V\ A\ p) \subseteq A \wedge (reject\ n\ V\ A\ p) \subseteq A$   
**using** *prof*  
**by** *(simp add: reject-in-alts)*  
**hence**  $finite\ (reject\ m\ V\ A\ p) \wedge finite\ (reject\ n\ V\ A\ p)$   
**using** *rev-finite-subset prof fin-A*  
**by** *metis*  
**hence** *card-difference*:  
 $card\ (reject\ (m\ ||_{\uparrow}\ n)\ V\ A\ p)$   
 $= card\ A + c - card\ ((reject\ m\ V\ A\ p) \cup (reject\ n\ V\ A\ p))$   
**using** *card-Un-Int reject-representation reject-sum*  
**by** *fastforce*  
**have**  $\forall a \in A. a \in (reject\ m\ V\ A\ p) \vee a \in (reject\ n\ V\ A\ p)$   
**using** *alt-set prof fin-A*  
**by** *blast*  
**hence**  $A = reject\ m\ V\ A\ p \cup reject\ n\ V\ A\ p$   
**using** *subsets*  
**by** *force*

```

thus  $\text{card } (\text{reject } (m \parallel_{\uparrow} n) \ V \ A \ p) = c$ 
using card-difference
by simp
qed

```

Using the max-aggregator for composing two compatible modules in parallel, whereof the first one is non-electing and defers exactly one alternative, and the second one rejects exactly two alternatives, the composition results in an electoral module that eliminates exactly one alternative.

```

theorem par-comp-elim-one[simp]:
fixes  $m \ n :: ('a, 'v, 'a \text{ Result}) \text{ Electoral-Module}$ 
assumes
  defers-m-one: defers 1 m and
  non-elec-m: non-electing m and
  rejec-n-two: rejects 2 n and
  disj-comp: disjoint-compatibility m n
shows eliminates 1 (m  $\parallel_{\uparrow}$  n)
proof (unfold eliminates-def, safe)
have SCF-result.electoral-module m
using non-elec-m
unfolding non-electing-def
by simp
moreover have SCF-result.electoral-module n
using rejec-n-two
unfolding rejects-def
by simp
ultimately show SCF-result.electoral-module (m  $\parallel_{\uparrow}$  n)
using max-par-comp-sound
by metis
next
fix
   $A :: 'a \text{ set}$  and
   $V :: 'v \text{ set}$  and
   $p :: ('a, 'v) \text{ Profile}$ 
assume
  min-card-two:  $1 < \text{card } A$  and
  prof: profile V A p
hence card-geq-one:  $\text{card } A \geq 1$ 
by presburger
have fin-A: finite A
using min-card-two card.infinite not-one-less-zero
by metis
have module: SCF-result.electoral-module m
using non-elec-m
unfolding non-electing-def
by simp
have elect-card-zero:  $\text{card } (\text{elect } m \ V \ A \ p) = 0$ 
using prof non-elec-m card-eq-0-iff
unfolding non-electing-def

```

```

    by simp
  moreover from card-geq-one
  have def-card-one: card (defer m V A p) = 1
    using defers-m-one module prof fin-A
    unfolding defers-def
    by blast
  ultimately have card-reject-m: card (reject m V A p) = card A - 1
  proof -
    have well-formed-SCF A (elect m V A p, reject m V A p, defer m V A p)
      using prof module
      unfolding SCF-result.electoral-module.simps
      by simp
    hence card A =
      card (elect m V A p) + card (reject m V A p) + card (defer m V A p)
      using result-count fin-A
      by blast
    thus ?thesis
      using def-card-one elect-card-zero
      by simp
  qed
  have card A ≥ 2
    using min-card-two
    by simp
  hence card (reject n V A p) = 2
    using prof rejec-n-two fin-A
    unfolding rejects-def
    by blast
  moreover from this
  have card (reject m V A p) + card (reject n V A p) = card A + 1
    using card-reject-m card-geq-one
    by linarith
  ultimately show card (reject (m ||↑ n) V A p) = 1
    using disj-comp prof card-reject-m par-comp-rej-card fin-A
    by blast
  qed
end

```

## 6.7 Elect Composition

```

theory Elect-Composition
  imports Basic-Modules/ Elect-Module
    Sequential-Composition
begin

```

The elect composition sequences an electoral module and the elect module. It finalizes the module's decision as it simply elects all their non-rejected alternatives. Thereby, any such elect-composed module induces a proper voting rule in the social choice sense, as all alternatives are either rejected or elected.

### 6.7.1 Definition

```
fun elector :: ('a, 'v, 'a Result) Electoral-Module  $\Rightarrow$ 
  ('a, 'v, 'a Result) Electoral-Module where
  elector m = (m  $\triangleright$  elect-module)
```

### 6.7.2 Auxiliary Lemmas

```
lemma elector-seqcomp-assoc:
  fixes a b :: ('a, 'v, 'a Result) Electoral-Module
  shows (a  $\triangleright$  (elector b)) = (elector (a  $\triangleright$  b))
  unfolding elector.simps elect-module.simps sequential-composition.simps
  using boolean-algebra-cancel.sup2 sup-commute fst-conv snd-conv
  by (metis (no-types, opaque-lifting))
```

### 6.7.3 Soundness

```
theorem elector-sound[simp]:
  fixes m :: ('a, 'v, 'a Result) Electoral-Module
  assumes SCF-result.electoral-module m
  shows SCF-result.electoral-module (elector m)
  using assms elect-mod-sound seq-comp-sound
  unfolding elector.simps
  by metis
```

```
lemma voters-determine-elector:
  fixes m :: ('a, 'v, 'a Result) Electoral-Module
  assumes voters-determine-election m
  shows voters-determine-election (elector m)
  using assms elect-mod-only-voters voters-determine-seq-comp
  unfolding elector.simps
  by metis
```

### 6.7.4 Electing

```
theorem elector-electing[simp]:
  fixes m :: ('a, 'v, 'a Result) Electoral-Module
  assumes
    module-m: SCF-result.electoral-module m and
    non-block-m: non-blocking m
  shows electing (elector m)
proof –
  have  $\forall$  m'.
```

$(\neg \text{electing } m' \vee \text{SCF-result.electoral-module } m' \wedge$   
 $(\forall A' V' p'. (A' \neq \{\} \wedge \text{finite } A' \wedge \text{profile } V' A' p') \longrightarrow \text{elect } m' V' A' p' \neq \{\})) \wedge$   
 $(\text{electing } m' \vee \neg \text{SCF-result.electoral-module } m'$   
 $\vee (\exists A V p. (A \neq \{\} \wedge \text{finite } A \wedge \text{profile } V A p \wedge \text{elect } m' V A p = \{\})))$   
**unfolding** *electing-def*  
**by** *blast*  
**hence**  $\forall m'.$   
 $(\neg \text{electing } m' \vee \text{SCF-result.electoral-module } m' \wedge$   
 $(\forall A' V' p'. (A' \neq \{\} \wedge \text{finite } A' \wedge \text{profile } V' A' p') \longrightarrow \text{elect } m' V' A' p' \neq \{\})) \wedge$   
 $(\exists A V p. (\text{electing } m' \vee \neg \text{SCF-result.electoral-module } m' \vee A \neq \{\}$   
 $\wedge \text{finite } A \wedge \text{profile } V A p \wedge \text{elect } m' V A p = \{\})))$   
**by** *simp*  
**then obtain**  
 $A :: ('a, 'v, 'a \text{ Result}) \text{ Electoral-Module} \Rightarrow 'a \text{ set}$  **and**  
 $V :: ('a, 'v, 'a \text{ Result}) \text{ Electoral-Module} \Rightarrow 'v \text{ set}$  **and**  
 $p :: ('a, 'v, 'a \text{ Result}) \text{ Electoral-Module} \Rightarrow ('a, 'v) \text{ Profile}$  **where**  
*electing-mod*:  
 $\forall m' :: ('a, 'v, 'a \text{ Result}) \text{ Electoral-Module}.$   
 $(\neg \text{electing } m' \vee \text{SCF-result.electoral-module } m' \wedge$   
 $(\forall A' V' p'. (A' \neq \{\} \wedge \text{finite } A' \wedge \text{profile } V' A' p') \longrightarrow \text{elect } m' V' A' p' \neq \{\})) \wedge$   
 $(\text{electing } m' \vee \neg \text{SCF-result.electoral-module } m'$   
 $\vee A m' \neq \{\} \wedge \text{finite } (A m') \wedge \text{profile } (V m') (A m') (p m')$   
 $\wedge \text{elect } m' (V m') (A m') (p m') = \{\})$   
**by** *metis*  
**moreover have** *non-block*:  
*non-blocking*  $(\text{elect-module} :: 'v \text{ set} \Rightarrow 'a \text{ set} \Rightarrow ('a, 'v) \text{ Profile} \Rightarrow 'a \text{ Result})$   
**by** *(simp add: electing-imp-non-blocking)*  
**moreover obtain**  
 $e :: 'a \text{ Result} \Rightarrow 'a \text{ set}$  **and**  
 $r :: 'a \text{ Result} \Rightarrow 'a \text{ set}$  **and**  
 $d :: 'a \text{ Result} \Rightarrow 'a \text{ set}$  **where**  
*result*:  $\forall s. (e s, r s, d s) = s$   
**using** *disjoint3.cases*  
**by** *(metis (no-types))*  
**moreover from this**  
**have**  $\forall s. (\text{elect-r } s, r s, d s) = s$   
**by** *simp*  
**moreover from this**  
**have**  
 $\text{profile } (V (\text{elector } m)) (A (\text{elector } m)) (p (\text{elector } m)) \wedge \text{finite } (A (\text{elector } m))$   
 $\longrightarrow d (\text{elector } m) (V (\text{elector } m)) (A (\text{elector } m)) (p (\text{elector } m)) = \{\}$   
**by** *simp*  
**moreover have** *SCF-result.electoral-module (elector m)*  
**using** *elector-sound module-m*  
**by** *simp*  
**moreover from** *electing-mod result*

```

have finite (A (elector m))  $\wedge$ 
      profile (V (elector m)) (A (elector m)) (p (elector m))  $\wedge$ 
      elect (elector m) (V (elector m)) (A (elector m)) (p (elector m)) =  $\{\}$   $\wedge$ 
      d (elector m (V (elector m)) (A (elector m)) (p (elector m))) =  $\{\}$   $\wedge$ 
      reject (elector m) (V (elector m)) (A (elector m)) (p (elector m)) =
      r (elector m (V (elector m)) (A (elector m)) (p (elector m)))  $\longrightarrow$ 
      electing (elector m)
using Diff-empty elector.simps non-block-m snd-conv non-blocking-def
      reject-not-elected-or-deferred non-block seq-comp-presv-non-blocking
by (metis (mono-tags, opaque-lifting))
ultimately show ?thesis
using non-block-m
unfolding elector.simps
by auto
qed

```

### 6.7.5 Composition Rule

If *m* is defer-Condorcet-consistent, then *elector(m)* is Condorcet consistent.

```

lemma dcc-imp-cc-elector:
  fixes m :: ('a, 'v, 'a Result) Electoral-Module
  assumes defer-condorcet-consistency m
  shows condorcet-consistency (elector m)
proof (unfold defer-condorcet-consistency-def condorcet-consistency-def, safe)
  show SCF-result.electoral-module (elector m)
    using assms elector-sound
    unfolding defer-condorcet-consistency-def
    by metis
next
fix
  A :: 'a set and
  V :: 'v set and
  p :: ('a, 'v) Profile and
  w :: 'a
  assume c-win: condorcet-winner V A p w
  have fin-A: finite A
    using condorcet-winner.simps c-win
    by metis
  have fin-V: finite V
    using condorcet-winner.simps c-win
    by metis
  have prof-A: profile V A p
    using c-win
    by simp
  have max-card-w:  $\forall y \in A - \{w\}.$ 
    card  $\{i \in V. (w, y) \in (p i)\}$ 
    < card  $\{i \in V. (y, w) \in (p i)\}$ 
    using c-win fin-V
    by simp

```



**have** *rej-is-complement*:  
 $\text{reject } m \ V \ A \ p = A - (\text{elect } m \ V \ A \ p \cup \text{defer } m \ V \ A \ p)$   
**using** *double-diff sup-bot.left-neutral Un-upper2 assms fin-A prof-A fin-V*  
*defer-condorcet-consistency-def elec-and-def-not-rej reject-in-alts*  
**by** (*metis (no-types, opaque-lifting)*)  
**have** *subset-in-win-set*:  $\text{elect } m \ V \ A \ p \cup \text{defer } m \ V \ A \ p \subseteq$   
 $\{e \in A. e \in A \wedge (\forall x \in A - \{e\}.$   
 $\text{card } \{i \in V. (e, x) \in p \ i\} < \text{card } \{i \in V. (x, e) \in p \ i\})\}$   
**proof** (*safe-step*)  
**fix**  $x :: 'a$   
**assume** *x-in-elect-or-defer*:  $x \in \text{elect } m \ V \ A \ p \cup \text{defer } m \ V \ A \ p$   
**hence** *x-eq-w*:  $x = w$   
**using** *Diff-empty Diff-iff assms cond-winner-unique c-win fin-A fin-V insert-iff*  
*snd-conv sup-bot.left-neutral fst-eqD*  
**unfolding** *defer-condorcet-consistency-def*  
**by** (*metis (mono-tags, lifting)*)  
**have**  $\forall x. x \in \text{elect } m \ V \ A \ p \longrightarrow x \in A$   
**using** *fin-A prof-A fin-V assms elect-in-alts in-mono*  
**unfolding** *defer-condorcet-consistency-def*  
**by** *metis*  
**moreover have**  $\forall x. x \in \text{defer } m \ V \ A \ p \longrightarrow x \in A$   
**using** *fin-A prof-A fin-V assms defer-in-alts in-mono*  
**unfolding** *defer-condorcet-consistency-def*  
**by** *metis*  
**ultimately have**  $x \in A$   
**using** *x-in-elect-or-defer*  
**by** *auto*  
**thus**  $x \in \{e \in A. e \in A \wedge$   
 $(\forall x \in A - \{e\}.$   
 $\text{card } \{i \in V. (e, x) \in p \ i\}$   
 $< \text{card } \{i \in V. (x, e) \in p \ i\})\}$   
**using** *x-eq-w max-card-w*  
**by** *auto*  
**qed**  
**moreover have**  
 $\{e \in A. e \in A \wedge$   
 $(\forall x \in A - \{e\}.$   
 $\text{card } \{i \in V. (e, x) \in p \ i\} <$   
 $\text{card } \{i \in V. (x, e) \in p \ i\})\}$   
 $\subseteq \text{elect } m \ V \ A \ p \cup \text{defer } m \ V \ A \ p$   
**proof** (*safe*)  
**fix**  $x :: 'a$   
**assume**  
*x-not-in-defer*:  $x \notin \text{defer } m \ V \ A \ p$  **and**  
 $x \in A$  **and**  
 $\forall x' \in A - \{x\}.$   
 $\text{card } \{i \in V. (x, x') \in p \ i\}$   
 $< \text{card } \{i \in V. (x', x) \in p \ i\}$   
**hence** *c-win-x: condorcet-winner V A p x*

```

using fin-A prof-A fin-V
by simp
have (SCF-result.electoral-module  $m \wedge \neg \text{defer-condorcet-consistency } m \longrightarrow$ 
 $(\exists A \ V \ rs \ a. \text{condorcet-winner } V \ A \ rs \ a \wedge$ 
 $m \ V \ A \ rs \neq (\{\}, A - \text{defer } m \ V \ A \ rs,$ 
 $\{a \in A. \text{condorcet-winner } V \ A \ rs \ a\})))$ 
 $\wedge (\text{defer-condorcet-consistency } m \longrightarrow$ 
 $(\forall A \ V \ rs \ a. \text{finite } A \longrightarrow \text{finite } V \longrightarrow \text{condorcet-winner } V \ A \ rs \ a \longrightarrow$ 
 $m \ V \ A \ rs =$ 
 $(\{\}, A - \text{defer } m \ V \ A \ rs, \{a \in A. \text{condorcet-winner } V \ A \ rs \ a\})))$ 
unfolding defer-condorcet-consistency-def
by blast
hence
 $m \ V \ A \ p = (\{\}, A - \text{defer } m \ V \ A \ p, \{a \in A. \text{condorcet-winner } V \ A \ p \ a\})$ 
using c-win-x assms fin-A fin-V
by blast
thus  $x \in \text{elect } m \ V \ A \ p$ 
using assms x-not-in-defer fin-A fin-V cond-winner-unique
defer-condorcet-consistency-def insertCI snd-conv c-win-x
by (metis (no-types, lifting))
qed
ultimately have
 $\text{elect } m \ V \ A \ p \cup \text{defer } m \ V \ A \ p =$ 
 $\{e \in A. e \in A \wedge$ 
 $(\forall x \in A - \{e\}.$ 
 $\text{card } \{i \in V. (e, x) \in p \ i\} <$ 
 $\text{card } \{i \in V. (x, e) \in p \ i\})\}$ 
by blast
thus  $\text{elector } m \ V \ A \ p =$ 
 $(\{e \in A. \text{condorcet-winner } V \ A \ p \ e\}, A - \text{elect } (\text{elector } m) \ V \ A \ p, \{\})$ 
using fin-A prof-A fin-V rej-is-complement
by simp
qed
end

```

## 6.8 Defer-One Loop Composition

```

theory Defer-One-Loop-Composition
imports Basic-Modules/Component-Types/Defer-Equal-Condition
Loop-Composition
Elect-Composition
begin

```

This is a family of loop compositions. It uses the same module in sequence

until either no new decisions are made or only one alternative is remaining in the defer-set. The second family herein uses the above family and subsequently elects the remaining alternative.

```
fun iter :: ('a, 'v, 'a Result) Electoral-Module  $\Rightarrow$ 
  ('a, 'v, 'a Result) Electoral-Module where
  iter m =
    (let t = defer-equal-condition 1 in
     (m  $\odot_t$ ))
```

```
abbreviation defer-one-loop :: ('a, 'v, 'a Result) Electoral-Module  $\Rightarrow$ 
  ('a, 'v, 'a Result) Electoral-Module ( $-\odot_{\exists!d}$  50) where
  m  $\odot_{\exists!d} \equiv$  iter m
```

```
fun iter-elect :: ('a, 'v, 'a Result) Electoral-Module  $\Rightarrow$ 
  ('a, 'v, 'a Result) Electoral-Module where
  iter-elect m = elector (m  $\odot_{\exists!d}$ )
```

### 6.8.1 Soundness

**theorem** *defer-one-loop-comp-sound*:

**fixes**

*m* :: ('a, 'v, 'a Result) Electoral-Module **and**

*t* :: 'a Termination-Condition

**assumes** *SCF-result.electoral-module* *m*

**shows** *SCF-result.electoral-module* (*m*  $\odot_{\exists!d}$ )

**using** *assms loop-comp-sound*

**unfolding** *Defer-One-Loop-Composition.iter.simps*

**by** *metis*

**end**

## Chapter 7

# Voting Rules

### 7.1 Plurality Rule

```
theory Plurality-Rule
  imports Compositional-Structures/Basic-Modules/Plurality-Module
           Compositional-Structures/Revision-Composition
           Compositional-Structures/Elect-Composition
begin
```

This is a definition of the plurality voting rule as elimination module as well as directly. In the former one, the max operator of the set of the scores of all alternatives is evaluated and is used as the threshold value.

#### 7.1.1 Definition

```
fun plurality-rule :: ('a, 'v, 'a Result) Electoral-Module where
  plurality-rule V A p = elector plurality V A p

fun plurality-rule' :: ('a, 'v, 'a Result) Electoral-Module where
  plurality-rule' V A p =
    (if finite A
     then ({a ∈ A. ∀ x ∈ A. win-count V p x ≤ win-count V p a},
           {a ∈ A. ∃ x ∈ A. win-count V p x > win-count V p a},
           {}))
     else (A, {}, {}))

lemma plurality-revision-equiv:
  fixes
    A :: 'a set and
    V :: 'v set and
    p :: ('a, 'v) Profile
  shows plurality V A p = (plurality-rule↓) V A p
  by fastforce

lemma plurality'-revision-equiv:
```

```

fixes
   $A :: 'a \text{ set}$  and
   $V :: 'v \text{ set}$  and
   $p :: ('a, 'v) \text{ Profile}$ 
shows  $\text{plurality}' V A p = (\text{plurality-rule}' \downarrow) V A p$ 
proof ( $\text{unfold } \text{plurality}'.\text{simps}$   $\text{revision-composition}.simps$ ,
   $\text{intro } \text{prod-eqI}$   $\text{equalityI}$   $\text{subsetI}$   $\text{prod.sel}$ )
fix  $b :: 'a$ 
assume
   $\text{assm}: b \in \text{fst}$ 
    ( $\text{if } \text{finite } A$ 
       $\text{then } (\{\}, \{a \in A. \exists x \in A. \text{win-count } V p a < \text{win-count } V p x\},$ 
         $\{a \in A. \forall x \in A. \text{win-count } V p x \leq \text{win-count } V p a\})$ 
       $\text{else } (\{\}, \{\}, A)$ )
have  $\text{finite } A \longrightarrow b \in \{\}$ 
  using  $\text{assm}$ 
  by  $\text{force}$ 
moreover have  $\text{infinite } A \longrightarrow b \in \{\}$ 
  using  $\text{assm}$ 
  by  $\text{fastforce}$ 
ultimately show
   $b \in \text{fst } (\{\}, A - \text{elect } \text{plurality-rule}' V A p, \text{elect } \text{plurality-rule}' V A p)$ 
  by  $\text{safe}$ 
next
fix  $b :: 'a$ 
assume  $b \in \text{fst } (\{\}, A - \text{elect } \text{plurality-rule}' V A p, \text{elect } \text{plurality-rule}' V A p)$ 
thus  $b \in \text{fst}$ 
  ( $\text{if } \text{finite } A$ 
     $\text{then } (\{\}, \{a \in A. \exists x \in A. \text{win-count } V p a < \text{win-count } V p x\},$ 
       $\{a \in A. \forall x \in A. \text{win-count } V p x \leq \text{win-count } V p a\})$ 
     $\text{else } (\{\}, \{\}, A)$ )
  by  $\text{force}$ 
next
fix  $b :: 'a$ 
assume
   $\text{assm}: b \in \text{fst } (\text{snd}$ 
    ( $\text{if } \text{finite } A$ 
       $\text{then } (\{\}, \{a \in A. \exists x \in A. \text{win-count } V p a < \text{win-count } V p x\},$ 
         $\{a \in A. \forall x \in A. \text{win-count } V p x \leq \text{win-count } V p a\})$ 
       $\text{else } (\{\}, \{\}, A)))$ 
  have  $\text{finite } A \longrightarrow$ 
     $b \in A - \{a \in A. \forall x \in A. \text{win-count } V p x \leq \text{win-count } V p a\}$ 
  using  $\text{assm}$ 
  by  $\text{fastforce}$ 
moreover have  $\text{infinite } A \longrightarrow b \in \{\}$ 
  using  $\text{assm}$ 
  by  $\text{fastforce}$ 
ultimately show
   $b \in \text{fst } (\text{snd } (\{\}, A - \text{elect } \text{plurality-rule}' V A p, \text{elect } \text{plurality-rule}' V A p))$ 

```

```

    by force
next
  fix  $b :: 'a$ 
  assume
     $assm: b \in$ 
       $fst (snd (\{\}, A - elect\ plurality-rule'\ V\ A\ p, elect\ plurality-rule'\ V\ A\ p))$ 
  have  $finite\ A \longrightarrow$ 
     $b \in A - \{a \in A. \forall\ x \in A. win-count\ V\ p\ x \leq win-count\ V\ p\ a\}$ 
    using  $assm$ 
    by fastforce
  moreover have  $infinite\ A \longrightarrow b \in \{\}$ 
    using  $assm$ 
    by fastforce
  ultimately show
     $b \in fst (snd$ 
      (if  $finite\ A$ 
        then  $(\{\}, \{a \in A. \exists\ x \in A. win-count\ V\ p\ a < win-count\ V\ p\ x\},$ 
           $\{a \in A. \forall\ x \in A. win-count\ V\ p\ x \leq win-count\ V\ p\ a\})$ 
        else  $(\{\}, \{\}, A))$ 
      using  $linorder-not-less$ 
    by force
next
  fix  $b :: 'a$ 
  assume
     $assm: b \in snd (snd$ 
      (if  $finite\ A$ 
        then  $(\{\}, \{a \in A. \exists\ x \in A. win-count\ V\ p\ a < win-count\ V\ p\ x\},$ 
           $\{a \in A. \forall\ x \in A. win-count\ V\ p\ x \leq win-count\ V\ p\ a\})$ 
        else  $(\{\}, \{\}, A))$ 
      have  $finite\ A \longrightarrow$ 
         $b \in A - \{a \in A. \exists\ x \in A. win-count\ V\ p\ a < win-count\ V\ p\ x\}$ 
        using  $assm$ 
        by fastforce
      moreover have  $infinite\ A \longrightarrow b \in A$ 
        using  $assm$ 
        by fastforce
      ultimately have  $b \in elect\ plurality-rule'\ V\ A\ p$ 
        by force
      thus  $b \in snd (snd$ 
         $(\{\}, A - elect\ plurality-rule'\ V\ A\ p, elect\ plurality-rule'\ V\ A\ p))$ 
        by simp
next
  fix  $b :: 'a$ 
  assume  $assm:$ 
     $b \in snd (snd (\{\}, A - elect\ plurality-rule'\ V\ A\ p, elect\ plurality-rule'\ V\ A\ p))$ 
  have  $finite\ A \longrightarrow$ 
     $b \in A - \{a \in A. \exists\ x \in A. win-count\ V\ p\ a < win-count\ V\ p\ x\}$ 
    using  $assm$ 
    by fastforce

```

```

moreover have infinite  $A \longrightarrow b \in A$ 
  using assm
  by fastforce
ultimately show  $b \in \text{snd} (\text{snd}$ 
  (if finite  $A$ 
    then  $(\{\}, \{a \in A. \exists x \in A. \text{win-count } V p a < \text{win-count } V p x\},$ 
       $\{a \in A. \forall x \in A. \text{win-count } V p x \leq \text{win-count } V p a\})$ 
    else  $(\{\}, \{\}, A))$ 
  by force
qed

lemma plurality-rule-equiv:
  fixes
     $A :: 'a \text{ set}$  and
     $V :: 'v \text{ set}$  and
     $p :: ('a, 'v) \text{ Profile}$ 
  shows  $\text{plurality-rule } V A p = \text{plurality-rule}' V A p$ 
proof (unfold plurality-rule.simps)
  have plurality-rule'-rev-equiv-plurality:
     $\text{plurality } V A p = (\text{plurality-rule}' \downarrow) V A p$ 
  using plurality-mod-equiv plurality'-revision-equiv
  by metis
  have defer (elector plurality) V A p = defer plurality-rule' V A p
  by force
  moreover have reject (elector plurality) V A p = reject plurality-rule' V A p
  using plurality-rule'-rev-equiv-plurality
  by force
  moreover have elect (elector plurality) V A p = elect plurality-rule' V A p
  using plurality-rule'-rev-equiv-plurality
  by force
  ultimately show  $\text{elector plurality } V A p = \text{plurality-rule}' V A p$ 
  using prod-eqI
  by (metis (mono-tags, lifting))
qed

```

### 7.1.2 Soundness

```

theorem plurality-rule-sound[simp]: SCF-result.electoral-module plurality-rule
  unfolding plurality-rule.simps
  using elector-sound plurality-sound
  by metis

theorem plurality-rule'-sound[simp]: SCF-result.electoral-module plurality-rule'
proof (unfold SCF-result.electoral-module.simps, safe)
  fix
     $A :: 'a \text{ set}$  and
     $V :: 'v \text{ set}$  and
     $p :: ('a, 'v) \text{ Profile}$ 
  have disjoint3 (

```

```

    {a ∈ A. ∀ a' ∈ A. win-count V p a' ≤ win-count V p a},
    {a ∈ A. ∃ a' ∈ A. win-count V p a < win-count V p a'},
    {}
  )
  by auto
  moreover have
    {a ∈ A. ∀ x ∈ A. win-count V p x ≤ win-count V p a} ∪
    {a ∈ A. ∃ x ∈ A. win-count V p a < win-count V p x} = A
  using not-le-imp-less
  by auto
  ultimately show well-formed-SCF A (plurality-rule' V A p)
  by simp
qed

lemma voters-determine-plurality-rule: voters-determine-election plurality-rule
  unfolding plurality-rule.simps
  using voters-determine-electors voters-determine-plurality
  by blast

lemma voters-determine-plurality-rule': voters-determine-election plurality-rule'
proof (unfold voters-determine-election.simps, safe)
  fix
    A :: 'k set and
    V :: 'v set and
    p p' :: ('k, 'v) Profile
  assume ∀ v ∈ V. p v = p' v
  thus plurality-rule' V A p = plurality-rule' V A p'
  using voters-determine-plurality-rule plurality-rule-equiv
  unfolding voters-determine-election.simps
  by (metis (full-types))
qed

```

### 7.1.3 Electing

```

lemma plurality-rule-elect-non-empty:
  fixes
    A :: 'a set and
    V :: 'v set and
    p :: ('a, 'v) Profile
  assumes
    A ≠ {} and
    finite A
  shows elect plurality-rule V A p ≠ {}
proof
  assume plurality-elect-none: elect plurality-rule V A p = {}
  obtain max :: enat where
    max: max = Max (win-count V p ` A)
  by simp
  then obtain a :: 'a where
    max-a: win-count V p a = max ∧ a ∈ A

```



```

    using Max-in assms empty-is-image finite-imageI imageE
    by (metis (no-types, lifting))
  hence  $\forall a' \in A. \text{win-count } V p a' \leq \text{win-count } V p a$ 
    using assms max
    by simp
  moreover have  $a \in A$ 
    using max-a
    by simp
  ultimately have  $a \in \{a' \in A. \forall c \in A. \text{win-count } V p c \leq \text{win-count } V p a'\}$ 
    by blast
  hence  $a \in \text{elect plurality-rule}' V A p$ 
    by simp
  moreover have  $\text{elect plurality-rule}' V A p = \text{defer plurality } V A p$ 
    using plurality-revision-equiv plurality-rule-equiv snd-conv
    unfolding revision-composition.simps
    by (metis (no-types, opaque-lifting))
  ultimately have  $a \in \text{defer plurality } V A p$ 
    by blast
  hence  $a \in \text{elect plurality-rule } V A p$ 
    by simp
  thus False
    using plurality-elect-none all-not-in-conv
    by metis
qed

```

```

lemma plurality-rule'-elect-non-empty:
  fixes
     $A :: 'a \text{ set}$  and
     $V :: 'v \text{ set}$  and
     $p :: ('a, 'v) \text{ Profile}$ 
  assumes
     $A \neq \{\}$  and
     $\text{profile } V A p$  and
     $\text{finite } A$ 
  shows  $\text{elect plurality-rule}' V A p \neq \{\}$ 
    using assms plurality-rule-elect-non-empty plurality-rule-equiv
    by metis

```

The plurality module is electing.

```

theorem plurality-rule-electing[simp]: electing plurality-rule
proof (unfold electing-def, safe)

```

```

  show SCF-result.electoral-module plurality-rule
    using plurality-rule-sound
    by simp

```

```

next

```

```

  fix
     $A :: 'b \text{ set}$  and
     $V :: 'a \text{ set}$  and
     $p :: ('b, 'a) \text{ Profile}$  and

```

```

  a :: 'b
assume
  fin-A: finite A and
  prof-p: profile V A p and
  elect-none: elect plurality-rule V A p = {} and
  a-in-A: a ∈ A
have ∀ B W q. B ≠ {} ∧ finite B ∧ profile W B q
  → elect plurality-rule W B q ≠ {}
  using plurality-rule-elect-non-empty
  by (metis (no-types))
hence empty-A: A = {}
  using fin-A prof-p elect-none
  by (metis (no-types))
thus a ∈ {}
  using a-in-A
  by simp
qed

theorem plurality-rule'-electing[simp]: electing plurality-rule'
proof (unfold electing-def, safe)
  show SCF-result.electoral-module plurality-rule'
  using plurality-rule'-sound
  by metis
next
fix
  A :: 'b set and
  V :: 'a set and
  p :: ('b, 'a) Profile and
  a :: 'b
assume
  fin-A: finite A and
  prof-p: profile V A p and
  no-elect': elect plurality-rule' V A p = {} and
  a-in-A: a ∈ A
have A-nonempty: A ≠ {}
  using a-in-A
  by blast
have elect plurality-rule V A p = {}
  using no-elect' plurality-rule-equiv
  by metis
moreover have elect plurality-rule V A p ≠ {}
  using fin-A prof-p A-nonempty plurality-rule'-elect-non-empty plurality-rule-equiv
  by metis
ultimately show a ∈ {}
  by force
qed

```

### 7.1.4 Properties

**lemma** *plurality-rule-inv-mono-eq*:

**fixes**

$A :: 'a \text{ set}$  **and**

$V :: 'v \text{ set}$  **and**

$p \ q :: ('a, 'v) \text{ Profile}$  **and**

$a :: 'a$

**assumes**

*elect-a*:  $a \in \text{elect } \text{plurality-rule } V \ A \ p$  **and**

*lift-a*: *lifted*  $V \ A \ p \ q \ a$

**shows**  $\text{elect } \text{plurality-rule } V \ A \ q = \text{elect } \text{plurality-rule } V \ A \ p$   
 $\vee \text{elect } \text{plurality-rule } V \ A \ q = \{a\}$

**proof** –

**have**  $a \in \text{elect } (\text{elector plurality}) \ V \ A \ p$

**using** *elect-a*

**by** *simp*

**moreover have**  $\text{eq-p}$ :  $\text{elect } (\text{elector plurality}) \ V \ A \ p = \text{defer plurality } V \ A \ p$

**by** *simp*

**ultimately have**  $a \in \text{defer plurality } V \ A \ p$

**by** *blast*

**hence**  $\text{defer plurality } V \ A \ q = \text{defer plurality } V \ A \ p$

$\vee \text{defer plurality } V \ A \ q = \{a\}$

**using** *lift-a plurality-def-inv-mono-alts*

**by** *metis*

**moreover have**  $\text{elect } (\text{elector plurality}) \ V \ A \ q = \text{defer plurality } V \ A \ q$

**by** *simp*

**ultimately show**

$\text{elect } \text{plurality-rule } V \ A \ q = \text{elect } \text{plurality-rule } V \ A \ p$

$\vee \text{elect } \text{plurality-rule } V \ A \ q = \{a\}$

**using** *eq-p*

**by** *simp*

**qed**

**lemma** *plurality-rule'-inv-mono-eq*:

**fixes**

$A :: 'a \text{ set}$  **and**

$V :: 'v \text{ set}$  **and**

$p \ q :: ('a, 'v) \text{ Profile}$  **and**

$a :: 'a$

**assumes**

$a \in \text{elect } \text{plurality-rule}' \ V \ A \ p$  **and**

*lifted*  $V \ A \ p \ q \ a$

**shows**  $\text{elect } \text{plurality-rule}' \ V \ A \ q = \text{elect } \text{plurality-rule}' \ V \ A \ p$   
 $\vee \text{elect } \text{plurality-rule}' \ V \ A \ q = \{a\}$

**using** *assms plurality-rule-equiv plurality-rule-inv-mono-eq*

**by** (*metis (no-types)*)

The plurality rule is invariant-monotone.

**theorem** *plurality-rule-inv-mono[simp]*: *invariant-monotonicity plurality-rule*

```

proof (unfold invariant-monotonicity-def, intro conjI impI allI)
  show SCF-result.electoral-module plurality-rule
    using plurality-rule-sound
    by metis
next
fix
  A :: 'b set and
  V :: 'a set and
  p q :: ('b, 'a) Profile and
  a :: 'b
assume a ∈ elect plurality-rule V A p ∧ Profile.lifted V A p q a
thus elect plurality-rule V A q = elect plurality-rule V A p
  ∨ elect plurality-rule V A q = {a}
using plurality-rule-inv-mono-eq
by metis
qed

theorem plurality-rule'-inv-mono[simp]: invariant-monotonicity plurality-rule'
proof –
  have (plurality-rule::('k, 'v, 'k Result) Electoral-Module) = plurality-rule'
    using plurality-rule-equiv
    by blast
  thus ?thesis
    using plurality-rule-inv-mono
    by (metis (full-types))
qed

(Weak) Monotonicity

theorem plurality-rule-monotone: monotonicity plurality-rule
proof (unfold monotonicity-def, safe)
  show SCF-result.electoral-module plurality-rule
    using plurality-rule-sound
    by (metis (no-types))
next
fix
  A :: 'b set and
  V :: 'a set and
  p q :: ('b, 'a) Profile and
  a :: 'b
assume
  a ∈ elect plurality-rule V A p and
  Profile.lifted V A p q a
thus a ∈ elect plurality-rule V A q
  using insertI1 plurality-rule-inv-mono-eq
  by (metis (no-types))
qed

end

```

## 7.2 Borda Rule

**theory** *Borda-Rule*

**imports** *Compositional-Structures/Basic-Modules/Borda-Module*

*Compositional-Structures/Basic-Modules/Component-Types/Votewise-Distance-Rationalization*

*Compositional-Structures/Elect-Composition*

**begin**

This is the Borda rule. On each ballot, each alternative is assigned a score that depends on how many alternatives are ranked below. The sum of all such scores for an alternative is hence called their Borda score. The alternative with the highest Borda score is elected.

### 7.2.1 Definition

**fun** *borda-rule* :: ('a, 'v, 'a Result) *Electoral-Module* **where**  
*borda-rule* *V A p* = *elector borda V A p*

**fun** *borda-rule<sub>R</sub>* :: ('a, 'v :: *wellorder*, 'a Result) *Electoral-Module* **where**  
*borda-rule<sub>R</sub>* *V A p* = *swap-R unanimity V A p*

### 7.2.2 Soundness

**theorem** *borda-rule-sound*: *SCF-result.electoral-module borda-rule*  
**unfolding** *borda-rule.simps*  
**using** *elector-sound borda-sound*  
**by** *metis*

**theorem** *borda-rule<sub>R</sub>-sound*: *SCF-result.electoral-module borda-rule<sub>R</sub>*  
**unfolding** *borda-rule<sub>R</sub>.simps swap-R.simps*  
**using** *SCF-result.R-sound*  
**by** *metis*

### 7.2.3 Anonymity

**theorem** *borda-rule<sub>R</sub>-anonymous*: *SCF-result.anonymity borda-rule<sub>R</sub>*

**proof** (*unfold borda-rule<sub>R</sub>.simps swap-R.simps*)

**let** *?swap-dist* = *votewise-distance swap l-one*

**from** *l-one-is-sym*

**have** *distance-anonymity ?swap-dist*

**using** *symmetric-norm-imp-distance-anonymous[of l-one]*

**by** *simp*

**with** *unanimity-anonymous*

**show** *SCF-result.anonymity (SCF-result.distance-R ?swap-dist unanimity)*

**using** *SCF-result.anonymous-distance-and-consensus-imp-rule-anonymity*

```

    by metis
qed

end

```

## 7.3 Pairwise Majority Rule

```

theory Pairwise-Majority-Rule
  imports Compositional-Structures/Basic-Modules/Condorcet-Module
           Compositional-Structures/Defer-One-Loop-Composition
begin

```

This is the pairwise majority rule, a voting rule that implements the Condorcet criterion, i.e., it elects the Condorcet winner if it exists, otherwise a tie remains between all alternatives.

### 7.3.1 Definition

```

fun pairwise-majority-rule :: ('a, 'v, 'a Result) Electoral-Module where
  pairwise-majority-rule V A p = elector condorcet V A p

fun condorcet' :: ('a, 'v, 'a Result) Electoral-Module where
  condorcet' V A p = ((min-eliminator condorcet-score)  $\circ$   $\exists!$ d) V A p

fun pairwise-majority-rule' :: ('a, 'v, 'a Result) Electoral-Module where
  pairwise-majority-rule' V A p = iter-elect condorcet' V A p

```

### 7.3.2 Soundness

```

theorem pairwise-majority-rule-sound: SCF-result.electoral-module pairwise-majority-rule
  unfolding pairwise-majority-rule.simps
  using condorcet-sound elector-sound
  by metis

theorem condorcet'-sound: SCF-result.electoral-module condorcet'
  using Defer-One-Loop-Composition.iter.elims loop-comp-sound min-elim-sound
  unfolding condorcet'.simps loop-comp-sound
  by metis

theorem pairwise-majority-rule'-sound: SCF-result.electoral-module pairwise-majority-rule'
  unfolding pairwise-majority-rule'.simps
  using condorcet'-sound elector-sound iter.simps iter-elect.simps loop-comp-sound
  by metis

```

### 7.3.3 Condorcet Consistency

**theorem** *condorcet-condorcet: condorcet-consistency pairwise-majority-rule*

**proof** (*unfold pairwise-majority-rule.simps*)

**show** *condorcet-consistency (elector condorcet)*

**using** *condorcet-is-dcc dcc-imp-cc-elector*

**by** *metis*

**qed**

**end**

## 7.4 Copeland Rule

**theory** *Copeland-Rule*

**imports** *Compositional-Structures/Basic-Modules/Copeland-Module*  
          *Compositional-Structures/Elect-Composition*

**begin**

This is the Copeland voting rule. The idea is to elect the alternatives with the highest difference between the amount of simple-majority wins and the amount of simple-majority losses.

### 7.4.1 Definition

**fun** *copeland-rule* :: ('a, 'v, 'a Result) Electoral-Module **where**

*copeland-rule V A p = elector copeland V A p*

### 7.4.2 Soundness

**theorem** *copeland-rule-sound: SCF-result.electoral-module copeland-rule*

**unfolding** *copeland-rule.simps*

**using** *elector-sound copeland-sound*

**by** *metis*

### 7.4.3 Condorcet Consistency

**theorem** *copeland-condorcet: condorcet-consistency copeland-rule*

**proof** (*unfold copeland-rule.simps*)

**show** *condorcet-consistency (elector copeland)*

**using** *copeland-is-dcc dcc-imp-cc-elector*

**by** *metis*

**qed**

**end**

## 7.5 Minimax Rule

```
theory Minimax-Rule
  imports Compositional-Structures/Basic-Modules/Minimax-Module
           Compositional-Structures/Elect-Composition
begin
```

This is the Minimax voting rule. It elects the alternatives with the highest Minimax score.

### 7.5.1 Definition

```
fun minimax-rule :: ('a, 'v, 'a Result) Electoral-Module where
  minimax-rule V A p = elector minimax V A p
```

### 7.5.2 Soundness

```
theorem minimax-rule-sound: SCF-result.electoral-module minimax-rule
  unfolding minimax-rule.simps
  using elector-sound minimax-sound
  by metis
```

### 7.5.3 Condorcet Consistency

```
theorem minimax-condorcet: condorcet-consistency minimax-rule
proof (unfold minimax-rule.simps)
  show condorcet-consistency (elector minimax)
    using minimax-is-dcc dcc-imp-cc-elect
    by metis
qed

end
```

## 7.6 Black's Rule

```
theory Blacks-Rule
  imports Pairwise-Majority-Rule
           Borda-Rule
begin
```

This is Black's voting rule. It is composed of a function that determines the Condorcet winner, i.e., the Pairwise Majority rule, and the Borda rule. Whenever there exists no Condorcet winner, it elects the choice made by the Borda rule, otherwise the Condorcet winner is elected.



### 7.6.1 Definition

**fun** *black* :: ('a, 'v, 'a Result) Electoral-Module **where**  
    *black* A p = (condorcet  $\triangleright$  borda) A p

**fun** *blacks-rule* :: ('a, 'v, 'a Result) Electoral-Module **where**  
    *blacks-rule* A p = elector *black* A p

### 7.6.2 Soundness

**theorem** *blacks-sound*: SCF-result.electoral-module *black*  
    **unfolding** *black.simps*  
    **using** *seq-comp-sound condorcet-sound borda-sound*  
    **by** *metis*

**theorem** *blacks-rule-sound*: SCF-result.electoral-module *blacks-rule*  
    **unfolding** *blacks-rule.simps*  
    **using** *blacks-sound elector-sound*  
    **by** *metis*

### 7.6.3 Condorcet Consistency

**theorem** *black-is-dcc*: defer-condorcet-consistency *black*  
    **unfolding** *black.simps*  
    **using** *condorcet-is-dcc borda-mod-non-blocking borda-mod-non-electing seq-comp-dcc*  
    **by** *metis*

**theorem** *black-condorcet*: condorcet-consistency *blacks-rule*  
    **unfolding** *blacks-rule.simps*  
    **using** *black-is-dcc dcc-imp-cc-elect*  
    **by** *metis*

**end**

## 7.7 Nanson-Baldwin Rule

**theory** *Nanson-Baldwin-Rule*  
    **imports** *Compositional-Structures/Basic-Modules/Borda-Module*  
            *Compositional-Structures/Defer-One-Loop-Composition*  
**begin**

This is the Nanson-Baldwin voting rule. It excludes alternatives with the lowest Borda score from the set of possible winners and then adjusts the Borda score to the new (remaining) set of still eligible alternatives.

### 7.7.1 Definition

**fun** *nanson-baldwin-rule* :: ('a, 'v, 'a Result) Electoral-Module **where**  
  *nanson-baldwin-rule* A p =  
    ((*min-eliminator borda-score*)  $\odot_{\exists!d}$ ) A p

### 7.7.2 Soundness

**theorem** *nanson-baldwin-rule-sound*: SCF-result.electoral-module *nanson-baldwin-rule*  
  **using** *min-elim-sound loop-comp-sound*  
  **unfolding** *nanson-baldwin-rule.simps Defer-One-Loop-Composition.iter.simps*  
  **by** *metis*  
  
**end**

## 7.8 Classic Nanson Rule

**theory** *Classic-Nanson-Rule*  
  **imports** *Compositional-Structures/Basic-Modules/Borda-Module*  
          *Compositional-Structures/Defer-One-Loop-Composition*  
**begin**

This is the classic Nanson's voting rule, i.e., the rule that was originally invented by Nanson, but not the Nanson-Baldwin rule. The idea is similar, however, as alternatives with a Borda score less or equal than the average Borda score are excluded. The Borda scores of the remaining alternatives are hence adjusted to the new set of (still) eligible alternatives.

### 7.8.1 Definition

**fun** *classic-nanson-rule* :: ('a, 'v, 'a Result) Electoral-Module **where**  
  *classic-nanson-rule* V A p =  
    ((*leq-average-eliminator borda-score*)  $\odot_{\exists!d}$ ) V A p

### 7.8.2 Soundness

**theorem** *classic-nanson-rule-sound*: SCF-result.electoral-module *classic-nanson-rule*  
  **using** *leq-avg-elim-sound loop-comp-sound*  
  **unfolding** *classic-nanson-rule.simps Defer-One-Loop-Composition.iter.simps*  
  **by** *metis*  
  
**end**

## 7.9 Schwartz Rule

```
theory Schwartz-Rule
  imports Compositional-Structures/Basic-Modules/Borda-Module
           Compositional-Structures/Defer-One-Loop-Composition
begin
```

This is the Schwartz voting rule. Confusingly, it is sometimes also referred as Nanson's rule. The Schwartz rule proceeds as in the classic Nanson's rule, but excludes alternatives with a Borda score that is strictly less than the average Borda score.

### 7.9.1 Definition

```
fun schwartz-rule :: ('a, 'v, 'a Result) Electoral-Module where
  schwartz-rule V A p =
    ((less-average-eliminator borda-score)  $\odot_{\exists!d}$ ) V A p
```

### 7.9.2 Soundness

```
theorem schwartz-rule-sound: SCF-result.electoral-module schwartz-rule
  using less-avg-elim-sound loop-comp-sound
  unfolding schwartz-rule.simps Defer-One-Loop-Composition.iter.simps
  by metis

end
```

## 7.10 Sequential Majority Comparison

```
theory Sequential-Majority-Comparison
  imports Plurality-Rule
           Compositional-Structures/Drop-And-Pass-Compatibility
           Compositional-Structures/Revision-Composition
           Compositional-Structures/Maximum-Parallel-Composition
           Compositional-Structures/Defer-One-Loop-Composition
begin
```

Sequential majority comparison compares two alternatives by plurality voting. The loser gets rejected, and the winner is compared to the next alternative. This process is repeated until only a single alternative is left, which is then elected.

### 7.10.1 Definition

```
fun smc :: 'a Preference-Relation  $\Rightarrow$  ('a, 'v, 'a Result) Electoral-Module where
```

```

smc x V A p =
  ((elector (((pass-module 2 x) ▷ ((plurality-rule↓) ▷ (pass-module 1 x))) ||↑
    (drop-module 2 x)) ∘∃!d)) V A p)

```

### 7.10.2 Soundness

As all basic modules are electoral modules (, aggregators, termination conditions, ...), and all used compositional structures create electoral modules, sequential majority comparison is also an electoral module.

**theorem** *smc-sound*:

```

fixes x :: 'a Preference-Relation
shows SCF-result.electoral-module (smc x)
proof (unfold SCF-result.electoral-module.simps well-formed-SCF.simps, safe)
fix
  A :: 'a set and
  V :: 'v set and
  p :: ('a, 'v) Profile
assume profile V A p
thus
  disjoint3 (smc x V A p) and
  set-equals-partition A (smc x V A p)
unfolding iter.simps smc.simps elector.simps
using drop-mod-sound elect-mod-sound loop-comp-sound max-par-comp-sound
  pass-mod-sound plurality-rule-sound rev-comp-sound seq-comp-sound
by (metis (no-types) seq-comp-presv-disj, metis (no-types) seq-comp-presv-alts)
qed

```

### 7.10.3 Electing

The sequential majority comparison electoral module is electing. This property is needed to convert electoral modules to a social-choice function. Apart from the very last proof step, it is a part of the monotonicity proof below.

**theorem** *smc-electing*:

```

fixes x :: 'a Preference-Relation
assumes linear-order x
shows electing (smc x)
proof –
  let ?pass2 = pass-module 2 x
  let ?tie-breaker = (pass-module 1 x)
  let ?plurality-defer = (plurality-rule↓) ▷ ?tie-breaker
  let ?compare-two = ?pass2 ▷ ?plurality-defer
  let ?drop2 = drop-module 2 x
  let ?eliminator = ?compare-two ||↑ ?drop2
  let ?loop =
    let t = defer-equal-condition 1 in (?eliminator ∘t)

  have 00011: non-electing (plurality-rule↓)
    using plurality-rule-sound rev-comp-non-electing

```

```

  by metis
have 00012: non-electing ?tie-breaker
  using assms
  by simp
have 00013: defers 1 ?tie-breaker
  using assms pass-one-mod-def-one
  by simp
have 20000: non-blocking (plurality-rule↓)
  by simp
have 0020: disjoint-compatibility ?pass2 ?drop2
  using assms
  by simp
have 1000: non-electing ?pass2
  using assms
  by simp
have 1001: non-electing ?plurality-defer
  using 00011 00012 seq-comp-presv-non-electing
  by blast
have 2000: non-blocking ?pass2
  using assms
  by simp
have 2001: defers 1 ?plurality-defer
  using 20000 00011 00013 seq-comp-def-one
  by blast
have 002: disjoint-compatibility ?compare-two ?drop2
  using assms 0020 disj-compat-seq pass-mod-sound plurality-rule-sound
    rev-comp-sound seq-comp-sound voters-determine-pass-mod
    voters-determine-plurality-rule voters-determine-seq-comp
    voters-determine-rev-comp
  by metis
have 100: non-electing ?compare-two
  using 1000 1001 seq-comp-presv-non-electing
  by simp
have 101: non-electing ?drop2
  using assms
  by simp
have 102: agg-conservative max-aggregator
  by simp
have 200: defers 1 ?compare-two
  using 2000 1000 2001 seq-comp-def-one
  by simp
have 201: rejects 2 ?drop2
  using assms
  by simp
have 10: non-electing ?eliminator
  using 100 101 102 conserv-max-agg-presv-non-electing
  by blast
have 20: eliminates 1 ?eliminator
  using 200 100 201 002 par-comp-elim-one

```

```

  by simp
have 2: defers 1 ?loop
  using 10 20 iter-elim-def-n zero-less-one prod.exhaust-sel
    defer-equal-condition.simps
  by metis
have 3: electing elect-module
  by simp
show ?thesis
  using 2 3 assms seq-comp-electing smc-sound
  unfolding Defer-One-Loop-Composition.iter.simps
    smc.simps elector.simps electing-def
  by metis
qed

```

#### 7.10.4 (Weak) Monotonicity

The following proof is a fully-modular proof for weak monotonicity of sequential majority comparison. It is composed of many small steps.

**theorem** *smc-monotone*:

**fixes**  $x :: 'a$  *Preference-Relation*

**assumes** *linear-order*  $x$

**shows** *monotonicity* (*smc*  $x$ )

**proof** –

**let**  $?pass2 = \text{pass-module } 2 \ x$

**let**  $?tie-breaker = \text{pass-module } 1 \ x$

**let**  $?plurality-defer = (\text{plurality-rule}\downarrow) \triangleright ?tie-breaker$

**let**  $?compare-two = ?pass2 \triangleright ?plurality-defer$

**let**  $?drop2 = \text{drop-module } 2 \ x$

**let**  $?eliminator = ?compare-two \parallel_{\uparrow} ?drop2$

**let**  $?loop =$

*let*  $t = \text{defer-equal-condition } 1 \text{ in } (?eliminator \circ_t)$

**have** 00010: *defer-invariant-monotonicity* (*plurality-rule* $\downarrow$ )

**by** *simp*

**have** 00011: *non-electing* (*plurality-rule* $\downarrow$ )

**using** *rev-comp-non-electing plurality-rule-sound*

**by** *blast*

**have** 00012: *non-electing*  $?tie-breaker$

**using** *assms*

**by** *simp*

**have** 00013: *defers* 1  $?tie-breaker$

**using** *assms pass-one-mod-def-one*

**by** *simp*

**have** 00014: *defer-monotonicity*  $?tie-breaker$

**using** *assms*

**by** *simp*

**have** 20000: *non-blocking* (*plurality-rule* $\downarrow$ )

**by** *simp*

**have** 0000: *defer-lift-invariance*  $?pass2$

```

    using assms
  by simp
have 0001: defer-lift-invariance ?plurality-defer
  using 00010 00012 00013 00014 def-inv-mono-imp-def-lift-inv
  unfolding pass-module.simps voters-determine-election.simps
  by blast
have 0020: disjoint-compatibility ?pass2 ?drop2
  using assms
  by simp
have 1000: non-electing ?pass2
  using assms
  by simp
have 1001: non-electing ?plurality-defer
  using 00011 00012 seq-comp-presv-non-electing
  by blast
have 2000: non-blocking ?pass2
  using assms
  by simp
have 2001: defers 1 ?plurality-defer
  using 20000 00011 00013 seq-comp-def-one
  by blast
have 000: defer-lift-invariance ?compare-two
  using 0000 0001 seq-comp-presv-def-lift-inv
    voters-determine-plurality-rule voters-determine-pass-mod
    voters-determine-rev-comp voters-determine-seq-comp
  by blast
have 001: defer-lift-invariance ?drop2
  using assms
  by simp
have 002: disjoint-compatibility ?compare-two ?drop2
  using assms 0020 disj-compat-seq pass-mod-sound plurality-rule-sound
    voters-determine-pass-mod rev-comp-sound seq-comp-sound voters-determine-seq-comp
    voters-determine-plurality-rule voters-determine-pass-mod voters-determine-rev-comp
  by metis
have 100: non-electing ?compare-two
  using 1000 1001 seq-comp-presv-non-electing
  by simp
have 101: non-electing ?drop2
  using assms
  by simp
have 102: agg-conservative max-aggregator
  by simp
have 200: defers 1 ?compare-two
  using 2000 1000 2001 seq-comp-def-one
  by simp
have 201: rejects 2 ?drop2
  using assms
  by simp
have 00: defer-lift-invariance ?eliminator

```

```

    using 000 001 002 par-comp-def-lift-inv
    by blast
  have 10: non-electing ?eliminator
    using 100 101 conserv-max-agg-presv-non-electing
    by blast
  have 20: eliminates 1 ?eliminator
    using 200 100 201 002 par-comp-elim-one
    by simp
  have 0: defer-lift-invariance ?loop
    using 00 loop-comp-presv-def-lift-inv
      voters-determine-plurality-rule voters-determine-pass-mod voters-determine-drop-mod
      voters-determine-rev-comp voters-determine-seq-comp voters-determine-max-par-comp
    by metis
  have 1: non-electing ?loop
    using 10 loop-comp-presv-non-electing
    by simp
  have 2: defers 1 ?loop
    using 10 20 iter-elim-def-n prod.exhaust-sel zero-less-one defer-equal-condition.simps
    by metis
  have 3: electing elect-module
    by simp
  show ?thesis
    using 0 1 2 3 assms seq-comp-mono
    unfolding Electoral-Module.monotonicity-def elector.simps
      Defer-One-Loop-Composition.iter.simps
      smc-sound smc.simps
    by (metis (full-types))
qed

end

```

## 7.11 Kemeny Rule

```

theory Kemeny-Rule
  imports
    Compositional-Structures/Basic-Modules/Component-Types/Votewise-Distance-Rationalization
    Compositional-Structures/Basic-Modules/Component-Types/Distance-Rationalization-Symmetry
begin

```

This is the Kemeny rule. It creates a complete ordering of alternatives and evaluates each ordering of the alternatives in terms of the sum of preference reversals on each ballot that would have to be performed in order to produce that transitive ordering. The complete ordering which requires the fewest preference reversals is the final result of the method.



### 7.11.1 Definition

**fun** *kemeny-rule* :: ('a, 'v :: wellorder, 'a Result) Electoral-Module **where**  
    *kemeny-rule* V A p = *swap- $\mathcal{R}$  strong-unanimity* V A p

### 7.11.2 Soundness

**theorem** *kemeny-rule-sound*: *SCF-result.electoral-module kemeny-rule*  
    **unfolding** *kemeny-rule.simps swap- $\mathcal{R}$ .simps*  
    **using** *SCF-result. $\mathcal{R}$ -sound*  
    **by** *metis*

### 7.11.3 Anonymity

**theorem** *kemeny-rule-anonymous*: *SCF-result.anonymity kemeny-rule*  
**proof** (*unfold kemeny-rule.simps swap- $\mathcal{R}$ .simps*)  
    **let** *?swap-dist* = *votewise-distance swap l-one*  
    **have** *distance-anonymity ?swap-dist*  
        **using** *l-one-is-sym symmetric-norm-imp-distance-anonymous[of l-one]*  
        **by** *simp*  
    **thus** *SCF-result.anonymity*  
        (*SCF-result.distance- $\mathcal{R}$  ?swap-dist strong-unanimity*)  
    **using** *strong-unanimity-anonymous*  
        *SCF-result.anonymous-distance-and-consensus-imp-rule-anonymity*  
    **by** *metis*  
**qed**

### 7.11.4 Neutrality

**lemma** *swap-dist-neutral*: *distance-neutrality well-formed-elections*  
    (*votewise-distance swap l-one*)  
    **using** *neutral-dist-imp-neutral-votewise-dist swap-neutral*  
    **by** *blast*

**theorem** *kemeny-rule-neutral*: *SCF-properties.neutrality kemeny-rule*  
    **using** *strong-unanimity-neutral' swap-dist-neutral strong-unanimity-closed-under-neutrality*  
        *SCF-properties.neutr-dist-and-cons-imp-neutr-dr*  
    **unfolding** *kemeny-rule.simps swap- $\mathcal{R}$ .simps*  
    **by** *blast*

**end**

# Bibliography

- [1] Karsten Diekhoff, Michael Kirsten, and Jonas Krämer. Formal property-oriented design of voting rules using composable modules. In Saša Pekeč and Kristen Brent Venable, editors, *6th International Conference on Algorithmic Decision Theory (ADT 2019)*, volume 11834 of *Lecture Notes in Artificial Intelligence*, pages 164–166. Springer, 2019. [doi:10.1007/978-3-030-31489-7](https://doi.org/10.1007/978-3-030-31489-7).
- [2] Karsten Diekhoff, Michael Kirsten, and Jonas Krämer. Verified construction of fair voting rules. In Maurizio Gabbrielli, editor, *29th International Symposium on Logic-Based Program Synthesis and Transformation (LOPSTR 2019), Revised Selected Papers*, volume 12042 of *Lecture Notes in Computer Science*, pages 90–104. Springer, 2020. [doi:10.1007/978-3-030-45260-5\\_6](https://doi.org/10.1007/978-3-030-45260-5_6).
- [3] Benjamin Hadjibeyli and Mark C. Wilson. Distance rationalization of social rules. *Computing Research Repository (CoRR)*, abs/1610.01902, 2016. [arXiv:1610.01902](https://arxiv.org/abs/1610.01902).