PROGRAM- TO IMPLEMENT THE VARIOUS FUNCTIONS LIKE – length(), insert(), replace(), erase(), size(), begin(), end(), FOR MANIPULATING STRINGS

//BHAVNA VERMA-171210019-26/03/2019

```
//MANIPULATING STRINGS
```

```
#include<iostream>
using namespace std;
int main()
     string s1("12345"), s2("abcde"), s3("pqrst"), s4("abc");
     int x;
     //INSERT 3=NO. OF CHARACTERS TO ESCAPE THEN PRINT s2 THEN REST OF S1
     cout<<"\nINSERT ----":
     cout << "\n s1=" << s1;
     cout << "\n s2=" << s2;
     s1.insert(3, s2);
     cout << "\n" << s1;
     //ERASE 4=NO. OF CHARACTERS TO ESCAPE THEN ERASE 5 CHARACTERS AND PRINT
REST
     cout<<"\n\nERASE -----";
     cout << "\n s1=" << s1;
     s1.erase(4,5);
     cout << "\n" << s1;
     //REPLACE 1=NO. OF CHARACTERS TO ESCAPE, 3=NO. OF CHARACTERS TO REPLACE
BY s1
     cout<<"\n\nREPLACE -----";
     cout << "\n s3=" << s3;
     cout<<"\n s2="<<s2;
     s2.replace(1,3,s3);
     cout<<"\n"<<s2;
     //COMPARE TWO STRINGS
     cout<<"\n\nCOMPARE -----";
     cout << "\n s3=" << s3;
     cout << "\n s4=" << s4;
     if(s4.compare(s3)<0)
```

```
cout << "\n" << s4;
cout<<"\n-----";
//APPEND STRING s2
cout<<"\n\nAPPEND -----";
cout<<"\n s2="<<s2;
cout << "\n s3=" << s3;
s2.append(s3);
cout<<"\n"<<s2;
//LENGTH STRING s2
cout<<"\n\nLENGTH -----";
cout<<"\n s2="<<s2;
x = s2.length();
cout << "\n" << x;
//SIZE STRING s2
cout<<"\n\nSIZE -----";
cout<<"\n s2="<<s2;
x = s2.size();
cout << "\n" << x;
//FIND in STRING s2
cout<<"\n\nFIND -----";
cout<<"\n s2="<<s2;
x = s2.find(s3);
cout << "\n" << x;
x = s2.find(s1);
cout << "\n" << x;
//SWAP in STRING s2
cout<<"\n\nSWAP -----";
cout<<"\n s2="<<s2;
s2.swap(s3);
cout<<"\n"<<s2;
//BEGIN & END in STRING s2
cout<<"\n\nBEGIN & END -----";
cout << "\n" << s1;
string s5(s1.begin()+2, s1.end());
```

```
cout<<"\n"<<s5;
return 0;
}</pre>
```

OUTPUT -

C:\Users\VERMA\Downloads\p4.exe

```
INSERT -----
s1=12345
s2=abcde
123abcde45
ERASE -----
s1=123abcde45
123a5
REPLACE ------
s3=pqrst
s2=abcde
apqrste
COMPARE -----
s3=pqrst
s4=abc
abc
APPEND -----APPEND -----
s2=apqrste
s3=pqrst
apqrstepqrst
LENGTH -----
s2=apqrstepqrst
12
SIZE ----
s2=apqrstepqrst
12
s2=apqrstepqrst
-1
SWAP -----
s2=apqrstepqrst
pgrst
BEGIN & END ------
```