

assignment_01_RamirezKyle

Kyle Ramirez

6/9/2021

Create a numeric vector with the values of 3, 2, 1 using the `c()` function

Assign the value to a variable named `num_vector`

Print the vector

```
num_vector <- c(3,2,1) print(num_vector) ## Create a character vector with the values of "three", "two",  
"one" "using the c() function ## Assign the value to a variable named char_vector ## Print the vector  
char_vector <- c("three","two","one") print(char_vector)
```

Create a vector called `week1_sleep` representing how many hours slept each night of the week

Use the values 6.1, 8.8, 7.7, 6.4, 6.2, 6.9, 6.6

```
week1_sleep <- c(6.1, 8.8, 7.7, 6.4, 6.2, 6.9, 6.6)
```

Display the amount of sleep on Tuesday of week 1 by selecting the variable index

```
week1_sleep[3]
```

Create a vector called `week1_sleep_weekdays`

Assign the weekday values using indice slicing

```
week1_sleep_weekdays <- week1_sleep[1:7]
```

Add the total hours slept in week one using the `sum` function

Assign the value to variable `total_sleep_week1`

```
total_sleep_week1 <- sum(week1_sleep)
```

Create a vector called `week2_sleep` representing how many hours slept each night of the week

Use the values 7.1, 7.4, 7.9, 6.5, 8.1, 8.2, 8.9

```
week2_sleep <- c(7.1, 7.4, 7.9, 6.5, 8.1, 8.2, 8.9)
```

Add the total hours slept in week two using the `sum` function

Assign the value to variable `total_sleep_week2`

```
total_sleep_week2 <- sum(week2_sleep)
```

Determine if the total sleep in week 1 is less than week 2 by using the `<` operator

```
total_sleep_week1 < total_sleep_week2
```

Calculate the mean hours slept in week 1 using the `mean()` function

```
mean(week1_sleep)
```

Create a vector called `days` containing the days of the week.

Start with Sunday and end with Saturday

```
days <- c("Sunday", "Monday", "Tuesday", "Wednesday", "Thursday", "Friday", "Saturday")
```

Assign the names of each day to `week1_sleep` and `week2_sleep` using the `names` function and `days` vector

```
names(week1_sleep) <- days names(week2_sleep) <- days
```

Display the amount of sleep on Tuesday of week 1 by selecting the variable name

```
week1_sleep[3]
```

Create vector called `weekdays` from the `days` vector

```
weekdays <- days[1:7]
```

Create vector called `weekends` containing Sunday and Saturday

```
weekends <- days[c(1,7)]
```

Calculate the mean about sleep on weekdays for each week

Assign the values to weekdays1__mean and weekdays2__mean

```
weekdays1__mean <- mean(week1_sleep[weekdays]) weekdays2__mean <- mean(week2_sleep[weekdays])
```

Using the weekdays1__mean and weekdays2__mean variables,

see if weekdays1__mean is greater than weekdays2__mean using the > operator

```
weekdays1__mean > weekdays2__mean
```

Determine how many days in week 1 had over 8 hours of sleep using the > operator

```
week1_sleep > 8
```

Create a matrix from the following three vectors

```
student01 <- c(100.0, 87.1) student02 <- c(77.2, 88.9) student03 <- c(66.3, 87.9)
students_combined <- c(student01, student02, student03) grades <- matrix(students_combined, byrow = 2, nrow = 3)
```

Add a new student row with rbind()

```
student04 <- c(95.2, 94.1) grades <- rbind(grades, student04)
```

Add a new assignment column with cbind()

```
assignment04 <- c(92.1, 84.3, 75.1, 97.8) grades <- cbind(grades, assignment04)
```

Add the following names to columns and rows using rownames() and colnames()

```
assignments <- c("Assignment 1", "Assignment 2", "Assignment 3") students <- c("Florinda Baird", "Jinny Foss", "Lou Purvis", "Nola Maloney")
rownames(grades) <- students colnames(grades) <- assignments
```

Total points for each assignment using colSums()

```
colSums(grades)
```

Total points for each student using rowSums()

```
rowSums(grades)
```

Matrix with 10% and add it to grades

```
weighted_grades <- grades * 0.1 + grades
```

Create a factor of book genres using the genres_vector

Assign the factor vector to factor_genre_vector

```
genres_vector <- c("Fantasy", "Sci-Fi", "Sci-Fi", "Mystery", "Sci-Fi", "Fantasy") factor_genre_vector <-  
genres_vector
```

Use the summary() function to print a summary of factor_genre_vector

```
summary(factor_genre_vector)
```

Create ordered factor of book recommendations using the recommendations_vector

no is the lowest and yes is the highest

```
recommendations_vector <- c("neutral", "no", "no", "neutral", "yes") factor_recommendations_vector <-  
factor(recommendations_vector, levels = c("no", "neutral", "yes"), ordered = TRUE)
```

Use the summary() function to print a summary of factor_recommendations_vector

```
summary(factor_recommendations_vector)
```

Using the built-in mtcars dataset, view the first few rows using the head() function

```
head(mtcars, 1)
```

Using the built-in mtcars dataset, view the last few rows using the tail() function

```
tail(mtcars, 1)
```

Create a dataframe called characters_df using the following information from LOTR

```
name <- c("Aragon", "Bilbo", "Frodo", "Galadriel", "Sam", "Gandalf", "Legolas", "Sauron", "Gollum")  
race <- c("Men", "Hobbit", "Hobbit", "Elf", "Hobbit", "Maia", "Elf", "Maia", "Hobbit") in_fellowship  
<- c(TRUE, FALSE, TRUE, FALSE, TRUE, TRUE, TRUE, FALSE, FALSE) ring_bearer <- c(FALSE,  
TRUE, TRUE, FALSE, TRUE, TRUE, FALSE, TRUE, TRUE) age <- c(88, 129, 51, 7000, 36, 2019, 2931,  
7052, 589)
```

```
characters_df <- data.frame(name, race, in_fellowship, ring_bearer, age)
```

Sorting the `characters_df` by age using the `order` function and assign the result to the `sorted_characters_df`

```
sorted_characters_df <- characters_df[order(age),]
```

Use `head()` to output the first few rows of `sorted_characters_df`

```
head(sorted_characters_df)
```

Select all of the ring bearers from the dataframe and assign it to `ringbearers_df`

```
ringbearers_df <- characters_df[characters_df$ring_bearer == TRUE,]
```

Use `head()` to output the first few rows of `ringbearers_df`

```
head(ringbearers_df)
```