

BADAN OTORITAS PELABUHAN / PORT ENGINEERING & HYDROGRAPHY

Wharf Bathymetric & Physical Capacity Specifications (Spesifikasi Dermaga)

BERTH CAPACITY & NAVIGATIONAL LIMITS SHEET

Sheet Ref: BIS-MIPS-01/2026 | Datum: Lowest Astronomical Tide (LAT/LWS)

REGULATORY HARBOR MASTER DIRECTIVE:

The Harbour Master strictly enforces Under Keel Clearance (UKC) regulations. For vessels drawing **10.20m**, the mandatory depth requirement is **11.50m (10.20m + 1.30m UKC)**. Berths failing either LOA or controlling depth criteria must be excluded from allocation.

Wharf Parameter	Berth B-01 (Deepwater Terminal)	Berth B-02 (Feeder Quay)
Designation & Terminal	International Container Pier	Regional Feeder Basin
Maximum Length (LOA)	300.00 Meters	250.00 Meters
Controlling Depth (LWS)	12.00 Meters	9.00 Meters
Quay Cranes Installed	2x Super Post-Panamax (QC-01, QC-02) Outreach: 52m (18 rows)	2x Panamax Cranes Outreach: 36m (12 rows)
Bollard Spacing & Rating	24 Bollards @ 100 MT Capacity	18 Bollards @ 60 MT Capacity
Compatibility: MV Nusantara (LOA: 280m, Draft: 10.2m)	✓ COMPLIANT LOA Margin: +20m Depth Margin: +0.5m above UKC	✗ INCOMPATIBLE LOA Deficit: -30m overreach Depth Deficit: -2.5m (Grounding Hazard)
Current Operational Status	AVAILABLE — CLEARED FOR BERTHING	AVAILABLE — RESTRICTED TO FEEDER

Chief Hydrographic Engineer

Ir. Dani Firmansyah
Marine Geodesy & Bathymetry Division

Berthing Master Officer



Capt. H. Gunawan
Senior Port Operations Officer