

Technical Report

COMP1100 Assignment 3

Jacob Bos
ANU u7469354

May 25, 2022

Lab: Tuesday 11am

Tutor: Abhaas Goyal

Word-count beyond cover page at ≤ 1500 words

Contents

1	Introduction	1
2	Documentation	1
2.1	Design Documentation and Technical Decisions	1
2.2	Program Design / Structure	3
2.3	Assumptions	3
3	Testing	3
4	Reflection	4
4.1	Design Choices	4
4.2	Reflection	4

1 Introduction

The program detailed herein is an implementation of a few AI's for solving the game Fanorona with complimentary unit tests.

2 Documentation

2.1 Design Documentation and Technical Decisions

First capture move is little more complex than the provided `firstLegalMove`, it is "content" with taking the head of the list of possible capturing moves as provided by the function `captures` else returning the first legal move. This was used to test the greedy AI, because a greedy should on average perform better than the first capture move which should beform slightly better than first legal move.

The Greedy AI has a simple functionality. The main function `greedy` cases on which player's turn it is given the provided `gameState` and chooses whether to maximize (for Player1) or minimize (for Player2) the heuristic value and calls `greedyHelp` with the appropriate evaluator to output a pair containing the ideal move and its heuristic value. `greedyHelp` recurses through a list of moves and their values and using an accumulator either minimizes or maximizes it. This list is a mapping of the list provided by `legalMoves` to a list of pairs of moves of each move with the value of the move created by the function `diffPieces` applied to the `applyMove` of the move and initial state.

The first Minimax uses two recursive tree structures, the first `GameTree`, stores all the possible game-state evolutions and is generated through an infinite recursion in `gameTree` which takes a state, puts it into a node and then maps `gameTree` to all its children states which are generated through a mapping of `applyMove` to a list of `legalMoves` which is then recursively purged of its `[Maybe GameState]` type by `purge` to become `[GameState]`.

The second tree structure, `evalTree` is the same as `GTree` except that it contains a value on each node corresponding to the best possible outcome (heuristic value) for the player who's state is at that node and is pruned to a given *move depth*. The `evalTree` is generated by recursively by `pruneMinMax` which cases firstly on integer depth given to the function, if the depth is zero then it evaluated the heuristic value at that node and then terminates that branch. If not, it then cases on the state held in the node, if the state contains a `GameOver` turn then it does as if the depth was zero, terminating the tree. If the state at a node contains `Turn Player1` then it assigns the maximum of the values in its child `EvalTree` nodes

else if the turn is the **Player2**, the minimizing player, it assigns the minimum value of its child nodes to the given node. This results in the best possible outcome for the player in the initial state ending up in the head node.

The heuristic value used is the difference in number of pieces between **Player1** and **Player2** and is calculated by **heuristicVal** which takes the pair output of the provided **countPieces** function and then takes the difference in the number of pieces.

To then retrieve the best move we note that the best move is at the same depth in the **legalMoves** list as best value stored in the head node is in the list of child **evalTree** nodes. This is because the list of children nodes is produced by a mapping on the **legalMoves** list. Consequently to find the best move we extract the value from the head of the output of **pruneMinMax** using **getVal** and then find it's depth recursively in the list provided by mapping **getVal** to the child nodes at depth 1 using **findDepth**. Consequently the function **getMove** uses the **(!!)** operator to extract the best move at its expected depth in the **legalMoves** list.

The second Minimax Is identical to the first except that the heuristic function assigns win or loss gamestates with heuristic values far more extreme their typical values. This was an experiment to see wether this would allow the AI to prioritize winning moves during the endgame.

The Alpha-Beta Minimax attempt tried to use the same initial structure **GameTree** and either **evalTree** or another tree structure

2.2 Program Design / Structure

2.3 Assumptions

3 Testing

Unit tests aimed to cover as many possible cases on as many functions as possible. Unfortunately, many of the functions deal with complex datatypes which makes it difficult to write typical arguments. Consequently many tests used `initialState` and checked the length of the argument and desired output lists.

The Greedy AI has two associated test groups. `pairPieces` was tested by checking that the list of pairs of legal moves and their associated heuristic value is the same length as the list of `legalMoves`. The passing of this test is able to support the assumption that the function is correct. Secondly, `diffPieces` is tested against two cases which were possible to write. It tested that the function returned `Nothing` for the same argument and returned `Just 0` for an input of just the initial state.

The MiniMax AI has four associated test groups. Firstly `purge` has four test cases. They were made easier to write because `purge` is polymorphic and so a simpler input type of `Int` was used. `purge` is then tested against a case of the empty list, all `Nothings`, all `Just x`'s and a mix of `Nothings` and `Justs`. Passing these tests implied that the function was correct. Similarly, since `findDepth` is polymorphic it was easier to write test cases. It was not tested against the empty list since that was supposed to return an error but it was tested against cases where the element occurred once or twice in the list where it was supposed to take the first. The passing of this indicated correctness. Thirdly, `getVal` was tested against one test case, indicating it's ability to correctly retrieve the value from a node. Lastly `heuristicVal` was tested with the initial state as an argument to ensure that the output is zero as would be expected. Unfortunately it was difficult to test it against any other inputs as other arguments are difficult to write.

Performance tests were done by playing my AI's against themselves and also against the course AI's in the tournament.

The Greedy AI was firstly tested against both the first legal move AI and the first capture move AI. The correctness of the Greedy AI was confirmed by it beating both as it should statistically behave better than both. Whilst a faulty Greedy may be able to beat FLM by chance it is less likely to beat an FCM by chance especially if it was accidentally minimizing when it was supposed to maximize or

vices-versa. Since the Greedy AI was also able to consistently beat me as a human I considered that it had a high likelihood of being correct.

The MiniMax AI's were tested against both my greedy AI and the Course AIs, my MiniMax consistently outperformed my greedy and all of the course greedy AIs except for third where playing first results in a draw. My AI majority draws against the course Minimaxes and Alpha-beta pruners further indicating correctness. It would be expected with such a simple heuristic that another minimax or minimax-alpha/beta AI with a better heuristic would slightly outperform.

4 Reflection

4.1 Design Choices

4.2 Reflection