System Evaluation 1–4: Methods, Executed Results and Evidence Limits

David Vesterlund
WestQuant, Vesterlund Ventures, Sweden

10 October 2026

This dossier records the four system-evaluation pathways. Steps 1, 3 and 4 are executed at their declared software scope. Step 2 has an executed synthetic molecular-spin control, with experimental physical validation still pending. The content is also integrated into the main manuscript and Supplement. No improved material lifetime, hardware result or prediction confidence interval is claimed.

Quantity	Result
Profiles / channel-age points	13 / 73
Processed fidelity values	90
Maximum full Choi discrepancy	1.310×10^{-14}
Maximum six-state output discrepancy	1.183×10^{-14}
Maximum conditional average-fidelity discrepancy	3.997×10^{-15}
Maximum acceptance / processed-value discrepancy	0 / 0
Declared numerical gate	1.000×10^{-8}

Table 1: Step 1: matched numerical and processed-data comparison. Twelve profiles are supplied software controls; one profile is an experiment-constrained point.

1 Additional system evaluation: complete executed protocol

Steps 1, 3 and 4 have executed results at their stated software scope. Step 2 has an executed synthetic second-family case, whereas its experimental physical objective remains blocked. The four selected records share evaluation-source fingerprint

`d8fc6d2ecb580e0ba1c8881ffbd542d087c493b7621cb89509948e595211ec92`.

Their common lab-source fingerprint is

`9c4490acf2e5a42e8e10007989eeb94b5e406b17f5d187ca310847581ee2edb7`.

These fingerprints identify source content, not hardware or an external scientific endorsement. Steps 2 and 3 were confirmed with the published implementation after their initial runs; the initial outputs remain archived. Table generation asserts the shared fingerprint and expected numerical/status gates without overwriting the original run records. The configuration digest and UTC timestamp of each selected record are in `evidence/system_evaluation_claim_map.json`. Generated table files are under `evaluation/paper/`.

1.1 Step 1: independent reference equations and matched inputs

The reference `evaluation/wqeval/reference.py` imports NumPy/SciPy without importing `memorylab`. For column vectorization and Hamiltonian $G = \mathrm{diag}(0, \delta)$ in Hz, it uses

$$\mathcal{L} = -2\pi i(I \otimes G - G^{\mathsf{T}} \otimes I) + \sum_J \left[J^* \otimes J - \tfrac{1}{2} I \otimes J^\dagger J - \tfrac{1}{2} (J^\dagger J)^{\mathsf{T}} \otimes I \right].$$

The jump operators are $\sqrt{\Gamma_1(1-p_e)}\,|0\rangle\langle 1|$, $\sqrt{\Gamma_1 p_e}\,|1\rangle\langle 0|$, and $\sqrt{\Gamma_\phi/2}\,Z$. The stage superoperator is $\exp(t\mathcal{L})$. Write and read stages include their specified depolarizing maps, and storage adds the declared network-activity

dephasing. The reference constructs $C = \sum_{a,b} |a\rangle\langle b| \otimes \mathcal{E}(|a\rangle\langle b|)$ by matrix-unit propagation, including an orthogonal erasure outcome for the full channel. It computes six Pauli-eigenstate outputs and their mean target fidelity independently of the lab's Kraus construction.

The four joint parameter choices (Γ_1, δ, p_e) are $(0, 0, 0)$, $(0.05, 123, 0.1)$, $(10, -500, 0.5)$ and $(100, 1000, 0.9)$, with rates in s^{-1} and detunings in Hz. Each is combined with storage temperatures 4.2, 10 and 80 K and ages $[0, 10^{-6}, 10^{-4}, 10^{-3}, 10^{-2}, 10^{-1}]$ s. Write/read stages remain at 4.2 K, last $10^{-4}/2 \times 10^{-4}$ s and use acceptance 0.8/0.7 and depolarization 0.01/0.02. The pure-dephasing rate is $0.01 + 0.001T + 0.001(T/10)^3$ s^{-1}, erasure rate 0.01 s^{-1}, and storage activity contributes $10 \times 0.002 = 0.02$ s^{-1}. Rate validity is declared over 1–300 K. These are chosen software profiles, not fitted material parameters. The measured Teller point supplies the thirteenth profile and its sole supported age of 18 μs at 3 K, giving $12 \times 6 + 1 = 73$ channel-age points.

The two experimental input files are `4.csv` and `8a.csv` from record 14929997:v1. Their SHA-256 hashes, original download URLs and data-license metadata are pinned in `evaluation/data/teller_sources.json`. Both parsers use the same checked bytes. The path file yields 30 values and mean 0.9510824228990328; the time-bin file yields 60 values and mean 0.9140479475068066. The discrepancy is zero for every processed value. The comparison threshold is 10^{-8} for the full Choi matrix, six states, average fidelity, acceptance and processed values. This threshold is numerical, not an experimental accuracy margin.

Both timing arms are warmed up before five repeats, with their order randomized by seed 20261010. All 73 channel constructions are included in each repeat. `construction_timing.csv` retains every measured duration and actual order. The arms do not perform equal amounts of metadata, export, validation or metric-construction work. File IO, source retrieval, network events, fits and electronic structure are excluded. Native thread environment variables are recorded but were not constrained for step 1. The medians cannot be interpreted as a fair end-to-end speedup or engineering-effort reduction. `related_tools_audit.json` distinguishes executed comparison from documentary context; AiiDA, PySCF, PyCCE, QuTiP and SeQUeNCe were not separately timed here. Existing AiiDA provenance and caching are not presented as new contributions.

1.2 Step 2: synthetic control, curve gate and physical stop

The model/curve comparison requires the observable `complex_pure_dephasing_coherence`, explicit exclusion of population relaxation, source hashes, curve reviewer, normalization and observable mapping. A measured case additionally requires reviewed model-parameter provenance, a nonhypothetical model and exact equality of full declared experimental conditions between curve and model. The fixed-model runner accepts `exact_spin_bath` or optional `pycce`; it fits zero parameters. The initial curve value must be unity, magnitudes must lie in the unit disk and a strictly increasing finite grid must start at zero. No silent clipping of noisy or unnormalized measurements is provided.

The executed control has one ^{13}C nuclear spin $I = 1/2$, central logical projections $\pm 1/2$, laboratory $A_{zz} = 4000$ Hz and $\nu_z = 214163.9829$ Hz, zero other couplings, 4.2 K and zero pulses. Forty-one equally spaced ages span 0–1 ms. An independent closed-form Gibbs-initialized FID produces the curve; the finite Hamiltonian solver supplies the comparison. Every complex residual is divided by the chosen scale 0.01, and the maximum must be at most three. The observed maximum is $3.7192473 \times 10^{-12}$. This chosen scale is not an experimental SEM, and the gate has no calibrated statistical false-positive rate. The 75–100 μs crossing bracket differs from the earlier 101-point control's 90–100 μs bracket solely because the grids differ; both are sampled numerical brackets and both detect revivals.

All write/store/read temperatures are hypothetically 4.2 K. The supplied interface has acceptance 0.8/0.7, depolarization 0.01/0.02 and durations 100/200 μs, with the independent rate models retained from the example. Export requires `-allow-hypothetical`. At 500 μs, the provider-neutral two-node workload has 10,000 trials, herald probability 0.1, 1 ms interval, Bell-fidelity threshold 0.8 and seed 20261010. It yields 1020 heralds and 313 retrieved/quality-qualified pairs. Conditional Bell fidelity is 0.9559176317211326; the retrieved-fraction Wilson interval is [0.0280630600,0.0348969001]. The simulated qualified rate is 31.3 s^{-1} under these supplied assumptions, not measured network performance. This workload is not the earlier 2000-trial SeQUeNCe control.

The separate pending descriptor targets a molecular reference at DOI 10.1039/C8SC04122A. Running it returns `blocked_missing_reviewed_data` and exit code two, with no physical validation and no network export. Required inputs are a reviewed normalized curve with measurement uncertainties, fixed Hamiltonian and tensor frames, field/temperature/isotopes/pulses, separation of relaxation from pure dephasing, and independent optical-interface review. Reported molecular phase-memory time alone does not satisfy these

requirements. Thus no second-family experimental reproduction or new-material lifetime is supplied by step 2.

1.3 Step 3: individual fault interventions

The suite creates local copies of inputs and explicitly unsafe bypasses without modifying production guards. Each invalid case has a valid positive control that must succeed. Rejection alone would be insufficient if every valid input also failed. All seven positive controls and all seven guarded rejections pass; the deliberate bypasses accept all seven cases.

Constructed fault	Guarded result	Accepted unsafe-bypass consequence
Operating-point age extrapolation	Blocked	10× unsupported age
Operating-point temperature extrapolation	Blocked	1 K unsupported shift
Total coherence rate reused as pure dephasing	Blocked	16.667% conditional T_2 error
Unreviewed noise independence	Blocked	One unsupported declaration
Hypothetical channel without opt-in	Blocked	Two hypothetical age samples
Absolute-age map applied incrementally	Blocked	0.097247 maximum element error
Modified source bytes	Blocked	1000× forged source value

Table 2: Step 3: all seven valid positive controls pass; all invalid cases are rejected. Consequences have distinct units and are not aggregated into an accuracy score.

The age bypass changes the declared sole point age before evaluating a tenfold longer age, thereby illustrating an unsupported extrapolation rather than measuring its physical error. The temperature bypass changes the declared point temperature by 1 K, again with no experimentally known extrapolation error. Noise independence is counted as an unsupported declaration; evidence promotion counts two age samples. The rate-definition example has $\Gamma_1 = 10\ \mathrm{s}^{-1}$ and correct independent $\Gamma_\phi = 20\ \mathrm{s}^{-1}$, giving 40 ms. Treating total coherence rate 25 s^{-1} as pure dephasing gives 33.333 ms instead. The modified-source case changes a chosen value from 0.001 to 1 s; it exercises the new evaluation source contract, whereas the other six cases exercise existing lab guards.

In the incremental-application control, the 1 ms complete channel includes write/read depolarization as well as storage; applying it twice produces maximum density-element discrepancy 0.0972467329 relative to applying it once. A separate units control converts 1 ms correctly to 0.001 s and contrasts it with an omitted conversion to 1 s; its maximum element discrepancy is 0.1322008762. These consequences have different units and scientific meanings. Neither their average nor seven out of seven represents a general material-prediction accuracy or real-world researcher error rate. Equivalent guards may be implemented in other frameworks.

1.4 Step 4: workload, timing scope and robustness

The native runner workload has Markov and one-spin exact-bath models, detunings $[0, 123, 500]$ Hz, two replicates and six ages $[0, 10^{-4}, 5\times10^{-4}, 10^{-3}, 2\times10^{-3}, 5\times10^{-3}]$ s. Replicates have distinct deterministic seed streams; they are not independent hardware measurements or stochastic bath realizations in this deterministic workload. The Cartesian count is $2\times3\times2 = 12$ jobs per study. Master seed is 20261010. Three repeats independently randomize worker order among 1, 2 and 4. Worker count is excluded from physics identity, allowing a direct consistency check across scheduling choices.

Each cold study runs in a separate output directory and an isolated measurement process. OMP, MKL, OpenBLAS and NumExpr thread limits are one in those benchmark subprocesses. Per-job timeout is 60 s, driver timeout 600 s and max-run budget 24. The measured interval includes process startup, actual channel construction and artifact IO. The warm interval reuses terminal-result checkpoints; it is not electronic-structure memoization. Nine cold studies complete 108 jobs, and nine warm passes reuse 108 results. The scientific digest, excluding durations and output paths but including configuration identities and channel data, is identical across all nine studies.

The reported bounds are observed ranges from three repeats, not confidence intervals. Separate resource measurements use process usage counters: parent maximum RSS is 34.578125–37.078125 MiB and the largest terminated child's maximum is 63.238281–66.414063 MiB. The metric is not peak total memory across concurrent workers. Child CPU seconds and each measurement's raw counters remain in the retained

Workers	Cold median [min,max] (s)	Resume median (s)	Median jobs/s
1	3.8674 [3.8089, 3.9101]	0.01814	3.103
2	1.9781 [1.9165, 2.0665]	0.01741	6.066
4	1.1782 [1.1299, 1.2286]	0.01817	10.185

Table 3: Step 4: three local cold studies and three checkpoint-reuse passes per worker count, with 12 jobs per study. Bounds are observed minima/maxima, not confidence intervals.

summary. Performance applies to this Linux environment and small supplied models, not general CCE, electronic structure, all elements or cluster-scale workloads.

Three additional robustness probes are distinct from the 108 cold jobs. A profile without write temperature produces `missing_data`. A real worker process with a 10^{-6} s timeout produces `timeout`; this deadline intentionally tests termination and is not a solve-time estimate. A precompleted valid job followed by the full study completes all 12 jobs with exactly one checkpoint reused. Thus robustness adds one missing-data worker, one timeout worker and 12 successful calculations across the partial/restarted study. No forced-kill during an atomic write, power-loss, corruption or concurrent cache-writer experiment was performed. Failed terminal checkpoints are preserved as failures, not retried or counted as successful physics results.

1.5 Core fresh-checkout CI and traceable work units

GitHub Actions run 38051481969 at commit `de52b32f0c34a05cf4f6a0c01bca6ee087e6cb67` uses Ubuntu 24.04 and Python 3.12.15. It installs the core editable package with NumPy 2.5.3 and SciPy 1.18.1, passes seven evaluation tests, automatically retrieves/checks both pinned experimental files, and reruns the matched comparison. Its maximum full-Choi discrepancy is $1.3214015 \times 10^{-14}$ versus the 10^{-8} gate. `evidence/core_ci_job.log` and `core_ci_verification.json` preserve the log and summary; the log hash is checked. This core CI result is additional environment evidence, not full optional-backend reproduction or colleague-led independent scientific review. CSV bytes are preserved and automatic Git line-ending conversion is disabled to protect source hashes.

The original 75 tests plus seven additional evaluation tests constitute 82 distinct local passing tests. Repeating controls, CI tests, numerical ages or Monte Carlo trials does not increase that count. Work units remain separate: 73 channel-age comparisons, 90 processed data values, 41 synthetic coherence ages, 10,000 provider-neutral network trials, seven selected invalid contracts with seven positive controls, 108 cold worker jobs and 108 checkpoint reuses. No new hardware experiment or ML training run is counted. Steps 5 and 6 remain the author's and colleagues' full independent reproduction and scientific/release review tasks.

2 Reproduction and data locations

From the repository root, use Python 3.12 and the dependency constraints in `REPRODUCIBILITY.md`. The public clone includes licensed numerical input files with hashes and attribution, so step 1 needs no Zenodo connection. `scripts/reproduce_system.py` executes all four software pathways and verifies the separate pending physical descriptor. The default `scripts/reproduce.py` replays licensed paper numerics offline into a fresh output tree, with the exclusions detailed in Section 3. `-online` explicitly selects wider source acquisition. Generate the historical system tables and claim map with `python scripts/document_system_evaluation.py`.

The four selected run summaries are `evaluation/results/step1-executed/summary.json`, `evaluation/results/step2-confirmation/summary.json`, `evaluation/results/step3-confirmation/summary.json` and `evaluation/results/step4-executed/summary.json`. The missing-data physical case is `evaluation/results/step2-physical-pending/summary.json`. The machine-readable evidence index is `evidence/system_evaluation_claim_map.json`. Full per-case tables retain units and every timing repeat; the CI log and verification record are under `evidence/`.

Source and article materials: https://github.com/VesterlundCoder/memory-discover-lab. Colleague-led independent reproduction and scientific/release review (steps 5 and 6) remain pending.

3 Clean-clone reproduction repair

The review of commit `de52b32` identified clean-clone acquisition, test and figure-generation failures. The later documentation commit retained confirmations, but the executable repair is version 0.6.1. It changes source acquisition, test fixtures and reporting/reproduction interfaces without changing the microscopic equations. Historical source identities and results are retained separately. Current outputs are in `evaluation/results/repaired/`; the repair manifest, execution/test logs, four comparison reports and paper replay claim map are under `evidence/repair/`.

3.1 Inputs, execution mode and scientific scope

The tracked bundle contains ten Teller CSV files and seven PR2026 OUT/NPZ files. Their unchanged bytes are verified against SHA256, and Teller replay additionally checks the original reviewed MD5 locks. The two data records declare CC BY 4.0; creator names, DOI, URLs, fixed revisions and license links are retained in `data/experimental/ATTRIBUTION.md` and `manifest.json`. Unused `3a.csv`, primary-paper PDFs and the unlicensed molecular raw collection are not bundled.

The default `scripts/reproduce.py` uses these licensed numerical inputs and retained reviewed paper transcriptions. It writes a fresh tree, refuses a nonempty output directory and verifies required dependencies/data before execution. It reexecutes the Teller consistency, holdout, readout-window, channel, QuTiP and four SeQUeNCe analyses; PR curve fits; reference-table, exact-bath and count controls; and the hypothetical network workload. It then regenerates figures/tables and runs ten reporting checks. Archived article evidence is not replaced. Records explicitly distinguish verified measurement bytes from unbundled reviewed paper references.

Offline replay does not reacquire the 201-entry molecular source collection or reverify unbundled paper bytes. Its freshly acquired molecular-observation count is zero, and its reporting mode checks that exclusion. The historical count remains attributed to the original archive. `-online` explicitly selects the wider original acquisition adapters and requires the external endpoints. That path was not rerun in the denied-network repair validation; denied endpoints and changed bytes remain failures.

3.2 Clean clone and installed environments

An author-operated local candidate Git repository was cloned into an empty tree, with no ignored source cache, processed-data tree, molecular source-lock file or preceding synthetic-demo output. Isolated core and full virtual environments were installed on Linux/Python 3.12.14. After installation, a test-only Python socket/DNS shim denied external destinations and allowed loopback for local HTTP download tests. This verifies absence of external retrieval during the tested commands; it is not a general security sandbox. Complete installed dependency constraints cover 14 core and 131 full distributions, with the editable project installed separately. CI and Docker use the constraints, and the recommended runtime is Python 3.12. Other Python/platform combinations are not claimed tested.

The database test now supplies temporary synthetic provisional rows, while the synthetic count fixture is a tracked owned input. Optional QuTiP/SeQUeNCe checks have availability skips. The core environment runs 75 lab tests: 68 pass and seven are skipped; all 15 evaluation/regression tests pass. The isolated full environment passes 75 plus 15 tests with no skips. The eight added regressions cover offline inputs, corruption, validation before writes, preservation of figures on missing input, metadata exclusion, changed scientific output, nested channel changes and strict source mismatch. A skipped test is not a passing solver validation.

3.3 Current execution identity and numerical comparisons

Two complete system passes share evaluation-source SHA256

`4c762e6e9c5352d0fa7892b24f0c5fa6fd6c8b6de0259415bfeae42e0a97fbaa`.

Their lab-source SHA256 is

`99b0ef35caf1791653ce2b9c029514b21e9340ed58198194e291bccc4095e62f`.

The same content fingerprints are checked against the published Python files. The candidate local Git identity, UTC times, full configuration and installed environment remain in original outputs; they are not relabeled as a remote release.

Each pass performs 73 channel-age comparisons and 90 processed fidelity comparisons. The full-Choi discrepancy remains $1.3103013 \times 10^{-14}$. The 41-point synthetic step-2 control and hypothetical network gate pass, with physical validation false. Seven faults are rejected and all seven valid positive controls pass. Each local benchmark pass completes 108 cold jobs and 108 terminal-checkpoint reuses, giving 216 of each over the two passes; robustness probes are counted separately. The physical descriptor returns exit 2 with `blocked_missing_reviewed_data` in both passes. The paper replay gives 87 retrieved pairs in 400,000 Teller attempts, six mismatching and two inconclusive PR fits, and 321 retrieved pairs in the separate 2000-trial hypothetical SeQUeNCe case.

`scripts/verify_evaluation.py` compares scientific fields, configuration, input hashes and seeds at 10^{-10} absolute and relative tolerance. Step 4 requires `scientific_results.json`, containing the complete channel/configuration payload with execution-derived IDs and environment removed. Source fingerprints are separately reported and optionally required to match. Timestamps, paths, timing, RSS/CPU and diagnostic path strings are excluded from numerical equality. Changed metrics/channels are rejected. Legacy step-4 summaries with source-dependent digests alone are insufficient for portable cross-version channel comparison. All four strict source/scientific comparisons pass. Runtime records remain evidence of execution, not portable physical predictions; repair wall times do not establish a performance improvement, and other author-validation tasks could be active.

3.4 Figures, optional imports and unexecuted scope

The figure builder validates/loads inputs before writing and stages plots before replacement. Missing-input regression returns exit 2 and preserves an existing architecture figure. PDF creation/modification timestamps are removed; two figure-only runs in the constrained environment are byte identical for all five PDFs and five PNGs. No equivalence across untested plotting/font versions is assumed. Delivered byte checksums are regenerated separately from numerical equality.

In a fresh process, direct PyCCE 1.1.1 import fails at the removed SciPy `isintlike` location. The adapter restores the same SciPy utility and NumPy Unicode dtype alias before import; adapter import and the independent one-spin analytical test pass. This compatibility route is documented. The pinned Dockerfile is updated but Docker was unavailable, so no image-build result is claimed. TeX sources were compiled and PDFs visually inspected separately. Author-operated clean clones/CI do not complete colleagues' independent reproduction or scientific/release review, and no improved material lifetime is established.