



PLATFORM

QNAP

Paths set for QNAP. Container Station stores app data under `/share/Container/`.

Roon Server requires a Linux host.

ROON SERVER RELEASE BRANCH

Which release branch to install on first start

Production

VOLUMES

REQUIRED

**/Roon**

Database, settings, cache, and machine identity. Must be writable and persistent.

`/share/Container/roon`**/Music**

Your primary music library.

`/share/Music`**/RoonBackups**

A host path for Roon's backup destination. Roon's Settings > Backups screen is where you actually enable scheduled backups; the path here just gives Roon somewhere to write them.

`/share/Container/roon-backups`

OPTIONS



Set timezone

RECOMMENDED

Correct timestamps for logs, last.fm scrobbles, and backup schedules.

America/New_York (GMT-4, detected) ▾



Local logging driver **RECOMMENDED**

Prevents unbounded Docker log growth. Uses Docker's local log driver with automatic rotation.



SMB/CIFS mount support

Grants the capabilities and relaxes the AppArmor profile needed to mount SMB shares. Most users should mount shares on the host instead.



USB audio (DAC)

Pass through USB and ALSA devices for local audio output to a USB DAC connected to the host. Not needed if streaming to network endpoints.



HDMI audio

Pass through GPU and ALSA devices for HDMI audio output. Requires GPU drivers on the host.

docker-compose.yml

docker run



```
1  services:
2    roonserver:
3      image: ghcr.io/roonlabs/roonserver:latest
4      container_name: roonserver
5      network_mode: host
6      environment:
7        - ROON_INSTALL_BRANCH=production
8        - TZ=America/New_York
9      volumes:
10       - /share/Container/roon:/Roon
11       - /share/Music:/Music
12       - /share/Container/roon-backups:/RoonBackups
13      restart: unless-stopped
14      logging:
15        driver: local
```



Uses `network_mode: host` for Roon's device discovery (SSDP/mDNS). No port mapping needed.