



Basic Object-Oriented Concepts





Concept: An object has behaviors

- In old style programming, you had:
 - data, which was completely passive
 - functions, which could manipulate any data
- An **object** contains both data and **methods** that manipulate that data
 - An object is *active*, not passive; it *does* things
 - An object is *responsible* for its own data
 - But: it can *expose* that data to other objects



Concept: An object has state

- An object contains both **data** and methods that manipulate that data
 - The data represent the **state** of the object
 - Data can also describe the relationships between this object and other objects
- Example: A **CheckingAccount** might have
 - A **balance** (the internal state of the account)
 - An **owner** (some object representing a person)

Example: A “Rabbit” object

- You could (in a game, for example) create an object representing a rabbit
- It would have data:
 - How hungry it is
 - How frightened it is
 - Where it is
- And methods:
 - eat, hide, run, dig





Concept: Classes describe objects

- Every object belongs to (is an **instance** of) a **class**
- An object may have **fields**, or **variables**
 - The class describes those fields
- An object may have **methods**
 - The class describes those methods
- A class is like a template, or cookie cutter
 - You use the class's **constructor** to make objects



Concept: Classes are like Abstract Data Types

- An **Abstract Data Type** (ADT) bundles together:
 - some data, representing an object or "thing"
 - the operations on that data
- The operations defined by the ADT are the *only* operations permitted on its data
- Example: a **CheckingAccount**, with operations **deposit**, **withdraw**, **getBalance**, etc.
- Classes enforce this bundling together
 - *If* all data values are **private**, a class can also enforce the rule that its defined operations are the only ones permitted on the data



Example of a class

```
class Employee {  
    // Fields  
    private String name;    //Can get but not change  
    private double salary; // Cannot get or set  
    // Constructor  
    Employee(String n, double s) {  
        name = n; salary = s;  
    }  
    // Methods  
    void pay () {  
        System.out.println("Pay to the order of " +  
                             name + " $" + salary);  
    }  
    public String getName() { return name; } // getter  
}
```



Approximate Terminology

- instance = object
- field = instance variable
- method = function
- sending a message to an object =
calling a function
- These are all *approximately* true




Concept: Classes form a hierarchy

- Classes are arranged in a treelike structure called a **hierarchy**
- The class at the root is named **Object**
- Every class, except **Object**, has a **superclass**
- A class may have several ancestors, up to **Object**
- When you define a class, you specify its superclass
 - If you don't specify a superclass, **Object** is assumed
- Every class may have one or more **subclasses**



Example of (part of) a hierarchy



A **FileDialog** is a **Dialog** is a **Window** is a **Container**



C++ is different

- In C++ there may be more than one root
 - but not in Java!
- In C++ an object may have more than one parent (immediate superclass)
 - but not in Java!
- Java has a single, strict hierarchy
 - *Java allows only single inheritance.*



Concept: Objects inherit from superclasses

- A class describes fields and methods
- Objects of that class have those fields and methods
- But an object *also* **inherits**:
 - the fields described in the class's superclasses
 - the methods described in the class's superclasses
- A class is *not* a complete description of its objects!



Example of inheritance

```
class Person {  
    String name;  
    int age;  
    void birthday () {  
        age = age + 1;  
    }  
}
```

```
class Employee  
    extends Person {  
    double salary;  
    void pay () { ...}  
}
```

Every **Employee** has **name** and **age** fields and **birthday** method *as well as* a **salary** field and a **pay** method.



Concept: Objects must be created

- `int n;` does two things:
 - It declares that `n` is an integer variable
 - It allocates space to hold a value for `n`
 - For a primitive, this is all that is needed
- `Employee secretary;` also does two things
 - It declares that `secretary` is type `Employee`
 - It allocates space to hold a *reference* to an Employee
 - For an object, this is *not* all that is needed
- `secretary = new Employee ();`
 - This allocate space to hold a *value* for the Employee
 - Until you do this, the Employee is `null`



Notation: How to declare and create objects

Employee secretary; // declares secretary

secretary = new Employee (); // allocates space

Employee secretary = new Employee(); // does both

- But the secretary is still "blank" (null)

secretary.name = "Adele"; // dot notation

secretary.birthday (); // sends a message



Notation: How to reference a field or method

- Inside a class, no dots are necessary
`class Person { ... age = age + 1; ...}`
- Outside a class, you need to say which object you are talking to
`if (john.age < 75) john.birthday ();`
- If you don't have an object, you cannot use its fields or methods!



Concept: `this` object

- Inside a class, no dots are necessary, because
 - you are working on `this` object
- If you wish, you can make it explicit:
`class Person { ... this.age = this.age + 1; ...}`
- `this` is like an extra parameter to the method
- You usually don't need to use `this`



Concept: A variable can hold subclass objects

- Suppose **B** is a subclass of **A**
 - **A** objects can be assigned to **A** variables
 - **B** objects can be assigned to **B** variables
 - **B** objects can be assigned to **A** variables, but
 - **A** objects can *not* be assigned to **B** variables
 - Every **B** is also an **A** *but* not every **A** is a **B**
- You can **cast**: **bVariable = (B) aObject;**
 - In this case, Java does a runtime check



Example: Assignment of subclasses

```
class Dog { ... }  
class Poodle extends Dog { ... }  
Dog myDog;  
Dog rover = new Dog ();  
Poodle yourPoodle;  
Poodle fifi = new Poodle ();
```

```
myDog = rover;           // ok  
yourPoodle = fifi;       // ok  
myDog = fifi;            //ok  
yourPoodle = rover;      // illegal  
yourPoodle = (Poodle) rover; //runtime check
```



Concept: Methods can be overridden

```
class Bird extends Animal {  
    void fly (String destination) {  
        location = destination;  
    }  
}
```

```
class Penguin extends Bird {  
    void fly (String whatever) { }  
}
```

- So birds can fly. Except penguins.



Concept: Don't call functions, send messages

```
Bird someBird = pingu;  
someBird.fly ("South America");
```

- Did **pingu** actually go anywhere?
 - You sent the message **fly(...)** to **pingu**
 - If **pingu** is a penguin, he ignored it
 - Otherwise he used the method defined in **Bird**
- You did *not* directly call any method
 - You cannot tell, without studying the program, which method actually gets used
 - The same statement may result in different methods being used at different times



Sneaky trick: How to use overridden methods

```
class FamilyMember extends Person {  
    void birthday () { // override birthday() in Person  
        super.birthday (); // call overridden method  
        givePresent ();    // and add your new stuff  
    }  
}
```



Concept: Constructors make objects

- Every class has a **constructor** to make its objects
- Use the keyword **new** to call a constructor
`secretary = new Employee ();`
- You can write your own constructors; but if you don't,
 - Java provides a **default constructor** with no arguments
 - It sets all the fields of the new object to zero
 - If this is good enough, you don't need to write your own
- The syntax for writing constructors is almost like that for writing methods



Syntax for constructors

- *Do not* use a return type and a name; use *only* the class name
- You can supply arguments

```
Employee (String theName, double theSalary) {  
    name = theName;  
    salary = theSalary;  
}
```




Trick: Give field and parameter the same name

- A parameter overrides a field with the same name
- But you can use **this.name** to refer to the field
- ```
class Person {
 String name;
 int age;

 Person (String name, int age) {
 this.name = name;
 this.age = age;
 }
}
```
- Using the same name is a common and useful convention



## Internal workings: Constructor chaining

- If an **Employee** is a **Person**, and a **Person** is an **Object**, then when you say **new Employee ()**
  - The **Employee** constructor calls the **Person** constructor
  - The **Person** constructor calls the **Object** constructor
  - The **Object** constructor creates a new **Object**
  - The **Person** constructor adds its own stuff to the **Object**
  - The **Employee** constructor adds its own stuff to the **Person**



## The case of the vanishing constructor

---

- If you don't write a constructor for a class, Java provides one (the **default constructor**)
  - The one Java provides has no arguments
- If you write *any* constructor for a class, Java does *not* provide a default constructor
- Adding a perfectly good constructor can break a constructor chain
- You may need to fix the chain



## Example: Broken constructor chain

```
class Person {
 String name;
 Person (String name) {
 this.name = name;
 }
}
class Employee extends Person {
 double salary;
 Employee () {
 super();
 salary = 12.50;
 }
}
```

Java tries to execute  
an implicit **super()**  
at this point

- cannot resolve symbol - constructor Person()



## Fixing a broken constructor chain

- Special syntax: **super(...)** calls the superclass constructor
- When one constructor calls another, that call *must be first*

```
class Employee {
 double salary;
 Employee (String name) {
 super(name); // must be first
 salary = 12.50;
 }
}
```
- Now you can only create Employees with names
- This is fair, because you can only create Persons with names



## Trick: one constructor calling another

- `this(...)` calls another constructor for this same class

```
class Something {
 Something (int x, int y, int z) {
 // do a lot of work here
 }
 Something () { this (0, 0, 0); }
}
```

- It is poor style to have the same code more than once
- If you call `this(...)`, that call *must be the first thing* in your constructor



## Concept: You can control access

---

```
class Person {
 public String name;
 private String age;
 protected double salary;
 public void birthday { age++; }
}
```

- Each object is responsible for its own data
- Access control lets an object protect its data *and* its methods



## Concept: *Classes* can have fields and methods

- Usually a class describes fields (variables) and methods for its objects (instances)
  - These are called **instance variables** and **instance methods**
- A class can have its own fields and methods
  - These are called **class variables** and **class methods**
- There is exactly *one* copy of a class variable, not one per object
- Use the special keyword **static** to say that a field or method belongs to the class instead of to objects





## Example of a class variable

---

```
class Person {
 String name;
 int age;
 static int population;

 Person (String name) {
 this.name = name;
 this.age = 0;
 population++;
 }
}
```



## Advice: Restrict access

---

- Always, *always* strive for a narrow interface
- Follow the **principle of information hiding**:
  - the caller should know as little as possible about how the method does its job
  - the method should know little or nothing about where or why it is being called
- Make as much as possible **private**
- Your class is responsible for it's own data; don't allow other classes to screw it up!



## Advice: Use setters and getters

---

```
class Employee extends Person {
 private double salary;
 private boolean male;
 public void setSalary (double newSalary) {
 salary = newSalary;
 }
 public double getSalary () { return salary; }
 public boolean isMale() { return male; }
}
```

- This way the object maintains control
- Setters and getters have conventional names: **set***DataName*, **get***DataName*, **is***DataName* (booleans only)



## Kinds of access

---

- Java provides four levels of access:
  - **public**: available everywhere
  - **protected**: available within the package (in the same subdirectory) and to all subclasses
  - [default]: available within the package
  - **private**: only available within the class itself
- The default is called **package** visibility
- In small programs this isn't important...right?



# The End

---