

GUI Basics

First three slides are repeated from previous lecture notes!

You will probably (in fact should) never write Java codes like the program examples given in these notes. You will use IDEs (integrated development environment / integrated design environment / integrated debugging environment) like Netbeans, Eclipse JDT, Kdeveloper etc. to design / develop / test GUIs.

Java codes given in these notes are for reference, understanding the underlying workings and design of Java GUI API, introducing key concepts, naming conventions and key terms, which you must know for sure to learn and practice in Java GUI API.

Key Terms: GUI, API, Swing, Component, Container, JFrame, JPanel, LayoutManager, GUI Helper Classes, Swing GUI Components (JButton, JTextField, JLabel, JComboBox, J...), Common Features

The Java API

The Java API (*Application Program Interface*, *Application Programming Interface*, or *Application Programmer interface*) consists of numerous classes and interfaces grouped into more than a dozen of packages. You have used classes and interfaces in the java.lang, javax.swing, and java.util packages.

Framework-Based Programming

To create comprehensive projects, you have to use more classes and interfaces in the Java API. The classes and interfaces in the Java API establish a framework for programmers to develop applications using Java. For example, the classes and interfaces in the Java GUI API establish a framework for developing GUI programs. You have to use these classes and interfaces and follow their conventions and rules to create applications. This is referred to as *framework-based programming*.

Framework-Based Programming, cont.

Once you understand the concept of Java and object-oriented programming, the most important lesson from now on is learning how to use the API to develop useful programs. The most effective way to achieve it is to imitate good examples. The book provides many carefully designed examples to demonstrate the concept of the framework-based programming using the Java API.

Motivations

The design of the API for Java GUI programming is an excellent example of how the object-oriented principle is applied. In the chapters that follow, you will learn the framework of Java GUI API and use the GUI components to develop user-friendly interfaces for applications and applets.

Objectives

- ➡ To distinguish between Swing and AWT.
- ➡ To describe the Java GUI API hierarchy.
- ➡ To create user interfaces using frames, panels, and simple GUI components.
- ➡ To understand the role of layout managers.
- ➡ To use the FlowLayout, GridLayout, and BorderLayout managers to layout components in a container.
- ➡ To use JPanel as subcontainers.
- ➡ To specify colors and fonts using the Color and Font classes.
- ➡ To apply common features such as borders, tool tips, fonts, and colors on Swing components.
- ➡ To use borders to visually group user-interface components.
- ➡ To create image icons using the ImageIcon class.


Creating GUI Objects

```
// Create a button with text OK
```

```
JButton jbtOK = new JButton("OK");
```

```
// Create a label with text "Enter your name: "
```

```
JLabel jlblName = new JLabel("Enter your name: ");
```



```
// Create a text field with text "Type Name Here"
```

```
JTextField jtfName = new JTextField("Type Name Here");
```

```
// Create a check box with text bold
```

```
JCheckBox jchkBold = new JCheckBox("Bold");
```

```
// Create a radio button with text red
```

```
JRadioButton jrbRed = new JRadioButton("Red");
```

```
// Create a combo box with choices red, green, and blue
```


```
JComboBox jchoColor = new JComboBox(new String[]{"Red",  
    "Green", "Blue"});
```

Swing vs. AWT


So why do the GUI component classes have a prefix *J*? Instead of JButton, why not name it simply Button? In fact, there is a class already named Button in the java.awt package.

When Java was introduced, the GUI classes were bundled in a library known as the Abstract Windows Toolkit (AWT). For every platform on which Java runs, the AWT components are automatically mapped to the platform-specific components through their respective agents, known as *peers*. AWT is fine for developing simple graphical user interfaces, but not for developing comprehensive GUI projects. Besides, AWT is prone to platform-specific bugs because its peer-based approach relies heavily on the underlying platform. With the release of Java 2, the AWT user-interface components were replaced by a more robust, versatile, and flexible library known as **Swing components**. Swing components are painted directly on canvases using Java code, except for components that are subclasses of java.awt.Window or java.awt.Panel, which must be drawn using native GUI on a specific platform. Swing components are less dependent on the target platform and use less of the native GUI resource. For this reason, Swing components that don't rely on native GUI are referred to as **lightweight components**, and AWT components are referred to as **heavyweight components**.


GUI Class Hierarchy (Swing)



Container Classes




GUI Helper Classes




The helper classes are not subclasses of Component. They are used to describe the properties of GUI components such as graphics context, colors, fonts, and dimension.

Swing GUI Components



Components Covered in the Brief Version



Frames

- ☞ Frame is a window that is not contained inside another window. Frame is the basis to contain other user interface components in Java GUI applications.
- ☞ The JFrame class can be used to create windows.
- ☞ For Swing GUI programs, use JFrame class to create windows.

Creating Frames


```
import javax.swing.*;  
public class MyFrame {  
    public static void main(String[] args) {  
        JFrame frame = new JFrame("Test Frame");  
        frame.setSize(400, 300);  
        frame.setVisible(true);  
        frame.setDefaultCloseOperation(  
            JFrame.EXIT_ON_CLOSE);  
    }  
}
```

MyFrame

Run

Adding Components into a Frame

```
// Add a button into the frame  
frame.getContentPane().add(  
    new JButton("OK"));
```




MyFrameWithComponents

Run

Content Pane Delegation in JDK 1.5

```
// Add a button into the frame  
frame.getContentPane().add(  
    new JButton("OK"));
```



Title bar

Content pane

```
// Add a button into the frame  
frame.add(  
    new JButton("OK"));
```

JFrame Class

javax.swing.JFrame

+JFrame()

Creates a default frame with no title.

+JFrame(title: String)

Creates a frame with the specified title.

+setSize(width: int, height: int): void

Specifies the size of the frame.

+setLocation(x: int, y: int): void

Specifies the upper-left corner location of the frame.

+setVisible(visible: boolean): void

Sets true to display the frame.

+setDefaultCloseOperation(mode: int): void

Specifies the operation when the frame is closed.

+setLocationRelativeTo(c: Component):
void

Sets the location of the frame relative to the specified component.

If the component is null, the frame is centered on the screen.

+pack(): void

Automatically sets the frame size to hold the components in the frame.

Layout Managers



- ☞ Java's layout managers provide a level of abstraction to automatically map your user interface on all window systems.
- ☞ The UI components are placed in containers. Each container has a layout manager to arrange the UI components within the container.
- ☞ Layout managers are set in containers using the `setLayout(LayoutManager)` method in a container.

Kinds of Layout Managers

- ➡ FlowLayout
- ➡ GridLayout
- ➡ BorderLayout
- ➡ Several other layout managers is introduced in textbook's chapter “Containers, Layout Managers, and Borders”

FlowLayout Example

Write a program that adds three labels and text fields into the content pane of a frame with a FlowLayout manager.



ShowFlowLayout

Run

The FlowLayout Class

java.awt.FlowLayout
<div><div>-alignment: int</div><div>-hgap: int</div><div>-vgap: int</div></div>
<div><div>+FlowLayout()</div><div>+FlowLayout(alignment: int)</div><div>+FlowLayout(alignment: int, hgap: int, vgap: int)</div></div>

The get and set methods for these data fields are provided in the class, but omitted in the UML diagram for brevity.

The alignment of this layout manager (default: CENTER).

The horizontal gap of this layout manager (default: 5 pixels).

The vertical gap of this layout manager (default: 5 pixels).


Creates a default FlowLayout manager.

Creates a FlowLayout manager with a specified alignment.

Creates a FlowLayout manager with a specified alignment, horizontal gap, and vertical gap.

GridLayout Example

Rewrite the program in the preceding example using a GridLayout manager instead of a FlowLayout manager to display the labels and text fields.



ShowGridLayout

Run

The GridLayout Class

java.awt.GridLayout
<ul style="list-style-type: none">-rows: int-columns: int-hgap: int-vgap: int
<ul style="list-style-type: none">+GridLayout()+GridLayout(rows: int, columns: int)+GridLayout(rows: int, columns: int, hgap: int, vgap: int)

The get and set methods for these data fields are provided in the class, but omitted in the UML diagram for brevity.

The number of rows in this layout manager (default: 1).

The number of columns in this layout manager (default: 1).

The horizontal gap of this layout manager (default: 0).

The vertical gap of this layout manager (default: 0).

Creates a default GridLayout manager.

Creates a GridLayout with a specified number of rows and columns.


Creates a GridLayout manager with a specified number of rows and columns, horizontal gap, and vertical gap.

The BorderLayout Manager

The BorderLayout manager divides the container into five areas: East, South, West, North, and Center. Components are added to a BorderLayout by using the add method.

```
add(Component,  
constraint), where  
constraint is  
BorderLayout.EAST,  
BorderLayout.SOUTH,  
BorderLayout.WEST,  
BorderLayout.NORTH, or  
BorderLayout.CENTER.
```


BorderLayout Example



ShowBorderLayout

Run

The BorderLayout Class



The Color Class

You can set colors for GUI components by using the java.awt.Color class. Colors are made of red, green, and blue components, each of which is represented by a byte value that describes its intensity, ranging from 0 (darkest shade) to 255 (lightest shade). This is known as the *RGB model*.

```
Color c = new Color(r, g, b);
```

`r`, `g`, and `b` specify a color by its red, green, and blue components.

Example:

```
Color c = new Color(228, 100, 255);
```

Standard Colors

Thirteen standard colors (black, blue, cyan, darkGray, gray, green, lightGray, magenta, orange, pink, red, white, yellow) are defined as constants in java.awt.Color.

The standard color names are constants, but they are named as variables with lowercase for the first word and uppercase for the first letters of subsequent words. Thus the color names violate the Java naming convention. Since JDK 1.4, you can also use the new constants: BLACK, BLUE, CYAN, DARK_GRAY, GRAY, GREEN, LIGHT_GRAY, MAGENTA, ORANGE, PINK, RED, WHITE, and YELLOW.

Setting Colors

You can use the following methods to set the component's background and foreground colors:

```
setBackground(Color c)
```

```
setForeground(Color c)
```

Example:

```
jbt.setBackground(Color.yellow);
```

```
jbt.setForeground(Color.red);
```

The Font Class

Font Names

Standard font names that are supported in all platforms are:

SansSerif, Serif,
Monospaced, Dialog,
or DialogInput.

Font Style

Font.PLAIN (0),
Font.BOLD (1),
Font.ITALIC (2), and
Font.BOLD +
Font.ITALIC (3)

`Font myFont = new Font(name, style, size);`

Example:

```
Font myFont = new Font("SansSerif ", Font.BOLD, 16);  
Font myFont = new Font("Serif", Font.BOLD+Font.ITALIC, 12);  
  
JButton jbtOK = new JButton("OK");  
jbtOK.setFont(myFont);
```

Finding All Available Font Names

```
GraphicsEnvironment e =  
    GraphicsEnvironment.getLocalGraphicsEnvironment();  
String[] fontnames =  
    e.getAvailableFontFamilyNames();  
for (int i = 0; i < fontnames.length; i++)  
    System.out.println(fontnames[i]);
```


Using Panels as Sub-Containers

- ➡ Panels act as sub-containers for grouping user interface components.
- ➡ It is recommended that you place the user interface components in panels and place the panels in a frame. You can also place panels in a panel.
- ➡ To add a component to JFrame, you actually add it to the content pane of JFrame. To add a component to a panel, you add it directly to the panel using the add method.



Creating a JPanel

You can use new JPanel() to create a panel with a default FlowLayout manager or new JPanel(LayoutManager) to create a panel with the specified layout manager. Use the add(Component) method to add a component to the panel. For example,

```
JPanel p = new JPanel();  
p.add(new JButton("OK"));
```

Testing Panels Example


This example uses panels to organize components. The program creates a user interface for a Microwave oven.



TestPanels

Run

Common Features of Swing Components



Borders

You can set a border on any object of the JComponent class. Swing has several types of borders. To create a titled border, use

`new TitledBorder(String title).`

To create a line border, use

`new LineBorder(Color color, int width),`

where width specifies the thickness of the line.

For example, the following code displays a titled border on a panel:

```
JPanel panel = new JPanel();  
panel.setBorder(new TitledBorder("My Panel"));
```

Test Swing Common Features

Component Properties

- ☞ font
- ☞ background
- ☞ foreground
- ☞ preferredSize
- ☞ minimumSize
- ☞ maximumSize

JComponent Properties

- ☞ tooltipText
- ☞ border

TestSwingCommonFeatures

Run

Image Icons

Java uses the javax.swing.ImageIcon class to represent an icon. An icon is a fixed-size picture; typically it is small and used to decorate components. Images are normally stored in image files. You can use new ImageIcon(filename) to construct an image icon. For example, the following statement creates an icon from an image file us.gif in the image directory under the current class path:

```
ImageIcon icon = new ImageIcon("image/us.gif");
```

TestImageIcon

Run

Splash Screen

A *splash screen* is an image that is displayed while the application is starting up. If your program takes a long time to load, you may display a splash screen to alert the user. For example, the following command:

```
java -splash:image/us.gf TestImageIcon
```

displays an image while the program TestImageIcon is being loaded.