```
0000 ¶   --|¬ATTENTION¬: RESPECTER LA CASSE DES CARACTERES DES¬TYPES, LE¬COMPILATEUR Y PRETE¬ATTENTION¶¶¬¬¬¬----------¶package¬¬¬¬_standrd¬¬¬¬¬¬¬¬--| Package
     invisible aux programmes¶is¬¬¬¬---------¶¶¶¬¬¬¬¬¬¬¬¬¬¬¬¬¶  package¬¬¬¬¬STANDARD¶  is¬¬¬¬¬¬¬¬¬¬¬¬¶¶    type BOOLEAN¬¬¬is (FALSE, TRUE);¶¶    type SHOR
     T_INTEGER¬¬is range -2**15 .. 2**15-1;¶    type INTEGER¬¬¬is range -2**31 .. 2**31-1;¶    type LONG_INTEGER¬¬is range -2**63 .. 2**63-1;¶¶    type FLO
     AT¬¬¬is digits¬ 6 range -1.0E38 ..¬1.0E38;¶    type LONG_FLOAT¬¬¬is digits¬15 range -1.0E308 .. 1.0E308;¶¶    type CHARACTER is (¶¬_nul,  _soh,  _stx,
     ¬ _etx,¬  _eot, _enq,  _ack,  _bel,¶¬_bs,   _ht,   _lf,¬ _vt,¬  _ff,  _cr,   _so,¬  _si,¶¬_dle,  _dc1,  _dc2,¬ _dc3,¬  _dc4, _nak,  _syn,  _etb,¶¬_can
     ,  _em,   _sub,¬ _esc,¬  _fs,  _gs,   _rs,¬  _us,¶¶¬' ',  '!',  '"',  '#',    '$',  '%',  '&',  ''',¶¬'(',  ')',  '*',  '+',    ',',  '-',  '.',  '/',
     ¶¬'0',  '1',  '2',  '3',    '4',  '5',  '6',  '7',¶¬'8',  '9',  ':',  ';',    '<',  '=',  '>',  '?',¶¶¬'@',  'A',  'B',  'C',    'D',  'E',  'F',  'G'
     ,¶¬'H',  'I',  'J',  'K',    'L',  'M',  'N',  'O',¶¬'P',  'Q',  'R',  'S',    'T',  'U',  'V',  'W',¶¬'X',  'Y',  'Z',  '[',    '\',  ']',  '^',  '_'
     ,¶¶¬'`',  'a',  'b',  'c',    'd',  'e',  'f',  'g',¶¬'h',  'i',  'j',  'k',    'l',  'm',  'n',  'o',¶¬'p',  'q',  'r',  's',    't',  'u',  'v',  'w
     ',¶¬'x',  'y',  'z',  '{',    '|',  '}',  '~',  _del¶¬);¶¶¬¬-----¶    package¬ASCII¶    is¬¬-----¶¶¬  NUL  : constant CHARACTER := _nul;  SOH  : const
0010 ant CHARACTER := _soh;¶¬  STX  : constant CHARACTER := _stx;  ETX  : constant CHARACTER := _etx;¶¬  EOT  : constant CHARACTER := _eot;  ENQ  : constan
     t CHARACTER := _enq;¶¬  ACK  : constant CHARACTER := _ack;  BEL  : constant CHARACTER := _bel;¶¬  BS   : constant CHARACTER := _bs;   HT   : constant
     CHARACTER := _ht;¶¬  LF   : constant CHARACTER := _lf;   VT   : constant CHARACTER := _vt;¶¬  FF   : constant CHARACTER := _ff;   CR   : constant CHAR
     ACTER := _cr;¶¬  SO   : constant CHARACTER := _so;   SI   : constant CHARACTER := _si;¶¬  DLE  : constant CHARACTER := _dle;  DC1  : constant CHARACTE
     R := _dc1;¶¬  DC2  : constant CHARACTER := _dc2;  DC3  : constant CHARACTER := _dc3;¶¬  DC4  : constant CHARACTER := _dc4;  NAK  : constant CHARACTER
     := _nak;¶¬  SYN  : constant CHARACTER := _syn;  ETB  : constant CHARACTER := _etb;¶¬  CAN  : constant CHARACTER := _can;  EM   : constant CHARACTER :=
      _em;¶¬  SUB  : constant CHARACTER := _sub;  ESC  : constant CHARACTER := _esc;¶¬  FS   : constant CHARACTER := _fs;   GS   : constant CHARACTER := _g
     s;¶¬  RS   : constant CHARACTER := _rs;   US   : constant CHARACTER := _us;¶¬  DEL  : constant CHARACTER := _del;¶¶¬  EXCLAM¬      : constant CHARACTE
     R :=¬'!';¶¬  SHARP¬      : constant CHARACTER :=¬'#';¶¬  PERCENT¬      : constant CHARACTER :=¬'%';¶¬  COLON¬      : constant CHARACTER :=¬':';¶¬  QUE
     RY¬      : constant CHARACTER :=¬'?';¶¬  L_BRACKET     : constant CHARACTER :=¬'[';¶¬  R_BRACKET     : constant CHARACTER :=¬']';¶¬  UNDERLINE     : c
0020 onstant CHARACTER :=¬'_';¶¬  L_BRACE¬      : constant CHARACTER :=¬'{';¶¬  R_BRACE¬      : constant CHARACTER :=¬'}';¶¶¬  QUOTATION     : constant CHA
     RACTER :=¬'";¶¬  DOLLAR¬      : constant CHARACTER :=¬'$';¶¬  AMPERSAND     : constant CHARACTER :=¬'&';¶¬  SEMICOLON     : constant CHARACTER :=¬';'
     ;¶¬  AT_SIGN¬      : constant CHARACTER :=¬'@';¶¬  BACK_SLASH    : constant CHARACTER :=¬'\';¶¬  CIRCUMFLEX    : constant CHARACTER :=¬'^';¶¬  GRAVE¬
          : constant CHARACTER :=¬'`';¶¬  BAR¬      : constant CHARACTER :=¬'|';¶¬  TILDE¬      : constant CHARACTER :=¬'~';¶¶¬  LC_A : constant CHARACTER
     := 'a';   LC_B : constant CHARACTER := 'b';¶¬  LC_C : constant CHARACTER := 'c';   LC_D : constant CHARACTER := 'd';¶¬  LC_E : constant CHARACTER := '
     e';   LC_F : constant CHARACTER := 'f';¶¬  LC_G : constant CHARACTER := 'g';   LC_H : constant CHARACTER := 'h';¶¬  LC_I : constant CHARACTER := 'i';
       LC_J : constant CHARACTER := 'j';¶¬  LC_K : constant CHARACTER := 'k';   LC_L : constant CHARACTER := 'l';¶¬  LC_M : constant CHARACTER := 'm';   LC
     _N : constant CHARACTER := 'n';¶¬  LC_O : constant CHARACTER := 'o';   LC_P : constant CHARACTER := 'p';¶¬  LC_Q : constant CHARACTER := 'q';   LC_R :
      constant CHARACTER := 'r';¶¬  LC_S : constant CHARACTER := 's';   LC_T : constant CHARACTER := 't';¶¬  LC_U : constant CHARACTER := 'u';   LC_V : con
     stant CHARACTER := 'v';¶¬  LC_W : constant CHARACTER := 'w';   LC_X : constant CHARACTER := 'x';¶¬  LC_Y : constant CHARACTER := 'y';   LC_Z : constan
0030 t CHARACTER := 'z';¶¶¬-----¶    end¬ASCII;¶¬-----¶¶    subtype NATURAL¬¬is INTEGER range 0 .. 2147483647;¶    subtype POSITIVE¬is INTEGER range 1 .. 2
     147483647;¶¶    type STRING¬is array (POSITIVE range <>) of CHARACTER;¶¬-- pragma¬PACK(STRING);¶¶    type DURATION¬is delta 2#1.0#E-14¬range -86_400.0
      .. 86_400.0;¶¶    CONSTRAINT_ERROR¬: exception;¶    NUMERIC_ERROR¬: exception;¶    PROGRAM_ERROR¬: exception;¶    STORAGE_ERROR¬: exception;¶    TASK
     ING_ERROR¬: exception;¶¶¬¬--| Type de base invisible renomm en ADDRESS (le¬type visible) dans SYSTEM¶¶    type _address¬is new LONG_INTEGER;¶¶¶    pri
     vate¶¶      --|¬Ce type est invisible, il doit tre en minuscules¬et sert de type de base pour DURATION¶¶    type _duration is delta 2#1.0#E-14 range -
      16#20000.0# .. 16#1FFFF.FFFC#;¶¶      -- Specification of implementation sizes¶¬for BOOLEAN'size¬¬use 1;¶¬for CHARACTER'size¬¬use 8;¶¬for SHORT_INTEG
     ER'size¬use 16;¶¬for INTEGER'size¬¬use 32;¶¬for LONG_INTEGER'size¬use 64;¶¬for FLOAT'size¬¬use 32;¶¬for LONG_FLOAT'size¬¬use 64;¶¬for DURATION'size¬¬u
     se 32;¶¶¬--------¶  end¬STANDARD;¶¬--------¶¶¬--------¶end¬_standrd;¶¬--------¶
```