```
0000 --|-------------------------------------------------------------------------------------------------------¶--|¬LEX¶--|-------------------------------------
     ------------------------------------------------------¶package LEX is¶       ¶  type LEX_TYPE is (¬¬¬¬¬¬¬¬¬--| TYPE D UNITE LEXICALE¶         LT_E
     RROR,¬¬¬¬¬¬¬¬¬--| ULEX ERREUR¶¶         LT_ABORT,¬¬LT_ABS,¬¬LT_ACCEPT,¬LT_ACCESS,¬¬¬--| UNITES LEXICALES TERMINALES MOTS RESERVES¶         LT_ALL,¬¬LT_
     AND,¬¬LT_ARRAY,¬¬LT_AT,¬¬LT_BEGIN,¶         LT_BODY,¬¬LT_CASE,¬¬LT_CONSTANT,¬LT_DECLARE,¬LT_DELAY,¶         LT_DELTA,¬¬LT_DIGITS,¬LT_DO,¬¬LT_ELSE,¬¬LT
     _ELSIF,¶         LT_END,¬¬LT_ENTRY,¬¬LT_EXCEPTION,¬LT_EXIT,¬¬LT_FOR,¶         LT_FUNCTION,¬LT_GENERIC,¬LT_GOTO,¬¬LT_IF,¶         LT_IN,¬¬LT_IS,¬¬LT_LI
     MITED,¬LT_LOOP,¬¬LT_MOD,¶         LT_NEW,¬¬LT_NOT,¬¬LT_NULL,¬¬LT_OF,¬¬LT_OR,¶         LT_OTHERS,¬¬LT_OUT,¬¬LT_PACKAGE,¬LT_PRAGMA,¬LT_PRIVATE,¶
      LT_PROCEDURE,¬LT_RAISE,¬¬LT_RANGE,¬¬LT_RECORD,¶         LT_REM,¬¬LT_RENAMES,¬LT_RETURN,¬LT_REVERSE,¬LT_SELECT,¶         LT_SEPARATE,¬LT_SUBTYPE,¬LT_T
     ASK,¬¬LT_TERMINATE,¶         LT_THEN,¬¬LT_TYPE,¬¬LT_USE,¬¬LT_WHEN,¬¬LT_WHILE,¶         LT_WITH,¬¬LT_XOR,¶¬¬¬¬¶         LT_AMPERSAND,¬LT_APOSTROPHE,¬LT
     _LEFT_PAREN,¬LT_RIGHT_PAREN,¬¬--| UNITES LEXICALES TERMINALES SYMBOLES¶         LT_STAR,¬¬LT_PLUS,¬¬LT_COMMA,¬¬LT_HYPHEN,¬LT_PERIOD,¶         LT_SLASH
     ,¬¬LT_COLON,¬¬LT_SEMICOLON,¬LT_LESS_THAN,¬LT_EQUAL,¶         LT_GREATER_THAN,¬LT_VERTICAL_BAR,¬LT_ARROW,¬¬LT_DOUBLE_DOT,¶         LT_DOUBLE_STAR,¬LT_B
0010 ECOMES,¬LT_NOT_EQUAL,¬LT_GREATER_EQUAL,¶         LT_LESS_EQUAL,¬LT_LEFT_LABEL,¬LT_RIGHT_LABEL,¬LT_BOX,¶¶         LT_IDENTIFIER,¬LT_NUMERIC_LIT,¬LT_STR
     ING_LIT,¬LT_CHAR_LIT,¬¬--| UNITES LEXICALES AVEC SEMANTIQUE¶¶         LT_END_MARK¬¬¬¬¬¬¬¬¬--| ULEX FIN DE SOURCE¶         );¶      ¶  subtype¬LT_RESERV
     ED¬is LEX_TYPE range LT_ABORT¬  .. LT_XOR;¶  subtype¬LT_SYMBOL¬¬is LEX_TYPE range LT_AMPERSAND  .. LT_BOX;¶  subtype¬LT_TERMINAL¬is LEX_TYPE range LT_
     ABORT¬  .. LT_BOX;¶  subtype¬LT_WITH_SEMANTICS¬is LEX_TYPE range LT_IDENTIFIER .. LT_CHAR_LIT;¶¶¶  MAX_STRING¬: constant POSITIVE¬:= 255;¬¬¬¬¬¬¬--| CHA
     INE DE 256 CARACTERES MAXIMUM¶      ¶  type LINE_OF_SOURCE¬is record¶¬¬¬  LEN¬: NATURAL;¶¬¬¬  BDY¬: STRING(¬1 .. MAX_STRING );¶¬¬¬end record;¶      ¶
      SLINE¬¬: LINE_OF_SOURCE;¬¬¬¬¬¬¬¬--| LIGNE¬COURANTE LUE¶  LAST¬¬: NATURAL;¬¬¬¬¬¬¬¬--| NOMBRE DE CARACTERES LUS¶  COL¬¬: NATURAL;¬¬¬¬¬¬¬¬--| DERNIERE COLO
     NNE BALAYEE¶  F_COL¬¬: NATURAL;¬¬¬¬¬¬¬¬--| POSITION DU PREMIER CARACTERE DU LEXEME¶  E_COL¬¬: NATURAL;¬¬¬¬¬¬¬¬--| POSITION DU DERNIER CARACTERE DU LEXEM
     E¶  LTYPE¬¬: LEX_TYPE;¬¬¬¬¬¬¬¬--| TYPE DU LEXEME¶   ¶    ¶  procedure LEX_SCAN;¶  function  TOKEN_STRING¬¬¬¬return STRING;¶¶  function  LEX_IMAGE¬( LT
     :LEX_TYPE )¬¬return STRING;¶      ¶--|-------------------------------------------------------------------------------------------------------¶end LEX;¶
```