

```

0000  --ATTENTION: RESPECTER LA CASSE DES CARACTERES DES-TYPES, LE-COMPILATEUR Y PRETE-ATTENTION
package STANDRD is
  type BOOLEAN is (FALSE, TRUE);
  type SHORT_INTEGER is range -2**15 .. 2**15-1;
  type INTEGER is range -2**31 .. 2**31-1;
  type LONG_INTEGER is range -2**63 .. 2**63-1;
  type FLOAT is digits 6 range -1.0E38 .. 1.0E38;
  type LONG_FLOAT is digits 15 range -1.0E308 .. 1.0E308;
  type CHARACTER is (' ', _nul, _soh, _stx, _etx, _eot, _enq, _ack, _bel, _bs, _ht, _lf, _vt, _ff, _cr, _so, _si, _dle, _dc1, _dc2, _dc3, _dc4, _nak, _syn, _etb, _can, _em, _sub, _esc, _fs, _gs, _rs, _us, _del);
  package ASCII is
    NUL : constant CHARACTER := _nul;
    SOH : constant CHARACTER := _soh;
    STX : constant CHARACTER := _stx;
    ETX : constant CHARACTER := _etx;
    EOT : constant CHARACTER := _eot;
    ENQ : constant CHARACTER := _enq;
    ACK : constant CHARACTER := _ack;
    BEL : constant CHARACTER := _bel;
    BS : constant CHARACTER := _bs;
    HT : constant CHARACTER := _ht;
    LF : constant CHARACTER := _lf;
    VT : constant CHARACTER := _vt;
    FF : constant CHARACTER := _ff;
    CR : constant CHARACTER := _cr;
    SO : constant CHARACTER := _so;
    SI : constant CHARACTER := _si;
    DLE : constant CHARACTER := _dle;
    DC1 : constant CHARACTER := _dc1;
    DC2 : constant CHARACTER := _dc2;
    DC3 : constant CHARACTER := _dc3;
    DC4 : constant CHARACTER := _dc4;
    NAK : constant CHARACTER := _nak;
    SYN : constant CHARACTER := _syn;
    ETB : constant CHARACTER := _etb;
    CAN : constant CHARACTER := _can;
    EM : constant CHARACTER := _em;
    SUB : constant CHARACTER := _sub;
    ESC : constant CHARACTER := _esc;
    FS : constant CHARACTER := _fs;
    GS : constant CHARACTER := _gs;
    RS : constant CHARACTER := _rs;
    US : constant CHARACTER := _us;
    DEL : constant CHARACTER := _del;
    EXCLAM : constant CHARACTER := '!';
    SHARP : constant CHARACTER := '#';
    PERCENT : constant CHARACTER := '%';
    COLON : constant CHARACTER := ':';
    QUOTE : constant CHARACTER := '"';
    UNDERLINE : constant CHARACTER := '_';
    L_BRACKET : constant CHARACTER := '[';
    R_BRACKET : constant CHARACTER := ']';
    L_BRACE : constant CHARACTER := '{';
    R_BRACE : constant CHARACTER := '}';
    QUOTATION : constant CHARACTER := '`';
    DOLLAR : constant CHARACTER := '$';
    AMPERSAND : constant CHARACTER := '&';
    SEMICOLON : constant CHARACTER := ';';
    AT_SIGN : constant CHARACTER := '@';
    BACK_SLASH : constant CHARACTER := '\';
    CIRCUMFLEX : constant CHARACTER := '^';
    GRAVE : constant CHARACTER := '`';
    BAR : constant CHARACTER := '|';
    TILDE : constant CHARACTER := '~';
    LC_A : constant CHARACTER := 'a';
    LC_B : constant CHARACTER := 'b';
    LC_C : constant CHARACTER := 'c';
    LC_D : constant CHARACTER := 'd';
    LC_E : constant CHARACTER := 'e';
    LC_F : constant CHARACTER := 'f';
    LC_G : constant CHARACTER := 'g';
    LC_H : constant CHARACTER := 'h';
    LC_I : constant CHARACTER := 'i';
    LC_J : constant CHARACTER := 'j';
    LC_K : constant CHARACTER := 'k';
    LC_L : constant CHARACTER := 'l';
    LC_M : constant CHARACTER := 'm';
    LC_N : constant CHARACTER := 'n';
    LC_O : constant CHARACTER := 'o';
    LC_P : constant CHARACTER := 'p';
    LC_Q : constant CHARACTER := 'q';
    LC_R : constant CHARACTER := 'r';
    LC_S : constant CHARACTER := 's';
    LC_T : constant CHARACTER := 't';
    LC_U : constant CHARACTER := 'u';
    LC_V : constant CHARACTER := 'v';
    LC_W : constant CHARACTER := 'w';
    LC_X : constant CHARACTER := 'x';
    LC_Y : constant CHARACTER := 'y';
    LC_Z : constant CHARACTER := 'z';
  end ASCII;
  subtype NATURAL is INTEGER range 0 .. 2147483647;
  subtype POSITIVE is INTEGER range 1 .. 2147483647;
  type STRING is array (POSITIVE range <>) of CHARACTER;
  pragma PACK (STRING);
  type DURATION is delta 2#1.0#E-14 range -86_400.0 .. 86_400.0;
  CONSTRAINT_ERROR : exception;
  NUMERIC_ERROR : exception;
  PROGRAM_ERROR : exception;
  STORAGE_ERROR : exception;
  TASKING_ERROR : exception;
  type _address is new LONG_INTEGER;
  type _duration is delta 2#1.0#E-14 range -16#20000.0 .. 16#1FFFF.FFFC#;
  --Ce type est invisible, il doit tre en minuscules-et sert de type de base pour DURATION
  type _duration is delta 2#1.0#E-14 range -16#20000.0 .. 16#1FFFF.FFFC#;
  -- Specification of implementation sizes
  for BOOLEAN'size use 1;
  for CHARACTER'size use 8;
  for SHORT_INTEGER'size use 16;
  for INTEGER'size use 32;
  for LONG_INTEGER'size use 64;
  for FLOAT'size use 32;
  for LONG_FLOAT'size use 64;
  for DURATION'size use 32;
end STANDRD;

```