```
--------------------------------------------------------------------------------¶-- TLALOC¬(The Lonesome Ada Loving Ol'timer Compiler) Strict Ada 83 C
ompiler¶-- Copyright (C) 2024-2026 Vincent MORIN - Universit de Bretagne Occidentale¶--¶-- This program is free software: you can redistribute it and/
or modify¶-- it under the terms of the GNU General Public License as published by¶-- the Free Software Foundation, either¬version 3¬of the License, or
¶-- (at your option)¬any later¬version.¶--¶-- This program is distributed in the hope that it will be useful,¶-- but WITHOUT ANY WARRANTY; without eve
n the implied warranty of¶-- MERCHANTABILITY or FITNESS¬FOR A PARTICULAR PURPOSE. See¬the¶-- GNU General Public License¬for more details.¶--¶-- You sh
ould have received a¬copy of the GNU General Public License¶-- along with this program. If not, see¬<https://www.gnu.org/licenses/>.¶----------------
---------------------------------------------------------------¶¶WITH SEQUENTIAL_IO;¶WITH TEXT_IO;¶SEPARATE(¬IDL )¶¶-----------------------------------
-------------------------------------------------------------------------------------------¶--¬¬IDL_TBL.ADB¬¬Vincent MORIN¶-----------------------------
---------------------------------------------------------------------------------------------¶--¬1¬2¬3¬4¬5¬6¬7¬8¬9¬A¬B¬C¶¶¬¬¬¬¬--------¶¬PACKAGE BODY¬¬¬IDL_
TBL¶IS¬¬¬¬¬-------¶¶--|||||||||||||||||||||||||||||||||||||||||||||||||||||||||||||||||||||||||||||||||||||||||||||||||¶--|¬¬PROCEDURE¬INIT_SPEC¶--|¶
PROCEDURE¬INIT_SPEC¬( SPEC_FILE : STRING ) IS¶¶  PACKAGE¬INT_IO IS¬NEW INTEGER_IO( INTEGER );¶  USE INT_IO;¶  USE TEXT_IO;¶¶  SFILE¬¬¬: FILE_TYPE;¶  T
_CHR¬¬¬: CHARACTER;¶  T_INT¬¬¬: INTEGER;¶  T_TXT¬¬¬: STRING(¬1 .. 50 );¶  T_LAST¬¬¬: NATURAL;¶  AS_SEEN¬¬¬: BOOLEAN;¶  AS_LIST_SEEN¬¬: BOOLEAN;¶  NON_
AS_SEEN¬¬: BOOLEAN;¶BEGIN¶  OPEN( SFILE, IN_FILE, SPEC_FILE & ".tbl" );¶  LAST_NODE := -1;¶  LAST_ATTR := -1;¶  LAST_NODE_ATTR :=¬0;¶  WHILE NOT END_O
F_FILE( SFILE ) LOOP¶    GET( SFILE, T_CHR );¬¬¬¬¬¬¬¬¬--| PRENDRE LE CARACTERE INDIQUANT LE TYPE DE LIGNE¶    IF T_CHR /= 'C'¬AND T_CHR¬/= 'E' THEN¬¬¬¬
¬¬--| PAS CLASSE (C OU E) DONC 'N' OU 'A'¶      GET( SFILE, T_INT );¬¬¬¬¬¬¬¬¬--| N DE¬NOEUD OU D'ATTRIBUT¬(NEGATIF)¶    END IF;¶    GET_LINE( SFILE, T_
TXT, T_LAST );¬¬¬¬¬¬¬¬--| PRENDRE LE RESTANT DE LA LIGNE¶¶    SUPPRESS_BLANKS:¶    DECLARE¶      D¬¬: INTEGER¬:= 0;¶      BEGIN¶      FOR¬S IN 1 ..¬T_LAS
T LOOP¶        IF T_TXT( S¬) /= ' ' AND T_TXT(¬S ) /= ASCII.HT THEN¬¬¬¬¬--| CARACTERE NON '¬' OU TAB¶¬D := D + 1;¬¬¬¬¬¬¬¬¬--| AVANCER LE POINTEUR DE DES
TINATION¶¬T_TXT( D ) := T_TXT( S );¬¬¬¬¬¬¬¬--| RECOPIER LE CARACTERE¶        END IF;¶      END¬LOOP;¶      T_LAST := D;¬¬¬¬¬¬¬¬¬¬--| LONGUEUR REDUITE DE
S ESPACES¶    END SUPPRESS_BLANKS;¶¶¬¬¬¬¬--| NOEUDS¶    IF T_CHR = 'N' THEN¬¬¬¬¬¬¬¬¬¬--| UNE LIGNE DECLARANT UN NOEUD¶      LAST_NODE := LAST_NODE + 1;¬¬
¬¬¬¬¬--| UN NOEUD DE PLUS¶      IF LAST_NODE /= T_INT THEN¬¬¬¬¬¬¬¬¬--| LE NUMERO D'ORDRE DOIT CORRESPONDRE¬AU NUMERO¬D'IDENTIFICATION¶        PUT_LINE(
"IDL.IDL_TBL.INIT_SPEC: LAST NODE /= T_INT" );¶        RAISE PROGRAM_ERROR;¶      END¬IF;¶¶      N_SPEC( NODE_NAME'VAL( LAST_NODE ) ) := (¬NS_SIZE¬¬=>
 0,¬¬¬¬--| PAS D'ATTRIBUT,¬DONC TAILLE NULLE¶¬¬¬¬¬NS_FIRST_A¬=> 0,¬¬¬¬--| PAS D'ATTRIBUT ENCORE VU,¬NUMERO DU¬PREMIER ¬0¶¬¬¬¬¬NS_ARITY¬¬=> NULLARY¶¬¬¬¬)
;¶      AS_LIST_SEEN := FALSE;¬¬¬¬¬¬¬¬¬--| PAS VU D' "as_"¬LIST¶      AS_SEEN      := FALSE;¬¬¬¬¬¬¬¬¬--| PAS VU D' "as_"¶      NON_AS_SEEN  := FALSE;¬¬¬
¬¬¬¬¬¬--| PAS VU DE NON "as_" (UN "xd_" OU "sm_" ...)¶¶¬¬¬¬¬--| ATTRIBUTS¶¶    ELSIF¬T_CHR = 'A' OR T_CHR = 'B' OR¬T_CHR = 'I' THEN¶      LAST_NODE_ATTR
 := LAST_NODE_ATTR + 1;¬¬¬¬¬¬¬--| UN ATTRIBUT DE PLUS¶      DECLARE¶        NN¬: NODE_NAME¬:= NODE_NAME'VAL( LAST_NODE );¶      BEGIN¶        IF N_SPEC
( NN ).NS_FIRST_A = 0 THEN¬¬¬¬¬¬¬--| SI L'ON A PAS VU LE PREMIER ATTRIBUT¶¬N_SPEC( NN ).NS_FIRST_A := LAST_NODE_ATTR;¬¬¬¬¬¬--| METTRE L'INDICE¬DE CET AT
TRIBUT COMME PREMIER¶        END IF;¶        N_SPEC( NN ).NS_SIZE := N_SPEC(¬ NN ).NS_SIZE + 1;¬¬¬¬¬¬--| INCREMENTER LA TAILLE DU NOEUD AUQUEL ON AJOUT
E L'ATTRIBUT¶¶        IF T_LAST >= 3 AND THEN T_TXT(1¬.. 3) = "as_" THEN¬¬¬¬¬¬--| ATTRIBUT COMMENANT PAR "as_"¶¬IF T_INT < 0 THEN¬¬¬¬¬¬¬¬¬--| IDENTIFICA
TEUR NEGATIF (REPERE UNE LISTE, UN SEQ_TYPE)¶¬  IF AS_SEEN OR NON_AS_SEEN THEN¬¬¬¬¬¬¬--| ON A DEJ VU UN¬AS_ OU UN¬NON AS_, INTERDIT :¬UNE "AS_"¬LIST DO
IT¬ARRIVER EN TTE¶¬    PUT_LINE ( "BAD AS_LIST: " &  T_TXT(1 .. T_LAST) );¶¬  END IF;¶¬  AS_SEEN¬:= TRUE;¬¬¬¬¬¬¬¬¬--| VU UN¬"AS_"¶¬  AS_LIST_SEEN := TR
UE;¬¬¬¬¬¬¬¬--| VU UNE "AS_" LIST¶¬  N_SPEC(¬NN ).NS_ARITY := ARITIES'VAL(¬ARITIES'POS( N_SPEC( NN ).NS_ARITY)+ 4 );¶¶¬ELSE¬¬¬¬¬¬¬¬¬¬--| IDENTIFICATEUR P
OSITIF (UN  AS_" QUI N'EST PAS UN SEQ_TYPE)¶¬  IF AS_LIST_SEEN OR NON_AS_SEEN THEN¬¬¬¬¬¬¬--| ON NE¬DOIT PAS AVOIR DE "AS_" LIST AVANT UN "AS_" NON LIST
E ET PAS DE NON "AS_" NON PLUS¶¬    PUT_LINE ( "BAD AS_...: "¬& T_TXT(1¬.. T_LAST) );¶¬  END IF;¶¬  AS_SEEN¬:= TRUE;¬¬¬¬¬¬¬¬¬--| VU UN¬"AS_"¶¬  N_SPEC(
¬NN ).NS_ARITY := ARITIES'VAL(¬ARITIES'POS( N_SPEC( NN ).NS_ARITY)+ 1 );¶¬END IF;¶¶        ELSE¬¬¬¬¬¬¬¬¬¬--| PAS UN "AS_"¶¬NON_AS_SEEN := TRUE;¬¬¬¬¬¬¬-
-| NON "AS_" VU¶        END IF;¶      END;¶¶      A_SPEC( LAST_NODE_ATTR ).IS_LIST :=  T_INT < 0;¬¬¬¬¬¬--| INDICATEUR DE LISTE (UNE SEULE PAR NOEUD)¶
    T_INT := ABS T_INT;¬¬¬¬¬¬¬¬¬--| IDENTIFICATEUR EN POSITIF¶      A_SPEC( LAST_NODE_ATTR ).ATTR := ATTRIBUTE_NAME'VAL( T_INT );¬¬¬¬¬--| STOCKER L'IDEN
TIFICATEUR DE L'ATTRIBUT¶      IF T_INT > LAST_ATTR THEN¬¬¬¬¬¬¬¬--| DEPASSE LE NOMBRE D'ATTRIBUTS VUS¶        LAST_ATTR := T_INT;¬¬¬¬¬¬¬¬¬--| METTRE  JO
UR CE NOMBRE (NOTRE ATTRIBUT INDIQUE QU'IL Y¬EN A PLUS)¶      END¬IF;¶¶    END IF;¶¶  END LOOP;¶  CLOSE( SFILE );¶END INIT_SPEC;¶--||||||||||||||||||
|||||||||||||||||||||||||||||||||||||||||||||||||||||||||||||||||||||||||||||||||||||¶¶  PACKAGE¬DTT_IO IS¬NEW SEQUENTIAL_IO (¬DIANA_TABLE_TYPE );¶  USE DTT
_IO;¶¶--|||||||||||||||||||||||||||||||||||||||||||||||||||||||||||||||||||||||||||||||||||||||||||||||||||||||||||||¶--|¬¬PROCEDURE¬WRITE_SPEC¶--|¶PROCEDURE¬WRI
TE_SPEC ( SPEC_FILE :STRING ) IS¶  SFILE¬¬: DTT_IO.FILE_TYPE;¶BEGIN¶  DTT_IO.CREATE( SFILE, OUT_FILE, SPEC_FILE & ".bin" );¶  DTT_IO.WRITE ( SFILE, DI
ANA_TABLE_AREA );¶  DTT_IO.CLOSE ( SFILE );¶END;¶--|||||||||||||||||||||||||||||||||||||||||||||||||||||||||||||||||||||||||||||||||||||||||||||||||||||||||||||¶
--|¬¬PROCEDURE¬READ_SPEC¶--|¶PROCEDURE¬READ_SPEC¬( SPEC_FILE :STRING¬) IS¶  SFILE¬¬: DTT_IO.FILE_TYPE;¶BEGIN¶  DTT_IO.OPEN ( SFILE, IN_FILE, SPEC_FILE
 & ".bin" );¶  DTT_IO.READ ( SFILE, DIANA_TABLE_AREA¬);¶  DTT_IO.CLOSE( SFILE );¶END;¶--||||||||||||||||||||||||||||||||||||||||||||||||||||||||||||||||||||||||||
||||||||||||||||||||||||||||||||||||||¶¶¬-------¶END¬IDL_TBL;¶¬-------¶¶--¬1¬2¬3¬4¬5¬6¬7¬8¬9¬A¬B¬C¶--------------------------------------------------------
-------------------------------------------------------------------¶
```