```
0000 SEPARATE (IDL)¶--|-----------------------------------------------------------------------------------------------------¶--|¬¬PROCEDURE¬NAM_PUT¶--|¶PROCEDU
     RE¬NAM_PUT (¬NOM_TEXTE¬:STRING )¬IS¬¬¬¬¬¬--| ECRIT¬DES PARTIES ADA POUR UN NOUVEL ENVIRONNEMENT IDL¶¶  RESULT_FILE¬: TEXT_IO.FILE_TYPE;¶¶  ASSERTION_E
     RROR¬: EXCEPTION;¶¶  --|-----------------------------------------------------------------------------------------------¶  --|¬¬PACKAGE TBL¶  --|------
     ---------------------------------------------------------------------------------¶  PACKAGE¬TBL IS¶¶    TYPE AC_STRING¬¬IS ACCESS¬STRING;¶¶
      TYPE NODE_IDX¬¬IS RANGE 0 .. 255;¬¬¬¬¬¬¬--| INDICE DES NOEUDS¶    TYPE ATTR_IDX¬¬IS RANGE 0 .. 255;¬¬¬¬¬¬¬--| INDICE DES ATTRIBUTS¶    TYPE CLASS_IDX¬¬
     IS RANGE 0 .. 150;¬¬¬¬¬¬¬--| INDICE DES CLASSES¶    TYPE FIELD_IDX¬¬IS RANGE 0 .. 1500;¬¬¬¬¬¬¬--| INDICE DES CHAMPS (CITATION D'UN ATTRIBUT DANS UN NOEU
     D)¶¶    LAST_NODE¬¬: NODE_IDX¬¬:= 0;¶    LAST_ATTR¬¬: ATTR_IDX¬¬:= 0;¶    LAST_CLASS¬¬: CLASS_IDX¬¬:= 0;¶¶    NODE_IMAGE¬¬: ARRAY( NODE_IDX )¬OF AC_ST
     RING;¶    START_FIELD¬¬: ARRAY( NODE_IDX )¬OF FIELD_IDX;¶    END_FIELD¬¬: ARRAY( NODE_IDX )¬OF FIELD_IDX;¶¶    ATTR_IMAGE¬¬: ARRAY( ATTR_IDX )¬OF AC_S
     TRING;¬¬¬¬--| NOMS DES ATTRIBUTS¶    ATTR_KIND¬¬: ARRAY( ATTR_IDX )¬OF CHARACTER;¬¬¬¬--| 'A' 'B' 'I' ATTRIBUT TREE, BOOLEAN,¬INTEGER OR SEQUENCE¶¶
     CLASS_IMAGE¬¬: ARRAY( CLASS_IDX ) OF AC_STRING;¬¬¬¬--| NOM DES CLASSES¶    START_NODE¬¬: ARRAY( CLASS_IDX ) OF NODE_IDX;¬¬¬¬--| PREMIER NOEUD DE CLASS
0010 E¶    END_NODE¬¬: ARRAY( CLASS_IDX ) OF NODE_IDX;¬¬¬¬--| DERNIER NOEUD DE CLASSE¶¶    ATTR_IDX_OF_NODE¬: ARRAY( FIELD_IDX ) OF ATTR_IDX;¶¶¶    FUNCTIO
     N  UPPER_CASE¬( A :STRING )¬¬RETURN STRING;¶    FUNCTION  LOWER_CASE¬( A :STRING )¬¬RETURN STRING;¶    PROCEDURE READ_TABLES¬( NOM_TABLE :STRING¬);¶¶
        --|-----------------------------------------------------------------------------------------------¶  END TBL;¶¶  USE TBL;¶  PACKAGE¬BODY TBL IS SEPAR
     ATE;¶¶¶  --|-----------------------------------------------------------------------------------------------¶  --|¬¬PROCEDURE¬PUT_NODES_NAMES¶  --|¶  P
     ROCEDURE PUT_NODES_NAMES IS¶    I¬¬: NATURAL¬¬:= 0;¶  BEGIN¶    PUT_LINE( "  type NODE_NAME" & ASCII.HT & "is (" );¶    FOR N¬IN 0 .. TBL.LAST_NODE LO
     OP¶      IF I > 4 THEN¶        NEW_LINE;¶        I¬:= 0;¶      END¬IF;¶      DECLARE¶        STR¬: STRING RENAMES TBL.NODE_IMAGE( N ).ALL;¶      BEGIN
     ¶      PUT( ASCII.HT & "DN_"¬& UPPER_CASE( STR )¬& "," );¶        IF STR'LENGTH+3 > 18 THEN¶¬I := I + 1;¶        END IF;¶      END;¶      I := I + 1
     ;¶    END LOOP;¶¶    NEW_LINE;¶    PUT_LINE( ASCII.HT & "DN_VIRGIN" );¶    PUT_LINE( ASCII.HT & ");"¬);¶    PUT_LINE( RESULT_FILE, ASCII.HT & "for NOD
     E_NAME'SIZE use 8;" );¶    NEW_LINE;¶  END PUT_NODES_NAMES;¶  --|-----------------------------------------------------------------------------------------------
     ----------¶  --|¬¬PROCEDURE¬PUT_ATTRIBUTES_NAMES¶  --|¶  PROCEDURE PUT_ATTRIBUTES_NAMES IS¶    I¬¬: NATURAL¬¬:= 0;¶  BEGIN¶    PUT_LINE( "  type ATTRI
0020 BUTE_NAME" &¬ASCII.HT & "is (" );¶    FOR A¬IN 0 .. TBL.LAST_ATTR-1 LOOP¶      IF I > 4 THEN¶        NEW_LINE;¶        I¬:= 0;¶      END¬IF;¶      DEC
     LARE¶        STR¬¬: STRING RENAMES TBL.ATTR_IMAGE( A ).ALL;¶      BEGIN¶        PUT( ASCII.HT & UPPER_CASE( STR( STR'FIRST .. STR'LAST ) ) & "," );¶
        IF STR'LENGTH > 18 THEN¶¬I := I + 1;¶        END IF;¶      END;¶      I := I + 1;¶    END LOOP;¶¶    IF TBL.LAST_ATTR MOD 5 = 0 THEN¶      NEW_L
     INE;¶    END IF;¶    DECLARE¶      STR¬¬: STRING RENAMES TBL.ATTR_IMAGE(  TBL.LAST_ATTR ).ALL;¶    BEGIN¶      PUT( ASCII.HT¬& UPPER_CASE( STR( STR'FI
     RST .. STR'LAST ) ) );¶    END;¶    NEW_LINE;¶    PUT_LINE( ASCII.HT & ");"¬);¶    NEW_LINE;¶  END PUT_ATTRIBUTES_NAMES;¶  --|------------------------
     ------------------------------------------------------------------------¶  --|¬¬PROCEDURE¬PUT_CLASSES¶  --|¶  PROCEDURE PUT_CLASSES IS¶  BEGIN¶    FOR
     C¬IN 0 .. TBL.LAST_CLASS LOOP¶      PUT_LINE( "  subtype CLASS_" & UPPER_CASE( CLASS_IMAGE( C ).ALL¬)¶¬       & ASCII.HT &¬"is NODE_NAME RANGE DN_" &
     UPPER_CASE( TBL.NODE_IMAGE( START_NODE( C ) ).ALL )¶¬       & ASCII.HT &¬".. DN_" & UPPER_CASE( TBL.NODE_IMAGE( END_NODE( C ) ).ALL )¶¬       & ';'¶¬
         );¶    END LOOP;¶    NEW_LINE;¶  END;¶¶¶BEGIN¶  TBL.READ_TABLES( NOM_TEXTE );¶¶  CREATE(¬RESULT_FILE, OUT_FILE, LOWER_CASE( NOM_TEXTE ) & "_node_a
     ttr_class_names.ads" );¶  SET_OUTPUT( RESULT_FILE );¶¶  PUT_LINE( RESULT_FILE, "--|-----------------------------------------------------------------------------
0030 ------------------------------");¶  PUT_LINE( RESULT_FILE, "--|" & ASCII.HT & NOM_TEXTE & "_NODE_ATTR_CLASS_NAMES");¶  PUT_LINE( RESULT_FILE, "--|----
     ---------------------------------------------------------------------------------");¶  PUT_LINE( "package " & NOM_TEXTE & "_NODE_ATTR_CLAS
     S_NAMES is");¶  NEW_LINE( RESULT_FILE );¶  PUT_NODES_NAMES;¶  PUT_ATTRIBUTES_NAMES;¶  PUT_CLASSES;¶  NEW_LINE( RESULT_FILE );¶  PUT_LINE( RESULT_FILE,
      "--|-----------------------------------------------------------------------------------------------");¶  PUT_LINE( RESULT_FILE, "end " & NOM_TEXTE
     & "_NODE_ATTR_CLASS_NAMES;");¶¶  SET_OUTPUT( STANDARD_OUTPUT¬);¶  CLOSE( RESULT_FILE );¶¶--|-----------------------------------------------------------------
     ---------------------------------¶END NAM_PUT;¶
```