

```
0000 SEPARATE (IDL.PAR_PHASE)
--REEMPLISSAGE INITIAL-PAR DEFALT DES NOEUDS
-----
PROCEDURE SET_DFLT (
  NODE : TREE ) IS
BEGIN
CASE NODE.TY IS
  WHEN DN_VARIABLE_ID =>
    D ( SM_INIT_EXP, NODE, TREE_VOID );
    DB ( SM_RENAMES_OBJ,
  NODE, FALSE );
    D ( SM_ADDRESS, NODE, TREE_VOID );
    DB ( SM_IS_SHARED, NODE, FALSE );
    WHEN DN_CONSTANT_ID =>
      D ( SM_INIT_EXP, NODE, TREE_VOID );
    DB ( SM_RENAMES_OBJ, NODE, FALSE );
    D ( SM_ADDRESS, NODE, TREE_VOID );
    D ( SM_FIRST, NODE, NODE );
    WHEN DN_COMP
  ONENT_ID =>
      D ( SM_INIT_EXP, NODE, TREE_VOID );
      D ( SM_COMP_REP, NODE, TREE_VOID );
      D ( SM_FIRST, NODE, NODE );
      WHEN DN_DISCRIMINANT_ID =>
        D ( SM_INIT_EXP, NODE, TREE_VOID );
        D ( SM_FIRST, NODE, NODE );
        WHEN DN_CLASS_PARAM_NAME =>
          D ( SM_INIT_EXP, NODE, TREE_VOID );
          D ( SM_FIRST, NODE, NODE );
          WHEN DN_PROCEDURE_ID | DN_FUNCTION_ID =>
            D ( SM_INIT_EXP, NODE, TREE_VOID );
            D ( SM_FIRST, NODE, NODE );
            D ( SM_ADDRESS, NODE, TREE_VOID );
            D ( XD_STUB, NODE, TREE_VOID );
            D ( XD_BODY, NODE, TREE_VOID );
            DB ( SM_IS_INLINE, NODE, FALSE );
            D ( SM_INTERFACE, NODE, TREE_VOID );
            WHEN DN_OPERATOR_ID =>
              D ( SM_FIRST, NODE, TREE_VOID );
              DB ( SM_IS_INLINE, NODE, FALSE );
              D ( SM_INTERFACE, NODE, TREE_VOID );
              D ( XD_NOT_EQUAL, NODE, TREE_VOID );
              WHEN DN_PACKAGE_ID =>
                D ( SM_FIRST, NODE, TREE_VOID );
                D ( SM_ADDRESS, NODE, TREE_VOID );
                D ( XD_STUB, NODE, TREE_VOID );
                D ( XD_BODY, NODE, TREE_VOID );
                WHEN DN_EXCEPTION_ID =>
                  D ( SM_FIRST, NODE, TREE_VOID );
                  D ( XD_STUB, NODE, TREE_VOID );
                  D ( XD_BODY, NODE, TREE_VOID );
                  D ( SM_BODY_ID =>
                    D ( SM_RENAMES_EXC, NODE, TREE_VOID );
                    WHEN DN_PACKAGE_SPEC =>
                      DB ( XD_BODY_IS_REQUIRED, NODE, FALSE );
                      WHEN DN_DERIVED_DEF =>
                        LIST ( NODE, TREE_NIL, TREE_NIL );
                        WHEN DN_EXIT =>
                          D ( SM_STM, NODE, TREE_VOID );
                          WHEN CLASS_USED_OBJECT =>
                            D ( SM_VALUE, NODE, TREE_VOID );
                            WHEN DN_ATTRIBUTE | DN_SELECTED =>
                              D ( SM_VALUE, NODE, TREE_VOID );
                              WHEN DN_FUNCTION_CALL =>
                                D ( SM_VALUE, NODE, TREE_VOID );
                                WHEN DN_COMPILATION_UNIT =>
                                  D ( XD_PARENT, NODE, TREE_VOID );
                                  WHEN OTHERS =>
                                    NULL;
                                END CASE;
                                END SET_DFLT;
0020
```