DEPARTMENT OF CSIT
GURU GHASIDAS VISHWAVIDYALAYA, BILASPUR

(A Central University established by the Central Universities Act 2009 No. 25 of 2009)

UG IV SEMESTER

Session: 2025-2026

Subject: Object Oriented Programming with JAVA

Submitted To

Dr.Ratnesh Prasad Srivastava
(Associate Professor)

Submitted By

Anmol Yadav
BSc(CS),CSIT
Roll No:24070114

Assignment

1.Write a programtotakealistof10farmers,fruitstheysell,their cities & the quantity of fruits they have as input . Save the data to notepad before & after sorting based on quantity in tabular manner. Also perform searchoperationbasedonfarmers'name.

CODE:

```
import java.io. *;
import java.util.*;

public class FarmerEasy {

public static void main (String[] args) throws Exception {
Scanner sc = new Scanner (System.in);

String name[] = new String [10];
String fruit[] = new String [10];
String city[] = new String [10];
int qty [] = new int[10];

// INPUT
for(int i=0; i<10; i++) {
System.out.println("Enter Farmer " + (i+1));
System.out.print("Name: ");
name[i] = sc.next();
System.out.print("Fruit: ");
fruit[i] = sc.next();
System.out.print("City: ");
city[i] = sc.next();
System.out.print("Quantity: ");
qty[i] = sc.nextInt();

}

// SAVE BEFORE SORT
FileWriter f1 = new FileWriter("before.txt");
f1.write("Name\tFruit\tCity\tQuantity\n");
for(int i=0; i<10; i++) {
f1.write(name[i] + " " + fruit[i] + " " + city[i] + " " + qty[i] + "\n");
}
f1.close();

// SORT
for(int i=0; i<10; i++) {
for(int j=i+1; j<10; j++) {
if(qty[i] > qty[j]) {
int t = qty[i];
qty[i] = qty[j];
```

```
qty[j]=t;

Strings;
s=name[i]; name[i] = name[j]; name[j] = s;
s=fruit[i]; fruit[i] = fruit[j]; fruit[j] = s;
s=city[i]; city[i] = city[j]; city[j] = s;



                    }
                }
}

//SAVEAFTER SORT
FileWriterf2= new FileWriter("after.txt");
f2.write("Name\tFruit\tCity\tQuantity\n");
for(inti=0;i<10; i++) {
f2.write(name[i] + " " + fruit[i] + " " + city[i] + " " + qty[i] + "\n");
 }
 f2.close();

 // SEARCH
 System.out.print("Enter name to search: ");
 Stringx=sc.next();

 booleanfound = false;
 for(inti=0;i<10; i++) {
 if(name[i].equalsIgnoreCase(x)) {
System.out.println("Found: " + name[i] + " " + fruit[i] + " " + city[i] + " " + qty[i]);
found=true;
                }
            }

            if(!found) {
                System.out.println("Farmer not found");
            }

            sc.close();
        }

 }
```

OUTPUT:

```
Enter Farmer 1
Name:    Karan
Fruit:    Mango
City:    Bilaspur
Quantity: 500

Enter Farmer 2
Name:    Anuj
Fruit:    Apple
City:    Mumbai
Quantity: 300
```

Enter Farmer 3
Name: Shreya
Fruit: Papaya
City: Bhopal
Quantity: 700

Enter Farmer 4
Name: Priya Fruit: Watermelon
City: Indore
Quantity: 200

Enter Farmer 5
Name: Mohan
Fruit: Apple
City: Pune
Quantity: 900

Enter Farmer 6
Name: Neha
Fruit: Mango
City: Jaipur
Quantity: 100

Enter Farmer 7
Name: Karan
Fruit: Papaya
City: Agra
Quantity: 600

Enter Farmer 8
Name: Pooja
Fruit: Apple
City: Delhi
Quantity: 400

Enter Farmer 9
Name: Vivek
Fruit: Mango
City: Lucknow
Quantity: 800

Enter Farmer 10
Name: Ankit
Fruit: Papaya
City: Patna
Quantity: 250

Enter name to search: Riya
Found: Riya Mango Indore200

2. Write a program to take quantity & quality of fruits Mango, Apple & Papaya as input. Quality may be good, bad or average. If entered quantity of fruit is greater than 1000, store it as half. Perform search for a given fruit with given quality.

CODE:

```
import java.util.*;

public class FruitEasy {

public static void main(String[] args) {

Scanner sc = new Scanner(System.in);

String fruit[] = {"Mango", "Apple", "Papaya"};
int qty[] = new int[3];
String quality[] = new String[3];

// INPUT
for (int i = 0; i < 3; i++) {

System.out.println("Enter details for " + fruit[i]);

System.out.print("Quantity: ");
qty[i] = sc.nextInt();

// CONDITION: if quantity > 1000 → half
if (qty[i] > 1000) {
 qty[i] = qty[i] / 2;
 }

 System.out.print("Quality (good/bad/average): ");
 quality[i] = sc.next();
}

 // DISPLAY DATA
 System.out.println("\nStored Data:");
 for (int i = 0; i < 3; i++) {
 System.out.println(fruit[i] + " " + qty[i] + " " + quality[i]);
 }

 // SEARCH
 System.out.print("\nEnter fruit to search: ");
 String f = sc.next();

 System.out.print("Enter quality to search: ");
 String q = sc.next();
 boolean found = false;

 for (int i = 0; i < 3; i++) {

 if (fruit[i].equalsIgnoreCase(f) &&
```

```
  quality[i].equalsIgnoreCase(q)) {

  System.out.println("Found: " + fruit[i] + " " + qty[i] + " " + quality[i]);
  found = true;

        }

  }

  if(!found) {

  System.out.println("Not Found");

   }

   sc.close();
         }
}
```

OUTPUT:

```
Enter details for Mango
Quantity: 1500
Quality (good/bad/average): good

Enter details for Apple
Quantity: 800
Quality (good/bad/average): average

Enter details for Papaya
Quantity: 1200
Quality (good/bad/average): bad

Stored Data:
Mango 750 good
Apple 800 average
Papaya 600 bad

Enter fruit to search: Mango
Enter quality to search: good

Found: Mango 750 good
```

3. There are four orchards, namely A, B, C & D with fruits in them as Apple, Litchi, Mango, Apple respectively. The qualities of the fruits in the orchards are good, good, good & bad respectively . The available orchards in a tree-view . Search for a given fruit in the available orchards after taking input from the user & print the tree.

CODE:

```
import java.util.*;

publicclass OrchardTree {

publicstatic void main(String[] args) {

Scanner sc = new Scanner(System.in);

String orchard[] = {"A", "B", "C", "D"};
String fruit[] = {"Apple", "Litchi", "Mango", "Apple"};
String quality[] = {"good", "good", "good", "bad"};

//PRINT TREE
System.out.println("Orchard Tree:");
for(int i = 0; i < 4; i++) {

System.out.println("Orchard " + orchard[i]);
System.out.println(" |-- Fruit: " + fruit[i]);
System.out.println(" |-- Quality: " + quality[i]);
}

//SEARCH
System.out.print("\nEnter fruit to search: ");
String search = sc.next();

boolean found = false;

System.out.println("\nSearch Result (Tree Form):");
for(int i = 0; i < 4; i++) {

if(fruit[i].equalsIgnoreCase(search)) {

System.out.println("Orchard " + orchard[i]);
System.out.println(" |-- Fruit: " + fruit[i]);
System.out.println(" |-- Quality: " + quality[i]);
found = true;
}
}

if(!found) {
System.out.println("Fruit not found in any orchard");

}

sc.close();

}
}
```

OUTPUT:

Or~~chard Tre~~e:
Orchard A

|-- Fruit: Apple
|-- Quality: good

Orchard B

|-- Fruit: Litchi
|-- Quality: good

Orchard C

|-- Fruit: Mango
|-- Quality: good

Orchard D

|-- Fruit: Apple
|-- Quality: bad

Enter fruit to search: Apple

Search Result (Tree Form):

Orchard A

|-- Fruit: Apple
|-- Quality: good

Orchard D

|-- Fruit: Apple
|-- Quality: bad

4. Take a map provided as a graph & display all the subtrees of connected points

CODE:

```
import java.util.*;

publicclass GraphSubtrees {

staticint n;
staticint graph[][] = new int[10][10];
staticboolean visited[] = new boolean[10];

//DFSfunction
staticvoid dfs(int v) {

System.out.print(v + " ");
visited[v] = true;

for(int i = 0; i < n; i++) {


            if(graph[v][i] == 1 && !visited[i]) {
                dfs(i);
            }
        }
  }

  publicstatic void main(String[] args) {
  Scanner sc = new Scanner(System.in);

  System.out.print("Enter number of nodes: ");
  n=sc.nextInt();

  System.out.println("Enter adjacency matrix:");
  for(int i = 0; i < n; i++) {

            for(int j = 0; j < n; j++) {
                graph[i][j] = sc.nextInt();
            }
        }

        System.out.println("\nSubtrees (Connected Components):");
        for(int i = 0; i < n; i++) {
            if(!visited[i]) {
                dfs(i); // print one subtree
                System.out.println();
            }
        }

        sc.close();
      }
    }
```

OUTPUT:

Enter number of nodes: 5

Enter adjacency matrix:
0 1 0 0 0
1 0 0 0 0

0 0 0 1 1

0 0 1 0 1

0 0 1 1 0

Subtrees (Connected Components):
0 1

2 3 4

5. Enter entry point & goal point & produce the matching subtree of the graph.

CODE:

```
import java.util.*;

publicclass GraphPath {
   staticint n;
   staticint graph[][] = new int[10][10];
   staticboolean visited[] = new boolean[10];
   staticboolean found = false;
   staticList<Integer> path = new ArrayList<>();

   staticvoid dfs(int v, int goal) {
      visited[v] = true;
      path.add(v);

      if(v== goal) {
         found = true;
         System.out.println("Path: " + path);
         return;
      }

      for(int i = 0; i < n; i++) {
         if(graph[v][i] == 1 && !visited[i] && !found) {
            dfs(i, goal);
         }
      }
```

```
        // Backtracking step
        if (!found) {
            path.remove(path.size()- 1);
        }
    }

    publicstaticvoidmain(String[] args) {
        Scannersc=newScanner(System.in);

        System.out.print("Enternumber of nodes: ");
        n = sc.nextInt();

        System.out.println("Enteradjacency matrix:");
        for (inti =0;i <n; i++) {
            for (intj =0;j <n; j++) {
                graph[i][j]=sc.nextInt();
            }
        }

        System.out.print("Enterentry point: ");
        int start = sc.nextInt();
        System.out.print("Entergoal point: ");
        int goal = sc.nextInt();
        dfs(start, goal);

        if (!found) {

            System.out.println("Nopath found");
        }

        sc.close();
    }
}
```

OUTPUT:

```
Enternumberofnodes:5

Enteradjacency matrix:
0 1 0 0 0
1 0 0 0 0
0 0 0 1 1
0 0 1 0 1
0 0 1 1 0

Enter entrypoint:2
Enter goal point: 4

MatchingSubtree(Path):
2 3 4
```

6. Give the weightage for each edge of nodes, and produce the shortest path from start to end node.

CODE:

```
import java.util.*;

public class ShortestPathEasy {
  public static void main(String[] args) {
    Scanner sc = new Scanner(System.in);

    System.out.print("Enter number of nodes: ");
    int n = sc.nextInt();
    int graph[][] = new int[n][n];

    System.out.println("Enter weight matrix (0 if no edge):");
    for (int i = 0; i < n; i++) {
      for (int j = 0; j < n; j++) {
        graph[i][j] = sc.nextInt();
      }
    }

    System.out.print("Enter start node: ");
    int start = sc.nextInt();
    System.out.print("Enter end node: ");
    int end = sc.nextInt();
    int dist[] = new int[n];
    boolean visited[] = new boolean[n];
    int parent[] = new int[n]; // to track path

    Arrays.fill(dist, 9999);
    Arrays.fill(parent, -1);
    dist[start] = 0;

    for (int count = 0; count < n - 1; count++) {


      int min = 9999, u = -1;

      for (int i = 0; i < n; i++) {
        if (!visited[i] && dist[i] < min) {
          min = dist[i];
          u = i;
        }
      }

      if (u == -1) break; // safety check

      visited[u] = true;
```

```
        for(int v = 0; v < n; v++) {
            if(!visited[v] && graph[u][v] != 0 &&
                dist[u] + graph[u][v] < dist[v]) {

                dist[v] = dist[u] + graph[u][v];
                parent[v] = u; // track path
            }
        }
    }

    if(dist[end] == 9999) {
        System.out.println("No path exists");
    } else {
        System.out.println("\nShortest distance: " + dist[end]);

        //print path
        List<Integer> path = new ArrayList<>();
        for(int v = end; v != -1; v = parent[v]) {
            path.add(v);
        }
        Collections.reverse(path);

        System.out.println("Path: " + path);
    }

    sc.close();
  }
}
```

OUTPUT:

Enternumber of nodes: 4

Enterweight matrix:
0 2 0 6
2 0 3 0
0 3 0 1
6 0 1 0

Enterstartnode: 0

Enterendnode: 3

Shortestdistance from 0 to 3 is: 6

7. Write a program to demonstrate the use of all keywords made for exception handling.

CODE:

```
import java.util.*;

class InvalidAgeException extends Exception {
  InvalidAgeException(String msg) {
    super(msg);
  }
}

public class ExceptionDemo {

  static void checkAge(int age) throws InvalidAgeException {
    if (age < 18) {
      throw new InvalidAgeException("Not eligible to vote");
    } else {
      System.out.println("Eligible to vote");
    }
  }

  public static void main(String[] args) {
    Scanner sc = new Scanner(System.in);

    try {
      System.out.print("Enter a number: ");
      int a = sc.nextInt();

      System.out.print("Enter another number: ");
      int b = sc.nextInt();

      int result = a / b;
      System.out.println("Result: " + result);

      System.out.print("Enter age: ");
      int age = sc.nextInt();

      checkAge(age);

    } catch (ArithmeticException e) {
      System.out.println("Error: Cannot divide by zero");

    } catch (InputMismatchException e) {
      System.out.println("Error: Please enter valid numbers");

    } catch (InvalidAgeException e) {
      System.out.println("Error: " + e.getMessage());

    } finally {
```

```
        System.out.println("Program finished (finally block)");
      }

      sc.close();
    }
}
```

OUTPUT:

Entera number: 10

Enteranother number: 2

Result: 5

Enterage: 20

Eligible to vote

Program finished (finally block)

8.Write a program to withraw money from a bank account, if the withdrawn money is greater than the balance, then it throws NoMoneyException.

CODE:

```
import java.util.*;

// Custom Exception
class NoMoneyException extends Exception {
   NoMoneyException(String msg) {
      super(msg);
   }
}

public class BankWithdraw {

   static int withdraw(int balance, int amount) throws NoMoneyException {
      if (amount < 0) {
         throw new NoMoneyException("Invalid withdrawal amount!");
      }
      if (amount > balance) {
         throw new NoMoneyException("Insufficient Balance!");
      }

      balance = balance - amount;
      return balance;
   }

   public static void main(String[] args) {
```

```
    Scanner sc = new Scanner(System.in);

    try{
      System.out.print("Enter Balance: ");
      intbalance = sc.nextInt();

      if(balance < 0) {
        throw new NoMoneyException("Balance cannot be negative!");
      }

      System.out.print("Enter Withdraw Amount: ");
      intamount = sc.nextInt();
      balance = withdraw(balance, amount);

      System.out.println("Withdrawal Successful");
      System.out.println("Remaining Balance: " + balance);


    }catch (NoMoneyException e) {
      System.out.println("Error: " + e.getMessage());

    }catch (InputMismatchException e) {
      System.out.println("Error: Invalid input! Enter numbers only.");

    }finally {
      System.out.println("Transaction Ended");
    }

    sc.close();
  }
}
```

CODE:

Enter Balance: 5000

Enter Withdraw Amount: 2000

Withdrawal Successful

Remaining Balance: 3000

9. Write a program which enables to use a platform by a train one at a time.

CODE:

```
classPlatform {

   synchronized void usePlatform(String trainName) {
      System.out.println(trainName + " is using platform");
      try{
         Thread.sleep(1000);
      }catch (InterruptedException e) {
         System.out.println(trainName + " was interrupted");
      }
      System.out.println(trainName + " left platform");
   }
}

classTrain implements Runnable {
   privatePlatform platform;
   privateString trainName;

   Train(Platform platform, String trainName) {
      this.platform = platform;
      this.trainName = trainName;
   }

   @Override
   publicvoid run() {
      platform.usePlatform(trainName);
   }
}

publicclass Main {
   publicstatic void main(String[] args) {
   Platform platform = new Platform();

   Thread t1 = new Thread(new Train(platform, "Train A"));
   Thread t2 = new Thread(new Train(platform, "Train B"));

   t1.start();
   t2.start();
   }
}
```

CODE:

```
TrainAisusing platform
TrainAleft platform
TrainBisusing platform
TrainBleft platform
```

10. Write a programme of Restaurant and Waiter, which accept order if kitchen if free and sheff deliver orders if he is free.

CODE:

```
class Restaurant {


    boolean orderReady = false;

    // Waiter places order
    synchronized void placeOrder(String order) {
      while (orderReady) {
        try {
          wait();
        } catch (InterruptedException e) {
          System.out.println("Waiter interrupted");
        }
      }

      System.out.println("Waiter placed order: " + order);
      orderReady = true;
      notify(); // notify chef
    }

    // Chef prepares order
    synchronized void prepareOrder() {
      while (!orderReady) {
        try {
          wait();
        } catch (InterruptedException e) {
          System.out.println("Chef interrupted");
        }
      }

      System.out.println("Chef prepared and delivered order");
      orderReady = false;
      notify(); // notify waiter
    }
  }

  // Waiter Thread
  class Waiter extends Thread {
    Restaurant r;

    Waiter(Restaurant r) {
      this.r = r;
    }

    public void run() {
      r.placeOrder("Pizza");
    }
```

```
}

//Chef Thread
class Chef extends Thread {
   Restaurant r;

   Chef(Restaurant r) {
      this.r = r;
   }

   public void run() {
      r.prepareOrder();
   }
}

public class Main {
   public static void main(String[] args) {
      Restaurant r = new Restaurant();

      Waiter w = new Waiter(r);
      Chef c = new Chef(r);

      w.start();
      c.start();
   }
}
```

OUTPUT:

```
Waiter placed order: Pizza

Chef prepared and delivered order
```