DUNEWRIGHT COLONY WORKS
Settlement Site 4 · Construction Division · Health & Safety

POCKET CARD.

EVERYTHING FROM THE REFRESHER ON ONE FOLD-OUT CARD. FILL IT IN, KEEP IT IN YOUR CHEST POCKET.

THE CARD

FOLD ON THE DASHED LINES

PANEL 1 · FRONT

DCW SITE 4

NAME

COLONIST ID

TRADE / STATION

SECTOR / CREW / CALL SIGN

BLOOD TYPE · ALLERGIES

MY MUSTER POINT · NEAREST SHELTER

HEAT RAMP (TICK EACH DAY DONE)

D1 20%	D2 40%	D3 60%	D4 80%	D5 100%
☐	☐	☐	☐	☐

EMERGENCY: CH 1

PANEL 2 · EMERGENCY

EMERGENCY CALL · CH 1

"**Emergency, emergency, emergency.**"
Type · Location · Number hurt · Hazards · Your call sign.

`e.g. "Man down, Charlie-14, Deck 3, one hurt, live power. Charlie Crew 14-3."`

ALL STOP

Hear "ALL STOP" on any channel or 3 short blasts: stop all motion, hot work and lifts. Wait for the all-clear.

SIREN	MEANS
Long steady	Take shelter
High-low	Evacuate to muster
3 short	All stop
1 long after	All clear

HEAT STROKE

Confused or collapsed and hot. **Cool first, transport second.** Ice trough to the neck, or soak and ice them. No drinks if confused.

START TRIAGE

GREEN WALKS · YELLOW DELAYED · RED NOW · BLACK EXPECTANT

Bleeding: press hard. Tourniquet 2–3 in above the wound, not on a joint. Write the time. **CPR:** 100–120 a minute, 2+ in deep, get the AED.

PANEL 3 · RADIO & HATS

CH	USE
1	**Site Emergency. Always monitor.**
2	Site Command (Hub)
3–10	Sectors: A3 B4 C5 D6 E7 F8 G9 H10
11	Crane & Lift
12	Heavy Equipment
13	Hot Work & Fire Watch
14	Medical
15	Logistics / Quartermaster
16	Atmospheric / Weather

Location: **sector-grid, deck**. "Charlie-14, Deck 3." Check in with your crew lead every 30 min.

HARD HATS

- Supervision
- Crew, operators
- Rigging, signals
- Electrical
- Welding, hot work
- Safety
- Fire, rescue
- Survey, QA/QC

Orange **RAMP** sticker = revived in the last 5 days. Watch out for them.

PANEL 4 · NUMBERS THAT KEEP YOU ALIVE

8 oz	Water every 15–20 min. Max 48 oz/hr.
90 WBGT	Black flag. Heavy work 10 on / 50 off.
125°F+	Cooling vest, pairs, 30 min max.
160°F+	Site closed. Shelter.
6 ft	Fall protection required.
5,000 lb	Anchor strength per worker.
4 : 1	Ladder angle. 3 ft above landing.
5 ft	Trench needs slope, shoring or shield.
35 ft	Clear combustibles from hot work.
60 min	Fire watch after hot work (site rule).
20 ft	Crane clearance from power up to 350 kV.
19.5–23.5%	Safe oxygen. Test before entry.
15 min	Flush eyes or skin after a chemical splash.
85 dBA	Hearing protection. Shouting at arm's length? Plug up.

Stop-work authority: anyone can stop unsafe work. No penalty.

Lockout: one person, one lock, one key.

Your entries save in this browser only. Fill in name and colonist ID once and every module's sign-off picks them up.

HOW TO CARRY IT

- Print it, or use the PDF, and fold it into four along the dashed lines with Panel 1 on the outside.
- Keep it in a chest pocket, not your pants. Responders check the chest.
- Update your sector, crew and muster point every time you're reassigned.
- Lost card? The Quartermaster issues a new one on Ch 15.

WHERE IT COMES FROM

Every line on this card comes from a refresher module. If something on the card doesn't make sense, go back to that module: see the full list.

Adapted from Old Earth standards: OSHA 1926 (falls, excavation, cranes, hot work), OSHA/NIOSH heat and noise guidance, US Army TB MED 507, START triage, AHA CPR, Stop the Bleed, ANSI Z358.1.