FORM REF-PC · REV. 5   POST-STASIS REFRESHER · REFERENCE SHEET   CARRY ON YOUR PERSON AT ALL TIMES

DUNEWRIGHT COLONY WORKS
Settlement Site 4 · Construction Division · Safety & Health

POCKET CARD.

THE REFRESHER'S LIFE-SAVING RULES ON ONE FOLD-OUT CARD. FILL IT IN, KEEP IT IN YOUR CHEST POCKET.

THE CARD

FOLD ON THE DASHED LINES

PANEL 1 · FRONT

DCW SITE 4

NAME

COLONIST ID

TRADE / STATION

SECTOR / CREW / CALL SIGN

FOREMAN TALKGROUP · BUDDY

BLOOD TYPE · ALLERGIES

MY MUSTER POINT (MP-) · NEAREST SHELTER

EMERGENCY: CH 1

SCAN CH 1 + CH 16 + YOUR SECTOR

HEAT RAMP (TICK EACH DAY DONE)

D1	D2	D3	D4	D5
20%	40%	60%	80%	100%
☐	☐	☐	☐	☐

% = most of the shift in the heat. **Days 1–4: also half the table's work minutes (“No limit” = 30/30). Day 1: light work only.** Days 6–14: crew lead checks you every 15 min at WBGT 85+. **Reset to Day 1** after fever, vomiting or diarrhea, any heat illness, or 7+ days away from heat work.

▨ **RAMP band** (black-and-yellow, reads RAMP) on your helmet from Day 1. Off only when your crew lead logs Day 5.

HEAT STROKE

Collapsed or not fully alert on a hot site = heat stroke until a medic says otherwise. **Ch 1 "Heat casualty".** Cool first (ice trough to the neck), transport second. No drinks if confused.

Heat exhaustion: pull off, cool, sips of water. Someone walks them to the Forward Aid Station (FAS) now, never alone.

PANEL 2 · EMERGENCY

EMERGENCY CALL · CH 1

"Emergency, emergency, emergency."
Type · Location · Number hurt · Hazards · Your call sign.

`e.g. "Emergency, emergency, emergency. Man down. Charlie-14, Tower B, Deck 3, east stair. One hurt. Falling debris. Charlie Crew 14-3 Seven."`

Then stay on Ch 1 until Hub Command or the medic releases you. Everyone else stays off Ch 1.

Types: Heat casualty · Man down · Fall · Fire · Gas · Chemical · Structural · Struck-by · Caught-in · Electrical · Confined space · Flood · Sandstorm.

ALL STOP

"ALL STOP, ALL STOP" on any channel, or 3 short blasts: stop all motion, hot work and machines. Hold position. A suspended load lands only on the signal person's direction. Cleared on the same channel by whoever called it, or by command.

SIREN	MEANS
Steady tone 3 min, repeats every 5 min · red strobes	**Take shelter**
High-low tone 3 min, repeats · amber strobes	**Evacuate to muster**
3 short blasts, 1 s each	**All stop**
One 15-s tone, then Ch 1 voice: "All clear, all clear, [area]"	**All clear**

Never leave a shelter or restart work on a tone alone. Wait for the Ch 1 voice all clear or your crew lead. Siren test: every 7th day at 1200, announced on Ch 1.

WARNINGS · ATMOS ON CH 16, REPEATED ON CH 1

Watch	Sandstorm possible within 2 h: secure loose material, plan how loads come down, stage near shelter.
Warning	Sandstorm within 30 min: land all loads, booms down, climbers and MEWPs down, go to shelter.
Flood	Called by grid: leave wadis, trenches and low cuts at once.
Lightning	Strikes within 10 mi: booms down, off steel, out of MEWPs, into a sealed shelter or closed vehicle, never under steel. Resume 30 min after the last strike.

Bleeding: press hard. Tourniquet 2–3 in above the wound, not on a joint. Write the time. Every crew carries a trauma kit with two tourniquets.

CPR: push hard and fast in the center of the chest, 100–120 a minute, 2–2.4 in deep. Let the chest come all the way back up. Get the AED (automated external defibrillator).

START TRIAGE · RESPONDERS TAG, YOU HELP

GREEN WALKS	YELLOW DELAYED	RED NOW	BLACK EXPECTANT

Can't walk, plus breathing over 30 a minute, no pulse at the wrist, or can't follow simple commands = Red.

PANEL 3 · RADIO & HATS

CH	USE
1	**Site Emergency. Always scanned.**
2	Site Command (Hub)
3–10	Sectors: A3 B4 C5 D6 E7 F8 G9 H10
11	Crane & Lift coordination. Never for moving loads.
12	Heavy Equipment, incl. printers
13	Hot Work & Fire Watch
14	Medical (medics, aid stations). Only when told.
15	Logistics / Quartermaster
16	**Atmospheric / Weather. Always scanned.**

Scan rule: every radio scans Ch 1 + Ch 16 + your sector channel. Crane, equipment and hot-work crews add their trade channel. Hub Command repeats every siren and every sandstorm, flood and lightning warning on Ch 1.

Crew channel = your foreman talkgroup (e.g. "C-F14"). Each lift runs on its own lift talkgroup.

Location: Sector-grid, structure, deck, landmark. "Charlie-14, Tower B, Deck 3, east stair." Say numbers digit by digit: "one-four", "niner".

Check-ins: buddies watch each other all shift. Your crew lead sees you at least every 30 min and checks in with the foreman every 30 min. Missed check-in: call-back at once. No answer in 5 min: someone goes in person.

Lone work: none at Caution heat or higher, at height, in confined spaces, or near wadis or trenches. Otherwise 15-min check-ins and a logged location.

HARD HATS

- ⚪ **White:** supers, general foremen, foremen, engineers, managers, Lift Directors
- 🟡 **Yellow:** crew, laborers, operators, all other trades
- 🟡 **Yellow + white LEAD band:** crew lead
- 🟠 **Orange:** riggers, signal persons, lift crew
- 🔵 **Blue:** electricians, power techs
- 🟤 **Brown:** welders, cutters, hot-work crews
- 🟢 **Green:** Safety & Health, Industrial Hygiene, Atmos field staff
- 🔴 **Red:** Fire & Rescue
- ✚ **Red, white cross:** medic, SRU staff
- ● **Grey:** survey, QA/QC, inspectors
- ⚫ **Black:** Security
- 🟣 **Purple:** visitors, non-construction staff (always escorted)
- ▨ **RAMP band, any hat:** heat-ramp Days 1–5. Watch out for them.

Red FIRE WATCH vest = fire watch. A fire watch has no rescue or command authority. Red hats do.

PANEL 4 · NUMBERS THAT KEEP YOU ALIVE

HEAT · FOLLOW THE STRICTER OF HEAT LEVEL AND WBGT

8 oz	Water every 15–20 min. Max 48 oz/hr, 12 qt/day. Electrolyte mix or rations with it. No salt tablets unless a medic gives them.
2%	Body weight lost: pull off. Drink 16–24 oz per lb lost.
WBGT 78+	Work/rest table applies (HS-03).
Gear	Leathers, chem suit or sealed coverall: add 10° to WBGT for light work, 20° for harder work, before reading the table.
WBGT 90+	Heavy and very heavy work 10 on / 50 off.
WBGT 92+	No heavy or very heavy work outside cooled spaces. Moderate 10/50 with cooling vest. No vest, no work (site rule).
WBGT 95+	Essential work only, Extreme rules (site rule).
125°F+ air	Extreme: essential work only, cooling vest, 30 min out then at least 30 min in a cooled shelter (site rule).
140°F+ air	Extreme heat entry: Heat Entry Permit PTW-HE only (site rule).
160°F+ air	Site closed. All crews to shelter.

WIND MPH · HIGHER OF LOCAL METER AND CH 16 · GUST = 3-S GUST

15+	Goggles outside cabs. Secure sheet goods and loose material.
20+	Sustained or gust: no outdoor hot work, no crane personnel platforms. High-sail loads need Lift Director approval.
25 / g30	25 sustained or 30 gust: off open steel, roofs, leading edges, swing stages and outdoor scaffolds above Deck 1. MEWPs down (or the maker's lower limit).
30+	Sustained or gust: all crane loads landed, booms secured per maker.
Vis ≤1 mi	Blowing-dust advisory: no outdoor hot work. Lifts stop when the operator loses sight of the load or signal person.

SITE NUMBERS

6 ft	Fall protection. Deck 1 and up always counts. Scaffolds 10 ft.
5,000 lb	Anchor per worker (or 2× safety factor set by a qualified person).
4 : 1	Ladder angle. 3 ft above the landing.
5 ft	Trench needs slope, shoring or shield. Shallower too if the competent person sees cave-in risk. Sand = Type C, slope 1.5:1. Way out within 25 ft at 4 ft deep.
35 ft	Clear combustibles from hot work.
1% LEL	No hot work at or above it (site rule). Entry stops at 10% LEL.
60 min	Fire watch after hot work (NFPA 51B).
20 ft	Crane clearance from power lines up to 350 kV (50 ft for 350–1,000 kV). Other work 10 ft up to 50 kV.
19.5–23.5%	Safe oxygen range. Confined-space entry only at 20.5% or more after ventilating (site rule, HS-SA).
15 min	Flush eyes or skin after a chemical splash, at the station. The medic comes to you.
20 min	Cool a burn under cool running water.
85 dBA	Hearing protection (NIOSH limit, site rule; OSHA limit 90). Shouting at arm's length? Plug up.

Fighting a fire: only if it's waste-bin size, your exit is behind you and you have the right extinguisher. Not out in about 10 seconds: leave and call Ch 1 "Fire". Never fight a polymer, power-cell or gas-fed fire. Polymer fire: bulk feedstock, a curing resin mass, a printed structure or panel stack, or a spray zone. Rags or scrap in a waste-bin-size fire may be fought; smother a rag can with its lid. A fire that's out: tell your foreman, who logs it on Ch 13.

Stop-work authority: anyone can stop unsafe work. No penalty, no questions. Stop it, make it safe, tell your crew lead (your foreman if there's no crew lead; any green hat if it isn't fixed). Work restarts only when the crew lead confirms the fix with the person who stopped it. Every stop is logged.

Lockout: one person, one lock, one key. Your red personal lock carries your Colonist ID.

Report it: every injury, illness, first aid case, near miss, damage and unsafe condition, to your crew lead before the end of the shift (at once if serious), on form HS-IR. No retaliation.

Your entries save in this browser only. Fill in name and Colonist ID once and every module's sign-off picks them up. This card is your own copy. Your badge record is the one that counts.

HOW TO CARRY IT

- Print it, or use the PDF, and fold it into four along the dashed lines with Panel 1 on the outside.
- Keep it in a chest pocket, not your pants. Responders check the chest.
- Update your sector, crew, talkgroup and muster point every time you're reassigned.
- Lost card? The Quartermaster issues a new one on Ch 15.

WHERE IT COMES FROM

Every line on this card comes from a module or reference sheet. If a line doesn't make sense, go back to its source: radio, sirens and hats in HS-01 and REF-RAD; hearing in HS-02; heat in HS-03; heights and wind in HS-04; hot work and fire in HS-05; cranes and trenches in HS-06; lockout in HS-07; warnings and first aid in HS-09; confined spaces in Supplement A (HS-SA); power lines in Supplement B (HS-SB); permits in REF-PTW; roles and hats in REF-GL. See the full list.

Adapted from Old Earth standards: OSHA 29 CFR 1926 (fall protection, excavations, cranes, welding and cutting), NFPA 51B (hot work), OSHA and NIOSH heat and noise guidance, US Army TB MED 507, START triage, AHA CPR guidelines, Stop the Bleed, ANSI/ISEA Z358.1 (eyewash).

REF-PC · Rev. 5 · Every line comes from a module or reference sheet · Keep it dry