

Comment	Description 2200 pF ±10% 250V	Designator	Footprint	LibRef Quantity
0.01uF	Ceramic Capacitor X7R Radial	C?	CAPRB500W50L450T3 00H550	Ceramic capacitor
10uF	FS-A	C?	CAPPRD500W50D500 H1100	Electrolytic capacitor
100uF	FS-A	C?	CAPPRD500W50D500 H1100	Electrolytic capacitor
1000uF	FS-A	C?	CAPPRD500W50D500 H1100	Electrolytic capacitor
1N4007	Diode Switching 1KV 1A 2-Pin DO-41	D?	DIOAD1060W80L520D 270	1N4007
1N5404	Diode Standard 400 V 3A Through Hole DO- 201AD	D?	DIOAD1990W125L900 D530	Schrotic diode
L08R5000Q1	LED, Orange, Through	D?	LEDRD254W57D500H1 070	LED
TBlock 2	2 Position Wire to Board Terminal Block Horizontal with Board 0.197 _5.00mm_Through Hole	J?	691111710002	Terminal Block - 2Pins
TBlock 3	5.08 MM TERMINAL BLOCK;	J?	Terminal block - 3Pins	3Pins Terminal block
USB-A1HSW6	USB - A Receptacle Connector 4 Position Through Hole, Right Angle	ינו	OST_USB-A1HSW6	USB-A
FIRCH-3	INDUCTOR 3.60uH@8.1ADC ROD CORE/FIRCH-3 REV D	L?	IND_FIRCH-3	Inductor
BC547	«a href="https://pricing. snapeda.com/parts/B C337- 16%:2041/Taiwan%20 Semiconductor/view-part?ref=eda*>Check availability/ab=ca href="https://pricing.snapeda.com/parts/B C337- 16%:2041/Taiwan%20 Semiconductor/view-part?ref=eda*>Check availability/a>	0?	T092250P\$10H770-3	BC547B
RF540	N-Channel 100V 22A (Tc) 85W (Tc) Through Hole TO-220AB	Q?	TO254P1052X465X198 9-3	IRF540
OR2	(MFR-25FBF52-10K) 10,2 kOhm bei 1% 0,25W, 1/4W Durchbohrlochwiders tand Axial Metal Film	R?	RESAD1100W55L680D 260	Resistor (0.25W)
1k	(MFR-25FBF52-10K) 10,2 kOhm bei 1% 0,25W, 1/4W Durchbohrlochwiders tand Axial Metal Film	R?	RESAD1100W55L680D 260	Resistor (0.25W)
2k4	(MFR-25FBF52-10K) 10,2 kOhm bei 1% 0,25W, 1/4W Durchbohrlochwiders tand Axial Metal Film	R?	RESAD1100W55L680D 260	Resistor (0.25W)
4.7k	(MFR-25FBF52-10K) 10,2 kOhm bei 1% 0,25W, 1/4W Durchbohrlochwiders tand Axial Metal Film	R?	RESAD1100W55L680D 260	Resistor (0.25W)
20k	(3306F-1-105) 1 MOhms 0.2W, 1/5W PC Pins Through Hole Trimmer Potentiometer Cermet 1 Turn Top Adjustment	R?	TRIM_3306F-1-105	Potentiometer1
240	(MFR-25FBF52-10K) 10,2 kOhm bei 1% 0,25W, 1/4W Durchbohrlochwiders tand Axial Metal Film	R?	RESAD1100W55L680D 260	Resistor (0.25W)
LM317		U?	TO255P1020X450X196 8-3	LM317
LM2596T		U?	TO170P1016X470X209 2-5	LM2596T
NE555N	555 Type, Timer/Oscillator (Single) IC 500kHz 8- DIP	U?	DIP254P762X533-8	NE555N