



| Comment | Description | Designator | Footprint | LibRef | Quantity |
|--------------------------|----------------------------------------------------------------------------------------------------------|------------|--------------------------------|------------------------------------|----------|
| AI-1223-TWT-12V-R | ELECTRO- MECHANICAL AUDIO INDICATOR | Bz1 | XDCR_AI-1223-TWT- 12V-R | Buzzer | 1 |
| 10uF | FS-A | C1, C3 | CAPPRD500W50D500 H1100 | Electrolytic capacitor | 2 |
| 100uF | FS-A | C2 | CAPPRD500W50D500 H1100 | Electrolytic capacitor | 1 |
| 100nF | 2200 pF ±10% 250V Ceramic Capacitor X7R Radial | C4, C5, C6 | CAPRB500W50L450T3 00H550 | Ceramic capacitor | 3 |
| 22pF | 2200 pF ±10% 250V Ceramic Capacitor X7R Radial | C7, C8 | CAPRB500W50L450T3 00H550 | Ceramic capacitor | 2 |
| 1N5404 | Diode Standard 400 V 3A Through Hole DO- 201AD | D1 | DIOAD1990W125L900 D530 | Schrotic diode | 1 |
| L08R5000Q1 | LED, Orange, Through Hole, T-1 3/4 (5mm), 30 mA, 2.1 V, 635 nm | D2, D3, D4 | LEDRD254W57D500H1 070 | LED | 3 |
| 691214110003 | 3 Position Wire to Board Terminal Block Horizontal with Board 0.138 (3.50mm) Through Hole | J1 | 691214110003 | Terminal blocks - 3Pins (Small) | 1 |
| TBlock 2 | 2 Position Wire to Board Terminal Block Horizontal with Board 0.197 _5.00mm_ Through Hole | J2, J3, J4 | 691111710002 | Terminal Block - 2Pins | 3 |
| Header 4 | 4 Position Header Connector Through Hole | J5 | SULLINS_PPTC041LFB N-RC | Female header - 4Pins | 1 |
| Header 6 | Header, 6-Pin | P1 | HDR1X6 | Header 6 | 1 |
| 100 | (MFR-25FBF52-10K) 10,2 kOhm bei 1% 0,25W, 1/4W Durchbohrlochwiders tand Axial Metal Film | R1 | RESAD1100W55L680D 260 | Resistor (0.25W) | 1 |
| 220 | (MFR-25FBF52-10K) 10,2 kOhm bei 1% 0,25W, 1/4W Durchbohrlochwiders tand Axial Metal Film | R2, R4 | RESAD1100W55L680D 260 | Resistor (0.25W) | 2 |
| 1k | (MFR-25FBF52-10K) 10,2 kOhm bei 1% 0,25W, 1/4W Durchbohrlochwiders tand Axial Metal Film | | RESAD1100W55L680D 260 | Resistor (0.25W) | 2 |
| LM7805 | | U1 | TO254P1054X470X195 5-3 | LM7805CT/NOPB | 1 |
| LD1117V33 | | U2 | TO255P1020X450X196 8-3 | LD1117V33 | 1 |
| NRF24L01P-MODULE- PCB | - Transceiver For Use With nRF24L01+ | U3 | XCVR_NRF24L01P- MODULE-PCB | NRF24L01P-MODULE- PCB | 1 |
| ATMEGA328 | ATmega Series 20 MHz 32 KB Flash 2 KB SRAM 8-Bit Microcontroller - DIP- 28 | U4 | DIP794W46P254L2967 H457Q28B | ATMEGA328P-PU | 1 |
| LD293 | 4-Channel Motor Driver 24V 16-Pin Power PDIP Tube | U5 | DIP880W50P254L2000 H510Q16 | L293D | 1 |
| 16MHz | CRYSTAL T/H | Y1 | XTAL_ECS-160-20-4X | Crystal oscilator | 1 |