

---

# Operating System Lab

## CEN-493

---

# Program - 11

## Code :-

```
#include <iostream>
#include <vector>
using namespace std;

typedef long long ll;

struct memoryBlocks
{
    bool isAllocated;
    int blockSize;
    int processSize;
    int internalFrag;
    string processName;
};

void printLines()
{
    for (int i = 0; i < 110; i++)
    {
```

```

        cout << "_";
    }
    cout << "\n";
}

void Display(vector<memoryBlocks> &memBlocks, int noOfBlocks, int
internalFrag, int externalFrag, vector<pair<int, string>>
&leftProcess)
{
    cout << "Best Fit Memory Allocation Table \n";
    cout << "-----\n";
    cout << "| Block No\t"
        << "Size Of Block\t"
        << "Proces Allocated\t"
        << "Internal Fragmentation  |\n";
    cout << "-----\n";
    for (int bindx = 0; bindx < noOfBlocks; bindx++)
    {
        if (memBlocks[bindx].isAllocated == false)
            cout << "| " << bindx + 1 << "\t\t\t" <<
memBlocks[bindx].blockSize << "\t\t"
                << "  ---  "
                << "\t\t\t"
                << "--"
                << "\t\t|\n";
        else
            cout << "| " << bindx + 1 << "\t\t\t" <<
memBlocks[bindx].blockSize << "\t\t"
                << memBlocks[bindx].processSize << "[" <<
memBlocks[bindx].processName << "]"
                << "\t\t\t" << memBlocks[bindx].internalFrag <<
"\t\t|\n";
    }
    cout << "-----\n";
    cout << "\n";
    printLines();
    printLines();
    if (!leftProcess.empty())
    {
        cout << "Process Whom Memory Is Not Allocated : \n";
    }
}

```

```

        for (int lindx = 0; lindx < leftProcess.size(); lindx++)
        {
            cout << leftProcess[lindx].second << " " <<
leftProcess[lindx].first << "\n";
        }

        printLines();
        cout << "\n\n";
        printLines();
        cout << "Total Internal Fragmentation = " << internalFrag <<
"\n";
        cout << "Total External Fragmentation = " << externalFrag <<
"\n";
        printLines();
    }

```

```

void Best_Fit(vector<memoryBlocks> &memBlocks, int noOfBlocks,
vector<pair<int, string>> &processSizes, int noOfProcess)
{

```

```

    vector<pair<int, string>> leftProcess;
    for (int pindx = 0; pindx < noOfProcess; pindx++)
    {
        bool isProcessMemAllocated = false;
        int emptyBlock = 0, bestBlockSize = 1e9;
        for (int bindx = 0; bindx < noOfBlocks; bindx++)
        {
            if (memBlocks[bindx].isAllocated == true ||
memBlocks[bindx].blockSize < processSizes[pindx].first)
                continue;

            isProcessMemAllocated = true;
            if (bestBlockSize > memBlocks[bindx].blockSize)
            {
                emptyBlock = bindx;
                bestBlockSize = memBlocks[bindx].blockSize;
            }
        }
        if (isProcessMemAllocated == false)
        {
            leftProcess.push_back(processSizes[pindx]);
        }
        else
        {
            memBlocks[emptyBlock].isAllocated = true;

```

```

        memBlocks[emptyBlock].processName =
processSizes[pindx].second;
        memBlocks[emptyBlock].processSize =
processSizes[pindx].first;
        memBlocks[emptyBlock].internalFrag =
memBlocks[emptyBlock].blockSize - processSizes[pindx].first;
    }
}
int externalFrag = 0, internalFrag = 0;
if (leftProcess.empty() == false)
{
    for (int bindx = 0; bindx < noOfBlocks; bindx++)
    {
        if (memBlocks[bindx].isAllocated == true)
            continue;
        externalFrag += memBlocks[bindx].blockSize;
    }
}
for (int bindx = 0; bindx < noOfBlocks; bindx++)
{
    internalFrag += memBlocks[bindx].internalFrag;
}
Display(memBlocks, noOfBlocks, internalFrag, externalFrag,
leftProcess);
}

int main()
{
    system("cls");

    printLines();
    cout << "Vicky Gupta 20BCS070\n";
    cout << "Best Fit Memory Allocation Algorithm\n";
    printLines();
    printLines();

    int noOfBlocks;
    cout << "Enter The No Of Blocks Of Memory : ";
    cin >> noOfBlocks;

    printLines();
    int noOfProcess;
    cout << "Enter The No Of Process : ";
    cin >> noOfProcess;

```

```

printLines();
vector<memoryBlocks> memBlocks(noOfBlocks);
cout << "Enter The Sizes Of Blocks : ";
for (int i = 0; i < noOfBlocks; i++)
{
    cin >> memBlocks[i].blockSize;
    memBlocks[i].isAllocated = false;
    memBlocks[i].processSize = 0;
    memBlocks[i].processName = "";
    memBlocks[i].internalFrag = 0;
}

printLines();
vector<pair<int, string>> processSizes(noOfProcess);
cout << "Enter The Sizes Of Process : ";
for (int i = 0; i < noOfProcess; i++)
{
    cin >> processSizes[i].first;
    processSizes[i].second = "P";
    processSizes[i].second += to_string(i + 1);
}
printLines();

cout << "\n\n";
printLines();
printLines();
Best_Fit(memBlocks, noOfBlocks, processSizes, noOfProcess);
return 0;
}

```

# Output :-

```
Vicky Gupta 20BCS070
Best Fit Memory Allocation Algorithm
```

```
Enter The No Of Blocks Of Memory : 5
```

```
Enter The No Of Process : 4
```

```
Enter The Sizes Of Blocks : 100 500 200 300 600
```

```
Enter The Sizes Of Process : 212 417 112 426
```

```
Best Fit Memory Allocation Table
```

Block No	Size Of Block	Proces Allocated	Internal Fragmentation
1	100	---	--
2	500	417[P2]	83
3	200	112[P3]	88
4	300	212[P1]	88
5	600	426[P4]	174

```
Total Internal Fragmentation = 433
Total External Fragmentation = 0
```