

# Rajalakshmi Engineering College

Name: vignesh rajaram

Email: 241001505@rajalakshmi.edu.in

Roll no: 241001505

Phone: 7904972586

Branch: REC

Department: IT - Section 3

Batch: 2028

Degree: B.E - IT

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 6\_Q2

Attempt : 1

Total Mark : 10

Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

Alice is managing an online store and wants to implement a program using inheritance to calculate the selling price of products after applying discounts.

Guide her by following the instructions:

Create a base class called Product with a public double attribute price. Create a subclass called DiscountedProduct, which extends Product and includes a private double attribute discount rate. This subclass has a method called calculateSellingPrice() to determine the final selling price after applying the discount.

Formula: Discounted selling price = price \* (1 - discount rate)

***Input Format***

The first line of input consists of a double value  $p$ , the initial price of the product.

The second line consists of a double value  $d$ , the discount rate.

### **Output Format**

The output prints "Rs.  $X$ ", where  $X$  is a double value, representing the calculated discounted selling price, rounded off to two decimal places.

If the discount rate is greater than 1, print "Not applicable".

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 50.00

0.20

Output: Rs. 40.00

### **Answer**

```
import java.util.Scanner;
```

```
class DiscountedProduct {  
    private double initialPrice;  
    private double discountRate;  
  
    public DiscountedProduct(double initialPrice, double discountRate) {  
        this.initialPrice = initialPrice;  
        this.discountRate = discountRate;  
    }  
  
    public double calculateSellingPrice() {  
        return initialPrice * (1 - discountRate);  
    }  
}  
  
class ProductPricing {  
    public static void main(String[] args) {
```

```
Scanner scanner = new Scanner(System.in);

double initialPrice = scanner.nextDouble();
double discountRate = scanner.nextDouble();
DiscountedProduct discountedProduct = new
DiscountedProduct(initialPrice, discountRate);
double sellingPrice = discountedProduct.calculateSellingPrice();

if (sellingPrice >= 0) {
    System.out.printf("Rs. %.2f%n", sellingPrice);
} else {
    System.out.println("Not applicable");
}
scanner.close();
}
```

**Status : Correct**

**Marks : 10/10**