

webMethods PIP Tools User's Guide

VERSION 6.0.1 SERVICE PACK 1

webMethods, Inc. 3930 Pender Drive Fairfax, VA 22030 USA 703.460.2500 http://www.webmethods.com

webMethods Administrator, webMethods Broker, webMethods Dashboard, webMethods Developer, webMethods Glue, webMethods Fabric, webMethods Installer, webMethods Integration Server, webMethods Mainframe, webMethods Manager, webMethods Mobile, webMethods Modeler, webMethods Monitor, webMethods Optimize, webMethods Trading Networks, webMethods Workflow, and the webMethods logo are trademarks of webMethods, Inc. "webMethods" is a registered trademark of webMethods, Inc.

Acrobat, Adobe, and Reader are registered trademarks of Adobe Systems Incorporated. Amdocs and ClarifyCRM are registered trademarks of Amdocs Ltd. Ariba is a registered trademark of Ariba Inc. Baan is a registered trademark of Baan Development NV. BEA is a registered trademark, and WebLogic Platform and WebLogic Server are trademarks of BEA Systems, Inc. BMC Software and PATROL are registered trademarks of BMC Software, Inc. BroadVision is a registered trademark of BroadVision, Inc. Chem eStandards and CIDX are trademarks of Chemical Industry Data Exchange. Unicenter is a registered trademark of Computer Associates International, Inc. Kenan and Arbor are registered trademarks of CSG Systems, Incorporated. SNAP-IX is a registered trademark, and Data Connection is a trademark of Data Connection Ltd. DataDirect, DataDirect Connect, and SequeLink are registered trademarks of DataDirect Technologies. D&B and D-U-N-S are registered trademarks of D&B, Inc. Entrust is a registered trademark of Entrust. Hewlett-Packard, HP, HP-UX, and OpenView are trademarks of Hewlett-Packard Company. i2 is a registered trademark of i2 Technologies, Inc. AIX, AS/400, CICS, DB2, IBM, Infoprint, Informix, MQSeries, OS/390, OS/400, RACF, RS/6000, SQL/400, S/390, System/390, VTAM, and WebSphere are registered trademarks; and Communications System for Windows NT, IMS, MVS, SQL/DS, Universal Database, and z/OS are trademarks of IBM Corporation. JBoss and JBoss Group are trademarks of Marc Fleury under operation by JBoss Group, LLC. J.D. Edwards and OneWorld are registered trademarks, and WorldSoftware is a trademark of J.D. Edwards, Linux is a registered trademark of Linus Torvalds and others. X Window System is a trademark of Massachusetts Institute of Technology, Merant is a registered trademark of Merant, Inc. MetaSolv is a registered trademark of Metasolv Software, Inc. ActiveX, Microsoft, Outlook, Visual Basic, Windows, and Windows NT are registered trademarks; and SQL Server is a trademark of Microsoft Corporation. Teradata is a registered trademark of NCR. Netscape is a registered trademark of Netscape Communications Corporation. New Atlanta and ServletExec are trademarks of New Atlanta Communications, LLC. CORBA is a registered trademark of Object Management Group, Inc. UNIX is a registered trademark of Open Group. Oracle is a registered trademark of Oracle Corporation. PeopleSoft and Vantive are registered trademarks, and PeopleSoft Pure Internet Architecture is a trademark of PeopleSoft, Inc. Infranet and Portal are trademarks of Portal Software, Inc. RosettaNet is a trademark of "RosettaNet," a non-profit organization. SAP and R/3 are trademarks or registered trademarks of SAP AG. Siebel is a trademark of Siebel Systems, Inc. EJB, Enterprise JavaBeans, Java, Java Naming and Directory Interface, JavaServer Pages, JDBC, JSP, J2EE, Solaris, SPARC, SPARCStation, Sun, Sun Microsystems, and SunSoft are trademarks of Sun Microsystems, Inc. SWIFT and SWIFTNet are trademarks of S.W.I.F.T. SCRL. Sybase is a registered trademark of Sybase, Inc. UCCnet is a trademark of UCCnet. eBusinessReady is a trademark of Uniform Code Council, Inc. (UCC) and Drummond Group, Inc. (DGJ). Verisign is a registered trademark of Verisign. VERITAS, VÉRITAS SOFTWARE, and VERITAS Cluster Server are trademarks of VERITAS Software. W3C is a registered trademark of World Wide Web Consortium.

All other marks are the property of their respective owners.

Copyright © 2002-2004 by webMethods, Inc. All rights reserved, including the right of reproduction in whole or in part in any form.

Contents

About This Guide	5
Additional Information	6
Chapter 1. Concepts What Does webMethods PIP Tools Do? What Does a PIP Contain? How Do I Use PIPs?	7 8 8
Chapter 2. Installing webMethods PIP Tools System Requirements Platform and Operating System Requirements webMethods Software Requirements Third-Party Software Requirements Database Requirements Hardware Requirements webMethods Component Compatibility Installing webMethods PIP Tools Upgrading webMethods PIP Tools Upgrading from webMethods PIP Tools 6.0.1 Upgrading from webMethods PIP Tools 4.6 Uninstalling webMethods PIP Tools	11 12 12 12 12 13 13 13 14 14 14 15
Chapter 3. Creating and Importing PIPs Creating DTD-based PIPs Importing Modular PIPs	17 18 21
Chapter 4. Managing Schema Dictionaries for DTD-based PIPs Managing Schema Dictionaries Importing a Schema Dictionary Exporting a Schema Dictionary Migrating a Schema Dictionary Migrating From Referenced Schema to Referenced Schema Migrating From Reference Schema to Static Schema Migrating From Static Schema to Referenced Schema	25 26 27 27 28 29
Index	21

About This Guide

This guide describes how to install and use the webMethods PIP Tools to create RosettaNet- compliant PIPs from the RosettaNet-distributed DTDs, XSDs, and PIP specifications.

To use this guide effectively, you should:

- Be familiar with the webMethods Integration Server, the Server Administrator, and the webMethods Developer and understand the concepts and procedures described in the webMethods Integration Server Administrator's Guide and the webMethods Developer User's Guide.
- Be familiar with the webMethods Trading Networks Console and understand the concepts and procedures described in the various webMethods Trading Networks guides.
- Be familiar with the webMethods RosettaNet Module and understand the concepts and procedures described in the various webMethods RosettaNet Module guides.
- Have installed the webMethods Integration Server, Server Administrator, webMethods Trading Networks, and webMethods RosettaNet Module software.

Document Conventions

Convention	Description
Bold	Identifies elements on a screen.
Italic	Identifies variable information that you must supply or change based on your specific situation or environment. Also identifies service input and output variables.
Narrow font	Identifies storage locations for services on the webMethods Integration Server using the convention folder.subfolder:service.
Typewriter font	Identifies characters and values that you must type exactly or messages that the system displays on the console.
UPPERCASE	Identifies keyboard keys. Keys that you must press simultaneously are joined with the "+" symbol.
\	Directory paths use the "\" directory delimiter unless the subject is UNIX-specific.
[]	Optional keywords or values are enclosed in []. Do not type the [] symbols in your own code.

Additional Information

The webMethods Advantage Web site at http://advantage.webmethods.com provides you with important sources of information about your webMethods Integration Platform:

- **Troubleshooting Information.** webMethods provides troubleshooting information for various webMethods components in the webMethods Knowledge Base.
- **Documentation Feedback**. To provide documentation feedback to webMethods, go to the Documentation Feedback Form.
- Additional Documentation. All of the webMethods documentation is available on the webMethods Bookshelf.

. . .

Concepts

What Does webMethods PIP Tools Do?	8
What Does a PIP Contain?	8
How Do I Use PIPs?	9

What Does webMethods PIP Tools Do?

webMethods PIP Tools enable you to create or import a webMethods-implementation of a PIP (referred to as a PIP). You then can use the PIP with the webMethods RosettaNet Module to implement the corresponding PIP transactions in the webMethods Integration Platform.

webMethods PIP Tools enables you to work with two types of PIPs:

■ DTD-based PIPs. These are PIPs based on DTD files and are used with schema dictionaries.

If you are using DTD-based PIPs, you can use PIP Tools to create the PIP directly from the RosettaNet-distributed specifications and DTDs in combination with validation schemas you have downloaded from the RosettaNet web site or that you created for your own installation.

■ Modular PIPs. These are PIPs based on these XML Schema (XSD) files.

If you are running webMethods RosettaNet Module 6.0.1 and webMethods PIP Tools 6.0.1 on Integration Server 6.0.1, you can use PIP Tools to import Modular PIPs. These XML schema–based PIPs are based on RosettaNet's New PIP Specification Format and do not require the use of a schema dictionary because they contain their own validation information.

What Does a PIP Contain?

When you create or import a PIP, the PIP Tools create the following in your webMethods Integration Platform:

- TN document types. The PIP Tools create TN document types in Trading Networks. When a RosettaNet document is sent to the webMethods RosettaNet Module, the webMethods RosettaNet Module uses these TN document types to determine the type of RosettaNet document that was sent.
- **IS document types.** The PIP Tools create IS document types in the Integration Server namespace. These IS document types define the format of RosettaNet documents used by a PIP. The webMethods RosettaNet Module uses the IS document types to validate the structure of the RosettaNet documents.
- Trading Partner Agreements (TPAs). The PIP Tools create TPAs in Trading Networks. These TPAs contain:
 - PIP information, for example, the name and version of a PIP
 - Default transport parameters that can be modified on a trading partner basis, for example, the type of transport to use, the version of the transport, signing and encryption information

The webMethods RosettaNet Module uses the TPAs to specify parameters that are specific to a PIP, the transport to use, and the transport behavior.

By using the PIP Tools you can create or import the PIPs you need as they are released by RosettaNet, without having to wait for webMethods or a third-party vendor to create them for you. Additionally, the PIP Tools enable you to manage the validation schemas that are related to the DTD-based PIPs you use in your production system.

How Do I Use PIPs?

After you create or import the PIP, you can use webMethods Modeler to create the process model(s) that define how the PIP transaction is conducted with your trading partner. webMethods provides generic process models with the WmRosettaNet package that you can use as a basis for creating the PIP-related process models. For more information about creating process models for your PIPs, see the webMethods RosettaNet Module User's Guide.

Installing webMethods PIP Tools

System Requirements	12
Installing webMethods PIP Tools	13
Upgrading webMethods PIP Tools	14
Uninstalling webMethods PIP Tools	15



Important! The information in this chapter might have been updated since the guide was published. Go to the webMethods Advantage Web site at http://advantage.webmethods.com for the latest version of the guide.

System Requirements

This section describes the system requirements that must be met before you can install the webMethods PIP Tools.

Platform and Operating System Requirements

The webMethods PIP Tools has no system requirements beyond those of the webMethods Integration Server. For Integration Server system requirements, see the *webMethods Integration Platform Installation Guide*.

webMethods Software Requirements

The table below lists the webMethods components you must install before or at the same time you install the Manager Server. The table also lists the webMethods components you must install at some point for the Manager Server to operate fully.

Required for Installation	Required for Operation
Integration Server 6.0.1 or 6.1	Developer 6.0.1 or 6.1
Trading Networks Server 6.0.1 or 6.1	Trading Networks Console 6.0.1 or 6.1
	webMethods Modeler 6.0.1 or 6.1
	webMethods Monitor 6.0.1 or 6.1

Third-Party Software Requirements

None.

Database Requirements

None.

Hardware Requirements

The webMethods PIP Tools has no hardware requirements beyond those for the Integration Server. For Integration Server hardware requirements, see the *webMethods Integration Platform Installation Guide*.

webMethods Component Compatibility

webMethods Integration Server 6.0.1, webMethods Trading Networks 6.0.1, webMethods Developer 6.0.1, webMethods Modeler 6.0.1, and webMethods Monitor 6.0.1 are compatible with the webMethods PIP Tools Version 6.0.1 Service Pack 1. For information about the Service Packs and Fixes needed for these components, see "webMethods Software Requirements" on page 12.

Installing webMethods PIP Tools



Important! This section provides only instructions that are specific to installing the webMethods PIP Tools. For complete instructions on using the webMethods Installer, see the *webMethods Integration Platform Installation Guide*.



Important! You must have administrator privileges on the webMethods Integration Server to execute these procedures. If you do not have administrator privileges, have your webMethods Integration Server administrator perform these procedures.



To install the webMethods PIP Tools

- 1 Download thewebMethods Installer 6.0.1 or 6.1 from the webMethods Advantage Web site at http://advantage.webmethods.com.
- 2 Run the installer using the username and password you received from webMethods.
- 3 Choose the webMethods platform version. If you are installing the Service Pack on an existing installation of the Integration Server, be sure to choose the same version of the webMethods platform as the existing installation of the Integration Server. Specify the webMethods Integration Platform installation directory (by default, webMethods6).
- 4 In the component selection list, navigate to webMethods Platform ▶ eStandards ▶ webMethods PIP Tools and select the desired components:
 - Documentation 6.0 (Optional). Contains the documentation for this package.
 - Program Files (Required). Contains the program files for this package.
 - Any required webMethods components you have not installed.

- 5 Click **Next** until the installer displays the **Installation Complete** panel.
- Click Close.

The webMethods PIP Tools starts automatically when you start the webMethods Integration Server.

Upgrading webMethods PIP Tools

This section describes how to upgrade from previous versions of the webMethods PIP Tools to webMethods PIP Tools 6.0.1 and 6.0.1 Service Pack 1.

Upgrading from webMethods PIP Tools 6.0.1

When you want to upgrade from the webMethods PIP Tools 6.0.1 to webMethods PIP Tools 6.0.1 Service Pack 1, you need to complete the following steps:

- 1 Download webMethods Installer 6.0.1 or 6.1 from the webMethods Advantage Web site at http://advantage.webmethods.com and start the installer.
- 2 Run the installer using the username and password you received from webMethods.
- 3 Choose the webMethods platform version. Be sure to choose the same version of the webMethods platform as the existing installation of the Integration Server. Specify the webMethods Integration Platform installation directory (by default, webMethods6).
- 4 In the component selection list, navigate to webMethods Platform ▶ eStandards ▶ webMethods PIP Tools and select the following component:
 - **Service Pack 1.** Contains the service pack for support of Modular PIPs.
- 5 Click **Next** until the installer displays the **Installation Complete** panel.
- 6 Click Close.

Upgrading from webMethods PIP Tools 4.6

When you want to upgrade from the webMethods PIP Tools 4.6 to webMethods PIP Tools 6.0.1, you need to complete the following steps:

- 1 Uninstall your webMethods Integration Server 4.6 as described in "Uninstalling webMethods PIP Tools" on page 15.
- **2** Install webMethods Integration Server 6.0.1. For more information about upgrading from webMethods Integration Server 4.6 to webMethods Integration Server 6.0.1, see the *webMethods Integration Platform Upgrade Guide*.

3 Install the webMethods PIP Tools 6.0.1 as described in "Installing webMethods PIP Tools" on page 13.

Uninstalling webMethods PIP Tools



Important! This section provides only instructions that are specific to uninstalling webMethods PIP Tools. For complete instructions on using the webMethods Uninstaller, see the *webMethods Integration Platform Installation Guide*.

You perform the following procedure when you want to completely uninstall the webMethods PIP Tools.



To uninstall webMethods PIP Tools

- 1 Shut down all webMethods components and applications that are running on your machine.
- **2** Start the webMethods Uninstaller.
- 3 Select **webMethods PIP Tools** as the program to uninstall.
- 4 The Uninstaller removes all webMethods PIP Tools-related files that were installed into the *Integration Server_directory*\packages directory. The Uninstaller does not delete files created after you installed the webMethods PIP Tools (for example, usercreated or configuration files), nor does it delete the directory structure that contains the files.
- 5 If you do not want to save the files that the Uninstaller did not delete, navigate to the *Integration Server_directory*\packages directory and delete the PIP Tools-related folders.

Creating and Importing PIPs

Creating DTD-based PIPs	. 18
Importing Modular PIPs	2

Creating DTD-based PIPs

You can use PIP Tools to create a PIP using a DTD file. The PIP then can be used in conjunction with a schema dictionary to process the PIP transaction.



To create a DTD-based PIP

- 1 Import a general schema dictionary to use for validating the PIP:
 - webMethods provides an enhanced version of the official RosettaNet schema dictionary as part of the webMethods RosettaNet Module. The schema dictionary webMethods provides is located in the webMethods6\IntegrationServer\packages\ WmPIPTools\import\rosettanet_v2-1_webm.XML file. Copy this file into the webMethods6\IntegrationServer\packages\WmPIPTools\import directory.
 - -OR-
 - From the RosettaNet web site (http://www.rosettanet.org), locate and download the PIP zip file for the dictionary that you want to use. Unzip the dictionary file into the webMethods6\IntegrationServer\packages\WmPIPTools\import directory.



Note: During the process to create a PIP, you will use the PIP Tools Schema Management facilities to import the schema dictionary into the Integration Server as an IS schema. The PIP Tools reference this IS schema to further define the field constants and optional values for the IS document type for the PIP. For instructions for importing the schema description, see "Importing a Schema Dictionary" on page 25.

2 From the RosettaNet web site (http://www.rosettanet.org), locate and download the PIP zip file for the PIP you want to create (for example, PIP3A4_MS_V02_00_ PurchaseOrderRequest.zip) into the webMethods6\IntegrationServer\packages\WmPIPTools\import directory.

The zip file contains the DTD(s) for the PIP, as well as the specification document and other files.



Tip! You can copy either a DTD file or a zip file that contains one or more DTD files into the directory. The process that creates the PIP will process either file type appropriately.

- **3** Ensure that the appropriate schema dictionary is in the webMethods6\IntegrationServer\ packages\WmPIPTools\import directory.
- 4 Start the webMethods Integration Server and Server Administrator, if they are not already running.
- 5 Import the schema dictionary using the procedure described in "Importing a Schema Dictionary" on page 25.

- **6** From the Server Administrator, in the **Adapters** menu of the navigation area, click **RosettaNet**. The **RosettaNet Management** screen displays in a new browser window.
- From the **RosettaNet Management** screen, in the navigation area, click **PIP Builder**. The **PIP Builder** screen appears.
- 8 Specify the values for the fields in the **Build PIP** section of the screen.

You can find the correct values to specify from information that you downloaded from the RosettaNet web site. The following table describes where to look for the values to specify.

For this field	field Where to look for the value to specify	
Pip Name	Front page of the RosettaNet Specification, for example, Request Purchase Order	
Pip Number	Front page of the RosettaNet Specification, for example, 3A4	
Pip Version	Front page of the RosettaNet Specification, for example, V02.00	
Transaction	In the RosettaNet Specification, Table 3-2, column <i>Activity Name</i> , for example, Request Purchase Order	
Action	In the RosettaNet Specification, Table 4-2, column <i>Business Action in FSV</i> , for example, Purchase Order Request Action	
DTD	Included in the PIP zip file you downloaded and loaded into the webMethods6\IntegrationServer\packages\WmPIPTools\import directory, for example, 3A4_MS_V02_00_PurchaseOrderRequest.dtd	
	Note : The DTD that you downloaded should appear in the drop-down list.	
From Role	In the RosettaNet Specification, Table 3-1, column <i>Role Name</i> , for example, Buyer	
To Role	In the RosettaNet Specification, Table 3-1, column <i>Role Name</i> , for example, Seller	
IS Schema Dictionary	Loaded into the webMethods6\IntegrationServer\packages\WmPIPTools\import directory and imported using the Schema Import facilities, for example, rosettanet_v2_webm	
	Note: The dictionary schema should appear in the drop-down list.	
Has Response Document	Whether the Transaction has a response document; specify either True or False	

- 9 Click either the Reference or the Static radio button beside the IS Schema Dictionary dropdown list to specify whether you want the schema information included in the IS document types by reference or by hardcoded entry, respectively.
 - If you select the **Reference**, the IS document types in the created PIP will point to the schema by reference. Alternatively, if you select the **Static**, the IS document types will actually include all schema values in the IS document types (that is, hardcoded, rather than referentially). The default is **Static**.
- 10 Click either the True or the False radio button for the Has Response Document field to specify whether the PIP does or does not contain or involve a response document, respectively.

If you select the **True** radio button for **Has Response Document**, the following additional data entry fields appear for you to specify information for the response document. You can find the correct values to specify for these fields from information that you downloaded from the RosettaNet web site. The following table describes where to look for the values to specify.

For this field	Where to look for the value to specify	
Response Action	In the RosettaNet Specification, Table 4-2, column <i>Business Action in FSV</i> , for example, Purchase Order Confirmation Action	
Response DTD	Included in the PIP zip file you downloaded; loaded into the webMethods6\IntegrationServer\packages\WmPIPTools\import directory, for example, 3A4_MS_V02_00_PurchaseOrderConfirmation.dtd	

11 Click Preview PIP.

Any errors in the information that you supplied display on the screen next to the fields that are in error. Correct errors, consulting the RosettaNet-distributed Specification and the ? button beside each field. After you have made your corrections, click **Preview PIP** again.

When all information is correct and you click **Preview PIP**, the **PIP Preview** screen displays the IS document types, TN document types, and Trading Partner Agreements (TPAs) that the PIP Tools will create for the PIP.

12 Click Build PIP.

A message appears indicating the build was successful. PIP Tools creates *and* imports the PIP directly into your webMethods Integration Platform. That is, the TN document types and TPAs are imported into webMethods Trading Networks and the IS document types are available in the Integration Server namespace. If you want to create a process archive file (.par file) to share the PIP with your trading partners, you must use the webMethods RosettaNet Module PIP export procedures. See the *webMethods RosettaNet Module User's Guide* for further information.

After you have created the PIP, you now can use webMethods Modeler to create a process model for the PIP transaction. For instructions on creating the process model, see the webMethods RosettaNet Module User's Guide.

Importing Modular PIPs

If you are running webMethods RosettaNet Module 6.0.1 and webMethods PIP Tools 6.0.1 on Integration Server 6.0.1, you can use PIP Tools to create a Modular PIP using an XSD file. This Modular PIP, which does not require a schema dictionary, can then be used to process the PIP transaction.



Tip! If you are using webMethods Integration Server 4.6, you can install webMethods Integration Server 6.0.1, import a Modular PIP, and then export the PIP to Integration Server 4.6 using webMethods PIP Tools.



To import a Modular PIP

- 1 From the RosettaNet web site (http://www.rosettanet.org), download the Modular PIP XSD zip file that you want to import (for example, PIP4A3_R11.01_NotifyOfThresholdRelease Forecast.zip) into the webMethods6\IntegrationServer6\WmPIPTools\import folder.
- **2** Start webMethods Integration Server and Server Administrator, if they are not already running.
- 3 From the Server Administrator, in the **Adapters** menu of the navigation area, click **RosettaNet**. The **RosettaNet Management** screen displays in a new browser window.
- 4 From the RosettaNet Management screen, in the navigation area, click Modular PIP Import. A screen appears listing all of the PIP XSDs in the webMethods6\IntegrationServer\WmpIPTools\import folder.
- 5 From the list, select the Modular PIP XSD file that you want to import, and then click **View**. A screen appears listing the items that will be imported.



Note: If you are re-importing this PIP, you will need to clear the check boxes for items that you do not want to re-import. Selected items will overwrite their existing counterparts on the Integration Server.

6 Click **Import**. A screen appears indicating whether the import was successful.

webMethods PIP Tools places the IS document types in the webMethods6\IntegrationServer6\packages\WmRNPips\ns\wm\b2b\rn\rec\PIP\ PipNumberAndVersion folder. webMethods PIP Tools also automatically stores any IS schema that is common to different PIPs (for example, country codes) in the webMethods6\IntegrationServer6\packages\WmRNPips\ns\wm\b2b\rn\rec\PIP\common folder in a directory structure similar to that defined in the PIP XSD zip file.

If you want to create a process archive file (.par file) to share the PIP with your trading partners, you must use the webMethods RosettaNet Module PIP export procedures. See the webMethods RosettaNet Module User's Guide for further information.

After you have imported the PIP, you now can use webMethods Modeler to create a process model for the PIP transaction. For instructions on creating the process model, see the *webMethods RosettaNet Module User's Guide*.

. . .

Managing Schema Dictionaries for DTD-based PIPs

Managing Schema Dictionaries	24
Importing a Schema Dictionary	25
Exporting a Schema Dictionary	26
Migrating a Schema Dictionary	27

Managing Schema Dictionaries

Using the webMethods PIP Tools, you can import, export, and migrate schema dictionaries for use with DTD-based PIPs. A schema dictionary contains a definition for each RosettaNet element.

When you create a PIP, you select whether you want the schema dictionary information included in the IS document type that the PIP Tools create (static) or whether you want the IS document type to reference the schema dictionary information (reference). Based on your selection, during PIP creation the PIP Tools look up the element definition in the schema dictionary and either apply the element definition to the IS document type (static) or apply a reference in the IS document type to the dictionary schema (reference).

The following table lists the tasks you can perform to manage your schema dictionaries:

Task	Description	
Import schema dictionaries	You can import a schema dictionary from an XML file. Use the import function along with the export function to modify or clone schemas in your webMethods installation and upgrade schema dictionaries as new ones are released by the RosettaNet organization.	
	For example, you can modify you schema dictionary using an XML editor, and then import the XML file containing the modified schema, either to replace an existing version of the schema dictionary or to create a new, independent schema dictionary.	
Export schema dictionaries	You can export a schema dictionary to an XML file. Use the export function along with the import function to modify or clone schemas in your webMethods installation and upgrade schema dictionaries as new ones are released by the RosettaNet organization.	
	For example, you can export a customized schema dictionary to an XML file, make modifications to the XML file, and then use the import function to re-import the updated schema dictionary.	
Migrate schema dictionaries	You can migrate your PIPs from one schema to another. This facility is useful when you have an updated schema dictionary with new IS document types or values and want to make an existing PIP use the new schema dictionary. This is typical of the case where you have downloaded a new version of a schema dictionary from the RosettaNet web site.	

Importing a Schema Dictionary

To import an XML file as a schema dictionary, perform the following steps.



To import a schema dictionary

- 1 Copy the schema dictionary file(s) that you want to import into the webMethods6\IntegrationServer\packages\WmPIPTools\import directory.
- **2** Start the webMethods Integration Server and Server Administrator, if they are not already running.
- From the Server Administrator, in the **Adapters** menu of the navigation area, click **RosettaNet**. The **RosettaNet Management** screen is displayed in a new browser window.
- 4 From the RosettaNet Management screen, in the navigation area, click **Schema** Management. The **Schema** Management screen is displayed.
- 5 From the **Dictionary XML File** drop-down list, select the name of the XML file that you want to import as a schema dictionary.
- Select the **Merge** or **Overwrite** radio button to indicate whether you want the PIP Tools to append the imported file to any existing schema dictionary with the same name or to overwrite any existing schema dictionary of the same name.
 - If you select **Merge**, the PIP Tools evaluate each field or IS document type individually. The PIP Tools add new fields or IS document types to the merged file.

Existing fields or IS document types must match in structure (i.e., in data type)-the PIP Tools add any differences in constraint values in the IS document type or field to be merged to the existing IS document type or field.

The PIP Tools generate an error for existing IS document types or fields that do not match structurally. You must ensure that no such mismatches are present in the schema dictionary you want to import.

If you select **Overwrite**, the PIP Tools overwrite the existing schema dictionary file with the new file.

7 Click Import Schema.

The PIP Tools display a message indicating the import was successful.

The PIP Tools import the XML file as a schema dictionary and the schema dictionary becomes available to use, for example to migrate your PIPs from one schema dictionary to another or to create a PIP.



Tip! You can view and edit an imported schema dictionary using the webMethods Developer and examining the WmPIPTools package.



Note: You can use the webMethods Developer to delete an imported schema dictionary. Doing so deletes the schema dictionary from your Integration Server run-time system, but does not remove the schema dictionary's XML file from the webMethods6\IntegrationServer\packages\WmPlPTools\import directory. Similarly, deleting the XML file from the import directory prevents you from importing the schema dictionary, but does not remove it from the run-time system if it has already been imported. Deleting the XML file from the import directory and deleting the imported schema dictionary using the webMethods Developer completely removes the schema dictionary from your installation.

Exporting a Schema Dictionary

To export a schema to an XML file, perform the following steps.



To export a schema dictionary

- 1 Start the webMethods Integration Server and Server Administrator, if they are not already running.
- 2 From the Server Administrator, in the Adapters menu of the navigation area, click RosettaNet. The RosettaNet Management screen is displayed in a new browser window.
- 3 From the RosettaNet Management screen, in the navigation area, click **Schema** Management. The **Schema** Management screen is displayed.
- 4 From the **IS Schema** drop-down list, select the name of the name of the schema that you want to export as an XML file.
- 5 Click Export Schema.

The PIP Tools display a message indicating the export was successful.

The PIP Tools export the schema dictionary as an XML file with the same name as the schema dictionary into the webMethods6\IntegrationServer\packages\WmPIPTools\export directory.



Tip! You can view and edit an exported schema dictionary's XML file using any common XML editor.

Migrating a Schema Dictionary

In general, migrating a schema dictionary involves one of the three following actions:

- **Referenced schema to referenced schema.** Taking a set of IS document types that refer to a specific schema and editing them so that they refer to another specific schema.
- Referenced schema to static schema. Taking a set of IS document types that refer to a specific schema and editing them so that they no longer refer to a schema, but stand on their own.
- **Static schema to referenced schema**. Taking a set of IS document types that does not refer to a specific schema and editing them so that they refer to a specific schema.

The PIP Tools schema migration allows you to make these changes automatically, rather than by hand. Migrating schema dictionaries is useful when upgrading from one version of a schema dictionary to a new version.

Note that when you created your PIP using the **PIP Builder** screens, you had to select whether the schema dictionary that the PIP used was referenced or static. The choice you made affects the actions you must take against PIPs after you update a schema dictionary.

- **Referenced schema dictionaries.** If the schema dictionary is referenced, you can export a schema dictionary, modify it, and then re-import it using the same schema dictionary name, and your PIPs will automatically use the new values.
- **Static schema dictionaries**. If the schema dictionary is static, you must either re-create the PIP if you modify the schema dictionary upon which the PIP is based or reference it to another schema.

Migrating From Referenced Schema to Referenced Schema




To migrate from a referenced schema dictionary to another referenced schema dictionary

- 1 Make sure that you have imported the schema dictionary to which you are migrating before performing the migration procedure.
- 2 Start the webMethods Integration Server and Server Administrator, if they are not already running.
- 3 From the Server Administrator, in the **Adapters** menu of the navigation area, click **RosettaNet**. The **RosettaNet Management** screen is displayed in a new browser window.
- 4 From the RosettaNet Management screen, in the navigation area, click Schema Management. The Schema Management screen appears.
- From the Namespace Folder drop-down list, select the name of the folder that contains the IS document types you want to migrate.

- **6** From the **from IS Schema** drop-down list, select the name of the schema dictionary to which the IS document types currently refer.
- 7 From the **to IS Schema** drop-down list, select the name of the schema dictionary to which you want to migrate the IS document types.
- 8 Click Migrate Schema.

The PIP Tools display a message indicating that the migration was successful. The IS document types are migrated to the new schema dictionary. The old schema dictionary is not deleted from your webMethods installation.

Migrating From Reference Schema to Static Schema



- 1 Make sure that you have imported the schema dictionary to which you are migrating before performing the migration procedure.
- **2** Start the webMethods Integration Server and Server Administrator, if they are not already running.
- 3 From the Server Administrator, in the **Adapters** menu of the navigation area, click **RosettaNet**. The **RosettaNet Management** screen is displayed in a new browser window.
- 4 From the RosettaNet Management screen, in the navigation area, click **Schema** Management. The **Schema** Management screen appears.
- 5 From the Namespace Folder drop-down list, select the name of the folder that contains the IS document types you want to migrate.
- **6** From the **from IS Schema** drop-down list, select the name of the schema dictionary to which the IS document types currently refer.
- 7 From the **to IS Schema** drop-down list, select **<Static>**.
- 8 Click Migrate Schema.

The PIP Tools display a message indicating that the migration was successful. The IS document types are disconnected from the original schema dictionary. The old schema dictionary is not deleted from your webMethods installation.

. . .

Migrating From Static Schema to Referenced Schema



To migrate from a static schema dictionary to a referenced schema dictionary

- 1 Make sure that you have imported the schema dictionary to which you are migrating before performing the migration procedure.
- **2** Start the webMethods Integration Server and Server Administrator, if they are not already running.
- From the Server Administrator, in the **Adapters** menu of the navigation area, click **RosettaNet**. The **RosettaNet Management** screen is displayed in a new browser window.
- 4 From the RosettaNet Management screen, in the navigation area, click **Schema** Management. The **Schema Management** screen appears.
- 5 From the Namespace Folder drop-down list, select the name of the folder that contains the IS document types you want to migrate.
- **6** From the **from IS Schema** drop-down list, select the blank line.
- 7 From the **to IS Schema** drop-down list, select the name of the schema dictionary to which you want to migrate the IS document types.
- 8 Click Migrate Schema.

The PIP Tools display a message indicating that the migration was successful. The IS document types are migrated to a schema dictionary.

Index

C .	downloading
cloning schemas 24	DTD-based PIPs 18
conventions used in this document 5	Modular PIPs 21
correcting errors in PIPs 20	DTD-based PIPs
creating DTD-based PIPs	actions when PIP built successfully 20
items created 8	description 8
steps 18	downloading 18
values to specify 19	items created in webMethods Integration Platform 8
creating process models for use with PIPs 9	making existing PIP use new schema dictionary 24 migrating from one schema to another 24
D	obtaining 18
dictionaries, schema	prerequisites for creating 18
exporting to XML files 24	specifying whether has a response document 20 steps for creating 18
importing	values to specify on PIP Builder screen 19
before migrating 27	where stored 20, 21
from XML files 24	Where Stored 20, 21
general information 18	E
making existing PIP use new dictionary 24	
migrating	errors, correcting those in PIP 20
general information 27	exporting schema dictionaries
IS document types from one to another 27, 28, 29	steps to exporting 26
when schema dictionary referenced 27	to XML files 24
when schema dictionary static 27	where XML file placed 26
overwriting on import 25	11
referenced 20	Н
static 20	hardcoding schema information in IS document type 20
steps to export 26	hardware requirements, PIP Tools 13
steps to import 25	
upgrading 24	1
where exported file placed 26	importing Modular PIPs
displaying	items created 8
entry fields for response document 20	steps 21
Modular PIP Import screen 21	importing schema dictionaries
PIP Builder screen 19	and migrating 27
RosettaNet Management screen 19	from XML files 24
Schema Management screen 25	general information 18
documentation, program code conventions 5	overwriting or merging 25
	steps for importing 25

IS document types	PIP Tools
and migrating schema dictionaries 27	hardware requirements 13
hardcoding schema information rather than referencing 20	installation instructions 13
referencing schema information rather than hardcoding 20	system requirements 12
steps to migrate from one schema dictionary to another 27, 28,	PIPs
29	correcting errors 20
	DTD-based
M	See DTD-based PIPs 8
merging schema dictionaries on import 25	exporting 20, 21
migrating	IS document types 20
PIPs from one schema to another 24	items created in webMethods Integration Platform 8
schema dictionaries 27	Modular
schema dictionaries and importing 27	See Modular PIPs 8
schema dictionaries when referenced 27	steps for creating 18
schema dictionaries when static 27	process models
schema dictionaries, steps 27, 28, 29	basic ones to use to create PIP-related models 9
modifying schemas 24	creating for use with PIPs 9
Modular PIP Import screen, displaying 21	generic ones provided with WmRosettaNet package 9
Modular PIPs	program code conventions 5
actions when PIP imported successfully 21	. •
description 8	R
downloading 21	referencing schema dictionaries 20
importing 21	response document
items created in webMethods Integration Platform 8	specifying whether PIP has one 20
obtaining 21	RosettaNet Management screen, displaying 19
prerequisites for importing 21	RosettaNet schema dictionaries
steps for importing 21	See also schema dictionaries 18
ctope for importing 21	importing 18
0	obtaining for a DTD-based PIP 18
	obtaining for a DTD-based Fit To
obtaining	S
DTD-based PIPs 18	
Modular PIPs 21	saving
overwriting schema dictionaries on import 25	DTD-based PIPs, where to save 18
_	Modular PIPs, where to save 21
P	schema dictionaries
PIP Builder screen	exporting to XML files 24
displaying 19	importing
obtaining values to use to fill in 19	before migrating 27
what to specify 19	from XML files 24
PIP Specification document	general information 18
using to fill in PIP Builder screen 19	making existing PIP use new dictionary 24

. . .

migrating
general information 27
IS document types from one to another 27, 28, 29
when schema dictionary referenced 27
when schema dictionary static 27
overwriting on import 25
referenced 20
static 20
steps to export 26
steps to import 25
upgrading 24
where exported file placed 26
Schema Management screen, displaying 25
schemas
cloning 24
migrating PIPs from 24
modifying 24
Server Administrator, displaying 18
sharing process archive file 20, 21
specifying
values on PIP Builders screen 19
whether PIP has response document 20
system requirements, PIP Tools 12
U
updating schemas 24
upgrade
from PIP Tools 4.6 14
from PIP Tools 6.0.1 14
W
webMethods PIP Tools
description 8
steps for creating a DTD-based PIP 18
steps for importing a Modular PIP 21
webMethodsModeler
creating process models for PIPs 9
VI

X

XML files
exporting schema dictionary to 26
importing as schema dictionary 25
where exported schema dictionary placed 26
XML-based schemas
See Modular PIPs 21
XSD files
See Modular PIPs 21

. . .