scribs&pixels school · v1 · 2 October 2026

Victor's Task Program

Everything you, not Claude, have to do, written like code: explicit inputs, numbered steps, IF/ELSE branches, expected output and what to do on error. Work through it slowly, one procedure at a time.

00	How to run this program (read first)	DO NOW
01	answer_phase2_questions()	✓ DONE 3 Oct
02	confirm_school_rules()	✓ DONE 9 Oct
03	test_school_as_learner()	DO NOW · weekends
04	bring_back_ui_design()	WHEN READY
05	deploy_on_vercel()	✓ DONE 9 Oct
06	connect_subdomain()	✓ DONE 9 Oct
07	create_supabase_project()	✓ DONE 12 Oct
08	set_up_resend()	NEXT
09	deploy_email_nudges()	ON HOLD
10	Appendix: words, tools and message templates	

Why some procedures are ON HOLD. You put hosting and the backend on hold. They're written out in full so they're ready when you decide. **Doing 07–09 today won't change anything you can see**, because the app doesn't log people in yet. Claude wires accounts into the app after your UI design comes back.

00 · How to run this program

Read this page once. It works like the rules of a programming language: every procedure after it follows them.

The rules

- ☐ `01` **One procedure at a time.** Finish it, or stop it cleanly, before starting another. Never run two at once.
- ☐ `02` **Run the steps in order.** Don't skip a step because it "looks obvious". If a step says *copy*, copy; don't retype.
- ☐ `03` **Tick each** ☐ with a pen as you finish it. If you stop halfway, the last tick tells you where to resume.
- ☐ `04` **Check the EXPECTED OUTPUT** at the end of each procedure. If what you see matches, the procedure is done.
- ☐ `05` **ON ERROR, stop.** Don't improvise. Take a screenshot, then send Claude the error template from the Appendix (section 10).
- ☐ `06` **Secrets never go into chat, email, WhatsApp or the repo.** A secret is any value this document labels `SECRET`. Keep them in a password manager (Apple Passwords, 1Password or Bitwarden).

How to read a procedure

PROCEDURE	The name of the task, like a function name.
WHY	What it achieves, in one sentence.
INPUTS	What you need before you start. If you don't have every input, don't start.
TIME	Roughly how long it takes.
STEPS	Numbered actions, done in order.
IF / ELSE	A fork: do the branch that matches what you see.
EXPECTED OUTPUT	What "done" looks like.
ON ERROR	What to do when it doesn't work.

Notation

- **Bold text in steps** = a button, menu or label to click on screen, spelt exactly as it appears.
- `Grey monospace` = text to type or paste exactly, character for character.
- `<LIKE_THIS>` = a placeholder. Replace the whole thing, including the < >, with your own value.
- → = "then click". **Settings** → **Domains** means click Settings, then click Domains.
- "Terminal" = the Mac app called Terminal (press ⌘ **+ Space**, type `Terminal`, press Enter).

01 · answer_phase2_questions() DO NOW

`PROCEDURE answer_phase2_questions() → 3 answers`

WHY	Fullstack Weeks 11–14 can't be written until you decide these. Weeks 1–10 are written and live.
INPUTS	15 quiet minutes. Optional: the draft plan at `src/content/courses/fullstack-ml/phase-2-plan.md` (on GitHub: repo → that path).
TIME	15 minutes

- ☐ **01** **Question 1: order.** The draft is: Week 11 modern CSS (Grid, multi-page sites) → Weeks 12–13 React (components, then state and fetching) → Week 14 milestone in plain HTML/CSS/JS. Decide:
  IF you're happy with that order → answer `Order: keep`
  ELSE IF you want React earlier and the milestone built in React → answer `Order: React first`
- ☐ **02** **Question 2: milestone business.** Week 14's milestone is a multi-page website (Home · Menu · About · Contact) for a pretend Nigerian business. The suggestion is **"Mama Put Kitchen"**, a Lagos buka: menu with ₦ prices, opening hours, WhatsApp ordering. Alternatives: an Abuja tailor, an Enugu phone-repair shop.
  IF you like it → `Business: Mama Put Kitchen`
  ELSE → `Business: <YOUR_IDEA>` plus one sentence about what it sells.
- ☐ **03** **Question 3: Saturdays.** As drafted, the Saturdays of Weeks 11–14 all build towards the milestone site. The alternative is one separate project each Saturday.
  IF yes → `Saturdays: build the milestone` **ELSE** → `Saturdays: separate mini-projects`
- ☐ **04** Open Claude Code (Mac or claude.ai/code) in this project.
- ☐ **05** Paste this message, with your three answers filled in, and send it:

```
Phase 2 decisions:
Order: <keep | React first>
Business: <Mama Put Kitchen | your idea + one sentence>
Saturdays: <build the milestone | separate mini-projects>
Write Fullstack Weeks 11–14 when it's a weekday.
```

EXPECTED OUTPUT: Claude replies confirming the plan. On the next weekday it writes Weeks 11–14 and pushes them to the test site.

ON ERROR: If you can't decide, send `Phase 2: use your defaults`. The defaults are: keep the order, Mama Put Kitchen, Saturdays build the milestone.

02 · confirm_school_rules() DO NOW

```
PROCEDURE confirm_school_rules() → 5 decisions
```

WHY	The app runs on default rules that you haven't approved yet. Each rule lives in one place in the code, so changing it later is cheap, but approving them now stops guesswork.
INPUTS	The table below.
TIME	10 minutes

For each row, write **KEEP** or **CHANGE: <how>** in the last column.

Rule	Current default
R1 Pacing	"Today" = your first unfinished day. Missing an evening never puts you behind. ☐ KEEP ☐ CHANGE: _____
R2 Week quiz pass mark	The end-of-week quiz is self-marked; you pass when every question is answered and marked "got it". (Daily gates stay at 70%.) ☐ KEEP ☐ CHANGE: _____
R3 Streak	Counts Mon–Sat study days. Sunday is rest and never breaks or adds to it. ☐ KEEP ☐ CHANGE: _____
R4 "Need a nudge?" button	No behaviour yet. Ideas: send a reminder email in 1 hour · show the 10-minute version of today · open a motivational note. ☐ pick: _____
R5 Who writes new weeks	Claude writes them in Claude Code, a slice at a time, verified before pushing. ☐ KEEP ☐ CHANGE: _____

☐ **01** Fill in all five rows on paper.

☐ **02** Send Claude:

```
School rules:
R1 pacing: <KEEP | CHANGE: ...>
R2 week quiz: <KEEP | CHANGE: ...>
R3 streak: <KEEP | CHANGE: ...>
R4 nudge button: <your pick>
R5 writing weeks: <KEEP | CHANGE: ...>
```

EXPECTED OUTPUT: Claude moves these from "Open decisions" to "Decided" in CLAUDE.md, and changes code only for rows you marked CHANGE.

03 · test_school_as_learner() DO NOW · weekends

```
PROCEDURE test_school_as_learner(course) → bug reports
```

WHY	You're the first real learner. Things you trip over will trip up every learner after you.
INPUTS	Your phone **and** a laptop. The school: `school.scribsandpixels.com`
TIME	20–40 minutes per session. Repeat any weekend.

Know this first: progress is saved **in this browser only**. A different phone or browser, a private tab, or clearing site data starts you from zero. That's expected until accounts exist.
Checkpoints are strict: once you press **Start checkpoint**, leaving, reloading or closing the page counts as a failed attempt (60-minute cooldown). Start only when you have 10 calm minutes.

- ☐ **01** Open the test site on your phone.
- ☐ **02** Tap one course. Choose one per session: Fullstack, French or Excel.
- ☐ **03** Open the week you're actually on, then today's day.
- ☐ **04** Do the day **as a learner**: read, open the links, tick blocks, do the quiz, use any sandbox, write the log.
- ☐ **05** While doing it, note anything in these 5 bug types:
  - **BROKEN**: an error, a blank screen, a button that does nothing.
  - **WRONG**: a wrong quiz answer, a wrong number, a typo, a dead link.
  - **CONFUSING**: you didn't know what to do next.
  - **UGLY**: overlapping text, too small on the phone, bad colours.
  - **SLOW**: you waited more than 3 seconds.
- ☐ **06** For each bug: take a screenshot, then copy the address bar (the bit after `#/` says exactly which page).
- ☐ **07** Optional, to test checkpoints quickly: tap the round 🧪 button (bottom right of the screen) → **Force checkpoint on this day**. To skip a 60-minute cooldown: **End cooldown now**.
- ☐ **08** `IF` you want to start a course again → 🧪 → **Reset my progress** → **OK**. `ELSE` leave it.
- ☐ **09** Send all bugs from the session in one message, using the bug template in section 10.

EXPECTED OUTPUT: One message to Claude listing your bugs. Claude fixes them and replies with what changed.

ON ERROR: If the whole site is blank, reload once. If it's still blank, try another browser. If it's blank everywhere, send `Site is blank on <device/browser>` with a screenshot.

04 · bring_back_ui_design() WHEN READY

```
PROCEDURE bring_back_ui_design() → design handed to Claude Code
```

WHY	The test site has plain screens. The real look is being designed on claude.ai. Claude Code can only build it once the design is in the project.
INPUTS	Your finished design conversation or artifact on claude.ai.
TIME	15 minutes

- ☐ **01** On claude.ai, open the design conversation.
- ☐ **02** Ask it: `Give me the final design as one HTML file plus a list of every screen and what each button does.`
- ☐ **03** **IF** it produced an artifact → click it → **Share / Publish** (or the link icon) → copy the link. **ELSE** → copy the whole HTML it gave you into a file named `design.html`.
- ☐ **04** In Claude Code, send:

```
Here is the final UI design: <LINK or attach design.html>.
Screens and buttons: <paste the list>.
Build it, replacing the test screens. Keep all content, quizzes and sandboxes
working.
```

EXPECTED OUTPUT: Claude confirms it can read the design and plans the build. Building happens on weekdays.

ON ERROR: If Claude says it can't open the link, attach the HTML file instead (step 3, ELSE branch).

05 · deploy_on_vercel() ✓ DONE 9 Oct

```
PROCEDURE deploy_on_vercel() → a second live copy of the site
```

WHY	Vercel is faster and handles custom domains easily. GitHub Pages keeps working either way.
INPUTS	Your GitHub login (account **VictorAnimasahun**).
TIME	10 minutes

- ☐ **01** Go to `vercel.com` → **Sign Up** → **Continue with GitHub**. Choose the free **Hobby** plan.
- ☐ **02** On the dashboard: **Add New…** → **Project**.
- ☐ **03** Find `scribsandpixels-school` in the list → **Import**.
  IF it isn't listed → **Adjust GitHub App Permissions** → allow the repo → come back.
- ☐ **04** Check the settings. Change only what's different:
  - Framework Preset: `Vite`
  - Build Command: `npm run build`
  - Output Directory: `dist`
  - Environment Variables: **none**. Leave the section empty.
- ☐ **05** Click **Deploy**. Wait for the confetti (about 1–2 minutes).
- ☐ **06** Click the preview image. A new tab opens on a `….vercel.app` address.
- ☐ **07** Check that the home page shows the three courses, then open any day.
- ☐ **08** Send Claude: `Vercel is live at <URL>`

EXPECTED OUTPUT: The same school at a `.vercel.app` address. Every push to `main` redeploys it automatically.

ON ERROR: If the build fails, open the build log, scroll to the first red line, screenshot it and send it to Claude. Don't change settings by guessing.

06 · connect_subdomain() ✓ DONE 9 Oct

```
PROCEDURE connect_subdomain(domain) → school.<yourdomain>
```

WHY	A clean address like `school.scribsandpixels.com` instead of the long GitHub one.
INPUTS	(a) 05 done. (b) A login to the company that holds your domain (the "registrar" or DNS host, e.g. Namecheap, GoDaddy, Cloudflare, Whogohost). (c) The exact domain and the subdomain you want.
TIME	15 minutes, then up to 24 hours for the internet to catch up

- ☐ **01** Decide the address, e.g. `school.<yourdomain>`. Done: `school.scribsandpixels.com`
- ☐ **02** In Vercel: open the project → **Settings** → **Domains** → type the address → **Add**.
- ☐ **03** Vercel shows a record to create. It's usually: Type `CNAME`, Name `school`, Value `cname.vercel-dns.com`. Copy what *it* shows if that's different.
- ☐ **04** Log in to your registrar → find **DNS** / **DNS Records** / **Advanced DNS** for the domain.
- ☐ **05** **Add record** → fill in exactly the Type, Name and Value from step 3. Leave TTL on Automatic → **Save**.
  IF your registrar is Cloudflare → set the orange cloud (proxy) to **grey / DNS only**.
- ☐ **06** Back in Vercel → **Domains**. Wait until the status says **Valid Configuration** (a refresh every few minutes is fine).
- ☐ **07** Open the new address in your phone browser.
- ☐ **08** Send Claude: `Subdomain live: <address>. Make it the main host and update APP_URL references.`

EXPECTED OUTPUT: The school opens at your subdomain with a padlock (https).

ON ERROR: "Invalid configuration" after 24 hours → screenshot the registrar's DNS page and Vercel's Domains page, and send both. **Don't delete other DNS records**: they run your email and main website.

07 · create_supabase_project() ✓ DONE 12 Oct

`PROCEDURE create_supabase_project() → database with tables + 2 keys`

WHY	Supabase will store learners' accounts and progress, so progress follows you across devices. Only useful once Claude wires accounts into the app.
INPUTS	A GitHub login, a password manager, and the Mac with this project.
TIME	25 minutes

- ☐ **01** Go to `supabase.com` → **Start your project** → **Continue with GitHub**.
- ☐ **02** **New project**. Name: `scribsandpixels-school`. Region: **West EU (London)** or **Central EU (Frankfurt)**, the closest to Lagos. Plan: **Free**.
- ☐ **03** Database Password: click **Generate a password** → save it in your password manager as **SECRET** "Supabase DB password" → **Create new project**. Wait about 2 minutes.
- ☐ **04** Open the Terminal and check the Supabase tool runs. Nothing to install: `npx` (part of Node, already on the Mac) fetches it the first time, which takes about a minute.

  ```
  cd ~/Desktop/scribsandpixels-school
  npx supabase --version
  ```

  It prints a version number such as `2.120.0`. If it asks `Ok to proceed? (y)`, type `y` and press Enter.
  Every Supabase command below starts with `npx`. Don't use `brew install supabase`: on this Mac it fails with "Command Line Tools are too outdated".
- ☐ **05** Log in from the Terminal (a browser window opens; approve it):

  ```
  npx supabase login
  ```
- ☐ **06** In Supabase: **Project Settings** (gear icon) → **General** → copy **Project ID** (the "project ref", 20 letters).
- ☐ **07** In the Terminal, go to the project and link it (paste your ref; type the DB password when asked):

  ```
  cd ~/Desktop/scribsandpixels-school
  npx supabase link --project-ref <PROJECT_REF>
  ```
- ☐ **08** Create all the tables (this runs the migration file Claude wrote):

  ```
  npx supabase db push
  ```

  When asked `Do you want to push these migrations?` type `Y` and press Enter.
- ☐ **09** In Supabase: **Table Editor**. You should see tables including `profiles`, `enrollments` and `quiz_attempts`.

☐ **10** Get the two values. Both are safe for the browser.

- **Project URL**: already known, no need to look it up: `https://ookbfjjsnzgbrcgltkot.supabase.co` (it's `https://` + your project ref + `.supabase.co`).
- **Publishable key**: left sidebar → **Project Settings** (gear icon, bottom) → **API Keys**. Copy the key that starts with `sb_publishable_` (click the copy icon next to it).
  IF there's no `sb_publishable_` key → open the **Legacy API Keys** tab and copy **anon** (a long key starting with `eyJ`). Either works.
- **Never** copy `sb_secret_…` or `service_role`: those are secret.

☐ **11** In the Terminal, create the local settings file:

```
cp .env.example .env.local
open -e .env.local
```

Replace the two placeholder values with your URL and anon key → save (⌘S) → close.

☐ **12** Tell Supabase where the school lives, so login emails link to it (not to `localhost`): **Authentication** → **URL Configuration**.

- Site URL: `https://school.scribsandpixels.com` → **Save**
- Redirect URLs → **Add URL**, one at a time: `https://school.scribsandpixels.com/**`, `https://scribsandpixels-school.vercel.app/**`, `http://localhost:5173/**`

☐ **13** Give the live site the same two values: Vercel → the project → **Settings** → **Environment Variables**. Add `VITE_SUPABASE_URL` = your Project URL, and `VITE_SUPABASE_KEY` = the anon / publishable key (environments: all) → **Save**. Then **Deployments** → the top one → ⋯ → **Redeploy**.

☐ **14** Send Claude: `Supabase project created and migrated. .env.local is filled in.` (Don't paste any keys.)

NEVER copy the `service_role` key anywhere except the password manager. It bypasses all security. If it ever leaks: Supabase → API settings → roll (regenerate) it.

EXPECTED OUTPUT: The tables are visible in the Table Editor, and `.env.local` holds two real values.

ON ERROR: If `npx supabase db push` prints red text → copy the whole Terminal output (⌘A, ⌘C) → send it to Claude. Don't run it again repeatedly.

08 · set_up_resend() NEXT

```
PROCEDURE set_up_resend(domain) → verified sending domain + API key
```

WHY	Resend sends the daily nudge and Sunday review emails, from an address on your own domain.
INPUTS	A registrar/DNS login (as in 06) and a password manager.
TIME	20 minutes, then up to a few hours for verification

- ☐ **01** Go to `resend.com` → **Sign up** (the free plan is enough).
- ☐ **02** **Domains** → **Add Domain** → type your domain, `scribsandpixels.com` → choose the region closest to you → **Add**.
- ☐ **03** Resend shows 3–4 DNS records (TXT, MX, DKIM). For **each** one: registrar → DNS → **Add record** → copy Type, Name and Value exactly → **Save**.
- ☐ **04** Back in Resend → **Verify DNS Records**. Repeat every 15 minutes until every row is green / **Verified**.
- ☐ **05** **API Keys** → **Create API Key**. Name: `school-nudges`. Permission: **Sending access** → **Add**.
- ☐ **06** Copy the key **now** (it starts with `re_` and is shown only once) → save it in your password manager as **`SECRET`** "Resend API key".
- ☐ **07** Decide the From address, e.g. `Scribs & Pixels <school@scribsandpixels.com>`. Write it here: _____
- ☐ **08** **`REQUIRED`** before anyone but you can sign in (Supabase's own email only reaches members of your Supabase team): Supabase → **Authentication** → **Emails** → **SMTP Settings** → enable custom SMTP: host `smtp.resend.com`, port `465`, username `resend`, password = your Resend API key, sender = your From address → **Save**.

EXPECTED OUTPUT: The domain shows **Verified** in Resend, and the API key is in your password manager.

ON ERROR: If records won't verify after 24 hours → screenshot Resend's domain page and your DNS page, and send both. A common cause is the registrar adding your domain to the Name automatically (e.g. `send.yourdomain.com.yourdomain.com`): type only the part Resend shows before your domain.

09 · deploy_email_nudges() ON HOLD

`PROCEDURE deploy_email_nudges() → hourly emails running`

WHY	Switches on the daily nudge (Mon–Sat, at each learner's chosen hour, only if they haven't studied) and the Sunday review digest.
INPUTS	07 and 08 done. Your project ref, Resend API key, From address, and the site address (APP_URL: `https://school.scribsandpixels.com`).
TIME	20 minutes

- ☐ **01** Make a cron password in the Terminal and save the output in your password manager as **SECRET** "CRON_SECRET":

```
openssl rand -hex 32
```

- ☐ **02** Set the four secrets. Paste this as **one** command after filling in the four placeholders; keep the quotes:

```
cd ~/Desktop/scribsandpixels-school
npx supabase secrets set RESEND_API_KEY="<re_...>" EMAIL_FROM="Scribs & Pixels
<school@scribsandpixels.com>" APP_URL="https://school.scribsandpixels.com"
CRON_SECRET="<from step 1>"
```

- ☐ **03** Upload the email function:

```
npx supabase functions deploy send-nudges --no-verify-jwt
```

- ☐ **04** Do a safe dry run, which shows what *would* be sent without sending anything (replace both placeholders):

```
curl -s -X POST "https://<PROJECT_REF>.supabase.co/functions/v1/send-nudges?
dry-run" -H "Authorization: Bearer <CRON_SECRET>"
```

  IF it prints JSON (even an empty list) → continue. **ELSE IF** it says `Unauthorized` → the CRON_SECRET doesn't match step 2; redo step 2.

- ☐ **05** In the project folder, open `supabase/setup/schedule-nudges.sql` in TextEdit. **Don't save changes to it**; you'll paste a filled-in copy instead.
- ☐ **06** Copy its whole content. In Supabase → **SQL Editor** → **New query** → paste.
- ☐ **07** In the pasted text only, replace `<project-ref>` with your project ref and `<CRON_SECRET>` with your cron secret.
- ☐ **08** Click **Run**.
- ☐ **09** Check it's scheduled: new query → `select jobname, schedule from cron.job;` → **Run**. You should see `send-nudges` with `0 * * * *`.
- ☐ **10** Send Claude: `Nudges deployed and scheduled. Dry run returned <paste the output>.`

EXPECTED OUTPUT: The cron job is listed and the dry run returns JSON. Real emails start once learners have accounts.

ON ERROR: If the SQL editor says `secret already exists`, you ran the script twice. Send Claude the message; don't try to delete vault secrets yourself.

10 · Appendix: words, tools and message templates

Message template: error

```
ERROR in procedure <number + name>, step <number>.
What I did: <one sentence>
What I expected: <from EXPECTED OUTPUT>
What I saw: <exact text or "see screenshot">
Device/browser: <e.g. iPhone 13 Safari>
```

Message template: bugs from a test session

```
TEST SESSION <date>, course <Fullstack | French | Excel>, device <...>
1. [BROKEN|WRONG|CONFUSING|UGLY|SLOW] page #/<address after #/>
   What happened: ...
   What I expected: ...
2. ...
```

Words

Repo	The project's folder on GitHub: `github.com/VictorAnimasahun/scribsandpixels-school`. Claude pushes every finished change to its `main` branch.
Deploy	Putting the latest version on the internet. GitHub Pages does it automatically about 2 minutes after each push.
DNS / record	The internet's address book. A CNAME record says "this name points to that server".
Registrar	The company you bought the domain from. That's where DNS records are edited.
Migration	A file that creates database tables. Running it twice is safe for Supabase; it skips what's done.
Secret / key	A password for a service. "anon/publishable" keys are safe in the browser. "service_role", the Resend API key, CRON_SECRET and the DB password are **SECRET**.
Edge function	A small program that runs on Supabase's servers. Here: `send-nudges`, the email sender.
Cron	A timer. `0 * * * *` means "every hour, on the hour".
Dry run	A rehearsal that shows what would happen without doing it.

Where to find things

The school	`school.scribsandpixels.com` (main; Vercel). Copies: `scribsandpixels-school.vercel.app`, `victoranimasahun.github.io/scribsandpixels-school`
To-do list (Claude's)	`TODO.md` in the repo

Project rules	`CLAUDE.md` in the repo
Phase 2 draft	`src/content/courses/fullstack-ml/phase-2-plan.md`
This document's source	`docs/your-tasks/your-tasks.html`. Ask Claude to update it when tasks change.