Incident report analysis

Instructions

As you continue through this course, you may use this template to record your findings after completing an activity or to take notes on what you've learned about a specific tool or concept. You can also use this chart as a way to practice applying the NIST framework to different situations you encounter.

Summary	On this day, the network of the company turned down for about two hours. The cybersecurity analysts found that a malicious actor had sent a flood of ICMP pings into the company's network through an unconfigured firewall. The network services stopped responding due to an incoming flood of ICMP packets. To respond, the incident management team blocked the incoming ICMP packets from the source IP and restored critical network services.
Identify	The incident management team recognizes after the DoS attack and blocks the incoming ICMP packets. This is a common attack from an unknown source. It's called a smurf attack, some hacker sniffs an authorized user's IP address then floods the network with packets.
Protect	The team has implemented new protection policies to prevent future attacks: a new firewall rule to limit the rate of incoming ICMP packets. And an IPS system to filter out some ICMP traffic based on suspicious characteristics.
Detect	To detect new incoming attacks in the future, the team will use Source IP address verification on the firewall to check for spoofed IP on incoming ICMP packets and Network monitoring software to detect abnormal traffic patterns.
Respond	To respond the tools will automatically block the incoming ICMP attacks and also unknown IPs that are trying to attack. The procedures it's to block the IP, analyse and report to the management team. They will attempt to restore any critical systems and services that were disrupted by the event.
Recover	In this case there is no information to recover immediately, only need to restore

	the connections (critical network services should be restored first) . After implementing the tools, the network will be more safe to return to the normal intern process of the company. Once the flood of ICMP packets have timed out, all non-critical network systems and services can be brought back online.

Reflections/Notes: In the future if tools don't work just respond to the attack by blocking the incoming ICMP packets, stopping all non-critical network services offline, and restore critical network services.