```
...or Lam\Desktop\Lab 1\Test Program 4\Test Program 4\main.c
```

```
* Test Program 4.c
 * Created: 2/11/2020 7:18:05 PM
 * Author : Victor Lam
#include <avr/io.h>
#include <util/delay.h>
int main(void) {
    /* Replace with your application code */
    ADMUX = (1 << REFS0) | (1 << MUX2) | (1 << MUX0);
    ADCSRA = (1 < ADEN) | (1 < ADSC) | (1 < ADPS2) | (1 < ADPS1) | (1 < ADPS0);
    DDRB = 0b00000001;
    while (1) {
        PORTB = 0b000000000;
        uint16_t adc = ADC;
        if ((adc >= 0x0000) & (adc <= 0x0028)) {
            PORTB = 0b00000001;
            _delay_us(3822.5);
            PORTB = 0b000000000;
            _delay_us(3822.5);
        } else if ((adc >= 0x0029) & (adc <= 0x0051)) {</pre>
            PORTB = 0b00000001;
            _delay_us(3607.5);
            PORTB = 0b00000000;
            _delay_us(3607.5);
        } else if ((adc >= 0x0052) & (adc <= 0x007A)) {
            PORTB = 0b00000001;
                                                                                           P
            _delay_us(3405.5);
            PORTB = 0b00000000;
            _delay_us(3405.5);
        } else if ((adc >= 0x007B) & (adc <= 0x00A3)) {</pre>
            PORTB = 0b00000001;
            _delay_us(3205);
            PORTB = 0b000000000;
            _delay_us(3205);
        } else if ((adc >= 0x00A4) & (adc <= 0x00CC)) {</pre>
            PORTB = 0b00000001;
            _delay_us(3033.5);
            PORTB = 0b000000000;
            _delay_us(3033.5);
```

```
} else if ((adc >= 0x00CD) & (adc <= 0x00F5)) {</pre>
    PORTB = 0b00000001;
    _delay_us(2863.5);
   PORTB = 0b00000000;
    _delay_us(2863.5);
} else if ((adc >= 0x00F6) & (adc <= 0x011E)) {</pre>
   PORTB = 0b00000001;
    _delay_us(2702.5);
   PORTB = 0b000000000;
    _delay_us(2702.5);
} else if ((adc >= 0x011F) & (adc <= 0x0147)) {</pre>
   PORTB = 0b00000001;
    _delay_us(2551);
   PORTB = 0b000000000;
    _delay_us(2551);
} else if ((adc >= 0x0148) & (adc <= 0x0170)) {</pre>
    PORTB = 0b00000001;
    _delay_us(2407);
   PORTB = 0b000000000;
    _delay_us(2407);
} else if ((adc >= 0x0171) & (adc <= 0x0199)) {</pre>
    PORTB = 0b00000001;
    _delay_us(2273);
   PORTB = 0b000000000;
    _delay_us(2273);
} else if ((adc >= 0x019A) & (adc <= 0x01C2)) {</pre>
    PORTB = 0b00000001;
    _delay_us(2145.5);
    PORTB = 0b000000000;
    _delay_us(2145.5);
} else if ((adc >= 0x01C3) & (adc <= 0x01EB)) {</pre>
    PORTB = 0b00000001;
    _delay_us(2025);
   PORTB = 0b00000000;
    _delay_us(2025);
} else if ((adc >= 0x01EC) & (adc <= 0x0214)) {
    PORTB = 0b00000001;
    _delay_us(1911);
   PORTB = 0b00000000;
    _delay_us(1911);
} else if ((adc >= 0x0215) & (adc <= 0x023D)) {
    PORTB = 0b00000001;
    _delay_us(1803.5);
   PORTB = 0b00000000;
    _delay_us(1803.5);
} else if ((adc >= 0x023E) & (adc <= 0x0266)) {</pre>
    PORTB = 0b00000001;
    _delay_us(1702.5);
   PORTB = 0b000000000;
```

```
_delay_us(1702.5);
} else if ((adc >= 0x0267) & (adc <= 0x028F)) {
    PORTB = 0b00000001;
    _delay_us(1607);
    PORTB = 0b000000000;
    _delay_us(1607);
} else if ((adc >= 0x0290) & (adc <= 0x02B8)) {
    PORTB = 0b00000001;
    _delay_us(1517);
   PORTB = 0b000000000;
    _delay_us(1517);
} else if ((adc >= 0x02B9) & (adc <= 0x02E1)) {</pre>
    PORTB = 0b00000001;
    _delay_us(1431.5);
   PORTB = 0b000000000;
    _delay_us(1431.5);
} else if ((adc >= 0x02E2) & (adc <= 0x030A)) {
    PORTB = 0b00000001;
    _delay_us(1351);
   PORTB = 0b000000000;
    _delay_us(1351);
} else if ((adc >= 0x030B) & (adc <= 0x0333)) {
    PORTB = 0b00000001;
    delay us(1275.5);
   PORTB = 0b000000000;
    _delay_us(1275.5);
} else if ((adc >= 0x0334) & (adc <= 0x035C)) {
    PORTB = 0b00000001;
    _delay_us(1203.5);
    PORTB = 0b000000000;
    _delay_us(1203.5);
} else if ((adc >= 0x035D) & (adc <= 0x0385)) {
   PORTB = 0b00000001;
    _delay_us(1136);
   PORTB = 0b000000000;
    delay us(1136);
} else if ((adc >= 0x0386) & (adc <= 0x03AE)) {
   PORTB = 0b00000001;
    _delay_us(1072.5);
   PORTB = 0b000000000;
    _delay_us(1072.5);
} else if ((adc \geq 0x03AF) & (adc \leq 0x03D7)) {
   PORTB = 0b00000001;
    _delay_us(1012.5);
   PORTB = 0b000000000;
    _delay_us(1012.5);
} else if ((adc >= 0x03D8) & (adc <= 0x0400)) {</pre>
   PORTB = 0b00000001;
    _delay_us(955);
```

```
PORTB = 0b00000000;

_delay_us(955);

}

while (!(ADCSRA & 0b01000000)) {

    ADCSRA |= (1<<ADSC);

}

}
```