

# Introduction

# Namespace QuickKit.AspNetCore.Attributes

## Classes

### [HttpAddKit](#)

Represents an attribute that is used to add a resource using HTTP POST method.

Does not define the data.

Does not define the response.

Uses the naming convention from [ADD](#)

### [HttpDeleteKit](#)

Represents an attribute that specifies that an action method should be accessible via HTTP DELETE requests.

Does not define the data.

Does not define the response.

Uses the naming convention from [DELETE](#)

### [HttpGetAllKit](#)

Represents an attribute that specifies an HTTP GET request to retrieve all data.

Does not define the data.

Does not define the response.

Uses the naming convention from [GET ALL](#)

### [HttpGetByIdKit](#)

Represents an attribute that specifies an HTTP GET request for retrieving a resource by its ID.

Does not define the data.

Does not define the response.

Uses the naming convention from [GET BY ID](#)

### [HttpGetTestEndPointKit](#)

Represents an attribute that specifies an HTTP GET for test endpoint.

Does not define the data.

Does not define the response.

Uses the naming convention from [TEST](#)

### [HttpUpdateKit](#)

Represents an attribute that is used to decorate a method as an HTTP update endpoint.

Does not define the data.

Does not define the response.

Uses the naming convention from [UPDATE](#)