

Namespace QuickKit.AspNetCore.Attributes

Classes

▼ Filter by title

HttpAddKit (QuickKit.AspNetCore.Attributes.HttpAddKit.html)

Represents an attribute that is used to add a resource using HTTP POST method.

Attributes

(QuickKit.AspNetCore.Attributes.HttpAddKit.html)

Does not define the data.

HttpAddKit

Does not define the response.

(QuickKit.AspNetCore.Attributes.HttpAddKit.html)

Uses the naming convention from ADD

HttpDeleteKit

(QuickKit.AspNetCore.Constants.ENDPOINT_NAME_CNT_KIT.html#QuickKit_AspNetCore_Constants_ENDPOINT_NAME_CNT_KIT_ADD)

HttpGetAllKit

(QuickKit.AspNetCore.Attributes.HttpDeleteKit.html)

HttpGetByIdKit

(QuickKit.AspNetCore.Attributes.HttpDeleteKit.html)

HttpDeleteKit (QuickKit.AspNetCore.Attributes.HttpDeleteKit.html)

Represents an attribute that specifies that an action method should be accessible via HTTP DELETE requests.

HttpDeleteKit

(QuickKit.AspNetCore.Attributes.HttpDeleteKit.html)

Does not define the data.

HttpUpdateKit

Does not define the response.

(QuickKit.AspNetCore.Attributes.HttpDeleteKit.html)

+ **QuickKit.AspNetCore.**

Uses the naming convention from DELETE

(QuickKit.AspNetCore.Constants.ENDPOINT_NAME_CNT_KIT.html#QuickKit_AspNetCore_Constants_ENDPOINT_NAME_CNT_KIT_DELETE)

Configuration

(QuickKit.AspNetCore.Configuration.HttpDeleteKit.html)

+ QuickKit.AspNetCore.

HttpGetAllKit (QuickKit.AspNetCore.Attributes.HttpGetAllKit.html)

Constants

Represents an attribute that specifies an HTTP GET request to retrieve all data.

(QuickKit.AspNetCore.Constants.HttpGetAllKit.html)

Does not define the data.

+ **QuickKit.AspNetCore.**

Does not define the response.

Controllers

(QuickKit.AspNetCore.Controllers.HttpGetAllKit.html)

Uses the naming convention from GET_ALL

(QuickKit.AspNetCore.Constants.ENDPOINT_NAME_CNT_KIT.html#QuickKit_AspNetCore_Constants_ENDPOINT_NAME_CNT_KIT_GET_ALL)

+ **QuickKit.AspNetCore.**

(QuickKit.AspNetCore.Constants.ENDPOINT_NAME_CNT_KIT_GET_ALL)

Middlewares.Requests

(QuickKit.AspNetCore.Middlewares.Requests.HttpGetAllKit.html)

HttpGetByIdKit (QuickKit.AspNetCore.Attributes.HttpGetByIdKit.html)

+ **QuickKit.AspNetCore.**

Represents an attribute that specifies an HTTP GET request for retrieving a resource by its ID.

Middlewares.Types

(QuickKit.AspNetCore.Middlewares.Types.HttpGetByIdKit.html)

+ **QuickKit.Cmd**

Does not define the response.

(QuickKit.Cmd.Cmd.html)

Uses the naming convention from GET_BY_ID

(QuickKit.AspNetCore.Constants.ENDPOINT_NAME_CNT_KIT.html#QuickKit_AspNetCore_Constants_ENDPOINT_NAME_CNT_KIT_GET_BY_ID)

+ **QuickKit.Cmd.Enums**

(QuickKit.Cmd.Enums.Cmd.html)

HttpGetTestEndPointKit

(QuickKit.AspNetCore.Attributes.HttpGetTestEndPointKit.html)

Represents an attribute that specifies an HTTP GET for test endpoint.

Does not define the data.

Does not define the response.

Uses the naming convention from TEST

- **QuickKit.AspNetCore.Attributes**
(QuickKit.AspNetCore.Constants.ENDPOINT_NAME_CNT_KIT.html#QuickKit_AspNetCore_Constants_ENDPOINT_NAME_CNT_KIT_TEST)

(QuickKit.AspNetCore.Attributes

HttpUpdateKit (QuickKit.AspNetCore.Attributes.HttpUpdateKit.html)

Represents an attribute that specifies an HTTP update endpoint.

HttpDeleteKit

Does not define the data.

(QuickKit.AspNetCore.Attributes.Ht

Does not define the response.

(QuickKit.AspNetCore.Attributes.Ht

Uses the naming convention from UPDATE

HttpGetByIdKit
(QuickKit.AspNetCore.Constants.ENDPOINT_NAME_CNT_KIT.html#QuickKit_AspNetCore_Constants_ENDPOINT_NAME_CNT_KIT_UPDATE)
HttpGetTestEndPointKit

(QuickKit.AspNetCore.Attributes.Ht

HttpUpdateKit

(QuickKit.AspNetCore.Attributes.Ht

+ QuickKit.AspNetCore.

Configuration

(QuickKit.AspNetCore.Configu

+ QuickKit.AspNetCore.

Constants

(QuickKit.AspNetCore.Constan

+ QuickKit.AspNetCore.

Controllers

(QuickKit.AspNetCore.Controll

+ QuickKit.AspNetCore.

Middlewares.Requests

(QuickKit.AspNetCore.Middlew

+ QuickKit.AspNetCore.

Middlewares.Types

(QuickKit.AspNetCore.Middlew

+ QuickKit.Cmd

(QuickKit.Cmd.html)

+ QuickKit.Cmd.Enums

(QuickKit.Cmd.Enums.html)