

50.15A

**University of Cape Town**  
**Department of Computer Science**

**Computer Science CSC1010H**

**Class Test 2**

**Wednesday, 20 August 2014**

Marks: 35

Time: 40 minutes

- Approximate marks per question are shown in brackets
- The use of calculators is permitted

NAME: Surname  
Initials  
ML

STUDENT NO: GMBMN0001 COURSE CODE: CSC 1010H

This paper consists of 6 questions and 6 pages (including this cover page).

Mark Allocation							
Question	Marks	Internal	External	Question	Marks	Internal	External
1	5			5	4		
2	7			6	6		
3	6						
4	7						
Total				Total			
Grand Total Final Mark							
Internal Examiner:				External Examiner:			

**Question 1. [5 marks]**

Consider the following problem. Answer it appropriately.

The Petersens have recently moved to a new town and are arranging a surprise birthday party for their son Andre, and have invited three families from the neighbourhood, the Smiths, the Januarys and the Hectors. They plan to make up party packets for the kids to take home after the party, blue for boys and pink for girls.

Being super organised, Mrs Petersen with the help of Mr Petersen wants to determine how many of each colour party packet she needs to buy, and also how many of each colour she needs to put aside for each family.

They sit down and come up with the following information. Mrs Petersen remembers that the Hectors have a "pigeon pair", i.e. a boy and a girl. Mr Petersen recalls that the Januarys only have a set of identical twin boys. Mrs Petersen notes that she's only ever noticed two girls from these local families to come over to play. Mr Petersen notes that the Smiths have three children, since the family fits nicely into their family sedan when they go out.

You happen to be visiting the Petersens at this point, and want to impress them with the problem solving skills you've learnt at university. Using the information they've provided, determine how many of each colour party packet they need to buy and how many of each colour they need to allocate to each family and what the total number of party packets are.

Use a diagram to show how you solve the problem.

	a) Smiths	b) Januarys	c) Hectors	
Boys (a)	2	2	1	$y = 2$
Girls (y)	1	0	1	2
				Smith = 3
				Hector = 2
				Jan = 2

  

$$y = a + b + c$$

$$2 = a + 0 + 1$$

$$a = 1$$

Smiths have one girl & 2 boys

The Petersens have to buy 7 party packets, 5 blue and 2 pink. 1 pink & 2 blue packets for the Smiths, 2 blue packets for the Januarys and 1 blue and 1 pink for the Hectors.

[5]

**Question 2. [7 marks]**

Answer the following questions:

- a) When using debugging features in an IDE, what should the user typically do once execution has reached the breakpoint?

Step over your code, try to find/locate,  
the error and devise a solution having a  
trace of your variables and once the error is detected, [2]  
fix it.

- b) When a new module has been defined, how do you ensure that it is accessible and can be imported into a program with no problems, i.e. "import newmodule" works?

It must be saved in the python Lib folder or in the [1]  
same folder as the programme.

- c) Explain what happens in memory when Python makes successive recursive function calls.

The memory stacks/saves copies of the  
function during recursive invokes/calls. [1]

Indicate whether the following statements are True or False.

- d) The accepted Python coding convention for module names is long descriptive names in uppercase.

False [1]

- e) Curly brackets {} are used to enclose parameters to a function.

False [1]

- f) The print() function can be used to write to a file.

True [1]

**Question 3. [6 marks]**

Write a Python function called `draw_line()` which draws a horizontal line of characters. The `draw_line()` function should take two parameters, with the first being the size of the line (i.e. the number of characters) and the second parameter being the character with which to draw the line. This character parameter should have a default value of an asterisk (\*).

Calling the `draw_line()` function with the following parameters should produce the corresponding output:

<code>draw_line(5)</code>	<i>produces</i>	*****
<code>draw_line(6, '\$')</code>		\$\$\$\$\$\$

```
def draw_line(n, char = "*"):
    print((char)*n)
```

[6]

**Question 4. [7 marks]**

Consider the following recursive function definition:

```
def do_this(stuff):
    if len(stuff) == 0:
        return ""
    else:
        return str(stuff[0] * 2) + do_this(stuff[1:])
```

a) What datatype can the parameter to this function be?

→ A string

→ A list or a tuple

[2]

b) What is the base case for this function?

if nothing is entered (stuff length = 0), it must return an empty string.

[1]

c) Based on the `do_this()` function definition, what will the following statements display?

i. `print(do_this([1,2,3]))`

2+4+6 = 12 [2]

ii. `print(do_this("123"))`

"1"\*2 + "2"\*2 + "3"\*2 = "112233" [2]

**Question 5. [4 marks]**

Consider the following Python program and answer the questions below:

```
def main():
    f = open('to_do_list.txt', 'a')
    while True:
        thing_to_do = input('Enter thing to do:')
        if thing_to_do == 'done': break
        else:
            f.write(thing_to_do + '\n')
    f.close()
```

`main()`

a) What is the name of the file created?

to\_do\_list (textfile) [1]

b) What mode is the file created in?

append mode [1]

c) Looking at the code, how does the user terminate the program?

The user terminates the program by entering "done" or the word done. [1]

d) How will the information that the user enters be written in the file?

Each piece of information entered will be written on a new line. [1]

**Question 6. [6 marks]**

Consider the following definition of the *classify\_weight()* function. Specify test cases which thoroughly test the function, using equivalence classes and boundary value. For each test case specify whether it is an equivalence class value or a boundary value.

```
# classifies weight in kgs
def classify_weight(w):
    if 0 < w <= 60:
        return "light"
    elif 60 < w <= 120:
        return "heavy"
    else:
        return "error"
```

---

Equivalence classes

→ Category values: 50, 100

→ Errorneous values: 160, -1

Boundary values

→ On boundary values: 60, 120

→ Below Boundary values: 50, -1, 100

→ Above boundary values: 70, 50,

[6]