



Energy Access Incorporated

Intelligent Charging Series



Charge rate	500mA - 3000mA
Charge range	2V to 20V
Input connector	2.5mm center positive
Weight	6oz (171g)
Material	ABS GSM
Color	Black
Dimensions	3.63" x 2.27" x 1.85" (92mm x 58mm x 47mm)

- Target Batteries:**
- Lithium Ion
 - Nickle Metal Hydride
 - Nickle Cadmium
 - Lead Acid



The standard ICS includes

Charger
8" output cable with stripped and tinned leads

Optional components

2-Bay Housing
PS2524 - universal power supply
Line cord (specify country)
VA2524 - vehicle power adapter

Charger Kit

Product Part Numbering

Series	-	Current	-	Voltage	-	Power Supply	-	Line Cord
<input type="text"/>		<input type="text"/>		<input type="text"/>		<input type="text"/>		<input type="text"/>
ICS		1000 1500 2000 3000		04200 08400 12600 16800 0DTDV		PS2524 VA2524		LCUL - North America LCUK - United Kingdom LCEC - European Community LCJA - Japan LCAS - Australia LCCH- China

**Agency
Approvals:**



Class B
FC
Cispr 22



Datasheet

Models

ICS-XXXX-XXXXX

Charge rates from 500mA to 3000mA
Single cell to 12 cells in series

Target Batteries: Lithium-Ion, Lithium-Polymer, Nickel Metal Hydride, Nickel Cadmium, and Sealed Lead Acid



ICS-1002

Target Batteries: “Dumb” NiMH, NiCd, and Lithium-Ion batteries with a standard 5-blade connector.
Typical packs include: Type 15, 17, 30, 35, 36, 201, 202, 204



ICS-1502

Target Batteries: SLA and NiMH



ICS-3010-XXXXX

PB5 - Power Base
Charges 10 batteries

