

SANITIZATION VERIFIED

MEDIA DETAILS	
Device path	\\.\PhysicalDrive7
Model	Example NVMe SSD (sample device)
Serial number	SAMPLE00000001
Device ID (EUI-64 / WWN, as reported by Windows)	SAMPLE-0000-0001
Firmware revision	(not reported)
Capacity	8.4 MB (8,388,608 bytes)
Bus type	Nvme
Media type	SSD (flash) – Confirmed
Partition layout	Unknown
Volumes (pre-wipe)	None mounted
Encrypted volumes detected (pre-wipe)	None detected
Hidden areas (HPA/DCO)	Not applicable (no HPA/DCO on this bus)
Logical sector size	512 bytes
SANITIZATION PROCESS	
Method	NVMe Firmware Purge (Sanitize / Format)
Sanitization category	PURGE (NIST SP 800-88 Rev. 1) – firmware sanitize
Standards reference	NIST SP 800-88 Rev. 1 – Purge (firmware sanitize, NVMe Sanitize / Format NVM). Consistent with CSE ITSP.40.006. Purge addresses reallocated and over-provisioned areas that overwriting (Clear) cannot reach.
Firmware command	NVMe Sanitize block erase – physical erase, reads zero, covers the whole medium including over-provisioned/spare (NIST 800-88 Purge)
Started	2026-07-10 20:57:26 UTC (2026-07-10 13:57:26 -07:00 local)
Completed	2026-07-10 20:57:27 UTC (2026-07-10 13:57:27 -07:00 local)
Duration	00:00:00
Operator	Sample Operator
Arming method	Serial number verified by operator
Media advisory	This device is solid-state media. Overwriting achieves NIST SP 800-88 Rev. 1 CLEAR, not PURGE: wear-leveled and overprovisioned areas of flash media are not addressed by overwrites. For PURGE, use firmware-level sanitization (ATA SECURE ERASE / NVMe Sanitize).
VERIFICATION	
Final readable state	CONFIRMED 0x00 (zeros): read-back at 100% (full read-back) sampled 8 of 8 region(s) – the first and last always included – and found only zero bytes.

SANITIZATION VERIFIED

Excluded from the state above (bad sectors)	None – every readable sampled region is covered by the state above.
Method	Advisory spot check – post-sanitize read-back sampling (evidence of sanitization; NOT the verification)
Finding	All 16 spot-check regions read as constant 0x00 – consistent with a block erase.
Spot-check regions	16
Unreadable regions	0
Note	For a firmware Purge no known pattern is written, so this spot check records evidence of sanitization rather than a byte-for-byte pattern comparison. The authoritative result is the 'Final readable state' row, produced by the full verification read-back – its region count comes from that separate, larger sampling.

EXCEPTIONS

Skipped bad sectors	None
---------------------	------

CERTIFICATE INTEGRITY

Certificate ID	483F1A3F-C4BA-4B61-90EE-A363DB7DE5E0
Tool	ProofWipe 1.4.0 (sha:09d5c96 · built 2026-07-10 20:57:10Z)
Session log entries	14
Log SHA-256 (tamper evidence)	ad906c90369389070cd0c58802409f1e864d61132c7ba82071e66cb150ff4211
Note	The SHA-256 digest covers the complete session log in canonical form. Recompute it over the retained log to detect tampering.

Operator signature

Date