

Visual Rules

CSS declarations

In CSS, a *declaration* is the key-value pair of a CSS property and its value. CSS declarations are used to set style properties and construct rules to apply to individual or groups of elements. The property name and value are separated by a colon, and the entire declaration must be terminated by a semi-colon.

```
/*  
CSS declaration format:  
property-name: value;  
*/  
  
/* CSS declarations */  
text-align: center;  
color: purple;  
width: 100px;
```

Font Size

The `font-size` CSS property is used to set text sizes. Font size values can be many different units or types such as pixels.

```
font-size: 30px;
```

Background Color

The `background-color` CSS property controls the background color of elements.

```
background-color: blue;
```

Opacity

The `opacity` CSS property can be used to control the transparency of an element. The value of this property ranges from `0` (transparent) to `1` (opaque).

```
opacity: 0.5;
```

Font Weight

The `font-weight` CSS property can be used to set the weight (boldness) of text. The provided value can be a keyword such as `bold` or `normal`.

```
font-weight: bold;
```

Text Align

The `text-align` CSS property can be used to set the text alignment of inline contents. This property can be set to these values: `left`, `right`, or `center`.

```
text-align: right;
```

CSS Rule Sets

A CSS rule set contains one or more selectors and one or more declarations. The selector(s), which in this example is `h1`, points to an HTML element. The declaration(s), which in this example are `color: blue` and `text-align: center` style the element with a property and value. The rule set is the main building block of a CSS sheet.

Setting foreground text color in CSS

Using the `color` property, foreground text color of an element can be set in CSS. The value can be a valid color name supported in CSS like `green` or `blue`. Also, 3 digit or 6 digit color code like `#22f` or `#2a2aff` can be used to set the color.

```
h1 {  
  color: blue;  
  text-align: center;  
}
```

```
p {  
  color : #2a2aff ;  
}  
  
span {  
  color : green ;  
}
```

Resource URLs

In CSS, the `url()` function is used to wrap resource URLs. These can be applied to several properties such as the `background-image`.

```
background-image:  
url("../resources/image.png");
```

Background Image

The `background-image` CSS property sets the background image of an element. An image URL should be provided in the syntax `url("moon.jpg")` as the value of the property.

```
background-image: url("nyan-cat.gif");
```

Font Family

The `font-family` CSS property is used to specify the typeface in a rule set. Fonts must be available to the browser to display correctly, either on the computer or linked as a web font. If a font value is not available, browsers will display their default font. When using a multi-word font name, it is best practice to wrap them in quotes.

```
h2 {  
  font-family: Verdana;  
}  
  
#page-title {  
  font-family: "Courier New";  
}
```

Color Name Keywords

Color name keywords can be used to set color property values for elements in CSS.

```
h1 {  
  color: aqua;  
}  
  
li {  
  color: khaki;  
}
```