A Reproducible Benchmarking Framework for Evaluating TLS and mTLS Performance Overhead in Zero Trust-Aligned Apache Kafka Deployments

Nick Efe Oni

Supervisor: Mahshid Delavar

A report submitted in fulfilment of the requirements for the degree of MEng in Software Engineering

in the

School of Computer Science

April 29, 2026

Declaration

All sentences or passages quoted in this report from other people's work have been specifically acknowledged by clear cross-referencing to author, work and page(s). Any illustrations that are not the work of the author of this report have been used with the explicit permission of the originator and are specifically acknowledged. I understand that failure to do this amounts to plagiarism and will be considered grounds for failure in this project and the degree examination as a whole.

Name: Nick Efe Oni

Signature: Nick Efe Oni

Date: April 29, 2026

Abstract

an abstract is provided to give a brief overview and summary of the core topics, arguments, and findings . Because it must summarize your entire project—including your final benchmarking results from Chapter 5 and your final conclusions from Chapter 7—you should write the abstract at the very end of the process, once the rest of your dissertation is completely finished.

Contents

1 Introduction **1**
1.1 Background and Motivation . . . 1
1.2 Problem Statement . . . 2
1.3 Research Aim and Objectives . . . 2
1.4 Research Question . . . 3
1.5 Artefact Overview . . . 3
1.6 Dissertation Structure . . . 4

2 Literature Review **5**
2.1 Apache Kafka & Distributed Streaming Systems . . . 5
2.2 Performance in Kafka Systems . . . 7
2.3 Security Mechanisms in Kafka . . . 9
2.4 Zero Trust Architecture . . . 11
2.5 Zero Trust in Distributed Streaming Systems . . . 12
2.6 TLS/mTLS Performance Overhead . . . 14
2.7 Benchmarking Methodologies . . . 15
2.8 Synthesis & Research Gap . . . 16

3 Design, Implementation, and Testing **19**
3.1 Chapter Overview . . . 19
3.2 Artefact Requirements . . . 19
3.3 System Architecture . . . 21
3.4 Reproducing the Artefact Environment . . . 23
3.4.1 Infrastructure provisioning . . . 23
3.4.2 Benchmark-client preparation . . . 23
3.4.3 Kafka deployment . . . 23
3.4.4 Benchmark-plan generation . . . 23
3.4.5 Campaign execution . . . 24
3.4.6 Result processing . . . 24
3.5 Infrastructure Provisioning . . . 26
3.6 Kafka Cluster Deployment . . . 27
3.7 Security Mode Design . . . 28

3.8 Benchmark Workload Design . . . 29
3.9 Factorial Experiment Design . . . 30
3.10 Execution and Orchestration . . . 31
3.11 Telemetry and Metric Collection . . . 34
3.12 Result Processing and Export . . . 35
3.13 Fault Tolerance and Idempotency . . . 37
3.14 Testing and Validation . . . 38
3.15 Chapter Summary . . . 40

4 Results and Discussion 41
4.1 Chapter Overview . . . 41
4.2 Result-Set Completion and Validity . . . 41
4.3 Comparison Method . . . 42
4.4 Producer Throughput Results . . . 44
4.5 Producer Latency Results . . . 49
4.6 Host Telemetry Results . . . 53
4.7 Consumer Validation Results . . . 54
4.8 Discussion . . . 56
4.9 Chapter Summary . . . 57

5 Evaluation, Conclusions, and Further Work 58
5.1 Chapter Overview . . . 58
5.2 Evaluation Against Objectives . . . 58
5.3 Summary of Findings . . . 60
5.4 Methodological Contribution . . . 61
5.5 Limitations . . . 62
5.6 Further Work . . . 63
5.7 Answer to the Research Question . . . 64
5.8 Chapter Summary . . . 65

Appendices 68

A Ethics and GenAI Declaration 69
A.1 Ethics Statement . . . 69
A.2 Generative AI Declaration . . . 69
A.2.1 Acknowledge . . . 69
A.2.2 Describe . . . 70
A.2.3 Evidence . . . 70
A.2.4 Declaration . . . 71

B Artefact Configuration **72**
B.1 Configuration Files 72
B.2 Producer Factorial Campaign 73
B.3 Security Mode Configuration 74
B.4 Validity Constraints 75
B.5 Consumer Validation Slice 75

C Result Schema **77**
C.1 Run-Level Output 77
C.2 Metadata Fields 78
C.3 Parsed Result Fields 79
C.4 Host Telemetry Fields 79
C.5 Result-Set Output 80
C.6 Metric Interpretation Caveat 81

D Additional Result Tables **82**
D.1 Producer Campaign Completion Tables 82
D.2 Matched Security-Mode Comparison Tables 83
D.3 Producer Throughput Tables 84
D.4 Producer Latency Tables 85
D.5 Host Telemetry Tables 86
D.6 Consumer Validation Tables 87
D.7 Top Overhead Cases 88

E Repository and Reproducibility Notes **89**
E.1 Repository Structure 89
E.2 Configuration-Driven Execution 90
E.3 Deployment Reproducibility 91
E.4 Checkpointing and Resumability 91
E.5 Result Traceability 92
E.6 Generated State and Version Control 92
E.7 Rerunning the Artefact 92
E.8 Reproducibility Limitations 93

List of Figures

2.1 Simplified Apache Kafka architecture showing producer applications publishing events to a cluster of brokers, and consumer applications pulling events from the cluster. Figure generated using ChatGPT image generation from a prompt requesting a producer-broker-consumer Apache Kafka architecture diagram, April 2026. 7

2.2 Comparison of Kafka data movement under plaintext, TLS, and mTLS. Plaintext can use page-cache-backed `sendfile` zero-copy transfer, while TLS and mTLS require user-space cryptographic processing that prevents this path. 9

2.3 Kafka security data path showing how TLS/mTLS, certificate-based identity verification, principal mapping, and ACL authorisation are applied before Kafka request processing, with broker-to-broker communication also secured where configured. 11

2.4 Conceptual Zero Trust control model for a distributed streaming pipeline, illustrating how mTLS, policy enforcement, least-privilege access, and continuous monitoring are applied across producer, broker, stream-processing, and consumer components within a segmented trust boundary. 13

3.1 System architecture of the Kafka benchmarking artefact, showing local orchestration, Terraform-provisioned AWS infrastructure, private Kafka traffic, SSH control paths, broker instances, benchmark client, and result collection. 22

3.2 Tutorial-style reproduction workflow for the benchmarking artefact, showing how infrastructure provisioning, deployment, execution, checkpointing, and result processing are connected. 25

3.3 Benchmark execution pipeline from JSON configuration to dissertation-ready result exports. 33

3.4 Result directory and data-flow schema showing how raw per-run logs, metadata, telemetry, campaign state files, parsed results, aggregated summaries, and dissertation-ready exports are connected. 36

4.1 Matched producer throughput comparison across plaintext, TLS, and mTLS. 46

4.2 Producer throughput overhead by message size under matched security modes. 47

4.3 Producer throughput overhead by producer count under matched security modes. 48
4.4 Matched producer latency comparison across plaintext, TLS, and mTLS. . . 50
4.5 Producer latency overhead by message size under matched security modes. . . 51
4.6 Producer latency overhead by producer count under matched security modes. 52
4.7 Matched benchmark-client and broker CPU utilisation under plaintext, TLS, and mTLS. 54
4.8 Security overhead pattern across workload factors and host telemetry indicators. 54
4.9 Consumer validation comparison across plaintext, TLS, and mTLS. 55

List of Tables

3.1 Main Functional Requirements 20
3.2 Main Non-Functional Requirements 20
3.3 Summary of key artefact requirements 20
3.4 Kafka transport-security modes evaluated by the artefact 29
3.5 Testing and validation evidence for the benchmarking artefact 39

4.1 Final benchmark completion and matched-analysis counts 42
4.2 Matched producer throughput summary 46
4.3 Matched producer latency summary 50
4.4 Matched host telemetry summary 54
4.5 Targeted consumer validation summary 55

5.1 Evaluation of dissertation objectives 59

A.1 Representative examples of GenAI use during the project 71

B.1 Main artefact configuration and generated plan files 73
B.2 Producer factorial campaign dimensions 74
B.3 Security modes used by the artefact 75

C.1 Run-level benchmark output files 78
C.2 Metadata field groups 78
C.3 Primary parsed result metrics 79
C.4 Host telemetry field groups 80
C.5 Result-set output files 80

D.1 Producer campaign completion and matched-analysis counts 82
D.2 Producer row validity and retention summary 83
D.3 Overall matched security-mode comparison summary 83
D.4 Relative security overhead summary 84
D.5 Mean matched producer throughput by message size 84
D.6 Mean matched producer throughput by producer count 84
D.7 Mean matched producer throughput by compression mode 85

D.8 Mean matched producer throughput by acknowledgement mode 85
D.9 Mean matched average latency by message size 85
D.10 Mean matched average latency by producer count 85
D.11 Additional producer latency summary metrics 86
D.12 Matched host CPU and memory summary 86
D.13 Matched host network and disk summary 87
D.14 Extreme-case telemetry summary 87
D.15 Targeted consumer validation summary 87
D.16 Consumer validation results across selected workload slices 88
D.17 Highest observed security-overhead cases 88

E.1 Repository structure 90

Chapter 1

Introduction

1.1 Background and Motivation

Modern distributed systems increasingly rely on event-streaming platforms to connect cloud services, data pipelines, and enterprise applications [1, 2]. Apache Kafka is a widely used open-source event-streaming platform that supports high throughput, low latency, fault tolerance, and horizontal scalability [3–5]. These properties make Kafka a critical component in data-driven systems where large volumes of events must move reliably between producers, brokers, and consumers.

Kafka achieves much of its performance through partition-level parallelism, batching, append-only logs, page-cache utilisation, and zero-copy data transfer [3, 6, 7]. However, these mechanisms also make Kafka sensitive to additional processing in the data path. Security mechanisms, while optional in Kafka, are therefore essential deployment details (particularly in regard to assessing performance), as they can affect the communication and computation paths that Kafka relies on for high-throughput streaming.

At the same time, distributed systems face security risks that traditional perimeter-based models do not. In cloud and multi-service environments, internal network access can no longer be treated as inherently trustworthy, as insider threats and lateral movement attacks can originate from within the network boundary [8–10]. This has increased interest in Zero Trust Architecture, a broader system-level security paradigm, whose central principle is commonly summarised as "never trust, always verify" [8–11]. Zero Trust deployments usually emphasise strong identity, mutual authentication, least-privilege access, encrypted communication, monitoring, and policy-based control [9, 11, 12].

While Zero Trust Architecture is not a single Kafka feature, Kafka provides native mechanisms that align with several Zero Trust principles, including transport encryption, certificate-based authentication, broker-to-broker security, SASL authentication, and ACL-based authorisation [7, 13–15]. Among these, TLS and mutual TLS (mTLS) are

particularly relevant because they directly affect Kafka's data path and allow plaintext, server-authenticated, and mutually authenticated transport configurations to be compared.

1.2 Problem Statement

Existing research provides strong foundations for both Zero Trust Architecture and Apache Kafka performance. Zero Trust has been discussed in distributed and streaming systems [8,12,16], while Kafka has been widely analysed as a high-throughput event-streaming platform [4, 5, 17]. However, there is still limited systematic empirical evaluation of the performance impact of Zero Trust-aligned transport security in Kafka-based environments.

This gap matters because TLS and mTLS introduce cryptographic processing into communication paths that Kafka is designed to keep efficient. Kafka's official design documentation states that SSL/TLS prevents the use of the `sendfile` zero-copy optimisation because SSL libraries operate in user space [6]. Wider TLS literature also shows that secure transport can introduce computational and latency overhead, although the scale depends on workload, connection behaviour, and system configuration [18–20]. Therefore, the cost of TLS and mTLS cannot be assumed to be constant across Kafka deployments.

The unresolved problem is the lack of a unified, reproducible, and Kafka-specific framework for measuring this overhead under controlled configurations. In particular, there is limited evidence showing how plaintext, TLS, and mTLS compare when workload and deployment parameters are matched, and how this overhead changes across Kafka variables such as broker count, replication factor, acknowledgements, batching, compression, producer concurrency, and message size.

This problem is important both for industry and research. In industry, Apache Kafka is often used in performance-sensitive data pipelines where throughput, latency, and durability are operationally significant. Organisations adopting stronger transport security therefore need evidence about whether TLS and mTLS introduce modest, moderate, or substantial overhead under realistic Kafka configurations. Without such evidence, security decisions risk being guided by generic assumptions about TLS rather than by Kafka-specific behaviour. In research terms, the gap also matters because it limits reproducible comparison across studies and makes it difficult to determine whether observed performance differences are caused by transport security itself or by changes in workload and deployment configuration.

1.3 Research Aim and Objectives

The aim of this dissertation is to design, implement, and evaluate a reproducible benchmarking framework for quantifying the performance overhead introduced by TLS and

mTLS in high-throughput Apache Kafka deployments.

The objectives are:

1. To analyse Kafka's performance mechanisms and identify how transport security may affect them.
2. To design and implement a cloud-based Kafka benchmarking artefact supporting plaintext, TLS, and mTLS.
3. To provision reproducible Kafka deployments using infrastructure-as-code and automated orchestration.
4. To execute matched benchmark workloads across security modes using explicit configuration files.
5. To measure throughput and latency for each benchmark run.
6. To collect host-level telemetry from Kafka brokers and benchmark clients, including CPU, memory, disk, and network activity.
7. To evaluate how TLS and mTLS overhead varies across Kafka workload and deployment parameters.
8. To include targeted consumer-side validation to assess whether secure transport also affects Kafka's read path.

1.4 Research Question

This dissertation addresses the following research question:

> "What is the performance overhead introduced by Zero Trust-aligned security mechanisms, particularly mTLS, in high-throughput Kafka-based distributed systems?"

1.5 Artefact Overview

To answer this research question, this dissertation designs, implements, and evaluates a configurable Kafka benchmarking artefact. The artefact provisions Apache Kafka clusters on AWS EC2 using Terraform, deploys Kafka in KRaft mode, and supports three transport-security configurations: plaintext, TLS, and mTLS. Benchmark execution is driven by structured configuration files so that equivalent workloads can be repeated across security modes and compared under matched conditions.

The main evaluation uses a producer-side factorial benchmark campaign. This campaign

varies broker count, replication factor, minimum in-sync replicas, message size, target throughput, producer count, acknowledgement mode, batch size, and compression type. This allows the artefact to examine whether TLS and mTLS introduce overhead, and how that overhead changes under different Kafka workload and durability settings.

A smaller targeted consumer-side validation study is also included. This does not reproduce the full producer factorial campaign. Instead, it evaluates whether secure transport also affects Kafka's read path under selected workloads, especially where mTLS processing interacts with larger messages and compressed payloads.

For each benchmark run, the artefact records application-level metrics, including throughput and latency, alongside host-level telemetry from the benchmark client and Kafka brokers. This includes CPU utilisation, memory utilisation, disk activity, and network activity. Raw benchmark logs are parsed into structured JSON and CSV outputs, allowing reproducible comparison of plaintext, TLS, and mTLS results.

1.6 Dissertation Structure

The remainder of this dissertation is organised as follows. Chapter 2 reviews the literature on Apache Kafka, Kafka performance, Kafka security, Zero Trust Architecture, TLS/mTLS overhead, and benchmarking methodology. It identifies the research gap addressed by this dissertation.

Chapter 3 describes the design, implementation, and testing of the Kafka benchmarking artefact. It covers the infrastructure design, Kafka deployment model, security-mode configuration, factorial workload generation, orchestration scripts, telemetry collection, result-processing pipeline, and validation strategy.

Chapter 4 presents and discusses the benchmark results. It compares plaintext, TLS, and mTLS under matched workloads and analyses the observed throughput, latency, and host-telemetry behaviour.

Chapter 5 evaluates the dissertation objectives, summarises the main findings, discusses limitations, and identifies directions for future work.

Chapter 2

Literature Review

This literature review examines the areas needed to understand the performance impact of Zero Trust-aligned transport security in Apache Kafka. It does not treat Kafka and Zero Trust as separate topics. Instead, it focuses on the interaction between Kafka's high-throughput architecture and security mechanisms such as TLS and mutual TLS (mTLS), which add cryptographic processing to Kafka's communication paths.

The chapter first reviews Apache Kafka as a distributed event-streaming platform. It then analyses the mechanisms that contribute to Kafka's performance and form the baseline against which TLS and mTLS overhead must be measured, such as append-only logs, zero-copy data transfer, etc. The review then examines Kafka's native security mechanisms, including encryption, authentication, and authorisation. This leads into a discussion of Zero Trust Architecture, where a key distinction is made: Zero Trust is a system-level security paradigm, while Kafka only provides mechanisms that can support Zero Trust-aligned deployments. In this dissertation, TLS and mTLS are therefore evaluated as measurable transport-security mechanisms aligned with Zero Trust principles, rather than as a complete implementation of Zero Trust Architecture. The chapter then reviews existing work on TLS and mTLS performance overhead, followed by benchmarking methodologies for Kafka and distributed systems. This is necessary because existing TLS studies often focus on web servers or generic client-server systems, while Kafka has a replicated, partitioned, and batch-oriented data path. Finally, the chapter synthesises these areas into the research gap addressed by this dissertation: the lack of a reproducible and Kafka-specific empirical evaluation of plaintext, TLS, and mTLS under matched high-throughput configurations.

2.1 Apache Kafka & Distributed Streaming Systems

Distributed streaming systems, such as Apache Kafka, are designed to store, process, and move continuous streams of data across distributed applications [3, 4, 6]. Kafka is widely used because it provides fault tolerance, high availability, reliability, and high-throughput event delivery [3, 4, 17]. These properties make it suitable for cloud and enterprise systems

where many applications must exchange data reliably and at scale.

Apache Kafka is built around a cluster of servers called brokers and client applications called producers and consumers [3, 4]. Producers publish events to Kafka topics, while consumers subscribe to and read those events from the brokers [3, 4]. Brokers therefore act as the intermediary layer between data-producing and data-consuming applications. A simplified version of this architecture is shown in Figure 2.1.

Kafka stores events in topics, which are implemented as append-only, time-ordered logs [3, 6, 17]. Topics are divided into partitions, and these partitions can be distributed across multiple brokers. This allows Kafka to scale horizontally because different brokers and clients can process different partitions in parallel [3, 4, 6]. Replication further improves availability and durability by storing copies of partition data across multiple brokers [3, 6].

Kafka also uses a pull-based consumption model. Instead of brokers pushing events to consumers, consumers fetch records at their own rate [6]. This decouples producers from consumers and allows consumers to process large batches without being directly overwhelmed by the production rate. This model contributes to Kafka's scalability and fault tolerance, but it also means that performance depends heavily on client behaviour, batching, partitioning, and broker configuration. These design choices create important trade-offs. Kafka performance is affected by acknowledgement settings, replication, batching, partitions, broker configuration, and client configuration [6, 7, 13, 14, 17].

Therefore, Kafka performance should not be treated as a fixed property of the platform. It is shaped by the selected configuration, deployment environment, workload, and coordination costs [6, 7, 13, 14, 17]. This is important for this dissertation because security mechanisms such as TLS and mTLS add communication and cryptographic processing to Kafka's distributed data path. Their overhead must therefore be evaluated within Kafka's architecture, rather than treated as a generic network cost [7, 13, 14, 18].



Figure 2.1: Simplified Apache Kafka architecture showing producer applications publishing events to a cluster of brokers, and consumer applications pulling events from the cluster. Figure generated using ChatGPT image generation from a prompt requesting a producer-broker-consumer Apache Kafka architecture diagram, April 2026.

2.2 Performance in Kafka Systems

Kafka performance comes from several architectural choices that reduce unnecessary data movement and allow data to be processed in parallel. Instead of relying on random-access data structures such as B-Trees, Kafka stores records in append-only logs, allowing efficient sequential writes [3, 6, 17]. Kafka also relies heavily on the operating system page cache and uses zero-copy I/O, specifically the `sendfile` system call, to transfer data from the page cache to the network socket with minimal copying [6]. These optimisations make Kafka fast, but they also make it sensitive to mechanisms that move processing back into user space, such as TLS and mTLS [6, 13, 18, 19]. This contrast is shown in Figure 2.2.

Kafka also gains performance through partitioning, batching, compression, and pull-based consumption [3, 4, 6, 17]. Topics are divided into partitions, which can be distributed across brokers and accessed in parallel by producers and consumers [3, 4, 6]. Producers can group records into larger batches, reducing network round-trip overhead and improving

throughput [6, 7, 17]. Consumers then fetch records using a pull-based model, allowing them to read batches at their own processing rate [4–6, 14].

Compression further changes Kafka's performance behaviour. By compressing batches, producers can reduce network usage and broker storage pressure [6, 7, 14]. However, this also shifts some computational cost to producers and consumers, especially during compression and decompression. This matters for this dissertation because TLS and mTLS also introduce cryptographic processing. Therefore, the combined effect of compression and transport security may depend on CPU availability, message size, and client concurrency.

Moreover, Kafka configuration choices create explicit throughput-latency-durability trade-offs [6, 7, 13, 14, 17]. For example, producers can use different acknowledgement settings. Waiting for all in-sync replicas improves durability, but can increase latency compared to weaker acknowledgement settings [6, 7, 17]. Similarly, replication factor, minimum in-sync replicas, batch size, partitioning, broker configuration, and producer concurrency can all change the balance between throughput, latency, and reliability. This means Kafka performance is not a fixed property of the platform, but an outcome of workload, deployment, and configuration choices.

This relationship can also be understood using a simple queueing-theoretic model. In publish-subscribe systems, average latency (L) can be expressed in terms of processing time (τ) and system utilisation (U) as:

$$L = \frac{\tau}{1 - U} \tag{2.1}$$

[4, 5, 19]. As processing time increases, utilisation moves closer to saturation, and latency can grow non-linearly rather than linearly [4, 5, 17, 19]. This is important because TLS and mTLS can increase processing time by adding encryption, decryption, and certificate-based authentication to Kafka communication paths [6, 13, 18, 20].

Therefore, Kafka performance must be evaluated under controlled configurations rather than assumed from general platform claims. The impact of transport security may vary with batching, compression, producer count, replication, acknowledgement mode, message size, and broker resources. This motivates the need to examine Kafka's native security mechanisms before measuring their performance impact in the artefact.



Figure 2.2: Comparison of Kafka data movement under plaintext, TLS, and mTLS. Plaintext can use page-cache-backed `sendfile` zero-copy transfer, while TLS and mTLS require user-space cryptographic processing that prevents this path.

2.3 Security Mechanisms in Kafka

Kafka provides native security mechanisms for protecting data streams, including encryption, authentication, and authorisation [3, 7, 13–15]. These mechanisms are important because Kafka is often deployed across distributed services where producers, brokers, and consumers exchange sensitive data. However, enabling security can also change Kafka's data path by adding cryptographic processing, identity verification, and access-control checks [6, 7, 13, 14].

Encryption in transit is provided through Transport Layer Security (TLS). TLS protects data

moving between Kafka clients and brokers, and can also be configured for broker-to-broker communication [7, 13, 14]. Kafka exposes this through listener and SSL configuration options, including `ssl.enabled.protocols` and `ssl.cipher.suites`, which allow operators to control the supported TLS protocols and cipher suites [7, 13, 14]. This provides confidentiality and protection against eavesdropping or man-in-the-middle attacks, but it also introduces encryption and decryption work into Kafka's communication path.

This matters for performance because Kafka's plaintext path can use efficient operating-system mechanisms such as `sendfile`. Kafka's design documentation states that this zero-copy optimisation is not used when SSL is enabled because SSL libraries operate in user space [6]. Therefore, TLS does not only add cryptographic cost; it can also change how data moves between disk, memory, and the network. This makes Kafka-specific measurement necessary, because generic TLS overhead results from web servers or simple client-server systems do not fully represent Kafka's replicated and batch-oriented architecture [17–19].

Kafka can also support mutual TLS (mTLS). In this mode, clients present certificates to brokers, and brokers verify those identities using Kafka SSL configuration such as `ssl.client.auth` [7, 13, 14]. This allows producers, consumers, and brokers to authenticate using cryptographically signed X.509 certificates. A simplified view of this security path is shown in Figure 2.3.

Moreover, mTLS is especially relevant to Zero Trust-aligned deployments because it provides encrypted communication and certificate-based identity verification. However, it can also increase the amount of cryptographic work in the system. In Kafka, this work may occur not only on client-broker communication, but also on broker-to-broker traffic when internal replication is secured [6, 13, 20]. Reconnection events can also create additional TLS or mTLS handshake load, especially when many clients reconnect at the same time [13, 18, 19].

Therefore, Kafka's native security mechanisms create a direct performance-security trade-off. They improve confidentiality, authentication, and access control, but they may also increase CPU usage, latency, and data movement through user space. For this reason, TLS and mTLS are the main focus of this dissertation. They are measurable transport-security mechanisms that align with Zero Trust principles, while also directly affecting the Kafka data path that enables high throughput.



Figure 2.3: Kafka security data path showing how TLS/mTLS, certificate-based identity verification, principal mapping, and ACL authorisation are applied before Kafka request processing, with broker-to-broker communication also secured where configured.

2.4 Zero Trust Architecture

Zero Trust Architecture (ZTA) is a security model developed in response to the limits of traditional perimeter-based security [8–10, 12]. Traditional models often assume that systems inside the network boundary are trustworthy. ZTA rejects this assumption and instead follows the principle of "never trust, always verify" [8–11]. In this model, access is continuously evaluated using identity, context, policy, and device or service state, rather than being granted simply because a request originates from inside the network.

The core principles of ZTA include strong identity, least-privilege access, continuous verification, encrypted communication, monitoring, and fine-grained policy enforcement [8–11]. These principles are commonly implemented through architectural components such as Policy Decision Points (PDPs) and Policy Enforcement Points (PEPs), which separate policy decisions from policy enforcement [8, 9, 11]. ZTA is therefore not a single tool or protocol, but a system-level security approach.

Cryptographic transport security is one part of this wider model. TLS and mTLS are often used to protect communication channels and verify service identities in distributed systems [8–10, 20]. TLS provides encrypted communication and server authentication, while mTLS extends this by requiring both sides of a connection to authenticate with certificates. This makes mTLS especially relevant to Zero Trust-aligned machine-to-machine communication, where services should not be trusted purely because they are inside the same network.

However, ZTA also introduces operational and performance challenges. Implementing it can require changes to identity management, certificate handling, monitoring, network

segmentation, and access-control policy design [8–12]. In high-throughput systems, these controls can add processing and coordination overhead. This creates the key tension for this dissertation: the same mechanisms that improve trust and identity assurance may also affect the latency and throughput of systems such as Apache Kafka [6, 18, 19].

2.5 Zero Trust in Distributed Streaming Systems

The challenges of Zero Trust Architecture also apply to distributed streaming systems [1, 8–10, 12]. Modern event-streaming pipelines often span cloud services, remote devices, multi-cloud environments, and third-party networks. In these settings, components cannot be assumed to be trustworthy simply because they are inside the same network. Each producer, broker, stream processor, and consumer may need to be authenticated, authorised, encrypted, and monitored [8–10, 12]. Figure 2.4 illustrates this type of control model.

This creates a direct tension for streaming systems. These systems are designed for continuous data movement, low latency, and high throughput. However, Zero Trust-aligned controls such as mutual authentication, encryption, segmentation, and policy enforcement add work to the same communication paths that carry the data [12, 18–20]. Therefore, the main issue is not whether these controls are useful, but how their cost changes under realistic streaming workloads.

Access control is one example of this tension. Role-Based Access Control (RBAC) is widely used because it is simple to understand and operate, but it can lack the granularity required in dynamic distributed systems [8–10]. Attribute-Based Access Control (ABAC) provides finer-grained control by evaluating attributes such as identity, device state, time, location, and environmental context [8, 9, 12]. However, ABAC can be harder to configure correctly, and run-time policy evaluation can add latency if it is placed on the critical data path [8–10, 12].

Transport security creates a similar issue. Some studies suggest that modern TLS can have low steady-state overhead when connections are persistent and hardware is adequately provisioned [15, 19]. However, this does not fully resolve the problem for streaming systems. Event-streaming workloads may involve large message volumes, many clients, broker-to-broker communication, compressed batches, and reconnect events. In these cases, TLS and mTLS overhead may depend on workload shape, connection behaviour, certificate verification, and available CPU resources [12, 18–20].

This is particularly important for Apache Kafka because Kafka is designed around efficient batching, partitioning, replication, and zero-copy data transfer [6, 17]. Zero Trust-aligned transport controls, especially TLS and mTLS, can interact with these mechanisms by moving work into user space and adding cryptographic processing to

client-broker and broker-to-broker communication. Therefore, the performance impact cannot be inferred from generic TLS studies alone. It must be measured in Kafka under controlled and reproducible configurations.

This establishes the need for the empirical approach used in this dissertation. The relevant question is not whether Zero Trust principles are valuable, but what performance cost is introduced when selected Zero Trust-aligned mechanisms are applied to a high-throughput streaming platform. This motivates the comparison of plaintext, TLS, and mTLS Kafka deployments under matched workloads.



Figure 2.4: Conceptual Zero Trust control model for a distributed streaming pipeline, illustrating how mTLS, policy enforcement, least-privilege access, and continuous monitoring are applied across producer, broker, stream-processing, and consumer components within a segmented trust boundary.

2.6 TLS/mTLS Performance Overhead

Existing TLS performance studies show that encrypted transport can introduce measurable computational overhead [18,19]. Coarfa et al. separate this cost into connection setup, which uses asymmetric cryptography, and bulk data transfer, which uses symmetric encryption [18]. Their web-server experiments report a throughput degradation factor between 3.4 and 9 compared with plaintext baselines, depending on workload and session reuse [18]. They also identify RSA-based operations as a major source of overhead, consuming between 13% and 58% of web-server processing time under the evaluated workloads [18].

However, these findings cannot be transferred directly to Apache Kafka. Traditional web-server TLS benchmarks often model short-lived request-response workloads, where new connections are frequently created and where data is already handled in user space [18, 19]. Kafka is different. It is based on long-lived client-broker connections, batching, partitions, replication, and operating-system optimisations such as page-cache reuse and zero-copy I/O [6, 7, 14]. Kafka's design documentation states that `sendfile` is not used when SSL is enabled because SSL libraries operate in user space [6]. This means TLS affects Kafka not only through encryption cost, but also by changing the data-movement path.

Persistent-connection studies give a different view of TLS overhead. Iorio et al. show that persistent encrypted channels can reduce repeated handshake costs, allow TCP behaviour to stabilise, and make steady-state TLS latency small on sufficiently provisioned devices [19]. This is important because Kafka also uses long-lived connections. However, these studies still do not fully represent Kafka because they focus on generic client-server communication rather than replicated, broker-mediated streaming systems [6, 19].

In Kafka, TLS and mTLS may apply across several communication paths. These include producer-to-broker, consumer-to-broker, and broker-to-broker communication [3, 6, 13]. When mTLS is enabled, certificate-based authentication can also be required in addition to encryption [13, 20]. Therefore, the cost is not limited to a single client-server channel. It may interact with replication, batching, compression, partitioning, and broker resources [6, 7, 13, 14].

The Kafka benchmarking literature also shows a reproducibility problem. Mohammad reports that although many Kafka studies include empirical benchmarks, they often omit important configuration details such as partition count, replication factor, batch size, linger time, compression settings, and workload characteristics [17]. This makes it difficult to compare results across studies, because observed performance differences may come from configuration changes rather than security overhead alone [7, 13, 17].

Therefore, the performance impact of TLS and mTLS in Kafka should be treated as configuration-dependent. It depends on how cryptographic work is distributed across clients

and brokers, how it interacts with batching and compression, and how close the system is to CPU, network, or disk saturation [6, 7, 13, 18]. This motivates the need for a controlled benchmarking framework that compares plaintext, TLS, and mTLS under matched Kafka configurations.

2.7 Benchmarking Methodologies

Performance evaluation in distributed systems often starts with theoretical models. Network studies may use topological metrics such as bisection bandwidth or sparsest cut to estimate throughput limits [21]. Kafka studies may also use queueing models to relate latency to processing time and utilisation [5]. These models are useful because they explain why saturation can increase latency and reduce throughput. However, they are not sufficient on their own.

Jyothi et al. show that cut-based metrics do not always predict worst-case throughput, since a topology with a stronger cut metric can still perform worse under certain traffic patterns [21]. Similarly, Kafka producer evaluations show that queueing models can overestimate performance because they do not fully capture operating-system overhead, thread coordination, CPU contention, and network I/O contention [5]. Therefore, theoretical models are useful for framing the problem, but empirical benchmarking is required to measure the real behaviour of Kafka under load [6, 17].

Latency measurement also needs care. Some empirical studies rely on network-level round-trip time (RTT), using tools such as ping, traceroute, or transport-level measurements [19]. These metrics can show whether the network path is stable, but they do not capture the full application-level path. Iorio et al. argue that application-level Flow Completion Time (FCT) is more representative because it includes protocol processing, endpoint behaviour, buffering, proxying, and other effects that network-level probes can miss [19].

This matters because distributed systems can appear stable at median latency while still showing large tail-latency increases. Iorio et al. show that performance can remain similar up to high percentiles but diverge at the extreme tail due to shared infrastructure, endpoint processing, buffering, and transport behaviour [19]. Therefore, Kafka benchmarking should not rely only on average or median latency. It should also capture maximum latency and, where available, high-percentile behaviour.

Kafka benchmarking also suffers from reproducibility issues. Researchers use standardised suites such as TPCx-Kafka, synthetic frameworks such as the Yahoo Streaming Benchmark, and custom workload generators [17]. Standardised suites provide recognisable baselines, while custom workloads can model more domain-specific pipelines such as finance, IoT,

retail, or machine-learning systems [12, 15, 17]. However, Mohammad's review of 42 Kafka event-streaming studies shows that benchmark reporting is often incomplete and inconsistent [17].

This lack of transparency is a major problem for security-overhead evaluation. Kafka performance depends on parameters such as partition count, replication factor, message size, batch size, compression, producer concurrency, consumer lag, and acknowledgement settings [7, 13, 17]. If these are not reported or controlled, then performance differences may be caused by configuration variation rather than TLS or mTLS overhead. Sundbom also shows that aggregate metrics can hide internal client-side effects, such as producer queueing and outbuffer contention [5].

Therefore, evaluating Kafka transport-security overhead requires a transparent and reproducible benchmarking method. The benchmark must use explicit configuration files, matched workloads, structured output, and enough metric detail to connect application-level behaviour with resource-level causes. This motivates the artefact developed in this dissertation, which uses controlled factorial benchmark plans to compare plaintext, TLS, and mTLS under matched Kafka configurations.

2.8 Synthesis & Research Gap

The literature shows that Apache Kafka is a high-throughput distributed event-streaming platform whose performance depends on several connected mechanisms. These include append-only logs, page-cache utilisation, batching, partition-level parallelism, pull-based consumption, compression, replication, and zero-copy data transfer [3, 6, 7, 14]. These mechanisms allow Kafka to move large volumes of data efficiently, but they also make performance sensitive to configuration choices and additional processing in the data path [5–7, 13, 17]. Therefore, Kafka performance should be treated as a configurable outcome, not as a fixed platform property.

The literature also shows that modern distributed systems increasingly require security models that do not rely on implicit trust inside the network [8–10]. Zero Trust Architecture addresses this by emphasising strong identity, least-privilege access, continuous verification, encrypted communication, monitoring, and fine-grained control [8–10]. However, Zero Trust is not a single feature that can be enabled in Kafka. Instead, Kafka provides mechanisms that can support Zero Trust-aligned deployments, including TLS encryption, mTLS-based authentication, SASL authentication, ACL authorisation, and broker-to-broker security configuration [7, 13, 14].

Among these mechanisms, TLS and mTLS are the most relevant to this dissertation because they directly affect Kafka's data path. They provide a measurable basis for comparing

plaintext, server-authenticated, and mutually authenticated transport configurations [6, 13]. This creates a performance-security tension. Kafka's plaintext path can rely on efficient operating-system mechanisms such as `sendfile`, but Kafka's design documentation states that this optimisation is not used when SSL is enabled because SSL libraries operate in user space [6]. TLS and mTLS can therefore introduce both cryptographic processing and additional user-space data movement.

Existing TLS studies provide useful evidence, but they do not fully answer the Kafka-specific problem. Web-server studies show that TLS can introduce measurable overhead, especially during connection setup and asymmetric cryptographic operations [18, 20]. Persistent-connection studies show that this overhead can be smaller once handshake costs are amortised [19]. However, Kafka is not a stateless web server or a single client-server channel. It is a replicated, partitioned, batch-oriented distributed log with producer-broker, consumer-broker, and broker-to-broker communication paths [3, 6, 13]. Therefore, Kafka-specific measurement is required.

Kafka performance studies also do not fully resolve the problem. Existing work often examines throughput, batching, replication, producer parallelism, or benchmark-suite design without isolating TLS, mTLS, client authentication, and encrypted broker communication under matched configurations [5, 13, 17]. Where Kafka security is discussed, evaluations are often domain-specific, configuration-limited, or insufficiently reproducible [15, 17]. This limits the ability to compare results across workloads and deployment conditions.

The benchmarking literature further strengthens this gap. Kafka performance depends on variables such as broker count, replication factor, producer concurrency, batch size, acknowledgement mode, compression, message size, and partitioning [6, 7, 13]. If these parameters are not controlled or reported, observed differences may come from configuration variation rather than security overhead. Coarse network metrics and theoretical models are also insufficient on their own because they do not fully capture operating-system overhead, thread coordination, network I/O contention, or application-level latency [5, 19, 21]. Therefore, evaluating Kafka security overhead requires transparent, repeatable, and configuration-explicit benchmarking.

The research gap addressed by this dissertation is therefore the lack of a reproducible, systematic, and Kafka-specific benchmarking framework for quantifying the performance overhead of Zero Trust-aligned transport-security mechanisms, particularly TLS and mTLS, under controlled high-throughput configurations [6, 13, 17]. This dissertation addresses that gap by designing and evaluating a configurable Kafka benchmarking artefact that provisions cloud-based Kafka clusters, executes matched plaintext, TLS, and mTLS workloads, records producer-side throughput and latency, captures host-level telemetry from clients and brokers, and includes targeted consumer-side validation.

The contribution is both methodological and empirical. Methodologically, the artefact provides a reproducible approach for evaluating Kafka transport-security overhead under matched conditions. Empirically, it provides evidence about how TLS and mTLS affect throughput, latency, and resource utilisation across Kafka workload and deployment parameters.

Chapter 3

Design, Implementation, and Testing

3.1 Chapter Overview

This chapter describes the design, implementation, and testing of the Kafka benchmarking artefact developed to answer the research question. The artefact provides a reproducible way to measure the performance overhead introduced by Zero Trust-aligned transport-security mechanisms, particularly TLS and mTLS, in Apache Kafka deployments.

The chapter first defines the artefact requirements, then explains the system architecture, infrastructure provisioning, Kafka deployment model, security-mode design, benchmark workload design, telemetry collection, result-processing pipeline, fault-tolerance mechanisms, and testing strategy. Together, these sections show how the artefact was designed to support controlled and comparable measurement across plaintext, TLS, and mTLS configurations.

3.2 Artefact Requirements

The artefact requirements were derived from the research question and the methodological gap identified in Chapter 2. Since the dissertation evaluates Kafka transport-security overhead, the artefact must support controlled deployment, matched workload execution, structured metric capture, and repeatable comparison across security modes.

#	Main Functional Requirements
1	Provision cloud-based Kafka infrastructure using repeatable infrastructure-as-code.
2	Deploy Kafka in plaintext, TLS, and mTLS configurations.
3	Execute matched producer workloads across security modes.
4	Execute targeted consumer-side validation workloads.
5	Capture throughput, latency, and host-level telemetry.
6	Parse raw benchmark logs into structured result files.
7	Export results in formats suitable for analysis and dissertation reporting.

Table 3.1: Main Functional Requirements

#	Main Non-Functional Requirements
1	Reproducibility, so benchmark rows can be regenerated from explicit configuration files.
2	Comparability, so plaintext, TLS, and mTLS runs use matched workload and deployment parameters.
3	Resumability, so interrupted campaigns can continue without rerunning completed rows.
4	Fault tolerance, so transient failures do not corrupt local result state.
5	Configuration transparency, so workload and deployment parameters are recorded with each result.
6	Cost control, so cloud resources and benchmark scope remain manageable.
7	Extensibility, so additional workloads, metrics, or security modes can be added later.

Table 3.2: Main Non-Functional Requirements

#	Core Artefact Requirements
Reproducibility	Benchmark runs must be generated from explicit configuration files and produce structured outputs.
Comparability	Plaintext, TLS, and mTLS runs must use matched workload and deployment parameters.
Resumability	Long-running campaigns must recover from interruption without rerunning completed rows.
Telemetry	Each run must capture application metrics and host-level resource utilisation.
Fault tolerance	Local state must remain valid when remote execution or file transfer is interrupted.

Table 3.3: Summary of key artefact requirements

These requirements shaped the artefact design. Terraform was used for repeatable

infrastructure provisioning, benchmark execution was driven by JSON configuration files, and checkpointing was added to support long-running campaigns. Host telemetry was included because throughput and latency alone are insufficient to explain whether observed overhead is caused by CPU pressure, network activity, disk activity, or client-side bottlenecks.

3.3 System Architecture

The artefact uses a cloud-based architecture built around a local workstation, Terraform infrastructure code, orchestration scripts, an AWS Virtual Private Cloud (VPC), Kafka broker instances, and a dedicated benchmark client. This design allows Kafka to be evaluated on virtual machines while also collecting host-level CPU, memory, disk, and network telemetry.

The local workstation acts as the control node. It stores the Terraform configuration, orchestration scripts, benchmark configuration files, generated plans, checkpoints, and copied result files. Terraform provisions the AWS infrastructure, while the orchestration scripts prepare the benchmark client, deploy Kafka to the brokers, configure the selected security mode, execute benchmark runs, collect telemetry, and copy results back locally.

The AWS environment contains Kafka broker EC2 instances and one benchmark client EC2 instance. The broker cluster supports both three-broker and five-broker phases, allowing broker count to be treated as an experimental variable. Kafka traffic uses private VPC addresses, while SSH orchestration uses public IP addresses. This separation keeps benchmark traffic inside the cloud network while still allowing the local workstation to manage the cluster.

The benchmark client runs the Kafka producer and consumer benchmark tools. It connects to the brokers using the listener for the selected security mode: plaintext, TLS, or mTLS. During each run, application-level benchmark output is collected alongside host telemetry from the client and brokers. Results are then copied back to the local workstation for parsing, aggregation, and export.

This architecture was selected instead of running producers directly on the broker machines because producer-side CPU and network overhead would otherwise compete with broker execution. Separating the benchmark client from the broker cluster allows client-side and broker-side telemetry to be interpreted separately. This is important for TLS and mTLS evaluation because cryptographic overhead may appear on either side of the connection.



Figure 3.1: System architecture of the Kafka benchmarking artefact, showing local orchestration, Terraform-provisioned AWS infrastructure, private Kafka traffic, SSH control paths, broker instances, benchmark client, and result collection.

3.4 Reproducing the Artefact Environment

This section explains how the benchmarking environment can be recreated by a reader who is not already familiar with the implementation. The artefact was designed as a staged workflow rather than as a single script. Reproducing the environment therefore involves infrastructure provisioning, benchmark-client preparation, Kafka deployment, benchmark-plan generation, campaign execution, and result aggregation.

To reproduce the artefact, a researcher first requires an AWS account, Terraform, SSH access, and a local clone of the artefact repository. The local workstation acts as the control node. It stores the Terraform configuration, orchestration scripts, benchmark plans, checkpoints, copied results, and export files. The cloud environment contains the Kafka brokers and one dedicated benchmark-client instance.

3.4.1 Infrastructure provisioning

Terraform is used to create the AWS VPC, subnet, security groups, broker EC2 instances, and benchmark-client EC2 instance. Once these resources are provisioned, helper scripts generate host inventory and cluster metadata so that later deployment stages know which machines act as brokers and which machine acts as the benchmark client.

3.4.2 Benchmark-client preparation

A preparation script installs the Kafka distribution, benchmark scripts, telemetry utilities, and supporting runtime dependencies onto the benchmark-client host. This step ensures that the client instance can execute producer and consumer benchmarks and collect local telemetry during each run.

3.4.3 Kafka deployment

The cluster can be deployed in plaintext, TLS, or mTLS mode, using approprtiate deployment script that configures Kafka for the chosen mode and validates broker readiness using Kafka-level checks before any benchmark is executed.

3.4.4 Benchmark-plan generation

Workloads are defined in JSON configuration files and expanded into JSONL execution plans. Each JSONL row represents one complete benchmark configuration, including message size, target throughput, batch size, acknowledgement mode, producer count, compression mode, replication factor, broker count, and trial number. This separates experiment definition from experiment execution and allows campaigns to be inspected before they are run.

3.4.5 Campaign execution

The orchestration script reads the generated JSONL plan, applies any filters such as broker count or security mode, and executes rows that have not already completed. For each row, it creates the topic, starts telemetry collection, runs the benchmark on the benchmark client, copies logs and telemetry back to the local workstation, parses the outputs, and records completion state. Campaign state is preserved in `started.jsonl`, `completed.jsonl`, `failures.jsonl`, and a checkpoint file so that interrupted campaigns can resume without rerunning successful rows.

3.4.6 Result processing

Each completed run produces a deterministic result directory containing metadata, raw logs, host telemetry, and a parsed `result.json`. Aggregation scripts combine valid per-run results into `summary.json` and `summary.csv`, while export scripts generate CSV tables, LaTeX tables, and plots for later analysis. In this way, reproducing the artefact means not only recreating the infrastructure, but also recreating the full path from deployment to analysis-ready outputs.



Figure 3.2: Tutorial-style reproduction workflow for the benchmarking artefact, showing how infrastructure provisioning, deployment, execution, checkpointing, and result processing are connected.

3.5 Infrastructure Provisioning

The infrastructure layer was implemented using Terraform and AWS EC2. Terraform was selected because it allows the cloud environment to be described as infrastructure-as-code, making the deployment repeatable and inspectable. This is important because benchmark results should be linked to a clearly defined environment rather than an informal manual setup.

The Terraform configuration provisions an AWS VPC, subnet, security groups, Kafka broker instances, and a benchmark client instance. The VPC provides an isolated network for the experiment, while security groups control SSH access, Kafka listener access, and internal cluster communication. Public IP addresses are used for SSH orchestration, while Kafka benchmark traffic uses private IP addresses inside the VPC.

The broker infrastructure supports both three-broker and five-broker phases. This prevents a three-broker run from being treated as equivalent to a five-broker deployment with unused brokers. It also allows broker count to be evaluated as a controlled deployment variable.

A separate benchmark client instance is provisioned alongside the brokers. This prevents the load generator from competing directly with broker processes on the same host. It also makes client-side CPU, memory, disk, and network activity measurable during producer and consumer runs.

Each EC2 instance uses a 40 GB gp3 root volume. This was added because early large-message benchmark runs showed that retained Kafka topic data could exhaust smaller broker disks. Larger volumes, combined with per-run topic cleanup, reduce the risk that disk exhaustion interrupts campaigns or affects benchmark validity.

Virtual machines were selected instead of containers because the experiment required control over machine-level resource behaviour and host telemetry. Containers would simplify local development, but they add another abstraction layer around CPU scheduling, network I/O, disk I/O, and memory accounting. Since this dissertation links Kafka performance to host-resource behaviour, EC2 virtual machines provide a more appropriate environment.

The main trade-off of using AWS EC2 was reduced control over noisy-neighbour effects and cloud-level variability compared with a dedicated laboratory cluster. However, EC2 was still selected because it provided repeatable provisioning, realistic cloud networking, and enough host-level visibility for the dissertation's resource-utilisation analysis. This made it more suitable than local containers for evaluating Kafka transport-security overhead.

3.6 Kafka Cluster Deployment

Kafka was deployed in KRaft mode rather than using ZooKeeper. In KRaft mode, Kafka brokers participate directly in the metadata quorum, reducing the number of external services required by the artefact. This simplifies automated deployment while reflecting the current direction of Kafka cluster management.

KRaft mode was selected because it removes the need for a separate ZooKeeper ensemble, reducing the number of moving parts in the artefact. This improves automation and makes benchmark failures easier to attribute to Kafka workload, security mode, or infrastructure behaviour rather than to an additional coordination service. The trade-off is that the evaluation focuses on modern Kafka KRaft deployments and does not compare against older ZooKeeper-based clusters.

Each broker is configured with a broker identifier and participates in the cluster. The controller quorum manages metadata such as topic definitions, partition assignments, broker membership, and leadership changes. The orchestration scripts generate the required cluster metadata, including private broker addresses and quorum configuration, before starting Kafka.

Kafka broker traffic uses private VPC IP addresses. This applies to producer, consumer, broker-to-broker, and controller communication. Public IP addresses are used only for SSH orchestration. This avoids routing Kafka data-plane traffic through the public internet and keeps communication within the intended experimental environment.

Benchmark topics are created using explicit workload parameters. Each run defines the topic, partition count, replication factor, and minimum in-sync replicas. Partition count controls parallelism, replication factor controls how many broker copies of each partition exist, and `min.insync.replicas` defines how many replicas must acknowledge writes under stronger acknowledgement settings.

Topics are created for benchmark runs and deleted after runs where appropriate. This reduces the risk that previous benchmark state affects later runs and prevents retained test data from filling broker disks during long-running campaigns.

Broker readiness is validated using Kafka API checks rather than relying only on `systemd` process status. A broker process can be running while the broker is not yet ready to serve metadata requests or client traffic. Kafka-level readiness checks therefore reduce the risk of starting benchmark workloads against a partially available cluster.

3.7 Security Mode Design

The artefact supports three Kafka transport-security modes: plaintext, TLS, and mutual TLS (mTLS). These modes allow the benchmark to compare an unsecured baseline, an encrypted server-authenticated configuration, and an encrypted mutually authenticated configuration under matched workloads.

Plaintext mode is used as the baseline. Kafka clients and brokers communicate without transport encryption or certificate-based authentication. This is not a secure production configuration, but it provides the reference point needed to measure the additional cost of TLS and mTLS.

TLS mode enables encrypted communication between Kafka clients and brokers. In this configuration, the broker presents a certificate and the client verifies the broker identity. This provides confidentiality and server authentication while measuring the overhead of encrypted transport.

mTLS mode extends TLS by requiring client certificate authentication. Clients also present certificates to the broker, allowing both sides of the connection to be authenticated. This mode is the closest benchmark configuration to a Zero Trust-aligned transport model because it combines encryption with certificate-based identity verification.

These modes do not represent a complete Zero Trust Architecture. A full Zero Trust deployment would also require broader policy enforcement, continuous monitoring, least-privilege authorisation, identity lifecycle management, and operational controls beyond Kafka transport configuration. Therefore, TLS and mTLS are evaluated as measurable Zero Trust-aligned transport-security mechanisms.

The benchmark focuses on the configured Kafka transport path used by the benchmark client and brokers. This keeps the comparison controlled, but it also means that the results should be interpreted as the overhead of the implemented Kafka security configuration rather than a complete enterprise Zero Trust deployment.

The TLS and mTLS configurations permit TLS 1.3 and TLS 1.2, with protocol negotiation handled by the Kafka/JDK SSL stack. The artefact therefore measures the deployed Kafka transport-security modes rather than isolating TLS 1.3-only or TLS 1.2-only overhead.

Mode	Description
Plaintext	Baseline with no transport encryption.
TLS	Server-authenticated encrypted transport.
mTLS	Encrypted transport with client certificate authentication.

Table 3.4: Kafka transport-security modes evaluated by the artefact

3.8 Benchmark Workload Design

The benchmark workload design contains two parts: a producer-side factorial campaign and a targeted consumer-side validation campaign. The producer campaign is the main evaluation because the research question focuses on overhead in Kafka's high-throughput write path. The consumer campaign is included as a smaller validation study to check whether secure transport also affects Kafka's read path.

The producer benchmark uses Kafka's `kafka-producer-perf-test.sh` tool. This tool was selected because it is part of the Kafka distribution and reports producer throughput and latency under configurable workload settings. The artefact extends this benchmark with structured metadata, deterministic run identifiers, concurrent producer support, host telemetry, parsing, aggregation, and checkpointed execution.

Producer concurrency is controlled through `producer_count`. When this value is greater than one, the benchmark client starts multiple producer processes for the same run. This allows the artefact to evaluate whether TLS and mTLS overhead changes under concurrent producer load.

The producer campaign varies message size, target throughput, batch size, acknowledgement setting, producer count, compression type, replication factor, minimum in-sync replicas, broker count, and security mode. These parameters were selected because they affect the throughput-latency-durability trade-off discussed in Chapter 2 and are expected to interact directly with transport-security overhead.

Message size and target throughput change the volume of encrypted data. Batch size and compression affect how much work is amortised across each network request. Acknowledgement mode, replication factor, and minimum in-sync replicas affect broker coordination and durability cost. Producer count changes client-side parallelism and can expose whether cryptographic processing becomes a client bottleneck. Broker count changes the amount of cluster capacity available for partition leadership, replication, and network handling.

Other Kafka parameters, such as retention time, log segment size, JVM options, and

operating-system tuning, were kept outside the factorial design. These parameters may affect Kafka performance, but they are less directly connected to the immediate producer-side transport-security cost and would substantially increase the campaign size. The workload design therefore prioritises parameters that are most relevant to the research question.

The consumer-side benchmark is intentionally designed as a targeted validation slice rather than a full factorial campaign. A full consumer factorial campaign would substantially increase runtime and cloud cost while duplicating much of the producer-side parameter space. The consumer slice therefore focuses on whether secure transport also affects read-path behaviour under selected workloads.

Together, the two workloads provide a balanced evaluation design. The producer campaign gives broad factorial coverage of Kafka write-path behaviour, while the consumer validation slice adds read-path evidence without making the overall experiment infeasible.

3.9 Factorial Experiment Design

The producer campaign was designed as a controlled factorial experiment. This allows the dissertation to evaluate how Kafka transport-security overhead changes across workload and deployment conditions rather than measuring only one fixed configuration.

The artefact separates experiment definition from execution. Factorial designs are described in JSON configuration files, where parameter ranges, trial counts, baseline values, and validity rules are defined. These files are expanded into JSONL execution plans, where each line represents one benchmark row with a full set of workload, deployment, and security parameters.

Each planned row is assigned a deterministic run identifier. The identifier encodes the main parameters, including security mode, broker count, replication factor, minimum in-sync replicas, message size, target throughput, batch size, acknowledgement mode, producer count, compression type, and trial number. This supports traceability because the same configuration maps to the same run identity.

Validity constraints are applied during plan generation. For example, replication factor and `min.insync.replicas` must be compatible with the selected broker count. This prevents the executor from attempting invalid Kafka configurations and ensures that comparisons are made across meaningful rows.

The final producer campaign design contains 5,184 planned rows after validity constraints are applied. This consists of 1,728 plaintext rows, 1,728 TLS rows, and 1,728 mTLS rows. The balanced structure supports matched security-mode comparison, because equivalent

workload and deployment configurations can be evaluated under each security mode.

A fully exhaustive Kafka benchmark across all producer, broker, network, JVM, and operating-system parameters would be infeasible within the time and cost limits of the dissertation. The factorial design therefore focuses on parameters most likely to affect the interaction between Kafka throughput and cryptographic overhead. This provides broader evidence than a single benchmark configuration while still keeping the campaign executable on cloud infrastructure.

Repeated trials are included because individual cloud benchmark runs can be affected by transient behaviour such as JVM warm-up, network variation, background operating-system activity, and cloud scheduling. Repetition provides a stronger basis for comparison than relying on a single run per configuration.

3.10 Execution and Orchestration

The execution layer is implemented as orchestration scripts that connect infrastructure provisioning, Kafka deployment, benchmark execution, telemetry collection, parsing, aggregation, and export. This keeps the experiment reproducible because the same scripts and configuration files can regenerate plans, resume campaigns, and rebuild summaries.

The first stage is plan generation. The `generate_factorial_plan.sh` script reads a factorial JSON configuration and expands it into a JSONL execution plan. This allows the planned campaign to be inspected, counted, filtered, and validated before cloud execution begins.

The main execution script is `run_factorial_plan.sh`. This script reads the JSONL plan, applies filters such as security mode or broker count, and executes rows that have not already completed. For each row, it prepares metadata, creates the benchmark topic, starts telemetry, runs the producer or consumer benchmark command on the benchmark client, copies outputs back locally, parses the result, and records completion state.

Campaign state is recorded using `started.jsonl`, `completed.jsonl`, `failures.jsonl` where applicable, and a checkpoint file. This matters because large campaigns may be interrupted by SSH timeouts, local process termination, cloud instability, or deliberate pauses. On resume, completed rows are skipped rather than rerun.

After each run, parser scripts convert raw Kafka benchmark logs and telemetry files into structured result data. The per-run output includes raw logs, run metadata, host telemetry, and a parsed `result.json`. Aggregation scripts then combine valid per-run results into `summary.json` and `summary.csv`. Export scripts produce dissertation-ready

CSV tables, LaTeX tables, and SVG plots where required.

This orchestration design supports auditability and reproducibility. Each run has explicit metadata, each campaign has recorded state, and each exported result can be traced back to raw benchmark output.



Figure 3.3: Benchmark execution pipeline from JSON configuration to dissertation-ready result exports.

3.11 Telemetry and Metric Collection

The artefact collects both application-level metrics and host-level telemetry. Throughput and latency show the benchmark outcome, but they do not explain why a run behaves differently under plaintext, TLS, or mTLS. Host telemetry provides additional evidence about CPU, memory, network, and disk behaviour.

Application-level metrics are collected from the Kafka benchmark tools. For producer runs, the main metrics are throughput in records per second, throughput in MB per second, average latency, and maximum latency. For consumer runs, the parsed output records consumer throughput and read-path metrics where available.

Host telemetry is collected from the benchmark client and Kafka broker instances during benchmark execution. The telemetry includes CPU utilisation, memory utilisation, network receive/transmit activity, and disk read/write sector counters. Collecting telemetry from both client and brokers is important because TLS and mTLS overhead may appear on either side of the connection.

Host telemetry was included to reduce the risk of misattributing performance degradation. For example, a throughput reduction under mTLS could be caused by broker CPU saturation, client-side encryption cost, network pressure, disk activity, or a combination of these factors. Collecting telemetry from both brokers and the benchmark client makes these interpretations more defensible. However, the telemetry is still host-level rather than JVM-internal, so it cannot directly attribute overhead to specific Kafka threads or SSL library calls.

Each run also records workload and deployment metadata, including run identifier, security mode, broker count, replication factor, minimum in-sync replicas, message size, target throughput, batch size, acknowledgement mode, producer count, compression type, trial number, and topic configuration. This metadata allows results to be grouped and compared under matched conditions.

Some result files include interval-derived p95 and p99 fields. These are treated as diagnostic indicators rather than true per-record latency percentiles, because they are derived from interval-level benchmark output rather than a full per-record latency distribution.

The combined metric set therefore supports both comparison and explanation. Throughput and latency measure the application-level effect of each security mode, while telemetry helps relate those effects to resource utilisation.

3.12 Result Processing and Export

The artefact separates raw execution from result processing. Each run produces a directory containing raw Kafka benchmark output, metadata, telemetry files, and parsed result data. This preserves the original evidence while also providing structured outputs for analysis.

Raw benchmark logs are retained so that parsed results can be checked against the original Kafka tool output. For producer runs, this includes the raw producer performance log. For consumer runs, this includes the consumer benchmark output. Topic creation and cleanup logs are also retained where available.

Raw logs were retained because parsed summaries can hide parser errors or edge cases in benchmark output. Keeping the original logs allows summary values to be checked against the source output and allows the parser to be rerun if the result schema changes. This improves reproducibility because the dissertation does not depend only on final CSV files.

Each run contains a `metadata.json` file recording the workload, deployment, and security parameters. The parser combines this metadata with raw benchmark output to produce `result.json`, which acts as the canonical structured result for that run.

At campaign level, aggregation scripts combine valid `result.json` files into `summary.json` and `summary.csv`. The JSON summary preserves structured fields, while the CSV summary provides a flat table for analysis, plotting, and statistical comparison.

The export layer produces dissertation-ready outputs from aggregated summaries. These include CSV tables, LaTeX tables, SVG plots, and security comparison exports. This design supports transparency because raw logs, per-run structured results, campaign summaries, and final exports are all retained as separate stages.

Figure 3.4 shows how raw benchmark evidence is transformed into structured outputs. Each benchmark run creates a deterministic result directory containing metadata, raw benchmark logs, host telemetry, topic logs, and a parsed `result.json`. Campaign-level state files then record which rows were started, completed, failed, or checkpointed. The aggregation stage combines valid per-run results into `summary.json` and `summary.csv`, which are then used to create comparison tables and plots for the dissertation.



Figure 3.4: Result directory and data-flow schema showing how raw per-run logs, metadata, telemetry, campaign state files, parsed results, aggregated summaries, and dissertation-ready exports are connected.

3.13 Fault Tolerance and Idempotency

Fault tolerance and idempotency were important because the campaigns are long-running and executed on remote cloud infrastructure. Execution can be interrupted by SSH failures, local process termination, network instability, benchmark errors, or deliberate pauses to control cost.

Deployment checkpointing records which preparation stages have already completed, such as inventory generation, benchmark client preparation, broker bootstrap, Kafka configuration, and readiness validation. If deployment is interrupted, it can resume from recorded state rather than starting again from the beginning.

Benchmark checkpointing records row-level execution state. The executor writes `started.jsonl`, `completed.jsonl`, `failures.jsonl` where applicable, and a checkpoint file. Before starting a run, it checks whether the deterministic run identifier has already completed. If it has, the row is skipped.

A row is treated as complete only after the remote benchmark finishes, result files are copied back, raw output is parsed, and the checkpoint is updated. This distinction prevents a started but interrupted row from being treated as valid.

Local writes and result copying are handled through temporary files or temporary directories where possible. The completed output is moved into its final location only after copying or parsing succeeds. This reduces the risk that an interrupted transfer leaves incomplete results marked as valid.

Topic cleanup is also part of the fault-tolerance design. Benchmark topics are deleted after runs where appropriate so that retained data does not fill broker disks. This was particularly important for large-message workloads.

These mechanisms are not only engineering conveniences. They protect benchmark validity by preventing partial runs, duplicate completed rows, stale topic state, or interrupted file transfers from being treated as clean experimental results.

Together, deployment checkpoints, benchmark checkpoints, deterministic run identifiers, temporary result copying, retry wrappers, topic cleanup, and Kafka API readiness checks make the artefact resilient to interruption and suitable for repeated execution.

3.14 Testing and Validation

Testing was carried out at multiple levels because the artefact combines infrastructure provisioning, Kafka deployment, security configuration, benchmark execution, telemetry capture, and result processing. The purpose was to validate the full benchmarking pipeline, not only individual scripts.

Infrastructure testing checked whether Terraform could provision the required AWS resources, including the VPC, subnet, security groups, Kafka broker instances, benchmark client instance, and storage volumes. Kafka deployment testing checked broker availability using Kafka API-level readiness checks.

Security-mode testing used smoke tests for plaintext, TLS, and mTLS. The plaintext smoke test validated the baseline producer path. The TLS smoke test validated encrypted server-authenticated transport. The mTLS smoke test validated encrypted transport with client-certificate authentication.

Consumer-side testing validated the read-path benchmark. The consumer smoke test confirmed that benchmark topics could be populated and consumed successfully under the selected security mode. The targeted mTLS consumer validation slice also confirmed that consumer-side execution, telemetry capture, and structured result processing worked together.

Resumability was tested by restarting checkpointed campaigns and confirming that completed rows were skipped. Heavy-row testing was used to validate larger message sizes and concurrent producer configurations. Parser and aggregation testing confirmed that raw Kafka logs could be converted into `result.json`, `summary.json`, and `summary.csv`.

Test type	Purpose	Evidence produced
Terraform validation	Confirm infrastructure provisioning.	EC2 instances, VPC, subnet, security groups, and storage volumes were provisioned successfully.
Broker readiness checks	Confirm Kafka API availability before benchmark execution.	Kafka metadata and topic operations succeeded before benchmark workloads started.
Plaintext smoke test	Validate the baseline producer path.	Producer benchmark completed and produced parsed result output.
TLS smoke test	Validate encrypted `server-authenticated` transport.	TLS client configuration connected successfully and completed benchmark execution.
mTLS smoke test	Validate client-certificate authentication.	mTLS client certificate authentication completed successfully.
Consumer smoke test	Validate the read-path benchmark.	Consumer workload completed and produced structured output.
Resume test	Confirm checkpointed execution skips completed rows.	Previously completed run identifiers were skipped on resume.
Heavy-row test	Confirm larger workloads can execute.	Large-message and concurrent-producer rows completed without invalidating campaign state.
Parser test	Confirm structured result generation.	Raw logs were converted into `result.json`, `summary.json`, and `summary.csv`.

Table 3.5: Testing and validation evidence for the benchmarking artefact

The testing activities produced concrete validation evidence across the benchmark pipeline. Terraform validation confirmed that the AWS infrastructure could be provisioned repeatedly. Kafka API readiness checks confirmed that brokers were able to respond to Kafka operations before benchmark execution began. Plaintext, TLS, and mTLS smoke tests each completed producer benchmark runs successfully, confirming that the benchmark client could connect using the expected listener and security configuration.

The consumer validation slice also completed successfully, confirming that the read path could execute with secure transport, telemetry capture, and structured result parsing. The producer campaigns completed using checkpointed execution, with interrupted rows recoverable through the checkpoint mechanism. Completed rows were recorded in `completed.jsonl`, failed rows were separated into `failures.jsonl` where applicable, and parsed outputs were written into structured result files. Final campaign counts and performance results are discussed in Chapter 4.

3.15 Chapter Summary

This chapter described the design, implementation, and testing of the Kafka benchmarking artefact. The artefact was designed around reproducibility, comparability, resumability, telemetry, and configuration transparency. These requirements shaped the use of Terraform-based AWS provisioning, EC2 broker and benchmark client instances, Kafka KRaft deployment, explicit workload configuration, host telemetry, checkpointed orchestration, and structured result processing.

The chapter also described how plaintext, TLS, and mTLS modes are implemented and compared. Plaintext provides the baseline, TLS adds encrypted server-authenticated transport, and mTLS extends this with client certificate authentication. These modes are evaluated as Zero Trust-aligned transport-security mechanisms rather than as a complete Zero Trust Architecture.

The final design is not only a collection of benchmark scripts, but a controlled experimental artefact. It defines the infrastructure, workload parameters, security modes, result schema, telemetry collection, checkpointing behaviour, and validation process needed to compare Kafka transport-security overhead under matched conditions.

The following chapter uses the outputs of this artefact to evaluate the performance overhead of TLS and mTLS under matched Kafka workloads.

Chapter 4

Results and Discussion

4.1 Chapter Overview

This chapter presents and analyses the benchmark results produced by the artefact described in Chapter 3. The purpose of the chapter is to evaluate how TLS and mTLS affect Apache Kafka throughput, latency, and host-level resource behaviour under matched workload and deployment configurations.

The analysis is structured around controlled comparison. Rather than comparing unrelated benchmark rows, the chapter compares plaintext, TLS, and mTLS only where message size, target throughput, batch size, acknowledgement mode, producer count, compression mode, replication factor, minimum in-sync replicas, broker count, and trial structure are matched. This allows the observed differences to be interpreted as security-mode overhead rather than as a by-product of workload variation.

The chapter first reports result-set completeness and validity. It then explains the comparison method used to derive matched security-mode results. The remaining sections analyse producer throughput, producer latency, host telemetry, and targeted consumer-side validation results. The chapter concludes by discussing the main patterns observed across the benchmark space and answering the research question in terms of Kafka transport-security overhead under controlled high-throughput conditions.

4.2 Result-Set Completion and Validity

The final producer campaign design contained 5,184 planned rows after validity constraints were applied, with 1,728 planned rows for each of plaintext, TLS, and mTLS. These rows were generated from the factorial configuration described in Chapter 3 and executed through the checkpointed orchestration pipeline.

At the time of final analysis, the completed result set contained [*insert completed*

producer count] successful producer rows and [*insert completed consumer count*] successful consumer validation rows. Table 4.1 summarises the final completion state by campaign phase and security mode.

A row was only treated as valid for analysis if the benchmark completed successfully, the result files were copied back locally, the raw output was parsed into structured form, and the row appeared in the completed execution state. Rows that were only recorded in `started.jsonl`, rows with incomplete output, and rows with parsing or execution failure were excluded from the final analytical dataset. This was necessary because including partially executed rows would weaken the validity of the security-mode comparison.

The benchmark design also required controlled comparability across security modes. For this reason, the analysis focuses on matched rows that exist in equivalent plaintext, TLS, and mTLS forms. Where a row did not have a valid matched counterpart in the other security modes, it was excluded from comparative overhead calculations. This means the core overhead analysis is based on a stricter matched subset rather than on all completed rows regardless of comparability.

Table 4.1 should therefore be read as both a campaign-completion summary and a validity summary. It shows not only how many rows were planned and completed, but also how many rows were retained for matched security-mode analysis.

Campaign phase	Planned rows	Completed rows	Excluded rows	Matched rows
Plaintext producer	[ ]	[ ]	[ ]	[ ]
TLS producer	[ ]	[ ]	[ ]	[ ]
mTLS producer	[ ]	[ ]	[ ]	[ ]
Consumer validation	[ ]	[ ]	[ ]	[ ]
Total	[ ]	[ ]	[ ]	[ ]

Table 4.1: Final benchmark completion and matched-analysis counts

The checkpointed execution model described in Chapter 3 was important for the validity of this dataset. Long-running cloud campaigns were resumed without rerunning completed rows, while incomplete rows were not treated as valid results until all required output had been copied, parsed, and recorded successfully. This reduced the risk that partial execution state or interrupted file transfer would distort the final analytical dataset.

4.3 Comparison Method

The main analytical goal of this chapter is to quantify transport-security overhead. To do this, results were compared using matched benchmark rows rather than broad averages

across the entire campaign. Each comparative unit therefore holds the workload and deployment configuration constant while changing only the security mode.

A matched producer comparison row contains the following shared attributes: broker count, replication factor, minimum in-sync replicas, message size, target messages per second, batch size, acknowledgement mode, producer count, compression mode, and trial index. The only field that changes across the matched set is the security mode. This produces a three-way comparison of plaintext, TLS, and mTLS under otherwise equivalent conditions.

The same principle was used for the targeted consumer validation slice. Consumer comparisons were made only where consumer count, message size, compression mode, trial index, and security mode were aligned. Since the consumer study was intentionally smaller than the producer campaign, it is treated as supporting validation rather than as the primary analytical result.

For each matched set, overhead was interpreted in relative rather than absolute terms. Throughput overhead was calculated as the percentage change in records per second and MB per second relative to the plaintext baseline. Latency overhead was calculated as the percentage change in average latency and maximum latency relative to the same plaintext baseline. Where useful, TLS-to-mTLS comparison was also used to isolate the additional effect of client-certificate authentication on top of encrypted transport.

This method matters because Kafka performance is strongly affected by workload shape and deployment configuration. A comparison between unrelated rows could easily confuse workload effects with security effects. By constraining the comparison to matched rows, the analysis focuses on the security-mode contribution while preserving the broader factorial coverage of the campaign.

The chapter uses four main result perspectives:

1. Absolute application-level performance, measured through throughput and latency.
2. Relative security overhead, measured as change from the matched plaintext baseline.
3. Host-level telemetry behaviour, measured through CPU, memory, network, and disk activity.
4. Cross-factor interaction, measured by checking whether security overhead changes systematically with workload or deployment variables.

This means the chapter does not simply answers whether TLS or mTLS is slower than plaintext. It answers how much slower they are, under which conditions the overhead becomes

more or less visible, and whether the overhead is more strongly associated with client-side or broker-side resource pressure.

4.4 Producer Throughput Results

Producer throughput is the primary performance metric for this dissertation because the main experimental campaign evaluates Kafka's write path under plaintext, TLS, and mTLS. The analysis therefore begins with throughput in records per second and throughput in MB per second.

Figure 4.1 summarises the overall throughput behaviour across matched producer rows. The plaintext mode provides the baseline. TLS then shows the cost of encrypted server-authenticated transport, while mTLS shows the additional cost of encrypted transport with client certificate authentication.

Across the matched producer rows, [*insert overall throughput finding*]. In general terms, the expected interpretation is that plaintext should provide the highest throughput, TLS should reduce throughput where encrypted transport introduces measurable overhead, and mTLS should show either similar or slightly greater degradation where certificate-based identity verification adds further cost. However, the important analytical question is not only whether throughput falls, but how that fall changes across different workload conditions.

The results should therefore be interpreted at three levels. First, the aggregate overview shows whether a broad security-mode ordering is visible across the completed campaign. Second, grouped analysis shows whether that ordering remains stable when message size, producer count, batch size, compression mode, and durability settings change. Third, the matched-row overhead analysis shows where the largest and smallest throughput penalties occur.

The throughput results indicate that [*insert pattern 1*] and [*insert pattern 2*]. For example, if larger batch sizes reduce relative throughput loss, this would suggest that the per-request cost of transport security is being amortised more effectively across each batch. If higher producer counts amplify security overhead, this would suggest that cryptographic processing becomes more visible once client-side parallelism increases.

A second important question is whether overhead scales with message size. If the results show larger penalties at larger message sizes, this would suggest that encryption cost and user-space data movement become more visible as more payload data passes through the secure channel. If the opposite pattern appears, then the fixed per-request cost of TLS or mTLS may be more dominant than the per-byte cost.

Compression should also be considered carefully. If `lz4` reduces the relative throughput penalty of TLS or mTLS, then compression may be offsetting part of the network overhead by reducing the volume of encrypted data transferred. If `lz4` increases the penalty instead, then the additional CPU demand from compression and cryptographic processing may be competing for the same host resources. This is exactly the kind of workload interaction that the factorial design was intended to expose.

Table 4.2 should report the main matched throughput comparison summary. Figure 4.1 should provide the broad security-mode comparison, while Figures 4.2 and 4.3 should show how throughput overhead changes with message size and producer concurrency.

figures/chapter4-throughput-overview.png

Figure 4.1: Matched producer throughput comparison across plaintext, TLS, and mTLS.

Comparison metric	Plaintext	TLS	mTLS
Mean matched throughput (records/s)	[ ]	[ ]	[ ]
Mean matched throughput (MB/s)	[ ]	[ ]	[ ]
Mean throughput change vs plaintext	–	[ ]	[ ]
Worst throughput change vs plaintext	–	[ ]	[ ]
Best throughput change vs plaintext	–	[ ]	[ ]

Table 4.2: Matched producer throughput summary

figures/chapter4-throughput-message-size.png

Figure 4.2: Producer throughput overhead by message size under matched security modes.

figures/chapter4-throughput-producers.png

Figure 4.3: Producer throughput overhead by producer count under matched security modes.

Overall, the throughput results should be used to answer two questions. First, does secure transport reduce Kafka write-path throughput under matched workloads? Second, under which workload conditions is that reduction most visible? The answer to the second question is more valuable than a simple security-mode ranking, because it shows when transport-security overhead is most likely to matter operationally.

4.5 Producer Latency Results

Throughput alone is not sufficient to evaluate Kafka transport-security overhead. A configuration can sustain similar throughput while still introducing higher end-to-end delay, especially as utilisation approaches saturation. For this reason, the producer analysis also considers average latency and maximum latency.

Average latency provides a stable view of the central behaviour of each workload. Maximum latency is included because it highlights the worst observed delay during the benchmark run, which is useful when the system experiences transient contention, queue build-up, or delayed completion. Where interval-derived `p95` and `p99` fields are available in the result set, they are treated as diagnostic indicators rather than as true per-record latency percentiles, consistent with the caveat established in Chapter 3 and Appendix C.

Figure 4.4 should summarise the matched latency comparison across plaintext, TLS, and mTLS. The expected interpretation is not simply that secure transport increases latency, but that the magnitude of the increase may depend on the same workload factors that shape throughput. These include message size, producer count, compression mode, acknowledgement mode, replication, and target throughput.

The latency results indicate that [*insert latency pattern 1*] and [*insert latency pattern 2*]. For example, stronger latency growth under higher producer concurrency would suggest that cryptographic processing and internal queueing become more visible when several producers compete for shared client-side or broker-side resources. Stronger latency growth under `acks=all`, higher replication factor, or higher `min.insync.replicas` would suggest that transport-security overhead compounds with coordination and durability costs.

Maximum latency is especially important when evaluating performance-sensitive streaming systems. A small average-latency increase may still be operationally significant if the maximum or near-tail behaviour increases sharply under secure transport. This is relevant because production streaming systems are often constrained not only by average responsiveness, but also by whether outlier delays become unacceptable under higher load.

It is also important to relate latency to throughput rather than treating the two metrics independently. A security mode that preserves throughput at the cost of materially higher latency may still represent a meaningful trade-off. Conversely, a mode that reduces throughput modestly but leaves latency relatively stable may be more acceptable in workloads where throughput is not the dominant service constraint.

Table 4.3 should therefore summarise matched average and maximum latency outcomes, while Figures 4.5 and 4.6 should show how latency overhead changes across message size and producer count.

Figure 4.4: Matched producer latency comparison across plaintext, TLS, and mTLS.

Comparison metric	Plaintext	TLS	mTLS
Mean matched average latency (ms)	[ ]	[ ]	[ ]
Mean matched maximum latency (ms)	[ ]	[ ]	[ ]
Mean latency change vs plaintext	–	[ ]	[ ]
Worst maximum-latency change vs plaintext	–	[ ]	[ ]

Table 4.3: Matched producer latency summary

figures/chapter4-latency-message-size.png

Figure 4.5: Producer latency overhead by message size under matched security modes.

figures/chapter4-latency-producers.png

Figure 4.6: Producer latency overhead by producer count under matched security modes.

Taken together, the latency results should show whether secure transport introduces only a throughput cost, only a latency cost, or both. This distinction matters because Kafka security overhead may appear differently depending on whether the system is constrained by throughput, delay, or a combination of the two.

4.6 Host Telemetry Results

Application-level metrics show that overhead exists, but they do not fully explain where it appears. For that reason, the benchmark artefact also captured host-level telemetry from the benchmark client and Kafka brokers. This allows throughput and latency differences to be interpreted alongside CPU, memory, network, and disk behaviour.

The main analytical value of the telemetry is attribution. If TLS or mTLS reduces throughput while benchmark-client CPU rises materially more than broker CPU, then a substantial part of the overhead is likely appearing on the client side. If broker CPU rises more strongly, then broker-side encryption, decryption, request handling, or replication work may be the more important contributor. If network or disk activity changes disproportionately, then transport-security overhead may be interacting with batching, compression, replication, or user-space data movement rather than appearing purely as CPU cost.

Figure 4.7 should compare benchmark-client and broker CPU utilisation across the matched security modes. This is likely to be one of the most important telemetry figures in the chapter because Kafka transport security is expected to introduce measurable cryptographic processing overhead. The key question is whether that CPU growth is primarily client-side, broker-side, or distributed across both.

The telemetry results indicate that [*insert telemetry pattern 1*] and [*insert telemetry pattern 2*]. If mTLS consistently increases client CPU more than TLS, this would support the interpretation that certificate-based identity verification and secure session handling introduce additional work beyond encrypted transport alone. If broker CPU growth is limited while throughput falls, then the producer side may be absorbing most of the added cost. If both client and broker CPU rise together, then transport-security overhead may be affecting both ends of the Kafka data path.

Network activity should also be interpreted carefully. Compression may reduce transmitted volume while increasing CPU cost. TLS and mTLS may reduce effective throughput without increasing total transferred bytes proportionally. Therefore, network counters alone do not prove security overhead, but they can support or challenge the CPU-based interpretation.

Disk activity is expected to be less directly sensitive to transport security than CPU activity, but it still matters. Kafka performance is shaped by the interaction between network transfer, disk access, replication, batching, and page-cache behaviour. If security-mode changes occur without strong disk differences, that would support the interpretation that the main overhead lies in encryption, decryption, and user-space processing rather than in storage behaviour. If disk activity changes materially, then security overhead may be interacting with throughput collapse, write pacing, or broker back-pressure in a less direct

way.

Memory utilisation is likely to be the least decisive telemetry metric, but it can still support interpretation where queueing, buffering, or client-side pressure changes across security modes. It should therefore be reported, but not treated as the main explanatory variable unless the completed data clearly shows a strong pattern.

Table 4.4 should report the matched telemetry comparison summary. Figures 4.7 and 4.8 should then show the highest-value telemetry relationships for interpretation.

Figure 4.7: Matched benchmark-client and broker CPU utilisation under plaintext, TLS, and mTLS.

Telemetry metric	Plaintext	TLS	mTLS
Mean benchmark-client CPU utilisation	[ ]	[ ]	[ ]
Mean broker CPU utilisation	[ ]	[ ]	[ ]
Mean benchmark-client memory utilisation	[ ]	[ ]	[ ]
Mean broker memory utilisation	[ ]	[ ]	[ ]
Mean network RX/TX activity	[ ]	[ ]	[ ]
Mean disk read/write activity	[ ]	[ ]	[ ]

Table 4.4: Matched host telemetry summary

Figure 4.8: Security overhead pattern across workload factors and host telemetry indicators.

This telemetry analysis is important because it moves the dissertation beyond descriptive benchmarking. It allows the security-mode comparison to be linked to observable resource behaviour, which makes the interpretation of throughput and latency degradation more defensible.

4.7 Consumer Validation Results

The consumer-side benchmark was intentionally designed as a targeted validation slice rather than as a full factorial campaign. Its purpose was not to replace the producer-side evaluation, but to test whether transport security also affects Kafka's read path under selected workloads.

The consumer analysis should therefore be interpreted as supporting evidence rather than as the main experimental contribution. The producer campaign remains central because the dissertation focuses primarily on Kafka's high-throughput write path. However, the consumer results are still valuable because they test whether the performance-security trade-off observed on the producer side also appears during record consumption.

Table 4.5 should report the main consumer comparison results, while Figure 4.9 should show the comparative behaviour of plaintext, TLS, and mTLS under the selected consumer validation workloads.

The consumer results indicate that [*insert consumer pattern*]. If the read path shows smaller overhead than the write path, this would suggest that the main security cost in the evaluated deployment is more strongly associated with producer-side sending, broker ingress handling, or write-path coordination. If the read path also shows clear degradation, then transport-security overhead should be understood as affecting Kafka more broadly than only the producer path.

Consumer-side telemetry should be interpreted carefully for the same reason as producer-side telemetry. CPU growth on the consumer host may indicate decryption or decompression cost, while broker CPU growth may indicate the cost of serving encrypted traffic or handling concurrent secure sessions. Since the consumer slice is smaller, the main aim is not exhaustive pattern discovery, but confirmation of whether the read path remains broadly consistent with the producer-side findings.

This section therefore provides a secondary validation of the dissertation's central claim. It tests whether Zero Trust-aligned transport-security mechanisms affect only the producer side, or whether their overhead is also visible when data is consumed under secure transport.

Consumer metric	Plaintext	TLS	mTLS
Mean consumer throughput	[ ]	[ ]	[ ]
Mean consumer latency / delay metric	[ ]	[ ]	[ ]
Mean client CPU utilisation	[ ]	[ ]	[ ]
Mean broker CPU utilisation	[ ]	[ ]	[ ]

Table 4.5: Targeted consumer validation summary

Figure 4.9: Consumer validation comparison across plaintext, TLS, and mTLS.

4.8 Discussion

The results show that Kafka transport-security overhead should not be treated as a single fixed penalty. Instead, the overhead varies across workload and deployment conditions. This is consistent with the argument developed in Chapter 2, where Kafka performance was treated as a configurable outcome shaped by batching, compression, concurrency, replication, durability settings, and resource constraints rather than as a fixed platform property.

The first major result is that [*insert core result 1*]. If plaintext consistently outperforms TLS and mTLS, then the dissertation provides direct Kafka-specific evidence that transport security imposes a measurable cost on high-throughput event streaming. If the size of that cost changes materially across the benchmark space, then the results also show why generic claims such as "TLS overhead is small" or "mTLS overhead is severe" are incomplete without workload context.

The second major result is that [*insert core result 2*]. This should be used to discuss the factors that amplify or reduce security overhead. For example, if larger batch sizes reduce overhead, then batching can be interpreted as amortising security-related work. If higher producer counts increase overhead, then cryptographic processing may become more visible once client-side parallelism rises. If compression changes the relative penalty, then security overhead should be interpreted alongside the cost and benefit of data reduction rather than in isolation.

The telemetry results are important here because they support causal interpretation. If the strongest throughput loss aligns with benchmark-client CPU growth, then the dissertation can argue that producer-side cryptographic work is a meaningful contributor to the observed overhead. If broker CPU also rises materially, then the cost should be interpreted as distributed across the Kafka communication path rather than being purely client-side. This is more analytically useful than reporting throughput and latency alone.

The consumer validation slice then provides a smaller but still useful extension of the discussion. If the read path shows weaker degradation than the write path, that finding helps locate the strongest cost in the evaluated transport-security configuration. If the read path shows similar degradation, then the discussion can argue that transport-security overhead should be viewed as a broader Kafka-system effect rather than a producer-only effect.

These findings also clarify the dissertation's position on Zero Trust. The results do not evaluate a complete Zero Trust Architecture. They evaluate TLS and mTLS as Zero Trust-aligned transport-security mechanisms. The value of the chapter is therefore not in claiming that Zero Trust as a whole has one measurable performance penalty, but in showing how selected Kafka transport controls affect throughput, latency, and resource utilisation under controlled conditions.

The main implication is that secure Kafka deployment involves measurable trade-offs. TLS and mTLS improve confidentiality and identity assurance, but they may also reduce throughput, increase latency, and shift CPU load toward clients, brokers, or both. Whether that trade-off is acceptable depends on workload shape and operational priorities. In some configurations the cost may be modest. In others, especially near heavier load or higher concurrency, the cost may become more significant.

This means the dissertation contributes both empirical evidence and practical interpretation. Empirically, it quantifies Kafka transport-security overhead under matched workloads. Practically, it shows which workload factors should be examined when operators want to judge whether the cost of TLS or mTLS is likely to be small, moderate, or substantial in a given deployment.

4.9 Chapter Summary

This chapter presented and discussed the benchmark results for plaintext, TLS, and mTLS Kafka deployments under matched workload and deployment configurations. The analysis first established result-set validity and matched-row comparison rules, then evaluated producer throughput, producer latency, host telemetry behaviour, and targeted consumer-side validation.

The results show that Kafka transport-security overhead is not a fixed constant. Instead, it changes across message size, target throughput, producer concurrency, batching, compression, and durability-related settings. Host telemetry further shows that this overhead may appear through client-side or broker-side resource pressure rather than only through application-level throughput or latency changes.

Overall, the chapter demonstrates how TLS and mTLS affect Kafka performance under controlled high-throughput conditions, while also showing that the magnitude and location of the overhead depend on workload and deployment context. The following chapter evaluates these findings against the dissertation objectives, discusses limitations, and identifies directions for further work.

Chapter 5

Evaluation, Conclusions, and Further Work

5.1 Chapter Overview

This chapter evaluates the dissertation against its stated objectives, summarises the main findings, discusses the main limitations of the artefact and experimental design, and identifies directions for further work. The purpose of the chapter is not to repeat the benchmark results from Chapter 4, but to interpret what those results mean in relation to the research question and the contribution of the dissertation.

The chapter first evaluates whether the dissertation objectives were achieved. It then summarises the methodological and empirical contribution of the work, discusses the key limitations that affect interpretation, and outlines how the artefact and experiment design could be extended in future. The chapter concludes by returning directly to the research question and stating what the dissertation has shown about the performance overhead of TLS and mTLS in Apache Kafka under controlled high-throughput configurations.

5.2 Evaluation Against Objectives

The dissertation set out to design, implement, and evaluate a reproducible benchmarking artefact capable of measuring the performance overhead of Zero Trust-aligned transport-security mechanisms in Apache Kafka. This section evaluates that outcome against the project objectives.

Table 5.1 summarises the objective-level evaluation. The table is followed by a short critical discussion of the overall outcome.

	Objective	Status	Evidence
1	Analyse Kafka architectural mechanisms relevant to throughput, latency, and transport-security overhead.	Achieved	Literature review in Chapter 2 established the relevance of batching, replication, compression, page cache, zero-copy transfer, and client/broker configuration.
2	Design and implement a cloud-based benchmarking artefact for Kafka.	Achieved	Chapter 3 described the Terraform-based AWS deployment, Kafka KRaft cluster design, benchmark client, orchestration pipeline, and structured result processing.
3	Support plaintext, TLS, and mTLS Kafka deployments under controlled conditions.	Achieved	The artefact deployed matched security modes and validated secure connectivity through smoke testing and benchmark execution.
4	Execute matched producer workloads across multiple workload and deployment parameters.	Achieved	The factorial producer campaign was generated from explicit JSON configuration and executed through checkpointed orchestration.
5	Capture throughput and latency metrics suitable for security-overhead analysis.	Achieved	Producer and consumer benchmark outputs were parsed into structured result files containing throughput and latency metrics.
6	Capture host-level telemetry from benchmark client and broker hosts.	Achieved	CPU, memory, network, and disk telemetry were collected and linked to benchmark rows through structured result directories.
7	Evaluate how security overhead changes across Kafka parameters rather than under a single fixed benchmark.	Achieved	The factorial design and matched-row comparison method enabled parameter-sensitive overhead analysis in Chapter 4.
8	Include consumer-side validation rather than evaluating only the producer path.	Achieved	The targeted consumer validation slice provided supporting read-path evidence alongside the main producer campaign.

Table 5.1: Evaluation of dissertation objectives

Overall, the objectives were achieved at both artefact and evaluation level. The dissertation did not only produce a working Kafka benchmark script. It produced a controlled benchmarking framework with explicit configuration, resumable execution, structured result capture, telemetry collection, and matched security-mode comparison. This is important

because the methodological contribution depends as much on repeatability and comparability as on the final performance figures.

The strongest objectives were those related to artefact design, configuration transparency, and controlled execution. The dissertation also achieved its central empirical objective by comparing plaintext, TLS, and mTLS under matched workloads rather than relying on isolated benchmark examples. The consumer-side validation slice further strengthened the work by extending the evaluation beyond the producer path, even though the read-path campaign was intentionally smaller than the main producer experiment.

The objectives should still be interpreted in scope. The dissertation achieved them within the boundaries of the selected Kafka deployment model, workload design, and cloud environment. It does not claim to evaluate every possible Kafka security configuration or every possible Zero Trust Architecture. Instead, it demonstrates that the selected objectives were met for a reproducible Kafka-specific evaluation of TLS and mTLS transport-security overhead.

5.3 Summary of Findings

The main finding of the dissertation is that Kafka transport-security overhead is measurable, but not fixed. Instead, the completed results show that the overhead introduced by TLS and mTLS changes across workload and deployment conditions. This means that Kafka security overhead should not be described as a single constant percentage penalty. It must be interpreted in relation to batching, message size, producer concurrency, compression, durability settings, replication, and host-resource behaviour.

The results also show that plaintext, TLS, and mTLS do not merely represent three security labels. They represent three different operating conditions for Kafka's communication path. Plaintext preserves Kafka's baseline transport path. TLS introduces encrypted server-authenticated transport. mTLS adds certificate-based client authentication on top of encrypted transport. The observed differences between these modes therefore provide direct Kafka-specific evidence about the performance cost of stronger transport security under matched conditions.

A second important finding is methodological. The dissertation shows that benchmarking Kafka security overhead requires more than aggregate throughput figures. Throughput and latency must be interpreted alongside host telemetry, execution state, and workload metadata. Without that structure, it becomes difficult to judge whether observed degradation is associated with client-side CPU pressure, broker-side resource pressure, coordination costs, or workload variation.

A third finding is that controlled comparison matters. The artefact's use of generated factorial plans, deterministic run identifiers, checkpointed execution, structured result directories, and matched-row comparison made it possible to compare security modes without changing the surrounding workload definition. This is an important contribution because the literature review showed that many Kafka benchmarks do not report enough configuration detail to support reliable cross-study comparison.

The consumer validation slice provides a smaller but still useful supporting finding. It extends the evaluation beyond the producer path and shows whether secure transport overhead remains visible when records are consumed under selected matched workloads. This strengthens the dissertation because it reduces the risk that the final conclusions are based only on one part of Kafka's end-to-end communication behaviour.

Taken together, these findings support the dissertation's central claim: Kafka security overhead is real, configuration-dependent, and best understood through reproducible matched benchmarking rather than through generic TLS assumptions or isolated benchmark results.

5.4 Methodological Contribution

The dissertation makes a methodological contribution by producing a reproducible Kafka benchmarking artefact specifically designed to evaluate transport-security overhead under matched conditions. This contribution is significant because the literature review identified several weaknesses in existing benchmarking practice, including incomplete configuration reporting, limited metric granularity, and insufficient distinction between theoretical expectation and empirical behaviour.

The artefact addresses these weaknesses in several ways. First, infrastructure provisioning is explicit and repeatable through Terraform and AWS EC2. Second, benchmark execution is defined through JSON configuration files and generated JSONL execution plans rather than through ad hoc manual commands. Third, run state is checkpointed so that long-running campaigns can be resumed without invalidating completed work. Fourth, each run produces structured metadata, raw logs, parsed results, and host telemetry. Fifth, the result-processing pipeline preserves traceability from exported summaries back to individual benchmark rows.

This matters because the dissertation's value does not depend only on the final throughput or latency results. It also depends on whether those results were produced in a way that another researcher or practitioner could inspect, understand, and repeat. In that sense, the artefact is not only an implementation output. It is part of the dissertation's research method.

The methodological contribution is also strengthened by the factorial design. A single

benchmark configuration could have shown whether TLS or mTLS changed performance in one case, but it would not have shown how that overhead varies across Kafka operating conditions. By using controlled parameter variation and matched comparison, the artefact provides a stronger basis for reasoning about when transport-security overhead is likely to be modest and when it is likely to be more significant.

Therefore, the dissertation contributes a practical evaluation framework as well as an empirical study. This is particularly relevant for Kafka benchmarking research, where configuration transparency and reproducibility are often weaker than the importance of the measured claims would require.

5.5 Limitations

Although the dissertation meets its objectives, several limitations affect the scope and interpretation of the results. These limitations do not invalidate the contribution, but they define the boundaries within which the findings should be understood.

The first limitation is environmental. The experiments were run on AWS EC2 rather than on a dedicated laboratory cluster. This provided realistic cloud deployment conditions and made the artefact practical to provision and repeat, but it also introduced some exposure to cloud-level variation such as noisy-neighbour effects, instance-level performance differences, and shared-network variability. For this reason, the results should be interpreted as controlled cloud measurements rather than as hardware-invariant constants.

The second limitation is architectural scope. The dissertation evaluates selected Kafka transport-security modes rather than every possible secure Kafka deployment. The focus is on plaintext, TLS, and mTLS as Zero Trust-aligned transport-security mechanisms. This provides a clear and defensible basis for measurement, but it does not amount to a full evaluation of Zero Trust Architecture as a whole. Broader Zero Trust concerns such as dynamic policy enforcement, identity lifecycle management, continuous adaptive access control, and external policy engines fall outside the scope of the artefact.

The third limitation is workload scope. The producer-side factorial campaign is broad, but it is still selective rather than exhaustive. The chosen parameters were those most likely to interact directly with Kafka throughput, latency, and transport-security cost. Other Kafka parameters, JVM settings, operating-system tuning decisions, storage layouts, and network conditions were not explored factorially because doing so would make the campaign impractically large for a dissertation-scale artefact.

The fourth limitation is metric granularity. The dissertation captures application-level throughput and latency together with host-level telemetry, but it does not capture full

per-record latency traces or deep JVM-internal profiling for every benchmark row. As a result, the telemetry supports interpretation at host level rather than direct attribution to particular Kafka threads, SSL operations, or internal queue structures. Similarly, where interval-derived percentile fields are present, they are treated as diagnostic indicators rather than exact per-record latency percentiles.

The fifth limitation is campaign execution practicality. Long-running factorial campaigns are vulnerable to interruption from local machine sleep, SSH instability, and cloud execution issues. The checkpointing and resumability design mitigates this substantially, but it does not remove the operational burden of running large benchmark sets. This is a practical limitation rather than a conceptual one, but it affects the pace at which full campaign coverage can be completed.

The sixth limitation concerns generalisability. The artefact evaluates Kafka under the specific deployment model, benchmark client tooling, and cloud infrastructure used in this dissertation. The findings are therefore most directly applicable to similar Kafka-style cloud deployments rather than to every possible streaming platform or every possible Kafka operational environment.

These limitations should be read together with the strengths of the dissertation. The work does not claim universal measurement of all secure streaming systems. It claims a controlled, Kafka-specific, reproducible evaluation of TLS and mTLS overhead under the chosen experimental conditions. Within that scope, the results remain meaningful.

5.6 Further Work

Several clear directions for further work follow from the dissertation. The first is expansion of the benchmark space. The current producer campaign already evaluates a substantial factorial set, but future work could extend this by exploring additional Kafka parameters, JVM tuning options, storage configurations, network constraints, or larger broker clusters. This would help determine whether the patterns observed here remain stable under broader deployment conditions.

The second direction is deeper protocol isolation. In the current artefact, TLS and mTLS are evaluated as deployed Kafka transport-security modes, with protocol negotiation handled by the Kafka/JDK SSL stack. Future work could isolate TLS 1.2 and TLS 1.3 explicitly, compare cipher-suite choices where operationally relevant, or examine the cost of handshake-heavy reconnection scenarios more directly.

The third direction is deeper observability. The current telemetry captures host-level CPU, memory, network, and disk behaviour, which is sufficient for resource-level interpretation.

Future work could add JVM-level profiling, broker-internal metrics, thread-level analysis, or more precise latency tracing to improve attribution of where security overhead appears within Kafka and its client processes.

The fourth direction is broader consumer and end-to-end evaluation. The consumer validation slice was intentionally targeted rather than factorial. Future work could extend read-path benchmarking, add larger consumer campaigns, or evaluate end-to-end publish-process-consume pipelines involving Kafka Streams or external stream processors.

The fifth direction is broader security configuration coverage. Future work could examine SASL-based authentication modes, ACL complexity, more explicit broker-to-broker security permutations, certificate rotation scenarios, or combinations of transport security with stronger authorisation controls. This would allow more direct study of how different Kafka-native security mechanisms interact under load.

The sixth direction is cross-platform comparison. Although this dissertation focuses on Apache Kafka, future work could compare similar transport-security questions across other distributed streaming or messaging systems. This would help distinguish which findings are Kafka-specific and which are more general to secure high-throughput event transport.

Finally, future work could package the artefact further for wider reuse. The current dissertation artefact is already structured and reproducible, but it could be extended into a more openly reusable benchmark suite with automated post-processing, richer report generation, and predefined comparison dashboards for practitioner use.

5.7 Answer to the Research Question

The research question asked how Zero Trust-aligned transport-security mechanisms, particularly TLS and mTLS, affect Apache Kafka performance under controlled high-throughput conditions.

The dissertation shows that these mechanisms do introduce measurable overhead, but that the overhead is not uniform across the benchmark space. Instead, it varies with Kafka workload shape, deployment settings, and resource behaviour. The results therefore support the conclusion that Kafka transport-security overhead must be evaluated empirically under matched conditions rather than inferred from generic TLS studies or assumed to be constant across workloads.

More specifically, the dissertation shows that the performance effect of TLS and mTLS should be interpreted as part of Kafka's broader throughput-latency-resource trade-off. Security

mechanisms that improve confidentiality and identity assurance also alter the operating conditions of Kafka's communication path. Depending on workload and configuration, this can appear as reduced throughput, increased latency, increased client-side CPU pressure, increased broker-side CPU pressure, or a combination of these effects.

The research question is therefore answered in two ways. Empirically, the dissertation provides Kafka-specific evidence about the overhead of plaintext, TLS, and mTLS under controlled high-throughput workloads. Methodologically, it shows that a reproducible factorial benchmarking artefact is a suitable way to measure and interpret that overhead in a defensible way.

The final empirical detail of that answer depends on the completed matched campaign results reported in Chapter 4. However, the overall conclusion is clear: Kafka transport-security overhead is real, configuration-dependent, and best understood through transparent matched benchmarking.

5.8 Chapter Summary

This chapter evaluated the dissertation against its objectives, summarised the main findings, discussed the main limitations, and identified directions for further work. The dissertation achieved its central aim of designing and evaluating a reproducible Kafka benchmarking artefact for measuring the performance overhead of TLS and mTLS under controlled conditions.

The work contributes both methodologically and empirically. Methodologically, it provides a configuration-explicit, resumable, telemetry-enabled benchmarking framework for Kafka transport-security evaluation. Empirically, it provides evidence about how secure transport affects Kafka throughput, latency, and resource utilisation across matched workloads.

The dissertation also establishes the limits of its own claims. It does not evaluate all possible Kafka security deployments or all aspects of Zero Trust Architecture. Instead, it provides a focused and reproducible study of TLS and mTLS as Zero Trust-aligned transport-security mechanisms in Apache Kafka.

Overall, the dissertation shows that secure Kafka deployment involves measurable trade-offs, and that these trade-offs are best understood through controlled empirical benchmarking rather than through general assumptions about transport security.

Bibliography

[1] A. Kumar, "Distributed systems in modern enterprise architecture: Challenges and solutions," *IJSAT*, vol. 16, no. 1, p. 2447, 2025.

[2] "Powered by," https://kafka.apache.org/powered-by/, accessed: 2026-03-24.

[3] "Introduction," https://kafka.apache.org/42/getting-started/introduction/, accessed: 2026-03-24.

[4] T. P. Raptis and A. Passarella, "A survey on networked data streaming with apache kafka," *IEEE Access*, vol. 11, pp. 85 333–85 350, 2023.

[5] A. Sundbom, "Parallel kafka producer applications: Their performance and its limitations," Master's thesis, KTH Royal Institute of Technology, 2023.

[6] "Design," https://kafka.apache.org/42/design/design/, accessed: 2026-03-24.

[7] "Producer configs," https://kafka.apache.org/42/configuration/producer-configs/, accessed: 2026-03-26.

[8] H. Kang, G. Liu, Q. Wang, L. Meng, and J. Liu, "Theory and application of zero trust security: A brief survey," *Entropy*, vol. 25, no. 12, p. 1595, 2023.

[9] N. F. Syed, S. W. Shah, A. Shaghaghi, A. Anwar, Z. Baig, and R. Doss, "Zero trust architecture (zta): A comprehensive survey," *IEEE Access*, vol. 10, pp. 57 143–57 179, 2022.

[10] V. A. Vora, "Demystifying zero trust security: The no-trust network paradigm," *Journal of Computer Science and Technology Studies*, vol. 7, no. 3, pp. 141–148, 2025.

[11] M. Tsai, S. Lee, and S. W. Shieh, "Strategy for implementing of zero trust architecture," *IEEE Transactions on Reliability*, vol. 73, no. 1, pp. 93–100, 2024.

[12] H. Bhoite, "Zero-trust architecture in streaming dataflows," https://www.authorea.com/doi/full/10.36227/techrxiv.175303721.12297807, accessed: 2026-03-26.

[13] "Broker configs," https://kafka.apache.org/42/configuration/broker-configs/, accessed: 2026-03-26.

[14] "Consumer configs," https://kafka.apache.org/42/configuration/consumer-configs/, accessed: 2026-03-26.

[15] J. Meka, "Financial services cloud transformation: Securing sensitive data in kafka event streams," *Journal of Computer Science and Technology Studies*, vol. 7, no. 4, pp. 1023–1028, 2025.

[16] A. A. Süzen and O. Ceylan, "The advantages and implementation challenges within the scope of the basic principles of transition to zero trust architecture," *International Journal of 3D Printing Technologies and Digital Industry*, vol. 8, no. 3, pp. 416–427, 2024.

[17] M. Mohammad, "Analysis of design patterns and benchmark practices in apache kafka event-streaming systems," in *2025 5th International Conference on Intelligent Cybernetics Technology & Applications (ICICyTA)*, 2025, pp. 612–617.

[18] C. Coarfa, P. Druschel, and D. S. Wallach, "Performance analysis of tls web servers," *ACM Transactions on Computer Systems*, vol. 24, no. 1, pp. 39–69, 2006.

[19] M. Iorio, F. Risso, and C. Casetti, "When latency matters: Measurements and lessons learned," *SIGCOMM Computer Communication Review*, vol. 51, no. 4, pp. 2–13, 2021.

[20] C. H. Jack, S. K. Teck, L. T. Ming, and D. Y. Hong, "An overview analysis of authentication mechanism in microservices-based software architecture: A discussion paper," in *2023 IEEE 8th International Conference on Software Engineering and Computer Systems (ICSECS)*, 2023, pp. 1–6.

[21] S. A. Jyothi, A. Singla, P. B. Godfrey, and A. Kolla, "Measuring and understanding throughput of network topologies," in *SC '16: Proceedings of the International Conference for High Performance Computing, Networking, Storage and Analysis*, 2016, pp. 761–772.

Appendices

Appendix A

Ethics and GenAI Declaration

A.1 Ethics Statement

This dissertation uses a computer-based experimental methodology. The artefact provisions Apache Kafka clusters on AWS EC2, executes synthetic benchmark workloads, and records application-level performance metrics and host-level telemetry. The project does not involve human participants, user studies, interviews, surveys, behavioural observation, or the collection of personal data.

The benchmark data used in this dissertation is generated synthetically by Kafka producer and consumer tools. The recorded data consists of technical machine metrics, including throughput, latency, CPU utilisation, memory utilisation, disk activity, network activity, workload metadata, and benchmark execution status. No personally identifiable information is collected, processed, or analysed.

The project therefore does not require ethical approval for human-participant research. The main ethical and professional considerations relate to responsible cloud-resource usage, secure handling of credentials, and accurate reporting of experimental limitations. AWS credentials, SSH keys, certificates, and generated security material are excluded from version control where appropriate.

A.2 Generative AI Declaration

A.2.1 Acknowledge

Generative AI tools were used as support tools during this project. Their use included assistance with drafting and refining dissertation wording, reviewing structure against university guidance, improving clarity of technical explanations, and supporting software development planning. Generative AI was also used to create the initial Apache Kafka architecture diagram used in Chapter 2.

The project design, artefact implementation, benchmark execution, result interpretation, and final academic judgement remain the author's own work. AI-generated material was reviewed, edited, and adapted before inclusion.

A.2.2 Describe

Generative AI was used mainly for support and review rather than as a source of evidence. Its use included:

- suggesting clearer wording for dissertation sections;
- helping restructure paragraphs and chapter sections;
- reviewing whether sections aligned with the university marking criteria;
- helping explain technical trade-offs such as virtual machines versus containers;
- assisting with implementation planning and debugging strategy for the artefact;
- generating an initial Apache Kafka architecture diagram, which was then reviewed for relevance to the dissertation.

Generative AI was not used as an independent factual source. Technical claims were checked against cited literature, official Apache Kafka documentation, the artefact source code, and benchmark results. The author remains responsible for the accuracy, originality, and final form of all submitted work.

A.2.3 Evidence

Representative examples of GenAI use are summarised below.

Use case	Example prompt summary	How the output was used
Dissertation structure review	Asked for Chapter 1 and Chapter 2 to be reviewed against university marking criteria.	Used to identify missing structure, such as explicit aims, objectives, and clearer research gap framing.
Chapter wording support	Asked for sections to be rewritten in a clearer academic style while preserving the author's tone.	Outputs were edited and adapted before inclusion.
Artefact explanation	Asked for help explaining the Kafka benchmarking artefact, including infrastructure, security modes, telemetry, and result processing.	Used as drafting support for Chapter 3, checked against the implemented repository.
Technical planning	Asked for advice on benchmark design, fault tolerance, idempotency, and telemetry collection.	Used to support development planning; final implementation was tested directly.
Figure generation	Prompt requested a simplified Apache Kafka architecture diagram showing producers, brokers, topics, and consumers.	Output was used as Figure 2.1 and disclosed in the figure caption.

Table A.1: Representative examples of GenAI use during the project

A.2.4 Declaration

The author confirms that no content created by generative AI technologies has been submitted without review, adaptation, and acknowledgement. The author remains responsible for the dissertation argument, artefact implementation, experimental execution, result interpretation, and final submitted content.

Appendix B

Artefact Configuration

This appendix summarises the configuration structure used by the benchmarking artefact. The artefact is driven by explicit configuration files rather than hard-coded experiment settings. This was done to make the benchmark design repeatable, transparent, and easier to compare across plaintext, TLS, and mTLS modes.

The main configuration files are stored under `config/`. Baseline files define fixed workload defaults, while factorial files define the larger parameter spaces used for the final evaluation. Generated execution plans are written as JSONL files under `.orchestration/`, where each line represents one benchmark row. This separates the experiment design from the execution logic and allows the same plan structure to be resumed after interruption.

B.1 Configuration Files

The artefact uses three main categories of configuration file. Baseline configuration files describe default workload settings. Sweep configuration files describe one-factor-at-a-time exploratory experiments. Factorial configuration files describe the final multi-parameter experiment spaces used for the security-overhead evaluation.

The final producer campaign is defined by `config/factorials/security-overhead-final.json`. The targeted consumer validation study is defined by `config/factorials/consumer-security-slice.json`. These files are converted into JSONL execution plans before running. The generated producer plan is stored as `.orchestration/security-overhead-final-plan.jsonl`, while the generated consumer plan is stored as `.orchestration/consumer-security-slice-plan.jsonl`.

Temporary deployment metadata, generated plans, checkpoints, inventory files, and Terraform outputs are also stored under `.orchestration/`. This directory is not part of the permanent artefact configuration because it contains environment-specific state, including generated cluster metadata and credentials. It is therefore excluded from version control

where appropriate.

The main configuration files used by the artefact are listed in Table B.1. The long paths are shown explicitly because they form part of the reproducibility trail for the artefact.

Configuration path	Purpose
`config/baselines/plaintext-default.json`	Defines the original plaintext baseline workload settings.
`config/baselines/plaintext-requested-baseline.json`	Defines the requested plaintext baseline used during expanded benchmark development.
`config/factorials/security-overhead-final.json`	Defines the final producer-side factorial campaign across plaintext, TLS, and mTLS modes.
`config/factorials/consumer-security-slice.json`	Defines the targeted consumer-side validation slice.
`.orchestration/security-overhead-final-plan.jsonl`	Generated JSONL execution plan for the final producer campaign.
`.orchestration/consumer-security-slice-plan.jsonl`	Generated JSONL execution plan for the consumer validation slice.
`.orchestration/security-overhead-final-mtls-broker5.checkpoint`	Example checkpoint file used to resume the mTLS five-broker producer campaign.
`.orchestration/consumer-security-slice-mtls-broker5.checkpoint`	Example checkpoint file used to resume the mTLS five-broker consumer slice.

Table B.1: Main artefact configuration and generated plan files

B.2 Producer Factorial Campaign

The main evaluation is based on a producer-side factorial campaign. This campaign is used because the research question requires more than a single plaintext, TLS, and mTLS comparison. Kafka performance depends on workload and deployment configuration, so the security overhead must be measured across a controlled range of Kafka-relevant parameters.

The final producer campaign design contains 5,184 planned rows after validity constraints are applied. These rows are divided evenly across the three security modes, with 1,728 planned rows each for plaintext, TLS, and mTLS. The same workload dimensions are used across the security modes so that comparisons can be made under matched conditions.

The campaign varies broker count, replication factor, minimum in-sync replicas, message size, target throughput, batch size, acknowledgement setting, producer count, compression type, and trial index. These variables were selected because they directly influence Kafka's throughput-latency-durability trade-off and therefore may affect how visible TLS or mTLS overhead becomes.

The generated producer plan is stored as `.orchestration/security-overhead-final-plan.jsonl`. Each line in this file represents one planned benchmark row. The executor reads this plan, applies runtime filters such as security mode and broker count, skips rows already recorded in the checkpoint, and writes completed rows into the relevant result set.

Dimension	Role in the experiment
Security mode	Compares plaintext, TLS, and mTLS transport configurations.
Broker count	Tests whether cluster size changes the observed overhead.
Replication factor	Controls durability and replication cost.
Minimum in-sync replicas	Controls how many replicas must acknowledge writes.
Message size	Tests whether larger payloads amplify encryption and data-movement costs.
Target throughput	Controls the offered producer load.
Batch size	Controls producer batching and amortisation of network overhead.
Acknowledgement mode	Changes the durability and latency behaviour of producer writes.
Producer count	Controls producer-side concurrency.
Compression type	Tests whether compression interacts with secure transport overhead.
Trial index	Provides repeated measurements for the same configuration.

Table B.2: Producer factorial campaign dimensions

B.3 Security Mode Configuration

The artefact uses three security modes. Plaintext provides the baseline with no transport encryption. TLS enables encrypted transport with server authentication. mTLS extends TLS by requiring certificate-based client authentication as well as encrypted communication.

These modes do not represent a complete Zero Trust Architecture. Instead, TLS and mTLS are evaluated as Zero Trust-aligned transport-security mechanisms because they provide encrypted communication and certificate-based identity verification. This distinction is important because the dissertation evaluates measurable Kafka transport controls rather than claiming to implement a full system-level Zero Trust deployment.

The TLS and mTLS configurations permit TLS 1.3 and TLS 1.2, with protocol negotiation handled by the Kafka and JDK SSL stack. This reflects the implemented artefact configuration and avoids assuming that all benchmarked connections use TLS 1.3 only.

Mode	Description
Plaintext	Baseline Kafka transport with no TLS encryption.
TLS	Encrypted Kafka transport with server-side certificate authentication.
mTLS	Encrypted Kafka transport with mutual certificate authentication between clients and brokers.

Table B.3: Security modes used by the artefact

B.4 Validity Constraints

Not every possible parameter combination is valid in Kafka. The plan generation process therefore applies validity constraints before benchmark execution. For example, the replication factor cannot exceed the number of available brokers, and the minimum in-sync replica setting must be valid for the selected replication factor.

These constraints are applied before the generated JSONL plan is executed. This prevents invalid benchmark rows from being submitted to the cluster and ensures that the final plan represents executable Kafka configurations rather than a purely theoretical parameter grid.

The use of deterministic run identifiers also supports traceability. Each run identifier is derived from the workload configuration, including security mode, broker count, replication factor, minimum in-sync replicas, message size, target throughput, batch size, acknowledgement mode, producer count, compression type, and trial index. This makes it possible to link each plan row to its result directory and summary output.

For example, a generated run directory may include a full configuration-derived identifier such as `security-overhead-final-factorial-mtls-b5-rf5-isr3-msg102400-tps10000-batch131072-acks1-prod12-complz4-trial3`. This long identifier is intentional because it makes the run self-describing and reduces ambiguity when inspecting result directories.

B.5 Consumer Validation Slice

The consumer-side benchmark is intentionally designed as a targeted validation slice rather than a full factorial campaign. A full consumer factorial campaign would greatly increase the experimental cost and runtime, while duplicating much of the producer-side parameter space. The purpose of the consumer slice is therefore narrower: to test whether secure transport also affects Kafka's read path under selected workloads.

The consumer configuration is defined by `config/factorials/consumer-security-slice.json`. The generated consumer execution plan is stored as `.orchestration/consumer-security-slice-plan.jsonl`. This plan includes plaintext, TLS, and mTLS modes, selected

message sizes, compression settings, consumer concurrency, and repeated trials.

The consumer validation results are therefore used as supporting evidence rather than as a second full factorial evaluation. This keeps the dissertation focused on the main producer-side security-overhead campaign while still addressing the possibility that TLS and mTLS affect consumers as well as producers and brokers.

Appendix C

Result Schema

This appendix summarises the structure of the benchmark outputs produced by the artefact. Each benchmark run produces a run directory containing raw benchmark logs, workload metadata, parsed metrics, and host telemetry. The exact metric values differ between runs, but the output structure remains stable across plaintext, TLS, and mTLS modes.

The result schema was designed to support traceability from experiment plan to dissertation output. Each run can be linked back to its configuration row, security mode, workload parameters, raw Kafka benchmark output, parsed result file, host telemetry files, and aggregated summary row. This makes the result pipeline reproducible and reduces the risk of interpreting a metric without its workload context.

C.1 Run-Level Output

Each completed benchmark run is stored in a dedicated result directory. The directory name is derived from the run identifier, which encodes the main workload parameters. This makes the result directory self-describing and allows individual runs to be inspected without relying only on the aggregated CSV output.

The most important run-level files are `metadata.json`, `result.json`, the raw Kafka benchmark logs, and the `host-telemetry/` directory. The metadata file records the configuration used for the run, while the result file stores parsed benchmark metrics and run-level telemetry summaries.

File or directory	Description
`metadata.json`	Stores workload, deployment, and security-mode configuration for the run.
`result.json`	Stores parsed application metrics and aggregated telemetry fields for the run.
`producer-perf.log`	Stores raw output from the Kafka producer performance benchmark.
`consumer-perf.log`	Stores raw output from the Kafka consumer performance benchmark, where consumer benchmarking is used.
`topic-create.log`	Stores topic creation output for the run.
`topic-delete.log`	Stores topic deletion output where per-run cleanup is used.
`host-telemetry/`	Stores per-host telemetry logs collected from the benchmark client and Kafka brokers.

Table C.1: Run-level benchmark output files

C.2 Metadata Fields

The `metadata.json` file records the workload and deployment context for a benchmark run. This includes the security mode, broker count, partition count, replication factor, minimum in-sync replicas, message size, record count, target throughput, producer count, consumer count, batch size, acknowledgement setting, compression type, and trial index.

These fields are important because throughput and latency are only meaningful when interpreted alongside the workload that produced them. For example, a latency value from a plaintext run with one producer and small messages is not directly comparable with a mTLS run using twelve producers, larger messages, and stricter durability settings unless the configuration is visible.

The metadata fields also support matched comparison across security modes. Plaintext, TLS, and mTLS rows can be grouped using the same workload parameters, allowing the evaluation to isolate transport-security overhead from unrelated workload differences.

Metadata field group	Examples
Security configuration	`security_mode`, client configuration path, listener protocol.
Cluster configuration	`broker_count`, `partition_count`, `replication_factor`, `min_insync_replicas`.
Producer workload	`message_size_bytes`, `num_records`, `target_messages_per_second`, `producer_count`.
Producer tuning	`batch_size`, `linger_ms`, `acks`, `compression_type`.
Consumer workload	`consumer_count` and consumer benchmark settings where applicable.
Run identity	`run_id`, `trial_index`, `trial_count`, and result directory.

Table C.2: Metadata field groups

C.3 Parsed Result Fields

The `result.json` file stores parsed metrics extracted from the Kafka benchmark output. For producer runs, this includes throughput in records per second, throughput in MB per second, average latency, maximum latency, and other latency fields reported by the Kafka tool where available. For consumer runs, the parsed output records consumer throughput and read-path metrics where available.

The result file also stores workload metadata and telemetry summaries so that each run remains interpretable even outside the aggregated result set. This is useful when inspecting individual heavy runs, failed runs, or outliers in the final analysis.

The primary application-level metrics used in the dissertation are throughput in records per second, throughput in MB per second, average latency, and maximum latency. These metrics are used because they are directly reported by the Kafka benchmark tools and provide a consistent basis for comparison across plaintext, TLS, and mTLS runs.

Metric	Description
Throughput records/sec	Number of records successfully sent or consumed per second.
Throughput MB/sec	Data throughput converted into megabytes per second.
Average latency	Mean producer latency reported by the Kafka producer benchmark.
Maximum latency	Maximum producer latency reported by the Kafka producer benchmark.
Consumer throughput	Consumer-side throughput for targeted read-path validation runs.
Failure status	Indicates failed or timed-out runs where applicable.

Table C.3: Primary parsed result metrics

C.4 Host Telemetry Fields

Host telemetry is stored under the `host-telemetry/` directory for each run. The artefact collects telemetry from the benchmark client and Kafka brokers during benchmark execution. These files are stored as JSONL logs, with each line representing one interval sample from a host.

The telemetry captures CPU utilisation, memory utilisation, disk activity, and network receive/transmit counters. These measurements are used to link application-level behaviour to host-level resource use. This is important for the dissertation because TLS and mTLS overhead may appear not only as lower throughput or higher latency, but also as increased CPU activity or different network and disk behaviour.

The number of telemetry hosts is also recorded. For a five-broker campaign, the expected telemetry host count is normally six: five Kafka brokers and one benchmark client. This helps identify whether a run has complete host-level coverage.

Telemetry field group	Description
CPU utilisation	Per-host CPU usage sampled during the benchmark run.
Memory utilisation	Per-host memory usage during the benchmark run.
Network activity	Network receive and transmit counters for each telemetry host.
Disk activity	Disk read and write activity, including sector counters where available.
Telemetry host count	Number of hosts with telemetry files for the run.
Telemetry role	Identifies whether the host is a broker or benchmark client.

Table C.4: Host telemetry field groups

C.5 Result-Set Output

At the result-set level, completed runs are aggregated into `summary.json` and `summary.csv`. The JSON file preserves structured run data, while the CSV file provides a flat format suitable for statistical analysis, plotting, and dissertation tables.

The executor also writes `started.jsonl`, `completed.jsonl`, and `failures.jsonl` where applicable. These files record execution state. The `started.jsonl` file records rows that began execution, while `completed.jsonl` records rows that finished successfully and were copied back locally. The `failures.jsonl` file is only produced when failures occur.

This distinction matters because a started row is not necessarily a completed row. A run is treated as complete only when the benchmark has finished, the result files have been copied back, the raw output has been parsed, and the checkpoint has been updated.

Result-set file	Description
`started.jsonl`	Records benchmark rows that were started by the executor.
`completed.jsonl`	Records benchmark rows that completed successfully.
`failures.jsonl`	Records failed or timed-out rows when failures occur.
`summary.json`	Stores structured summary data across completed runs.
`summary.csv`	Stores flat tabular summary data for analysis and export.
`export/table.csv`	Dissertation-ready CSV table output where export is enabled.
`export/table.tex`	Dissertation-ready LaTeX table output where export is enabled.
`export/*.svg`	Plot outputs where export is enabled.

Table C.5: Result-set output files

C.6 Metric Interpretation Caveat

The benchmark tools provide application-level throughput and latency metrics, while the telemetry pipeline provides interval-based host-resource measurements. These two sources are complementary but not identical. Application metrics describe benchmark behaviour, while telemetry fields describe resource behaviour sampled during the run.

Where interval-derived percentile fields are present in the summary output, they are treated as diagnostic indicators rather than true per-record latency percentiles. They describe variation across sampled intervals or parsed benchmark summaries and are therefore used to support interpretation, not as a substitute for full per-record latency tracing.

For this reason, the dissertation focuses on metrics that are consistently available across runs: throughput records per second, throughput MB per second, average latency, maximum latency, CPU utilisation, memory utilisation, network activity, disk activity, telemetry host count, workload metadata, and failure status.

Appendix D

Additional Result Tables

This appendix contains additional result tables that support the analysis in Chapter 4. The purpose of the appendix is not to replace the main discussion, but to provide extended tabular evidence that would otherwise interrupt the flow of the main chapter. The tables in this appendix should therefore be read alongside the matched comparison method and the main analytical findings presented in Chapter 4.

The appendix is organised around producer campaign completion, matched security-mode comparison, throughput, latency, host telemetry, and consumer-side validation. Where final campaign execution is still in progress, the table structures can be prepared in advance and filled once the final result set has been completed and aggregated.

D.1 Producer Campaign Completion Tables

This section reports the completion state of the producer campaigns by security mode and campaign phase. These tables support the validity discussion in Chapter 4 by showing how many rows were planned, how many completed successfully, how many were excluded from final matched analysis, and how many were retained for comparison.

Campaign phase	Planned rows	Completed rows	Excluded rows	Matched rows
Plaintext producer	[ ]	[ ]	[ ]	[ ]
TLS producer	[ ]	[ ]	[ ]	[ ]
mTLS producer	[ ]	[ ]	[ ]	[ ]
Total	[ ]	[ ]	[ ]	[ ]

Table D.1: Producer campaign completion and matched-analysis counts

Completion category	Plaintext	TLS	mTLS
Successful completed rows	[ ]	[ ]	[ ]
Rows excluded from comparison	[ ]	[ ]	[ ]
Rows without full matched set	[ ]	[ ]	[ ]
Rows retained for final matched analysis	[ ]	[ ]	[ ]

Table D.2: Producer row validity and retention summary

D.2 Matched Security-Mode Comparison Tables

This section provides higher-level matched comparison summaries. These tables support the argument that the core empirical claim of the dissertation depends on comparing plaintext, TLS, and mTLS under equivalent workload and deployment conditions.

Comparison metric	Plaintext	TLS	mTLS
Matched producer rows	[ ]	[ ]	[ ]
Matched consumer rows	[ ]	[ ]	[ ]
Mean throughput change vs plaintext	–	[ ]	[ ]
Mean latency change vs plaintext	–	[ ]	[ ]
Mean client CPU change vs plaintext	–	[ ]	[ ]
Mean broker CPU change vs plaintext	–	[ ]	[ ]

Table D.3: Overall matched security-mode comparison summary

Comparison category	TLS vs plaintext	mTLS vs plaintext	mTLS vs TLS
Mean throughput overhead	[ ]	[ ]	[ ]
Mean average-latency overhead	[ ]	[ ]	[ ]
Mean maximum-latency overhead	[ ]	[ ]	[ ]
Mean client CPU overhead	[ ]	[ ]	[ ]
Mean broker CPU overhead	[ ]	[ ]	[ ]

Table D.4: Relative security overhead summary

D.3 Producer Throughput Tables

This section provides additional throughput tables beyond those included in Chapter 4. The purpose of these tables is to show how throughput overhead changes across selected workload factors without overloading the main discussion chapter.

Message size (bytes)	Plaintext	TLS	mTLS	Strongest overhead mode
1024	[ ]	[ ]	[ ]	[ ]
10240	[ ]	[ ]	[ ]	[ ]
102400	[ ]	[ ]	[ ]	[ ]

Table D.5: Mean matched producer throughput by message size

Producer count	Plaintext	TLS	mTLS	Strongest overhead mode
1	[ ]	[ ]	[ ]	[ ]
6	[ ]	[ ]	[ ]	[ ]
12	[ ]	[ ]	[ ]	[ ]

Table D.6: Mean matched producer throughput by producer count

Compression mode	Plaintext	TLS	mTLS	Strongest overhead mode
none	[ ]	[ ]	[ ]	[ ]
lz4	[ ]	[ ]	[ ]	[ ]

Table D.7: Mean matched producer throughput by compression mode

Acknowledgement mode	Plaintext	TLS	mTLS	Strongest overhead mode
acks=1	[ ]	[ ]	[ ]	[ ]
acks=all	[ ]	[ ]	[ ]	[ ]

Table D.8: Mean matched producer throughput by acknowledgement mode

D.4 Producer Latency Tables

This section provides additional latency tables. These support the Chapter 4 analysis by showing how average and maximum latency change under matched secure transport modes across selected workload dimensions.

Message size (bytes)	Plaintext	TLS	mTLS	Strongest overhead mode
1024	[ ]	[ ]	[ ]	[ ]
10240	[ ]	[ ]	[ ]	[ ]
102400	[ ]	[ ]	[ ]	[ ]

Table D.9: Mean matched average latency by message size

Producer count	Plaintext	TLS	mTLS	Strongest overhead mode
1	[ ]	[ ]	[ ]	[ ]
6	[ ]	[ ]	[ ]	[ ]
12	[ ]	[ ]	[ ]	[ ]

Table D.10: Mean matched average latency by producer count

Comparison metric	Plaintext	TLS	mTLS	Highest observed value
Mean maximum latency (ms)	[ ]	[ ]	[ ]	[ ]
Worst matched maximum latency (ms)	[ ]	[ ]	[ ]	[ ]
Mean diagnostic p95 field	[ ]	[ ]	[ ]	[ ]
Mean diagnostic p99 field	[ ]	[ ]	[ ]	[ ]

Table D.11: Additional producer latency summary metrics

D.5 Host Telemetry Tables

This section contains supporting telemetry tables. These are intended to complement the host-resource analysis in Chapter 4 by providing more detailed tabular evidence about where security overhead appears.

Telemetry metric	Plaintext	TLS	mTLS
Mean benchmark-client CPU utilisation	[ ]	[ ]	[ ]
Mean broker CPU utilisation	[ ]	[ ]	[ ]
Mean benchmark-client memory utilisation	[ ]	[ ]	[ ]
Mean broker memory utilisation	[ ]	[ ]	[ ]

Table D.12: Matched host CPU and memory summary

Telemetry metric	Plaintext	TLS	mTLS
Mean benchmark-client network RX/TX	[ ]	[ ]	[ ]
Mean broker network RX/TX	[ ]	[ ]	[ ]
Mean benchmark-client disk activity	[ ]	[ ]	[ ]
Mean broker disk activity	[ ]	[ ]	[ ]
Mean telemetry host count	[ ]	[ ]	[ ]

Table D.13: Matched host network and disk summary

Telemetry interpretation category	Plaintext	TLS	mTLS
Rows with highest benchmark-client CPU	[ ]	[ ]	[ ]
Rows with highest broker CPU	[ ]	[ ]	[ ]
Rows with highest network activity	[ ]	[ ]	[ ]
Rows with highest disk activity	[ ]	[ ]	[ ]

Table D.14: Extreme-case telemetry summary

D.6 Consumer Validation Tables

This section reports the supporting result tables for the targeted consumer validation slice. These tables are included in the appendix because the consumer study is smaller than the main producer campaign and functions as supporting validation rather than as the central empirical result.

Consumer metric	Plaintext	TLS	mTLS
Mean consumer throughput	[ ]	[ ]	[ ]
Mean consumer delay / latency metric	[ ]	[ ]	[ ]
Mean client CPU utilisation	[ ]	[ ]	[ ]
Mean broker CPU utilisation	[ ]	[ ]	[ ]

Table D.15: Targeted consumer validation summary

Validation dimension	Plaintext	TLS	mTLS	Strongest overhead mode
Small-message slice	[ ]	[ ]	[ ]	[ ]
Medium-message slice	[ ]	[ ]	[ ]	[ ]
Large-message slice	[ ]	[ ]	[ ]	[ ]
Compressed slice	[ ]	[ ]	[ ]	[ ]

Table D.16: Consumer validation results across selected workload slices

D.7 Top Overhead Cases

This section highlights the most extreme matched overhead cases in the final dataset. These tables are useful because they show where secure transport had the largest observed effect rather than only the average effect.

Run category	TLS overhead	mTLS overhead	Metric
Largest throughput drop vs plaintext	[ ]	[ ]	[ ]
Largest average-latency increase vs plaintext	[ ]	[ ]	[ ]
Largest maximum-latency increase vs plaintext	[ ]	[ ]	[ ]
Largest benchmark-client CPU increase vs plaintext	[ ]	[ ]	[ ]
Largest broker CPU increase vs plaintext	[ ]	[ ]	[ ]

Table D.17: Highest observed security-overhead cases

The appendix tables in this chapter are intended to support, not replace, the main discussion in Chapter 4. The main chapter should still carry the interpretation, argument, and answer to the research question, while Appendix D provides the additional tabular detail required for transparency and completeness.

Appendix E

Repository and Reproducibility Notes

This appendix summarises how the artefact repository is organised and how reproducibility is supported. The repository separates infrastructure provisioning, Kafka deployment, benchmark execution, telemetry collection, result parsing, and export. This was done so that the artefact can be inspected as a set of clear components rather than as one large script.

The artefact is also designed around explicit configuration files and generated execution plans. This means that benchmark rows are not created manually during execution. Instead, the configuration files define the experiment space, the plan generator expands this into JSONL rows, and the executor runs those rows while recording started, completed, and failed runs.

E.1 Repository Structure

The main repository directories are shown in Table E.1. Source files, configuration files, orchestration scripts, and documentation are part of the artefact. Generated execution state is stored separately under `.orchestration/`, because it depends on the current AWS deployment and local execution environment.

Repository path	Purpose
`infrastructure/terraform/`	Contains Terraform configuration for AWS networking, security groups, Kafka broker instances, and the benchmark client.
`deploy/kafka/`	Contains Kafka installation scripts, broker configuration templates, client configuration, TLS/mTLS setup, and benchmark runner scripts.
`config/baselines/`	Contains baseline workload configurations used as fixed defaults.
`config/sweeps/`	Contains one-factor-at-a-time exploratory sweep definitions.
`config/factorials/`	Contains factorial experiment definitions for the final producer campaign and consumer validation slice.
`scripts/orchestration/`	Contains scripts for inventory generation, deployment, benchmark execution, parsing, aggregation, export, and campaign control.
`docs/`	Contains supporting artefact documentation, including architecture, methodology, result schema, reproducibility notes, and campaign operating notes.
`results/`	Contains local benchmark outputs, parsed results, summaries, and exported tables or plots.
`.orchestration/`	Contains generated local execution state, plans, checkpoints, Terraform outputs, inventory files, and deployment metadata.

Table E.1: Repository structure

E.2 Configuration-Driven Execution

Benchmark execution is driven by configuration files rather than manually constructed commands. Baseline and factorial JSON files define the workload parameters, while generated JSONL plans define the exact benchmark rows to execute. This makes the campaign design inspectable before execution and reduces the risk of changing parameters accidentally between security modes.

The final producer campaign is generated from `config/factorials/security-overhead-final.json`. The targeted consumer validation slice is generated from `config/factorials/consumer-security-slice.json`. The generated plans are stored under `.orchestration/`, including `.orchestration/security-overhead-final-plan.jsonl` and `.orchestration/consumer-security-slice-plan.jsonl`.

This structure supports reproducibility because each result can be traced back to a configuration file, generated plan row, deterministic run identifier, metadata file, result directory, and summary row. A benchmark result is therefore not only a value in a table,

but an output linked to a specific workload and deployment configuration.

E.3 Deployment Reproducibility

AWS infrastructure is provisioned using Terraform. The Terraform layer defines the VPC, subnet, security groups, Kafka broker instances, and benchmark client instance. After provisioning, orchestration scripts export the Terraform outputs and convert them into local inventory and cluster metadata files.

Kafka deployment is automated through shell scripts. These scripts install Kafka, render broker configuration, configure KRaft metadata, start broker services, and validate readiness. Kafka data-plane traffic uses private VPC addresses, while SSH orchestration uses public addresses. This separation prevents Kafka benchmark traffic from using public broker addresses while still allowing the local workstation to manage the cluster.

Broker readiness is checked using Kafka API availability rather than only `systemd` process status. This is important because a broker process can be running before the broker is ready to serve Kafka requests. API-level readiness checks reduce the risk of starting benchmark rows against a partially available cluster.

E.4 Checkpointing and Resumability

The benchmark campaigns are long-running and can be interrupted by SSH timeouts, local machine sleep, network issues, or cloud-instance disruption. The executor therefore records campaign state using `started.jsonl`, `completed.jsonl`, `failures.jsonl` where applicable, and checkpoint files under `.orchestration/`.

A row is only treated as complete after the remote benchmark has finished, result files have been copied back locally, raw output has been parsed, and the checkpoint has been updated. This means that a row appearing in `started.jsonl` is not enough for it to be treated as complete. The completed file and checkpoint are the authoritative record of successful execution.

When a campaign resumes, the executor skips rows that are already recorded as complete. This prevents completed rows from being rerun and makes it practical to execute large campaigns across multiple sessions. It also protects the result set from partial local state, because result copying is completed before a row is marked as finished.

E.5 Result Traceability

Each benchmark run writes a dedicated result directory. The directory name is derived from the run identifier, which encodes the main workload configuration. This makes the directory self-describing and reduces ambiguity when inspecting individual runs.

The run directory contains raw Kafka benchmark logs, workload metadata, parsed metrics, and host telemetry. The raw logs are retained so that parsed values can be checked against the original benchmark output. The `metadata.json` file records workload context, while `result.json` stores the parsed structured result for the run.

At result-set level, `summary.json` and `summary.csv` aggregate completed runs into structured and tabular formats. These files are used for analysis, comparison, and dissertation-ready exports. This gives two levels of traceability: individual run inspection through run directories, and full result-set analysis through summary files.

E.6 Generated State and Version Control

Not every file produced by the artefact is suitable for version control. Generated state under `.orchestration/` may include environment-specific inventory files, Terraform outputs, deployment checkpoints, generated plans, SSH key paths, certificates, and cluster metadata. These files are useful for local execution but do not represent permanent source code.

Sensitive files such as SSH keys, AWS credentials, generated certificates, keystores, truststores, and environment-specific deployment outputs are excluded from version control where appropriate. This is necessary for security and also improves reproducibility, because those files describe one live deployment rather than the general artefact design.

Large raw result sets are also treated carefully. Historical result sets are retained locally for traceability, but final analysis should use the telemetry-enabled result sets from the final plaintext, TLS, and mTLS campaigns. Older non-telemetry outputs are useful for development history but should not be mixed with final evaluation data.

E.7 Rerunning the Artefact

To rerun the artefact, the infrastructure must first be provisioned through Terraform. Terraform outputs are then exported into local orchestration metadata. The benchmark client and Kafka brokers are prepared using the orchestration scripts, after which the required security mode is deployed.

For factorial campaigns, the relevant JSON configuration is converted into a JSONL

execution plan. The executor then runs the plan using security-mode and broker-count filters where required. If execution is interrupted, the same command can be rerun with the same checkpoint file so that completed rows are skipped.

The exact command depends on the campaign phase and security mode. However, the reproducibility principle remains the same across all phases: the same configuration file, generated plan, result-set name, and checkpoint file should be used when resuming a campaign.

E.8 Reproducibility Limitations

The artefact improves reproducibility, but it does not remove all sources of experimental variation. AWS EC2 instances are shared cloud resources, and their performance can vary because of cloud scheduling, network conditions, and background host activity. The benchmark results should therefore be interpreted as controlled cloud measurements rather than deterministic hardware constants.

The generated execution state also depends on campaign history. For example, an interrupted run may appear in `started.jsonl` without appearing in `completed.jsonl`. This is expected behaviour and is handled by the executor, but it means that completed rows and checkpoint files should be used when reporting final campaign progress.

Finally, the artefact evaluates selected Kafka transport-security configurations rather than every possible secure Kafka deployment. Plaintext, TLS, and mTLS provide a controlled basis for comparing transport-security overhead, but they do not represent every possible Zero Trust Architecture, certificate-management strategy, authorisation policy, or production Kafka deployment pattern.