CommandMate Pivot: Migration Guide

CommandMate Pivot: Mac mini → MacBook Pro Migration Guide
Option A: “Polsia for Vietnamese SMEs”
📋 Tổng Quan
🚀 Phase 1: MacBook Pro Setup (30-45 phút)
Step 1: Install Core Tools
Step 2: Setup SSH Key for GitHub
Step 3: Clone Repository
Step 4: Install Dependencies
Step 5: Setup Environment Variables
Step 6: Test Local Development
Step 7: Install VSCode + Claude Code Max
💾 Phase 2: Database Backup Strategy
Current Database: Supabase Production
Backup Strategy
Development Database Strategy
🏗️ Phase 3: New Architecture (Pivot to Business-First)
Current Architecture (MCP-focused)
New Architecture (Business OS Pivot)
Database Schema Changes (Extend, Don’t Replace)
UI Component Structure
Feature Flags (Gradual Rollout)
🔄 Phase 4: Development Workflow
Branch Strategy
Development Loop
Code Review with Claude
📦 Phase 5: Backup & Safety
Git Backup Strategy
Rollback Plan
⏱️ Timeline
Week 1: Setup + Wireframe (March 12-19)
Week 2: Backend + Integration (March 19-26)
Week 3: Playbooks + Polish (March 26 - April 2)
Week 4: Beta Launch (April 2-9)
📞 Support & Troubleshooting
Common Issues
🎯 Success Criteria
📚 Next Steps After Setup
🆘 Need Help?

CommandMate Pivot: Mac mini → MacBook Pro Migration Guide

Option A: "Polsia for Vietnamese SMEs"

Created: 2026-03-12 15:00 ICT
Owner: Đệ 🐾 + Sếp Victor
Goal: Setup MacBook Pro for CommandMate pivot development (VSCode + Claude Code Max)

📋 Tổng Quan

Current State: - **Mac mini:** Production repo at `/Users/bizmatehub/Projects/mission-control` - **GitHub:** `git@github.com:Victorpham1984/mission-control.git` - **Deploy:** Vercel (https://mission-control-sable-three.vercel.app) - **Database:** Supabase (production data) - **Codebase:** ~14,173 lines (Next.js 15 + Supabase + MCP)

Target State: - **MacBook Pro:** Development environment (VSCode + Claude Code Max) - **Workflow:** Code on MacBook → Push to GitHub → Auto-deploy Vercel - **Database:** Use Supabase production (read-only mode during dev) - **Architecture:** Pivot to business-first UI (CEO dashboard, onboarding, playbooks)

🚀 Phase 1: MacBook Pro Setup (30-45 phút)

Step 1: Install Core Tools

Terminal commands:

```
# 1. Install Homebrew (nếu chưa có)
/bin/bash -c "$(curl -fsSL
        https://raw.githubusercontent.com/Homebrew/install/HEAD/install.sh)"

# 2. Install Node.js (v22+)
brew install node@22
echo 'export PATH="/opt/homebrew/opt/node@22/bin:$PATH"' >> ~/.zshrc
source ~/.zshrc

# 3. Verify versions
node --version  # Should be v22.x
npm --version   # Should be 10.x+

# 4. Install Git (nếu chưa có)
```

```
brew install git

# 5. Configure Git
git config --global user.name "Victor Pham"
git config --global user.email "victor@bizmatehub.com"  # Use your
        actual email

# 6. Install pnpm (package manager)
npm install -g pnpm

# 7. Verify
pnpm --version  # Should be 9.x+
```

Step 2: Setup SSH Key for GitHub

Generate SSH key:

```
# 1. Generate new SSH key
ssh-keygen -t ed25519 -C "victor@bizmatehub.com"
# Press Enter 3 times (default location, no passphrase)

# 2. Start SSH agent
eval "$(ssh-agent -s)"

# 3. Add key to agent
ssh-add ~/.ssh/id_ed25519

# 4. Copy public key to clipboard
cat ~/.ssh/id_ed25519.pub | pbcopy
```

Add to GitHub: 1. Open https://github.com/settings/keys 2. Click "New SSH key" 3. Title: `MacBook Pro - CommandMate Dev` 4. Paste key from clipboard 5. Click "Add SSH key"

Test connection:

```
ssh -T git@github.com
# Should see: "Hi Victorpham1984! You've successfully
        authenticated..."
```

Step 3: Clone Repository

Choose location:

```
# Option A: ~/Projects (same as Mac mini)
mkdir -p ~/Projects
cd ~/Projects

# Option B: ~/Code (if you prefer)
mkdir -p ~/Code
```

```
cd ~/Code

# Clone repo
git clone git@github.com:Victorpham1984/mission-control.git
        commandmate-pivot

# Enter directory
cd commandmate-pivot

# Check branches
git branch -a
```

Expected output:

```
* main
  remotes/origin/dev
  remotes/origin/main
  remotes/origin/feature/phase-2b-frontend
```

Step 4: Install Dependencies

```
# Install all packages
pnpm install

# Wait 2-3 minutes for download + install
# Should see ~500+ packages installed
```

Step 5: Setup Environment Variables

Copy secrets from Mac mini:

On Mac mini (current session), run:

```
cd ~/Projects/mission-control
cat .env.local
```

Copy output to MacBook Pro:

```
# On MacBook Pro
cd ~/Projects/commandmate-pivot  # Or wherever you cloned

# Create .env.local
nano .env.local

# Paste these values (get from Mac mini):
NEXT_PUBLIC_SUPABASE_URL=https://your-project.supabase.co
NEXT_PUBLIC_SUPABASE_ANON_KEY=eyJ...
SUPABASE_SERVICE_ROLE_KEY=eyJ...
OPENCLAW_GATEWAY_URL=http://localhost:3000
OPENCLAW_GATEWAY_TOKEN=your-token-here
```

```
YOUTUBE_API_KEY=AIza...
OPENROUTER_API_KEY=sk-or-...
ADMIN_PASSWORD=your-admin-password
CRON_SECRET=your-cron-secret

# Save: Ctrl+O, Enter, Ctrl+X
```

Security check:

```
# Verify .env.local is gitignored
cat .gitignore | grep ".env.local"
# Should see: .env.local

# Verify file exists but NOT tracked
git status
# Should NOT see .env.local in "Changes to be committed"
```

Step 6: Test Local Development

```
# Start dev server
pnpm dev

# Should start on http://localhost:3000
# Open browser and verify site loads
```

Verify: - ✅ Home page loads (no errors) - ✅ Supabase connection works (check browser console) - ✅ No build errors in terminal

Stop server:

```
Ctrl+C
```

Step 7: Install VSCode + Claude Code Max

Install VSCode: 1. Download from https://code.visualstudio.com/ 2. Drag to Applications folder 3. Open VSCode

Install extensions:

```
# Open command palette: Cmd+Shift+P
# Type: "Shell Command: Install 'code' command in PATH"
# Click to install

# Install extensions via terminal
code --install-extension GitHub.copilot
code --install-extension dbaeumer.vscode-eslint
code --install-extension esbenp.prettier-vscode
code --install-extension bradlc.vscode-tailwindcss
code --install-extension Prisma.prisma
```

Install Claude Code Max (Anthropic): 1. Open VSCode Extensions panel (Cmd+Shift+X) 2. Search: "Claude Code" 3. Install "Claude Code Max" by Anthropic 4. Sign in with Anthropic account 5. Configure API key (if needed)

Open project:

```
cd ~/Projects/commandmate-pivot
code .
```

💾 Phase 2: Database Backup Strategy

Current Database: Supabase Production

Tables (from schema): - `users` - User accounts - `workspaces` - User workspaces - `workspace_members` - Membership data - `agents` - MCP agents - `mcp_servers` - MCP server configs - `mcp_tools` - Available tools - `tasks` - Agent tasks - `webhooks` - Webhook configs

Backup Strategy

Option A: Use Supabase Dashboard (Recommended)

1. Go to https://supabase.com/dashboard
2. Select project: `mission-control`
3. Go to: Database → Backups
4. Click "Create Backup" → Wait 2-3 minutes
5. Download backup file (SQL format)
6. Save to: `~/Backups/commandmate-backup-2026-03-12.sql`

Option B: CLI Backup (Alternative)

```
# Install Supabase CLI
brew install supabase/tap/supabase

# Login
supabase login

# Link project
supabase link --project-ref your-project-ref

# Create backup
supabase db dump -f ~/Backups/commandmate-backup-2026-03-12.sql

# Verify file
ls -lh ~/Backups/commandmate-backup-2026-03-12.sql
```

Development Database Strategy

Recommended: Keep using production Supabase during pivot

Why: - Avoid data sync issues - Faster development (no local Postgres setup) - Easy rollback if pivot fails

Safety measures: 1. **Read-only mode during development:** ```typescript // Add to lib/supabaseClient.ts const DEV_MODE = process.env.NODE_ENV === 'development';

// Wrap mutations in dev check if (DEV_MODE && !confirmMutation) {

console.warn('⚠️ Mutation blocked in dev mode'); return; } ```

2. **Use feature flags for new UI:**

```
// app/dashboard/page.tsx
const BUSINESS_UI = process.env.NEXT_PUBLIC_BUSINESS_UI === 'true';

return BUSINESS_UI ? <CEODashboard /> : <TechDashboard />;
```

3. **Branch strategy:**

   - `main` = production (current MCP-focused UI)
   - `pivot/business-os` = new branch for pivot work
   - Keep both alive until pivot proven

🏗️ Phase 3: New Architecture (Pivot to Business-First)

Current Architecture (MCP-focused)

```
┌──────────────────────────────────────┐
│         Next.js 15 Frontend          │
│  (Agent-centric UI: servers, tools)  │
├──────────────────────────────────────┤
│         API Routes                   │
│  /api/v1/mcp/*  (MCP operations)     │
│  /api/auth/*    (Supabase auth)      │
├──────────────────────────────────────┤
│         Supabase                     │
│  (users, workspaces, mcp_servers, etc.) │
└──────────────────────────────────────┘
```

Pages: - `/dashboard` - Agent management (tech-focused) - `/agents` - MCP agent list - `/tools` - MCP tool catalog - `/settings` - Config (agent-centric)

New Architecture (Business OS Pivot)

```
┌──────────────────────────────────────┐
│         Next.js 15 Frontend          │
│  (Business-first UI: goals, KPIs, etc.)  │
├──────────────────────────────────────┤
│  🆕 CEO Dashboard                    │
```

```
│  - Company health overview                    │
│  - Revenue, KPIs, Bottlenecks                 │
│  - Next 24h action plan                       │
├──────────────────────────────────────────────┤
│  🆕 Onboarding Wizard                         │
│  - 5-min magic setup                          │
│  - Auto-generate: landing, email, tasks       │
│  - Instant value delivery                     │
├──────────────────────────────────────────────┤
│  🆕 Playbook Library                          │
│  - E-commerce SaaS (COSMATE template)         │
│  - Content Creator                            │
│  - B2B Lead Gen                               │
├──────────────────────────────────────────────┤
│         API Routes                            │
│  /api/business/* (new business endpoints)     │
│  /api/v1/mcp/*   (keep for backend)           │
├──────────────────────────────────────────────┤
│         Supabase (Extended Schema)            │
│  🆕 companies, goals, kpis, playbooks        │
│  (keep existing: users, workspaces, etc.)     │
└──────────────────────────────────────────────┘
```

New Pages: - `/` - Landing page (Vietnamese, SEA-focused) - `/onboarding` - 5-min wizard (company → ICP → playbook → launch) - `/ceo` - CEO Dashboard (health, KPIs, actions) - `/playbooks` - Template library (install & customize) - `/apps` - Installed playbooks (e.g., "E-commerce OS") - `/settings/billing` - Pricing & usage (action-based)

Database Schema Changes (Extend, Don't Replace)

New tables to add:

```sql
-- Companies (business entity)
CREATE TABLE companies (
  id UUID PRIMARY KEY DEFAULT uuid_generate_v4(),
  workspace_id UUID REFERENCES workspaces(id),
  name TEXT NOT NULL,
  mission TEXT,
  icp_segment TEXT,  -- 'creator' | 'sme' | 'agency'
  industry TEXT,
  created_at TIMESTAMPTZ DEFAULT NOW()
);

-- Goals (business objectives)
CREATE TABLE goals (
  id UUID PRIMARY KEY DEFAULT uuid_generate_v4(),
  company_id UUID REFERENCES companies(id),
  title TEXT NOT NULL,
  target_value DECIMAL,
```

```sql
  current_value DECIMAL,
  unit TEXT,  -- 'MRR' | 'users' | 'leads'
  deadline DATE,
  status TEXT DEFAULT 'active',  -- 'active' | 'completed' | 'paused'
  created_at TIMESTAMPTZ DEFAULT NOW()
);

-- KPIs (key performance indicators)
CREATE TABLE kpis (
  id UUID PRIMARY KEY DEFAULT uuid_generate_v4(),
  company_id UUID REFERENCES companies(id),
  name TEXT NOT NULL,
  category TEXT,  -- 'acquisition' | 'activation' | 'revenue' |
        'operations'
  current_value DECIMAL,
  target_value DECIMAL,
  unit TEXT,
  updated_at TIMESTAMPTZ DEFAULT NOW()
);

-- Playbooks (pre-built templates)
CREATE TABLE playbooks (
  id UUID PRIMARY KEY DEFAULT uuid_generate_v4(),
  name TEXT NOT NULL,
  description TEXT,
  category TEXT,  -- 'ecommerce' | 'content' | 'b2b'
  config JSONB,  -- Skills, cron jobs, KPI structure
  created_at TIMESTAMPTZ DEFAULT NOW()
);

-- Installed Playbooks (company-specific)
CREATE TABLE installed_playbooks (
  id UUID PRIMARY KEY DEFAULT uuid_generate_v4(),
  company_id UUID REFERENCES companies(id),
  playbook_id UUID REFERENCES playbooks(id),
  customization JSONB,
  active BOOLEAN DEFAULT true,
  installed_at TIMESTAMPTZ DEFAULT NOW()
);

-- Actions (business operations log)
CREATE TABLE actions (
  id UUID PRIMARY KEY DEFAULT uuid_generate_v4(),
  company_id UUID REFERENCES companies(id),
  action_type TEXT,  -- 'send_email' | 'post_social' | 'update_crm'
  description TEXT,
  success BOOLEAN,
  evidence JSONB,  -- Screenshots, links, metrics
  cost DECIMAL,
  created_at TIMESTAMPTZ DEFAULT NOW()
);
```

Keep existing tables: - `users` - Still needed for auth - `workspaces` - Map to companies - `mcp_servers` - Use as backend execution engine - `mcp_tools` - Skills library for playbooks

---

UI Component Structure

New directories:

```
src/
├── app/
│   ├── (business)/         # Business-first UI (new)
│   │   ├── layout.tsx      # Vietnamese UI, business nav
│   │   ├── page.tsx        # Landing page
│   │   ├── onboarding/
│   │   │   ├── page.tsx    # 5-min wizard
│   │   │   └── steps/      # Step components
│   │   ├── ceo/
│   │   │   ├── page.tsx    # CEO dashboard
│   │   │   ├── health.tsx  # Company health widget
│   │   │   ├── kpis.tsx    # KPI board
│   │   │   └── actions.tsx # Next 24h plan
│   │   ├── playbooks/
│   │   │   ├── page.tsx    # Template library
│   │   │   ├── [id].tsx    # Playbook detail
│   │   │   └── install.tsx # Install flow
│   │   └── apps/
│   │       ├── page.tsx    # Installed playbooks
│   │       └── [id]/       # App dashboard
│   │
│   ├── (tech)/             # Tech UI (keep for backend)
│   │   ├── dashboard/      # Old MCP dashboard
│   │   ├── agents/
│   │   └── tools/
│   │
│   └── api/
│       ├── business/       # New business endpoints
│       │   ├── companies/
│       │   ├── goals/
│       │   ├── kpis/
│       │   ├── playbooks/
│       │   └── actions/
│       └── v1/mcp/         # Keep existing MCP API
│
├── components/
│   ├── business/           # Business UI components
│   │   ├── CompanyHealth.tsx
│   │   ├── KPICard.tsx
│   │   ├── ActionLog.tsx
│   │   └── PlaybookCard.tsx
│   └── tech/               # Tech UI (keep)
```

```
│
└── lib/
    ├── playbooks/           # Playbook templates
    │   ├── ecommerce-saas.ts
    │   ├── content-creator.ts
    │   └── b2b-leadgen.ts
    └── actions/             # Action handlers
        ├── email.ts
        ├── social.ts
        └── crm.ts
```

Feature Flags (Gradual Rollout)

Environment variables:

```
# .env.local
NEXT_PUBLIC_BUSINESS_UI=true          # Enable business UI
NEXT_PUBLIC_TECH_UI=true              # Keep tech UI (for debugging)
NEXT_PUBLIC_ONBOARDING_WIZARD=true    # Enable 5-min wizard
NEXT_PUBLIC_CEO_DASHBOARD=true        # Enable CEO dashboard
NEXT_PUBLIC_PLAYBOOKS=true            # Enable playbook library
```

Code example:

```
// app/layout.tsx
const BUSINESS_UI = process.env.NEXT_PUBLIC_BUSINESS_UI === 'true';

export default function RootLayout({ children }) {
  return (
    <html lang={BUSINESS_UI ? 'vi' : 'en'}>
      <body>
        {BUSINESS_UI ? <BusinessNav /> : <TechNav />}
        {children}
      </body>
    </html>
  );
}
```

🔄 Phase 4: Development Workflow

Branch Strategy

```
# Mac mini (current production)
main              # Keep stable, current MCP version
  ├── dev         # Tech features (MCP integration)

# MacBook Pro (pivot work)
```

```
pivot/business-os # New branch for pivot
  ├── pivot/onboarding
  ├── pivot/ceo-dashboard
  └── pivot/playbooks
```

Create pivot branch:

```
# On MacBook Pro
cd ~/Projects/commandmate-pivot

# Create new branch from main
git checkout main
git pull origin main
git checkout -b pivot/business-os

# Push to GitHub
git push -u origin pivot/business-os
```

Development Loop

On MacBook Pro:

```
# 1. Start dev server
pnpm dev

# 2. Edit files in VSCode
# Use Claude Code Max for AI-assisted coding

# 3. Test changes locally
# Open http://localhost:3000

# 4. Commit changes
git add .
git commit -m "feat: Add CEO dashboard wireframe"

# 5. Push to GitHub
git push origin pivot/business-os
```

Deploy strategy:

Option A: Separate Vercel project (Recommended) - Create new Vercel project: `commandmate-pivot` - Connect to branch: `pivot/business-os` - URL: `https://commandmate-pivot.vercel.app` - Keep production stable: `https://mission-control-sable-three.vercel.app`

Option B: Same project, preview deployment - Push to `pivot/business-os` → Auto-preview URL - Only merge to `main` when pivot ready to replace production

---

Code Review with Claude

VSCode shortcuts with Claude Code Max:

```
Cmd+K    Ask Claude (inline)
Cmd+L    Explain code
Cmd+I    Generate code from prompt
Cmd+E    Edit selection with AI
```

Example prompts:

1. "Convert this MCP agent dashboard to a business-first CEO dashboard with Vietnamese UI"
2. "Generate Supabase schema migration for adding companies, goals, and KPIs tables"
3. "Build a 5-step onboarding wizard component with form validation and progress bar"
4. "Create a playbook template for e-commerce SaaS with pre-configured skills and cron jobs"

📦 Phase 5: Backup & Safety

Git Backup Strategy

Auto-backup script:

```
# Create backup script
nano ~/backup-commandmate.sh

# Paste this:
#!/bin/bash
DATE=$(date +%Y-%m-%d-%H%M)
BACKUP_DIR=~/Backups/commandmate
mkdir -p $BACKUP_DIR

# Backup code
cd ~/Projects/commandmate-pivot
git bundle create $BACKUP_DIR/repo-$DATE.bundle --all

# Backup .env
cp .env.local $BACKUP_DIR/env-$DATE.txt

# Backup database (if using local)
# supabase db dump -f $BACKUP_DIR/db-$DATE.sql

echo "✅ Backup complete: $BACKUP_DIR/repo-$DATE.bundle"

# Save: Ctrl+O, Enter, Ctrl+X

# Make executable
chmod +x ~/backup-commandmate.sh
```

```
# Run manually
~/backup-commandmate.sh

# Or schedule daily (optional)
crontab -e
# Add line: 0 2 * * * ~/backup-commandmate.sh
```

Rollback Plan

If pivot fails:

```
# 1. Switch back to main branch
git checkout main

# 2. Verify production still works
pnpm dev

# 3. Delete pivot branch (if needed)
git branch -D pivot/business-os
git push origin --delete pivot/business-os

# 4. Restore database from backup (if modified)
supabase db reset
psql -f ~/Backups/commandmate-backup-2026-03-12.sql
```

⏱️ Timeline

Week 1: Setup + Wireframe (March 12-19)

- ✅ Day 1: MacBook Pro setup (this guide)
- 📋 Day 2-3: Database schema design + migration
- 🎨 Day 4-5: CEO dashboard wireframe (no backend)
- 📝 Day 6-7: Onboarding wizard UI mockup

Week 2: Backend + Integration (March 19-26)

- 🔧 Day 1-2: API endpoints (companies, goals, KPIs)
- 🔌 Day 3-4: Connect CEO dashboard to Supabase
- ✨ Day 5-6: Onboarding wizard backend (artifact generation)
- 🧪 Day 7: Testing + bug fixes

Week 3: Playbooks + Polish (March 26 - April 2)

- 📚 Day 1-3: Build first playbook (E-commerce SaaS from COSMATE)
- 🎀 Day 4-5: UI polish + Vietnamese localization
- 📊 Day 6: Action-based tracking (log business operations)
- 🚀 Day 7: Internal beta test

Week 4: Beta Launch (April 2-9)

- 👥 Day 1-2: Invite 5 beta users (Vietnamese SMEs)
- 📈 Day 3-5: Collect feedback + iterate
- 🐛 Day 6: Bug fixes + performance
- 🎉 Day 7: Public launch prep

📞 Support & Troubleshooting

Common Issues

1. `pnpm install` fails

```
# Clear cache
rm -rf node_modules
rm pnpm-lock.yaml
pnpm install
```

2. Supabase connection error

```
# Verify .env.local values
cat .env.local | grep SUPABASE

# Test connection
pnpm dev
# Open browser → check console for errors
```

3. Git push rejected

```
# Force push (only on pivot branch, NOT main!)
git push origin pivot/business-os --force
```

4. Port 3000 already in use

```
# Kill process
lsof -ti:3000 | xargs kill -9

# Or use different port
PORT=3001 pnpm dev
```

🎯 Success Criteria

Setup complete when: - ✅ VSCode + Claude Code Max installed - ✅ Repo cloned, dependencies installed - ✅ `pnpm dev` runs without errors - ✅ Can edit files, see live reload - ✅ Git push works to `pivot/business-os` branch - ✅ Database backup created - ✅ Ready to start building CEO dashboard

---

📚 Next Steps After Setup

Immediate (Day 1): 1. ✅ Complete this setup guide 2. 📸 Screenshot: VSCode open with repo 3. 🧪 Test: Edit `app/page.tsx`, see live reload 4. 💬 Confirm with Sếp: "Setup xong, ready to pivot!"

Day 2 onwards: 1. 📋 Design database schema (companies, goals, KPIs) 2. 🎨 Wireframe CEO dashboard (Vietnamese UI) 3. ⚡ Build onboarding wizard (5-min magic) 4. 📦 Create first playbook template (COSMATE → E-commerce SaaS)

🆘 Need Help?

Ask Đệ in Telegram: - "Bị lỗi X khi setup" - "Cần giải thích thêm về Y" - "Hướng khác để làm Z"

Or spawn tech squad: - Kiến 🏗️ (Frontend) - UI components, React/Next.js - Thép ⚙️ (Backend) - API, database, Supabase

---

Ready to start? Execute Phase 1 steps now! 🚀