

dati-basati

A Typst package to draw ER diagrams.

<https://github.com/victuarvi/dati-basati>

Version 0.1.1

Manual

1. Import	2
2. Basic usage	3
2.1. Entities	3
2.1.1. Entity with attributes . . .	3
2.1.2. Subentities	5
2.1.3. Attributes positioning . .	8
2.2. Relations	11
3. Formatting & customization	14
3.1. Individual styling overrides . . .	17
4. Advanced usage	18
4.1. Weak entities	18
4.2. Unorthodox relation position .	20
4.3. Exceptions	20
4.4. Touying integration	21
5. Themes showcase	22

Documentation

6. User functions	27
6.1 dati-basati	27
6.2 er-diagram	28
6.3 entity	28
6.4 subentities	30
6.5 relation	31

1. Import

Depending on your needs there are different types of imports:

- Import *all* the functions (recommended¹):

typ

```
1 #import "@preview/dati-basati:0.1.1": *
```

- Import *only* the functions you want to use:

typ

```
1 #import "@preview/dati-basati:0.1.1": er-diagram, entity, relation
```

- Import and (optionally) rename:

typ

```
1 #import "@preview/dati-basati:0.1.1" as renamed
```

but your code would be more verbose, like in the following example:

typ

```
1 #renamed.er-diagram({  
2   renamed.entity(  
3     (0, 0),  
4     name: "entity0",  
5   )  
6 })
```

The package is designed to be as straightforward and intuitive as possible, so you should be able to just write diagrams without even needing to read the manual – or at least that was the design goal.

¹Since it's unlikely there will be conflicts with identically named functions.

2. Basic usage

2.1. Entities


A basic entity would appear like this:

```
#er-diagram({  
  entity(  
    // coordinates  
    (0, 0),  
    // the internal reference  
    name: "entity",  
    // the content label  
    label: "Nice Name"  
  )  
})
```




2.1.1. Entity with attributes

```
#er-diagram({  
  entity(  
    (0, 0),  
    name: "student",  
    label: "student",  
    attributes: (  
      north: ("name", "surname"),  
      east: ("mail",),  
      west: ("address",),  
      south: ("cellphone",),  
    ),  
  )  
})
```




Primary key Adding a single primary key:

```
#er-diagram({  
  entity(  
    (0, 0),  
    name: "student",  
    label: "student",  
    attributes: (  
      north: ("name", "surname"),  
      east: ("mail",),  
      west: ("address",),  
      south: ("cellphone",),  
    ),  
    primary-key: "name"  
  )  
})
```



Composite primary key Adding a composite primary key:


```
#er-diagram({
  entity(
    (0, 0),
    name: "student",
    label: "student",
    attributes: (
      north: ("mail",),
      east: ("name", "surname"),
      west: ("address",),
      south: ("cellphone",),
    ),
    primary-key: ("name", "surname")
  )
})
```



i Info


The direction of the line will depend on the exact order you give the attributes:

```
#er-diagram({
  entity(
    (0, 0),
    name: "student",
    label: "student",
    attributes: (
      north: ("mail",),
      east: ("name", "surname"),
      west: ("address",),
      south: ("cellphone",),
    ),
    primary-key: ("name", "surname").rev()
  )
})
```



Composite attributes You might want to group some attributes together:

```
#er-diagram({
  entity(
    (0, 0),
    name: "student",
    label: "student",
    attributes: (
      east: ("name", "surname"),
      south: (
        // instead of a string, the comp.
        // attr. is an array
        ("street", "street_number",
        "city", "country"),
      ),
    ),
    primary-key: ("name", "surname").rev()
  )
})
```




i Info

The composite attributes is designed to be *the only attribute* on its side, meaning that other attributes on the same side will NOT be drawn.

2.1.2. Subentities

```
#er-diagram({
  entity(
    (0, 4),
    name: "A",
    label: "car",
  )
  entity(
    (-2, 0),
    name: "B",
    label: "electric",
  )
  entity(
    (2, 0),
    name: "C",
    label: "gasoline",
  )
  subentities(
    entity: "A",
    subentities: ("B", "C"),
  )
})
```




⚠ Warning

You can't connect a subentity to an entity if that entity has not been drawn yet: typ

```
1 // this will NOT work
2 #er-diagram({
3   subentities(
4     entity: "A",
5     subentities: ("B", "C"),
6   )
7   entity(
8     (0, 0),
9     name: "A",
10    label: "entity1",
11  )
12  entity(
13    (-2, 4),
14    name: "B",
15    label: "entity2",
16  )
17 })
```

Although subentities generally tend to be below their superentity, you can place them wherever you like best:

```
#er-diagram({
  entity(
    (0, 0),
    name: "A",
    label: "book",
  )
  entity(
    (6, 2),
    name: "B",
    label: "paper",
  )
  entity(
    (6, -2),
    name: "C",
    label: "ebook",
  )
  subentities(
    hierarchy: "(p,o)",
    entity: "A",
    subentities: ("B", "C"),
  )
})
```




A more complex layout:

```

#er-diagram({
  entity(
    (0, 0),
    name: "A",
    label: "senior",
  )
  entity(
    (-2, 4),
    name: "B",
    label: "overseer",
  )
  entity(
    (2, 4),
    name: "C",
    label: "manager",
  )
  entity(
    (2, 8),
    name: "D",
    label: "health",
  )
  entity(
    (-2, 8),
    name: "E",
    label: "logistics",
  )
  subentities(
    entity: "A",
    subentities: ("B", "C"),
  )
  subentities(
    entity: "B",
    subentities: ("D", "E"),
  )
})

```




If you need a relation between an entity and one of its subentities you can do so via the intersect argument:

```

#er-diagram({
  entity(
    (0, 0),
    label: "belt",
    name: "belt",
  )
  entity(
    (5, 0),
    label: "complex",
    name: "complex",
  )
  entity(
    (5, -3),
    label: "simple",
    name: "simple",
  )
  relation(
    coordinates: (2.5, 3),
    intersect: true,
    entities: ("belt", "complex"),
    label: "belongs",
    name: "belt-complex",
    cardinality: ("(0,1)", "(1,n)"),
  )
  subtentities(
    hierarchy: "(t,e)",
    entity: "belt",
    subtentities: ("complex", "simple"),
  )
})

```



2.1.3. Attributes positioning

Depending on what you are trying to achieve, the default placement could be wrong – you can modify it with `attributes-position`:

typ


```

1 attributes-position: (
2   side: (
3     alignment: left | center | right,
4     dir: "ltr" | "rtl",           // left-to-right, right-to-left
5     start: "from-short" | "from-long" // from shortest to longest
6   ),
7 )

```



Default:

```
#er-diagram({
  entity(
    (0, 0),
    name: "student",
    label: "student",
    attributes: (
      north: ("name", "surname", "mail"),
    ),
  )
})
```



Mirrored:


```
#er-diagram({
  entity(
    (0, 0),
    name: "student",
    label: "student",
    attributes: (
      north: ("name", "surname", "mail"),
    ),
    attributes-position: (
      north: (alignment: right, dir: "rtl")
    ),
  )
})
```



⚠ Warning

You will find out *some combinations* will lead to visual errors:


```
#er-diagram({
  entity(
    (0, 0),
    name: "student",
    label: "student",
    attributes: (
      north: ("name", "surname", "mail"),
    ),
    attributes-position: (
      north: (alignment: right)
    )
  )
})
```



In the future this might be patched.


From high to low:

```
#er-diagram({  
  entity(  
    (0, 0),  
    name: "student",  
    label: "student",  
    attributes: (  
      north: ("name", "surname", "mail"),  
    ),  
    attributes-position: (  
      north: (start: "from-long")  
    )  
  )  
})
```



Mirrored:


```
#er-diagram({  
  entity(  
    (0, 0),  
    name: "student",  
    label: "student",  
    attributes: (  
      north: ("name", "surname", "mail"),  
    ),  
    attributes-position: (  
      north: (  
        start: "from-long",  
        alignment: right,  
        dir: "rtl"  
      )  
    )  
  )  
})
```



2.2. Relations


Ideally the relation should be a straight line connecting two entities:

```
#er-diagram({  
  entity(  
    (0, 0),  
    name: "child",  
    label: "child",  
  )  
  entity(  
    (0, 4),  
    name: "parent",  
    label: "parent",  
  )  
  relation(  
    entities: ("parent", "child"),  
    cardinality: ("(0,n)", "(1,1)"),  
  )  
})
```




With label:

```
#er-diagram({  
  entity(  
    (0, 0),  
    name: "child",  
    label: "child",  
  )  
  entity(  
    (0, 4),  
    name: "parent",  
    label: "parent",  
  )  
  relation(  
    label: "has",  
    entities: ("parent", "child"),  
    cardinality: ("(0,n)", "(1,1)"),  
  )  
})
```




With label outside:

```
#er-diagram({
  entity(
    (0, 0),
    name: "child",
    label: "child",
  )
  entity(
    (0, 4),
    name: "parent",
    label: "parent",
  )
  relation(
    label: ("has", "east"),
    entities: ("parent", "child"),
    cardinality: ("(0,n)", "(1,1)"),
  )
})
```




With an attribute (same API as entities, see [Section 2.1.1](#)):

```
#er-diagram({
  entity(
    (0, 0),
    name: "user",
    label: "user",
  )
  entity(
    (0, -4),
    name: "subscription",
    label: "subscription",
  )
  relation(
    entities: ("user", "subscription"),
    cardinality: ("(1,n)", "(1,1)"),
    attributes: (east: ("date",)),
  )
})
```



Combined:

```
#er-diagram({
  entity(
    (0, 0),
    name: "user",
    label: "user",
  )
  entity(
    (0, -4),
    name: "subscription",
    label: "subscription",
  )
  relation(
    label: ("purchases", "east"),
    entities: ("user", "subscription"),
    cardinality: ("(1,n)", "(1,1)"),
    attributes: (east: ("date",)),
  )
})
```




i Info

Relations **can't** have primary keys; also there is no such thing as a “weak relation” (see [Section 4.1](#)).

Manual placement² If you need to manually specify where to place a relation you can:

```
#er-diagram({
  entity(
    (0, 0),
    name: "user",
    label: "user",
  )
  entity(
    (4, -4),
    name: "subscription",
    label: "subscription",
  )
  relation(
    coordinates: (4,0),
    label: ("purchases", "south-west"),
    entities: ("user", "subscription"),
    cardinality: ("(1,n)", "(1,1)"),
  )
})
```



²Since the relation attributes API is the same as entities, [Section 2.1.3](#) would apply as expected. Though remember the relations don't have... many anchors to draw from.

3. Formatting & customization

The package provides an handful of themes you can use by importing the corresponding module and applying the show rule:

typ

```
1 #import "@preview/dati-basati:0.1.1" as db
2 #show: db.with(..db.themes.at("theme-name"))
```

Currently the themes are:

- tiw
- snow
- ghibli
- tiramisu
- futurama
- C62-50
- C62-48
- polimi
- vaporvawe

The theme schema is as follows:

typ

```
1 #let default-settings = (
2   fill: (
3     entities: none,
4     relations: auto, // auto inherits entities
5     primary-key: black,
6     weak-entity: auto, // auto inherits primary-key
7     cardinality: auto, // auto = page fill
8     hierarchy: auto, // auto inherits cardinality
9     composite-attributes: auto, // auto inherits cardinality
10  ),
11  stroke: (
12    entities: black,
13    relations: black, // auto inherits entities
14    lines: auto, // auto inherits entities
15    attributes: black,
16    composite-attributes: auto, // auto inherits attributes
17    primary-key: auto, // auto inherits attributes
18    weak-entity: auto, // auto inherits primary-key
19    cardinality: none,
20    hierarchy: auto, // auto inherits cardinality
21  ),
22  radius: (
23    entities: 0pt,
24    cardinality: 0pt,
25    hierarchy: auto, // auto inherits cardinality
26  ),
27  spacing: (
28    in-between: (x: 1.2em, y: 1.2em), // spacing between attributes
29    padding: 1.2em, // distance from the entity
30  ),
31  text: (
32    entities: l => {
33      set par(leading: 0.35em)
34      text(
```

```

35     top-edge: "bounds",
36     size: 1.5em,
37     weight: "bold",
38     smallcaps(lower(l)),
39   )
40 },
41 relations: l => l,
42 attributes: l => l,
43 cardinality: l => text(top-edge: "bounds", bottom-edge: "bounds", l),
44 hierarchy: auto,
45 ),
46 attributes-position: (
47   "north": (
48     alignment: left,
49     dir: "ltr",
50     start: "from-short",
51   ),
52   "east": (
53     alignment: center,
54     dir: "ltr",
55   ),
56   "south": (
57     alignment: right,
58     dir: "rtl",
59     start: "from-short",
60   ),
61   "west": (
62     alignment: center,
63     dir: "rtl",
64   ),
65 ),
66 misc: (
67   weak-entities-stroke: false, // double stroke weak entities
68   relations-intersection: "|-",
69 ),
70 )

```

You can override single settings:

typ

```

1 #import "@preview/dati-basati:0.1.1" as db
2 #show: db.with(..db.themes.at("theme-name"),entities: (fill: green))

```

Or create new themes following the schema:

typ

```

1 #import "@preview/dati-basati:0.1.1" as db
2 #import "@preview/catppuccin:1.0.1": *
3 #let palette = flavors.latte.colors
4 #show: db.with(
5   fill: (
6     cardinality: palette.flamingo.rgb,

```

```

7     entities: palette.red.rgb,
8     relations: palette.red.rgb,
9     attributes: palette.red.rgb,
10    primary-key: palette.maroon.rgb,
11    weak-entity: palette.red.rgb,
12  ),
13  stroke: (
14    cardinality: palette.surface0.rgb + 0.1pt,
15    entities: black,
16    relations: black,
17    attributes: palette.rosewater.rgb,
18    weak-entity: orange,
19  ),
20  text: (
21    entities: l => text(
22      fill: palette.surface0.rgb,
23      weight: 500,
24      size: 1.2em,
25      smallcaps(l),
26    ),
27    cardinality: l => text(
28      top-edge: "bounds",
29      bottom-edge: "bounds",
30      fill: palette.surface0.rgb,
31      l,
32    ),
33  ),
34  radius: (
35    entities: 6pt,
36    cardinality: 6pt,
37  ),
38 )

```

There are plenty of examples with each and every theme – and corresponding source code – in [/examples](#).

Tip


If you need different ER diagrams to have different themes, create a .typ file and then include that – in this way, you can apply the show rule with the specific theme in the scope of the single file.

In the future, the theming settings could be implemented per er-diagram.

3.1. Individual styling overrides

At the start of the document the user is able to declare the global styling arguments, however there can be the need to individually override elements:

```
#er-diagram({  
  entity(  
    (0, 0),  
    name: "user",  
    label: "user",  
    fill: red.lighten(70%),  
    stroke: red,  
  )  
  entity(  
    (4, -4),  
    name: "subscription",  
    label: "subscription",  
    fill: orange.lighten(70%),  
    stroke: orange,  
  )  
  relation(  
    coordinates: (4,0),  
    label: ("purchases", "south-west"),  
    entities: ("user", "subscription"),  
    cardinality: ("(1,n)", "(1,1)"),  
    fill: yellow.lighten(70%),  
    stroke: yellow  
  )  
})
```




4. Advanced usage

4.1. Weak entities


Sometimes there is the need to express a weak constraint, such a carriage number *within the context* of a train; in order to do so specify the weak entity argument with the (attribute, strong-entity, direction) format:

```
#er-diagram({  
  entity(  
    (0, 0),  
    name: "train",  
    label: "train",  
  )  
  entity(  
    (0, -4),  
    name: "carriage",  
    label: "carriage",  
    attributes: (west: ("num", )),  
    weak-entity: ("num", "train")  
  )  
  relation(  
    entities: ("train", "carriage"),  
    cardinality: ("(1,n)", "(1,1)"),  
  )  
})
```



Changing the direction – now CCW, counter clockwise:

```
#er-diagram({  
  entity(  
    (0, 0),  
    name: "train",  
    label: "train",  
  )  
  entity(  
    (0, -4),  
    name: "carriage",  
    label: "carriage",  
    attributes: (west: ("num", )),  
    weak-entity: ("num", "train", "CCW")  
  )  
  relation(  
    entities: ("train", "carriage"),  
    cardinality: ("(1,n)", "(1,1)"),  
  )  
})
```




⚠ Warning

By default, you can't relate a weak entity to a strong entity *if the strong entity does not exist yet* – this behaviour mirrors how a possible SQL translation would work:

```
1 create table train(  
2   id int primary key  
3 );  
4 create table carriage(  
5   id int primary key,  
6   foreign key(id) references train(id)  
7 )
```

If you need to, you can specify the location of the strong entity via cardinal points:

```
#er-diagram({  
  entity(  
    (0, 0),  
    name: "carriage",  
    label: "carriage",  
    attributes: (south: ("num", )),  
    weak-entity: ("num", "south")  
  )  
  entity(  
    (0, -4),  
    name: "train",  
    label: "train",  
  )  
  relation(  
    entities: ("train", "carriage"),  
    cardinality: ("(1,n)", "(1,1)"),  
  )  
})
```



Note carriage and train have been swapped, so that the weak entity has been drawn *before* its corresponding strong entity.

4.2. Unorthodox relation position

Sometimes, due to the density of entities, the relations cannot be placed right above, left, right or below – the package acknowledges this and automatically handles this situation:

```
#er-diagram({
```

```
  entity(
```

```
    (0, 0),
```

```
    name: "train",
```

```
    label: "train",
```

```
  )
```

```
  entity(
```

```
    (4, -4),
```

```
    name: "carriage",
```

```
    label: "carriage",
```

```
    attributes: (east: ("num", )),
```

```
  )
```


```
  relation(
```

```
    entities: ("train", "carriage"),
```

```
    cardinality: ("(1,n)", "(1,1)"),
```

```
  )
```

```
})
```



Weak entity It also automatically handles weak entities in such cases:

```
#er-diagram({
```

```
  entity(
```

```
    (3, 0),
```

```
    name: "train",
```

```
    label: "train",
```

```
  )
```

```
  entity(
```

```
    (0, -4),
```

```
    name: "carriage",
```

```
    label: "carriage",
```

```
    attributes: (east: ("num", )),
```

```
    weak-entity: ("num", "train", "CCW")
```

```
  )
```


```
  relation(
```

```
    entities: ("train", "carriage"),
```

```
    cardinality: ("(1,n)", "(1,1)"),
```

```
  )
```

```
})
```




4.3. Exceptions

For some reason, you might need to create a weak entity that involves two entities but can't – or won't – start from the semantically correct attribute; you can still use the cardinal points:

```

#er-diagram({
  entity(
    (6, 0),
    name: "carriage",
    label: "carriage",
    attributes: (south: ("num", )),
    attributes-position: (south: (alignment: left)),
    weak-entity: ("south", "west")
  )
  entity(
    (0, 0),
    name: "train",
    label: "train",
  )
  entity(
    (6, -4),
    name: "convoy",
    label: "convoy",
  )
  relation(
    entities: ("train", "carriage"),
    cardinality: ("(1,n)", "(1,1)"),
  )
  relation(
    entities: ("convoy", "carriage"),
    cardinality: ("(1,n)", "(1,1)"),
  )
})

```



Also do note carriage is the first entity to be drawn.

4.4. Touying integration

Since the package is based on [CeTZ](#), you can pause the animations as you would do directly with CeTZ via [touying-reducer](#):

```

1 #import "@preview/dati-basati:0.1.1" as db
2 #import "@preview/cetz:0.5.2"
3 #import "@preview/touying:0.7.3": *
4
5 #let db-er-diagram = touying-reducer.with(
6   reduce: db.er-diagram,
7   cover: cetz.draw.hide.with(bounds: true),
8 )
9
10 #db-er-diagram({
11   entity(...)
12   (pause,)
13   entity(...)
14 })

```

typ

5. Themes showcase

```
(
  "C62-48",
  "C62-50",
  "futurama",
  "ghibli",
  "polimi",
  "snow",
  "tiramisu",
  "tiw",
  "vaporvawe",
)
```




Figure 1: C62-48 theme (font: Libertinus Serif).




Figure 2: c62-50 theme (font: Libertinus Serif).




Figure 3: futurama theme (font: Libertinus Serif).




Figure 4: ghibli theme (font: Carlito).




Figure 5: polimi theme (font: Manrope).




Figure 6: snow theme (font: Titillium Web).




Figure 7: tiramisu theme (font: IBM Plex Sans).




Figure 8: tiw theme (font: Barlow).




Figure 9: vaporvawe theme (font: Libertinus Sans).

6. User functions

For *all* the generated documentation, refer to </docs/docs.pdf>.

6.1 dati-basati

Default global settings.

Parameters

```
dati-basati(  
  fill: dictionary ,  
  stroke: dictionary ,  
  radius: dictionary ,  
  spacing: dictionary ,  
  text: dictionary ,  
  attributes-position: dictionary ,  
  misc: dictionary ,  
  body  
) -> dictionary
```

fill dictionary

The fill of each element.

Default: (:)

stroke dictionary

The stroke of each element.

Default: (:)

radius dictionary

The radius of entities, cardinality and hierarchy.

Default: (:)

spacing dictionary

The spacing of attributes.

Default: (:)

text dictionary

Text formatting of each element.

Default: (:)

attributes-position dictionary

The position and direction of attributes.

Default: (:)

misc dictionary

Miscellaneous options.

Default: (:)

6.2 er-diagram

Draw an Entity-Relation Diagram. This is the function that wraps all the diagrams.

Parameters

```
er-diagram(  
  theme: dictionary ,  
  ..args: dictionary ,  
  body: content  
) -> content
```

theme dictionary

The theme of this diagram.

Default: (:)

..args dictionary

Arguments directly passed to `#cetz.canvas()`.

body content

Body of the diagram.

6.3 entity

Draw an entity.

Parameters

```
entity(  
    coordinates: array ,  
    name: str ,  
    label: str content ,  
    attributes: dictionary ,  
    attributes-position: dictionary ,  
    primary-key: str array ,  
    weak-entity: array ,  
    misc: dictionary ,  
    ..args: args  
) -> content
```

coordinates array

Coordinates of the entity.

name str

Unique name of the entity.

Default: ""

label str or content

Label for the entity (e.g. Person, Book, Employee...).

Default: "Entity"

attributes dictionary

Attributes of the entity (e.g. id, name, surname, address...).

Default: (:)

attributes-position dictionary

Fine tune positioning of attributes.

Default: (:)

primary-key str or array

Primary key(s).

Default: none

weak-entity array

Whether this entity is weak and the corresponding attribute. The format is as follows:

- SQL mirror: (attribute, strong entity, direction)
- With cardinal points: (cardinal pt, cardinal pt, direction)

They can be mixed.

Default: none

misc dictionary

Miscellaneous options:

- weak-entity-intersection

Default: none

..args args

Arguments passed to `#std.rect()`.

6.4 subentities

Connect subentities to the superentity.

Parameters

```
subentities(  
  hierarchy: "(t,e)" or "(p,e)" or "(p,o)" ,  
  entity: str ,  
  subentities: array  
) -> content
```

hierarchy "(t,e)" or "(p,e)" or "(p,o)"

The hierarchy of the subentities:

- (t,e)=(total, exclusive)
- (p,e)=(partial, exclusive)
- (p,o)=(partial, overlapping)

Default: "(t,e)"

entity `str`

The superentity, the one to which the subentities will connect.

Default: `""`

subentities `array`

The subentities. Can be just one.

Default: `( "", )`

6.5 relation

Draw a relation between (sub)entities.

Parameters

```
relation(  
    coordinates: array ,  
    entities: array ,  
    name: str ,  
    label: str ,  
    attributes: dictionary ,  
    cardinality: array ,  
    intersect: bool ,  
    ..args: args  
) -> content
```

coordinates `array`

The specific coordinates of this relation. If left empty, they will be the middle point between the two entities.

Default: `none`

entities `array`

Entities that are tied by this relation.

Default: `()`

name `str`

Unique name of relation.

Default: `""`

label `str`

Label for the relation (e.g. "occupies", "relates", "is part of"...).

Default: `""`

attributes `dictionary`

Attributes of the relation (e.g. id, name, surname, address...).

Default: `( : )`

cardinality `array`

Cardinality of the given relation:

Default: `( )`

intersect `bool`

Whether to intersect the lines connecting relations instead of a direct connection.

Default: `false`

..args `args`

Arguments passed to `#std.rect()`.