Sri Lanka Institute of Information Technology

# PROTECTIVA: A MULTI-MODAL EDGE-AI FRAMEWORK

## INDIVIDUAL THESIS

**K. Vidusha Upashalya De Abrew**
(IT22168054)

Individual component: Audio Guardian and Frontend Orchestration
Group ID: RP_WE_G104

Report submitted in partial fulfilment of the requirements for the
**B.Sc. (Hons) in Information Technology**
Specializing in Software Engineering

Department of Information Technology
Sri Lanka Institute of Information Technology
Sri Lanka

October 11, 2026

# DECLARATION AND SUPERVISOR CERTIFICATION

**Candidate declaration.** I declare that this thesis is my own work and does not incorporate, without acknowledgement, material previously submitted for a degree or diploma at any university or institute of higher learning. To the best of my knowledge, it contains no material previously published or written by another person except where acknowledgement is made in the text. I grant the Sri Lanka Institute of Information Technology the non-exclusive right to reproduce and distribute this thesis, in whole or in part, in print, electronic, or other media, while retaining the right to use the content in future work.

**Academic integrity and AI disclosure.** I have disclosed all use of generative AI and other automated tools in accordance with the module policy. I remain responsible for the accuracy, originality, citations, code, data, analyses, and conclusions in this thesis.

Student name: K. Vidusha Upashalya De Abrew

Student ID: IT22168054

Signature: _____ Date: _____

**Supervisor certification.** The above candidate carried out this research for the bachelor's degree thesis under my supervision.

| **Role and name** | **Signature** | **Date** |
|---|---|---|
| Supervisor: Prof. Pradeep Abeygunawardhana | | |

| Role and name | Signature | Date |
|---|---|---|
| Co-supervisor: [Co-supervisor Name] | | |

# ABSTRACT

Single-sensor child-safety monitors suffer from complementary blind spots and high false-positive rates. This thesis details the Audio Guardian component of the Protectiva system, a resilient React Native frontend and edge-AI acoustic pipeline. The system utilizes a 120-channel 1D-CNN-LSTM network to distinguish genuine pediatric distress from ambient household noise. By combining on-device feature extraction on a low-cost ESP32-S3 edge node with deterministic caregiver-voice verification, the system is designed to reduce the alert fatigue common in traditional monitors. Evaluation on a balanced 100-sample benchmark reports 98.0% classification accuracy, 96.0% safety-critical recall, and a 0.0% false-positive rate, with a targeted end-to-end latency below 200 ms supported by a dual-backend fallback design.

**Keywords:** Edge AI, Acoustic Threat Detection, 1D-CNN-LSTM, React Native, Child Safety, ESP32

# ACKNOWLEDGEMENTS

I would like to express my sincere gratitude to my supervisor, Prof. Pradeep Abeygunawardhana, for his continuous guidance, valuable advice, and encouragement throughout this research. His support and direction were instrumental in shaping this study and helping me complete it successfully.

In addition, I would like to acknowledge the Sri Lanka Institute of Information Technology (SLIIT) for providing the laboratory facilities and academic environment required to carry out this work. Finally, I would like to express my heartfelt thanks to my family and friends for their unwavering encouragement, patience, and moral support throughout the completion of this research.

# Contents

**DECLARATION AND SUPERVISOR CERTIFICATION** i

**ABSTRACT** iii

**ACKNOWLEDGEMENTS** iv

**LIST OF ABBREVIATIONS** x

**1 INTRODUCTION** 1

1.1 Overall project context . . . . . 1

1.2 Individual component context . . . . . 2

1.3 Problem statement . . . . . 2

1.4 Research gap . . . . . 2

1.5 Aim and objectives . . . . . 3

1.6 Research questions or hypotheses . . . . . 3

1.7 Scope limitations and assumptions . . . . . 4

1.8 Individual contribution . . . . . 4

1.9 Thesis structure . . . . . 4

**2 LITERATURE REVIEW AND RELATED WORK** 5

2.1 Review method and scope . . . . . 5

2.2 Domain and theoretical foundations . . . . . 5

2.2.1 Acoustic Bio-Mechanics of Pediatric Distress Vocalizations . . . . 5

2.2.2 Digital Signal Processing and Cepstral Parameterization . . . . . 6

2.3 Related research . . . . . 7

2.3.1 Speech Emotion Recognition and Infant Cry Classification . . . . . 7

2.3.2 Critique of Existing Empirical Literature . . . . . 7

2.4 Existing systems products and techniques . . . . . 8
2.4.1 Commercial Baby Monitors and Intensity Bias . . . . . 8
2.4.2 Cloud-Connected Smart Monitors and Privacy Violations . . . . . 8
2.5 Gap synthesis and conceptual framework . . . . . 8

**3 RESEARCH METHODOLOGY 10**
3.1 Research design . . . . . 10
3.2 Data participants or study materials . . . . . 10
3.2.1 Acoustic Datasets and Taxonomy Mapping . . . . . 10
3.2.2 Data Partitioning and Augmentation Protocols . . . . . 11
3.3 Experimental or study procedure . . . . . 11
3.4 Measures and evaluation metrics . . . . . 12
3.5 Data analysis . . . . . 12
3.6 Ethics privacy security and responsible AI . . . . . 12
3.6.1 Enforcement of the Zero-Raw-Audio Protocol . . . . . 12
3.6.2 Biometric Data Governance and Security . . . . . 13
3.7 Reproducibility and research artefacts . . . . . 13

**4 PRODUCT AND SOLUTION DESIGN 14**
4.1 Requirements . . . . . 14
4.2 Component architecture within the complete solution . . . . . 14
4.3 Design alternatives and decisions . . . . . 17
4.4 Detailed design . . . . . 17
4.5 Standards and professional practice . . . . . 18

**5 IMPLEMENTATION INTEGRATION AND TESTING 19**
5.1 Development environment and technology stack . . . . . 19
5.2 Component implementation . . . . . 20
5.2.1 Frontend React Native Orchestration . . . . . 20
5.2.2 Backend API Specifications . . . . . 20
5.3 Integration with the other components . . . . . 20
5.4 Verification and software testing . . . . . 20
5.5 Deployment and operation . . . . . 21

**6 RESULTS AND VALIDATION** **22**

6.1 Research results . . . . . 22

6.2 Product and technical results . . . . . 23

6.3 User or stakeholder validation . . . . . 23

6.4 Integration results . . . . . 24

6.5 Summary of findings . . . . . 24

**7 DISCUSSION** **25**

7.1 Interpretation of findings . . . . . 25

7.2 Comparison with literature baselines and existing solutions . . . . . 26

7.3 Research contribution . . . . . 26

7.4 Product contribution . . . . . 26

7.5 Limitations and threats to validity . . . . . 26

7.6 Implications . . . . . 27

**8 COMMERCIALISATION AND SUSTAINABILITY** **28**

8.1 Value proposition and target users . . . . . 28

8.2 Market and competitive position . . . . . 28

8.3 Business or sustainability model . . . . . 29

8.4 Scalability intellectual property and compliance . . . . . 30

8.5 Contribution to the Sustainable Development Goals . . . . . 30

**9 CONCLUSION AND FUTURE DIRECTIONS** **31**

9.1 Conclusion . . . . . 31

9.2 Achievement of objectives . . . . . 31

9.3 Individual research and product contributions . . . . . 31

9.4 Future directions . . . . . 32

**REFERENCES** **33**

**GLOSSARY** **38**

**APPENDICES** **39**

# List of Figures

3.1 End-to-end operational processing pipeline of the Audio Guardian. . . . . 11

4.1 Overall System Architecture of the Audio Guardian Component . . . . . 15
4.2 Multi-Tiered Dual-Backend Fallback Architecture . . . . . 16
4.3 State Transition Diagram of the 3-Step Guided Biometric Voice Enrollment Wizard . . . . . 17

6.1 Normalised confusion matrix for the AudioThreatNet binary classifier on the 100-sample balanced test set. . . . . 22
6.2 Multi-metric benchmark comparison and validation loss vs. inference latency across evaluated architectures. . . . . 23

7.1 Ablation study showing incremental accuracy gains and false-alarm suppression across acoustic pipeline modules. . . . . 25

# List of Tables

5.1 API Endpoint Specification and Execution Flow . . . . . 20

6.1 Scenario-Based Validation of the Anti-Fatigue Suppressor Override Mechanism (four test cases). . . . . 23

8.1 Competitive positioning of Audio Guardian against commercial monitoring paradigms. . . . . 29

# LIST OF ABBREVIATIONS

| Abbreviation | Meaning |
|---|---|
| CNN | Convolutional Neural Network |
| DSP | Digital Signal Processing |
| I2S | Inter-IC Sound |
| LSTM | Long Short-Term Memory |
| MEMS | Micro-Electro-Mechanical Systems |
| MFCC | Mel-Frequency Cepstral Coefficients |
| SPL | Sound Pressure Level |
| VAD | Voice Activity Detection |

# Chapter 1

# INTRODUCTION

## 1.1 Overall project context

Child physical safety within residential and domestic environments is a significant societal and public health concern. Children aged 4 to 8 years are particularly vulnerable, as they transition toward greater physical independence while lacking the cognitive maturity required to report hazardous domestic encounters. Conventional domestic surveillance paradigms typically rely on closed-circuit television (CCTV) cameras or simplistic radio baby monitors. However, these legacy systems have notable limitations, including visual blind spots, susceptibility to ambient acoustic interference, and video transmission that intrudes on household privacy.

To address these challenges, the ‘‘Protectiva’’ project was conceptualized as a multimodal, end-to-end child safety monitoring and legal decision-support ecosystem tailored specifically for children aged 4 to 8 years. The platform integrates four specialized subsystems:

1. **Vision Guardian:** A vision-based edge subsystem employing convolutional neural networks and human pose estimation.

2. **Audio Guardian:** A privacy-preserving bio-acoustic Edge-AI sensor node dedicated to continuous acoustic monitoring.

3. **Legal RAG System:** A Retrieval-Augmented Generation regulatory pipeline that provides context-aware child welfare advisory.

4. **Data Fusion Dashboard:** A centralized supervisory interface that correlates multi-modal visual and acoustic metadata.

## 1.2 Individual component context

Within the broader Protectiva multi-modal ecosystem, the author's individual research and engineering component is the **Audio Guardian**. Bio-acoustic monitoring is a useful complementary modality, as sound propagation is omnidirectional and inherently non-line-of-sight (NLOS), capable of penetrating acoustic pathways across occluded domestic spaces where cameras are prohibited. The Audio Guardian integrates an ultra-low-cost Espressif ESP32-S3 microcontroller, an INMP441 digital microphone, and a FastAPI cloud inference engine to continuously monitor the acoustic environment for acute pediatric distress.

## 1.3 Problem statement

Commercial sound detection apparatuses share two common limitations: *Intensity Bias* and *Caregiver Alert Fatigue*. Current monitors rely overwhelmingly on simplistic scalar sound pressure level (SPL) or Root-Mean-Square (RMS) amplitude thresholding. These systems trigger alerts whenever the ambient sound intensity exceeds an arbitrary decibel threshold. In an active domestic household, benign events such as dropped cookware or animated television broadcasts generate sound pressure levels comparable to a child's distress scream. Consequently, monitors can generate frequent false-positive notifications, contributing to Caregiver Alert Fatigue and, in some cases, leading parents to disable the alarm.

## 1.4 Research gap

A critical review shows a split in domestic acoustic monitoring:

1. **Heuristic, Low-Intelligence Edge Devices:** Low-power consumer monitors rely exclusively on basic RMS volume thresholds, which leads to frequent false alarms.

2. **Centralized, Privacy-Violating Cloud Architectures:** Modern deep learning monitors stream raw pulse-code modulation (PCM) audio continuously to centralized third-

party cloud servers. This introduces serious privacy risks, exposing household audio to possible data breaches.

There is a gap for a lightweight, hybrid-edge acoustic surveillance framework capable of evaluating distress sequences through deep neural networks and enforcing biometric false-alarm suppression, all while operating under a strict ‘‘Zero-Raw-Audio’’ transmission protocol.

## 1.5 Aim and objectives

The primary aim of this research is to design, implement, and evaluate the ‘‘Audio Guardian’’: an edge-native, privacy-preserving bio-acoustic monitoring system that accurately detects pediatric distress vocalizations and suppresses benign household false alarms. Specific objectives include:

- **Objective 1:** Deploy an efficient DSP pipeline on the ESP32-S3 to compute 120-channel multi-spectral representations (MFCC + $\Delta$ + $\Delta\Delta$) and immediately flush raw PCM waveforms.
- **Objective 2:** Formulate and optimize a hybrid 1D-CNN+LSTM sequence classification architecture to discriminate pediatric distress screams from domestic transients.
- **Objective 3:** Engineer a lightweight, text-independent voice verification mechanism to suppress false alarms when parents speak loudly within the sensor's perimeter.

## 1.6 Research questions or hypotheses

- **RQ1:** To what extent can an ultra-low-cost microcontroller (ESP32-S3) execute continuous 120-channel multi-spectral feature extraction within constrained hardware limits (512 KB SRAM)?
- **RQ2:** How effectively can a hybrid 1D-CNN+LSTM architecture differentiate acute pediatric pain screams from high-decibel domestic transients compared to standard threshold baselines?
- **RQ3:** Can a dual-stage biometric suppression gate reliably discriminate registered caregiver speech to achieve a zero false-alarm rate (0.0% FAR)?

## 1.7 Scope limitations and assumptions

The system is scoped for children aged 4 to 8 years within domestic residential interiors. The edge sensing node is strictly bound to the ESP32-S3-WROOM-1 module interfaced with an INMP441 microphone. Acoustic inputs exceeding the microphone's 120 dB Acoustic Overload Point will undergo hardware-level clipping. The system assumes continuous mains power and a stable local area network Wi-Fi connection.

## 1.8 Individual contribution

The author was exclusively responsible for the design, theoretical formulation, firmware engineering, deep learning pipeline, and empirical evaluation of the Audio Guardian subsystem, including deploying the 1D-CNN+LSTM model, building the 3-step biometric enrollment wizard in React Native, and ensuring a sub-200ms dual-backend fallback strategy.

## 1.9 Thesis structure

Chapter 2 reviews related literature. Chapter 3 outlines the research methodology. Chapter 4 details the product and solution design. Chapter 5 covers implementation, integration, and testing. Chapter 6 presents results and validation. Chapter 7 provides a critical discussion. Chapter 8 evaluates commercialisation and sustainability. Finally, Chapter 9 concludes the thesis.

# Chapter 2

# LITERATURE REVIEW AND RELATED WORK

## 2.1 Review method and scope

To establish the theoretical and empirical foundation for the Audio Guardian subsystem, a literature review was conducted, guided by established software engineering and biomedical informatics survey methodologies [1, 2]. The objective of this review was to evaluate existing academic paradigms, algorithmic models, and commercial systems at the intersection of Acoustic Event Detection (AED), Speech Emotion Recognition (SER), embedded digital signal processing (DSP), and edge computing for pediatric monitoring.

The search covered major electronic bibliographic databases, including IEEE Xplore, the ACM Digital Library, ScienceDirect (Elsevier), SpringerLink, and the National Library of Medicine (PubMed). Boolean search strings built from standard keywords were used.

## 2.2 Domain and theoretical foundations

### 2.2.1 Acoustic Bio-Mechanics of Pediatric Distress Vocalizations

Human vocal production is traditionally modeled using the classical source-filter acoustic theory [3]. In standard modal phonation, pulmonic airstream pressure induces quasi-periodic self-sustained oscillations of the vocal folds within the larynx, generating an acoustic source signal characterized by a fundamental frequency ($F_0$) and an associated harmonic spectrum.

As this glottal volume velocity wave propagates through the supraglottal vocal tract, specific frequency bands are reinforced by acoustic resonances known as formants ($F_1, F_2, F_3, \dots$), establishing the spectral envelope of human speech [37].

Under extreme physiological distress, acute physical trauma, or panic, neuro-motor activation triggers extreme aerodynamic and muscular adaptations. High subglottal pressure combined with hyperadduction of the laryngeal musculature destabilizes the linear oscillation regime of the vocal folds [4]. This gives rise to pronounced non-linear bio-acoustic phenomena:

1. **Fundamental Frequency Elevation and Dispersion:** In pediatric subjects, standard conversational pitch exhibits fundamental frequencies between 200 Hz and 300 Hz. Under genuine pain screams, $F_0$ can rise well above this range, accompanied by erratic pitch contours [5].

2. **Subharmonic Bifurcations and Period Doubling:** Non-linear vocal fold desynchronization introduces fractional frequency components ($\frac{F_0}{2}$, $\frac{F_0}{3}$), creating distinct subharmonic spectral lines intercalated between standard glottal harmonics [6].

3. **Deterministic Chaos and Acoustic Roughness:** Severe physical distress forces the laryngeal mechanism into chaotic vibration, generating non-harmonic, broadband turbulent noise. Psychophysically, this energy dispersion in the 30–150 Hz modulation rate domain produces severe ‘‘acoustic roughness,’’ a property thought to bypass habituation and trigger immediate threat responses in human listeners [7].

### 2.2.2 Digital Signal Processing and Cepstral Parameterization

Because raw, time-domain acoustic waveforms are non-stationary, digital audio must be converted into compact, time-frequency representations that preserve discriminative spectral geometry while compressing dimensionality. A widely used technique in bio-acoustics is the computation of Mel-Frequency Cepstral Coefficients (MFCCs) [8]. To capture the velocity and acceleration trajectories of evolving distress vocalizations, static MFCC vectors are augmented with first-order delta ($\Delta$) and second-order delta-delta ($\Delta\Delta$) temporal dynamics. Stacking static, velocity, and acceleration coefficients produces a 120-channel multi-spectral dynamic tensor, representing the evolving acoustic signature of distress vocalizations [9].

## 2.3 Related research

### 2.3.1 Speech Emotion Recognition and Infant Cry Classification

The automatic classification of acoustic distress evolved from early paradigms in Speech Emotion Recognition (SER) and Infant Cry Classification (ICC). Early works utilized classical machine learning models, such as Gaussian Mixture Models (GMMs) and Support Vector Machines (SVMs), operating on handcrafted acoustic features [35, 36]. While foundational, these classical approaches showed performance degradation when exposed to unseen acoustic environments.

With the proliferation of deep learning, researchers shifted toward Convolutional Neural Networks (CNNs) trained on two-dimensional time-frequency representations [20]. Although 2D-CNNs exhibit superior localized spatial feature extraction, they require dense floating-point operations (tens of millions of FLOPs), making them impractical for low-power edge microcontrollers without dedicated neural processing units.

To capture temporal context, subsequent research explored recurrent topologies, specifically Long Short-Term Memory (LSTM) networks [22]. Hybrid Convolutional Recurrent Neural Networks (CRNNs), which cascade 1D convolutional layers with an LSTM sequence layer, became a widely used configuration for acoustic event detection [23].

### 2.3.2 Critique of Existing Empirical Literature

Despite significant theoretical advancements, a critical analysis of current literature identifies two main limitations. Firstly, the overwhelming majority of models are evaluated against closed, highly sanitized acoustic corpora [24]. They often omit overlapping domestic transient noises common to active households, causing models reporting > 95% laboratory accuracy to show high false-positive rates when deployed into real-world homes [38]. Secondly, extant frameworks operate as blind classification pipelines. To the author's knowledge, prior work has not integrated speaker biometric suppression gates within distress detection pipelines, leaving caregiver-induced false alarms largely unaddressed.

## 2.4 Existing systems products and techniques

### 2.4.1 Commercial Baby Monitors and Intensity Bias

The commercial consumer landscape for domestic nursery monitoring relies largely on analog envelope detectors or trivial Root-Mean-Square (RMS) software thresholds to detect acoustic events [26]. This exposes a common weakness: *Intensity Bias*. Intensity-based thresholding assumes that sound pressure level directly correlates with human danger. In real-world households, benign events can reach 75–85 dB SPL. Because these devices lack semantic signal analysis, they trigger continuous false alarms, contributing to *Caregiver Alert Fatigue* [27].

### 2.4.2 Cloud-Connected Smart Monitors and Privacy Violations

Modern ‘‘smart nursery’’ products employ cloud-based artificial intelligence [28]. While these systems leverage high-parameter neural networks, many stream raw Pulse Code Modulation (PCM) audio across wide-area networks. Security studies have identified weaknesses in consumer smart-home devices, including interception and unauthorised-access risks [39]. Transmitting raw household speech can conflict with GDPR principles such as data protection by design (Article 25) and exposes families to privacy loss [29].

## 2.5 Gap synthesis and conceptual framework

The synthesis of existing literature reveals an unresolved gap. To the author's knowledge, no reported acoustic child-safety monitoring system couples deep-learning sequence classification with embedded edge feature extraction to guarantee household auditory privacy while deploying speaker biometric suppression to eliminate false alarms.

To resolve this systemic gap, this thesis establishes the conceptual framework of the **Audio Guardian**. The architecture operates on an asymmetric Edge-Cloud collaborative topology grounded in three core principles:

1. **Zero-Raw-Audio Edge Isolation:** Digital pulse-code modulation waveforms are captured exclusively within volatile DMA memory buffers.

2. **Acoustic Texture and Sequence Classification:** A hybrid 1D-CNN+LSTM neural network evaluates irreversible spectral coefficient matrices.

3. **Biometric Anti-Fatigue Gating:** When high-intensity acoustic events occur, the inference pipeline activates a biometric verification gate to suppress false alarms.

# Chapter 3

# RESEARCH METHODOLOGY

## 3.1 Research design

This study adopts the Design Science Research (DSR) paradigm, a structured engineering research methodology formulated by Peffers et al. [30] and Hevner et al. [40]. DSR is well suited to applied software engineering, prioritizing the iterative creation, deployment, and empirical evaluation of innovative technological artifacts designed to solve recognized real-world operational problems.

## 3.2 Data participants or study materials

### 3.2.1 Acoustic Datasets and Taxonomy Mapping

Model training and offline benchmarking leveraged two established, peer-reviewed acoustic corpora:

1. **The RAVDESS Corpus:** Comprises 1,440 standardized vocalizations produced by professional stage actors [31]. Emotional categories were mapped onto a binary schema: Class 0 (Safe / Benign Vocalizations) encompassing neutral, calm, and happy expressions, and Class 1 (Threat / Distress Vocalizations) encompassing angry and fearful expressions.

2. **The ESC-50 Dataset:** To ensure the model discriminates distress vocalizations from non-hazardous, high-amplitude household transients, 400 domestic environmental au-

dio recordings [32] (e.g., door slams, vacuum cleaners) were integrated exclusively into Class 0 (Safe).

### 3.2.2 Data Partitioning and Augmentation Protocols

The combined acoustic dataset (1,840 total samples) was partitioned using a stratified 80:20 train-test split. To strictly prevent speaker identity leakage, the partition was stratified by actor identity. From the resulting 20% validation partition (roughly 368 samples), a perfectly balanced sub-sample of exactly 100 instances (50 Threat, 50 Safe) was extracted to compute the final, normalized confusion matrix and rigorous classification metrics.

To inhibit neural overfitting, the training pipeline implemented on-the-fly *SpecAugment* data augmentation [33] via frequency channel masking, temporal frame masking, and additive Gaussian white noise.

## 3.3 Experimental or study procedure

The complete data collection, processing, and inference pipeline operates across seven sequential phases:





Figure 3.1: End-to-end operational processing pipeline of the Audio Guardian.

The INMP441 omnidirectional MEMS microphone captures continuous acoustic waves in 3.0-second duration buffers at 16 kHz. The embedded firmware computes static 40-dimensional MFCCs augmented with first-order velocity ($\Delta$) and second-order acceleration ($\Delta\Delta$) temporal derivatives. The raw 16-bit PCM audio samples residing in DMA memory are overwritten with zeros and deallocated. The lightweight 120-channel feature tensor is dispatched to the local FastAPI backend. Two 1D convolutional layers with ReLU activations extract localized formant energy transitions, while a single-layer recurrent LSTM unit tracks long-term temporal progression. If Class 1 (Threat) is predicted, the biometric gate matches the incoming vocal tract resonances against registered parental templates. If a match occurs, the threat prediction is overridden, completely suppressing the alarm.

## 3.4 Measures and evaluation metrics

System performance is evaluated across standard classification performance metrics derived from the binary confusion matrix: Classification Accuracy, Sensitivity (Recall), Precision, Specificity, and the Macro F1-Score. End-to-End System Latency ($T_{\text{total}}$) is also physically measured from the cessation of the sound event to notification dispatch.

## 3.5 Data analysis

Quantitative analysis incorporates four distinct analytical methods:

- **Confusion Matrix Analysis:** Mapping raw instance distributions across predicted versus actual labels.
- **Receiver Operating Characteristic (ROC) and Precision-Recall (PR) Curves:** Evaluating Area Under the Curve trade-offs between sensitivity and false alarm rates.
- **Ablation Studies:** Systematically isolating components to evaluate their individual contributions (e.g., measuring False Alarm Rates before and after introducing the biometric gate).
- **Comparative Model Benchmarking:** Benchmarking the proposed 1D-CNN+LSTM against classical Artificial Neural Networks and 2D-CNN architectures.

## 3.6 Ethics privacy security and responsible AI

### 3.6.1 Enforcement of the Zero-Raw-Audio Protocol

The foundational ethical imperative of the Audio Guardian is the preservation of domestic acoustic privacy, structurally aligned with GDPR Privacy-by-Design mandates [29]. During continuous monitoring, raw PCM audio is buffered strictly within volatile internal SRAM via DMA. Following execution of the 120-channel MFCC algorithm, the memory buffer containing raw audio is explicitly cleared with zeros and deallocated. The discrete Fourier phase spectrum is deliberately discarded, which substantially limits the ability to reconstruct intelligible speech from the transmitted cepstral matrices.

### 3.6.2 Biometric Data Governance and Security

Parental voice templates used for biometric false-alarm suppression are not stored as audio recordings. The system extracts a 64-dimensional float vector representing anatomical vocal tract formant ratios. These mathematical representations are transmitted over TLS-encrypted HTTPS tunnels and stored as non-audio feature arrays in Supabase.

## 3.7 Reproducibility and research artefacts

To facilitate independent verification, all software artifacts and configuration schemas have been formalized and archived under version control. The Configuration Master Schema defines all system hyperparameters, and the PyTorch model state dictionary is versioned alongside exact neural definition scripts with locked random seeds to support reproducibility.

# Chapter 4

# PRODUCT AND SOLUTION DESIGN

## 4.1 Requirements

The Audio Guardian must fulfill several rigorous functional and non-functional requirements. It must continuously capture 16kHz audio, compute 120-channel MFCC matrices locally, and transmit metadata to a cloud backend with an end-to-end latency under 200ms. Non-functionally, the system must guarantee user privacy (Zero-Raw-Audio) and maintain an overall detection recall exceeding 95%.

## 4.2 Component architecture within the complete solution

The Audio Guardian component employs a decoupled architecture comprising a mobile presentation layer, a high-performance edge ingestion engine, and a real-time database communication tier. As illustrated in Figure 4.1, the presentation layer is implemented using React Native with Expo, delivering a responsive, touch-optimized user experience for Android, iOS, and Web targets.

In a life-safety IoT application, single points of failure are unacceptable. The Audio Guardian implements a multi-tiered dual-backend fallback strategy spanning client, server, and local storage layers, as mapped in Figure 4.2.





Figure 4.1: Overall System Architecture of the Audio Guardian Component







Figure 4.2: Multi-Tiered Dual-Backend Fallback Architecture

## 4.3 Design alternatives and decisions

A pivotal design decision was migrating from a Raspberry Pi 4 Single Board Computer to an ESP32-S3 microcontroller. While the Raspberry Pi offers superior computational headroom, its higher cost and thermal overhead make it less suitable for mass-market domestic deployment. The ESP32-S3, priced under $15, features vector instructions capable of executing the required DSP algorithms while drastically reducing power consumption and physical footprint.

## 4.4 Detailed design

To allow non-technical parents to register robust acoustic voiceprints that operate independently of the exact phrases spoken, the system incorporates a 3-Step Guided Enrollment Studio Modal (`VoiceEnrollmentModal`). The complete state transition workflow is detailed in Figure 4.3.





Figure 4.3: State Transition Diagram of the 3-Step Guided Biometric Voice Enrollment Wizard

The 64-dimensional feature embedding $\mathbf{e} \in \mathbb{R}^{64}$ is L2 unit-normalized and verification is

performed using standard Cosine Distance against a stored profile $\mathbf{v}$:

$$\text{Dist}(\mathbf{u}, \mathbf{v}) = 1 - (\mathbf{u} \cdot \mathbf{v}) \tag{4.1}$$

## 4.5 Standards and professional practice

The design follows REST API architectural conventions. Secure communication is enforced via HTTPS/WSS protocols, and the database schema complies with standard relational normalization practices.

# Chapter 5

# IMPLEMENTATION INTEGRATION AND TESTING

## 5.1 Development environment and technology stack

The edge-inference hardware platform consists of an **Espressif ESP32-S3** microcontroller unit (MCU) paired with an **INMP441** MEMS digital microphone. The ESP32-S3 operates at 240 MHz with 512 KB SRAM, providing I2S peripheral connectivity for real-time PCM audio capture at a sample rate of 16 kHz. Audio chunks of 3-second duration are buffered on-device and transmitted to the inference server over a local Wi-Fi (802.11n) link using HTTP multipart POST requests.

The software architecture spans three tiers:

- **ML Backend:** Python 3.11, PyTorch 2.1+, Librosa 0.10+
- **API Middleware:** FastAPI, Uvicorn (ASGI), PyAV
- **Mobile Frontend & DB:** React Native (Expo SDK 50+), TypeScript, Supabase (PostgreSQL) with Realtime WebSocket CDC.

## 5.2 Component implementation

### 5.2.1 Frontend React Native Orchestration

Telemetry and alert states are decoupled from presentation components through the dedicated `useAlerts()` custom hook. In-app microphone recording is handled via the `expo-av` library, encapsulating recording instances via `Audio.RecordingOptionsPresets.HIGH_QUALITY` to produce WAV/M4A recordings.

### 5.2.2 Backend API Specifications

Table 5.1 details the core REST ingestion and orchestration endpoints exposed by the FastAPI service.

Table 5.1: API Endpoint Specification and Execution Flow

| **Endpoint** | **Method** | **Request Payload** | **Purpose & Execution Flow** |
|---|---|---|---|
| `/api/audio/upload-chunk` | POST | `file`: 3.0s Audio Chunk | Core ingestion for ESP32 nodes. Executes AudioThreatNet. |
| `/api/audio/check-environment` | POST | `file`: 2.0s Ambient WAV | Step 1: Calibrates background noise floor (< 52 dB). |
| `/api/audio/validate-phrase-sample` | POST | `file`: Recited Phrase Sample | Step 2: Executes VAD, HPSS, and harmonic resonance checks. |
| `/api/audio/register-parent` | POST | `file`: Biometric WAV | Step 3: Computes 64-D vector, persists to Supabase. |
| `/api/v1/alerts/history` | GET | `page, limit, event_type` | Returns paginated historical distress and threat alert records. |

## 5.3 Integration with the other components

The Audio Guardian successfully integrates with the central Supabase PostgreSQL database, acting as the primary acoustic telemetry provider for the overarching Protectiva Data Fusion Dashboard.

## 5.4 Verification and software testing

Unit testing was performed on the FastAPI routes using the PyTest framework, verifying JSON payload validation and HTTP status code responses. Integration testing validated the WebSocket Change Data Capture (CDC) triggers between Supabase and the React Native frontend.

## 5.5 Deployment and operation

The backend microservice was containerized using Docker and deployed to a local inference server. The React Native frontend was compiled into standalone Android APKs and iOS IPA binaries via Expo Application Services (EAS).

# Chapter 6

# RESULTS AND VALIDATION

## 6.1 Research results

The trained AudioThreatNet model was evaluated on the held-out test split. Focusing on the balanced 100-sample sub-set, the confusion matrix in Figure 6.1 shows that the model achieved zero false positives (FP = 0) and only two false negatives (FN = 2), corresponding to a specificity of 100% and a safety-critical recall of 96.0%.





Figure 6.1: Normalised confusion matrix for the AudioThreatNet binary classifier on the 100-sample balanced test set.

To contextualise AudioThreatNet's performance, a comparative benchmark was conducted

against four baseline architectures commonly used in audio classification tasks. Figure 6.2 reports the accuracy, recall, F1-score, and mean inference latency.





Figure 6.2: Multi-metric benchmark comparison and validation loss vs. inference latency across evaluated architectures.

## 6.2 Product and technical results

AudioThreatNet achieves a 16 percentage-point improvement in accuracy over the closest baseline (1D-CNN) with a model inference latency of 28.2 ms. Factoring in network transit and Supabase CDC dispatch, the total measured end-to-end latency reliably hit 195.4 ms, successfully remaining well below the 200 ms threshold target.

## 6.3 User or stakeholder validation

When the AudioThreatNet classifier predicts a threat but the biometric module simultaneously confirms an authorised caregiver via Cosine Distance, the alert is **suppressed**. Table 6.1 documents empirical validation of this mechanism.

Table 6.1: Scenario-Based Validation of the Anti-Fatigue Suppressor Override Mechanism (four test cases).

| Test ID | Acoustic Scenario | dB | Raw Model | $P$(Threat) | Caregiver | Final Decision | System Action |
|---|---|---|---|---|---|---|---|
| TC-AF-01 | Loud TV Broadcast | 89.4 | Class 1 | 0.88 | True | **Safe** | Suppressed |
| TC-AF-02 | Parent Shouting | 85.2 | Class 1 | 0.92 | True | **Safe** | Suppressed |
| TC-AF-03 | Child Crying | 52.4 | Class 1 | 0.96 | False | **Threat** | Alert Triggered |
| TC-AF-04 | Vacuum + Parent | 81.8 | Class 1 | 0.79 | True | **Safe** | Suppressed |

## 6.4 Integration results

The real-time WebSocket push notifications successfully triggered the React Native full-screen Emergency Modal across 100% of the simulated integration test scenarios without dropping packets, suggesting the resilience of the Supabase CDC integration.

## 6.5 Summary of findings

The results suggest that a dual-stage edge-AI architecture, combining a 1D-CNN+LSTM classifier with deterministic biometric gating, can reduce false alarms on the tested scenarios while maintaining a 96.0% safety-critical recall rate.

# Chapter 7

# DISCUSSION

## 7.1 Interpretation of findings

An ablation study was conducted to quantify the individual contribution of each pipeline module. Figure 7.1 reports the results. The addition of Delta and Delta-Delta coefficients (40 → 120 channels) provided a 9.5% accuracy improvement over the base CNN, suggesting that dynamic spectral features help separate distress screams from merely loud sounds. Integrating the LSTM and 64-D biometrics reduced the false-alarm rate to 0.0% on the test set.





Figure 7.1: Ablation study showing incremental accuracy gains and false-alarm suppression across acoustic pipeline modules.

## 7.2 Comparison with literature baselines and existing solutions

Unlike the generic RF monitors critiqued in Chapter 2, which alert on every sound above a fixed threshold (e.g., 80 dB), the Audio Guardian uses learned spectral features to identify loud but safe sounds (e.g., action movies or vacuum cleaners) and suppress them.

## 7.3 Research contribution

The primary technical contribution is a 120-channel multi-spectral extraction pipeline designed to run on a $15 ESP32-S3 microcontroller, demonstrating the feasibility of localizing DSP workloads to preserve privacy.

## 7.4 Product contribution

The commercial deliverable is a functional, cross-platform mobile application with a fallback database architecture, intended to keep critical alert history accessible to parents even during localized server outages.

## 7.5 Limitations and threats to validity

Notwithstanding the strong empirical results obtained during testing, several operational constraints must be formally acknowledged:

- **Acoustic Domain Transfer Gap:** The recurrent distress classifier was trained primarily on RAVDESS, comprising adult professional actors vocalizing simulated fear and anger. Adult vocal-tract dimensions produce fundamental frequencies that diverge from infant cry bio-acoustics.
- **Hardware Power Constraints:** Sustaining high-frequency I2S Direct Memory Access (DMA) and active Wi-Fi transmission on the ESP32-S3 rapidly depletes portable lithium-polymer cells, restricting the edge device to a continuous tethered wall-power supply.

- **Evaluation Scale:** Results come from a small held-out test set and four scenario tests; no field trials in real households or with real child vocalizations were performed.
- **Microphone Acoustic Clipping:** In extreme acoustic regimes (e.g., dropped objects near the capsule), the sensor undergoes hardware-level waveform clipping, distorting spectral filterbank energies.

## 7.6 Implications

The findings suggest that sending only compact feature representations, rather than raw audio, can still support accurate classification, reducing the need for raw household audio to leave the home.

# Chapter 8

# COMMERCIALISATION AND SUSTAINABILITY

## 8.1 Value proposition and target users

The rapid expansion of the smart nursery and domestic Internet of Things (IoT) markets has generated substantial commercial demand for automated child monitoring technologies. However, modern commercial offerings present a tension: they compel parents to trade family privacy for domestic safety. The *Audio Guardian* addresses this gap by establishing a specialized value proposition: non-line-of-sight acoustic distress detection built on a privacy-by-design approach.

The primary target consumer segment comprises dual-income working parents, single guardians, and domestic caregivers of children aged 4 to 8 years. A secondary target market encompasses early childhood education institutions, including private preschools, daycares, and pediatric clinics.

For these target user groups, the value proposition is defined across three fundamental pillars: Guaranteed Domestic Privacy (Privacy-by-Design), Reduction of Caregiver Alert Fatigue, and Affordability for Emerging Markets.

## 8.2 Market and competitive position

The global baby monitor and smart nursery market is split between high-cost, privacy-invasive cloud cameras and low-cost, functionally primitive analog monitors. A strategic analysis of

competitive offerings highlights the unique market positioning of the Audio Guardian, as summarized in Table 8.1.

Table 8.1: Competitive positioning of Audio Guardian against commercial monitoring paradigms.

| **Feature / Dimension** | **Commercial Smart Cameras (e.g., Nanit, Owlet, Nest)** | **Conventional RF Monitors (e.g., Motorola, VTech)** | **Audio Guardian (Proposed Solution)** |
|---|---|---|---|
| **Retail Price (USD)** | $150 – $350+ | $30 – $60 | **$25 – $35 (BOM: ≈$15)** |
| **Sensing Modality** | Continuous Video / Audio | Analog / Digital Audio | **Non-Line-of-Sight Edge Bio-Acoustics** |
| **Privacy Preservation** | Varies (cloud video/audio streaming is common) | Moderate (Unencrypted local RF interception risk) | **High (no raw audio in the monitoring path; MFCC tensors transmitted)** |
| **Alert Mechanism** | Proprietary motion/sound/vitals alerts (varies by product) | Basic sound level LED meters | **Dual-Stage (1D-CNN+LSTM + Biometric Voice Gate)** |
| **False-Alarm Mitigation** | Not reported | None (Triggered by all sounds) | **Reduced (0.0% on the test set with caregiver voice filtering)** |
| **Bandwidth Overhead** | High (2.0 – 4.0 Mbps continuous) | N/A (Dedicated RF band) | **Ultra-Low (≈ 192 kbps intermittent metadata)** |

By re-engineering the digital signal processing pipeline to execute on the dual-core 240 MHz Xtensa LX7 architecture of the ESP32-S3, the total unit hardware BOM was compressed to approximately $15 USD. This reduction in production cost relative to camera-based monitors enables a projected retail price point of $25 to $35 USD, making it a mass-market safety device.

## 8.3 Business or sustainability model

To guarantee long-term commercial viability, a hybrid business model is established:

1. **Tier 1: Base Consumer Hardware Purchase (One-Time Fee):** The direct sale of the standalone Audio Guardian sensor node at an accessible consumer price point ($29.99 USD retail).

2. **Tier 2: Premium Caregiver Cloud Subscription (Recurring SaaS):** An optional premium service tier ($3.99 USD/month) unlocking multi-room synchronized monitoring, longitudinal acoustic health analytics, and Legal RAG advisory.

3. **Tier 3: Institutional B2B Enterprise Licensing (HaaS):** For daycares and preschools, offered under a Hardware-as-a-Service model ($15.00 USD/room/month).

## 8.4 Scalability intellectual property and compliance

Because raw digital audio is compressed into compact 120-channel MFCC matrices on the microcontroller prior to transmission, network bandwidth requirements are expected to drop from approximately 256 kbps (16 kHz, 16-bit mono) to roughly $\approx$ 192 kbps for the intermittent transmission of float32 array metadata. A standard domestic 2.4 GHz Wi-Fi router can reasonably host an array of 5 to 10 Audio Guardian nodes.

Under the European Union General Data Protection Regulation (GDPR), the Audio Guardian implements *Privacy-by-Design* (Article 25) and *Data Minimisation* (Article 5(1)(c)). Because raw PCM audio is flushed from volatile memory after feature extraction, the monitoring path is designed to reduce wiretap risk and to support GDPR alignment. A formal legal compliance review is left to future work.

## 8.5 Contribution to the Sustainable Development Goals

The commercial deployment of the Audio Guardian directly contributes to the United Nations Sustainable Development Goals (UN SDGs):

- **UN SDG 16: Peace, Justice, and Strong Institutions (Target 16.2):** Explicitly mandates the international community to *''End abuse, exploitation, trafficking and all forms of violence against and torture of children.''*
- **UN SDG 3: Good Health and Well-being (Target 3.4):** By eliminating the false-alarm epidemic that plagues commercial monitors, the Audio Guardian may help reduce parental stress, anxiety, and sleep fragmentation induced by alert fatigue.

# Chapter 9

# CONCLUSION AND FUTURE DIRECTIONS

## 9.1 Conclusion

The ‘‘Audio Guardian’’ component was developed and validated as an edge-native, privacy-preserving acoustic distress monitoring system. A primary milestone of this work was the successful implementation of an asymmetric Hybrid-Edge computing architecture utilizing an ultra-low-cost ($15 USD) Espressif ESP32-S3 microcontroller, indicating that semantic acoustic monitoring is feasible within domestic environments.

## 9.2 Achievement of objectives

The project successfully deployed a localized DSP pipeline on the ESP32-S3 to compute 120-channel multi-spectral representations. It formulated a hybrid 1D-CNN+LSTM sequence classification architecture that discriminates pediatric distress screams from domestic transients, and built a text-independent biometric voice gate that suppressed false alarms in the tested scenarios.

## 9.3 Individual research and product contributions

Rigorous empirical evaluation confirmed that the integrated dual-stage classification and suppression pipeline achieved a 98.0% overall classification accuracy, a 96.0% sensitivity (recall)

on critical acoustic distress events, and a 0.0% false-alarm rate under calibrated evaluation conditions.

## 9.4 Future directions

To address current constraints and advance the Audio Guardian toward clinical and commercial deployment, the following enhancements are proposed:

- **Architectural Evolution (ECAPA-TDNN):** Integration of an edge-tailored Emphasized Channel Attention, Propagation, and Aggregation Time Delay Neural Network (ECAPA-TDNN) to enable full temporal parallelization and static INT8 Post-Training Quantization.
- **Pediatric Dataset Expansion:** Fine-tuning the feature extractor on authentic neonatal distress recordings (e.g., Baby Chillanto datasets) to capture non-linear vocal phenomena characteristic of infant distress.
- **Ultra-Low-Power Wake-on-Sound:** Offloading acoustic surveillance to the ESP32-S3's internal Ultra-Low-Power (ULP) RISC-V co-processor to facilitate multi-month wire-free battery operation.
- **Smart Home Protocol Integration:** Operating over the local Matter-over-Thread mesh standard to dispatch autonomous ambient responses (e.g., illuminating nursery lighting in red alert modes) without active internet connectivity.

# REFERENCES

# Bibliography


[1] B. Kitchenham *et al.*, ‘‘Guidelines for performing Systematic Literature Reviews in Software Engineering,’’ *EBSE Technical Report*, 2007.

[2] M. J. Page *et al.*, ‘‘The PRISMA 2020 statement: an updated guideline for reporting systematic reviews,’’ *BMJ*, vol. 372, n71, 2021.

[3] G. Fant, *Acoustic Theory of Speech Production*. The Hague, Netherlands: Mouton & Co., 1960.

[4] W. T. Fitch *et al.*, ‘‘Production of vocalizations in mammals,’’ in *Acoustic Communication*, Springer, pp. 221–260, 2002.

[5] S. J. Sheinkopf *et al.*, ‘‘Acoustic properties of infant cries,’’ *Journal of Autism and Developmental Disorders*, vol. 42, no. 3, pp. 431–438, 2012.

[6] I. Wilden *et al.*, ‘‘Subharmonics, biphonation, and deterministic chaos in mammal vocalization,’’ *Bioacoustics*, vol. 9, no. 3, pp. 171–196, 1998.

[7] L. H. Arnal *et al.*, ‘‘Human screams occupy a privileged niche in the communication acoustic space,’’ *Current Biology*, vol. 25, no. 15, pp. 2051–2056, 2015.

[8] S. Davis and P. Mermelstein, ‘‘Comparison of parametric representations for monosyllabic word recognition,’’ *IEEE Transactions on Acoustics, Speech, and Signal Processing*, vol. 28, no. 4, pp. 357–366, 1980.

[9] A. V. Oppenheim and R. W. Schafer, *Discrete-Time Signal Processing*. 3rd ed., Pearson, 2010.

[10] A. Almaini, J. Folz, and G. Ashour, ‘‘TinyML for acoustic anomaly detection in IoT sensor networks,’’ in *Proc. 5th Int. Conf. Electr., Comput., Commun. Mechatronics Eng. (ICECCME)*, Zanzibar, Tanzania, 2025, pp. 1–5.

[11] M. Neri, F. Battisti, A. Neri, and M. Carli, ‘‘Sound event detection for human safety and security in noisy environments,’’ *IEEE Access*, vol. 10, pp. 132454–132468, 2022.

[12] A. McCofie *et al.*, ‘‘A review of deep learning model approach for pain assessment in infant cry sounds,’’ *Mach. Learn. Knowl. Extr.*, vol. 8, no. 3, p. 76, 2026.

[13] L. R. Rabiner and B. H. Juang, *Fundamentals of Speech Recognition*. Englewood Cliffs, NJ, USA: Prentice-Hall, 1993.

[14] InvenSense, ‘‘INMP441 Omnidirectional Microphone with Bottom Port and I2S Digital Output,’’ *Datasheet*, San Jose, CA, USA, 2014.

[15] X. Zhou *et al.*, ‘‘Linear versus mel frequency cepstral coefficients for speaker recognition,’’ in *Proc. IEEE Autom. Speech Recognit. Underst. Workshop (ASRU)*, 2011, pp. 559–564.

[16] L. Lin, X. Chen, and L. Zhang, ‘‘Towards automatic depression detection: A BILSTM/1D-CNN-based model,’’ *Appl. Sci.*, vol. 10, no. 23, p. 8701, 2020.

[17] M. Song and Z. Yang, ‘‘Performance improvement of speech emotion recognition systems by combining 1D CNN and LSTM with data augmentation,’’ *Electronics*, vol. 12, no. 11, p. 2436, 2023.

[18] D. Snyder *et al.*, ‘‘X-vectors: Robust DNN embeddings for speaker recognition,’’ in *Proc. IEEE Int. Conf. Acoust., Speech Signal Process. (ICASSP)*, 2018, pp. 5329–5333.

[19] V. Jüttner, C. S. Löffler, and E. Buchmann, ‘‘Actionable cybersecurity notifications for smart homes: A user study on the role of length and complexity,’’ *arXiv preprint arXiv:2510.21508*, 2025.

[20] S. Hershey *et al.*, ‘‘CNN architectures for large-scale audio classification,’’ in *2017 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pp. 131–135, 2017.

[21] C. Ji *et al.*, ‘‘A Deep Learning Approach for Infant Cry Classification,’’ *IEEE Access*, vol. 9, pp. 11444–11452, 2021.

[22] S. Hochreiter and J. Schmidhuber, ‘‘Long short-term memory,’’ *Neural Computation*, vol. 9, no. 8, pp. 1735–1780, 1997.

[23] E. Cakir *et al.*, ''Convolutional recurrent neural networks for polyphonic sound event detection,'' *IEEE/ACM Transactions on Audio, Speech, and Language Processing*, vol. 25, no. 6, pp. 1291–1303, 2017.

[24] M. Reyes *et al.*, ''Baby Chillanto: A database of infant cries,'' in *Proceedings of ICASSP*, 2008.

[25] Ubenwa, ''Donate-a-Cry Corpus,'' *Public Dataset*, 2015. [Online].

[26] M. Asplund *et al.*, ''Security and privacy in consumer IoT: A systematic literature review,'' *IEEE Access*, vol. 8, pp. 82183–82200, 2020.

[27] S. Sendelbach and M. Funk, ''Alarm fatigue: A patient safety concern,'' *AACN Advanced Critical Care*, vol. 24, no. 4, pp. 378–386, 2013.

[28] O. Alrawi *et al.*, ''SoK: Security evaluation of home-based IoT deployments,'' in *IEEE Symposium on Security and Privacy*, pp. 1362–1380, 2019.

[29] P. Voigt and A. Von dem Bussche, *The EU General Data Protection Regulation (GDPR): A Practical Guide*. 1st ed., Springer, 2017.

[30] K. Peffers *et al.*, ''A design science research methodology for information systems research,'' *Journal of Management Information Systems*, vol. 24, no. 3, pp. 45–77, 2007.

[31] S. R. Livingstone and F. A. Russo, ''The Ryerson Audio-Visual Database of Emotional Speech and Song (RAVDESS),'' *PLoS ONE*, vol. 13, no. 5, e0196391, 2018.

[32] K. J. Piczak, ''ESC: Dataset for Environmental Sound Classification,'' in *Proceedings of the 23rd ACM international conference on Multimedia*, pp. 1015–1018, 2015.

[33] D. S. Park *et al.*, ''SpecAugment: A simple data augmentation method for automatic speech recognition,'' in *Interspeech*, 2019.

[34] Q. McNemar, ''Note on the sampling error of the difference between correlated proportions or percentages,'' *Psychometrika*, vol. 12, no. 2, pp. 153–157, 1947.

[35] T. L. Nwe, S. W. Foo, and L. C. De Silva, ''Speech emotion recognition using hidden Markov models,'' *Speech Communication*, vol. 41, no. 4, pp. 603–623, 2003.

[36] B. Schuller *et al.*, ‘‘Recognising realistic emotions and affect in speech: State of the art and lessons learnt from the first challenge,’’ *Speech Communication*, vol. 53, no. 9–10, pp. 1062–1087, 2011.

[37] I. R. Titze, *Principles of Voice Production*. Iowa City, IA, USA: National Center for Voice and Speech, 2000.

[38] A. Mesaros *et al.*, ‘‘Detection and classification of acoustic scenes and events: Outcome of the DCASE 2016 challenge,’’ *IEEE/ACM Trans. Audio, Speech, Lang. Process.*, vol. 26, no. 2, pp. 379–393, 2018.

[39] E. Fernandes, J. Jung, and A. Prakash, ‘‘Security analysis of emerging smart home applications,’’ in *Proc. IEEE Symp. Security and Privacy*, 2016, pp. 636–654.

[40] A. R. Hevner, S. T. March, J. Park, and S. Ram, ‘‘Design science in information systems research,’’ *MIS Quarterly*, vol. 28, no. 1, pp. 75–105, 2004.

# GLOSSARY

- **Acoustic Texture:** The complex, non-linear physical characteristics of a sound wave (e.g., chaos, roughness) independent of its raw volume.
- **Alert Fatigue:** The psychological desensitization of caregivers due to constant false-positive notifications from monitoring devices.
- **Dysphonia:** An abnormal acoustic quality of voice, commonly exhibited during intense physical distress or pain screaming.
- **Edge Computing:** Processing data natively on a local hardware device (e.g., an ESP32 microcontroller) rather than transmitting it to centralized cloud servers.
- **Hybrid-Edge Architecture:** A system design where lightweight data extraction (DSP) occurs on local hardware, while heavy algorithmic inference (Deep Learning) occurs on a secure local or proximal server.
- **Intensity Bias:** A critical flaw in legacy baby monitors where devices trigger alerts based solely on the raw decibel volume of an acoustic event, ignoring semantic context.

# APPENDICES

## Appendix A Research instruments or extended results

[Replace the title and content as appropriate]

## Appendix B Academic integrity and AI use disclosure

[List the tools used, purpose, representative prompts or workflows where required, verification performed, and sections or artefacts affected, in accordance with module policy.]