

The cooking-units package*

Ben Vitecek
b.vitecek@gmx.at

October 23, 2017

Abstract

This package enables user to globally format units, to switch between them and since v1.10 you can also change your recipes for a given number of persons. It should be used for light-hearted things like cookery books (and not e.g. scientific texts).¹ Please read through the section “Important Changes”

Contents

1	Introduction	2
1.1	Important Changes	2
1.2	Supported languages	3
2	The Commands	3
3	Label & refs: Changing the amount of the recipe	6
4	Some Interesting options	7
5	Predefined units & some notes	8
6	Defining units	8
7	Defining options to change units	9
8	Language support	13
8.1	Phrases	15

*This document corresponds to Benedikt Vitecek v1.20, dated 2017/10/23.

¹I did hide some grammatical and spelling errors for easter egg hunters ☺.

9	Options	16
9.1	Load time options	17
9.2	Normal options	17
9.2.1	Unit Specific options	17
9.2.2	Command behavior	18
9.2.3	Input and Outputs	19
9.2.4	Rounding options	23
9.2.5	Fractions	25
9.2.6	Spaces	26
9.2.7	label & refs	28
9.3	Weird options	30
10	Bugs & Feedback	32
A	Translations	33
A.1	English	34
A.2	american	35
A.3	German	36
A.4	French	38
	Change History	39
	Index	40

1 Introduction

While writing on a cookery book I used – for reasons whatsoever – three different units for weight: kilogram (kg), gram (g) and decagram (dag, or older: dkg). Later my mother told me that she doesn’t like it if a cookery book uses more than two different units (for weight in this case). Happily I hardly used Decagram and therefore didn’t have many problems changing the units. But, well ... I am using \LaTeX and changing those units by hand seemed not very \LaTeX like, so I started writing some code to convert units. I expanded the code, rewrote it in $\text{\LaTeX}3$ (which is much more pleasant than $\text{\LaTeX}2_{\epsilon}$) and here it is.

1.1 Important Changes

Language I am now using the `translations` package and I hope it makes things easier. As such, declaring the used language through class options shouldn’t be necessary anymore.

Phrases This package now supports the usage of “phrases” (words used instead of certain integers) (which I think are called “counting measures” in english, but I am not sure).

`\cutext` and `\Cutext` If no translation is found for a specific language, `\cutext` and `\Cutext` are replaced by `\cunum` with a warning is given.

Commands Currently, it seems that allowing $\langle label \rangle$ to be set by arrow-brackets was not the best idea as it leads to problems if they are made active (e.g. `babel` and option `spanish`). As such, `<` is not allowed as a “special-sign” anymore as this package tries to “fix” this idea (at least make it work). If any problems occur (for this specific case or in general) please feel free to contact me.

1.2 Supported languages

- German
- English
- French (currently suboptimal²)

Have another language to add or a correction of an existing one? See section 10 for more details. Wanna just check the existing translations? See appendix A.

2 The Commands

This package offers the following commands for unit printing (and converting):

- `\cunum` $\langle label \rangle$ [$\langle options \rangle$] { $\langle amount \rangle$ } [$\langle space \rangle$] { $\langle unit-key \rangle$ }
- `\cutext` $\langle label \rangle$ [$\langle options \rangle$] { $\langle amount \rangle$ } { $\langle unit-key \rangle$ }
- `\Cutext` $\langle label \rangle$ [$\langle options \rangle$] { $\langle amount \rangle$ } { $\langle unit-key \rangle$ }
- `\cuam` $\langle label \rangle$ [$\langle options \rangle$] { $\langle amount \rangle$ }
- `\cusetup`{ $\langle options \rangle$ }

Numbers and units are printed using `\cunum`. The numerical part can interpret `_` and `/` as (mixed) fractions and `--` as a separator for ranges; to convert units use the option $\langle old-unit \rangle = \langle new-unit \rangle$ ³. It furthermore allows the sign `?` to be used as a placeholder for not known amounts and raises a warning to remind that this amount needs a check-up⁴. [$\langle space \rangle$] adds a space between the number and the unit using `\phantom`.

For a list of predefined units have a look at table 1.

$\langle label \rangle$ is explained in section 3.

²You can only get limited information from the internet.

³New keys can be added and defined, see section 5 and section 6 for further information.

⁴You can customize this behavior, see section 9

1 kg	<code>\cunum{1}{kg}\</code>
2.3 kg	<code>\cunum{2.3}{kg}\</code>
2.3 kg	<code>\cunum{2,3}{kg}\</code>
2–3 kg	<code>\cunum{2--3}{kg}\</code>
2.5–3.5 kg	<code>\cunum{2.5--3.5}{kg}\</code>
2500–3500 g	<code>\cunum[kg=g]{2.5--3.5}{kg}\</code>
392 °F	<code>\cunum[C=F]{200}{C}\</code>
356–392 °F	<code>\cunum[C=F]{180--200}{C}\</code>
$\frac{1}{2}$ m	<code>\cunum{1/2}{m}\</code>
1 $\frac{1}{2}$ m	<code>\cunum{1_1/2}{m}\</code>
1 $\frac{1}{2}$ m	<code>\cunum[m=cm]{1_1/2}{m}\</code>
? ℓ	<code>\cunum{?}{l}\</code>
50 dag	<code>\cunum{50}{dag}\</code>
5 dag	<code>\cunum{5}[0]{dag}\</code>
1.12 m	<code>\cunum{1.1234}{m}</code>

Decimal numbers are automatically rounded to 2 digits after the colon, temperatures (C, F, K and Re) are automatically rounded to integers.⁵

`\cutext` and `\Cutext` print the number and the written name of the unit. Since v1.10 it works similar⁶ to `\cunum`: it allows the conversion between units and interprets the numerical part (again `_` and `/` are used for (mixed) fractions and `--` for ranges). Furthermore, if the package option `use-numerals` is used, integers below a specific integer (by default 13; see `use-numerals-below`) are written out with `\Cutext` capitalizing the first letter (using package `fmtcount`).

1 litre	<code>\cutext{1}{l}\</code>
1 litre	<code>\Cutext{1}{l}\</code>
1–2 litres	<code>\Cutext{1--2}{l}\</code>
12 litres	<code>\cutext{12}{l}\</code>
13 litres	<code>\Cutext{13}{l}</code>

and using package option `use-numerals=true`

one litre	<code>\cutext{1}{l}\</code>
One litre	<code>\Cutext{1}{l}\</code>
one–two litres	<code>\cutext{1--2}{l}\</code>
twelve litres	<code>\cutext{12}{l}\</code>
13 litres	<code>\Cutext{13}{l}</code>

Furthermore, since v1.10 `\cutext` and `\Cutext` also allow their units to be changed (this behavior can be altered using `cutext-change-unit`):

	<code>\cusetup{l=ml}</code>
1000 millilitres	<code>\cutext{1}{l}\</code>
1000 millilitres	<code>\Cutext{1}{l}\</code>
1000–2000 millilitres	<code>\cutext{1--2}{l}\</code>
12000 millilitres	<code>\cutext{12}{l}\</code>
13000 millilitres	<code>\Cutext{13}{l}\</code>
? litres	<code>\Cutext{?}{l}\</code>
$\frac{1}{2}$ litres	<code>\Cutext{1/2}{l}\</code>

⁵You can – of course – change this behavior, see section 9.

⁶One could also say “exactly like”.

`\cuam` works like `\cunum`, but without a unit, so changing units doesn't affect it. Like `\cunum _` and `/` are used to imply a (mixed) fraction and `--` is used for ranges.

3	<code>\cuam{3}\</code>
2–3	<code>\cuam{2--3}\</code>
$\frac{2}{3}$	<code>\cuam{2/3}\</code>
$1\frac{2}{3}$	<code>\cuam{1_2/3}</code>

Furthermore it allows the concept of “phrases” (replacing a positive integer by a word, such as “12” becoming “dozen”⁷) which can be activated by the option `use-phrases` (as I don't know any english phrases, I switched the language to german for the following examples)

	<code>\cusetup{use-phrases=true}</code>
1 Dutzend	<code>\cuam{12}\</code>
13	<code>\cuam{13}\</code>
2 Dutzend	<code>\cuam{24}\</code>
1–2 Dutzend	<code>\cuam{12--24}\</code>
12–13	<code>\cuam{12--13}\</code>
18	<code>\cuam{18}\</code>
5 Dutzend	<code>\cuam{60}</code>

3 Label & refs: Changing the amount of the recipe

What if you don't want to change units, but the amounts of the recipe because you cook not for 4 persons, but for 2 and don't like to do the math? Simple, use the following commands:

- `\culabel{<label>}{<number of persons>}`
- `\curef{<label>}`

The first one is the important one: It defines a `<label>` for a recipe which is initially for `<number of persons>`. Afterwards `<label>` can be used to tell the commands from section 2 that the given amounts are for `<number of persons>`. Each `<label>` must be unique and an error is raised if a `<label>` is already defined.

If you would like to print the number of persons this recipe is for, use `\curef`, which is fully expandable.

The following example uses `\culabel` to specify that the recipe is initially intended for 2 persons:

	<code>\culabel{recipe}{2}</code>
recipe for 2 persons:	<code>recipe for \curef{recipe} persons:\</code>
10–20 dag flour,	<code>\cunum<recipe>{10--20}{dag} flour,\</code>
$\frac{1}{2}$ ℓ water,	<code>\cunum<recipe>{1/2}{l} water,\</code>
10 gramme nuts,	<code>\cutext[ref=recipe]{10}{g} nuts,\</code>
2–3 eggs,	<code>\cuam<recipe>{2--3} eggs,\</code>
180 °C (356 °F) open fire	<code>\cunum{180}{C} (\cunum[C=F]{180}{C})</code>
	<code>open fire</code>

Now with combination of the option `set-number-of-persons` and setting `recalculate-amount` to `true` you can have this recipe changed to four persons:

⁷At least I think

```

\culabel{recipe}{2}
%% adding options:
\cusetup{set-number-of-persons=4,recalculate-amount=true}

recipe for 4 persons:
20–40 dag flour,
1 ℓ water,
20 gramme nuts,
4–6 eggs,
180 °C (356 °F) open fire

recipe for \curef{recipe} persons:\\
\cunum<recipe>{10--20}{dag} flour,\\
\cunum<recipe>{1/2}{1} water,\\
\cutext[ref=recipe]{10}{g} nuts,\\
\cuam<recipe>{2--3} eggs,\\
\cunum{180}{C}
(\cunum[C=F]{180}{C}) open fire

```

Note that fractions are automatically evaluated and that only values with a *<label>* are changed (`\cunum{180}{C}` for example stays the same which also makes sense as the heat should be the same).

4 Some Interesting options

This package has some options which might be of interest and to highlight them, this section exists. All options can be found in section 9.

`use-numerals` As seen above, you can use the *package*-option `use-numerals` to print integers used by `\cutext` and `\Cutext` below `use-numerals-below` (13 by default) by `fmtcount`. You can still decide if numerals should be printed or not with `print-numerals`.

Note: `use-numerals` is a package option as it needs to load `fmtcount` which is not loaded by default.

`use-phrases` In (I presume) all languages there exist phrases for a given amount or a number of things (think it is called “counting measurement”). In German you may say instead of “12”: “ein Dutzend”. Using this option you can tell this package to replace predefined integers used in `\cuam` by phrases for the currently used language (to define new ones, see section 8.1)

Using (for example) language `ngerman` (or `naustrian`, etc.) with package option `use-phrases=true` gives:

```

\cusetup{use-phrases=true}
1 Dutzend \cuam{12}\\
2 Dutzend \cuam{24}\\
1–2 Dutzend \cuam{12--24}\\
12–13 \cuam{12--13}\\
18 \cuam{18}\\
5 Dutzend \cuam{60}

```

This of course also works with the *package*-option `use-numerals`:

```

\cusetup{use-phrases=true}
ein Dutzend \cuam{12}\\
zwei Dutzend \cuam{24}\\
ein–zwei Dutzend \cuam{12--24}\\
12–13 \cuam{12--13}\\
18 \cuam{18}\\
fünf Dutzend \cuam{60}

```

Note: Currently only the lower-case variant for `use-numerals` is supported. Furthermore this feature is only available for `\cuam`.

5 Predefined units & some notes

In table 1 and you can find all predefined units which can be transformed into each other (sorted by group). Other predefined units (which cannot be used for transformation) are shown in table 2. Table 3 pretty much exists just for fun.

Table 1: This table shows all units which can be transformed into each other, sorted by group. The columns “default” show the abbreviations used if for given language no translation is defined. The translations used for `\cutext` and `\Cutext` are shown in appendix A. Note that “electron volt” exists just for fun.

description	key	default	description	key	default
kilogramme	kg	kg	metre	m	m
decagramme	dag	dag	decimetre	dm	dm
gramme	g	g	centimetre	cm	cm
ounce	oz	oz	millimetre	mm	mm
pound	lb	lb	inch	in	in
stick (of butter)	stick	stick			
day	d	d	litre	l	l
hour	h	h	decilitre	dl	dl
minute	min	min	centilitre	cl	cl
second	s	s	millilitre	ml	ml
calorie	cal	cal	degree Celsius	C	°C
kilocalorie	kcal	kcal	degree Fahrenheit	F	°F
joule	J	J	degree Réaumur	Re	°Ré
kilojoule	kJ	kJ	kelvin	K	K
electron volt	eV	eV			

6 Defining units

New units can be defined using `\declarecookingunit`, `\newcookingunit` and `\providecookingunit`:

Table 2: A (not only) spoonful of (more or less) country and language dependent units. Please note that sometimes a translation is nearly impossible as a unit (e.g. “saltspoonful”) may not exist in another language (like german; at least I never heard of it). So please only use units known to you.

description	key	symbol
pinch	pn	pinch
tablespoon	EL	EL
teaspoon	TL	TL
dessertspoonful	dsp	dsp.
coffeespoonful	csp	csp.
saltspoonful	ssp	ssp.
Messerpsitze (point of a knife)	Msp	Msp.

Table 3: List of (not really) nonsense units (exist just for fun, there will be no support for those units; unless – of course – you really want it).

unit-key	symbol
eVc-2	eV/c^2
hbareV-1	\hbar/eV
chbareV-1	ch/eV
(chbareV-1)3	$c^3\hbar^3/eV^3$

\declarecookingunit	\declarecookingunit[\symbol]{\unit-key}
\newcookingunit	\newcookingunit[\symbol]{\new-unit-key}
\providecookingunit	\providecookingunit[\symbol]{\new-unit-key}

These commands define the unit $\langle unit-key \rangle$. If the key is not the same as the printed symbol use $[\langle symbol \rangle]$. Note that $\langle unit-key \rangle$ should neither contain / nor ,.

`\newcookingunit` raises an error if the unit is already defined, `\declarecookingunit` creates or (if given) overwrites $\langle symbol \rangle$ and `\providecookingunit` does nothing if the unit is already defined.

All units have male gender m by default.

Some examples:

```

\declarecookingunit{kg}
\declarecookingunit{g}
\declarecookingunit[Msp.] {Msp}
\declarecookingunit[\ensuremath{\{\}^{\circ}}\kern-\scriptspace C] {C}

```

Note: The definition of the printed degree Celsius is directly copied and pasted from (a maybe older version of) siunitx

7 Defining options to change units

Options (to change units) can be newly defined or added to already existing keys (units) using

- `\cdefinekeys`
- `\cdefinesinglekey`
- `\cuaddkeys`
- `\cuaddsinglekeys`
- `\cuaddtokeys`

I apologize for the (name) inconsistency between `\cdefinekeys` and `\cdefinesinglekey` (although they are named similarly they work different).

<code>\cdefinekeys</code>	<code>\cdefinekeys{⟨unit-key-1⟩}</code>
<code>\cdefinesinglekey</code>	<pre> { {⟨unit-key-2⟩} {⟨1 unit-key-1 are ... unit-key-2⟩} {⟨unit-key-3⟩} {⟨1 unit-key-1 are ... unit-key-3⟩} {⟨unit-key-4⟩} {⟨1 unit-key-1 are ... unit-key-4⟩} ... } \cdefinesinglekey{⟨unit-key-1⟩} { {⟨unit-key-2⟩} {⟨1 unit-key-2 are ... unit-key-1⟩} {⟨unit-key-3⟩} {⟨1 unit-key-3 are ... unit-key-1⟩} ... } </pre>

If you define new units (see section 6) and cannot add them to already existing keys you can use `\cdefinekeys` bzw. `\cdefinesinglekey` to define new keys.

`\cdefinekeys` takes $\{⟨unit-key-1⟩\}$ as a “basis”, defines a key with the name $⟨unit-key-1⟩$ and adds the values $⟨unit-key-1⟩$, $⟨unit-key-2⟩$, $⟨unit-key-3⟩$, etc. Furthermore this command also defines the keys $⟨unit-key-2⟩$, $⟨unit-key-3⟩$, etc. with the same values as $⟨unit-key-1⟩$. Please note that $⟨...⟩$ has to be a number.

Sometimes it is not that easy and the conversion of one unit into another needs are more complicated formula (see for example temperatures). If that is the case use `\cdefinesinglekey`. As the name says it defines *only* the key $⟨unit-key-1⟩$ with the values $⟨unit-key-1⟩$, $⟨unit-key-2⟩$, etc. The advantage of this command is that now $⟨...⟩$ can be a formula and the numerical input can be placed explicitly using `#1`.

Example: This example defines following keys with their respective value:

- the key `kg` with the values `kg`, `dag`, `g` and `oz`
- the key `dag` with the values `kg`, `dag`, `g` and `oz`
- the key `g` with the values `kg`, `dag`, `g` and `oz`
- the key `oz` with the values `kg`, `dag`, `g` and `oz`
- the key `d` with the values `d`, `h`, `min` and `s`
- ...

1 kg = 1 kg	1 kg = 100 dag	1 kg = 1000 g
1 kg = 35.273 99 oz	1 kg = 2.204 622 6 lb	

```
\cdefinekeys {kg}
{
  {dag}{ 100 } %% 1 kg are 100 dag
  {g} { 1000 } %% 1 kg are 1000 g
  {oz} { 35.27399 } %% 1 kg are 35.27399 oz
  {lb} { 2.204 622 6 } %% 1 kg are 2.204 622 6 lb
}

\cdefinekeys {d}
{
  {h} { 24 } %% 1 day are 24 hours
  {min}{ 1440 } %% 1 day are 1440 minutes
  {s} { 86400 } %% 1 day are 86400 seconds
}
```

To convert degree Fahrenheit to degree Celsius, kelvin and degree Réamur one needs the formulas⁸

$$T_C = (T_F - 32) \cdot \frac{5}{9}$$

$$T_K = (T_F - 459.67) \cdot \frac{5}{9}$$

$$T_{Re} = (T_F - 32) \cdot \frac{4}{9}$$

with T_F being the input temperature in degree Fahrenheit and T_C being the same temperature in degree Celsius, etc. Using `\cdefinesinglekey` the key `F` with values `C`, `K` and `Re` is defined:

```
\cdefinesinglekey {F}
{
  {C} { ( #1 - 32 ) * 5/9 } %% see formulas above
  {K} { ( #1 + 459.67 ) * 5/9 }
  {Re} { ( #1 - 32 ) * 4/9 }
}
```

This defines the key `F` with the values `F`, `C`, `K` and `Re`.

⁸See Wikipedia.

```

\cuaddkeys      \cuaddkeys{\unit-key-1}
\cuaddsinglekeys {
    {\unit-key-2} {\langle 1 unit-key-1 are ... unit-key-2 \rangle}
    {\unit-key-3} {\langle 1 unit-key-1 are ... unit-key-3 \rangle}
    {\unit-key-4} {\langle 1 unit-key-1 are ... unit-key-4 \rangle}
    ...
}
\cuaddsinglekeys{\unit-key-1}
{
    {\unit-key-2} {\langle 1 unit-key-2 are ... unit-key-1 \rangle}
    {\unit-key-3} {\langle 1 unit-key-3 are ... unit-key-1 \rangle}
    ...
}

```

These commands add $\langle unit-key-2 \rangle$, etc. to the already defined key $\langle unit-key-1 \rangle$.

`\cuaddkeys` takes the already defined key $\{\langle unit-key-1 \rangle\}$ as a “basis”, and adds $\langle unit-key-2 \rangle$, $\langle unit-key-3 \rangle$, etc. to its values. Furthermore it adds those new values to other keys linked to $\langle unit-key-1 \rangle$ and defines the new keys $\langle unit-key-2 \rangle$, etc. with the same values as $\langle unit-key-1 \rangle$.

If the conversion is more complicated use `\cuaddsinglekeys`. It adds $\langle unit-key-2 \rangle$, etc. as values to $\langle unit-key-1 \rangle$. The numerical input can be placed using `#1` (see `\cundefinesinglekey`). This command neither defines new keys nor does it add values to other keys than $\langle unit-key-1 \rangle$.

Example: Suppose you are British (I am sorry, I can’t think of another reason to use those units) and you want to implement ‘stone’ (yes, I was surprised myself that such a unit exists, but it even appears in a Sherlock Holmes story). You exactly know that 1 st equals 14 lb, well ... now you have two choices. `\cuaddkeys` or `\cuaddtokeys` (use the one best fitting). This example uses the first, the next the latter one.

```

\newcookingunit{st} %% defining new unit 'stone'
\cuaddkeys{lb} %% adding st to lb (could also add to kg, dag and oz)
{
    {st} { 1/14 } %% 1 lb are 1/14 st as 14 lb are 1 st
}

```

0.07 st	<code>\cunum[lb=st]{1}{lb}\</code>
14 lb	<code>\cunum[st=lb]{1}{st}\</code>
6350.29 g	<code>\cunum[st=g]{1}{st}\</code>
6.35 kg	<code>\cunum[st=kg]{1}{st}\</code>
0.16 st	<code>\cunum[kg=st]{1}{kg}\</code>
101.6 kg	<code>\cunum[st=kg]{16}{st}</code>

Example: Now you want to add degree Rømer and convert Celsius to degree Rømer:

$$T_{Rø} = T_C * \frac{21}{40} + 7.5$$

```

%% defining new unit 'degree R{\o}mer'
\newcookingunit [\ensuremath{ {}^{\circ} } ]\kern-\scriptspace R{\o} {Ro}
\cuaddsinglekeys {C} %% adds value 'Ro' to 'C'.
{

```

```

{Ro} { #1 * 21/40 + 7.5 }
}
\cusetup %% round to integer automatically
{
  set-option-for-Ro = { round-to-int = true }
}

10 °C
13 °Rø

```

`\cunum{10}{C}\`
`\cunum[C=Ro]{10}{C}`

`\cuaddtokeys` `\cuaddtokeys {<unit-key-1>} {<unit-key-2>} {<1 unit-key-2 are ... unit-key-1>}`

Works similar to `\cuaddkeys` regarding the definition of keys.

Example: Continuing the example from before, this time with `\cuaddtokeys`:

```

\newcookingunit{st} %% defining (again) new unit 'stone'
\cuaddtokeys {lb} {st} { 14 } %% 1 st are 14 lb

0.07 st
14 lb
6350.29 g
6.35 kg
0.16 st
101.6 kg

```

`\cunum[lb=st]{1}{lb}\`
`\cunum[st=lb]{1}{st}\`
`\cunum[st=g]{1}{st}\`
`\cunum[st=kg]{1}{st}\`
`\cunum[kg=st]{1}{kg}\`
`\cunum[st=kg]{16}{st}`

8 Language support

Unit names and symbols depend on the language. To change the name depending on the language you can use `\cudefinename` and to only change symbols use `\cudefinesymbol`.

`decimal-mark`
`one(m)`
`one(f)`
`one(n)`

Those are special keys (as they cannot be used as units). Not only are printed units language depending, but as is the decimal mark (“.” or “,”). To set the decimal mark use `decimal-mark` (see examples below).

Furthermore if you are using the package-option `use-numerals` you may also use the keys `one(m)`, `one(f)` and `one(n)`. If you use this option, integers below a certain value (see option `use-numerals-below`) are written-out. The only problem is the written-out “1” mostly depends on the gender of the following word (e.g. “ein Baum” (m), “eine Pflanze” (f) and “ein Auto” (n)). To set the written-out 1 to be correct with the gender of the used unit, use these keys (see also examples below)

```
\cudefinename{\<Language>}
```

```
{
  {\<unit-key-1>} [\<symbol-1>] {\<singular-1>} [\<plural-1>] \<gender>
  {\<unit-key-2>} [\<symbol-2>] {\<singular-2>} [\<plural-2>] \<gender>
  ...
}
```

This command defines the names (and optionally the symbol) of the units printed in `\cutext` and `\Cutext` (and `\cunum` regarding the symbol) for the specific *\<Language>*. For details regarding *\<language>* see the [translations](#) documentation.

If the plural form of the name differs from the singular form use `[\<plural>]` to specify the plural form, if no `[\<plural>]` is given the plural will be set equal to its singular. The singular form is only used if the number in `\cutext` and `\Cutext` is equal to 1.

\<gender> can be `m` (maskulin), `f` (feminin) or `n` (neutrum). If not given `m` is used as default.

```
\cudefinename {English}
{
  {kg} {kilogramme}
  {oz} {ounce}
  {h} {hour} [hours]
  {C} {degree\space Celsius} [degrees\space Celsius]
  {decimal-marker} {..}
  {one(m)} {one}
  {one(f)} {one}
  {one(n)} {one}
}
```

```
\cudefinename {German}
{
  {kg} {Kilogramm} <n>
  {oz} {Unze} <f>
  {d} {Tag} [Tage]
  {h} {Stunde} [Stunden] <f>
  {C} {Grad\space Celsius}
  {decimal-marker} {,,}
  {one(m)} {ein}
  {one(f)} {eine}
  {one(n)} {ein}
}
```

```
\cudefinesymbol{\<Language>}
```

```
{
  {\<unit-key-1>} {\<symbol-1>}
  {\<unit-key-2>} {\<symbol-2>}
  ...
}
```

This command defines the symbols of the units printed in `\cunum` for the specific *\<language>*. It works similar as `\cudefinename`, but only the symbols (and no names) can be set. For details regarding *\<language>* see the [translations](#) documentation.

```
\cudefinesymbol {English}
```

```

{
  {decimal-mark} {.,}
  {one(m)} {one}
  {one(f)} {one}
  {one(n)} {one}
}
\cudefinesymbol {German}
{
  {decimal-mark} {.,}
  {one(m)} {ein}
  {one(f)} {eine}
  {one(n)} {ein}
}
\cudefinesymbol {French}
{
  {l} {L}
  {dl} {dL}
  {cl} {cL}
  {ml} {mL}
  {decimal-mark} {.,}
  {one(m)} {un}
  {one(f)} {une}
  {one(n)} {un}
}

```

Example: Imagine that instead of the abbreviation “dag” for “decagramme” you want to use “ducks” (because ... I don’t know). You can easily do this via

```

\cudefinesymbol {English}
{
  {dag} {ducks}
}

```

As you can see it may be a bit suboptimal as there is no plural version allowed. You do it anyway and end up with:

12 ducks weed	<code>\cunum{12}{dag} weed\\</code>
3 ducks nuts	<code>\cunum{3}{dag} nuts\\</code>
10 ducks duckmeat	<code>\cunum{10}{dag} duckmeat</code>

8.1 Phrases

Each language has synonyms for certain (integer) numbers. This package supports those phrases and they can be implemented with the following command and used by `\cuam`:

```
\cdefinephrase \cdefinesymbol{<Language>}
{
  {<integer-1>} {<phrase-1>} [<phrase-1-plural>] <gender-1>
  {<integer-2>} * {<phrase-2>} [<phrase-2-plural>] <gender-2>
  ...
}
```

This command pairs for a given $\{\langle Language \rangle\}$ the number $\{\langle integer-1 \rangle\}$ with $\{\langle phrase-1 \rangle\}$ (plural and gender). The package then checks if the amount given in `\cuam` is either this number or a *multiple* of it.

If the behavior of checking for a multiple is not wanted, you can use the optional star `*` for a given $\{\langle integer \rangle\}$

$\langle gender \rangle$ can be `m`, `f` or `n`. It is `m` by default.

Afterwards the numbers are ordered from highest to lowest so that the phrase with the highest number is used (if used at all).

Furthermore, it chooses star (`*`) phrases over non-star phrases.

Note: Numbers with the optional star `*` are stored as negative numbers.

Example: The following example creates some phrases for the language “German”:

```
\cdefinephrase {German}
{
  { 12 } {Dutzend} <n> %% implemented by default
  { 60 } {Schock} <n>
  { 6 } * {halbes\ Dutzend} <n>
}
```

Let’s just use them (activating the german language):

	<code>\cusetup{use-phrases=true}</code>
1 Dutzend	<code>\cuam{12}\\</code>
2 Dutzend	<code>\cuam{24}\\</code>
1 Schock	<code>\cuam{60}\\</code>
2 Schock	<code>\cuam{120}\\</code>
1 halbes Dutzend	<code>\cuam{6}\\</code>
18	<code>\cuam{18}</code>

As you can see, “Schock” (60) is preferred over “Dutzend” (12) as it linked to the higher number. Furthermore, for 6 the phrase “halbes Dutzend” (half a dozen) is used, but because it is a star version it is *not* used for 18.

9 Options

Options in `cooking-units` can mostly be set globally using `\cusetup` or locally using the optional argument of the respective command (but *not* as a package option). The only exception is the option given in section 9.1 which needs to be used as a package option.

9.1 Load time options

use-numerals `\usepackage[use-numerals=<true/false>]{cooking-units}`

If set to `true` loads package `fmtcount` and uses `\numberstringnum` for `\cutext` and `\Numberstringnum` for `\Cutext` to write-out numbers below `use-numerals-below` (13 by default), integers above are printed as numbers. You can decide to not print any numerals by setting `print-numerals` to `false`.

Note: `use-numerals` is a package option as it needs to load `fmtcount` which is not loaded by default.

Note: Please note the keys `one(m)`, `one(f)` and `one(n)` to change the printed “one” (as “one” is in many languages dependent on the gender of the following word. E.g in German: Masculine: ein Baum, Feminin: eine Pflanze, Neutrum: ein Auto).

one kilogramme	<code>\cutext{1}{kg}\</code>
One kilogramme	<code>\Cutext{1}{kg}\</code>
two kilogramme	<code>\cutext{2}{kg}\</code>
Two kilogramme	<code>\Cutext{2}{kg}\</code>
twelve kilogramme	<code>\cutext{12}{kg}\</code>
13 kilogramme	<code>\cutext{13}{kg}\</code>
13 kilogramme	<code>\cutext{13}{kg}\</code>
14 kilogramme	<code>\Cutext{14}{kg}</code>

9.2 Normal options

Options in this subsection can only be set as local options or using `\cusetup`, but *not* as load time options.

\cusetup Options can be set using `\cusetup{<options>}`.

9.2.1 Unit Specific options

unit `<unit-key-1> = <unit-key-2>`

Change unit `<unit-key-1>` to `<unit-key-2>` (see section 7 to define new options).

<code>set-option-for-<unit-key></code>	<code>set-option-for-<unit-key> = <key1=value1,...></code>
<code>add-option-for-<unit-key></code>	<code>add-option-for-<unit-key> = <key1=value1,...></code>
<code>erase-all-options</code>	<code>erase-all-options</code>

Sets and adds `<key1=value1,...>` to a specific `<unit-key>`, `erase-all-options` is used to erase all options for all `<unit-key>`s.

You may want to attach some options to a special `<unit-key>`. Those options are automatically activated if (and only if) the specific `<unit-key>` is used (or changed into this unit). Setting options overwrites old options. Adding options, well ... adds the options to the old ones.

The following rounds the values to integers for F, C, K and Re.


```

\cusetup
{
  set-option-for-F = { round-to-int = true } ,
  set-option-for-C = { round-to-int = true } ,
  set-option-for-K = { round-to-int = true } ,
  set-option-for-Re = { round-to-int = true }
}

```

You can “delete” the options by setting an empty value for a specific $\langle unit-key \rangle$ (or use `erase-all-options` to erase all options for all $\langle unit-key \rangle$ s)

9.2.2 Command behavior

<code>cutext-to-cunum</code>	<code>cutext-to-cunum = $\langle true/false \rangle$</code>
------------------------------	--

Want to get rid of all `\cutext` and `\Cutext`? Set this option to `true` and all `\cutext` and `\Cutext` are changed into `\cunum`.

1 kilogramme	<code>\cutext{1}{kg}\</code>
2 kilogramme	<code>\Cutext{2}{kg}\</code>
$\frac{1}{2}$ kilogramme	<code>\cutext{1/2}{kg}\</code>
? kilogramme	<code>\cutext{?}{kg}\</code>
1000–2000 gramme	<code>\cutext[kg=g]{1--2}{kg}\</code>
	<code>\cusetup{cutext-to-cunum=true}</code>
1 kg	<code>\cutext{1}{kg}\</code>
2 kg	<code>\Cutext{2}{kg}\</code>
$\frac{1}{2}$ kg	<code>\cutext{1/2}{kg}\</code>
? kg	<code>\cutext{?}{kg}\</code>
1000–2000 g	<code>\cutext[kg=g]{1--2}{kg}</code>

<code>cutext-change-unit</code>	<code>cutext-change-unit = $\langle true/false \rangle$</code>
---------------------------------	---

Set this option to `true` if you do *not* want the units of `\cutext` and `\Cutext` to be changed. Set to `true` by default

1000 gramme	<code>\cutext[kg=g]{1}{kg}\</code>
$\frac{1}{2}$ kilogramme	<code>\cutext[kg=g]{1/2}{kg}\</code>
1000–2000 gramme	<code>\cutext[kg=g]{1--2}{kg}\</code>
	<code>\cusetup{cutext-change-unit=false}</code>
1 kilogramme	<code>\cutext[kg=g]{1}{kg}\</code>
$\frac{1}{2}$ kilogramme	<code>\cutext[kg=g]{1/2}{kg}\</code>
1–2 kilogramme	<code>\cutext[kg=g]{1--2}{kg}</code>

<code>cuam-version</code>	<code>cuam-version = $\langle old/new \rangle$</code>
<code>cutext-version</code>	<code>cutext-version = $\langle old/new \rangle$</code>

Since v1.10 this package also parses and checks the input of `\cutext` and `\Cutext` and `\cuam`. If you want to restore the old behavior, set this option to `old`, but note that then you can neither change the amounts for a given number of persons nor change the unit of `\cutext` and `\Cutext`. Both of them are set to `new` by default.

9.2.3 Input and Outputs

set-special-sign	set-special-sign = $\langle character(s) \rangle$
add-special-sign	add-special-sign = $\langle character(s) \rangle$

Allows $\langle character(s) \rangle$ to be used in the first mandatory argument of $\backslash\text{cunum}$, $\backslash\text{cuam}$, $\backslash\text{cutext}$ and $\backslash\text{Cutext}$ without raising an error (you can customize this behavior, see $\text{set-unknown-message}$). By default it is set to `?`. Please note that the sign `<` is not allowed as a special sign.

? kg	$\backslash\text{cunum}\{?\}\{\text{kg}\}\backslash\backslash$
10?–20? kg	$\backslash\text{cunum}[g=\text{kg}]\{10?--20?\}\{\text{kg}\}\backslash\backslash$
	$\backslash\text{cusetup}\{\text{add-special-sign}=\{\text{xX}\}\}$
x kg	$\backslash\text{cunum}\{\text{x}\}\{\text{kg}\}\backslash\backslash$
X–? kg	$\backslash\text{cunum}\{\text{X}--?\}\{\text{kg}\}\backslash\backslash$
	$\backslash\text{cusetup}\{\text{set-special-sign}=\{\}\}\}$
1 kg	$\backslash\text{cunum}\{1\}\{\text{kg}\}\backslash\backslash$
1–2 kg	$\backslash\text{cunum}\{1--2\}\{\text{kg}\}$

set-unknown-message	set-unknown-message = $\langle error/warning/none \rangle$
---------------------	--

Using a special sign (`?` by default) causes a warning to be raised. Set this option to **error** if you want an error (as an extra emphasis), **warning** if you want a warning (default) and **none** if you don't want to know anything about it.

set-cutext-translation-message	set-cutext-translation-message = $\langle error/warning/none \rangle$
--------------------------------	---

If a translation for $\backslash\text{cutext}$ and $\backslash\text{Cutext}$ is not available the commands are replaced by $\backslash\text{cunum}$. Currently – if this is happening – a warning is shown, you may change the behavior of the message (error, warning or not showing at all) using this option.

print-numerals	print-numerals = $\langle true/false \rangle$
----------------	---

If the package option `use-numerals` is set to `true` you can deactivate the printing of numerals by setting `print-numerals` to `false` and activate them by setting it to `true`.

Note that this option is automatically set to `true` if `use-numerals` is used.

one kilogramme	$\backslash\text{cutext}\{1\}\{\text{kg}\}\backslash\backslash$
two kilogramme	$\backslash\text{cutext}\{2\}\{\text{kg}\}\backslash\backslash$
twelve kilogramme	$\backslash\text{cutext}\{12\}\{\text{kg}\}\backslash\backslash$
13 kilogramme	$\backslash\text{cutext}\{13\}\{\text{kg}\}\backslash\backslash$
	$\backslash\text{cusetup}\{\text{print-numerals}=\text{false}\}$
1 kilogramme	$\backslash\text{cutext}\{1\}\{\text{kg}\}\backslash\backslash$
2 kilogramme	$\backslash\text{cutext}\{2\}\{\text{kg}\}\backslash\backslash$
12 kilogramme	$\backslash\text{cutext}\{12\}\{\text{kg}\}\backslash\backslash$
13 kilogramme	$\backslash\text{cutext}\{13\}\{\text{kg}\}\backslash\backslash$

use-numerals-below	use-numerals-below = $\langle integer \rangle$
--------------------	--

Only usable if the package option `use-numerals` is active. Prints the name of the numbers for integers used in $\backslash\text{cutext}$ and $\backslash\text{Cutext}$ smaller than $\langle integer \rangle$. $\langle integer \rangle$ is by default 13. Package `fmtcount` is used for this purpose.

one kilogramme	<code>\cutext{1}{kg}\</code>
two kilogramme	<code>\cutext{2}{kg}\</code>
twelve kilogramme	<code>\cutext{12}{kg}\</code>
13 kilogramme	<code>\cutext{13}{kg}\</code>
	<code>\cusetup{use-numerals-below=10}</code>
one kilogramme	<code>\cutext{1}{kg}\</code>
two kilogramme	<code>\cutext{2}{kg}\</code>
12 kilogramme	<code>\cutext{12}{kg}\</code>
13 kilogramme	<code>\cutext{13}{kg}\</code>
	<code>\cusetup{use-numerals-below=0}</code>
1 kilogramme	<code>\cutext{1}{kg}\</code>
2 kilogramme	<code>\cutext{2}{kg}\</code>
12 kilogramme	<code>\cutext{12}{kg}\</code>
13 kilogramme	<code>\cutext{13}{kg}\</code>
	<code>\cusetup{use-numerals-below=12001}</code>
one thousand gramme	<code>\cutext[kg=g]{1}{kg}\</code>
two thousand gramme	<code>\cutext[kg=g]{2}{kg}\</code>
twelve thousand gramme	<code>\cutext[kg=g]{12}{kg}\</code>
13000 gramme	<code>\cutext[kg=g]{13}{kg}\</code>

parse-number `parse-number = <true/false>`

If set to **false** prints the number of `\cunum`, `\cutext`, `\Cutext` and `\cuam` as they are (after some ... well ... parsing due to “_”). Is set to **true** by default.

	<code>\cusetup{parse-number=false}</code>
1 kg	<code>\cunum[kg=g]{1}{kg}\</code>
1–2 kg	<code>\cunum{1--2}{kg}\</code>
1————2 kg	<code>\cunum{1-----2}{kg}\</code>
1.2 kg	<code>\cunum{1.2}{kg}\</code>
1,2 kg	<code>\cunum[kg=g]{1,2}{kg}\</code>
1/2 kg	<code>\cunum{1/2}{kg}\</code>
1_2/3 kg	<code>\cunum{1_2/3}{kg}\</code>
1/2_3 kg	<code>\cunum{1/2_3}{kg}\</code>
qwertyuiop kg	<code>\cunum{qwertyuiop}{kg}\</code>
1 kilogramme	<code>\cutext{1}{kg}\</code>
100 kilogramme	<code>\cutext{100}{kg}\</code>
gjfak kilogramme	<code>\cutext{gjfak}{kg}\</code>
12 kilogramme	<code>\cutext[kg=g]{12}{kg}\</code>
1————2	<code>\cuam{1-----2}\</code>
1,2	<code>\cuam{1,2}\</code>
1_1/2	<code>\cuam{1_1/2}\</code>
kwflk	<code>\cuam{kwflk}\</code>

range-sign range-sign = $\langle string \rangle$
 cunum-range-sign = $\langle string \rangle$
 cutext-range-sign = $\langle string \rangle$

The second sets the *printed* range sign used in `\cunum` (and `\cuam`) to $\langle string \rangle$, the third sets the printed range sign used in `\cutext` and `\Cutext` to $\langle string \rangle$. Using the first option sets the range signs for both `\cunum` (and `\cuam`) and `\cutext`/`\Cutext` to $\langle string \rangle$.

The default for $\langle string \rangle$ is `--` (for both).

	<code>\cusetup{cunum-range-sign={~to~}}</code>
1 to 2 kg	<code>\cunum{1--2}{kg}\</code>
1 to 2	<code>\cuam{1--2}\</code>
1–2 kilogramme	<code>\cutext{1--2}{kg}\</code>
1–2 kilogramme	<code>\Cutext{1--2}{kg}</code>
	<code>\cusetup{cutext-range-sign={~to~}}</code>
1–2 kg	<code>\cunum{1--2}{kg}\</code>
1–2	<code>\cuam{1--2}\</code>
1 to 2 kilogramme	<code>\cutext{1--2}{kg}\</code>
1 to 2 kilogramme	<code>\Cutext{1--2}{kg}</code>
	<code>\cusetup{range-sign={~to~}}</code>
1 to 2 kg	<code>\cunum{1--2}{kg}\</code>
1 to 2	<code>\cuam{1--2}\</code>
1 to 2 kilogramme	<code>\cutext{1--2}{kg}\</code>
1 to 2 kilogramme	<code>\Cutext{1--2}{kg}</code>

use-phrases use-phrases = $\langle true/false \rangle$

Setting this option to **true** replaces certain integers (see section 8.1 for more information) with their phrase counterpart. This option is set to **false** by default.

For the German language:

12	<code>\cuam{12}\</code>
12–24	<code>\cuam{12--24}\</code>
36	<code>\cuam{36}\</code>
	<code>\cusetup{use-phrases=true}</code>
1 Dutzend	<code>\cuam{12}\</code>
1–2 Dutzend	<code>\cuam{12--24}\</code>
3 Dutzend	<code>\cuam{36}\</code>

9.2.4 Rounding options

round-precision round-precision = $\langle integer \rangle$

Rounds the amount automatically to $\langle integer \rangle$ digits after the colon. Note that units like C, F, K and Re are still rounded to integers due to `set-option-for- $\langle unit-key \rangle$` .

1.23457 kg	<code>\csetup{round-precision=5}</code>
0.01259 kg	<code>\cunum{1.23456789}{kg}\\</code>
194 kg	<code>\cunum[g=kg]{12.587}{g}\\</code>
392–410 °F	<code>\cunum{194}{kg}\\</code>
–273 °C	<code>\cunum[C=F]{200--210}{C}\\</code>
	<code>\cunum[K=C]{0.0012}{K}\\</code>
1.2 kg	<code>\csetup{round-precision=1}</code>
12.6 kg	<code>\cunum{1.23456789}{kg}\\</code>
0.2 kg	<code>\cunum{12.58}{kg}\\</code>
392–410 °F	<code>\cunum[g=kg]{194}{g}\\</code>
–273 °C	<code>\cunum[C=F]{200--210}{C}\\</code>
	<code>\cunum[K=C]{0.0012}{K}</code>

round-to-int `round-to-int = <true/false>`

Rounds the amount to an integer if set **true**.

1 kg	<code>\csetup{round-to-int=true}</code>
13 kg	<code>\cunum{1.23456789}{kg}\\</code>
0–0 kg	<code>\cunum{12.58}{kg}\\</code>
1235 g	<code>\cunum[g=kg]{194--294}{g}\\</code>
	<code>\cunum[kg=g]{1.23456789}{kg}</code>

round-half `round-half = <default/commercial>`

This option is only important for half-way numbers (e.g. 0.005). By setting it to **default** the value will be rounded to the nearest even number. Setting it to **commercial** rounds the value away from zero.

It is set to **default** by ... default.

Note: **default** actually refers to the fact that it is the default rounding algorithm used by `\fp_eval:n { round() }` without a third argument.

0 kg	<code>\csetup{round-half=default}</code>
–0 kg	<code>\cunum{0.005}{kg}\\</code>
1.24 kg	<code>\cunum{-0.005}{kg}\\</code>
	<code>\cunum{1.245}{kg}\\</code>
0.01 kg	<code>\csetup{round-half=commercial}</code>
–0.01 kg	<code>\cunum{0.005}{kg}\\</code>
1.25 kg	<code>\cunum{-0.005}{kg}\\</code>
	<code>\cunum{1.245}{kg}</code>

9.2.5 Fractions

eval-fraction `eval-fraction = <true/false>`

This option takes **true** or **false** as values. If set to **true** fractions are evaluated. Please note that divisions through zero are not allowed.

0.33 kg	<code>\cusetup{eval-fraction=true}</code>
0.5 kg	<code>\cunum{1/3}{kg}\</code>
500 g	<code>\cunum{1/2}{kg}\</code>
1.5 kg	<code>\cunum[kg=g]{1/2}{kg}\</code>
1500 g	<code>\cunum{1_1/2}{kg}\</code>
-1500 g	<code>\cunum[kg=g]{1_1/2}{kg}\</code>

`fraction-command` `fraction-command = <\command>`

Sets the command used for printing fractions equal to `<\command>`. `<\command>` has to take two arguments. By default it is equal to `\sfrac` from `xfrac`.

Please note that the amount is *not* printed inside a math environment by default.

	<code>\newcommand\myfrac[2]{#1/#2}</code>
	<code>\cusetup{fraction-command=\myfrac}</code>
$1/8$	<code>\cuam{1/8}\</code>
$1/2$ kg	<code>\cunum{1/2}{kg}\</code>
$4/5$ °C	<code>\cunum{4/5}{C}\</code>
$12/3$ kg	<code>\cunum{1_2/3}{kg}\</code>
	<code>\cusetup{fraction-command=\nicefrac}</code>
$1/8$	<code>\cuam{1/8}\</code>
$1/2$ kg	<code>\cunum{1/2}{kg}\</code>
$4/5$ °C	<code>\cunum{4/5}{C}\</code>
$12/3$ kg	<code>\cunum{1_2/3}{kg}</code>

`fraction-inline` `fraction-inline = <input containing #1 and #2>`

Similar to `fraction-command` only that you don't have to define a command to alter the output of the fraction.

	<code>\cusetup{fraction-inline={#1/#2}}</code>
$1/8$	<code>\cuam{1/8}\</code>
$1/2$ kg	<code>\cunum{1/2}{kg}\</code>
$4/5$ °C	<code>\cunum{4/5}{C}\</code>
$12/3$ kg	<code>\cunum{1_2/3}{kg}\</code>
	<code>\cusetup{fraction-inline={\nicefrac{#2}{#1}}}</code>
$8/1$	<code>\cuam{1/8}\</code>
$2/1$ kg	<code>\cunum{1/2}{kg}\</code>
$5/4$ °C	<code>\cunum{4/5}{C}\</code>
$13/2$ kg	<code>\cunum{1_2/3}{kg}</code>

9.2.6 Spaces

`mixed-fraction-space` `mixed-fraction-space = <length>`

Sets the length between the fraction and the number in a mixed-fraction, default is `0.1em` (because I said so; if someone has some literature or sources to look up the space, please let me know).

$1\frac{2}{3}$	<code>\cuam{1_2/3}\\</code>
$1\frac{2}{3}$ kg	<code>\cunum{1_2/3}{kg}\\</code>
$10\frac{2}{3}$ kg	<code>\cunum{10_2/3}{kg}\\</code>
	<code>\cusetup{mixed-fraction-space=1em}</code>
$1\frac{2}{3}$	<code>\cuam{1_2/3}\\</code>
$1\frac{2}{3}$ kg	<code>\cunum{1_2/3}{kg}\\</code>
$10\frac{2}{3}$ kg	<code>\cunum{10_2/3}{kg}\\</code>
	<code>\cusetup{mixed-fraction-space=0em}</code>
$1\frac{2}{3}$	<code>\cuam{1_2/3}\\</code>
$1\frac{2}{3}$ kg	<code>\cunum{1_2/3}{kg}\\</code>
$10\frac{2}{3}$ kg	<code>\cunum{10_2/3}{kg}</code>

cutext-space `cutext-space = <string>`

<string> is inserted between the numeral part and the unit part when using `\cutext` and `\Cutext`. By default it is set to `\space`. Use this option if you want to e.g. insert an unbreakable space.

1 kilogramme	<code>\cutext{1}{kg}\\</code>
10 kilogramme	<code>\Cutext{10}{kg}\\</code>
	<code>\cusetup{cutext-space=~}</code>
1 kilogramme	<code>\cutext{1}{kg}\\</code>
10 kilogramme	<code>\Cutext{10}{kg}\\</code>
	<code>\cusetup{cutext-space={}}</code>
1kilogramme	<code>\cutext{1}{kg}\\</code>
10kilogramme	<code>\Cutext{10}{kg}\\</code>
	<code>\cusetup{cutext-space={qwe}}</code>
1qwekilogramme	<code>\cutext{1}{kg}\\</code>
10qwekilogramme	<code>\Cutext{10}{kg}\\</code>

phrase-space `phrase-space = <string>`

<string> is inserted between the numeral part and the phrase part while using `\cuam`. By default it is set to `\space`. Use this option if you want to e.g. insert an unbreakable space.

(Switching to german)

1 Dutzend	<code>\cuam{12}\\</code>
12 Dutzend	<code>\cuam{144}\\</code>
	<code>\cusetup{phrase-space=~}</code>
1 Dutzend	<code>\cuam{12}\\</code>
12 Dutzend	<code>\cuam{144}\\</code>
	<code>\cusetup{phrase-space={}}</code>
1Dutzend	<code>\cuam{12}\\</code>
12Dutzend	<code>\cuam{144}\\</code>
	<code>\cusetup{phrase-space={qwe}}</code>
1qweDutzend	<code>\cuam{12}\\</code>
12qweDutzend	<code>\cuam{144}\\</code>

amount-unit-space**amount-unit-space** = $\langle string \rangle$

Change the spacing for `\cunum` between the printed amount(s) and the unit. The default value is `\thinspace`.

1 kg	<code>\selectlanguage{ngerman}</code>
$\frac{1}{2}$ kg	<code>\cunum{1}{kg}\</code>
1–2 kg	<code>\cunum{1/2}{kg}\</code>
	<code>\cunum{1--2}{kg}\</code>
	<code>\cusetup{amount-unit-space={\hspace{1em}}}</code>
1 kg	<code>\cunum{1}{kg}\</code>
$\frac{1}{2}$ kg	<code>\cunum{1/2}{kg}\</code>
1–2 kg	<code>\cunum{1--2}{kg}\</code>
	<code>\cusetup{amount-unit-space={}}</code>
1kg	<code>\cunum{1}{kg}\</code>
$\frac{1}{2}$ kg	<code>\cunum{1/2}{kg}\</code>
1–2kg	<code>\cunum{1--2}{kg}\</code>
	<code>\cusetup{amount-unit-space={qwe}}</code>
1qwekg	<code>\cunum{1}{kg}\</code>
$\frac{1}{2}$ qwekg	<code>\cunum{1/2}{kg}\</code>
1–2qwekg	<code>\cunum{1--2}{kg}\</code>

9.2.7 label & refs

recalculate-amount**recalculate-amount** = $\langle true/false \rangle$

Set this option to `true` if you want to change your recipes to the given number of people set by `set-number-of-persons`. Note that only those values who have a label are changed.

set-number-of-persons**set-number-of-persons** = $\langle integer \rangle$

With this option you can determine the number of people your recipes are. Note that this option only has an effect on those who have a $\langle label \rangle$ given. It is set to 4 by default.

2 persons	<code>\culabel{anotherrecipe}{2}</code>
1 kg	<code>\curef{anotherrecipe}~persons\\</code>
1	<code>\cunum<anotherrecipe>{1}{kg}\\</code>
1 kilogramme	<code>\cuam<anotherrecipe>{1}\\</code>
2 persons	<code>\cutext<anotherrecipe>{1}{kg}\\</code>
	<code>\curef{anotherrecipe}~persons\\</code>
4 persons	<code>\cusetup{recalculate-amount=true}</code>
2 kg	<code>\curef{anotherrecipe}~persons\\</code>
2	<code>\cunum<anotherrecipe>{1}{kg}\\</code>
2 kilogramme	<code>\cuam<anotherrecipe>{1}\\</code>
20 kilogramme	<code>\cutext<anotherrecipe>{1}{kg}\\</code>
	<code>\Cutext[ref=anotherrecipe]{10}{kg}\\</code>
3 persons	<code>\cusetup{set-number-of-persons=3}</code>
1.5 kg	<code>\curef{anotherrecipe}~persons\\</code>
1.5	<code>\cunum<anotherrecipe>{1}{kg}\\</code>
1.5 kilogramme	<code>\cuam<anotherrecipe>{1}\\</code>
15 kilogramme	<code>\cutext<anotherrecipe>{1}{kg}\\</code>
	<code>\Cutext[ref=anotherrecipe]{10}{kg}\\</code>
2 persons	<code>\cusetup{set-number-of-persons=2}</code>
1 kg	<code>\curef{anotherrecipe}~persons\\</code>
1	<code>\cunum<anotherrecipe>{1}{kg}\\</code>
1 kilogramme	<code>\cuam<anotherrecipe>{1}\\</code>
10 kilogramme	<code>\cutext<anotherrecipe>{1}{kg}\\</code>
	<code>\Cutext[ref=anotherrecipe]{10}{kg}\\</code>
1 person	<code>\cusetup{set-number-of-persons=1}</code>
0.5 kg	<code>\curef{anotherrecipe}~person\\</code>
0.5	<code>\cunum<anotherrecipe>{1}{kg}\\</code>
0.5 kilogramme	<code>\cuam<anotherrecipe>{1}\\</code>
5 kilogramme	<code>\cutext<anotherrecipe>{1}{kg}\\</code>
	<code>\Cutext[ref=anotherrecipe]{10}{kg}\\</code>

label `label = <string>*<integer>`

The key-value version of `\culabel`. It defines the label `<string>` which is originally for `<integer>` people. Please note that the `*` is mandatory as it separates the string from the integer. Note that each label is defined globally and must be unique.

1 person	<code>\cusetup{label=Toast*1}</code>
2	<code>\curef{Toast}~person\\</code>
2 dag	<code>\cuam<Toast>{2}\\</code>
	<code>\cunum<Toast>{2}{dag}\\</code>
4 persons	<code>\cusetup{recalculate-amount=true}</code>
8	<code>\curef{Toast}~persons\\</code>
8 dag	<code>\cuam<Toast>{2}\\</code>
	<code>\cunum<Toast>{2}{dag}</code>

get-label

get-label = $\langle label \rangle$

The key-value version of `\curef`. Note that this key doesn't save the value inside a macro but rather prints it directly into the document.

	<code>\culabel{Schinken}{3}</code>
3	<code>\cusetup{get-label=Schinken}\\</code>
3	<code>\curef{Schinken}\\</code>
	<code>\cusetup{recalculate-amount=true}</code>
4	<code>\cusetup{get-label=Schinken}\\</code>
4	<code>\curef{Schinken}\\</code>

ref

ref = $\langle label \rangle$

Instead of using the first optional arguments of the commands in section 2 you may use this option. It requires a valid value and throws an error if $\langle label \rangle$ is not defined.

	<code>\culabel{Kaese}{3}</code>
10 dm	<code>\cunum<Kaese>[m=dm]{1}{m}\\</code>
10 dm	<code>\cunum[ref=Kaese,m=dm]{1}{m}\\</code>
	<code>\cusetup{recalculate-amount=true}</code>
13.33 dm	<code>\cunum<Kaese>[m=dm]{1}{m}\\</code>
13.33 dm	<code>\cunum[ref=Kaese,m=dm]{1}{m}</code>

9.3 Weird options

check-temperature

check-temperature = $\langle true/false \rangle$

Checks if the used temperature is below absolute zero. Currently C, F, K and Re are supported. While `\cunum{0}{K}` is ok, `\cunum{-1}{K}` raises an error, same for the others. Is set to `false` by default. To add new units see `add-temperature-to-check`.

add-temperature-to-check

add-temperature-to-check =
{
 $\langle unit-key-1 \rangle$ = $\langle minimum-value-1 \rangle$,
 $\langle unit-key-2 \rangle$ = $\langle minimum-value-2 \rangle$,
 ...
}

This option adds $\langle unit-key-1 \rangle$ and so on to the list of units to be checked if `check-temperature` is active. The argument can be a comma-separated list of $\langle unit-key \rangle$ = $\langle minimum-value \rangle$. This sets the allowed minimum value of $\langle unit-key \rangle$ to $\langle minimum-value \rangle$.

For example, this package implements the allowed minimum values for the temperatures C, F, K and Re to be checked if `check-temperature` is active using:

```
\cusetup
{
  add-temperature-to-check =
  {
    K = 0,
    C = -273.15 ,
```

```

        F = -459.67 ,
        Re = -218.52
    }
}

```

If you want to add a new value, for example degree Rømer (which has be defined in another example) you can write:

```
\cusetup
{
  add-temperature-to-check = { Ro = -135.90375 }
}
```

```
convert-to-eV    convert-to-eV =  $\langle true/false \rangle$ 
```

Converts (nearly) every unit in table 1 to electron volt or the respective derivative. Note that this option is: a) experimental and probably will forever be and b) just a joke, you are not supposed to use this units in a cookery book (and as you see this package doesn't support the arrangement of such huge numbers). Also you may want to check the values if you really want to use them, just to be sure (I've checked them several times and hope they are finally correct, but mistakes happen).

	\cusetup{convert-to-eV=true}
560958865000000000000000000000000000000000 eV	\x^2\cunum{1}{kg}\\
130148929500000000 c ³ ħ ³ /eV ³	\cunum{1}{1}\\
62415091260000000000 eV	\cunum{1}{J}\\
5067730.76 ħ/eV	\cunum{1}{m}\\
0.02 eV	\cunum{1}{C}\\
1519267461000000 ħ/eV	\cunum{1}{s}

10 Bugs & Feedback

Bug reports are always welcome. If you are sending a bug report please include a minimal working example showing the bug and a short description. If you use mail please add **cooking-units** to the e-mail header. GMX has the habit of putting e-mails into the spam account and adding **cooking-units** to the header makes it easier to recognize those e-mails.

Feedback and requests (commands, units, etc.) are also welcome. Please also add (if possible) an example of the desired output into the minimal example (and – if by mail – add `cooking-units` to the header).

Furthermore, as you can see I am not able to speak too many languages (german and english to be precise; I managed to add french with the help of the internet, which is not optimal) so if you are able to speak a language not yet implemented and would like to help you can send me the translations known to you. A list of all units (and their current translations) is given in appendix A.

A Translations

This section contains the list of available translations. Each table shows the available translations regarding the unit symbol, the unit name (printed if `\cutext` or `\Cutext` is used) and the plural form (if different from the singular form). A second table shows the translations used for phrases (if given).

If a translation is not available a “—” is shown.

A.1 English

$\langle unit\text{-}key \rangle$	printed unit	unitname	(plural)	gender
kg	kg	kilogramme		m
dag	dag	decagramme		m
g	g	gramme		m
oz	oz	ounce		m
lb	lb	pound	(pounds)	m
C	°C	degree Celsius	(degrees Celsius)	m
F	°F	degree Fahrenheit	(degrees Fahrenheit)	m
Re	°Ré	degree Réaumur	(degrees Réaumur)	m
K	K	kelvin		m
d	d	day	(days)	m
h	h	hour	(hours)	m
min	min	minute	(minutes)	m
s	s	second	(seconds)	m
m	m	metre	(metres)	m
dm	dm	decimetre	(decimetres)	m
cm	cm	centimetre	(centimetres)	m
mm	mm	millimetre	(millimetres)	m
in	in	inch	(inches)	m
l	ℓ	litre	(litres)	m
dl	dl	decilitre	(decilitres)	m
cl	cl	centilitre	(centilitres)	m
ml	ml	millilitre	(millilitres)	m
cal	cal	calorie	(calories)	m
kcal	kcal	kilocalorie	(kilocalories)	m
J	J	joule	(joules)	m
kJ	kJ	kilojoule	(kilojoules)	m
eV	eV	electron volt		m
pn	pinch	pinch	(pinches)	m
EL	tbsp.	tablespoon	(tablespoons)	m
TL	tsp.	teaspoon	(teaspoons)	m
csp	csp.	coffeespoonful		m
dsp	dsp.	dessertspoonful		m
ssp	ssp.	saltspoonful		m
Msp	Msp.	—		m
decimal-mark	—	.	—	m
one(m)	—	one	—	m
one(f)	—	one	—	m
one(n)	—	one	—	m

A.2 american

$\langle unit-key \rangle$	printed unit	unitname	(plural)	gender
kg	kg	kilogram		m
dag	dag	decagram		m
g	g	gram		m
oz	oz	ounce		m
lb	lb	pound	(pounds)	m
C	°C	degree Celsius	(degrees Celsius)	m
F	°F	degree Fahrenheit	(degrees Fahrenheit)	m
Re	°Ré	degree Réaumur	(degrees Réaumur)	m
K	K	kelvin		m
d	d	day	(days)	m
h	h	hour	(hours)	m
min	min	minute	(minutes)	m
s	s	second	(seconds)	m
m	m	meter	(meters)	m
dm	dm	decimeter	(decimeters)	m
cm	cm	centimeter	(centimeters)	m
mm	mm	millimeter	(millimeters)	m
in	in	inch	(inches)	m
l	ℓ	liter	(liters)	m
dl	dl	deciliter	(deciliters)	m
cl	cl	centiliter	(centiliters)	m
ml	ml	milliliter	(milliliters)	m
cal	cal	calorie	(calories)	m
kcal	kcal	kilocalorie	(kilocalories)	m
J	J	joule	(joules)	m
kJ	kJ	kilojoule	(kilojoules)	m
eV	eV	electron volt		m
pn	pn.	pinch	(pinches)	m
EL	tbsp.	tablespoon	(tablespoons)	m
TL	tsp.	teaspoon	(teaspoons)	m
csp	csp.	coffeespoonful		m
dsp	dsp.	dessertspoonful		m
ssp	ssp.	saltspoonful		m
Msp	Msp.	—		m
decimal-mark	—	.	—	m
one(m)	—	one	—	m
one(f)	—	one	—	m
one(n)	—	one	—	m

A.3 German

$\langle unit-key \rangle$	printed unit	unitname	(plural)	gender
kg	kg	Kilogramm		n
dag	dag	Dekagramm		n
g	g	Gramm		n
oz	oz	Unze		f
lb	lb	Pfund		n
C	°C	Grad Celsius		m
F	°F	Grad Fahrenheit		m
Re	°Ré	Grad Réamur		m
K	K	Kelvin		n
d	d	Tag	(Tage)	m
h	h	Stunde	(Stunden)	f
min	min	Minute	(Minuten)	f
s	s	Sekunde	(Sekunden)	f
m	m	Meter		n
dm	dm	Dezimeter		n
cm	cm	Centimeter		n
mm	mm	Millimeter		n
in	in	Zoll		m
l	l	Liter		m
dl	dl	Deziliter		m
cl	cl	Centiliter		m
ml	ml	Milliliter		m
cal	cal	Kalorie	(Kalorien)	f
kcal	kcal	Kilokalorie	(Kilokalorien)	f
J	J	Joule		m
kJ	kJ	Kilojoule		m
eV	eV	Elektronenvolt		n
pn	Prise	Prise	(Prisen)	f
EL	EL	Esslöffel		m
TL	TL	Teelöffel		m
csp	KL	Mokkalöffel		m
dsp	dsp.	—		m
ssp	ssp.	—		m
Msp	Msp.	Messerspitze	(Messerspitzen)	f
decimal-mark	—	,	—	m
one(m)	—	ein	—	m
one(f)	—	eine	—	m
one(n)	—	ein	—	m

$\langle Phrase-key \rangle$	phrase	(plural)	gender
12	Dutzend	n	

Some further phrases, just to write them down (they are not implemented, as they are barely used).

$\langle number \rangle$	name	Note	(plural)	gender
60	Schock	(5 Dutzend, 12 * 5)		n
144	Gros	(12 Dutzend, 12 * 12)		n
1728	Großgros	(12 Groß, 12 * 144)		n

Note that Großgros has other (probably more common) synonyms.

A.4 French

$\langle unit-key \rangle$	printed unit	unitname	(plural)	gender
kg	kg	kilogramme	(kilogrammes)	m
dag	dag	décagramme	(décagrammes)	m
g	g	gramme		m
oz	oz	once		f
lb	lb	livre	(livres)	f
C	°C	degré Celsius	(degrés Celsius)	m
F	°F	kelvin	(kelvins)	m
Re	°Ré	échelle Réaumur	(degrés Réaumur)	m
K	K	degré Fahrenheit	(degrés Fahrenheit)	m
d	d	jour	(jours)	m
h	h	heure	(heures)	f
min	min	minute	(minutes)	f
s	s	seconde	(secondes)	f
m	m	mètre	(mètres)	m
dm	dm	décimètre	(décimètres)	m
cm	cm	centimètre	(centimètres)	m
mm	mm	millimètre	(millimètres)	m
in	po	pouce	(pouces)	m
l	L	litre	(litres)	m
dl	dL	décilitre	(décilitres)	m
cl	cL	centilitre	(centilitres)	m
ml	mL	millilitre	(millilitres)	m
cal	cal	calorie		m
kcal	kcal	kilocalorie	(kilocalories)	m
J	J	joule	(joules)	m
kJ	kJ	kilojoule	(kilojoules)	m
eV	eV	électron-volt	(électron-volts)	m
pn	pinch	pincée		f
EL	EL	cuillère à soupe		f
TL	TL	cuillère à café		f
csp	csp.	—		m
dsp	dsp.	—		m
ssp	ssp.	—		m
Msp	Msp.	—		m
decimal-mark	—	.	—	m
one(m)	—	un	—	m
one(f)	—	une	—	m
one(n)	—	un	—	m

Change History

2016/06/11	General: Added the package option to load 'fmtcount'.	1	New option: 'round-half'.	1
2016/08/31	General: Fixed calculation: degree Reamur to eV	1	Recalculated all electron volt values for conversion (as 'kg' was wrong before). Let's hope they are correct this time.	1
2016/09/03	Initial version	1	Replaced <code>\prop_clear_new:c</code> by <code>\prop_clear:c</code>	1
2016/09/05	General: Added units 'ssp', 'csp', 'dsp' British English: 'pinch' is written in full	1	2016/10/19	General: 'convert-to-eV' now also as optional argument available.
	English unit: litre (and only litre) uses the curly l ℓ now	1		Option 'load-time-option' now spells 'available' correct.
	Separated Messerspitze and pinch	1		Update of documentation.
	General: New message: 'obsolete-command'	1		Use <code>\keys_set:nn</code> only if second argument is not empty.
	Replaced <code>\cfrac</code> by <code>\cuam</code>	1	2016/10/28	General: <code>\cutext</code> (and <code>\Cutext</code>) and <code>\cuam</code> now parse their input like <code>\cunum</code> . This is needed as they also need to be changed.
2016/09/09	General: <code>\@@_calculate_input_and_store_in:nN</code> optimiert durch neue property-key: single.	1		Start implementation of "Change recipe from n to m persons.".
	Add 'single' to property list of singlekeys.	1	2016/10/29	General: Tiding code: Now every command is separated into a "calc" function, a "print numeric value" and a "print unit" (if there) function. At least, that's the plan.
	Changed name from <code>\@@_cunum_parse_range</code> (and derivatives) to <code>\@@_cutext_parse_range</code>	1	2016/10/30	General: Fractions should now deal correctly with minus signs.
	Changed name from <code>\@@_parse_fraction_in_input:www</code> to <code>\@@_parse_mixed_fraction_in_input:www</code>	1	2016/11/07	General: Finished writing v1.10.
	Corrected mistake: 'ELEktronenvolt' (note uppercase L) to 'Elektronenvolt' in german.	1	2016/11/13	General: <code>\cutext</code> , <code>\Cutext</code> and <code>\cuam</code> check their input, allows conversion of units.
	Delete 'single' from property lists of singlekeys cause it is not as safe as I thought.	1		Change amounts for specific number of persons.
	In <code>\@@_cutext_default:nnn</code> it is only checked once if a range is inside.	1		New commands: <code>\culabel</code> and <code>\curef</code>
2016/09/16	General: Only use <code>\phantom</code> if the argument (for <code>\phantom</code>) is not empty.	1		New commands: <code>\declarecookingunit</code> and <code>\providecookingunit</code>
2016/09/26	General: <code>\cuaddsinglekeys</code> now tests if the unit exists (it didn't before).	1		New options: <code>cunum-version</code> and <code>cutext-version</code>
	New option (and needed macros): add-temperature-to-check.	1		New options: <code>cutext-to-cunum</code> , <code>cutext-change-unit</code> and <code>cutext-space</code>

New options: <code>recalculate-amount</code> and <code>set-number-of-persons</code> , <code>label</code> , <code>get-label</code> , <code>ref</code>	1	Added unit “stick” (of butter).	1
2017/03/10		New option: <code>amount-unit-space</code>	1
General: <code>\curef</code> is now defined by <code>\NewExpandableDocumentCommand</code> instead of the <code>Declare variant</code>	1	New option: <code>phrase-space</code>	1
Removed <code>\translate</code> and others from code and replaced them with wrapper-macros.	1	New option: <code>print-numerals</code>	1
Removed things like ‘cu-unit’ from translate input and placed them into separate tl’s.	1	New option: <code>set-cutext-translation-message</code>	1
2017/10/23		New option: <code>use-phrases</code>	1
General: Added “phrases”.	1	Now checks for ranges if both values can be printed as numerals (if activated) (bug fix).	1
		Replaced translator by translations.	1
		Reworked quite a lot of code.	1

Index

The italic numbers denote the pages where the corresponding entry is described, numbers underlined point to the definition, all others indicate the places where it is used.

Symbols			
<code>\Cutext</code>	2, 2, 3, 4, 4, 6, 7, 15, 16, 16, 16, 17, 17, 17, 17, 18, 19, 19, 22, 28	<code>convert-to-eV</code>	26
<code>\cuaddkeys</code>	8, 10, 11	<code>\cuaddkeys</code>	10
<code>\cuaddsinglekeys</code>	8, 10	<code>\cuaddsinglekeys</code>	10
<code>\cuaddtokeys</code>	8, 11	<code>\cuaddtokeys</code>	11
<code>\cuam</code>	3, 6, 6, 14, 14, 17, 17, 18, 19, 19, 23	<code>cuam-version</code>	17
<code>\cudfinekeys</code>	8, 8, 9	<code>\cudfinekeys</code>	9
<code>\cudfinename</code>	12	<code>\cudfinename</code>	12
<code>\cudfinesinglekey</code>	8, 8, 9	<code>\cudfinephrase</code>	14
<code>\cudfinesymbol</code>	13, 14	<code>\cudfinesinglekey</code>	9
<code>\culabel</code>	5, 5, 24	<code>\cudfinesymbol</code>	13
<code>\cunum</code>	2, 3, 3, 4, 4, 4, 16, 17, 17, 19, 19, 23	<code>\cusetup</code>	15
<code>\curef</code>	5, 5, 25	<code>cutext-change-unit</code>	16
<code>\cusetup</code>	3, 15	<code>cutext-space</code>	22
<code>\cutext</code>	2, 2, 3, 4, 4, 6, 7, 15, 16, 16, 16, 17, 17, 17, 17, 18, 19, 19, 22, 28	<code>cutext-to-cunum</code>	16
<code>\declarecookingunit</code>	8, 8, 8	<code>cutext-version</code>	17
<code>\newcookingunit</code>	8, 8, 8	D	
<code>\providecookingunit</code>	8, 8, 8	<code>decimal-mark</code>	12
		<code>\declarecookingunit</code>	8
A		E	
<code>add-option-for-<unit-key></code>	16	<code>erase-all-options</code>	16
<code>add-special-sign</code>	17	<code>eval-fraction</code>	21
<code>add-temperature-to-check</code>	25	F	
<code>amount-unit-space</code>	23	<code>fraction-command</code>	21
C		<code>fraction-inline</code>	21
<code>check-temperature</code>	25	G	
<code>\command</code>	21, 21, 21	<code>get-label</code>	25

L		R	
label	24	range-sign	19
M		recalculate-amount	23
mixed-fraction-space	22	ref	25
N		round-half	20
\newcookingunit	8	round-precision	20
\Numberstringnum	15	round-to-int	20
\numberstringnum	15	S	
O		set-cuttext-translation-message	17
one(f)	12	set-number-of-persons	24
one(m)	12	set-option-for-<unit-key>	16
one(n)	12	set-special-sign	17
P		set-unknown-message	17
parse-number	18	\space	22, 23
phrase-space	23	U	
print-numerals	17	unit	15
\providecookingunit	8	use-numerals	15
		use-numerals-below	18
		use-phrases	19
		\usepackage	15