

vxgcloudagent

1.3.2

Generated by Doxygen 1.8.17

1 VXG Cloud Agent Library	1
2 Build System	3
2.0.1 Overview	3
2.0.2 C++ Toolchain Requirements	3
2.0.3 Build system installation	3
3 Application Development	5
3.1 Overview	5
3.2 Examples	5
3.2.1 Minimal application example	5
3.2.2 Complete application example	7
3.2.3 Linking application against the VXG Agent Cloud Library	10
4 Library Compilation Guide	13
4.0.1 Library build process	13
4.0.2 Cross-compilation	13
5 Deprecated List	15
6 Hierarchical Index	17
6.1 Class Hierarchy	17
7 Data Structure Index	19
7.1 Data Structures	19
8 File Index	23
8.1 File List	23
9 Namespace Documentation	25
9.1 nlohmann Namespace Reference	25
9.2 std Namespace Reference	25
9.2.1 Function Documentation	43
9.2.1.1 make_unique()	43
9.3 vxg Namespace Reference	43
9.4 vxg::cloud Namespace Reference	44
9.4.1 Typedef Documentation	44
9.4.1.1 duration	44
9.4.1.2 time	45
9.4.1.3 timed_storage_ptr	45
9.4.2 Function Documentation	45
9.4.2.1 operator<()	45
9.5 vxg::cloud::agent Namespace Reference	45
9.5.1 Detailed Description	46
9.5.2 Typedef Documentation	47

9.5.2.1 event_manager_ptr	47
9.5.2.2 event_state_ptr	47
9.5.2.3 synchronizer_ptr	47
9.5.3 Function Documentation	47
9.5.3.1 version()	47
9.6 vxg::cloud::agent::media Namespace Reference	47
9.6.1 Typedef Documentation	48
9.6.1.1 stream_ptr	48
9.7 vxg::cloud::agent::proto Namespace Reference	48
9.7.1 Typedef Documentation	50
9.7.1.1 wifi_list	50
9.7.2 Enumeration Type Documentation	50
9.7.2.1 audio_file_format	50
9.7.2.2 audio_format	50
9.7.2.3 event_status	51
9.7.2.4 event_type	51
9.7.2.5 memorycard_status	52
9.7.2.6 mode	52
9.7.2.7 motion_region_shape	52
9.7.2.8 motion_sensitivity	53
9.7.2.9 ptz_action	53
9.7.2.10 ptz_preset_action	53
9.7.2.11 time_format_n	54
9.7.2.12 video_format	54
9.7.2.13 wifi_encryption	54
9.7.2.14 wifi_network_state	55
9.7.3 Function Documentation	55
9.7.3.1 name()	55
9.8 vxg::cloud::sync Namespace Reference	55
9.8.1 Typedef Documentation	56
9.8.1.1 timeline_ptr	56
9.9 vxg::cloud::time_spec Namespace Reference	56
9.9.1 Detailed Description	56
9.9.2 Typedef Documentation	56
9.9.2.1 duration	56
9.9.2.2 precision	57
9.9.2.3 precision_ratio	57
9.10 vxg::cloud::utils Namespace Reference	57
9.10.1 Typedef Documentation	58
9.10.1.1 queued_async_handler_ptr	58
9.10.2 Function Documentation	58
9.10.2.1 dirname()	58

9.10.2.2 random_string()	58
9.10.2.3 set_thread_name()	58
9.10.2.4 string_contains() [1/2]	58
9.10.2.5 string_contains() [2/2]	59
9.10.2.6 string_endswith()	59
9.10.2.7 string_format()	59
9.10.2.8 string_replace()	59
9.10.2.9 string_split()	59
9.10.2.10 string_startswith()	60
9.10.2.11 string_tolower()	60
9.10.2.12 string_toupper()	60
9.10.2.13 string_trim() [1/2]	60
9.10.2.14 string_trim() [2/2]	60
9.10.2.15 string_urldecode()	60
9.10.2.16 string_urlencode()	60
9.11 vxg::cloud::utils::gcc_abi Namespace Reference	61
9.11.1 Function Documentation	61
9.11.1.1 demangle()	61
9.12 vxg::cloud::utils::motion Namespace Reference	61
9.13 vxg::cloud::utils::time Namespace Reference	61
9.13.1 Function Documentation	62
9.13.1.1 epoch()	62
9.13.1.2 from_double()	62
9.13.1.3 from_iso()	62
9.13.1.4 from_iso2()	62
9.13.1.5 from_iso_packed()	62
9.13.1.6 is_iso()	62
9.13.1.7 is_iso_packed()	63
9.13.1.8 iso_time_valid()	63
9.13.1.9 max()	63
9.13.1.10 now()	63
9.13.1.11 now_ISO8601_UTC()	63
9.13.1.12 now_ISO8601_UTC_packed()	63
9.13.1.13 null()	63
9.13.1.14 to_double()	64
9.13.1.15 to_iso()	64
9.13.1.16 to_iso2()	64
9.13.1.17 to_iso_8601()	64
9.13.1.18 to_iso_local()	64
9.13.1.19 to_iso_packed()	64
9.14 vxg::media Namespace Reference	64
9.14.1 Typedef Documentation	65

9.14.1.1 rtsp_source_ptr	65
9.15 vxg::media::ffmpeg Namespace Reference	65
9.16 vxg::media::stream_error Namespace Reference	65
9.16.1 Detailed Description	66
9.16.2 Enumeration Type Documentation	66
9.16.2.1 error	66
9.16.2.2 origin	66
9.17 vxg::media::Streamer Namespace Reference	67
9.17.1 Typedef Documentation	67
9.17.1.1 on_error_cb	67
9.17.2 Enumeration Type Documentation	67
9.17.2.1 DropDirection	67
9.17.2.2 MediaType	68
9.17.2.3 StreamError	68
9.17.3 Variable Documentation	69
9.17.3.1 SINK_THREAD_PRIO	69
9.17.3.2 SRC_THREAD_PRIO	69
10 Data Structure Documentation	71
10.1 vxg::cloud::agent::access_token Struct Reference	71
10.1.1 Detailed Description	71
10.1.2 Member Typedef Documentation	72
10.1.2.1 ptr	72
10.1.3 Member Function Documentation	72
10.1.3.1 api_uri()	72
10.1.3.2 cam_base_uri()	72
10.1.3.3 pack()	72
10.1.3.4 parse()	72
10.2 alter_bool Struct Reference	73
10.2.1 Detailed Description	73
10.2.2 Member Enumeration Documentation	73
10.2.2.1 n_alter_bool	73
10.2.3 Constructor & Destructor Documentation	74
10.2.3.1 alter_bool() [1/2]	74
10.2.3.2 alter_bool() [2/2]	74
10.2.4 Member Function Documentation	74
10.2.4.1 operator bool()	74
10.2.4.2 operator=()	74
10.2.5 Friends And Related Function Documentation	75
10.2.5.1 from_json	75
10.2.5.2 to_json	75
10.2.6 Field Documentation	75

10.2.6.1 val	75
10.3 vxg::cloud::agent::proto::audio_caps Struct Reference	76
10.3.1 Detailed Description	76
10.3.2 Field Documentation	76
10.3.2.1 audio_file_formats	77
10.3.2.2 backward	77
10.3.2.3 backward_formats	77
10.3.2.4 echo_cancel	77
10.3.2.5 mic	77
10.3.2.6 spkr	78
10.4 vxg::cloud::agent::audio_config Struct Reference	78
10.4.1 Detailed Description	79
10.4.2 Field Documentation	79
10.4.2.1 caps	79
10.4.2.2 echo_cancel	79
10.4.2.3 mic_gain	79
10.4.2.4 mic_mute	79
10.4.2.5 spkr_mute	80
10.4.2.6 spkr_vol	80
10.5 vxg::cloud::agent::audio_detection_config::audio_detection_conf_caps Struct Reference	80
10.5.1 Detailed Description	81
10.5.2 Member Function Documentation	81
10.5.2.1 JSON_DEFINE_TYPE_INTRUSIVE()	81
10.5.3 Field Documentation	81
10.5.3.1 level	81
10.6 vxg::cloud::agent::audio_detection_config Struct Reference	82
10.6.1 Detailed Description	83
10.6.2 Member Function Documentation	83
10.6.2.1 JSON_DEFINE_TYPE_INTRUSIVE()	83
10.6.3 Field Documentation	83
10.6.3.1 caps	83
10.6.3.2 length	83
10.6.3.3 level	84
10.7 vxg::cloud::agent::proto::audio_stream_config Struct Reference	84
10.7.1 Detailed Description	85
10.7.2 Field Documentation	85
10.7.2.1 brt	85
10.7.2.2 format	85
10.7.2.3 srt	85
10.7.2.4 stream	85
10.8 vxg::media::Streamer::StreamInfo::AudioInfo Struct Reference	86
10.8.1 Detailed Description	86

10.8.2 Field Documentation	86
10.8.2.1 bitrate	87
10.8.2.2 channels	87
10.8.2.3 codec	87
10.8.2.4 extradata	87
10.8.2.5 samplerate	87
10.8.2.6 timebase	88
10.9 vxg::cloud::agent::callback Class Reference	88
10.9.1 Detailed Description	89
10.9.2 Member Typedef Documentation	89
10.9.2.1 ptr	89
10.9.3 Member Function Documentation	90
10.9.3.1 on_audio_file_play()	90
10.9.3.2 on_bye()	90
10.9.3.3 on_cam_ptz()	90
10.9.3.4 on_cam_ptz_preset()	91
10.9.3.5 on_cam_upgrade_firmware()	91
10.9.3.6 on_get_audio_detection()	92
10.9.3.7 on_get_cam_audio_config()	92
10.9.3.8 on_get_cam_video_config()	92
10.9.3.9 on_get_log()	93
10.9.3.10 on_get_memorycard_info()	93
10.9.3.11 on_get_motion_detection_config()	94
10.9.3.12 on_get_osd_config()	94
10.9.3.13 on_get_ptz_config()	94
10.9.3.14 on_get_timezone()	95
10.9.3.15 on_get_wifi_config()	95
10.9.3.16 on_raw_msg()	96
10.9.3.17 on_registered()	96
10.9.3.18 on_set_audio_detection()	96
10.9.3.19 on_set_cam_audio_config()	97
10.9.3.20 on_set_cam_video_config()	97
10.9.3.21 on_set_motion_detection_config()	97
10.9.3.22 on_set_osd_config()	98
10.9.3.23 on_set_timezone()	98
10.9.3.24 on_set_wifi_config()	99
10.9.3.25 on_start_backward_audio()	99
10.9.3.26 on_stop_backward_audio()	100
10.9.3.27 on_trigger_event()	100
10.10 vxg::cloud::agent::proto::stream_caps::caps_audio_object Struct Reference	100
10.10.1 Detailed Description	101
10.10.2 Field Documentation	101

10.10.2.1 brt	101
10.10.2.2 formats	101
10.10.2.3 srt	101
10.10.2.4 streams	102
10.11 vxg::cloud::agent::proto::stream_caps::caps_video_object Struct Reference	102
10.11.1 Detailed Description	103
10.11.2 Field Documentation	103
10.11.2.1 brt	103
10.11.2.2 formats	104
10.11.2.3 fps	104
10.11.2.4 gop	104
10.11.2.5 profiles	104
10.11.2.6 quality	104
10.11.2.7 resolutions	105
10.11.2.8 smoothing	105
10.11.2.9 streams	105
10.11.2.10 vbr	105
10.11.2.11 vbr_brt	105
10.12 vxg::cloud::cloud_storage Class Reference	106
10.12.1 Detailed Description	106
10.12.2 Constructor & Destructor Documentation	107
10.12.2.1 cloud_storage()	107
10.12.2.2 ~cloud_storage()	107
10.12.3 Member Function Documentation	107
10.12.3.1 erase()	107
10.12.3.2 list()	107
10.12.3.3 load()	108
10.12.3.4 store()	108
10.13 vxg::cloud::agent::event_manager::config Struct Reference	108
10.13.1 Detailed Description	108
10.13.2 Field Documentation	108
10.13.2.1 attach_qos_report_to_motion	109
10.13.2.2 send_qos_report_as_separate_event	109
10.13.2.3 send_qos_report_period_sec	109
10.13.2.4 stateful_event_continuation_kick_snapshot	109
10.14 vxg::cloud::agent::synchronizer::config Struct Reference	110
10.14.1 Detailed Description	110
10.14.2 Field Documentation	110
10.14.2.1 record_by_event_upload_step	110
10.15 vxg::cloud::agent::proto::event_caps Struct Reference	111
10.15.1 Detailed Description	111
10.15.2 Field Documentation	111

10.15.2.1 internal_hidden	112
10.15.2.2 periodic	112
10.15.2.3 snapshot	112
10.15.2.4 state_emulation	112
10.15.2.5 state_emulation_report_delay	112
10.15.2.6 stateful	113
10.15.2.7 stream	113
10.15.2.8 trigger	113
10.16 vxg::cloud::agent::event_config Struct Reference	113
10.16.1 Detailed Description	114
10.16.2 Member Function Documentation	114
10.16.2.1 caps_eq()	114
10.16.2.2 name()	115
10.16.2.3 name_eq()	115
10.16.3 Field Documentation	115
10.16.3.1 active	115
10.16.3.2 caps	116
10.16.3.3 custom_event_name	116
10.16.3.4 event	116
10.16.3.5 period	116
10.16.3.6 snapshot	116
10.16.3.7 stream	117
10.17 vxg::cloud::agent::event_manager Class Reference	117
10.17.1 Detailed Description	117
10.17.2 Member Typedef Documentation	117
10.17.2.1 event_state_report_cb_ptr	118
10.17.2.2 handle_event_payload_cb	118
10.17.3 Constructor & Destructor Documentation	118
10.17.3.1 event_manager()	118
10.17.3.2 ~event_manager()	118
10.17.4 Member Function Documentation	118
10.17.4.1 get_events()	118
10.17.4.2 notify_event()	119
10.17.4.3 set_events()	119
10.17.4.4 start()	119
10.17.4.5 stop()	119
10.17.4.6 trigger_event()	119
10.18 vxg::cloud::agent::event_state Class Reference	119
10.18.1 Detailed Description	120
10.18.2 Member Typedef Documentation	120
10.18.2.1 event_state_changed_cb_ptr	120
10.18.3 Member Enumeration Documentation	120

10.18.3.1 stream_delivery_mode	120
10.18.4 Constructor & Destructor Documentation	121
10.18.4.1 event_state() [1/3]	121
10.18.4.2 event_state() [2/3]	121
10.18.4.3 ~event_state()	121
10.18.4.4 event_state() [3/3]	121
10.18.5 Member Function Documentation	122
10.18.5.1 active()	122
10.18.5.2 config()	122
10.18.5.3 need_record()	122
10.18.5.4 operator=()	122
10.18.5.5 start() [1/2]	122
10.18.5.6 start() [2/2]	123
10.18.5.7 stateful()	123
10.18.5.8 stop() [1/2]	123
10.18.5.9 stop() [2/2]	123
10.18.6 Friends And Related Function Documentation	123
10.18.6.1 swap	123
10.19 vxg::cloud::agent::event_state::event_state_changed_cb Struct Reference	124
10.19.1 Detailed Description	124
10.19.2 Constructor & Destructor Documentation	124
10.19.2.1 event_state_changed_cb()	124
10.19.2.2 ~event_state_changed_cb()	124
10.19.3 Member Function Documentation	124
10.19.3.1 on_ongoing()	125
10.19.3.2 on_started()	125
10.19.3.3 on_stopped()	125
10.19.3.4 on_triggered()	125
10.20 vxg::cloud::agent::event_manager::event_state_report_cb Struct Reference	126
10.20.1 Detailed Description	126
10.20.2 Constructor & Destructor Documentation	126
10.20.2.1 event_state_report_cb()	127
10.20.2.2 ~event_state_report_cb()	127
10.20.3 Member Function Documentation	127
10.20.3.1 on_event_continue()	127
10.20.3.2 on_event_start()	127
10.20.3.3 on_event_stop()	127
10.20.3.4 on_event_trigger()	128
10.20.3.5 on_need_stream_sync_continue()	128
10.20.3.6 on_need_stream_sync_start()	128
10.20.3.7 on_need_stream_sync_stop()	128
10.21 vxg::cloud::agent::event_stream Class Reference	128

10.21.1 Detailed Description	129
10.21.2 Member Typedef Documentation	129
10.21.2.1 ptr	129
10.21.3 Constructor & Destructor Documentation	130
10.21.3.1 event_stream()	130
10.21.3.2 ~event_stream()	131
10.21.4 Member Function Documentation	131
10.21.4.1 finit()	131
10.21.4.2 get_events()	131
10.21.4.3 init()	132
10.21.4.4 notify()	132
10.21.4.5 set_events()	132
10.21.4.6 set_trigger_recording()	133
10.21.4.7 start()	133
10.21.4.8 stop()	134
10.21.4.9 trigger_event()	134
10.22 vxg::cloud::agent::events_config Struct Reference	134
10.22.1 Detailed Description	135
10.22.2 Member Function Documentation	135
10.22.2.1 get_event_config()	135
10.22.3 Field Documentation	136
10.22.3.1 enabled	136
10.22.3.2 events	136
10.23 vxg::media::Streamer::ISink Class Reference	137
10.23.1 Detailed Description	138
10.23.2 Member Typedef Documentation	138
10.23.2.1 ptr	138
10.23.2.2 PtrU	139
10.23.3 Constructor & Destructor Documentation	139
10.23.3.1 ISink()	139
10.23.3.2 ~ISink()	139
10.23.4 Member Function Documentation	139
10.23.4.1 droppable()	139
10.23.4.2 duration()	140
10.23.4.3 error()	140
10.23.4.4 finit()	140
10.23.4.5 init()	141
10.23.4.6 name()	142
10.23.4.7 negotiate()	142
10.23.4.8 process()	143
10.23.4.9 set_eos()	143
10.23.4.10 set_eos_cb()	143

10.23.4.11 set_error_cb()	143
10.23.5 Field Documentation	143
10.23.5.1 on_error_cb_	144
10.24 vxg::media::Streamer::ISource Class Reference	144
10.24.1 Detailed Description	145
10.24.2 Member Typedef Documentation	145
10.24.2.1 ptr	145
10.24.3 Member Enumeration Documentation	146
10.24.3.1 Mode	146
10.24.4 Constructor & Destructor Documentation	147
10.24.4.1 ISource()	147
10.24.5 Member Function Documentation	147
10.24.5.1 error()	147
10.24.5.2 finit()	148
10.24.5.3 init()	148
10.24.5.4 name()	148
10.24.5.5 negotiate()	149
10.24.5.6 pullFrame()	149
10.24.5.7 pushFrame()	149
10.24.5.8 set_error_cb()	150
10.24.6 Field Documentation	150
10.24.6.1 mode_	150
10.24.6.2 on_error_cb_	150
10.25 vxg::cloud::timed_storage::item Struct Reference	150
10.25.1 Detailed Description	151
10.25.2 Member Enumeration Documentation	152
10.25.2.1 data_state	152
10.25.3 Constructor & Destructor Documentation	152
10.25.3.1 item() [1/3]	152
10.25.3.2 item() [2/3]	152
10.25.3.3 item() [3/3]	152
10.25.4 Member Function Documentation	153
10.25.4.1 clear()	153
10.25.4.2 empty()	153
10.25.4.3 operator<()	153
10.25.5 Field Documentation	153
10.25.5.1 category	153
10.25.5.2 data	153
10.25.5.3 media_type	154
10.25.5.4 state	154
10.26 vxg::logger Class Reference	154
10.26.1 Detailed Description	155

10.26.2 Member Typedef Documentation	155
10.26.2.1 logger_ptr	155
10.26.3 Member Enumeration Documentation	156
10.26.3.1 loglevel	156
10.26.4 Member Function Documentation	156
10.26.4.1 critical()	156
10.26.4.2 debug() [1/2]	156
10.26.4.3 debug() [2/2]	157
10.26.4.4 error() [1/2]	157
10.26.4.5 error() [2/2]	157
10.26.4.6 info() [1/2]	157
10.26.4.7 info() [2/2]	158
10.26.4.8 instance()	158
10.26.4.9 reset() [1/2]	158
10.26.4.10 reset() [2/2]	159
10.26.4.11 set_level()	159
10.26.4.12 trace() [1/2]	160
10.26.4.13 trace() [2/2]	160
10.26.4.14 warn() [1/2]	160
10.26.4.15 warn() [2/2]	160
10.27 vxg::cloud::agent::manager Class Reference	161
10.27.1 Detailed Description	163
10.27.2 Member Typedef Documentation	163
10.27.2.1 direct_upload_payload_map	163
10.27.2.2 direct_upload_payload_map_ptr	163
10.27.2.3 ptr	164
10.27.3 Member Function Documentation	164
10.27.3.1 __notify_record_event()	164
10.27.3.2 _update_storage_status()	164
10.27.3.3 create()	164
10.27.3.4 handle_event()	165
10.27.3.5 handle_event_meta_file()	165
10.27.3.6 handle_event_snapshot()	165
10.27.3.7 on_audio_file_play()	165
10.27.3.8 on_cam_memorycard_recording()	165
10.27.3.9 on_cam_memorycard_synchronize()	165
10.27.3.10 on_cam_memorycard_synchronize_cancel()	166
10.27.3.11 on_cam_ptz()	166
10.27.3.12 on_cam_ptz_preset()	166
10.27.3.13 on_cam_upgrade_firmware()	166
10.27.3.14 on_closed()	166
10.27.3.15 on_direct_upload_url()	166

10.27.3.16	on_get_audio_detection()	167
10.27.3.17	on_get_cam_audio_config()	167
10.27.3.18	on_get_cam_events_config()	167
10.27.3.19	on_get_cam_memorycard_timeline()	167
10.27.3.20	on_get_cam_video_config()	167
10.27.3.21	on_get_log()	167
10.27.3.22	on_get_motion_detection_config()	167
10.27.3.23	on_get_osd_config()	168
10.27.3.24	on_get_ptz_config()	168
10.27.3.25	on_get_stream_by_event()	168
10.27.3.26	on_get_stream_caps()	168
10.27.3.27	on_get_stream_config()	168
10.27.3.28	on_get_supported_streams()	168
10.27.3.29	on_get_timezone()	168
10.27.3.30	on_get_wifi_config()	169
10.27.3.31	on_prepared()	169
10.27.3.32	on_raw_message()	169
10.27.3.33	on_registered()	169
10.27.3.34	on_set_activity()	169
10.27.3.35	on_set_audio_detection()	169
10.27.3.36	on_set_cam_audio_config()	169
10.27.3.37	on_set_cam_events_config()	170
10.27.3.38	on_set_cam_video_config()	170
10.27.3.39	on_set_log_enable()	170
10.27.3.40	on_set_motion_detection_config()	170
10.27.3.41	on_set_osd_config()	170
10.27.3.42	on_set_periodic_events()	170
10.27.3.43	on_set_stream_by_event()	170
10.27.3.44	on_set_stream_config()	171
10.27.3.45	on_set_timezone()	171
10.27.3.46	on_set_wifi_config()	171
10.27.3.47	on_start_backward()	171
10.27.3.48	on_stop_backward()	171
10.27.3.49	on_stream_start()	171
10.27.3.50	on_stream_stop()	172
10.27.3.51	on_trigger_event()	172
10.27.3.52	on_update_preview()	172
10.27.3.53	start()	172
10.27.3.54	stop()	172
10.28	vxg::cloud::utils::motion::map Struct Reference	173
10.28.1	Detailed Description	173
10.28.2	Constructor & Destructor Documentation	174

10.28.2.1 map() [1/2]	174
10.28.2.2 map() [2/2]	174
10.28.3 Member Function Documentation	174
10.28.3.1 operator=()	174
10.28.3.2 pack()	174
10.28.3.3 unpack()	174
10.29 vxg::media::Streamer::MediaFrame Struct Reference	175
10.29.1 Detailed Description	176
10.29.2 Member Function Documentation	176
10.29.2.1 operator<()	176
10.29.3 Field Documentation	176
10.29.3.1 data	176
10.29.3.2 dts	177
10.29.3.3 duration	177
10.29.3.4 is_key	177
10.29.3.5 len	177
10.29.3.6 NOPTS	177
10.29.3.7 pts	178
10.29.3.8 time_realtime	178
10.29.3.9 timescale	178
10.29.3.10 type	178
10.30 vxg::cloud::agent::proto::motion_detection_caps Struct Reference	178
10.30.1 Detailed Description	179
10.30.2 Field Documentation	179
10.30.2.1 max_regions	179
10.30.2.2 region_shape	179
10.30.2.3 sensitivity	179
10.31 vxg::cloud::agent::proto::motion_detection_config Struct Reference	180
10.31.1 Detailed Description	180
10.31.2 Field Documentation	180
10.31.2.1 caps	180
10.31.2.2 columns	181
10.31.2.3 regions	181
10.31.2.4 rows	181
10.32 vxg::cloud::agent::proto::motion_region Struct Reference	181
10.32.1 Detailed Description	182
10.32.2 Field Documentation	182
10.32.2.1 enabled	182
10.32.2.2 map	182
10.32.2.3 region	183
10.32.2.4 sensitivity	183
10.33 vxg::logger::options Struct Reference	183

10.33.1 Detailed Description	184
10.33.2 Field Documentation	184
10.33.2.1 crash_logfile_path	184
10.33.2.2 default_loglevel	184
10.33.2.3 log_pattern	184
10.33.2.4 logfile_max_files	185
10.33.2.5 logfile_max_size	185
10.33.2.6 logfile_path	185
10.33.2.7 syslog_ident	185
10.33.2.8 tcp_logsink_enabled	185
10.33.2.9 tcp_logsink_host	185
10.33.2.10 tcp_logsink_port	186
10.34 vxg::cloud::agent::proto::osd_caps Struct Reference	186
10.34.1 Detailed Description	187
10.34.2 Field Documentation	187
10.34.2.1 alignment	187
10.34.2.2 bkg_color	187
10.34.2.3 bkg_transp	187
10.34.2.4 date	188
10.34.2.5 date_format	188
10.34.2.6 font_color	188
10.34.2.7 font_size	188
10.34.2.8 system_id	189
10.34.2.9 system_id_text	189
10.34.2.10 time	189
10.34.2.11 time_format	189
10.35 vxg::cloud::agent::osd_config Struct Reference	190
10.35.1 Detailed Description	191
10.35.2 Field Documentation	191
10.35.2.1 alignment	191
10.35.2.2 bkg_color	191
10.35.2.3 bkg_transp	191
10.35.2.4 caps	191
10.35.2.5 date	192
10.35.2.6 date_format	192
10.35.2.7 font_color	192
10.35.2.8 font_size	192
10.35.2.9 system_id	192
10.35.2.10 system_id_text	193
10.35.2.11 time	193
10.35.2.12 time_format	193
10.36 vxg::cloud::period Struct Reference	193

10.36.1 Detailed Description	194
10.36.2 Constructor & Destructor Documentation	194
10.36.2.1 period() [1/2]	195
10.36.2.2 period() [2/2]	195
10.36.3 Member Function Documentation	195
10.36.3.1 clear()	195
10.36.3.2 duration()	195
10.36.3.3 intersects()	195
10.36.3.4 is_null()	196
10.36.3.5 is_open()	196
10.36.3.6 is_valid()	196
10.36.3.7 operator<()	196
10.36.4 Field Documentation	196
10.36.4.1 begin	196
10.36.4.2 end	197
10.37 vxg::cloud::agent::access_token::proxy_config Struct Reference	197
10.37.1 Detailed Description	197
10.37.2 Field Documentation	198
10.37.2.1 socks4	198
10.37.2.2 socks5	198
10.38 vxg::cloud::agent::ptz_command Struct Reference	198
10.38.1 Detailed Description	198
10.38.2 Field Documentation	199
10.38.2.1 action	199
10.38.2.2 tm	199
10.39 vxg::cloud::agent::ptz_config Struct Reference	199
10.39.1 Detailed Description	200
10.39.2 Field Documentation	200
10.39.2.1 actions	200
10.39.2.2 maximum_number_of_presets	200
10.39.2.3 presets	201
10.40 vxg::cloud::agent::ptz_preset Struct Reference	201
10.40.1 Detailed Description	201
10.40.2 Field Documentation	202
10.40.2.1 action	202
10.40.2.2 name	202
10.40.2.3 token	202
10.41 vxg::cloud::utils::queued_async_handler< T > Class Template Reference	202
10.41.1 Detailed Description	203
10.41.2 Member Typedef Documentation	203
10.41.2.1 handler_func	203
10.41.3 Constructor & Destructor Documentation	203

10.41.3.1 <code>queued_async_handler()</code>	203
10.41.3.2 <code>~queued_async_handler()</code>	203
10.41.4 Member Function Documentation	204
10.41.4.1 <code>get_handler()</code>	204
10.41.4.2 <code>push()</code>	204
10.41.4.3 <code>set_handler()</code>	204
10.41.4.4 <code>start()</code>	204
10.41.4.5 <code>stop()</code>	204
10.42 <code>vxg::media::stream_error::report</code> Struct Reference	205
10.42.1 Detailed Description	205
10.42.2 Field Documentation	205
10.42.2.1 <code>code</code>	205
10.42.2.2 <code>from</code>	205
10.43 <code>vxg::media::rtmp_sink</code> Class Reference	206
10.43.1 Detailed Description	207
10.43.2 Constructor & Destructor Documentation	207
10.43.2.1 <code>rtmp_sink()</code>	207
10.43.3 Member Function Documentation	207
10.43.3.1 <code>droppable()</code>	207
10.43.3.2 <code>init()</code>	208
10.43.3.3 <code>name()</code>	209
10.43.3.4 <code>negotiate()</code>	209
10.44 <code>vxg::media::rtmp_source</code> Class Reference	210
10.44.1 Detailed Description	211
10.44.2 Member Function Documentation	211
10.44.2.1 <code>init()</code>	211
10.45 <code>vxg::media::rtsp_source</code> Class Reference	212
10.45.1 Detailed Description	214
10.45.2 Member Enumeration Documentation	214
10.45.2.1 <code>transport</code>	214
10.45.3 Constructor & Destructor Documentation	214
10.45.3.1 <code>rtsp_source()</code>	214
10.45.4 Member Function Documentation	215
10.45.4.1 <code>__transport_to_ff()</code>	215
10.45.4.2 <code>init()</code>	215
10.45.4.3 <code>name()</code>	216
10.45.5 Field Documentation	216
10.45.5.1 <code>ffmpeg_opts_</code>	216
10.46 <code>vxg::cloud::agent::media::rtsp_stream</code> Class Reference	216
10.46.1 Detailed Description	217
10.46.2 Member Typedef Documentation	217
10.46.2.1 <code>ptr</code>	217

10.46.3 Constructor & Destructor Documentation	217
10.46.3.1 rtsp_stream()	217
10.46.3.2 ~rtsp_stream()	218
10.46.4 Member Function Documentation	218
10.46.4.1 start()	218
10.47 vxg::cloud::agent::synchronizer::segmenter Struct Reference	219
10.47.1 Detailed Description	220
10.47.2 Member Typedef Documentation	220
10.47.2.1 ptr	220
10.47.3 Constructor & Destructor Documentation	220
10.47.3.1 ~segmenter()	220
10.47.4 Member Function Documentation	221
10.47.4.1 intersects()	221
10.47.4.2 operator<()	221
10.47.5 Field Documentation	221
10.47.5.1 canceled	221
10.47.5.2 chunks_done	221
10.47.5.3 chunks_failed	221
10.47.5.4 chunks_planned	222
10.47.5.5 cur_seg_start	222
10.47.5.6 cur_seg_stop	222
10.47.5.7 delay	222
10.47.5.8 final_sync_status_reported	222
10.47.5.9 finished	222
10.47.5.10 last_processed_time	223
10.47.5.11 processed	223
10.47.5.12 realtime	223
10.47.5.13 step	223
10.47.5.14 sync_status_cb	223
10.47.5.15 ticket	223
10.48 vxg::media::ffmpeg::Sink Class Reference	224
10.48.1 Detailed Description	225
10.48.2 Constructor & Destructor Documentation	225
10.48.2.1 Sink()	225
10.48.2.2 ~Sink()	225
10.48.3 Member Function Documentation	226
10.48.3.1 droppable()	226
10.48.3.2 duration()	226
10.48.3.3 error()	226
10.48.3.4 finit()	227
10.48.3.5 init() [1/2]	227
10.48.3.6 init() [2/2]	228

10.48.3.7 name()	228
10.48.3.8 negotiate()	228
10.48.3.9 stop()	229
10.49 vxg::media::ffmpeg::Source Class Reference	229
10.49.1 Detailed Description	230
10.49.2 Constructor & Destructor Documentation	231
10.49.2.1 Source()	231
10.49.2.2 ~Source()	231
10.49.3 Member Function Documentation	231
10.49.3.1 finit()	231
10.49.3.2 init() [1/3]	231
10.49.3.3 init() [2/3]	232
10.49.3.4 init() [3/3]	232
10.49.3.5 name()	233
10.49.3.6 negotiate()	233
10.49.3.7 pullFrame()	233
10.49.3.8 stop()	234
10.50 vxg::media::stream Class Reference	234
10.50.1 Detailed Description	236
10.50.2 Member Typedef Documentation	236
10.50.2.1 on_error_cb	236
10.50.2.2 ptr	236
10.50.3 Constructor & Destructor Documentation	236
10.50.3.1 stream()	236
10.50.3.2 ~stream()	237
10.50.4 Member Function Documentation	237
10.50.4.1 finit_sink()	237
10.50.4.2 finit_source()	237
10.50.4.3 init_sink()	237
10.50.4.4 init_source()	238
10.50.4.5 set_on_error_cb()	238
10.50.5 Field Documentation	239
10.50.5.1 sink_	239
10.50.5.2 source_	239
10.51 vxg::cloud::agent::media::stream Class Reference	239
10.51.1 Detailed Description	240
10.51.2 Member Typedef Documentation	240
10.51.2.1 ptr	240
10.51.3 Constructor & Destructor Documentation	240
10.51.3.1 stream()	240
10.51.3.2 ~stream()	241
10.52 vxg::cloud::agent::media::stream_callbacks Class Reference	241

10.52.1 Detailed Description	242
10.52.2 Constructor & Destructor Documentation	242
10.52.2.1 stream_callbacks()	242
10.52.2.2 ~stream_callbacks()	243
10.52.3 Member Function Documentation	243
10.52.3.1 get_snapshot()	243
10.52.3.2 get_stream_caps()	243
10.52.3.3 get_stream_config()	244
10.52.3.4 get_supported_stream()	244
10.52.3.5 record_export()	245
10.52.3.6 record_get_list()	245
10.52.3.7 record_needs_source()	246
10.52.3.8 set_stream_config()	246
10.52.3.9 start_record()	246
10.52.3.10 stop_record()	247
10.53 vxg::cloud::agent::media::stream_callbacks_stub Class Reference	247
10.53.1 Detailed Description	248
10.53.2 Constructor & Destructor Documentation	248
10.53.2.1 stream_callbacks_stub()	249
10.53.2.2 ~stream_callbacks_stub()	249
10.53.3 Member Function Documentation	249
10.53.3.1 get_snapshot()	249
10.53.3.2 get_stream_caps()	249
10.53.3.3 get_stream_config()	250
10.53.3.4 get_supported_stream()	250
10.53.3.5 record_export()	250
10.53.3.6 record_get_list()	251
10.53.3.7 set_stream_config()	251
10.53.3.8 start_record()	252
10.53.3.9 stop_record()	252
10.54 vxg::cloud::agent::proto::stream_caps Struct Reference	253
10.54.1 Detailed Description	253
10.54.2 Field Documentation	253
10.54.2.1 caps_audio	254
10.54.2.2 caps_video	254
10.55 vxg::cloud::agent::proto::stream_config Struct Reference	254
10.55.1 Detailed Description	255
10.55.2 Field Documentation	255
10.55.2.1 audio	255
10.55.2.2 video	255
10.56 vxg::cloud::stream_storage Class Reference	255
10.56.1 Detailed Description	256

10.56.2 Member Typedef Documentation	256
10.56.2.1 ptr	256
10.56.3 Constructor & Destructor Documentation	257
10.56.3.1 stream_storage()	257
10.56.3.2 ~stream_storage()	257
10.56.4 Member Function Documentation	257
10.56.4.1 erase()	257
10.56.4.2 list()	257
10.56.4.3 load()	258
10.56.4.4 store()	258
10.56.4.5 store_async()	258
10.57 vxg::media::Streamer::StreamInfo Struct Reference	258
10.57.1 Detailed Description	259
10.57.2 Member Enumeration Documentation	259
10.57.2.1 AudioCodec	259
10.57.2.2 DataCodec	260
10.57.2.3 StreamType	260
10.57.2.4 VideoCodec	261
10.57.3 Field Documentation	261
10.57.3.1 audio	261
10.57.3.2 type	261
10.57.3.3 video	261
10.58 vxg::cloud::agent::supported_stream_config Struct Reference	262
10.58.1 Detailed Description	262
10.58.2 Field Documentation	262
10.58.2.1 audio	262
10.58.2.2 id	263
10.58.2.3 video	263
10.59 vxg::cloud::agent::supported_streams_config Struct Reference	263
10.59.1 Detailed Description	264
10.59.2 Field Documentation	264
10.59.2.1 audio_es	264
10.59.2.2 streams	264
10.59.2.3 video_es	264
10.60 vxg::cloud::agent::synchronizer::sync_request Struct Reference	265
10.60.1 Detailed Description	265
10.60.2 Field Documentation	265
10.60.2.1 segmenter	265
10.61 vxg::cloud::agent::synchronizer Class Reference	265
10.61.1 Detailed Description	266
10.61.2 Member Typedef Documentation	266
10.61.2.1 ptr	266

10.61.2.2 segmenter_ptr	267
10.61.2.3 sync_request_ptr	267
10.61.2.4 sync_status_report_cb	267
10.61.3 Member Enumeration Documentation	267
10.61.3.1 sync_request_status	267
10.61.4 Member Function Documentation	267
10.61.4.1 create()	268
10.61.4.2 start()	268
10.61.4.3 stop()	268
10.61.4.4 sync()	268
10.61.4.5 sync_cancel()	268
10.61.4.6 sync_finalize()	269
10.62 vxg::cloud::timed_storage Class Reference	269
10.62.1 Detailed Description	270
10.62.2 Member Typedef Documentation	270
10.62.2.1 async_store_finished_cb	270
10.62.2.2 async_store_is_canceled_cb	270
10.62.2.3 item_ptr	270
10.62.3 Constructor & Destructor Documentation	270
10.62.3.1 timed_storage()	270
10.62.3.2 ~timed_storage()	270
10.62.4 Member Function Documentation	271
10.62.4.1 erase()	271
10.62.4.2 finit()	271
10.62.4.3 init()	271
10.62.4.4 list()	271
10.62.4.5 load()	271
10.62.4.6 store()	272
10.62.4.7 store_async()	272
10.63 vxg::cloud::timeline< T > Class Template Reference	272
10.63.1 Detailed Description	272
10.63.2 Constructor & Destructor Documentation	272
10.63.2.1 timeline() [1/2]	273
10.63.2.2 timeline() [2/2]	273
10.63.3 Member Function Documentation	273
10.63.3.1 _squash_periods()	273
10.63.3.2 slices()	273
10.64 vxg::cloud::sync::timeline Class Reference	273
10.64.1 Detailed Description	274
10.64.2 Member Typedef Documentation	274
10.64.2.1 async_store_finished_cb	274
10.64.2.2 async_store_is_canceled_cb	274

10.64.3 Constructor & Destructor Documentation	274
10.64.3.1 timeline()	275
10.64.3.2 ~timeline()	275
10.64.4 Member Function Documentation	275
10.64.4.1 _squash_periods()	275
10.64.4.2 finit()	275
10.64.4.3 init()	275
10.64.4.4 list()	276
10.64.4.5 load()	276
10.64.4.6 slices()	276
10.64.4.7 store()	276
10.64.4.8 store_async()	276
10.65 vxg::cloud::utils::uri Struct Reference	277
10.65.1 Detailed Description	277
10.65.2 Member Function Documentation	277
10.65.2.1 parse()	278
10.65.3 Field Documentation	278
10.65.3.1 fragment	278
10.65.3.2 host	278
10.65.3.3 password	278
10.65.3.4 path	278
10.65.3.5 port	279
10.65.3.6 query	279
10.65.3.7 scheme	279
10.65.3.8 user	279
10.66 vxg::cloud::agent::proto::video_caps Struct Reference	279
10.66.1 Detailed Description	280
10.66.2 Field Documentation	280
10.66.2.1 brightness	280
10.66.2.2 contrast	281
10.66.2.3 horz_flip	281
10.66.2.4 ir_light	281
10.66.2.5 nr_level	281
10.66.2.6 nr_type	281
10.66.2.7 pwr_frequency	282
10.66.2.8 saturation	282
10.66.2.9 sharpness	282
10.66.2.10 tdn	282
10.66.2.11 vert_flip	282
10.66.2.12 wb_type	283
10.67 vxg::cloud::agent::proto::video_clip_info Struct Reference	283
10.67.1 Detailed Description	284

10.67.2 Field Documentation	284
10.67.2.1 data	284
10.67.2.2 local_start	284
10.67.2.3 local_stop	284
10.67.2.4 tp_start	284
10.67.2.5 tp_stop	285
10.67.2.6 video_height	285
10.67.2.7 video_width	285
10.68 vxg::cloud::agent::proto::video_config Struct Reference	285
10.68.1 Detailed Description	287
10.68.2 Field Documentation	287
10.68.2.1 brightness	287
10.68.2.2 caps	287
10.68.2.3 contrast	287
10.68.2.4 horz_flip	288
10.68.2.5 ir_light	288
10.68.2.6 nr_level	288
10.68.2.7 nr_type	288
10.68.2.8 pwr_frequency	288
10.68.2.9 saturation	289
10.68.2.10 sharpness	289
10.68.2.11 tdn	289
10.68.2.12 vert_flip	289
10.68.2.13 wb_type	289
10.69 vxg::cloud::agent::proto::video_stream_config Struct Reference	290
10.69.1 Detailed Description	291
10.69.2 Field Documentation	291
10.69.2.1 brt	291
10.69.2.2 format	291
10.69.2.3 fps	291
10.69.2.4 gop	291
10.69.2.5 horz	292
10.69.2.6 profile	292
10.69.2.7 quality	292
10.69.2.8 smoothing	292
10.69.2.9 stream	292
10.69.2.10 vbr	293
10.69.2.11 vbr_brt	293
10.69.2.12 vert	293
10.70 vxg::media::Streamer::StreamInfo::VideoInfo Struct Reference	293
10.70.1 Detailed Description	294
10.70.2 Field Documentation	294

10.70.2.1 bitrate	294
10.70.2.2 codec	294
10.70.2.3 extradata	295
10.70.2.4 framerate	295
10.70.2.5 height	295
10.70.2.6 timebase	295
10.70.2.7 width	295
10.71 vxg::cloud::agent::proto::wifi_config Struct Reference	296
10.71.1 Detailed Description	296
10.71.2 Field Documentation	296
10.71.2.1 networks	296
10.72 vxg::cloud::agent::proto::wifi_network Struct Reference	297
10.72.1 Detailed Description	297
10.72.2 Field Documentation	297
10.72.2.1 encryption	298
10.72.2.2 encryption_caps	298
10.72.2.3 mac	298
10.72.2.4 password	298
10.72.2.5 signal	298
10.72.2.6 ssid	298
11 File Documentation	299
11.1 app-dev.md File Reference	299
11.2 arm-example.txt File Reference	299
11.3 base_streamer.h File Reference	299
11.3.1 Macro Definition Documentation	301
11.3.1.1 __BASE_STREAMER_H	301
11.4 build-system.md File Reference	301
11.5 callback.h File Reference	301
11.6 caps.h File Reference	302
11.6.1 Macro Definition Documentation	304
11.6.1.1 ignore_exception	305
11.6.2 Typedef Documentation	305
11.6.2.1 json	305
11.7 cloud-agent-minimal.cc File Reference	305
11.7.1 Function Documentation	306
11.7.1.1 main()	306
11.7.1.2 parse_args()	306
11.7.1.3 signal_handler()	306
11.7.2 Variable Documentation	306
11.7.2.1 agent_config	306
11.7.2.2 props	307

11.7.2.3 quit	307
11.7.2.4 rtsp_url	307
11.7.2.5 vxg_cloud_token	307
11.8 cloud-agent.cc File Reference	307
11.8.1 Function Documentation	308
11.8.1.1 main()	308
11.8.1.2 parse_args()	308
11.8.1.3 signal_handler()	309
11.8.2 Variable Documentation	309
11.8.2.1 agent_config	309
11.8.2.2 props	309
11.8.2.3 quit	309
11.8.2.4 rtsp_url	309
11.8.2.5 vxg_cloud_token	310
11.9 compile.md File Reference	310
11.10 config.h File Reference	310
11.10.1 Detailed Description	313
11.11 event-manager.h File Reference	313
11.12 event-state.h File Reference	314
11.13 event-stream.h File Reference	315
11.14 ffmpeg_sink.h File Reference	316
11.15 ffmpeg_source.cc File Reference	317
11.16 ffmpeg_source.h File Reference	317
11.17 logging.h File Reference	318
11.18 mainpage.md File Reference	319
11.19 manager.h File Reference	319
11.20 meson.build File Reference	320
11.21 queued-handler.h File Reference	320
11.22 rtmp_sink.h File Reference	322
11.22.1 Detailed Description	323
11.23 rtmp_source.h File Reference	323
11.23.1 Detailed Description	323
11.24 rtsp-stream.h File Reference	323
11.25 rtsp_source.h File Reference	324
11.25.1 Detailed Description	325
11.26 stream-storage.h File Reference	325
11.27 stream.h File Reference	326
11.28 stream.h File Reference	327
11.29 timeline-synchronizer.h File Reference	328
11.30 timeline.h File Reference	330
11.31 unset-helper.h File Reference	331
11.31.1 Function Documentation	333

11.31.1.1 <code>__is_unset()</code> [1/2]	333
11.31.1.2 <code>__is_unset()</code> [2/2]	334
11.31.1.3 <code>__is_unset< alter_bool >()</code>	334
11.31.1.4 <code>__is_unset< double >()</code>	334
11.31.1.5 <code>__is_unset< int >()</code>	334
11.31.1.6 <code>__is_unset< nlohmann::json >()</code>	335
11.31.1.7 <code>__is_unset< std::nullptr_t >()</code>	335
11.31.1.8 <code>__is_unset< std::string >()</code>	335
11.31.1.9 <code>__is_unset< vxg::cloud::duration >()</code>	336
11.31.1.10 <code>__is_unset< vxg::cloud::time >()</code>	336
11.31.1.11 <code>unset_value_for()</code>	336
11.31.1.12 <code>unset_value_for_impl()</code> [1/10]	336
11.31.1.13 <code>unset_value_for_impl()</code> [2/10]	337
11.31.1.14 <code>unset_value_for_impl()</code> [3/10]	337
11.31.1.15 <code>unset_value_for_impl()</code> [4/10]	337
11.31.1.16 <code>unset_value_for_impl()</code> [5/10]	337
11.31.1.17 <code>unset_value_for_impl()</code> [6/10]	337
11.31.1.18 <code>unset_value_for_impl()</code> [7/10]	338
11.31.1.19 <code>unset_value_for_impl()</code> [8/10]	338
11.31.1.20 <code>unset_value_for_impl()</code> [9/10]	338
11.31.1.21 <code>unset_value_for_impl()</code> [10/10]	338
11.31.2 Variable Documentation	338
11.31.2.1 <code>UnsetDouble</code>	338
11.31.2.2 <code>UnsetDuration</code>	339
11.31.2.3 <code>UnsetFloat</code>	339
11.31.2.4 <code>UnsetInt</code>	339
11.31.2.5 <code>UnsetInt64</code>	339
11.31.2.6 <code>UnsetString</code>	339
11.31.2.7 <code>UnsetTime</code>	339
11.31.2.8 <code>UnsetUInt64</code>	340
11.32 <code>utils.h</code> File Reference	340

Chapter 1

VXG Cloud Agent Library

1. [Build system](#)
2. [Library compilation](#)
3. [Application development](#)
4. [API reference](#)

Chapter 2

Build System

2.0.1 Overview

VXG Cloud Agent library uses [Meson](#) build system as a modern, fast and flexible build system that supports easy to set up and maintain a cross-compilation process.

It's recommended to refer to the [Meson](#) guide.

2.0.2 C++ Toolchain Requirements

IMPORTANT: This projects requires C++ toolchain with C++11 support

VXG Cloud Agent Library requires modern C++11 so in order to build and use this library the user needs a compiler with C++11 support.

GCC [supports](#) C++11 since version 4.8.1 released on May 31, 2013.

C++11 Support in GCC

GCC 4.8.1 was the first feature-complete implementation of the 2011 C++ standard, previously known as C++0x.

This mode can be selected with the `-std=c++11` command-line flag, or `-std=gnu++11` to enable GNU extensions as well.

2.0.3 Build system installation

IMPORTANT: This projects requires Meson version `>= 0.56.0`

It's recommended to use [Ubuntu 20.04 LTS](#) distribution in development process but other distributions or operation systems are also supported by [Meson](#).

Please refer to [Meson installation guide](#) to get and install Meson, preferable way to install Meson is `pip` method.

Quick install guide for Ubuntu 20.04. If you have an old version of meson already installed please remove it first.

```
sudo apt-get update
sudo apt-get install -y python3-pip git ninja-build curl tzdata python3-tz
pip3 install git+https://github.com/mesonbuild/meson@0.56.0
# pip3 puts meson main script into the $HOME/.local/bin/ directory, you need to
# add $HOME/.local/bin/ into your PATH environment variable, for bash shell you
# can run the following command and restart the shell session.
echo 'export PATH=$HOME/.local/bin:$PATH' » $HOME/.bashrc
# Check currently installed meson version
meson -v
```


Chapter 3

Application Development

3.1 Overview

An application that uses VXG Cloud Agent Library should implement 3 classes derived from the base classes provided by the library:

- `agent::callback` - common callbacks class, only `on_bye` callback is mandatory for implementation
- `agent::media::stream` class, abstract class for media streams, library provides basic `media::rtsp_stream` implementation which retransmits RTSP source stream to the endpoint of the VXG Cloud, all callbacks are stubbed. Developer normally should implement own class derived from the `media::stream` with own `vvg::media::Streamer::ISource` implementation(`vvg::media::ffmpeg::Source` class implementation from the `ffmpeg_source.cc` can be used as a reference), or if RTSP source is acceptable developer can implement own class derived from the `media::rtsp_stream` but with callbacks implemented.
- `agent::event_stream` class, abstract class for events generation.

Any callback implementation as well as `ISource::init` and `ISource::finit` implementations should be non-blocking, VXG Cloud messages processing is single-threaded which means any VXG Cloud messages are handled sequentially hence no new message will be processed until the callback triggered by the previous message is returned.

The library provides the stub implementation for most of the virtual methods of these classes, the stub implementation prints a log message about this method is not implemented and returns an error, the final application should implement all virtual methods on its own.

Most of the callbacks are just getter/setter for the library's `objects`.

3.2 Examples

3.2.1 Minimal application example

Headers and namespaces:

```
#include <agent/manager.h>
#include <agent/rtsp-stream.h>
#include <utils/logging.h>
#include <utils/properties.h>
using namespace vvg::cloud;
using namespace vvg::cloud::agent;
```

Common callbacks class, minimal implementation derived from the `agent::callback` class:

```
using namespace vxg::cloud;
class agent_callback_minimal : public agent::callback {
public:
    virtual void on_bye(proto::bye_reason reason) override {
        vxg::logger::warn("Connection close {}", json(reason).dump());
    }
    virtual void on_registered(const std::string& sid) override {
        // Save Cloud registration session id in the local properties file.
        // This is required for the fast reconnection to the Cloud.
        props.set("prev_sid", sid);
    }
};
```

Create and start agent object `agent::manager` with one basic media stream `agent::media::rtsp_stream`

```
using namespace vxg::cloud::agent;
// Agent
manager::ptr agent;
// VXG Cloud token
auto access_token =
    proto::access_token::parse(vxg_cloud_token);
// Agent callback
callback::ptr cb = std::make_unique<agent_callback_minimal>();
// Media stream
std::vector<agent::media::stream::ptr> streams;
media::stream::ptr stream =
    std::make_shared<media::rtsp_stream>(rtsp_url, "DemoStream");
streams.push_back(stream);
// Create agent
if ((agent = agent::manager::create(agent_config, std::move(cb),
    access_token, streams)) == nullptr) {
    vxg::logger::error("Failed to create agent");
    return EXIT_FAILURE;
}
if (!quit && !agent->start())
    quit = true;
```

Complete minimal example:

```
#include <signal.h>
#include <args.hxx>
#include <agent/manager.h>
#include <agent/rtsp-stream.h>
#include <utils/logging.h>
#include <utils/properties.h>
using namespace vxg::cloud;
using namespace vxg::cloud::agent;
agent::config agent_config;
static bool quit = 0;
static vxg::properties props;
#ifdef _WIN32
static void signal_handler(int sig) {
    if (sig == SIGINT || sig == SIGTERM) {
        fprintf(stderr, "\nSIGTERM received\n\n");
        quit = true;
    }
}
#endif
using namespace vxg::cloud;
class agent_callback_minimal : public agent::callback {
public:
    virtual void on_bye(proto::bye_reason reason) override {
        vxg::logger::warn("Connection close {}", json(reason).dump());
    }
    virtual void on_registered(const std::string& sid) override {
        // Save Cloud registration session id in the local properties file.
        // This is required for the fast reconnection to the Cloud.
        props.set("prev_sid", sid);
    }
};
std::string vxg_cloud_token;
std::string rtsp_url;
bool parse_args(int argc, char** argv) {
    args::ArgumentParser parser("This is a test program.", "");
    args::HelpFlag help(parser, "help", "Display this help menu",
        {'h', "help"});
    args::CompletionFlag completion(parser, {"complete"});
    args::Positional<std::string> token(parser, "vxg_cloud_token",
        "VXG Cloud Access Token", "",
        args::Options::Required);
    args::Positional<std::string> url(parser, "rtsp_url", "RTSP stream url", "",
        args::Options::Required);
    args::Flag secure_connection_arg(
        parser, "",
        "Use secure cloud connection(enables encryption, cloud agent library "
        "must be compiled with openssl support enabled)",
```

```

    {"secure-channel", 's'});
try {
    parser.ParseCLI(argc, argv);
    vxg_cloud_token = args::get(token);
    rtsp_url = args::get(url);
    agent_config.insecure_cloud_channel =
        !args::get(secure_connection_arg);
} catch (const args::RequiredError& e) {
    std::cout << e.what() << std::endl;
    return false;
} catch (const args::Completion& e) {
    std::cout << e.what();
    return false;
} catch (const args::Help&) {
    std::cout << parser;
    return false;
} catch (const args::ParseError& e) {
    std::cerr << e.what() << std::endl;
    std::cerr << parser;
    return false;
}
return true;
}
int main(int argc, char** argv) {
    vxg::properties::reset("agent-test.props");
    // Try to load and set previously saved session id.
    // This is required for the fast reconnection to the Cloud.
    if (!props.get("prev_sid").empty())
        agent_config.cm_registration_sid = props.get("prev_sid");
    // Parse args and retrieve token and rtsp url
    if (!parse_args(argc, argv))
        return EXIT_FAILURE;
#ifdef _WIN32
    // Catch signal
    signal(SIGINT, signal_handler);
    signal(SIGTERM, signal_handler);
    signal(SIGPIPE, SIG_IGN);
#endif
    vxg::logger::info("VXG Cloud Agent Library Version: {}",
        vxg::cloud::agent::version());
    using namespace vxg::cloud::agent;
    // Agent
    manager::ptr agent;
    // VXG Cloud token
    auto access_token =
        proto::access_token::parse(vxg_cloud_token);
    // Agent callback
    callback::ptr cb = std::make_unique<agent_callback_minimal>();
    // Media stream
    std::vector<agent::media::stream::ptr> streams;
    media::stream::ptr stream =
        std::make_shared<media::rtsp_stream>(rtsp_url, "DemoStream");
    streams.push_back(stream);
    // Create agent
    if ((agent = agent::manager::create(agent_config, std::move(cb),
        access_token, streams)) == nullptr) {
        vxg::logger::error("Failed to create agent");
        return EXIT_FAILURE;
    }
    if (!quit && !agent->start())
        quit = true;
    // Spin main thread until stopped
    while (!quit) {
        std::this_thread::sleep_for(std::chrono::seconds(1));
    }
    agent->stop();
    agent = nullptr;
    vxg::logger::info("Agent stopped");
    return EXIT_SUCCESS;
}

```

3.2.2 Complete application example

Common callback class: derived from `agent::callback`

```

using namespace vxg::cloud;
class my_agent_callback : public agent::callback {
public:
    virtual void on_registered(const std::string& sid) override {
        // Save Cloud registration session id in the local properties file.
        // This is required for the fast reconnection to the Cloud.
        props.set("prev_sid", sid);
    }
}

```

```

virtual void on_bye(proto::bye_reason reason) override {
    if (reason != proto::bye_reason::BR_RECONNECT)
        vxg::logger::error("Error {}", json(reason));
}
virtual bool on_raw_msg(std::string client_id, std::string& data) override {
    vxg::logger::info("Raw message {} from client '{}'", data, client_id);
    // Reply json
    data = "{\"reply\": \"OK\"}";
    return true;
}
virtual bool on_get_log(std::string& log_data) override {
    log_data = "log messages...";
    vxg::logger::warn("{} not implemented", __func__);
    return true;
}
virtual bool on_start_backward_audio(std::string url) override {
    // Start backward audio playback from url
    vxg::logger::warn("{} not implemented", __func__);
    return false;
}
virtual bool on_stop_backward_audio(std::string url) override {
    vxg::logger::warn("{} not implemented", __func__);
    return false;
}
virtual bool on_get_cam_video_config(proto::video_config& config) override {
    vxg::logger::warn("{} not implemented", __func__);
    return false;
}
virtual bool on_set_cam_video_config(
    const proto::video_config& config) override {
    vxg::logger::warn("{} not implemented", __func__);
    return false;
}
virtual bool on_get_cam_audio_config(proto::audio_config& config) override {
    vxg::logger::warn("{} not implemented", __func__);
    return false;
}
virtual bool on_set_cam_audio_config(
    const proto::audio_config& config) override {
    vxg::logger::warn("{} not implemented", __func__);
    return false;
}
virtual bool on_get_ptz_config(proto::ptz_config& config) override {
    vxg::logger::warn("{} not implemented", __func__);
    return false;
}
virtual bool on_cam_ptz(proto::ptz_command& command) override {
    vxg::logger::warn("{} not implemented", __func__);
    return false;
}
virtual bool on_get_osd_config(proto::osd_config& config) override {
    vxg::logger::warn("{} not implemented", __func__);
    return false;
}
virtual bool on_set_osd_config(const proto::osd_config& config) override {
    vxg::logger::warn("{} not implemented", __func__);
    return false;
}
virtual bool on_get_wifi_config(proto::wifi_config& config) override {
    vxg::logger::warn("{} not implemented", __func__);
    return false;
}
virtual bool on_set_wifi_config(
    const proto::wifi_network& config) override {
    vxg::logger::warn("{} not implemented", __func__);
    return false;
}
virtual bool on_get_motion_detection_config(
    proto::motion_detection_config& config) override {
    vxg::logger::warn("{} not implemented", __func__);
    return false;
}
virtual bool on_set_motion_detection_config(
    const proto::motion_detection_config& config) override {
    vxg::logger::warn("{} not implemented", __func__);
    return false;
}
virtual bool on_get_timezone(std::string& timezone) override {
    vxg::logger::warn("{} not implemented", __func__);
    return false;
}
virtual bool on_set_timezone(std::string timezone) override {
    vxg::logger::warn("{} not implemented", __func__);
    return false;
}
virtual bool on_get_memorycard_info(
    proto::event_object::memorycard_info_object& info) override {

```

```

        vxg::logger::warn("{} not implemented", __func__);
        return false;
    }
    virtual bool on_set_audio_detection(
        const proto::audio_detection_config& conf) {
        vxg::logger::warn("{} not implemented", __func__);
        return false;
    }
    virtual bool on_get_audio_detection(proto::audio_detection_config& conf) {
        vxg::logger::warn("{} not implemented", __func__);
        return false;
    }
};

```

Media stream callback class: derived from `agent::media::stream`

```

class my_media_stream : public media::rtsp_stream {
public:
    my_media_stream(std::string url, std::string name)
        : media::rtsp_stream(url, name) {
        set_on_error_cb([&](const vxg::media::stream_error::report& report) {
            using namespace vxg::media;
            vxg::logger::instance(std::string("my-media-stream-") + name)
                ->error("Error {} from {} received", report.code, report.from);
            // switch (report.from)
            // case : stream_error::origin::O_SOURCE - RTSP input stream error
            // case : stream_error::origin::O_SINK - Cloud streaming error
        });
    }
    virtual bool get_supported_stream(
        proto::supported_stream_config& config) override {
        vxg::logger::warn("{} default implementation should be overridden",
            __func__);
        config.id = cloud_name();
        config.video = "Video" + std::to_string(0);
        // config.audio = "Audio" + std::to_string(0);
        return true;
    }
    virtual bool get_stream_caps(proto::stream_caps& caps) override {
        vxg::logger::warn("{} not implemented", __func__);
        return false;
    }
    virtual bool get_stream_config(
        proto::stream_config& streamConfig) override {
        vxg::logger::warn("{} not implemented", __func__);
        return false;
    }
    virtual bool set_stream_config(
        const proto::stream_config& streamConfig) override {
        vxg::logger::warn("{} not implemented", __func__);
        return false;
    }
    virtual bool get_snapshot(
        proto::event_object::snapshot_info_object& snapshot) override {
        vxg::logger::warn("{} not implemented", __func__);
        return false;
    }
    virtual std::vector<proto::video_clip_info> record_get_list(
        vxg::cloud::time begin,
        vxg::cloud::time end,
        bool align) override {
        std::vector<proto::video_clip_info> empty_vector(0);
        vxg::logger::warn("{} not implemented", __func__);
        return empty_vector;
    }
    virtual proto::video_clip_info record_export(
        vxg::cloud::time begin,
        vxg::cloud::time end) override {
        proto::video_clip_info clip;
        vxg::logger::warn("{} not implemented", __func__);
        // empty clip
        return clip;
    }
    virtual bool start_record() override {
        vxg::logger::warn("{} not implemented", __func__);
        return false;
    }
    virtual void stop_record() override {
        vxg::logger::warn("{} not implemented", __func__);
    }
};

```

Event stream callback class: derived from `agent::media::event_stream`

```

class my_event_stream : public agent::event_stream {
public:
    my_event_stream(std::string name) : agent::event_stream(name) {}
};

```

```

virtual bool start() {
    vxg::logger::warn("{} not implemented", __func__);
    return false;
}
virtual void stop() { vxg::logger::warn("{} not implemented", __func__); }
virtual bool init() {
    vxg::logger::warn("{} not implemented", __func__);
    return false;
}
virtual void finit() { vxg::logger::warn("{} not implemented", __func__); }
virtual bool set_trigger_recording(bool enabled, int pre, int post) {
    vxg::logger::warn("{} not implemented", __func__);
    return false;
}
virtual bool get_events(std::vector<proto::event_config>& configs) {
    return false;
}
virtual bool set_events(const std::vector<proto::event_config>& config) {
    return false;
}
};

```

Creating and start agent instance with all callbacks:

```

using namespace vxg::cloud::agent;
// Agent
manager::ptr agent;
// VXG Cloud token
auto access_token = proto::access_token::parse(vxg_cloud_token);
// Agent callback
callback::ptr cb = std::make_unique<my_agent_callback>();
// Media stream
std::vector<agent::media::stream::ptr> streams;
media::stream::ptr stream =
    std::make_shared<my_media_stream>(rtsp_url, "MyMediaStream");
streams.push_back(stream);
// Event stream
std::vector<agent::event_stream::ptr> event_streams;
event_stream::ptr event_stream =
    std::make_shared<my_event_stream>("MyEventStream");
event_streams.push_back(event_stream);
// Create agent
if ((agent =
    agent::manager::create(agent_config, std::move(cb), access_token,
        streams, event_streams)) == nullptr) {
    vxg::logger::error("Failed to create agent");
    return EXIT_FAILURE;
}
if (!quit && !agent->start())
    quit = true;

```

3.2.3 Linking application against the VXG Agent Cloud Library

There are 3 possible ways of how to build and link your application

1. Building the application inside the VXG CCloud Agent library's Meson project, the app will be assembled during the library project compilation in this case.

You need to add a new executable target into the main `meson.build` file, please refer to the example app build target declaration:

```

cloud_agent_minimal = executable('cloud-agent-minimal', 'src/cloud-agent-minimal.cc',
    install : true, dependencies: dep)

```

User must declare own executable target with a list of sources and dependencies, user may need to declare own dependencies if application requires it.

This method is not recommended as it makes updating of the VXG Cloud Agent library mostly not possible or very difficult for application developer

2. Building your app using your own build system and linking against the installed library.

Running the `install` step from the `compile` section installs the binary libraries and headers into the directory you specified during the `setup` step, it also puts the `pkg-config's .pc` files into the prefix directory which could be used by your own build system.

3. Preferred and recommended way of application development is to hold the app as a separate `Meson` project and use the VXG Cloud Agent library as a `Meson` subproject of the application's `Meson` project.

Using this approach gives the most flexible and convenient workflow for updating the VXG Cloud Library, all library dependencies will be promoted to the main project and will be also accessible by the application.

How does it work

- Assuming you have a `Meson` build system [installed](#)
- Start a new `Meson` project with a following command:

```
meson init -l cpp -n your-project-name
```
- As a result of this command you should have the following files tree:

```
|-- meson.build
|-- your_project_name.cpp
```
- Add VXG Cloud Agent library as a `Meson` subproject
 All subprojects should be located in the `subprojects` directory so you have to create it first

```
mkdir subprojects
```

Now you have 2 options depending on how you want to store the VXG Cloud Agent library sources:

- (a) If you want to store the VXG Cloud Agent library as a files tree locally.

- Create a symlink to the library path inside the `subprojects` dir:

```
ln -s path/to/vxgcloudagent subprojects/vxgcloudagent
```

Or you can just move `vxgcloudagent` directory inside the `subprojects` dir.

- Create a library's `Meson` wrap file inside the `subprojects` dir, the name of the file should be the same as symlink you created in 1.1 and the content of the file should be:

```
[wrap-file]
directory = vxgcloudagent
[provide]
vxgcloudagent = vxgcloudagent_dep
```

- (b) If you want to store the library in a git repository you just need to create a wrap file with the content like below:

```
[wrap-git]
url=https://your-git-repo-url.com/path/vxgcloudagent.git
# You can specify tag, branch or commit hash as revision
revision=master
[provide]
vxgcloudagent = vxgcloudagent_dep
```

You can find the example app `Meson` project in the `example/app` directory of the VXG Cloud library sources package.

Chapter 4

Library Compilation Guide

4.0.1 Library build process

Here is a compilation quickstart guide:

- First of all you need to have a build system and toolchain [installed](#)
- **Setup the build directory**

```
meson setup --prefix=path/to/install --strip -Dbuildtype=debug builddir/  
# --prefix=path specifies the installation path  
# --strip indicates that final binaries should be stripped  
# -Dbuildtype= specifies the debug/release build type, please check the Meson docs about full list of  
the build types.
```

- **Build**

```
meson compile -C builddir  
# Or  
ninja -C builddir
```

- **Install**

```
meson install -C builddir  
# Or  
ninja -C builddir/ install
```

As a result of the `install` step you should have the library compiled and installed into the prefix directory you specified during the `setup` step.

- **Clean**

```
ninja -C builddir clean
```

Or you can just delete the `builddir`, you will need to `setup` it again in this case.

```
rm -rf builddir
```

4.0.2 Cross-compilation

- By default `Meson` builds project for the host platform, but it's also possible to cross-compile the library and your application using `Meson`.
- Full `Meson` cross-compilation documentation can be found [here](#).

- The difference between the host compilation described above and the cross-compilation is the additional `--cross-file=path/to/cross-file.txt` flag for the Meson Setup step, the Setup command should look like below:

```
meson setup --prefix=path/to/install --strip -Dbuildtype=debug --cross-file=path/to/cross-file.txt  
builddir/
```

`cross-file.txt` is the target platform description which in terms of Meson called a `cross-file`.

- cross-file example below is for the Debian provided arm-linux-gnueabihf toolchain installable using the Ubuntu's package manager command
`sudo apt install g++-arm-linux-gnueabihf`

- Example of the ARMv7 cross-file:

```
[host_machine]
system = 'linux'
cpu_family = 'arm'
cpu = 'armv7-a'
endian = 'little'
[built-in options]
# Example of platform specific CFLAGS and CXXFLAGS
c_args = ['-mfloat-abi=hard', '-march=armv7-a+vfpv3']
cpp_args = c_args
default_library = 'static'
[properties]
# If your toolchain requires specifying the sysroot dir you can setup it like below, sysroot_dir is a
# constant declared in [constants] section of the cross-file
#sys_root = sysroot_dir
# Meson uses pkg-config and cmake to detect external dependencies
# Set the correct path to your cross-compilation pkgconfig directory if your app depends on some
# external dependencies like platform specific libs.
#pkg_config_libdir = sysroot_dir / 'usr/lib/pkgconfig/'
[constants]
cross_prefix = 'arm-linux-gnueabihf-'
#sysroot_dir = '/opt/arm-linux-gnueabihf/sysroot/'
[binaries]
c = cross_prefix + 'gcc'
cpp = cross_prefix + 'g++'
ar = cross_prefix + 'ar'
strip = cross_prefix + 'strip'
# You should specify your platform toolchain pkg-config binary here
#pkgconfig = '/opt/arm-linux-gnueabihf/bin/pkg-config'
```

Chapter 5

Deprecated List

Global `vxg::logger::reset` (int argc, char **argv, loglevel l, std::string syslog_ident="VXGCloudAgent↵
Default", std::string crash_logfile_path="", std::string logfile_path="", size_t logfile_max_size=(1024
*1024), size_t logfile_max_files=3)

Use `reset(const options& opts)`

Chapter 6

Hierarchical Index

6.1 Class Hierarchy

This inheritance list is sorted roughly, but not completely, alphabetically:

vxg::cloud::agent::access_token	71
alter_bool	73
vxg::cloud::agent::proto::audio_caps	76
vxg::cloud::agent::audio_config	78
vxg::cloud::agent::audio_detection_config::audio_detection_conf_caps	80
vxg::cloud::agent::audio_detection_config	82
vxg::cloud::agent::proto::audio_stream_config	84
vxg::media::Streamer::StreamInfo::AudioInfo	86
vxg::cloud::agent::callback	88
vxg::cloud::agent::proto::stream_caps::caps_audio_object	100
vxg::cloud::agent::proto::stream_caps::caps_video_object	102
command_handler	
vxg::cloud::agent::manager	161
common	
vxg::media::ffmpeg::Sink	224
vxg::media::rtmp_sink	206
vxg::media::ffmpeg::Source	229
vxg::media::rtmp_source	210
vxg::media::rtsp_source	212
vxg::cloud::agent::event_manager::config	108
vxg::cloud::agent::synchronizer::config	110
std::enable_shared_from_this< manager > [external]	
vxg::cloud::agent::manager	161
vxg::cloud::agent::proto::event_caps	111
vxg::cloud::agent::event_config	113
vxg::cloud::agent::event_manager	117
vxg::cloud::agent::event_state	119
vxg::cloud::agent::event_state::event_state_changed_cb	124
vxg::cloud::agent::event_manager::event_state_report_cb	126
vxg::cloud::agent::manager	161
vxg::cloud::agent::event_stream	128
vxg::cloud::agent::events_config	134
vxg::media::Streamer::ISink	137
vxg::media::ffmpeg::Sink	224

vxg::media::Streamer::ISource	144
vxg::media::ffmpeg::Source	229
vxg::logger	154
vxg::media::Streamer::MediaFrame	175
vxg::cloud::agent::proto::motion_detection_caps	178
vxg::cloud::agent::proto::motion_detection_config	180
vxg::cloud::agent::proto::motion_region	181
vxg::logger::options	183
vxg::cloud::agent::proto::osd_caps	186
vxg::cloud::agent::osd_config	190
vxg::cloud::period	193
vxg::cloud::agent::synchronizer::segmenter	219
vxg::cloud::timed_storage::item	150
vxg::cloud::agent::access_token::proxy_config	197
vxg::cloud::agent::ptz_command	198
vxg::cloud::agent::ptz_config	199
vxg::cloud::agent::ptz_preset	201
vxg::cloud::utils::queued_async_handler< T >	202
vxg::cloud::utils::queued_async_handler< stream_error::report >	202
vxg::media::stream	234
vxg::cloud::agent::media::stream	239
vxg::cloud::agent::media::rtsp_stream	216
vxg::media::stream_error::report	205
vxg::cloud::agent::media::stream_callbacks	241
vxg::cloud::agent::media::stream_callbacks_stub	247
vxg::cloud::agent::media::stream	239
vxg::cloud::agent::proto::stream_caps	253
vxg::cloud::agent::proto::stream_config	254
vxg::media::Streamer::StreamInfo	258
std::string[external]	
vxg::cloud::utils::motion::map	173
vxg::cloud::agent::supported_stream_config	262
vxg::cloud::agent::supported_streams_config	263
vxg::cloud::agent::synchronizer::sync_request	265
vxg::cloud::agent::synchronizer	265
vxg::cloud::timed_storage	269
vxg::cloud::cloud_storage	106
vxg::cloud::stream_storage	255
vxg::cloud::timeline< T >	272
vxg::cloud::sync::timeline	273
vxg::cloud::utils::uri	277
vxg::cloud::agent::proto::video_caps	279
vxg::cloud::agent::proto::video_clip_info	283
vxg::cloud::agent::proto::video_config	285
vxg::cloud::agent::proto::video_stream_config	290
vxg::media::Streamer::StreamInfo::VideoInfo	293
vxg::cloud::agent::proto::wifi_config	296
vxg::cloud::agent::proto::wifi_network	297

Chapter 7

Data Structure Index

7.1 Data Structures

Here are the data structures with brief descriptions:

vxg::cloud::agent::access_token	71
VXG Cloud access token	
alter_bool	73
Alternative bool class Standard bool type has two states, this class adds 3rd state - undefined .	
vxg::cloud::agent::proto::audio_caps	76
Audio capabilities	
vxg::cloud::agent::audio_config	78
Audio config	
vxg::cloud::agent::audio_detection_config::audio_detection_conf_caps	80
vxg::cloud::agent::audio_detection_config	82
5.6 audio_detection_config (CM) Current audio detection settings	
vxg::cloud::agent::proto::audio_stream_config	84
Audio media stream config	
vxg::media::Streamer::StreamInfo::AudioInfo	86
Audio stream info	
vxg::cloud::agent::callback	88
VXG Cloud manager common callbacks class	
vxg::cloud::agent::proto::stream_caps::caps_audio_object	100
Audio streams capabilities	
vxg::cloud::agent::proto::stream_caps::caps_video_object	102
Video streams capabilities	
vxg::cloud::cloud_storage	106
vxg::cloud::agent::event_manager::config	108
vxg::cloud::agent::synchronizer::config	110
vxg::cloud::agent::proto::event_caps	111
Events capabilities	
vxg::cloud::agent::event_config	113
Event config	
vxg::cloud::agent::event_manager	117
vxg::cloud::agent::event_state	119
vxg::cloud::agent::event_state::event_state_changed_cb	124
vxg::cloud::agent::event_manager::event_state_report_cb	126
vxg::cloud::agent::event_stream	128
Event stream, abstract class for event generation	
vxg::cloud::agent::events_config	134
Events config, list of event_config objects	

vxg::media::Streamer::ISink	137
vxg::media::Streamer::ISource	
ISource interface class	144
vxg::cloud::timed_storage::item	150
vxg::logger	
Logger class, current implementation based on spdlog	154
vxg::cloud::agent::manager	
VXG Cloud agent manager class	161
vxg::cloud::utils::motion::map	173
vxg::media::Streamer::MediaFrame	
Media frame container	175
vxg::cloud::agent::proto::motion_detection_caps	
Motion detection capabilities camera capabilities that limit possible motion detection configuration	178
vxg::cloud::agent::proto::motion_detection_config	
Motion detection config	180
vxg::cloud::agent::proto::motion_region	
Motion detection related structs	181
vxg::logger::options	183
vxg::cloud::agent::proto::osd_caps	
OSD capabilities	186
vxg::cloud::agent::osd_config	
OSD config	190
vxg::cloud::period	193
vxg::cloud::agent::access_token::proxy_config	
Socks proxy settings	197
vxg::cloud::agent::ptz_command	
PTZ command	198
vxg::cloud::agent::ptz_config	
PTZ config	199
vxg::cloud::agent::ptz_preset	
PTZ preset	201
vxg::cloud::utils::queued_async_handler< T >	202
vxg::media::stream_error::report	
Media stream error report simple object	205
vxg::media::rtmp_sink	
RTMP sink class	206
vxg::media::rtmp_source	
RTMP source class	210
vxg::media::rtsp_source	
RTSP source class	212
vxg::cloud::agent::media::rtsp_stream	
Implementation of the media::stream with RTSP source and NIY stubs	216
vxg::cloud::agent::synchronizer::segmenter	219
vxg::media::ffmpeg::Sink	
Base ffmpeg sink class	224
vxg::media::ffmpeg::Source	
Base ffmpeg source class	229
vxg::media::stream	
Base media stream abstract class	234
vxg::cloud::agent::media::stream	
Cloud agent media stream abstract class	239
vxg::cloud::agent::media::stream_callbacks	
Cloud agent media stream callbacks abstract class	241
vxg::cloud::agent::media::stream_callbacks_stub	247
vxg::cloud::agent::proto::stream_caps	
Media stream capabilities	253

vxg::cloud::agent::proto::stream_config	
Media stream config	254
vxg::cloud::stream_storage	255
vxg::media::Streamer::StreamInfo	
Stream info description	258
vxg::cloud::agent::supported_stream_config	
Supported stream config	262
vxg::cloud::agent::supported_streams_config	
Supported streams config, list of supported_stream_config	263
vxg::cloud::agent::synchronizer::sync_request	265
vxg::cloud::agent::synchronizer	265
vxg::cloud::timed_storage	269
vxg::cloud::timeline< T >	272
vxg::cloud::sync::timeline	273
vxg::cloud::utils::uri	277
vxg::cloud::agent::proto::video_caps	
Video image capabilities	279
vxg::cloud::agent::proto::video_clip_info	
Video recoding(mp4 file) clip description,	283
vxg::cloud::agent::proto::video_config	
Video image config	285
vxg::cloud::agent::proto::video_stream_config	
Video stream config	290
vxg::media::Streamer::StreamInfo::VideoInfo	
Video stream info	293
vxg::cloud::agent::proto::wifi_config	
WiFi config	296
vxg::cloud::agent::proto::wifi_network	
WiFi network object	297

Chapter 8

File Index

8.1 File List

Here is a list of all files with brief descriptions:

base_streamer.h	299
callback.h	301
caps.h	302
cloud-agent-minimal.cc	305
cloud-agent.cc	307
config.h	310
event-manager.h	313
event-state.h	314
event-stream.h	315
ffmpeg_sink.h	316
ffmpeg_source.cc	317
ffmpeg_source.h	317
logging.h	318
manager.h	319
meson.build	320
queued-handler.h	320
rtmp_sink.h	322
rtmp_source.h	323
rtsp-stream.h	323
rtsp_source.h	324
stream-storage.h	325
streamer/stream.h	326
agent/stream.h	327
timeline-synchronizer.h	328
timeline.h	330
unset-helper.h	331
utils.h	340

Chapter 9

Namespace Documentation

9.1 nlohmann Namespace Reference

9.2 std Namespace Reference

Namespaces

- `chrono`
- `experimental`
- `regex_constants`
- `rel_ops`
- `this_thread`

Data Structures

- class `add_const`
- class `add_cv`
- class `add_lvalue_reference`
- class `add_pointer`
- class `add_rvalue_reference`
- class `add_volatile`
- class `adopt_lock_t`
- class `aligned_storage`
- class `aligned_union`
- class `alignment_of`
- class `allocator`
- class `allocator_arg_t`
- class `allocator_traits`
- class `array`
- class `atomic`
- class `atomic_flag`
- class `auto_ptr`
- class `back_insert_iterator`
- class `bad_alloc`
- class `bad_array_length`
- class `bad_array_new_length`

- class **bad_cast**
- class **bad_exception**
- class **bad_function_call**
- class **bad_optional_access**
- class **bad_typeid**
- class **bad_weak_ptr**
- class **basic_filebuf**
- class **basic_fstream**
- class **basic_ifstream**
- class **basic_ios**
- class **basic_iostream**
- class **basic_istream**
- class **basic_istreamstream**
- class **basic_ofstream**
- class **basic_ostream**
- class **basic_ostreamstream**
- class **basic_regex**
- class **basic_streambuf**
- class **basic_string**
- class **basic_stringbuf**
- class **basic_stringstream**
- class **bernoulli_distribution**
- class **bidirectional_iterator_tag**
- class **binary_function**
- class **binary_negate**
- class **binomial_distribution**
- class **bit_and**
- class **bit_not**
- class **bit_or**
- class **bitset**
- class **cauchy_distribution**
- class **centi**
- class **cerr**
- class **char_traits**
- class **chi_squared_distribution**
- class **cin**
- class **clock_t**
- class **clog**
- class **cmatch**
- class **codecvt**
- class **codecvt_base**
- class **codecvt_byname**
- class **codecvt_utf16**
- class **codecvt_utf8**
- class **codecvt_utf8_utf16**
- class **collate**
- class **collate_byname**
- class **common_type**
- class **complex**
- class **condition_variable**
- class **condition_variable_any**
- class **conditional**
- class **cout**
- class **cregex_iterator**
- class **cregex_token_iterator**

- class **csub_match**
- class **ctype**
- class **ctype_base**
- class **ctype_byname**
- class **deca**
- class **decay**
- class **deci**
- class **default_delete**
- class **default_random_engine**
- class **defer_lock_t**
- class **deque**
- class **discard_block_engine**
- class **discrete_distribution**
- class **divides**
- class **domain_error**
- class **dynarray**
- class **enable_if**
- class **enable_shared_from_this**
- class **equal_to**
- class **errc**
- class **error_category**
- class **error_code**
- class **error_condition**
- class **exa**
- class **exception**
- class **exception_ptr**
- class **exponential_distribution**
- class **extent**
- class **extreme_value_distribution**
- class **false_type**
- class **femto**
- class **FILE**
- class **filebuf**
- class **fisher_f_distribution**
- class **forward_iterator_tag**
- class **forward_list**
- class **fpos**
- class **fpos_t**
- class **front_insert_iterator**
- class **fstream**
- class **function**
- class **future**
- class **future_error**
- class **gamma_distribution**
- class **geometric_distribution**
- class **giga**
- class **greater**
- class **greater_equal**
- class **has_virtual_destructor**
- class **hash**
- class **hecto**
- class **ifstream**
- class **independent_bits_engine**
- class **initializer_list**
- class **input_iterator_tag**

- class **insert_iterator**
- class **int16_t**
- class **int32_t**
- class **int64_t**
- class **int8_t**
- class **int_fast16_t**
- class **int_fast32_t**
- class **int_fast64_t**
- class **int_fast8_t**
- class **int_least16_t**
- class **int_least32_t**
- class **int_least64_t**
- class **int_least8_t**
- class **integer_sequence**
- class **integral_constant**
- class **intmax_t**
- class **intptr_t**
- class **invalid_argument**
- class **ios_base**
- class **iostream**
- class **is_abstract**
- class **is_arithmetic**
- class **is_array**
- class **is_assignable**
- class **is_base_of**
- class **is_bind_expression**
- class **is_class**
- class **is_compound**
- class **is_const**
- class **is_constructible**
- class **is_convertible**
- class **is_copy_assignable**
- class **is_copy_constructible**
- class **is_default_constructible**
- class **is_destructible**
- class **is_empty**
- class **is_enum**
- class **is_error_code_enum**
- class **is_error_condition_enum**
- class **is_floating_point**
- class **is_function**
- class **is_fundamental**
- class **is_integral**
- class **is_literal_type**
- class **is_lvalue_reference**
- class **is_member_function_pointer**
- class **is_member_object_pointer**
- class **is_member_pointer**
- class **is_move_assignable**
- class **is_move_constructible**
- class **is_nothrow_assignable**
- class **is_nothrow_constructible**
- class **is_nothrow_copy_assignable**
- class **is_nothrow_copy_constructible**
- class **is_nothrow_default_constructible**

- class **is_nothrow_destructible**
- class **is_nothrow_move_assignable**
- class **is_nothrow_move_constructible**
- class **is_object**
- class **is_placeholder**
- class **is_pod**
- class **is_pointer**
- class **is_polymorphic**
- class **is_reference**
- class **is_rvalue_reference**
- class **is_same**
- class **is_scalar**
- class **is_signed**
- class **is_standard_layout**
- class **is_trivial**
- class **is_trivially_assignable**
- class **is_trivially_constructible**
- class **is_trivially_copy_assignable**
- class **is_trivially_copy_constructible**
- class **is_trivially_copyable**
- class **is_trivially_default_constructible**
- class **is_trivially_destructible**
- class **is_trivially_move_assignable**
- class **is_trivially_move_constructible**
- class **is_union**
- class **is_unsigned**
- class **is_void**
- class **is_volatile**
- class **istream**
- class **istream_iterator**
- class **istreambuf_iterator**
- class **istreamstringstream**
- class **istrstream**
- class **iterator**
- class **iterator_traits**
- class **jmp_buf**
- class **kilo**
- class **knuth_b**
- class **lconv**
- class **length_error**
- class **less**
- class **less_equal**
- class **linear_congruential_engine**
- class **list**
- class **locale**
- class **lock_guard**
- class **logic_error**
- class **logical_and**
- class **logical_not**
- class **logical_or**
- class **lognormal_distribution**
- class **make_signed**
- class **make_unsigned**
- class **map**
- class **match_results**

- class **max_align_t**
- class **mbstate_t**
- class **mega**
- class **mersenne_twister_engine**
- class **messages**
- class **messages_base**
- class **messages_byname**
- class **micro**
- class **milli**
- class **minstd_rand**
- class **minstd_rand0**
- class **minus**
- class **modulus**
- class **money_base**
- class **money_get**
- class **money_put**
- class **moneypunct**
- class **moneypunct_byname**
- class **move_iterator**
- class **mt19937**
- class **mt19937_64**
- class **multimap**
- class **multiplies**
- class **multiset**
- class **mutex**
- class **nano**
- class **negate**
- class **negative_binomial_distribution**
- class **nested_exception**
- class **new_handler**
- class **normal_distribution**
- class **not_equal_to**
- class **nothrow_t**
- class **nullptr_t**
- class **num_get**
- class **num_put**
- class **numeric_limits**
- class **numpunct**
- class **numpunct_byname**
- class **ofstream**
- class **once_flag**
- class **ostream**
- class **ostream_iterator**
- class **ostreambuf_iterator**
- class **ostringstream**
- class **ostrstream**
- class **out_of_range**
- class **output_iterator_tag**
- class **overflow_error**
- class **owner_less**
- class **packaged_task**
- class **pair**
- class **peta**
- class **pico**
- class **piecewise_constant_distribution**

- class **piecewise_construct_t**
- class **piecewise_linear_distribution**
- class **placeholders**
- class **plus**
- class **pointer_safety**
- class **pointer_traits**
- class **poisson_distribution**
- class **priority_queue**
- class **promise**
- class **ptrdiff_t**
- class **queue**
- class **random_access_iterator_tag**
- class **random_device**
- class **range_error**
- class **rank**
- class **ranlux24**
- class **ranlux24_base**
- class **ranlux48**
- class **ranlux48_base**
- class **ratio**
- class **ratio_add**
- class **ratio_divide**
- class **ratio_equal**
- class **ratio_greater**
- class **ratio_greater_equal**
- class **ratio_less**
- class **ratio_less_equal**
- class **ratio_multiply**
- class **ratio_not_equal**
- class **ratio_subtract**
- class **raw_storage_iterator**
- class **recursive_mutex**
- class **recursive_timed_mutex**
- class **reference_wrapper**
- class **regex**
- class **regex_error**
- class **regex_iterator**
- class **regex_token_iterator**
- class **regex_traits**
- class **remove_all_extents**
- class **remove_const**
- class **remove_cv**
- class **remove_extent**
- class **remove_pointer**
- class **remove_reference**
- class **remove_volatile**
- class **result_of**
- class **reverse_iterator**
- class **runtime_error**
- class **scoped_allocator_adaptor**
- class **seed_seq**
- class **set**
- class **shared_future**
- class **shared_lock**
- class **shared_ptr**

- class **shared_timed_mutex**
- class **shuffle_order_engine**
- class **sig_atomic_t**
- class **size_t**
- class **smatch**
- class **sregex_iterator**
- class **sregex_token_iterator**
- class **ssub_match**
- class **stack**
- class **streambuf**
- class **streamoff**
- class **streampos**
- class **streamsize**
- class **string**
- class **stringbuf**
- class **stringstream**
- class **strstream**
- class **strstreambuf**
- class **student_t_distribution**
- class **sub_match**
- class **subtract_with_carry_engine**
- class **system_error**
- class **tera**
- class **terminate_handler**
- class **thread**
- class **time_base**
- class **time_get**
- class **time_get_byname**
- class **time_put**
- class **time_put_byname**
- class **time_t**
- class **timed_mutex**
- class **tm**
- class **true_type**
- class **try_to_lock_t**
- class **tuple**
- class **type_index**
- class **type_info**
- class **u16streampos**
- class **u16string**
- class **u32streampos**
- class **u32string**
- class **uint16_t**
- class **uint32_t**
- class **uint64_t**
- class **uint8_t**
- class **uint_fast16_t**
- class **uint_fast32_t**
- class **uint_fast64_t**
- class **uint_fast8_t**
- class **uint_least16_t**
- class **uint_least32_t**
- class **uint_least64_t**
- class **uint_least8_t**
- class **uintmax_t**

- class **uintptr_t**
- class **unary_function**
- class **unary_negate**
- class **underflow_error**
- class **underlying_type**
- class **unexpected_handler**
- class **uniform_int_distribution**
- class **uniform_real_distribution**
- class **unique_lock**
- class **unique_ptr**
- class **unordered_map**
- class **unordered_multimap**
- class **unordered_multiset**
- class **unordered_set**
- class **uses_allocator**
- class **valarray**
- class **vector**
- class **wbuffer_convert**
- class **wcerr**
- class **wcin**
- class **wclog**
- class **wcmatch**
- class **wcout**
- class **wcregex_iterator**
- class **wcregex_token_iterator**
- class **wcsub_match**
- class **weak_ptr**
- class **weibull_distribution**
- class **wfilebuf**
- class **wfstream**
- class **wifstream**
- class **wiostream**
- class **wistream**
- class **wistringstream**
- class **wofstream**
- class **wostream**
- class **wostringstream**
- class **wregex**
- class **wsmatch**
- class **wsregex_iterator**
- class **wsregex_token_iterator**
- class **wssub_match**
- class **wstreambuf**
- class **wstreampos**
- class **wstring**
- class **wstring_convert**
- class **wstringbuf**
- class **wstringstream**
- class **yocto**
- class **yotta**
- class **zetta**

Functions

- T **atomic_fetch_and_explicit** (T... args)
- T **atomic_fetch_xor_explicit** (T... args)
- T **set_unexpected** (T... args)
- T **fputs** (T... args)
- T **modf** (T... args)
- T **not2** (T... args)
- T **strlen** (T... args)
- T **exp2** (T... args)
- T **setiosflags** (T... args)
- T **adjacent_difference** (T... args)
- T **cos** (T... args)
- T **fwscanf** (T... args)
- T **atomic_init** (T... args)
- T **forward_as_tuple** (T... args)
- T **abort** (T... args)
- T **wcsncmp** (T... args)
- T **set_intersection** (T... args)
- T **atomic_signal_fence** (T... args)
- T **llabs** (T... args)
- T **make_move_iterator** (T... args)
- T **scanf** (T... args)
- T **nextafter** (T... args)
- T **stol** (T... args)
- T **strcspn** (T... args)
- T **ungetwc** (T... args)
- T **transform** (T... args)
- T **putc** (T... args)
- T **iswdigit** (T... args)
- T **rint** (T... args)
- T **memset** (T... args)
- T **isgraph** (T... args)
- T **replace_copy_if** (T... args)
- T **scalbn** (T... args)
- T **partial_sort_copy** (T... args)
- T **make_exception_ptr** (T... args)
- T **frexp** (T... args)
- T **isxdigit** (T... args)
- T **atomic_exchange_explicit** (T... args)
- T **wprintf** (T... args)
- T **fdim** (T... args)
- T **wctype** (T... args)
- T **mbrtoc32** (T... args)
- T **setw** (T... args)
- T **get_temporary_buffer** (T... args)
- T **fmax** (T... args)
- T **atomic_thread_fence** (T... args)
- T **atomic_exchange** (T... args)
- T **fgetwc** (T... args)
- T **swprintf** (T... args)
- T **prev_permutation** (T... args)
- T **max_element** (T... args)
- T **set_symmetric_difference** (T... args)
- T **wcscpy** (T... args)

- T **const_pointer_cast** (T... args)
- T **minmax_element** (T... args)
- T **wcstok** (T... args)
- T **ref** (T... args)
- T **feupdateenv** (T... args)
- T **endl** (T... args)
- T **end** (T... args)
- T **wmemmove** (T... args)
- T **fmin** (T... args)
- T **uninitialized_fill_n** (T... args)
- T **noupper** (T... args)
- T **noshowpos** (T... args)
- T **ctime** (T... args)
- T **wmemset** (T... args)
- T **iswpunct** (T... args)
- T **pop_heap** (T... args)
- T **sprintf** (T... args)
- T **fixed** (T... args)
- T **make_shared** (T... args)
- T **make_heap** (T... args)
- T **fmod** (T... args)
- T **atol** (T... args)
- T **uninitialized_copy** (T... args)
- T **dynamic_pointer_cast** (T... args)
- T **set_union** (T... args)
- T **hexfloat** (T... args)
- T **vswprintf** (T... args)
- T **asctime** (T... args)
- T **iswspace** (T... args)
- T **nan** (T... args)
- T **sort** (T... args)
- T **quick_exit** (T... args)
- T **log10** (T... args)
- T **mbstowcs** (T... args)
- T **isspace** (T... args)
- T **strncat** (T... args)
- T **isinf** (T... args)
- T **atof** (T... args)
- T **erf** (T... args)
- T **is_sorted_until** (T... args)
- T **cbrt** (T... args)
- T **log1p** (T... args)
- T **return_temporary_buffer** (T... args)
- T **mbsrtowcs** (T... args)
- T **feraiseexcept** (T... args)
- T **fseek** (T... args)
- T **atomic_fetch_or_explicit** (T... args)
- T **log** (T... args)
- T **putchar** (T... args)
- T **make_tuple** (T... args)
- T **expm1** (T... args)
- T **fma** (T... args)
- T **remove_copy_if** (T... args)
- T **showpoint** (T... args)
- T **fscanf** (T... args)

- T **stable_partition** (T... args)
- T **fill_n** (T... args)
- T **remove_copy** (T... args)
- T **atomic_compare_exchange_strong_explicit** (T... args)
- T **wctomb** (T... args)
- T **fgets** (T... args)
- T **remainder** (T... args)
- T **allocate_shared** (T... args)
- T **unique** (T... args)
- T **includes** (T... args)
- T **iswalnum** (T... args)
- T **exit** (T... args)
- T **put_time** (T... args)
- T **to_string** (T... args)
- T **is_heap_until** (T... args)
- T **wcstold** (T... args)
- T **stold** (T... args)
- T **ftell** (T... args)
- T **copy_backward** (T... args)
- T **wcstoll** (T... args)
- T **perror** (T... args)
- T **vscanf** (T... args)
- T **stable_sort** (T... args)
- T **generic_category** (T... args)
- T **abs(int)** (T... args)
- T **fgetws** (T... args)
- T **showpos** (T... args)
- T **exp** (T... args)
- T **fill** (T... args)
- T **isalpha** (T... args)
- T **lgamma** (T... args)
- T **feclearexcept** (T... args)
- T **wcsncpy** (T... args)
- T **undecclare_reachable** (T... args)
- T **oct** (T... args)
- T **strspn** (T... args)
- T **realloc** (T... args)
- T **copy** (T... args)
- T **binary_search** (T... args)
- T **system_category** (T... args)
- T **mbrtowc** (T... args)
- T **strtouf** (T... args)
- T **mem_fn** (T... args)
- T **distance** (T... args)
- T **lock** (T... args)
- T **strcmp** (T... args)
- T **tmpfile** (T... args)
- T **hypot** (T... args)
- T **getenv** (T... args)
- T **strrchr** (T... args)
- T **count** (T... args)
- T **tan** (T... args)
- T **strftime** (T... args)
- T **stod** (T... args)
- T **towupper** (T... args)

- T **atoll** (T... args)
- T **atomic_store** (T... args)
- T **stoi** (T... args)
- T **rethrow_exception** (T... args)
- T **sin** (T... args)
- T **atomic_fetch_sub_explicit** (T... args)
- T **unexpected** (T... args)
- T **mbtowc** (T... args)
- T **get_time** (T... args)
- T **partition** (T... args)
- T **next** (T... args)
- T **isfinite** (T... args)
- T **boolalpha** (T... args)
- T **fetestexcept** (T... args)
- T **mbrlen** (T... args)
- T **iswgraph** (T... args)
- T **time** (T... args)
- T **atomic_compare_exchange_strong** (T... args)
- T **wcschr** (T... args)
- T **uppercase** (T... args)
- T **lower_bound** (T... args)
- T **copy_if** (T... args)
- T **isnan** (T... args)
- T **has_facet** (T... args)
- T **kill_dependency** (T... args)
- T **uninitialized_copy_n** (T... args)
- T **feholdexcept** (T... args)
- T **div** (T... args)
- T **at_quick_exit** (T... args)
- T **wcspbrk** (T... args)
- T **search** (T... args)
- T **find_first_of** (T... args)
- T **iota** (T... args)
- T **declare_reachable** (T... args)
- T **atomic_compare_exchange_weak** (T... args)
- T **strtod** (T... args)
- T **accumulate** (T... args)
- T **wcsrchr** (T... args)
- T **min_element** (T... args)
- T **clearerr** (T... args)
- T **random_shuffle** (T... args)
- T **iswalpha** (T... args)
- T **atomic_fetch_and** (T... args)
- T **wmemchr** (T... args)
- T **bsearch** (T... args)
- T **ilogb** (T... args)
- T **unique_copy** (T... args)
- T **_Exit** (T... args)
- T **move** (T... args)
- T **find_end** (T... args)
- T **fesetexceptflag** (T... args)
- T **nth_element** (T... args)
- T **gets** (T... args)
- T **lexicographical_compare** (T... args)
- T **nearbyint** (T... args)

- T **memcpy** (T... args)
- T **fwrite** (T... args)
- T **unitbuf** (T... args)
- T **iswlower** (T... args)
- T **mblen** (T... args)
- T **swscanf** (T... args)
- T **wcstoimax** (T... args)
- T **fprintf** (T... args)
- T **find_if** (T... args)
- T **strtoimax** (T... args)
- T **isalnum** (T... args)
- T **atomic_fetch_add_explicit** (T... args)
- T **push_heap** (T... args)
- T **min** (T... args)
- T **fwprintf** (T... args)
- T **uncaught_exception** (T... args)
- T **strtoll** (T... args)
- T **throw_with_nested** (T... args)
- T **shuffle** (T... args)
- T **isprint** (T... args)
- T **get_new_handler** (T... args)
- T **call_once** (T... args)
- T **trunc** (T... args)
- T **wcscspn** (T... args)
- T **mbrtoc16** (T... args)
- T **lround** (T... args)
- T **pow** (T... args)
- T **tgamma** (T... args)
- T **erfc** (T... args)
- T **llround** (T... args)
- T **abs(float)** (T... args)
- T **asinh** (T... args)
- T **feof** (T... args)
- T **noskipws** (T... args)
- T **find** (T... args)
- T **atoi** (T... args)
- T **not1** (T... args)
- T **vscanf** (T... args)
- T **stof** (T... args)
- T **regex_search** (T... args)
- T **rotate_copy** (T... args)
- T **set_new_handler** (T... args)
- T **undecclare_no_pointers** (T... args)
- T **async** (T... args)
- T **partition_point** (T... args)
- T **vsscanf** (T... args)
- T **fesetround** (T... args)
- T **atomic_is_lock_free** (T... args)
- T **tanh** (T... args)
- T **ldiv** (T... args)
- T **setbase** (T... args)
- T **remove** (T... args)
- T **strtol** (T... args)
- T **strpbrk** (T... args)
- T **signbit** (T... args)

- T **wcsncat** (T... args)
- T **get_money** (T... args)
- T **set_difference** (T... args)
- T **cref** (T... args)
- T **getline** (T... args)
- T **to_wstring** (T... args)
- T **system** (T... args)
- T **static_pointer_cast** (T... args)
- T **wcstoumax** (T... args)
- T **memmove** (T... args)
- T **getwchar** (T... args)
- T **scientific** (T... args)
- T **wcsftime** (T... args)
- T **begin** (T... args)
- T **ceil** (T... args)
- T **sinh** (T... args)
- T **is_permutation** (T... args)
- T **generate_n** (T... args)
- T **acosh** (T... args)
- T **advance** (T... args)
- T **flush** (T... args)
- T **atomic_fetch_xor** (T... args)
- T **ws** (T... args)
- T **signal** (T... args)
- T **noshowbase** (T... args)
- T **generate** (T... args)
- T **ldexp** (T... args)
- T **vsprintf** (T... args)
- T **remove_if** (T... args)
- T **stoull** (T... args)
- T **fegetexceptflag** (T... args)
- T **find_if_not** (T... args)
- T **merge** (T... args)
- T **free** (T... args)
- T **count_if** (T... args)
- T **clock** (T... args)
- T **mktime** (T... args)
- T **inserter** (T... args)
- T **puts** (T... args)
- T **asin** (T... args)
- T **isctrl** (T... args)
- T **difftime** (T... args)
- T **terminate** (T... args)
- T **memcmp** (T... args)
- T **uninitialized_fill** (T... args)
- T **hex** (T... args)
- T **tie** (T... args)
- T **back_inserter** (T... args)
- T **upper_bound** (T... args)
- T **adjacent_find** (T... args)
- T **use_facet** (T... args)
- T **vfprintf** (T... args)
- T **atomic_fetch_add** (T... args)
- T **fsetpos** (T... args)
- T **malloc** (T... args)

- T **localtime** (T... args)
- T **wcscmp** (T... args)
- T **c32rtomb** (T... args)
- T **isupper** (T... args)
- T **wcstod** (T... args)
- T **tolower** (T... args)
- T **sort_heap** (T... args)
- T **isdigit** (T... args)
- T **wcslen** (T... args)
- T **wmemcmp** (T... args)
- T **move_if_noexcept** (T... args)
- T **declval** (T... args)
- T **fpclassify** (T... args)
- T **iswupper** (T... args)
- T **rand** (T... args)
- T **atomic_compare_exchange_weak_explicit** (T... args)
- T **partial_sort** (T... args)
- T **llrint** (T... args)
- T **fclose** (T... args)
- T **reverse** (T... args)
- T **partial_sum** (T... args)
- T **showbase** (T... args)
- T **vswscanf** (T... args)
- T **atan** (T... args)
- T **atanh** (T... args)
- T **iter_swap** (T... args)
- T **scalbln** (T... args)
- T **reverse_copy** (T... args)
- T **forward** (T... args)
- T **getc** (T... args)
- T **equal_range** (T... args)
- T **atomic_fetch_sub** (T... args)
- T **is_partitioned** (T... args)
- T **next_permutation** (T... args)
- T **isblank** (T... args)
- T **noshowpoint** (T... args)
- T **atan2** (T... args)
- T **nanf** (T... args)
- T **towctrans** (T... args)
- T **right** (T... args)
- T **fputwc** (T... args)
- T **strtoul** (T... args)
- T **is_heap** (T... args)
- T **fflush** (T... args)
- T **strtoumax** (T... args)
- T **nexttoward** (T... args)
- T **nounitbuf** (T... args)
- T **ispunct** (T... args)
- T **noboolalpha** (T... args)
- T **make_pair** (T... args)
- T **iswctype** (T... args)
- T **srand** (T... args)
- T **replace_copy** (T... args)
- T **future_category** (T... args)
- T **resetiosflags** (T... args)

- T **vprintf** (T... args)
- T **gmtime** (T... args)
- T **align** (T... args)
- T **tuple_cat** (T... args)
- T **ends** (T... args)
- T **set_terminate** (T... args)
- T **lrint** (T... args)
- T **none_of** (T... args)
- T **wscanf** (T... args)
- T **fputc** (T... args)
- T **dec** (T... args)
- T **strcat** (T... args)
- T **raise** (T... args)
- T **wcsspn** (T... args)
- T **fabs** (T... args)
- T **wmemcpy** (T... args)
- T **copy_n** (T... args)
- T **rethrow_if_nested** (T... args)
- T **setlocale** (T... args)
- T **addressof** (T... args)
- T **calloc** (T... args)
- T **strerror** (T... args)
- T **strcpy** (T... args)
- T **wcstoull** (T... args)
- T **c16rtomb** (T... args)
- T **generate_canonical** (T... args)
- T **vfprintf** (T... args)
- T **notify_all_at_thread_exit** (T... args)
- T **rotate** (T... args)
- T **current_exception** (T... args)
- T **strtok** (T... args)
- T **wscat** (T... args)
- T **strncpy** (T... args)
- T **tolower** (T... args)
- T **floor** (T... args)
- T **left** (T... args)
- T **ferror** (T... args)
- T **atomic_load_explicit** (T... args)
- T **swap** (T... args)
- T **acos** (T... args)
- T **wscoll** (T... args)
- T **sqrt** (T... args)
- T **mbsinit** (T... args)
- T **qsort** (T... args)
- T **stoll** (T... args)
- T **put_money** (T... args)
- T **wcstoul** (T... args)
- T **wcstol** (T... args)
- T **atexit** (T... args)
- T **atomic_fetch_or** (T... args)
- T **rewind** (T... args)
- T **wcsxfrm** (T... args)
- T **round** (T... args)
- T **vwprintf** (T... args)
- T **all_of** (T... args)

- T **replace** (T... args)
- T **remquo** (T... args)
- T **setbuf** (T... args)
- T **strncmp** (T... args)
- T **localeconv** (T... args)
- T **wctrans** (T... args)
- T **any_of** (T... args)
- T **equal** (T... args)
- T **max** (T... args)
- T **strxfrm** (T... args)
- T **iswxdigit** (T... args)
- T **labs** (T... args)
- T **regex_match** (T... args)
- T **fputws** (T... args)
- T **wcrtomb** (T... args)
- T **setprecision** (T... args)
- T **setvbuf** (T... args)
- T **regex_replace** (T... args)
- T **freopen** (T... args)
- T **logb** (T... args)
- T **wctob** (T... args)
- T **atomic_load** (T... args)
- T **search_n** (T... args)
- T **toupper** (T... args)
- T **move_backward** (T... args)
- T **is_sorted** (T... args)
- T **strtoull** (T... args)
- T **iswblank** (T... args)
- T **get_pointer_safety** (T... args)
- T **get_unexpected** (T... args)
- T **sscanf** (T... args)
- T **fesetenv** (T... args)
- T **atomic_store_explicit** (T... args)
- T **strtold** (T... args)
- T **fread** (T... args)
- T **memchr** (T... args)
- T **btowc** (T... args)
- T **replace_if** (T... args)
- T **strcoll** (T... args)
- T **vsprintf** (T... args)
- T **mismatch** (T... args)
- T **getchar** (T... args)
- T **islower** (T... args)
- T **tmpnam** (T... args)
- T **nanl** (T... args)
- T **fopen** (T... args)
- T **for_each** (T... args)
- T **fegetround** (T... args)
- T **ungetc** (T... args)
- T **internal** (T... args)
- T **vfwscanf** (T... args)
- T **fgetc** (T... args)
- T **wcstof** (T... args)
- T **bind** (T... args)
- T **skipws** (T... args)

- T **iswprint** (T... args)
- T **wcstombs** (T... args)
- T **inplace_merge** (T... args)
- T **copysign** (T... args)
- T **putwchar** (T... args)
- T **wcsstr** (T... args)
- T **fegetenv** (T... args)
- T **longjmp** (T... args)
- T **iswcntrl** (T... args)
- T **declare_no_pointers** (T... args)
- T **isnormal** (T... args)
- T **swap_ranges** (T... args)
- T **minmax** (T... args)
- T **defaultfloat** (T... args)
- T **rename** (T... args)
- T **snprintf** (T... args)
- T **try_lock** (T... args)
- T **stoul** (T... args)
- T **fgetpos** (T... args)
- T **partition_copy** (T... args)
- T **vscanf** (T... args)
- T **front_inserter** (T... args)
- T **get_terminate** (T... args)
- T **cosh** (T... args)
- T **prev** (T... args)
- T **strchr** (T... args)
- T **strstr** (T... args)
- T **printf** (T... args)
- T **setfill** (T... args)
- T **inner_product** (T... args)
- template<typename T , typename... CONSTRUCTOR_ARGS>
std::unique_ptr< T > [make_unique](#) (CONSTRUCTOR_ARGS &&... constructor_args)

9.2.1 Function Documentation

9.2.1.1 make_unique()

```
template<typename T , typename... CONSTRUCTOR_ARGS>
std::unique_ptr<T> std::make_unique (
    CONSTRUCTOR_ARGS &&... constructor_args )
```

Definition at line 203 of file utils.h.

9.3 vxg Namespace Reference

Namespaces

- [cloud](#)
- [media](#)

Data Structures

- class [logger](#)
Logger class, current implementation based on spdlog.

9.4 vxg::cloud Namespace Reference

Namespaces

- [agent](#)
VXG Cloud Agent namespace.
- [sync](#)
- [time_spec](#)
time point
- [utils](#)

Data Structures

- class [cloud_storage](#)
- struct [period](#)
- class [stream_storage](#)
- class [timed_storage](#)
- class [timeline](#)

Typedefs

- using [time](#) = `std::chrono::time_point< std::chrono::system_clock, time_spec::precision >`
- using [duration](#) = `time_spec::duration< time_spec::precision >`
- typedef `std::shared_ptr< timed_storage >` [timed_storage_ptr](#)

Functions

- bool [operator<](#) (const [timed_storage::item_ptr](#) l, const [timed_storage::item_ptr](#) r)

9.4.1 Typedef Documentation

9.4.1.1 duration

```
typedef time\_spec::duration< time\_spec::precision > vxg::cloud::duration
```

Definition at line 40 of file config.h.

9.4.1.2 time

```
typedef std::chrono::time_point< std::chrono::system_clock, time_spec::precision > vxg::cloud::time
```

Definition at line 39 of file config.h.

9.4.1.3 timed_storage_ptr

```
typedef std::shared_ptr<timed_storage> vxg::cloud::timed_storage_ptr
```

Definition at line 131 of file timeline.h.

9.4.2 Function Documentation

9.4.2.1 operator<()

```
bool vxg::cloud::operator< (
    const timed_storage::item_ptr l,
    const timed_storage::item_ptr r ) [inline]
```

Definition at line 127 of file timeline.h.

9.5 vxg::cloud::agent Namespace Reference

VXG Cloud Agent namespace.

Namespaces

- [media](#)
- [proto](#)

Data Structures

- struct [access_token](#)
VXG Cloud access token.
- struct [audio_config](#)
Audio config.
- struct [audio_detection_config](#)
5.6 [audio_detection_config](#) (CM) Current audio detection settings.
- class [callback](#)
VXG Cloud manager common callbacks class.
- struct [event_config](#)
Event config.
- class [event_manager](#)
- class [event_state](#)
- class [event_stream](#)
Event stream, abstract class for event generation.
- struct [events_config](#)
Events config, list of [event_config](#) objects.
- class [manager](#)
VXG Cloud agent manager class.
- struct [osd_config](#)
OSD config.
- struct [ptz_command](#)
PTZ command.
- struct [ptz_config](#)
PTZ config.
- struct [ptz_preset](#)
PTZ preset.
- struct [supported_stream_config](#)
Supported stream config.
- struct [supported_streams_config](#)
Supported streams config, list of [supported_stream_config](#).
- class [synchronizer](#)

Typedefs

- using [event_manager_ptr](#) = `std::shared_ptr< event_manager >`
- using [event_state_ptr](#) = `std::shared_ptr< event_state >`
- using [synchronizer_ptr](#) = `std::shared_ptr< synchronizer >`

Functions

- `std::string version ()`
VXG Cloud Agent library version.

9.5.1 Detailed Description

VXG Cloud Agent namespace.

9.5.2 Typedef Documentation

9.5.2.1 event_manager_ptr

```
using vxg::cloud::agent::event_manager_ptr = typedef std::shared_ptr<event_manager>
```

Definition at line 210 of file event-manager.h.

9.5.2.2 event_state_ptr

```
using vxg::cloud::agent::event_state_ptr = typedef std::shared_ptr<event_state>
```

Definition at line 200 of file event-state.h.

9.5.2.3 synchronizer_ptr

```
using vxg::cloud::agent::synchronizer_ptr = typedef std::shared_ptr<synchronizer>
```

Definition at line 803 of file timeline-synchronizer.h.

9.5.3 Function Documentation

9.5.3.1 version()

```
std::string vxg::cloud::agent::version ( )
```

VXG Cloud Agent library version.

Returns

std::string version string

9.6 vxg::cloud::agent::media Namespace Reference

Data Structures

- class [rtsp_stream](#)
Implementation of the [media::stream](#) with RTSP source and NIY stubs.
- class [stream](#)
Cloud agent media stream abstract class.
- class [stream_callbacks](#)
Cloud agent media stream callbacks abstract class.
- class [stream_callbacks_stub](#)

Typedefs

- using `stream_ptr` = `std::shared_ptr< stream >`

9.6.1 Typedef Documentation

9.6.1.1 stream_ptr

```
using vxg::cloud::agent::media::stream_ptr = typedef std::shared_ptr<stream>
```

Definition at line 236 of file agent/stream.h.

9.7 vxg::cloud::agent::proto Namespace Reference

Data Structures

- struct `audio_caps`
Audio capabilities.
- struct `audio_stream_config`
Audio media stream config.
- struct `event_caps`
Events capabilities.
- struct `motion_detection_caps`
Motion detection capabilities camera capabilities that limit possible motion detection configuration.
- struct `motion_detection_config`
Motion detection config.
- struct `motion_region`
Motion detection related structs.
- struct `osd_caps`
OSD capabilities.
- struct `stream_caps`
Media stream capabilities.
- struct `stream_config`
Media stream config.
- struct `video_caps`
Video image capabilities.
- struct `video_clip_info`
Video recoding(mp4 file) clip description,.
- struct `video_config`
Video image config.
- struct `video_stream_config`
Video stream config.
- struct `wifi_config`
WiFi config.
- struct `wifi_network`
WiFi network object.

Typedefs

- typedef [wifi_config](#) [wifi_list](#)
wifi_config

Enumerations

- enum [mode](#) { [M_OFF](#), [M_ON](#), [M_AUTO](#), [M_INVALID](#) }
Mode on/off.
- enum [video_format](#) { [VF_H264](#), [VF_H265](#), [VF_MJPEG](#), [VF_INVALID](#) }
Video codec format.
- enum [audio_format](#) {
[AF_G711A](#), [AF_G711U](#), [AF_RAW](#), [AF_ADPCM](#),
[AF_MP3](#), [AF_NELLY8](#), [AF_NELLY16](#), [AF_NELLY](#),
[AF_OPUS](#), [AF_AAC](#), [AF_SPEEX](#), [AF_INVALID](#) }
Audio codec format.
- enum [audio_file_format](#) { [AFF_AU_G711U](#), [AFF_MP3](#), [AFF_WAV_PCM](#), [AFF_INVALID](#) }
Audio file format.
- enum [motion_sensitivity](#) { [MS_REGION](#), [MS_FRAME](#), [MS_INVALID](#) }
Motion sensitivity.
- enum [motion_region_shape](#) { [MR_RECTANGLE](#), [MR_ANY](#), [MR_INVALID](#) }
Motion region shape.
- enum [ptz_action](#) {
[A_LEFT](#), [A_RIGHT](#), [A_TOP](#), [A_BOTTOM](#),
[A_ZOOM_IN](#), [A_ZOOM_OUT](#), [A_STOP](#), [A_INVALID](#) }
PTZ actions.
- enum [ptz_preset_action](#) {
[PA_CREATE](#), [PA_DELETE](#), [PA_GOTO](#), [PA_UPDATE](#),
[PA_INVALID](#) }
PTZ preset action.
- enum [time_format_n](#) { [TF_12H](#), [TF_24H](#), [TF_INVALID](#) }
3.34 get_osd_conf (SRV) 3.35 osd_conf (CM) 3.36 set_osd_conf (SRV)
- enum [event_status](#) { [ES_OK](#), [ES_ERROR](#), [ES_INVALID](#) }
Event status.
- enum [event_type](#) {
[ET_MOTION](#), [ET_SOUND](#), [ET_NET](#), [ET_RECORD](#),
[ET_MEMORYCARD](#), [ET_WIFI](#), [ET_CUSTOM](#), [ET_INVALID](#) }
Types of events.
- enum [memorycard_status](#) {
[MCS_NONE](#), [MCS_NORMAL](#), [MCS_NEED_FORMAT](#), [MCS_FORMATTING](#),
[MCS_INITIALIZATION](#), [MCS_INVALID](#) }
Memory card status.
- enum [wifi_encryption](#) {
[WFE_OPEN](#), [WFE_WEP](#), [WFE_WPA](#), [WFE_WPA2](#),
[WFE_WPA_ENTERPRISE](#), [WFE_WPA2_ENTERPRISE](#), [WFE_INVALID](#) }
WiFi encryption type.
- enum [wifi_network_state](#) {
[WNS_UNKNOWN](#), [WNS_INITIALIZE_0](#), [WNS_INITIALIZE_1](#), [WNS_TRY_CONNECT](#),
[WNS_RECEIVING_IP](#), [WNS_CONNECTED](#), [WNS_INVALID](#) }
WiFi connection state.

Functions

- `std::string name () const`

9.7.1 Typedef Documentation

9.7.1.1 wifi_list

```
typedef wifi\_config vxg::cloud::agent::proto::wifi_list
```

[wifi_config](#)

Definition at line 594 of file config.h.

9.7.2 Enumeration Type Documentation

9.7.2.1 audio_file_format

```
enum vxg::cloud::agent::proto::audio\_file\_format
```

Audio file format.

Enumerator

<code>AFF_AU_G711U</code>	AU file format, encoded in mu-law and sampled with 8 or 16 kHz;.
<code>AFF_MP3</code>	MP3 file format, in mono or stereo with bitrate of 64 kbps to 320 kbps and sample rate of 8 to 48 kHz.
<code>AFF_WAV_PCM</code>	WAV file format, encoded in PCM audio that depends on what the product supports. It may support encoded as 8 or 16-bit mono or stereo and sample rate of 8 to 48 kHz;
<code>AFF_INVALID</code>	Invalid value.

Definition at line 147 of file caps.h.

9.7.2.2 audio_format

```
enum vxg::cloud::agent::proto::audio\_format
```

Audio codec format.

Enumerator

AF_G711A	G711A - PCMA, A-Law.
AF_G711U	G711U - PCMU, U-Law.
AF_RAW	PCM.
AF_ADPCM	G726LE.
AF_MP3	
AF_NELLY8	
AF_NELLY16	
AF_NELLY	
AF_OPUS	
AF_AAC	AAC.
AF_SPEEX	
AF_INVALID	Invalid value.

Definition at line 106 of file caps.h.

9.7.2.3 event_status

```
enum vxg::cloud::agent::proto::event_status
```

Event status.

Enumerator

ES_OK	Ok.
ES_ERROR	Error.
ES_INVALID	Default status, invalid.

Definition at line 378 of file config.h.

9.7.2.4 event_type

```
enum vxg::cloud::agent::proto::event_type
```

Types of events.

Enumerator

ET_MOTION	"motion" for motion detection events
ET_SOUND	"sound" for audio detection
ET_NET	"net" for the camera network status change
ET_RECORD	"record" CM informs server about necessity of changing of recording state
ET_MEMORYCARD	"memorycard" camera's memory-card status change
ET_WIFI	"wifi" status of camera's currently used Wi-Fi
ET_CUSTOM	Custom event.
ET_INVALID	Invalid event type.

Definition at line 401 of file config.h.

9.7.2.5 memorycard_status

```
enum vxg::cloud::agent::proto::memorycard_status
```

Memory card status.

Enumerator

MCS_NONE	No memorycard.
MCS_NORMAL	Memorycard is OK.
MCS_NEED_FORMAT	Need formatting.
MCS_FORMATTING	Formatting ongoing.
MCS_INITIALIZATION	Initialization, not mounted yet for example.
MCS_INVALID	Invalid value.

Definition at line 481 of file config.h.

9.7.2.6 mode

```
enum vxg::cloud::agent::proto::mode
```

Mode on/off.

Enumerator

M_OFF	
M_ON	
M_AUTO	
M_INVALID	

Definition at line 30 of file caps.h.

9.7.2.7 motion_region_shape

```
enum vxg::cloud::agent::proto::motion_region_shape
```

Motion region shape.

Enumerator

MR_RECTANGLE	Rectangle.
MR_ANY	Any shape.
MR_INVALID	Invalid.

Definition at line 313 of file caps.h.

9.7.2.8 motion_sensitivity

```
enum vxg::cloud::agent::proto::motion_sensitivity
```

Motion sensitivity.

Enumerator

MS_REGION	Indicates if sensitivity can be set for region.
MS_FRAME	Indicates if sensitivity can be only for the full frame.
MS_INVALID	Invalid value.

Definition at line 291 of file caps.h.

9.7.2.9 ptz_action

```
enum vxg::cloud::agent::proto::ptz_action
```

PTZ actions.

Enumerator

A_LEFT	Go left.
A_RIGHT	Go right.
A_TOP	Go tip.
A_BOTTOM	Go bottom.
A_ZOOM_IN	Zoom in.
A_ZOOM_OUT	Zoom out.
A_STOP	Stop current action.
A_INVALID	Invalid value.

Definition at line 533 of file caps.h.

9.7.2.10 ptz_preset_action

```
enum vxg::cloud::agent::proto::ptz_preset_action
```

PTZ preset action.

Enumerator

PA_CREATE	
PA_DELETE	
PA_GOTO	
PA_UPDATE	
PA_INVALID	

Definition at line 569 of file caps.h.

9.7.2.11 time_format_n

```
enum vxg::cloud::agent::proto::time_format_n
```

3.34 get_osd_conf (SRV) 3.35 osd_conf (CM) 3.36 set_osd_conf (SRV)

Time format

Enumerator

TF_12H	12 hours
TF_24H	24 hours
TF_INVALID	Invalid value.

Definition at line 598 of file caps.h.

9.7.2.12 video_format

```
enum vxg::cloud::agent::proto::video_format
```

Video codec format.

Enumerator

VF_H264	H264 (AVC)
VF_H265	H265 (HEVC)
VF_MJPEG	Motion JPEG.
VF_INVALID	Invalid value.

Definition at line 81 of file caps.h.

9.7.2.13 wifi_encryption

```
enum vxg::cloud::agent::proto::wifi_encryption
```

WiFi encryption type.

Enumerator

WFE_OPEN	No encryption.
WFE_WEP	WEP.
WFE_WPA	WPA-PSK.
WFE_WPA2	WPA2-PSK.
WFE_WPA_ENTERPRISE	WPA-Enterprise.
WFE_WPA2_ENTERPRISE	WPA2-Enterprise.
WFE_INVALID	Default, invalid value.

Definition at line 517 of file config.h.

9.7.2.14 wifi_network_state

```
enum vxg::cloud::agent::proto::wifi_network_state
```

WiFi connection state.

Enumerator

WNS_UNKNOWN	
WNS_INITIALIZE_0	
WNS_INITIALIZE_1	
WNS_TRY_CONNECT	
WNS_RECEIVING_IP	
WNS_CONNECTED	
WNS_INVALID	Invalid value.

Definition at line 597 of file config.h.

9.7.3 Function Documentation

9.7.3.1 name()

```
std::string vxg::cloud::agent::proto::name ( ) const
```

Definition at line 884 of file config.h.

9.8 vxg::cloud::sync Namespace Reference

Data Structures

- class [timeline](#)

Typedefs

- using `timeline_ptr` = `std::shared_ptr< timeline >`

9.8.1 Typedef Documentation

9.8.1.1 timeline_ptr

```
using vxg::cloud::sync::timeline_ptr = typedef std::shared_ptr<timeline>
```

Definition at line 591 of file timeline.h.

9.9 vxg::cloud::time_spec Namespace Reference

time point

Typedefs

- using `precision` = `std::chrono::microseconds`
- template<typename T >
using `duration` = typename `std::conditional< std::is_same< T, precision >::value, precision, std::chrono::duration< T > >::type`
- using `precision_ratio` = `std::micro`

9.9.1 Detailed Description

time point

9.9.2 Typedef Documentation

9.9.2.1 duration

```
template<typename T >  
using vxg::cloud::time_spec::duration = typedef typename std::conditional< std::is_same<T,  
precision>::value, precision, std::chrono::duration<T> >::type
```

Definition at line 36 of file config.h.

9.9.2.2 precision

```
typedef std::chrono::microseconds vxg::cloud::time_spec::precision
```

Definition at line 32 of file config.h.

9.9.2.3 precision_ratio

```
using vxg::cloud::time_spec::precision_ratio = typedef std::micro
```

Definition at line 16 of file utils.h.

9.10 vxg::cloud::utils Namespace Reference

Namespaces

- [gcc_abi](#)
- [motion](#)
- [time](#)

Data Structures

- class [queued_async_handler](#)
- struct [uri](#)

Typedefs

- `template<class T >`
using [queued_async_handler_ptr](#) = `std::shared_ptr< queued_async_handler< T > >`

Functions

- void [set_thread_name](#) (`std::string name`)
- `template<typename... Args>`
`std::string string_format (const std::string &format, Args... args)`
- `std::string string_trim (const std::string &name, std::regex regx)`
- `std::string string_trim (const std::string &name)`
- `std::vector< std::string > string_split (const std::string &s, char delimiter)`
- bool [string_startswith](#) (`std::string const &fullString, std::string const &start`)
- bool [string_endswith](#) (`std::string const &fullString, std::string const &ending`)
- bool [string_replace](#) (`std::string &str, const std::string &from, const std::string &to`)
- `std::string string_urlencode (const std::string &value)`
- `std::string string_urldecode (const std::string &text)`
- `std::string string_tolower (const std::string &s)`
- `std::string string_toupper (const std::string &s)`
- bool [string_contains](#) (`std::string s, char c`)
- bool [string_contains](#) (`std::string s, std::string substring`)
- `std::string dirname (const std::string &filepath)`
- `std::string random_string (size_t length=32)`

9.10.1 Typedef Documentation

9.10.1.1 `queued_async_handler_ptr`

```
template<class T >
using vxg::cloud::utils::queued_async_handler_ptr = typedef std::shared_ptr<queued_async_handler<T>
>
```

Definition at line 61 of file `queued-handler.h`.

9.10.2 Function Documentation

9.10.2.1 `dirname()`

```
std::string vxg::cloud::utils::dirname (
    const std::string & filepath )
```

9.10.2.2 `random_string()`

```
std::string vxg::cloud::utils::random_string (
    size_t length = 32 ) [inline]
```

Definition at line 182 of file `utils.h`.

9.10.2.3 `set_thread_name()`

```
void vxg::cloud::utils::set_thread_name (
    std::string name )
```

9.10.2.4 `string_contains()` [1/2]

```
bool vxg::cloud::utils::string_contains (
    std::string s,
    char c ) [inline]
```

Definition at line 170 of file `utils.h`.

9.10.2.5 string_contains() [2/2]

```
bool vxg::cloud::utils::string_contains (
    std::string s,
    std::string substring ) [inline]
```

Definition at line 173 of file utils.h.

9.10.2.6 string_endswith()

```
bool vxg::cloud::utils::string_endswith (
    std::string const & fullString,
    std::string const & ending )
```

9.10.2.7 string_format()

```
template<typename... Args>
std::string vxg::cloud::utils::string_format (
    const std::string & format,
    Args... args )
```

Definition at line 147 of file utils.h.

9.10.2.8 string_replace()

```
bool vxg::cloud::utils::string_replace (
    std::string & str,
    const std::string & from,
    const std::string & to )
```

9.10.2.9 string_split()

```
std::vector< std::string> vxg::cloud::utils::string_split (
    const std::string & s,
    char delimiter )
```

9.10.2.10 string_startswith()

```
bool vxg::cloud::utils::string_startswith (
    std::string const & fullString,
    std::string const & start )
```

9.10.2.11 string_tolower()

```
std::string vxg::cloud::utils::string_tolower (
    const std::string & s )
```

9.10.2.12 string_toupper()

```
std::string vxg::cloud::utils::string_toupper (
    const std::string & s )
```

9.10.2.13 string_trim() [1/2]

```
std::string vxg::cloud::utils::string_trim (
    const std::string & name )
```

9.10.2.14 string_trim() [2/2]

```
std::string vxg::cloud::utils::string_trim (
    const std::string & name,
    std::regex regx )
```

9.10.2.15 string_urldecode()

```
std::string vxg::cloud::utils::string_urldecode (
    const std::string & text )
```

9.10.2.16 string_urlencode()

```
std::string vxg::cloud::utils::string_urlencode (
    const std::string & value )
```

9.11 vxg::cloud::utils::gcc_abi Namespace Reference

Functions

- `std::string demangle (std::string name)`

9.11.1 Function Documentation

9.11.1.1 demangle()

```
std::string vxg::cloud::utils::gcc_abi::demangle (
    std::string name )
```

9.12 vxg::cloud::utils::motion Namespace Reference

Data Structures

- struct `map`

9.13 vxg::cloud::utils::time Namespace Reference

Functions

- `cloud::time now ()`
- `std::string now_ISO8601_UTC ()`
- `std::string now_ISO8601_UTC_packed ()`
- `std::string to_iso_8601 (cloud::time t)`
- `std::string to_iso (cloud::time t)`
- `std::string to_iso2 (cloud::time t)`
- `std::string to_iso_packed (cloud::time t)`
- `std::string to_iso_local (cloud::time t)`
- `cloud::time from_double (double t)`
- `double to_double (cloud::time t)`
- `cloud::time from_iso (std::string st)`
- `cloud::time from_iso2 (std::string st)`
- `cloud::time from_iso_packed (std::string st)`
- `bool iso_time_valid (const std::string &s)`
- `cloud::time null ()`
- `cloud::time epoch ()`
- `cloud::time max ()`
- `bool is_iso_packed (const std::string &s)`
- `bool is_iso (const std::string &s)`

9.13.1 Function Documentation

9.13.1.1 epoch()

```
cloud::time vxg::cloud::utils::time::epoch ( ) [inline]
```

Definition at line 54 of file utils.h.

9.13.1.2 from_double()

```
cloud::time vxg::cloud::utils::time::from_double (
    double t )
```

9.13.1.3 from_iso()

```
cloud::time vxg::cloud::utils::time::from_iso (
    std::string st )
```

9.13.1.4 from_iso2()

```
cloud::time vxg::cloud::utils::time::from_iso2 (
    std::string st )
```

9.13.1.5 from_iso_packed()

```
cloud::time vxg::cloud::utils::time::from_iso_packed (
    std::string st )
```

9.13.1.6 is_iso()

```
bool vxg::cloud::utils::time::is_iso (
    const std::string & s )
```

9.13.1.7 is_iso_packed()

```
bool vxg::cloud::utils::time::is_iso_packed (
    const std::string & s )
```

9.13.1.8 iso_time_valid()

```
bool vxg::cloud::utils::time::iso_time_valid (
    const std::string & s )
```

9.13.1.9 max()

```
cloud::time vxg::cloud::utils::time::max ( ) [inline]
```

Definition at line 58 of file utils.h.

9.13.1.10 now()

```
cloud::time vxg::cloud::utils::time::now ( ) [inline]
```

Definition at line 32 of file utils.h.

9.13.1.11 now_ISO8601.UTC()

```
std::string vxg::cloud::utils::time::now_ISO8601.UTC ( )
```

9.13.1.12 now_ISO8601.UTC_packed()

```
std::string vxg::cloud::utils::time::now_ISO8601.UTC_packed ( )
```

9.13.1.13 null()

```
cloud::time vxg::cloud::utils::time::null ( ) [inline]
```

Definition at line 51 of file utils.h.

9.13.1.14 to_double()

```
double vxg::cloud::utils::time::to_double (
    cloud::time t )
```

9.13.1.15 to_iso()

```
std::string vxg::cloud::utils::time::to_iso (
    cloud::time t )
```

9.13.1.16 to_iso2()

```
std::string vxg::cloud::utils::time::to_iso2 (
    cloud::time t )
```

9.13.1.17 to_iso_8601()

```
std::string vxg::cloud::utils::time::to_iso_8601 (
    cloud::time t )
```

9.13.1.18 to_iso_local()

```
std::string vxg::cloud::utils::time::to_iso_local (
    cloud::time t )
```

9.13.1.19 to_iso_packed()

```
std::string vxg::cloud::utils::time::to_iso_packed (
    cloud::time t )
```

9.14 vxg::media Namespace Reference

Namespaces

- [ffmpeg](#)
- [stream_error](#)
Media stream error namespace.
- [Streamer](#)

Data Structures

- class [rtmp_sink](#)
RTMP sink class.
- class [rtmp_source](#)
RTMP source class.
- class [rtsp_source](#)
RTSP source class.
- class [stream](#)
base media stream abstract class

Typedefs

- using [rtsp_source_ptr](#) = `std::shared_ptr<rtsp_source>`

9.14.1 Typedef Documentation

9.14.1.1 rtsp_source_ptr

using [vxg::media::rtsp_source_ptr](#) = typedef `std::shared_ptr<rtsp_source>`

Definition at line 187 of file `rtsp_source.h`.

9.15 vxg::media::ffmpeg Namespace Reference

Data Structures

- class [Sink](#)
Base ffmpeg sink class.
- class [Source](#)
Base ffmpeg source class.

9.16 vxg::media::stream_error Namespace Reference

Media stream error namespace.

Data Structures

- struct [report](#)
Media stream error report simple object.

Enumerations

- enum `origin` : int { `origin::O_SOURCE`, `origin::O_SINK`, `origin::O_UNKNOWN` }
Origin of the error.
- enum `error` : int { `error::E_CONNECT`, `error::E_PROCESS`, `error::E_UNKNOWN` }
Error code.

9.16.1 Detailed Description

Media stream error namespace.

9.16.2 Enumeration Type Documentation

9.16.2.1 error

```
enum vxg::media::stream_error::error : int [strong]
```

Error code.

Enumerator

E_CONNECT	Connection failed.
E_PROCESS	Processing failed, may be caused by peer connection problems.
E_UNKNOWN	Unknown error.

Definition at line 30 of file streamer/stream.h.

9.16.2.2 origin

```
enum vxg::media::stream_error::origin : int [strong]
```

Origin of the error.

Enumerator

O_SOURCE	Source element of the media stream pipeline (ex. rtsp_source or custom source)
O_SINK	Sink element of the media stream pipeline (ex. rtmp_sink or custom sink)
O_UNKNOWN	Unknown origin.

Definition at line 18 of file streamer/stream.h.

9.17 vxg::media::Streamer Namespace Reference

Data Structures

- class [ISink](#)
- class [ISource](#)
ISource interface class.
- struct [MediaFrame](#)
Media frame container.
- struct [StreamInfo](#)
Stream info description.

Typedefs

- using [on_error_cb](#) = **std::function**< void([Streamer::StreamError](#) e)>
On error callback, used for both [ISink](#) and [ISource](#) if was provided by user.

Enumerations

- enum [DropDirection](#) { [DROP_FRONT](#), [DROP_BACK](#) }
- enum [StreamError](#) { [E_NONE](#), [E_FATAL](#), [E_EOS](#) }
Stream error.
- enum [MediaType](#) {
[UNKNOWN](#), [VIDEO](#), [VIDEO_AVC_SPS](#), [VIDEO_AVC_PPS](#),
[VIDEO_SEQ_HDR](#), [AUDIO](#), [AUDIO_SEQ_HDR](#), [FLV](#),
[DATA](#), [MAX](#) }
Media frame type.

Variables

- constexpr int [SINK_THREAD_PRIO](#)
- constexpr int [SRC_THREAD_PRIO](#)

9.17.1 Typedef Documentation

9.17.1.1 on_error_cb

```
using vxg::media::Streamer::on_error_cb = typedef std::function<void(Streamer::StreamError e)>
```

On error callback, used for both [ISink](#) and [ISource](#) if was provided by user.

Definition at line 53 of file base_streamer.h.

9.17.2 Enumeration Type Documentation

9.17.2.1 DropDirection

```
enum vxg::media::Streamer::DropDirection
```

Enumerator

DROP_FRONT	
DROP_BACK	

Definition at line 38 of file base_streamer.h.

9.17.2.2 MediaType

```
enum vxg::media::Streamer::MediaType
```

Media frame type.

Used to indicate when type of frame was passed from source to sink.

Enumerator

UNKNOWN	
VIDEO	
VIDEO_AVC_SPS	
VIDEO_AVC_PPS	
VIDEO_SEQ_HDR	
AUDIO	
AUDIO_SEQ_HDR	
FLV	
DATA	
MAX	

Definition at line 404 of file base_streamer.h.

9.17.2.3 StreamError

```
enum vxg::media::Streamer::StreamError
```

Stream error.

Enumerator

E_NONE	
E_FATAL	
E_EOS	

Definition at line 44 of file base_streamer.h.

9.17.3 Variable Documentation

9.17.3.1 SINK_THREAD_PRIO

```
constexpr int vxg::media::Streamer::SINK_THREAD_PRIO [constexpr]
```

Definition at line 36 of file base_streamer.h.

9.17.3.2 SRC_THREAD_PRIO

```
constexpr int vxg::media::Streamer::SRC_THREAD_PRIO [constexpr]
```

Definition at line 37 of file base_streamer.h.

Chapter 10

Data Structure Documentation

10.1 vxg::cloud::agent::access_token Struct Reference

VXG Cloud access token.

```
#include <agent-proto/objects/config.h>
```

Data Structures

- struct [proxy_config](#)
Socks proxy settings.

Public Types

- typedef **std::shared_ptr**< [access_token](#) > ptr

Public Member Functions

- **std::string** [api_uri](#) (bool secure=true)
- **std::string** [cam_base_uri](#) (bool secure=true, const **std::string** &input_host="")
- **std::string** [pack](#) ()

Static Public Member Functions

- static [access_token](#) [parse](#) (**std::string** packed_token)

10.1.1 Detailed Description

VXG Cloud access token.

Definition at line 1189 of file config.h.

10.1.2 Member Typedef Documentation

10.1.2.1 ptr

```
typedef std::shared_ptr<access_token> vxg::cloud::agent::access_token::ptr
```

Definition at line 1190 of file config.h.

10.1.3 Member Function Documentation

10.1.3.1 api_uri()

```
std::string vxg::cloud::agent::access_token::api_uri (
    bool secure = true ) [inline]
```

Definition at line 1258 of file config.h.

10.1.3.2 cam_base_uri()

```
std::string vxg::cloud::agent::access_token::cam_base_uri (
    bool secure = true,
    const std::string & input_host = "" ) [inline]
```

Definition at line 1266 of file config.h.

10.1.3.3 pack()

```
std::string vxg::cloud::agent::access_token::pack ( ) [inline]
```

Definition at line 1276 of file config.h.

10.1.3.4 parse()

```
static access_token vxg::cloud::agent::access_token::parse (
    std::string packed_token ) [inline], [static]
```

Definition at line 1278 of file config.h.

The documentation for this struct was generated from the following file:

- [config.h](#)

10.2 alter_bool Struct Reference

alternative bool class Standard bool type has two states, this class adds 3rd state - undefined.

```
#include <agent-proto/command/unset-helper.h>
```

Public Types

- enum `n_alter_bool` { `B_FALSE`, `B_TRUE`, `B_INVALID` }
Internal boolean values.

Public Member Functions

- `alter_bool` (const `n_alter_bool` &*v*)
- `alter_bool` (const bool &*v*)
- `alter_bool operator=` (const bool &*b*)
- `operator bool` () const

Data Fields

- `n_alter_bool` *val*

Friends

- void `from_json` (const `nlohmann::json` &*j*, `alter_bool` &*c*)
- void `to_json` (`nlohmann::json` &*j*, const `alter_bool` &*c*)

10.2.1 Detailed Description

alternative bool class Standard bool type has two states, this class adds 3rd state - undefined.

This class used for json boolean => C++ bool type reflection. The `B_INVALID` value of the C++ data indicates that source json has no such field.

Definition at line 168 of file unset-helper.h.

10.2.2 Member Enumeration Documentation

10.2.2.1 n_alter_bool

```
enum alter_bool::n_alter_bool
```

Internal boolean values.

Enumerator

B_FALSE	false
B_TRUE	true
B_INVALID	Undefined, i.e. if the object was constructed from the json object this value means that original json had no such field.

Definition at line 170 of file unset-helper.h.

10.2.3 Constructor & Destructor Documentation

10.2.3.1 alter_bool() [1/2]

```
alter_bool::alter_bool (
    const n_alter_bool & v ) [inline]
```

Definition at line 180 of file unset-helper.h.

10.2.3.2 alter_bool() [2/2]

```
alter_bool::alter_bool (
    const bool & v ) [inline]
```

Definition at line 182 of file unset-helper.h.

10.2.4 Member Function Documentation

10.2.4.1 operator bool()

```
alter_bool::operator bool ( ) const [inline]
```

Definition at line 196 of file unset-helper.h.

10.2.4.2 operator=()

```
alter_bool alter_bool::operator= (
    const bool & b ) [inline]
```

Definition at line 189 of file unset-helper.h.

10.2.5 Friends And Related Function Documentation

10.2.5.1 from_json

```
void from_json (  
    const nlohmann::json & j,  
    alter_bool & c ) [friend]
```

Definition at line 202 of file unset-helper.h.

10.2.5.2 to_json

```
void to_json (  
    nlohmann::json & j,  
    const alter_bool & c ) [friend]
```

Definition at line 209 of file unset-helper.h.

10.2.6 Field Documentation

10.2.6.1 val

```
n_alter_bool alter_bool::val
```

Definition at line 216 of file unset-helper.h.

The documentation for this struct was generated from the following file:


- [unset-helper.h](#)

10.3 vxg::cloud::agent::proto::audio_caps Struct Reference

Audio capabilities.

```
#include <agent-proto/objects/caps.h>
```

Collaboration diagram for vxg::cloud::agent::proto::audio_caps:



Data Fields

- [alter_bool mic](#)
mic: bool, microphone is supported
- [alter_bool spkr](#)
spkr: bool, speaker is supported
- **std::vector**< [mode](#) > [echo_cancel](#)
echo_cancel: list of string, echo cancellation modes, empty or absent means not supported
- [alter_bool backward](#)
backward: bool, backward audio supported.
- **std::vector**< [audio_format](#) > [backward_formats](#)
backward_formats: list of audio_format, list of supported backward formats.
- **std::vector**< [audio_file_format](#) > [audio_file_formats](#)
audio_file_formats: list of string, list of supported formats of audio files.

10.3.1 Detailed Description

Audio capabilities.

Definition at line 490 of file caps.h.

10.3.2 Field Documentation

10.3.2.1 audio_file_formats

```
std::vector<audio_file_format> vxg::cloud::agent::proto::audio_caps::audio_file_formats
```

audio_file_formats: list of string, list of supported formats of audio files.

Definition at line 513 of file caps.h.

10.3.2.2 backward

```
alter_bool vxg::cloud::agent::proto::audio_caps::backward
```

backward: bool, backward audio supported.

Obsolete. Server will ignore it when backward_formats exists. If true and backward_formats is missed, server will interpret supported formats list as ["UNKNOWN"]

Definition at line 503 of file caps.h.

10.3.2.3 backward_formats

```
std::vector<audio_format> vxg::cloud::agent::proto::audio_caps::backward_formats
```

backward_formats: list of audio_format, list of supported backward formats.

Supported values: ["RAW", "ADPCM", "MP3", "NELLY8", "NELLY16", "NELLY", "G711A", "G711U", "AAC", "SPEEX", "UNKNOWN"]. Empty list or missing parameter – camera doesn't support back audio channel.

Definition at line 509 of file caps.h.

10.3.2.4 echo_cancel

```
std::vector<mode> vxg::cloud::agent::proto::audio_caps::echo_cancel
```

echo_cancel: list of string, echo cancellation modes, empty or absent means not supported

Definition at line 498 of file caps.h.

10.3.2.5 mic

```
alter_bool vxg::cloud::agent::proto::audio_caps::mic
```

mic: bool, microphone is supported

Definition at line 492 of file caps.h.

10.3.2.6 spkr

`alter_bool vxg::cloud::agent::proto::audio_caps::spkr`

spkr: bool, speaker is supported

Definition at line 495 of file caps.h.

The documentation for this struct was generated from the following file:


- [caps.h](#)

10.4 vxg::cloud::agent::audio_config Struct Reference

Audio config.

```
#include <agent-proto/objects/config.h>
```

Collaboration diagram for vxg::cloud::agent::audio_config:



Data Fields

- int [mic_gain](#)
mic_gain: optional int range 0-100, microphone gain
- [alter_bool](#) [mic_mute](#)
mic_mute: optional bool, microphone mute
- int [spkr_vol](#)
spkr_vol: optional int range 0-100, speaker volume
- [alter_bool](#) [spkr_mute](#)
spkr_mute: optional bool, speaker mute
- mode [echo_cancel](#)
echo_cancel: optional string, echo cancellation mode, "" means off
- audio_caps [caps](#)
caps

10.4.1 Detailed Description

Audio config.

Definition at line 1033 of file config.h.

10.4.2 Field Documentation

10.4.2.1 caps

```
audio_caps vxg::cloud::agent::audio_config::caps
```

caps

Definition at line 1046 of file config.h.

10.4.2.2 echo_cancel

```
mode vxg::cloud::agent::audio_config::echo_cancel
```

echo_cancel: optional string, echo cancellation mode, "" means off

Definition at line 1043 of file config.h.

10.4.2.3 mic_gain

```
int vxg::cloud::agent::audio_config::mic_gain
```

mic_gain: optional int range 0-100, microphone gain

Definition at line 1035 of file config.h.

10.4.2.4 mic_mute

```
alter_bool vxg::cloud::agent::audio_config::mic_mute
```

mic_mute: optional bool, microphone mute

Definition at line 1037 of file config.h.

10.4.2.5 spkr_mute

`alter_bool vxg::cloud::agent::audio_config::spkr_mute`

`spkr_mute`: optional bool, speaker mute

Definition at line 1041 of file `config.h`.

10.4.2.6 spkr_vol

`int vxg::cloud::agent::audio_config::spkr_vol`

`spkr_vol`: optional int range 0-100, speaker volume

Definition at line 1039 of file `config.h`.


The documentation for this struct was generated from the following file:

- [config.h](#)

10.5 vxg::cloud::agent::audio_detection_config::audio_detection_conf_caps Struct Reference

```
#include <agent-proto/objects/config.h>
```

Collaboration diagram for `vxg::cloud::agent::audio_detection_config::audio_detection_conf_caps`:



Public Member Functions

- [JSON_DEFINE_TYPE_INTRUSIVE](#) (`audio_detection_conf_caps`, `level`)

Data Fields

- **std::tuple**< int, int, int > [level](#)
level: (min:int, max:int, step:int), volume range and step in -dB

10.5.1 Detailed Description

Definition at line 1428 of file config.h.

10.5.2 Member Function Documentation

10.5.2.1 JSON_DEFINE_TYPE_INTRUSIVE()

```
vxg::cloud::agent::audio_detection_config::audio_detection_conf_caps::JSON_DEFINE_TYPE_INTRUSIVE (
    audio_detection_conf_caps ,
    level )
```

10.5.3 Field Documentation

10.5.3.1 level

```
std::tuple<int, int, int> vxg::cloud::agent::audio_detection_config::audio_detection_conf_caps::level
```

level: (min:int, max:int, step:int), volume range and step in -dB

Definition at line 1430 of file config.h.

The documentation for this struct was generated from the following file:


- [config.h](#)

10.6 vxg::cloud::agent::audio_detection_config Struct Reference

5.6 [audio_detection_config](#) (CM) Current audio detection settings.

```
#include <agent-proto/objects/config.h>
```

Collaboration diagram for vxg::cloud::agent::audio_detection_config:



Data Structures

- struct [audio_detection_conf_caps](#)

Public Member Functions

- [JSON_DEFINE_TYPE_INTRUSIVE](#) ([audio_detection_config](#), [level](#), [length](#), [caps](#))

Data Fields

- int [level](#)
level: int, audio volume in -dB
- int [length](#)
length: int, duration before event trigger, msec
- [audio_detection_conf_caps](#) [caps](#)
caps:

10.6.1 Detailed Description

5.6 [audio_detection_config](#) (CM) Current audio detection settings.

Reply 5.4 [get_audio_detection](#) (SRV).

Definition at line 1422 of file [config.h](#).

10.6.2 Member Function Documentation

10.6.2.1 JSON_DEFINE_TYPE_INTRUSIVE()

```
vxg::cloud::agent::audio_detection_config::JSON_DEFINE_TYPE_INTRUSIVE (
    audio\_detection\_config ,
    level ,
    length ,
    caps )
```

10.6.3 Field Documentation

10.6.3.1 caps

[audio_detection_conf_caps](#) vxg::cloud::agent::audio_detection_config::caps

caps:

Definition at line 1435 of file [config.h](#).

10.6.3.2 length

```
int vxg::cloud::agent::audio_detection_config::length
```

length: int, duration before event trigger, msec

Definition at line 1426 of file [config.h](#).

10.6.3.3 level

```
int vxg::cloud::agent::audio_detection_config::level
```

level: int, audio volume in -dB

Definition at line 1424 of file config.h.

The documentation for this struct was generated from the following file:


- [config.h](#)

10.7 vxg::cloud::agent::proto::audio_stream_config Struct Reference

Audio media stream config.

```
#include <agent-proto/objects/config.h>
```

Collaboration diagram for vxg::cloud::agent::proto::audio_stream_config:



Data Fields

- **std::string** [stream](#)
Mandatory: audio ES to use.
- [audio_format](#) [format](#)
Mandatory: audio encoding format.
- int [brt](#)
Mandatory: bitrate, kbps.
- double [srt](#)
Mandatory: samplerate, KHz.

10.7.1 Detailed Description

Audio media stream config.

Definition at line 179 of file config.h.

10.7.2 Field Documentation

10.7.2.1 brt

```
int vxg::cloud::agent::proto::audio_stream_config::brt
```

Mandatory: bitrate, kbps.

Definition at line 190 of file config.h.

10.7.2.2 format

```
audio_format vxg::cloud::agent::proto::audio_stream_config::format
```

Mandatory: audio encoding format.

Definition at line 186 of file config.h.

10.7.2.3 srt

```
double vxg::cloud::agent::proto::audio_stream_config::srt
```

Mandatory: samplerate, KHz.

Definition at line 194 of file config.h.

10.7.2.4 stream

```
std::string vxg::cloud::agent::proto::audio_stream_config::stream
```

Mandatory: audio ES to use.

Definition at line 182 of file config.h.

The documentation for this struct was generated from the following file:


- [config.h](#)

10.8 vxg::media::Streamer::StreamInfo::AudioInfo Struct Reference

Audio stream info.

```
#include <streamer/base_streamer.h>
```

Collaboration diagram for vxg::media::Streamer::StreamInfo::AudioInfo:



Data Fields

- [AudioCodec codec](#)
Audio codec.
- int [channels](#)
Audio channels.
- int [samplerate](#)
Audio samplerate.
- int [bitrate](#)
Audio bitrate.
- **std::pair**< int, int > [timebase](#)
Audio timestamps timescale.
- **std::vector**< uint8_t > [extradata](#)
Audio extradata. AAC requires one.

10.8.1 Detailed Description

Audio stream info.

Definition at line 364 of file base_streamer.h.

10.8.2 Field Documentation

10.8.2.1 bitrate

```
int vxg::media::Streamer::StreamInfo::AudioInfo::bitrate
```

Audio bitrate.

Definition at line 372 of file base_streamer.h.

10.8.2.2 channels

```
int vxg::media::Streamer::StreamInfo::AudioInfo::channels
```

Audio channels.

Definition at line 368 of file base_streamer.h.

10.8.2.3 codec

```
AudioCodec vxg::media::Streamer::StreamInfo::AudioInfo::codec
```

Audio codec.

Definition at line 366 of file base_streamer.h.

10.8.2.4 extradata

```
std::vector<uint8_t> vxg::media::Streamer::StreamInfo::AudioInfo::extradata
```

Audio extradata. AAC requires one.

Definition at line 376 of file base_streamer.h.

10.8.2.5 samplerate

```
int vxg::media::Streamer::StreamInfo::AudioInfo::samplerate
```

Audio samplerate.

Definition at line 370 of file base_streamer.h.

10.8.2.6 timebase

```
std::pair<int, int> vxg::media::Streamer::StreamInfo::AudioInfo::timebase
```

Audio timestamps timescale.

Definition at line 374 of file base_streamer.h.

The documentation for this struct was generated from the following file:

- [base_streamer.h](#)

10.9 vxg::cloud::agent::callback Class Reference

VXG Cloud manager common callbacks class.

```
#include <agent/callback.h>
```

Public Types

- typedef **std::unique_ptr**< [callback](#) > ptr
std::unique_ptr to callback

Public Member Functions

- virtual void [on_bye](#) (proto::command::bye_reason reason)=0
VXG Cloud Bye command callback.
- virtual void [on_registered](#) (const **std::string** &sid)
Registration on the Cloud has passed callback.
- virtual bool [on_raw_msg](#) (**std::string** client_id, **std::string** &data)
raw message callback
- virtual bool [on_get_log](#) (**std::string** &log_data)
Get logging data callback.
- virtual bool [on_start_backward_audio](#) (**std::string** url)
Start backward audio stream.
- virtual bool [on_stop_backward_audio](#) (**std::string** url)
Stop backward audio.
- virtual bool [on_get_cam_video_config](#) (proto::video_config &config)
Get video image config.
- virtual bool [on_set_cam_video_config](#) (const proto::video_config &config)
Set video input config.
- virtual bool [on_get_cam_audio_config](#) (proto::audio_config &config)
Get audio input configuration.
- virtual bool [on_set_cam_audio_config](#) (const proto::audio_config &config)
Set audio input/output config.
- virtual bool [on_get_ptz_config](#) (proto::ptz_config &config)
Get PTZ config.
- virtual bool [on_cam_ptz](#) (proto::ptz_command &command)

- PTZ command.*
- virtual bool [on_cam_ptz_preset](#) (proto::ptz_preset &preset_op)
- PTZ preset command.*
- virtual bool [on_get_osd_config](#) (proto::osd_config &config)
- Get OSD config.*
- virtual bool [on_set_osd_config](#) (const proto::osd_config &config)
- Set OSD config.*
- virtual bool [on_get_wifi_config](#) (proto::wifi_config &config)
- Get WiFi config.*
- virtual bool [on_set_wifi_config](#) (const proto::wifi_network &config)
- Set WiFi config.*
- virtual bool [on_get_motion_detection_config](#) (proto::motion_detection_config &config)
- Get motion detection configuration.*
- virtual bool [on_set_motion_detection_config](#) (const proto::motion_detection_config &config)
- Set motion detection config.*
- virtual bool [on_get_timezone](#) (**std::string** &timezone)
- Get device timezone in IANA format.*
- virtual bool [on_set_timezone](#) (**std::string** timezone)
- Set device timezone in IANA format.*
- virtual bool [on_get_memorycard_info](#) (proto::event_object::memorycard_info_object &info)
- Get memory card information, If this callback returned false or if `info` status not equal to [proto::MCS_NORMAL](#), the recording will not be started, i.e.*
- virtual bool [on_cam_upgrade_firmware](#) (const **std::string** &firmware)
- Firmware upgrade.*
- virtual bool [on_audio_file_play](#) (const **std::string** audio_file_data, const **std::string** filename)
- Audio file play.*
- virtual bool [on_trigger_event](#) (proto::event_object &event)
- virtual bool [on_set_audio_detection](#) (const proto::audio_detection_config &conf)
- virtual bool [on_get_audio_detection](#) (proto::audio_detection_config &conf)

10.9.1 Detailed Description

VXG Cloud manager common callbacks class.

Definition at line 17 of file callback.h.

10.9.2 Member Typedef Documentation

10.9.2.1 ptr

```
typedef std::unique_ptr<callback> vxg::cloud::agent::callback::ptr
```

std::unique_ptr to callback

Definition at line 20 of file callback.h.

10.9.3 Member Function Documentation

10.9.3.1 on_audio_file_play()

```
virtual bool vxg::cloud::agent::callback::on_audio_file_play (
    const std::string audio_file_data,
    const std::string filename ) [inline], [virtual]
```

Audio file play.

Parameters

in	<i>audio_file</i>	Audio file binary data.
in	<i>audio_file_format</i>	Audio file data format.

Returns

true if firmware upgrade was successful.

false if firmware upgrade failed.

Definition at line 309 of file callback.h.

10.9.3.2 on_bye()

```
virtual void vxg::cloud::agent::callback::on_bye (
    proto::command::bye_reason reason ) [pure virtual]
```

VXG Cloud Bye command callback.

Parameters

<i>reason</i>	bye reason
---------------	------------

10.9.3.3 on_cam_ptz()

```
virtual bool vxg::cloud::agent::callback::on_cam_ptz (
    proto::ptz_command & command ) [inline], [virtual]
```

PTZ command.

Parameters

<i>in</i>	<i>command</i>	ptz command
-----------	----------------	-------------

Returns

true success
false PTZ command failure

Definition at line 163 of file callback.h.

10.9.3.4 on_cam_ptz_preset()

```
virtual bool vxg::cloud::agent::callback::on_cam_ptz_preset (  
    proto::ptz_preset & preset_op ) [inline], [virtual]
```

PTZ preset command.

Parameters

<i>in, out</i>	<i>preset_op</i>	ptz preset operation, if operation is proto::PA_CREATE the callee should fill the token.
----------------	------------------	--

Returns

true PTZ preset operation success
false PTZ preset operation failure

Definition at line 175 of file callback.h.

10.9.3.5 on_cam_upgrade_firmware()

```
virtual bool vxg::cloud::agent::callback::on_cam_upgrade_firmware (  
    const std::string & firmware ) [inline], [virtual]
```

Firmware upgrade.

Parameters

<i>in</i>	<i>firmware</i>	Firmware binary data.
-----------	-----------------	-----------------------

Returns

true if firmware upgrade was successful.
false if firmware upgrade failed.

Definition at line 299 of file callback.h.

10.9.3.6 on_get_audio_detection()

```
virtual bool vxg::cloud::agent::callback::on_get_audio_detection (
    proto::audio_detection_config & conf ) [inline], [virtual]
```

Definition at line 326 of file callback.h.

10.9.3.7 on_get_cam_audio_config()

```
virtual bool vxg::cloud::agent::callback::on_get_cam_audio_config (
    proto::audio_config & config ) [inline], [virtual]
```

Get audio input configuration.

Parameters

out	<i>config</i>	audio input config
-----	---------------	--------------------

Returns

true get audio input configuration success
false get audio input configuration failed

Definition at line 127 of file callback.h.

10.9.3.8 on_get_cam_video_config()

```
virtual bool vxg::cloud::agent::callback::on_get_cam_video_config (
    proto::video_config & config ) [inline], [virtual]
```

Get video image config.

Parameters

out	<i>config</i>	video image config
-----	---------------	--------------------

Returns

true if get image config success
false get image config failed

Definition at line 103 of file callback.h.

10.9.3.9 on_get_log()

```
virtual bool vxg::cloud::agent::callback::on_get_log (
    std::string & log_data ) [inline], [virtual]
```

Get logging data callback.

Cloud API provides the way to request log data using Cloud API

Parameters

<i>log_data</i>	log data
-----------------	----------

Returns

true on success
false on failure

Definition at line 65 of file callback.h.

10.9.3.10 on_get_memorycard_info()

```
virtual bool vxg::cloud::agent::callback::on_get_memorycard_info (
    proto::event_object::memorycard_info_object & info ) [inline], [virtual]
```

Get memory card information, If this callback returned false or if *info* status not equal to [proto::MCS_NORMAL](#), the recording will not be started, i.e.

no agent::media::stream::record_start() will be called.

Parameters

out	<i>info</i>	memorycard info
-----	-------------	-----------------

Returns

true if *info* is valid
false if *info* is not valid

Definition at line 289 of file callback.h.

10.9.3.11 on_get_motion_detection_config()

```
virtual bool vxg::cloud::agent::callback::on_get_motion_detection_config (
    proto::motion_detection_config & config ) [inline], [virtual]
```

Get motion detection configuration.

Parameters

out	<i>config</i>	Motion detection config if return value is true
-----	---------------	---

Returns

true if *config* is valid
false if failed to get motion detection config

Definition at line 236 of file callback.h.

10.9.3.12 on_get_osd_config()

```
virtual bool vxg::cloud::agent::callback::on_get_osd_config (
    proto::osd_config & config ) [inline], [virtual]
```

Get OSD config.

Parameters

out	<i>config</i>	OSD config
-----	---------------	------------

Returns

true OSD config get success, *config* is valid
false OSD config get failure, *config* should not be used

Definition at line 187 of file callback.h.

10.9.3.13 on_get_ptz_config()

```
virtual bool vxg::cloud::agent::callback::on_get_ptz_config (
    proto::ptz_config & config ) [inline], [virtual]
```

Get PTZ config.

Parameters

out	<i>config</i>	ptz config
-----	---------------	------------

Returns

true success
false Get PTZ config failed

Definition at line 151 of file callback.h.

10.9.3.14 on_get_timezone()

```
virtual bool vxg::cloud::agent::callback::on_get_timezone (
    std::string & timezone ) [inline], [virtual]
```

Get device timezone in IANA format.

Parameters

out	<i>timezone</i>	name in IANA format
-----	-----------------	---------------------

Returns

true if *timezone* is valid
false if *timezone* is not valid

Definition at line 262 of file callback.h.

10.9.3.15 on_get_wifi_config()

```
virtual bool vxg::cloud::agent::callback::on_get_wifi_config (
    proto::wifi_config & config ) [inline], [virtual]
```

Get WiFi config.

Parameters

out	<i>config</i>	WiFi config
-----	---------------	-------------

Returns

true success
false failed

Definition at line 211 of file callback.h.

10.9.3.16 on_raw_msg()

```
virtual bool vxg::cloud::agent::callback::on_raw_msg (
    std::string client_id,
    std::string & data ) [inline], [virtual]
```

raw message callback

Parameters

in	<i>client_id</i>	unique id of the client, every raw messages session uses the same unique client_id
in, out	<i>data</i>	raw message payload from client, output value will be sent to the client if return value is true

Returns

true raw message handled and reply in the output *data* argument should be sent to the client as reply
false raw message handling failure, *data* output argument should not be sent to client

Definition at line 53 of file callback.h.

10.9.3.17 on_registered()

```
virtual void vxg::cloud::agent::callback::on_registered (
    const std::string & sid ) [inline], [virtual]
```

Registration on the Cloud has passed callback.

Parameters

<i>sid</i>	Cloud connection session id. Must be saved and provided via the agent::config.cm_register_sid before the next vxg::cloud::agent::manager::start() , otherwise the Cloud will block connection with CONN_CONFLICT for some period of time.
------------	---

Definition at line 37 of file callback.h.

10.9.3.18 on_set_audio_detection()

```
virtual bool vxg::cloud::agent::callback::on_set_audio_detection (
    const proto::audio_detection_config & conf ) [inline], [virtual]
```

Definition at line 320 of file callback.h.

10.9.3.19 on_set_cam_audio_config()

```
virtual bool vxg::cloud::agent::callback::on_set_cam_audio_config (
    const proto::audio_config & config ) [inline], [virtual]
```

Set audio input/output config.

Parameters

<i>config</i>	audio input/output config
---------------	---------------------------

Returns

true applied
false failed to set config

Definition at line 139 of file callback.h.

10.9.3.20 on_set_cam_video_config()

```
virtual bool vxg::cloud::agent::callback::on_set_cam_video_config (
    const proto::video_config & config ) [inline], [virtual]
```

Set video input config.

Parameters

<i>config</i>	video input config
---------------	--------------------

Returns

true Video image input config was successfully set
false Failed to set video input image config

Definition at line 115 of file callback.h.

10.9.3.21 on_set_motion_detection_config()

```
virtual bool vxg::cloud::agent::callback::on_set_motion_detection_config (
    const proto::motion_detection_config & config ) [inline], [virtual]
```

Set motion detection config.

Parameters

in	<i>config</i>	motion detection config
----	---------------	-------------------------

Returns

true if `config` was successfully set
false if failed to set `config`

Definition at line 249 of file `callback.h`.

10.9.3.22 on_set_osd_config()

```
virtual bool vxg::cloud::agent::callback::on_set_osd_config (  
    const proto::osd_config & config ) [inline], [virtual]
```

Set OSD config.

Parameters

in	<i>config</i>	OSD config
----	---------------	------------

Returns

true OSD config was successfully set
false failed to set OSD config

Definition at line 199 of file `callback.h`.

10.9.3.23 on_set_timezone()

```
virtual bool vxg::cloud::agent::callback::on_set_timezone (  
    std::string timezone ) [inline], [virtual]
```

Set device timezone in IANA format.

Parameters

in	<i>timezone</i>	timezone in IANA format
----	-----------------	-------------------------

Returns

true if timezone was successfully set
false if timezone was not set

Definition at line 274 of file callback.h.

10.9.3.24 on_set_wifi_config()

```
virtual bool vxg::cloud::agent::callback::on_set_wifi_config (
    const proto::wifi\_network & config ) [inline], [virtual]
```

Set WiFi config.

Parameters

<i>in</i>	<i>config</i>	WiFi configuration
-----------	---------------	--------------------

Returns

true if *config* is valid
false if *config* is invalid

Definition at line 223 of file callback.h.

10.9.3.25 on_start_backward_audio()

```
virtual bool vxg::cloud::agent::callback::on_start_backward_audio (
    std::string url ) [inline], [virtual]
```

Start backward audio stream.

Parameters

<i>url</i>	rtmp url for backward channel, device supports backward audio if on_get_cam_audio_config() set <code>proto::audio_config.caps spkr</code> to true
------------	---

Implementation should start rtmp client by its own, final implementation is also responsible for the demuxing, decoding and rendering of the audio stream.

Returns

true on success
false on failure

Definition at line 81 of file callback.h.

10.9.3.26 on_stop_backward_audio()

```
virtual bool vxg::cloud::agent::callback::on_stop_backward_audio (
    std::string url ) [inline], [virtual]
```

Stop backward audio.

Parameters

<i>url</i>	backward audio url which was used to start the backward channel
------------	---

Definition at line 92 of file callback.h.

10.9.3.27 on_trigger_event()

```
virtual bool vxg::cloud::agent::callback::on_trigger_event (
    proto::event_object & event ) [inline], [virtual]
```

Definition at line 315 of file callback.h.

The documentation for this class was generated from the following file:


- [callback.h](#)

10.10 vxg::cloud::agent::proto::stream_caps::caps_audio_object Struct Reference

Audio streams capabilities.

```
#include <agent-proto/objects/caps.h>
```

Collaboration diagram for vxg::cloud::agent::proto::stream_caps::caps_audio_object:



Data Fields

- **std::vector< std::string > streams**
Mandatory: list of strings, audio ES that are covered by this capability config.
- **std::vector< audio_format > formats**
Mandatory: list of string, supported audio formats; currently only "AAC" and "G711U" is supported.
- **std::vector< int > brt**
Mandatory: [min:int, max:int, step:int], range of bitrates, kbps.
- **std::vector< double > srt**
Mandatory: list of float, supported samplersates.

10.10.1 Detailed Description

Audio streams capabilities.

Definition at line 247 of file caps.h.

10.10.2 Field Documentation

10.10.2.1 brt

```
std::vector<int> vxg::cloud::agent::proto::stream_caps::caps_audio_object::brt
```

Mandatory: [min:int, max:int, step:int], range of bitrates, kbps.

Definition at line 259 of file caps.h.

10.10.2.2 formats

```
std::vector<audio_format> vxg::cloud::agent::proto::stream_caps::caps_audio_object::formats
```

Mandatory: list of string, supported audio formats; currently only "AAC" and "G711U" is supported.

Definition at line 255 of file caps.h.

10.10.2.3 srt

```
std::vector<double> vxg::cloud::agent::proto::stream_caps::caps_audio_object::srt
```

Mandatory: list of float, supported samplersates.

Definition at line 263 of file caps.h.

10.10.2.4 streams

```
std::vector< std::string> vxg::cloud::agent::proto::stream_caps::caps_audio_object::streams
```

Mandatory: list of strings, audio ES that are covered by this capability config.

Definition at line 250 of file caps.h.

The documentation for this struct was generated from the following file:


- [caps.h](#)

10.11 vxg::cloud::agent::proto::stream_caps::caps_video_object Struct Reference

Video streams capabilities.

```
#include <agent-proto/objects/caps.h>
```

Collaboration diagram for vxg::cloud::agent::proto::stream_caps::caps_video_object:



Data Fields

- **std::vector< std::string > streams**
Mandatory: list of strings, video ES that are covered by this capability config.
- **std::vector< video_format > formats**
Mandatory: list of string, supported video formats; currently only "H.264" is supported.
- **std::vector< std::pair< video_format, std::string > > profiles**
Optional: list of pairs [string (format), string (profile)], list of profiles for formats (when they have).
- **std::vector< std::pair< int, int > > resolutions**
Mandatory: list of pairs [int (horz), int (vert)], - supported video resolutions.
- **std::vector< double > fps**
Mandatory: list of float, supported framerates.
- bool **vbr**
Mandatory: VBR is supported.
- **std::pair< int, int > quality**
Optional: [min:int, max:int], range of quality for VBR.
- **std::vector< int > gop**
Mandatory: gop: [min:int, max:int, step:int], range of gop sizes.
- **std::vector< int > brt**
Mandatory: [min:int, max:int, step:int], range of bitrates, kbps.
- **std::vector< int > vbr_brt**
Optional: [min:int, max:int, step:int], range of bitrates, kbps.
- bool **smoothing**
Optional: True when stream smoothing can be controlled.

10.11.1 Detailed Description

Video streams capabilities.

Definition at line 177 of file caps.h.

10.11.2 Field Documentation

10.11.2.1 brt

```
std::vector<int> vxg::cloud::agent::proto::stream_caps::caps_video_object::brt
```

Mandatory: [min:int, max:int, step:int], range of bitrates, kbps.

Definition at line 219 of file caps.h.

10.11.2.2 formats

```
std::vector<video_format> vxg::cloud::agent::proto::stream_caps::caps_video_object::formats
```

Mandatory: list of string, supported video formats; currently only "H.264" is supported.

Definition at line 185 of file caps.h.

10.11.2.3 fps

```
std::vector<double> vxg::cloud::agent::proto::stream_caps::caps_video_object::fps
```

Mandatory: list of float, supported framerates.

Definition at line 203 of file caps.h.

10.11.2.4 gop

```
std::vector<int> vxg::cloud::agent::proto::stream_caps::caps_video_object::gop
```

Mandatory: gop: [min:int, max:int, step:int], range of gop sizes.

Definition at line 215 of file caps.h.

10.11.2.5 profiles

```
std::vector< std::pair<video_format, std::string> > vxg::cloud::agent::proto::stream_caps↵  
::caps_video_object::profiles
```

Optional: list of pairs [string (format), string (profile)], list of profiles for formats (when they have).

Empty list means – color selection is not supported. "format" - one of listed in "formats" names. "profile"

- name of profile. Example: [{"H.264", "Baseline"}, {"H.264", "Main"}, {"H.264", "High"}]

Definition at line 194 of file caps.h.

10.11.2.6 quality

```
std::pair<int, int> vxg::cloud::agent::proto::stream_caps::caps_video_object::quality
```

Optional: [min:int, max:int], range of quality for VBR.

Definition at line 211 of file caps.h.

10.11.2.7 resolutions

```
std::vector< std::pair<int, int> > vxg::cloud::agent::proto::stream_caps::caps_video_↵  
object::resolutions
```

Mandatory: list of pairs [int (horz), int (vert)], - supported video resolutions.

Definition at line 199 of file caps.h.

10.11.2.8 smoothing

```
bool vxg::cloud::agent::proto::stream_caps::caps_video_object::smoothing
```

Optional: True when stream smoothing can be controlled.

Definition at line 227 of file caps.h.

10.11.2.9 streams

```
std::vector< std::string> vxg::cloud::agent::proto::stream_caps::caps_video_object::streams
```

Mandatory: list of strings, video ES that are covered by this capability config.

Definition at line 180 of file caps.h.

10.11.2.10 vbr

```
bool vxg::cloud::agent::proto::stream_caps::caps_video_object::vbr
```

Mandatory: VBR is supported.

Definition at line 207 of file caps.h.

10.11.2.11 vbr_brt

```
std::vector<int> vxg::cloud::agent::proto::stream_caps::caps_video_object::vbr_brt
```

Optional: [min:int, max:int, step:int], range of bitrates, kbps.

Definition at line 223 of file caps.h.


The documentation for this struct was generated from the following file:

- [caps.h](#)


10.12 vxg::cloud::cloud_storage Class Reference

```
#include <agent/timeline.h>
```

Inheritance diagram for vxg::cloud::cloud_storage:



Collaboration diagram for vxg::cloud::cloud_storage:



Public Member Functions

- `cloud_storage` (const agent::proto::access_token &token, transport::libwebsockets::http::ptr http=nullptr)
- virtual `~cloud_storage` ()
- virtual `std::vector< item_ptr > list` (cloud::time start, cloud::time stop) override
- virtual bool `load` (item_ptr item) override
- bool `store` (item_ptr item)
- virtual void `erase` (item_ptr)

Additional Inherited Members

10.12.1 Detailed Description

Definition at line 284 of file timeline.h.

10.12.2 Constructor & Destructor Documentation

10.12.2.1 cloud_storage()

```
vxg::cloud::cloud_storage::cloud_storage (
    const agent::proto::access_token & token,
    transport::libwebsockets::http::ptr http = nullptr ) [inline]
```

Definition at line 291 of file timeline.h.

10.12.2.2 ~cloud_storage()

```
virtual vxg::cloud::cloud_storage::~~cloud_storage ( ) [inline], [virtual]
```

Definition at line 308 of file timeline.h.

10.12.3 Member Function Documentation

10.12.3.1 erase()

```
virtual void vxg::cloud::cloud_storage::erase (
    item_ptr ) [inline], [virtual]
```

Implements [vxg::cloud::timed_storage](#).

Definition at line 453 of file timeline.h.

10.12.3.2 list()

```
virtual std::vector<item_ptr> vxg::cloud::cloud_storage::list (
    cloud::time start,
    cloud::time stop ) [inline], [override], [virtual]
```

Implements [vxg::cloud::timed_storage](#).

Definition at line 310 of file timeline.h.

10.12.3.3 load()

```
virtual bool vxg::cloud::cloud_storage::load (
    item_ptr item ) [inline], [override], [virtual]
```

Implements [vxg::cloud::timed_storage](#).

Definition at line 344 of file timeline.h.

10.12.3.4 store()

```
bool vxg::cloud::cloud_storage::store (
    item_ptr item ) [inline], [virtual]
```

Implements [vxg::cloud::timed_storage](#).

Definition at line 382 of file timeline.h.

The documentation for this class was generated from the following file:

- [timeline.h](#)

10.13 vxg::cloud::agent::event_manager::config Struct Reference

```
#include <agent/event-manager.h>
```

Data Fields

- bool [attach_qos_report_to_motion](#)
Attach qos report as motion event's meta.
- bool [send_qos_report_as_separate_event](#)
Periodically send qos-report event instead of attaching qos to motion event.
- size_t [send_qos_report_period_sec](#)
Period between the qos-report events in seconds.
- bool [stateful_event_continuation_kick_snapshot](#)
Attach snapshot to event's state emulation dummy event.

10.13.1 Detailed Description

Definition at line 15 of file event-manager.h.

10.13.2 Field Documentation

10.13.2.1 attach_qos_report_to_motion

```
bool vxg::cloud::agent::event_manager::config::attach_qos_report_to_motion
```

Attach qos report as motion event's meta.

Definition at line 17 of file event-manager.h.

10.13.2.2 send_qos_report_as_separate_event

```
bool vxg::cloud::agent::event_manager::config::send_qos_report_as_separate_event
```

Periodically send qos-report event instead of attaching qos to motion event.

Definition at line 20 of file event-manager.h.

10.13.2.3 send_qos_report_period_sec

```
size_t vxg::cloud::agent::event_manager::config::send_qos_report_period_sec
```

Period between the qos-report events in seconds.

Definition at line 22 of file event-manager.h.

10.13.2.4 stateful_event_continuation_kick_snapshot

```
bool vxg::cloud::agent::event_manager::config::stateful_event_continuation_kick_snapshot
```

Attach snapshot to event's state emulation dummy event.

Stateful events emulation kicks Cloud with event of same type every 10 seconds during stateful event state is active. This flag enables snapshots for such events. Snapshot will be attached only if original event has snapshot flag enabled in its caps and settings.

Definition at line 29 of file event-manager.h.


The documentation for this struct was generated from the following file:

- [event-manager.h](#)

10.14 vxg::cloud::agent::synchronizer::config Struct Reference

```
#include <agent/timeline-synchronizer.h>
```

Collaboration diagram for vxg::cloud::agent::synchronizer::config:



Data Fields

- **std::chrono::seconds** [record_by_event_upload_step](#)
by event recording segment duration

10.14.1 Detailed Description

Definition at line 20 of file timeline-synchronizer.h.

10.14.2 Field Documentation

10.14.2.1 record_by_event_upload_step

```
std::chrono::seconds vxg::cloud::agent::synchronizer::config::record_by_event_upload_step
```

by event recording segment duration

Definition at line 22 of file timeline-synchronizer.h.

The documentation for this struct was generated from the following file:


- [timeline-synchronizer.h](#)

10.15 vxg::cloud::agent::proto::event_caps Struct Reference

Events capabilities.

```
#include <agent-proto/objects/caps.h>
```

Collaboration diagram for vxg::cloud::agent::proto::event_caps:



Data Fields

- bool [stream](#)
stream: bool, event can generate stream start
- bool [snapshot](#)
snapshot: bool, event is sent with snapshot
- bool [periodic](#)
periodic: optional bool, the event is a periodic event (camera generates and processes it using specified time interval)
- bool [trigger](#)
trigger: optional bool, the event can be triggered externally, using 6.7
- bool [stateful](#)
- bool [state_emulation](#)
- **std::chrono::seconds** [state_emulation_report_delay](#)
- bool [internal_hidden](#)
Library internal hidden event, not reported to the Cloud.

10.15.1 Detailed Description

Events capabilities.

Definition at line 438 of file caps.h.

10.15.2 Field Documentation

10.15.2.1 internal_hidden

```
bool vxg::cloud::agent::proto::event_caps::internal_hidden
```

Library internal hidden event, not reported to the Cloud.

Definition at line 475 of file caps.h.

10.15.2.2 periodic

```
bool vxg::cloud::agent::proto::event_caps::periodic
```

periodic: optional bool, the event is a periodic event (camera generates and processes it using specified time interval)

Definition at line 447 of file caps.h.

10.15.2.3 snapshot

```
bool vxg::cloud::agent::proto::event_caps::snapshot
```

snapshot: bool, event is sent with snapshot

Definition at line 443 of file caps.h.

10.15.2.4 state_emulation

```
bool vxg::cloud::agent::proto::event_caps::state_emulation
```

Definition at line 471 of file caps.h.

10.15.2.5 state_emulation_report_delay

```
std::chrono::seconds vxg::cloud::agent::proto::event_caps::state_emulation_report_delay
```

Definition at line 472 of file caps.h.

10.15.2.6 stateful

```
bool vxg::cloud::agent::proto::event_caps::stateful
```

Definition at line 469 of file caps.h.

10.15.2.7 stream

```
bool vxg::cloud::agent::proto::event_caps::stream
```

stream: bool, event can generate stream start

Definition at line 440 of file caps.h.

10.15.2.8 trigger

```
bool vxg::cloud::agent::proto::event_caps::trigger
```

trigger: optional bool, the event can be triggered externally, using 6.7

Definition at line 450 of file caps.h.

The documentation for this struct was generated from the following file:


- [caps.h](#)

10.16 vxg::cloud::agent::event_config Struct Reference

Event config.

```
#include <agent-proto/objects/config.h>
```

Collaboration diagram for vxg::cloud::agent::event_config:



Public Member Functions

- bool `name_eq` (const `event_config` &r) const
Is-equal predicate based on event's name only.
- bool `caps_eq` (const `event_config` &r) const
Is-equal predicate based on event's caps.
- `std::string name` () const

Data Fields

- event_type `event`
event: string, event name, see 6.1 Events naming for details
- `std::string custom_event_name`
Custom event name, used if event set to event_type::ET_CUSTOM.
- bool `active`
active: bool, event is active; if not set, corresponding events will not be sent
- bool `stream`
stream: bool, start stream when event happens
- bool `snapshot`
snapshot: bool, generate snapshot when event happens
- int `period`
period: optional int, an interval between periodic events, seconds
- event_caps `caps`
Event capabilities.

10.16.1 Detailed Description

Event config.

Definition at line 894 of file config.h.

10.16.2 Member Function Documentation

10.16.2.1 caps_eq()

```
bool vxg::cloud::agent::event_config::caps_eq (
    const event_config & r ) const [inline]
```

Is-equal predicate based on event's caps.

Parameters

<i>r</i>	
----------	--

Returns

- true Compared configs have equal caps.
- false Compared configs have non-equal caps.

Definition at line 934 of file config.h.

10.16.2.2 name()

```
std::string vxg::cloud::agent::event_config::name ( ) const [inline]
```

Definition at line 938 of file config.h.

10.16.2.3 name_eq()

```
bool vxg::cloud::agent::event_config::name_eq (
    const event_config & r ) const [inline]
```

Is-equal predicate based on event's name only.

Parameters

<i>r</i>	
----------	--

Returns

- true Compared configs are for the event with equal names.
- false Compared configs are for events with non-equal names.

Definition at line 925 of file config.h.

10.16.3 Field Documentation**10.16.3.1 active**

```
bool vxg::cloud::agent::event_config::active
```

active: bool, event is active; if not set, corresponding events will not be sent

Definition at line 903 of file config.h.

10.16.3.2 caps

```
event_caps vxg::cloud::agent::event_config::caps
```

Event capabilities.

Definition at line 918 of file config.h.

10.16.3.3 custom_event_name

```
std::string vxg::cloud::agent::event_config::custom_event_name
```

Custom event name, used if event set to event_type::ET_CUSTOM.

Definition at line 899 of file config.h.

10.16.3.4 event

```
event_type vxg::cloud::agent::event_config::event
```

event: string, event name, see 6.1 Events naming for details

Definition at line 896 of file config.h.

10.16.3.5 period

```
int vxg::cloud::agent::event_config::period
```

period: optional int, an interval between periodic events, seconds

Definition at line 912 of file config.h.

10.16.3.6 snapshot

```
bool vxg::cloud::agent::event_config::snapshot
```

snapshot: bool, generate snapshot when event happens

Definition at line 909 of file config.h.

10.16.3.7 stream

`bool vxg::cloud::agent::event_config::stream`

stream: bool, start stream when event happens

Definition at line 906 of file config.h.

The documentation for this struct was generated from the following file:

- [config.h](#)

10.17 vxg::cloud::agent::event_manager Class Reference

```
#include <agent/event-manager.h>
```

Data Structures

- struct [config](#)
- struct [event_state_report_cb](#)

Public Types

- using [event_state_report_cb_ptr](#) = `std::shared_ptr< event_manager::event_state_report_cb >`
- using [handle_event_payload_cb](#) = `std::function< bool(agent::proto::event_object &, bool)>`

Public Member Functions

- [event_manager](#) (const [event_manager::config](#) &config, `std::vector< agent::event_stream::ptr >` event_streams, [event_state_report_cb_ptr](#) sync_cb_ptr, [handle_event_payload_cb](#))
- [~event_manager](#) ()
- void [start](#) ()
- void [stop](#) ()
- bool [set_events](#) (const agent::proto::events_config &config)
- bool [get_events](#) (agent::proto::events_config &config)
- bool [notify_event](#) (const agent::proto::event_object &event)
- bool [trigger_event](#) (const `std::string` &event, const `json` &meta, `cloud::time` time)

10.17.1 Detailed Description

Definition at line 11 of file event-manager.h.

10.17.2 Member Typedef Documentation

10.17.2.1 event_state_report_cb_ptr

```
using vxg::cloud::agent::event_manager::event_state_report_cb_ptr = std::shared_ptr<event_manager::event_sta
```

Definition at line 65 of file event-manager.h.

10.17.2.2 handle_event_payload_cb

```
using vxg::cloud::agent::event_manager::handle_event_payload_cb = std::function<bool (agent↔  
::proto::event_object&, bool)>
```

Definition at line 67 of file event-manager.h.

10.17.3 Constructor & Destructor Documentation

10.17.3.1 event_manager()

```
vxg::cloud::agent::event_manager::event_manager (
    const event_manager::config & config,
    std::vector< agent::event_stream::ptr > event_streams,
    event_state_report_cb_ptr sync_cb_ptr,
    handle_event_payload_cb )
```

10.17.3.2 ~event_manager()

```
vxg::cloud::agent::event_manager::~event_manager ( )
```

10.17.4 Member Function Documentation

10.17.4.1 get_events()

```
bool vxg::cloud::agent::event_manager::get_events (
    agent::proto::events_config & config )
```

10.17.4.2 notify_event()

```
bool vxg::cloud::agent::event_manager::notify_event (
    const agent::proto::event_object & event )
```

10.17.4.3 set_events()

```
bool vxg::cloud::agent::event_manager::set_events (
    const agent::proto::events_config & config )
```

10.17.4.4 start()

```
void vxg::cloud::agent::event_manager::start ( )
```

10.17.4.5 stop()

```
void vxg::cloud::agent::event_manager::stop ( )
```

10.17.4.6 trigger_event()

```
bool vxg::cloud::agent::event_manager::trigger_event (
    const std::string & event,
    const json & meta,
    cloud::time time )
```

The documentation for this class was generated from the following file:

- [event-manager.h](#)

10.18 vxg::cloud::agent::event_state Class Reference

```
#include <agent/event-state.h>
```

Data Structures

- struct [event_state_changed_cb](#)

Public Types

- enum `stream_delivery_mode` { `SDM_NONE`, `SDM_UPLOAD`, `SDM_STREAM` }
- using `event_state_changed_cb_ptr` = `std::shared_ptr<event_state_changed_cb>`

Public Member Functions

- `event_state` ()
- `!`
- `event_state` (const agent::proto::event_config &event_conf, `event_state_changed_cb_ptr` state_changed_cb, transport::timed_callback_ptr timed_cb)
- `~event_state` ()
- `event_state` (const `event_state` &r)
- `event_state` & `operator=` (`event_state` r) noexcept
- void `start` (cloud::time start, cloud::time stop=utils::time::null())
- void `stop` (cloud::time time)
- bool `active` () const
- bool `stateful` () const
- bool `need_record` () const
- cloud::time `start` () const
- cloud::time `stop` () const
- const agent::proto::event_config & `config` () const

Friends

- void `swap` (`event_state` &l, `event_state` &r)

10.18.1 Detailed Description

Definition at line 11 of file event-state.h.

10.18.2 Member Typedef Documentation

10.18.2.1 event_state_changed_cb_ptr

```
using vxg::cloud::agent::event_state::event_state_changed_cb_ptr = std::shared_ptr<event_state_changed_cb>
```

Definition at line 42 of file event-state.h.

10.18.3 Member Enumeration Documentation

10.18.3.1 stream_delivery_mode

```
enum vxg::cloud::agent::event_state::stream_delivery_mode
```

Enumerator

SDM_NONE	
SDM_UPLOAD	
SDM_STREAM	

Definition at line 29 of file event-state.h.

10.18.4 Constructor & Destructor Documentation

10.18.4.1 event_state() [1/3]

```
vxg::cloud::agent::event_state::event_state ( ) [inline]
```

!

Definition at line 98 of file event-state.h.

10.18.4.2 event_state() [2/3]

```
vxg::cloud::agent::event_state::event_state (
    const agent::proto::event_config & event_conf,
    event_state_changed_cb_ptr state_changed_cb,
    transport::timed_callback_ptr timed_cb ) [inline]
```

Definition at line 99 of file event-state.h.

10.18.4.3 ~event_state()

```
vxg::cloud::agent::event_state::~~event_state ( ) [inline]
```

Definition at line 107 of file event-state.h.

10.18.4.4 event_state() [3/3]

```
vxg::cloud::agent::event_state::event_state (
    const event_state & r ) [inline]
```

Definition at line 129 of file event-state.h.

10.18.5 Member Function Documentation

10.18.5.1 active()

```
bool vxg::cloud::agent::event_state::active ( ) const [inline]
```

Definition at line 193 of file event-state.h.

10.18.5.2 config()

```
const agent::proto::event_config& vxg::cloud::agent::event_state::config ( ) const [inline]
```

Definition at line 198 of file event-state.h.

10.18.5.3 need_record()

```
bool vxg::cloud::agent::event_state::need_record ( ) const [inline]
```

Definition at line 195 of file event-state.h.

10.18.5.4 operator=()

```
event_state& vxg::cloud::agent::event_state::operator= (   
    event_state r ) [inline], [noexcept]
```

Definition at line 146 of file event-state.h.

10.18.5.5 start() [1/2]

```
cloud::time vxg::cloud::agent::event_state::start ( ) const [inline]
```

Definition at line 196 of file event-state.h.

10.18.5.6 start() [2/2]

```
void vxg::cloud::agent::event_state::start (
    cloud::time start,
    cloud::time stop = utils::time::null() ) [inline]
```

Definition at line 152 of file event-state.h.

10.18.5.7 stateful()

```
bool vxg::cloud::agent::event_state::stateful ( ) const [inline]
```

Definition at line 194 of file event-state.h.

10.18.5.8 stop() [1/2]

```
cloud::time vxg::cloud::agent::event_state::stop ( ) const [inline]
```

Definition at line 197 of file event-state.h.

10.18.5.9 stop() [2/2]

```
void vxg::cloud::agent::event_state::stop (
    cloud::time time ) [inline]
```

Definition at line 182 of file event-state.h.

10.18.6 Friends And Related Function Documentation

10.18.6.1 swap

```
void swap (
    event_state & l,
    event_state & r ) [friend]
```

Definition at line 136 of file event-state.h.

The documentation for this class was generated from the following file:

- [event-state.h](#)

10.19 vxg::cloud::agent::event_state::event_state_changed_cb Struct Reference

```
#include <agent/event-state.h>
```

Public Member Functions

- [event_state_changed_cb](#) ()
- virtual [~event_state_changed_cb](#) ()
- virtual void [on_started](#) (const [event_state](#) &state, const [cloud::time](#) &)
- virtual void [on_stopped](#) (const [event_state](#) &state, const [cloud::time](#) &)
- virtual void [on_ongoing](#) (const [event_state](#) &state, const [cloud::time](#) &)
- virtual void [on_triggered](#) (const [event_state](#) &state, const [cloud::time](#) &)

10.19.1 Detailed Description

Definition at line 30 of file event-state.h.

10.19.2 Constructor & Destructor Documentation

10.19.2.1 event_state_changed_cb()

```
vxg::cloud::agent::event_state::event_state_changed_cb::event_state_changed_cb ( ) [inline]
```

Definition at line 31 of file event-state.h.

10.19.2.2 ~event_state_changed_cb()

```
virtual vxg::cloud::agent::event_state::event_state_changed_cb::~~event_state_changed_cb ( )  
[inline], [virtual]
```

Definition at line 32 of file event-state.h.

10.19.3 Member Function Documentation

10.19.3.1 on_ongoing()

```
virtual void vxg::cloud::agent::event_state::event_state_changed_cb::on_ongoing (
    const event_state & state,
    const cloud::time & ) [inline], [virtual]
```

Definition at line 37 of file event-state.h.

10.19.3.2 on_started()

```
virtual void vxg::cloud::agent::event_state::event_state_changed_cb::on_started (
    const event_state & state,
    const cloud::time & ) [inline], [virtual]
```

Definition at line 35 of file event-state.h.

10.19.3.3 on_stopped()

```
virtual void vxg::cloud::agent::event_state::event_state_changed_cb::on_stopped (
    const event_state & state,
    const cloud::time & ) [inline], [virtual]
```

Definition at line 36 of file event-state.h.

10.19.3.4 on_triggered()

```
virtual void vxg::cloud::agent::event_state::event_state_changed_cb::on_triggered (
    const event_state & state,
    const cloud::time & ) [inline], [virtual]
```

Definition at line 39 of file event-state.h.


The documentation for this struct was generated from the following file:

- [event-state.h](#)

10.20 vxg::cloud::agent::event_manager::event_state_report_cb Struct Reference

```
#include <agent/event-manager.h>
```

Inheritance diagram for vxg::cloud::agent::event_manager::event_state_report_cb:



Public Member Functions

- [event_state_report_cb](#) ()
- virtual [~event_state_report_cb](#) ()
- virtual void [on_event_start](#) (const [event_state](#) &state, const [cloud::time](#) &start)
- virtual void [on_event_stop](#) (const [event_state](#) &state, const [cloud::time](#) &stop)
- virtual void [on_event_trigger](#) (const [event_state](#) &state, const [cloud::time](#) &t)
- virtual void [on_event_continue](#) (const [event_state](#) &state, const [cloud::time](#) &t)
- virtual [std::shared_ptr](#)< void > [on_need_stream_sync_start](#) (const [event_state](#) &state, const [cloud::time](#) &start)
- virtual void [on_need_stream_sync_stop](#) (const [event_state](#) &state, const [cloud::time](#) &stop, [std::shared_ptr](#)< void > userdata)
- virtual [std::shared_ptr](#)< void > [on_need_stream_sync_continue](#) (const [event_state](#) &state, const [cloud::time](#) &t, [std::shared_ptr](#)< void > userdata)

10.20.1 Detailed Description

Definition at line 32 of file event-manager.h.

10.20.2 Constructor & Destructor Documentation

10.20.2.1 event_state_report_cb()

```
vxg::cloud::agent::event_manager::event_state_report_cb::event_state_report_cb ( ) [inline]
```

Definition at line 33 of file event-manager.h.

10.20.2.2 ~event_state_report_cb()

```
virtual vxg::cloud::agent::event_manager::event_state_report_cb::~~event_state_report_cb ( )  
[inline], [virtual]
```

Definition at line 34 of file event-manager.h.

10.20.3 Member Function Documentation

10.20.3.1 on_event_continue()

```
virtual void vxg::cloud::agent::event_manager::event_state_report_cb::on_event_continue (   
    const event_state & state,  
    const cloud::time & t ) [inline], [virtual]
```

Definition at line 45 of file event-manager.h.

10.20.3.2 on_event_start()

```
virtual void vxg::cloud::agent::event_manager::event_state_report_cb::on_event_start (   
    const event_state & state,  
    const cloud::time & start ) [inline], [virtual]
```

Definition at line 36 of file event-manager.h.

10.20.3.3 on_event_stop()

```
virtual void vxg::cloud::agent::event_manager::event_state_report_cb::on_event_stop (   
    const event_state & state,  
    const cloud::time & stop ) [inline], [virtual]
```

Definition at line 39 of file event-manager.h.

10.20.3.4 on_event_trigger()

```
virtual void vxg::cloud::agent::event_manager::event_state_report_cb::on_event_trigger (
    const event_state & state,
    const cloud::time & t ) [inline], [virtual]
```

Definition at line 42 of file event-manager.h.

10.20.3.5 on_need_stream_sync_continue()

```
virtual std::shared_ptr<void> vxg::cloud::agent::event_manager::event_state_report_cb::on_↵
need_stream_sync_continue (
    const event_state & state,
    const cloud::time & t,
    std::shared_ptr< void > userdata ) [inline], [virtual]
```

Definition at line 57 of file event-manager.h.

10.20.3.6 on_need_stream_sync_start()

```
virtual std::shared_ptr<void> vxg::cloud::agent::event_manager::event_state_report_cb::on_↵
need_stream_sync_start (
    const event_state & state,
    const cloud::time & start ) [inline], [virtual]
```

Definition at line 48 of file event-manager.h.

10.20.3.7 on_need_stream_sync_stop()

```
virtual void vxg::cloud::agent::event_manager::event_state_report_cb::on_need_stream_sync_stop
(
    const event_state & state,
    const cloud::time & stop,
    std::shared_ptr< void > userdata ) [inline], [virtual]
```

Definition at line 54 of file event-manager.h.

The documentation for this struct was generated from the following file:

- [event-manager.h](#)

10.21 vxg::cloud::agent::event_stream Class Reference

Event stream, abstract class for event generation.

```
#include <agent/event-stream.h>
```

Public Types

- typedef **std::shared_ptr**< [event_stream](#) > **ptr**
***std::shared_ptr** to [event_stream](#)*

Public Member Functions

- [event_stream](#) (**std::string** name)
Construct a new event stream object.
- virtual [~event_stream](#) ()
- bool [notify](#) (proto::event_object event)
Callback should be called to notify event.
- virtual bool [start](#) ()=0
Start events generation, called by internal code when the events generation requested by the VXG Cloud.
- virtual void [stop](#) ()=0
Stop events generation.
- virtual bool [get_events](#) (**std::vector**< proto::event_config > &configs)=0
Get the events configs list This method should update `config` object and add all configurations for the events provided by this event stream.
- virtual bool [set_events](#) (const **std::vector**< proto::event_config > &config)=0
Set the events configuration.
- virtual bool [trigger_event](#) (proto::event_object &event)
Trigger event provided by [event_stream](#) If [get_events\(\)](#) returned event config with `proto::event_config.caps.trigger == true` and this event was triggered via the Cloud API this method will be called.
- virtual bool [set_trigger_recording](#) (bool enabled, int pre, int post)=0
Turn on/off the [event_stream](#) triggered recording and pre/post recording time.
- virtual bool [init](#) ()=0
- virtual void [finit](#) ()=0

10.21.1 Detailed Description

Event stream, abstract class for event generation.

Definition at line 13 of file event-stream.h.

10.21.2 Member Typedef Documentation

10.21.2.1 ptr

```
typedef std::shared_ptr<event\_stream> vxg::cloud::agent::event_stream::ptr
```

std::shared_ptr to [event_stream](#)

Definition at line 24 of file event-stream.h.

10.21.3 Constructor & Destructor Documentation

10.21.3.1 event_stream()

```
vxg::cloud::agent::event_stream::event_stream (
    std::string name ) [inline]
```

Construct a new event stream object.

Parameters

in	<i>name</i>	Event stream name, unique name for event stream
----	-------------	---

Definition at line 30 of file event-stream.h.

10.21.3.2 ~event_stream()

```
virtual vxg::cloud::agent::event_stream::~~event_stream ( ) [inline], [virtual]
```

Definition at line 32 of file event-stream.h.

10.21.4 Member Function Documentation

10.21.4.1 finit()

```
virtual void vxg::cloud::agent::event_stream::finit ( ) [pure virtual]
```

10.21.4.2 get_events()

```
virtual bool vxg::cloud::agent::event_stream::get_events (
    std::vector< proto::event_config > & configs ) [pure virtual]
```

Get the events configs list This method should update `config` object and add all configurations for the events provided by this event stream.

`config` may already include event configs reported by this `get_event()`, hence the implementation should consider this and do not include its event configs more than one time.

Parameters

out	<i>configs</i>	Events configurations.
-----	----------------	------------------------

Returns

`true` `configs` is valid.

`false` `configs` is invalid, should not be applied.

Note

This method **MUST** always return the configs with the same caps, otherwise the new config will not be applied by the library.

10.21.4.3 init()

```
virtual bool vxg::cloud::agent::event_stream::init ( ) [pure virtual]
```

10.21.4.4 notify()

```
bool vxg::cloud::agent::event_stream::notify (
    proto::event_object event ) [inline]
```

Callback should be called to notify event.

Parameters

in	<i>event</i>	Event object
----	--------------	--------------

Returns

true Event successfully notified
false Notification failed

Definition at line 45 of file event-stream.h.

10.21.4.5 set_events()

```
virtual bool vxg::cloud::agent::event_stream::set_events (
    const std::vector< proto::event_config > & config ) [pure virtual]
```

Set the events configuration.

Parameters

<i>config</i>	Events configurations list which includes all events reported by the system and other event streams, implementation should find own event configurations and apply them.
---------------	--

Returns

true config applied.
false config not applied.

10.21.4.6 set_trigger_recording()

```
virtual bool vxg::cloud::agent::event_stream::set_trigger_recording (
    bool enabled,
    int pre,
    int post ) [pure virtual]
```

Turn on/off the [event_stream](#) triggered recording and pre/post recording time.

Triggered recording means that event generated by this [event_stream](#) should start recording. Final recorded file should have duration of pre time + duration of the even + post time.

Note

Trigger driven recording can be used if platform supports such type of recording, implementation of such type of recording should include specific [agent::media::stream](#) records exporting mechanism which handles two consecutive events pre/post time intersections.

Parameters

in	<i>enabled</i>	true if event stream should trigger the recording. Implementation may ignore this if not trigger driven record method is used.
in	<i>pre</i>	Pre recording time in milliseconds.
in	<i>post</i>	Post recording time in milliseconds.

Returns

true
false

10.21.4.7 start()

```
virtual bool vxg::cloud::agent::event_stream::start ( ) [pure virtual]
```

Start events generation, called by internal code when the events generation requested by the VXG Cloud.

Event stream MUST immediately notify states of all stateful events after the [start\(\)](#) was invoked.

Returns

true Events generation started
false Failed to start events generation

10.21.4.8 stop()

```
virtual void vxg::cloud::agent::event_stream::stop ( ) [pure virtual]
```

Stop events generation.

10.21.4.9 trigger_event()

```
virtual bool vxg::cloud::agent::event_stream::trigger_event (
    proto::event_object & event ) [inline], [virtual]
```

Trigger event provided by [event_stream](#) If [get_events\(\)](#) returned event config with `proto::event_config.caps.trigger == true` and this event was triggered via the Cloud API this method will be called.

The logic of this method should be the same as for [vxg::cloud::agent::callback::on_trigger_event\(\)](#).

See also

[vxg::cloud::agent::callback::on_trigger_event\(\)](#)

Parameters

<i>event</i>	
--------------	--

Returns

true

false

Definition at line 102 of file event-stream.h.

The documentation for this class was generated from the following file:


- [event-stream.h](#)

10.22 vxg::cloud::agent::events_config Struct Reference

Events config, list of [event_config](#) objects.

```
#include <agent-proto/objects/config.h>
```

Collaboration diagram for vxg::cloud::agent::events_config:



Public Member Functions

- bool [get_event_config](#) (const event_object &event, [event_config](#) &result)
Finds event which corresponds to [event_config](#) arg in the [events_config](#) structure.

Data Fields

- bool [enabled](#)
enabled: bool, indicates global events and event-driven streaming enabling flag
- **std::vector< [event_config](#) > [events](#)**
events: list of [event_config](#) struct

10.22.1 Detailed Description

Events config, list of [event_config](#) objects.

Definition at line 983 of file config.h.

10.22.2 Member Function Documentation

10.22.2.1 get_event_config()

```
bool vxg::cloud::agent::events_config::get_event_config (
    const event_object & event,
    event\_config & result ) [inline]
```

Finds event which corresponds to [event_config](#) arg in the [events_config](#) structure.

Parameters

in	<i>event</i>	- event_object, event_object.event used to find the event_config
out	<i>result</i>	- if event_config found it will be stored here

Returns

true event found
false event not found

Definition at line 1000 of file config.h.

10.22.3 Field Documentation

10.22.3.1 enabled

```
bool vxg::cloud::agent::events_config::enabled
```

enabled: bool, indicates global events and event-driven streaming enabling flag

Definition at line 986 of file config.h.

10.22.3.2 events

```
std::vector<event_config> vxg::cloud::agent::events_config::events
```

events: list of [event_config](#) struct

Definition at line 989 of file config.h.


The documentation for this struct was generated from the following file:

- [config.h](#)


10.23 vxg::media::Streamer::ISink Class Reference

```
#include <streamer/base_streamer.h>
```

Inheritance diagram for vxg::media::Streamer::ISink:



Collaboration diagram for vxg::media::Streamer::ISink:



Public Types

- typedef `std::shared_ptr< ISink > ptr`
std::shared_ptr alias
- typedef `std::unique_ptr< ISink > PtrU`
std::unique_ptr alias

Public Member Functions

- [ISink](#) (uint8_t prio=[SINK_THREAD_PRIO](#))
Construct a new [ISink](#) object.
- virtual [~ISink](#) ()
- virtual bool [init](#) ([std::string](#) url="")=0
Init sink.
- virtual bool [finit](#) ()=0
Deinit sink.
- virtual bool [process](#) ([std::shared_ptr](#)< [MediaFrame](#) > frame)=0
Process next media frame.
- virtual bool [droppable](#) ()=0
If sink of with dropping its media frames.
- virtual bool [negotiate](#) ([std::vector](#)< [Streamer::StreamInfo](#) > info)
Negotiation callback, this method called with collected from the [ISource::negotiate](#) media stream description.
- virtual void [error](#) ([StreamError](#) error)
Media processing error callback, called when [ISink::process](#) returned false or linked source's [ISource::pullFrame](#) returned false, or when [ISource::error](#) was called.
- virtual [std::string](#) [name](#) ()=0
Sink name.
- virtual [cloud::duration](#) [duration](#) ()
Processed stream duration.
- void [set_eos_cb](#) ([std::function](#)< void([cloud::duration](#))> eos_cb)
- void [set_eos](#) (bool eos)
- void [set_error_cb](#) (on_error_cb cb)

Protected Attributes

- [on_error_cb](#) [on_error_cb_](#)

10.23.1 Detailed Description

Definition at line 507 of file `base_streamer.h`.

10.23.2 Member Typedef Documentation

10.23.2.1 ptr

```
typedef std::shared\_ptr<ISink> vxg::media::Streamer::ISink::ptr
```

[std::shared_ptr](#) alias

Definition at line 512 of file `base_streamer.h`.

10.23.2.2 PtrU

```
typedef std::unique_ptr<ISink> vxg::media::Streamer::ISink::PtrU
```

std::unique_ptr alias

Definition at line 514 of file base_streamer.h.

10.23.3 Constructor & Destructor Documentation

10.23.3.1 ISink()

```
vxg::media::Streamer::ISink::ISink (
    uint8_t prio = SINK_THREAD_PRIO ) [inline]
```

Construct a new [ISink](#) object.

Parameters

<i>prio</i>	internall thread priority, used on RTOS.
-------------	--

Definition at line 519 of file base_streamer.h.

10.23.3.2 ~ISink()

```
virtual vxg::media::Streamer::ISink::~ISink ( ) [inline], [virtual]
```

Definition at line 525 of file base_streamer.h.

10.23.4 Member Function Documentation

10.23.4.1 droppable()

```
virtual bool vxg::media::Streamer::ISink::droppable ( ) [pure virtual]
```

If sink of with dropping its media frames.

Returns

- true Internal media thread allowed to drop frames if internal media queue is full.
- false No media frames dropping allowed.

Implemented in [vxg::media::rtmp_sink](#), and [vxg::media::ffmpeg::Sink](#).

10.23.4.2 duration()

```
virtual cloud::duration vxg::media::Streamer::ISink::duration ( ) [inline], [virtual]
```

Processed stream duration.

Returns

duration

Reimplemented in [vxg::media::ffmpeg::Sink](#).

Definition at line 617 of file base_streamer.h.

10.23.4.3 error()

```
virtual void vxg::media::Streamer::ISink::error (
    StreamError error ) [inline], [virtual]
```

Media processing error callback, called when [ISink::process](#) returned false or linked source's [ISource::pullFrame](#) returned false, or when [ISource::error](#) was called.

Method may be overridden, default implementation calls on_error_cb that was provided by user with [set_error_cb\(\)](#).

Parameters

<i>error</i>	Error type.
--------------	-------------

Reimplemented in [vxg::media::ffmpeg::Sink](#).

Definition at line 574 of file base_streamer.h.

10.23.4.4 finit()

```
virtual bool vxg::media::Streamer::ISink::finit ( ) [pure virtual]
```

Deinit sink.

Returns

true finit success.
false finit failed.

Implemented in [vxg::media::ffmpeg::Sink](#).

10.23.4.5 init()

```
virtual bool vxg::media::Streamer::ISink::init (
    std::string url = "" ) [pure virtual]
```

Init sink.

Parameters

<i>in</i>	<i>url</i>	Url if needed.
-----------	------------	----------------

Returns

true init success.

false init failed.

Implemented in [vxd::media::ffmpeg::Sink](#), and [vxd::media::rtmp_sink](#).

10.23.4.6 name()

```
virtual std::string vxd::media::Streamer::ISink::name ( ) [pure virtual]
```

Sink name.

Returns

std::string

Implemented in [vxd::media::rtmp_sink](#), and [vxd::media::ffmpeg::Sink](#).

10.23.4.7 negotiate()

```
virtual bool vxd::media::Streamer::ISink::negotiate (
    std::vector< Streamer::StreamInfo > info ) [inline], [virtual]
```

Negotiation callback, this method called with collected from the [ISource::negotiate](#) media stream description.

Parameters

<i>info</i>	List of elementary streams descriptions.
-------------	--

Returns

true If streams descriptions accepted.

false Streams not accepted, will cause media thread stopping.

Reimplemented in [vxd::media::ffmpeg::Sink](#), and [vxd::media::rtmp_sink](#).

Definition at line 564 of file base_streamer.h.

10.23.4.8 process()

```
virtual bool vxg::media::Streamer::ISink::process (
    std::shared_ptr< MediaFrame > frame ) [pure virtual]
```

Process next media frame.

Internal function called by media thread, the last function of media frame travel. Final class process frame in this function: sends to server, writes on disk etc.

Parameters

in	<i>frame</i>	Media frame.
----	--------------	--------------

Returns

true Media frame successfully processed.

false Media frame processing failed.

10.23.4.9 set_eos()

```
void vxg::media::Streamer::ISink::set_eos (
    bool eos ) [inline]
```

Definition at line 680 of file base_streamer.h.

10.23.4.10 set_eos_cb()

```
void vxg::media::Streamer::ISink::set_eos_cb (
    std::function< void(cloud::duration)> eos_cb ) [inline]
```

Definition at line 676 of file base_streamer.h.

10.23.4.11 set_error_cb()

```
void vxg::media::Streamer::ISink::set_error_cb (
    on_error_cb cb ) [inline]
```

Definition at line 682 of file base_streamer.h.

10.23.5 Field Documentation

10.23.5.1 on_error_cb_

`on_error_cb` `vxg::media::Streamer::ISink::on_error_cb_` [protected]

Definition at line 685 of file `base_streamer.h`.

The documentation for this class was generated from the following file:


- [base_streamer.h](#)

10.24 vxg::media::Streamer::ISource Class Reference


`ISource` interface class.

```
#include <streamer/base_streamer.h>
```

Inheritance diagram for `vxg::media::Streamer::ISource`:



Collaboration diagram for `vxg::media::Streamer::ISource`:



Public Types

- enum [Mode](#) { [PULL](#), [PUSH](#) }
Source operation mode.
- typedef **std::shared_ptr**< [ISource](#) > [ptr](#)

Public Member Functions

- [ISource](#) (uint8_t _prio=[SRC_THREAD_PRIO](#), [Mode](#) _mode=[PULL](#), bool drop=true)
Construct a new [ISource](#) object.
- virtual bool [init](#) (**std::string** url="")=0
Init source.
- virtual void [finit](#) ()=0
Finit souce.
- virtual void [error](#) ([StreamError](#) stream_error)
Error notification.
- virtual **std::vector**< [Streamer::StreamInfo](#) > [negotiate](#) ()=0
Negotiation callback.
- virtual **std::shared_ptr**< [MediaFrame](#) > [pullFrame](#) ()=0
Main method of the [Mode::PULL](#) mode data producing.
- virtual **std::string** [name](#) ()=0
Source class name.
- void [pushFrame](#) (**std::shared_ptr**< [MediaFrame](#) > frame)
Implementation should call this method to provide media frames in the [Mode::PUSH](#) source operation mode.
- void [set_error_cb](#) ([on_error_cb](#) cb)

Protected Attributes

- [Mode](#) [mode_](#)
- [on_error_cb](#) [on_error_cb_](#)

10.24.1 Detailed Description

[ISource](#) interface class.

Definition at line 708 of file [base_streamer.h](#).

10.24.2 Member Typedef Documentation

10.24.2.1 ptr

```
typedef std::shared_ptr<ISource> vxg::media::Streamer::ISource::ptr
```

Definition at line 713 of file [base_streamer.h](#).

10.24.3 Member Enumeration Documentation

10.24.3.1 Mode

enum `vsg::media::Streamer::ISource::Mode`

Source operation mode.

Enumerator

PULL	Pull mode. The ISource::pullFrame() will be called from the separate thread. User should implement it and return <code>std::shared_ptr<MediaFrame></code> .
PUSH	Push mode. Inherited class should feed media data on its own by calling the ISource::pushFrame() method with MediaFrame object passed as argument.

Definition at line 715 of file `base_streamer.h`.

10.24.4 Constructor & Destructor Documentation

10.24.4.1 ISource()

```
vxg::media::Streamer::ISource::ISource (
    uint8_t _prio = SRC_THREAD_PRIO,
    Mode _mode = PULL,
    bool drop = true ) [inline]
```

Construct a new [ISource](#) object.

Parameters

in	<code>_prio</code>	Push thread priority. Used if <code>_mode</code> is <code>Mode::PUSH</code> .
in	<code>_mode</code>	Source operating mode.
in	<code>drop</code>	If true the media frames may be dropped if queue is full.

Definition at line 731 of file `base_streamer.h`.

10.24.5 Member Function Documentation

10.24.5.1 error()

```
virtual void vxg::media::Streamer::ISource::error (
    StreamError stream_error ) [inline], [virtual]
```

Error notification.

Calling this method will inform media thread and all sinks about error happened in the source.

Parameters

in	<code>stream_error</code>	
----	---------------------------	--

Definition at line 767 of file base_streamer.h.

10.24.5.2 finit()

```
virtual void vxg::media::Streamer::ISource::finit ( ) [pure virtual]
```

Finit souce.

Implemented in [vxg::media::ffmpeg::Source](#).

10.24.5.3 init()

```
virtual bool vxg::media::Streamer::ISource::init (
    std::string url = "" ) [pure virtual]
```

Init source.

Parameters

<i>url</i>	Url if needed.
------------	----------------

Returns

true Init success.

false Init failed.

Implemented in [vxg::media::ffmpeg::Source](#), [vxg::media::rtsp_source](#), and [vxg::media::rtmp_source](#).

10.24.5.4 name()

```
virtual std::string vxg::media::Streamer::ISource::name ( ) [pure virtual]
```

Source class name.

Returns

std::string

Implemented in [vxg::media::rtsp_source](#), and [vxg::media::ffmpeg::Source](#).

10.24.5.5 negotiate()

```
virtual std::vector<Streamer::StreamInfo> vxg::media::Streamer::ISource::negotiate ( ) [pure virtual]
```

Negotiation callback.

Called by internals. Class implementation should return the list of the streams info source will be producing for the sinks, this list will be then passed to the [ISink::negotiate](#) method.

Returns

std::vector<Streamer::StreamInfo>

Implemented in [vxg::media::ffmpeg::Source](#).

10.24.5.6 pullFrame()

```
virtual std::shared_ptr<MediaFrame> vxg::media::Streamer::ISource::pullFrame ( ) [pure virtual]
```

Main method of the Mode::PULL mode data producing.

Called by internals if the source operation mode is Mode::PULL. Implementation should return media frame object with correctly filled fields.

Returns

std::shared_ptr<MediaFrame>

Implemented in [vxg::media::ffmpeg::Source](#).

10.24.5.7 pushFrame()

```
void vxg::media::Streamer::ISource::pushFrame (
    std::shared_ptr< MediaFrame > frame ) [inline]
```

Implementation should call this method to provide media frames in the Mode::PUSH source operation mode.

Parameters

<i>frame</i>	smart pointer to MediaFrame .
--------------	---

Definition at line 870 of file base_streamer.h.

10.24.5.8 set_error_cb()

```
void vxg::media::Streamer::ISource::set_error_cb (
    on_error_cb cb ) [inline]
```

Definition at line 971 of file base_streamer.h.

10.24.6 Field Documentation

10.24.6.1 mode_

```
Mode vxg::media::Streamer::ISource::mode_ [protected]
```

Definition at line 1009 of file base_streamer.h.

10.24.6.2 on_error_cb_

```
on_error_cb vxg::media::Streamer::ISource::on_error_cb_ [protected]
```

Definition at line 1010 of file base_streamer.h.


The documentation for this class was generated from the following file:

- [base_streamer.h](#)


10.25 vxg::cloud::timed_storage::item Struct Reference

```
#include <agent/timeline.h>
```

Inheritance diagram for vxg::cloud::timed_storage::item:



Collaboration diagram for vxg::cloud::timed_storage::item:



Public Types

- enum `data_state` { `data_state::empty`, `data_state::loaded`, `data_state::async_ready` }

Public Member Functions

- `item` (`cloud::time begin=utils::time::null()`, `cloud::time end=utils::time::null()`, `std::vector< uint8_t > data=std::vector< uint8_t >()`)
- `item` (`period p`, `std::vector< uint8_t > data=std::vector< uint8_t >()`)
- `item` (`std::vector< uint8_t > &&data`)
- void `clear` ()
- bool `empty` ()
- bool `operator<` (const `item` &r)

Data Fields

- `std::vector< uint8_t > data`
- `data_state state`
- `agent::proto::command::upload_category category`
- `agent::proto::command::media_type media_type`

10.25.1 Detailed Description

Definition at line 72 of file `timeline.h`.

10.25.2 Member Enumeration Documentation

10.25.2.1 data_state

```
enum vxg::cloud::timed_storage::item::data_state [strong]
```

Enumerator

empty	
loaded	
async_ready	

Definition at line 73 of file timeline.h.

10.25.3 Constructor & Destructor Documentation

10.25.3.1 item() [1/3]

```
vxg::cloud::timed_storage::item::item (
    cloud::time begin = utils::time::null(),
    cloud::time end = utils::time::null(),
    std::vector< uint8_t > data = std::vector<uint8_t>() ) [inline]
```

Definition at line 79 of file timeline.h.

10.25.3.2 item() [2/3]

```
vxg::cloud::timed_storage::item::item (
    period p,
    std::vector< uint8_t > data = std::vector<uint8_t>() ) [inline]
```

Definition at line 86 of file timeline.h.

10.25.3.3 item() [3/3]

```
vxg::cloud::timed_storage::item::item (
    std::vector< uint8_t > && data ) [inline]
```

Definition at line 91 of file timeline.h.

10.25.4 Member Function Documentation

10.25.4.1 clear()

```
void vxg::cloud::timed_storage::item::clear ( ) [inline]
```

Definition at line 95 of file timeline.h.

10.25.4.2 empty()

```
bool vxg::cloud::timed_storage::item::empty ( ) [inline]
```

Definition at line 101 of file timeline.h.

10.25.4.3 operator<()

```
bool vxg::cloud::timed_storage::item::operator< (
    const item & r ) [inline]
```

Definition at line 106 of file timeline.h.

10.25.5 Field Documentation

10.25.5.1 category

```
agent::proto::command::upload_category vxg::cloud::timed_storage::item::category
```

Definition at line 76 of file timeline.h.

10.25.5.2 data

```
std::vector<uint8_t> vxg::cloud::timed_storage::item::data
```

Definition at line 74 of file timeline.h.

10.25.5.3 media_type

```
agent::proto::command::media_type vxg::cloud::timed_storage::item::media_type
```

Definition at line 77 of file timeline.h.

10.25.5.4 state

```
data_state vxg::cloud::timed_storage::item::state
```

Definition at line 75 of file timeline.h.

The documentation for this struct was generated from the following file:

- [timeline.h](#)

10.26 vxg::logger Class Reference

Logger class, current implementation based on spdlog.

```
#include <utils/logging.h>
```

Data Structures

- struct [options](#)

Public Types

- enum [loglevel](#) {
 [lvl_crit](#), [lvl_off](#), [lvl_error](#), [lvl_warn](#),
 [lvl_info](#), [lvl_debug](#), [lvl_trace](#) }
- typedef **std::shared_ptr**< spdlog::logger > [logger_ptr](#)

Static Public Member Functions

- static **std::shared_ptr**< spdlog::logger > **instance** (**std::string** name)
Get pointer to the instance of the named spdlog::logger object.
- static void **reset** (int argc, char **argv, **loglevel** l, **std::string** syslog_ident="VXGCloudAgentDefault", **std::string** crash_logfile_path="", **std::string** logfile_path="", size_t logfile_max_size=(1024 *1024), size_t logfile_max_files=3)
Reset default logger parameters.
- static void **reset** (const **options** &opts)
- static void **set_level** (**logger_ptr** log_ptr, **loglevel** lvl)
Change the logger object loglevel.
- template<typename FormatString , typename... Args>
static void **info** (const FormatString &fmt, const Args &... args)
Static info log.
- template<typename FormatString , typename... Args>
static void **error** (const FormatString &fmt, const Args &... args)
- template<typename FormatString , typename... Args>
static void **warn** (const FormatString &fmt, const Args &... args)
- template<typename FormatString , typename... Args>
static void **debug** (const FormatString &fmt, const Args &... args)
- template<typename FormatString , typename... Args>
static void **trace** (const FormatString &fmt, const Args &... args)
- template<typename T >
static void **trace** (const T &msg)
- template<typename T >
static void **debug** (const T &msg)
- template<typename T >
static void **info** (const T &msg)
- template<typename T >
static void **warn** (const T &msg)
- template<typename T >
static void **error** (const T &msg)
- template<typename T >
static void **critical** (const T &msg)

10.26.1 Detailed Description

Logger class, current implementation based on spdlog.

Definition at line 22 of file logging.h.

10.26.2 Member Typedef Documentation

10.26.2.1 logger_ptr

```
typedef std::shared_ptr<spdlog::logger> vxg::logger::logger_ptr
```

Definition at line 24 of file logging.h.

10.26.3 Member Enumeration Documentation

10.26.3.1 loglevel

```
enum vxg::logger::loglevel
```

Enumerator

lvl_crit	
lvl_off	
lvl_error	
lvl_warn	
lvl_info	
lvl_debug	
lvl_trace	

Definition at line 25 of file logging.h.

10.26.4 Member Function Documentation

10.26.4.1 critical()

```
template<typename T >  
static void vxg::logger::critical (  
    const T & msg ) [inline], [static]
```

Definition at line 315 of file logging.h.

10.26.4.2 debug() [1/2]

```
template<typename FormatString , typename... Args>  
static void vxg::logger::debug (  
    const FormatString & fmt,  
    const Args &... args ) [inline], [static]
```

Definition at line 282 of file logging.h.

10.26.4.3 debug() [2/2]

```
template<typename T >
static void vxg::logger::debug (
    const T & msg ) [inline], [static]
```

Definition at line 295 of file logging.h.

10.26.4.4 error() [1/2]

```
template<typename FormatString , typename... Args>
static void vxg::logger::error (
    const FormatString & fmt,
    const Args &... args ) [inline], [static]
```

Definition at line 274 of file logging.h.

10.26.4.5 error() [2/2]

```
template<typename T >
static void vxg::logger::error (
    const T & msg ) [inline], [static]
```

Definition at line 310 of file logging.h.

10.26.4.6 info() [1/2]

```
template<typename FormatString , typename... Args>
static void vxg::logger::info (
    const FormatString & fmt,
    const Args &... args ) [inline], [static]
```

Static info log.

Template Parameters

<i>FormatString</i>	
<i>Args</i>	

Parameters

<i>fmt</i>	
<i>args</i>	

Definition at line 270 of file logging.h.

10.26.4.7 info() [2/2]

```
template<typename T >
static void vxg::logger::info (
    const T & msg ) [inline], [static]
```

Definition at line 300 of file logging.h.

10.26.4.8 instance()

```
static std::shared_ptr<spdlog::logger> vxg::logger::instance (
    std::string name ) [inline], [static]
```

Get pointer to the instance of the named spdlog::logger object.

On the very first call creates default logger named 'default'. Constructs new logger if logger with such name was never requested

Parameters

in	name	Logger name. If logger with such name was already created, then it will be reused, otherwise a new one will be constructed.
----	------	---

Returns

std::shared_ptr<spdlog::logger>

Definition at line 192 of file logging.h.

10.26.4.9 reset() [1/2]

```
static void vxg::logger::reset (
    const options & opts ) [inline], [static]
```

Definition at line 239 of file logging.h.

10.26.4.10 reset() [2/2]

```
static void vxg::logger::reset (
    int argc,
    char ** argv,
    loglevel l,
    std::string syslog_ident = "VXGCloudAgentDefault",
    std::string crash_logfile_path = "",
    std::string logfile_path = "",
    size_t logfile_max_size = (1024 * 1024),
    size_t logfile_max_files = 3 ) [inline], [static]
```

Reset default logger parameters.

Used to change all loggers parameters such as syslog/file sinks usage. Should be called before very first [logger::instance\(\)](#) call to take effect. If wasn't called the default console logging sink only will be used for all loggers.

Deprecated Use [reset\(const options& opts\)](#)

Parameters

<i>argc</i>	Process argc
<i>argv</i>	Process argv
<i>l</i>	default loglevel, all loggers will be created with this loglevel, can be overridden with SPDLOG_LEVEL env variable
<i>syslog_ident</i>	Syslog identification string, if empty syslog logging will be disabled.
<i>logfile_path</i>	Rotating plain log file path, if empty no plain log file will be used.
<i>logfile_max_size</i>	Max log file size before invoking logrotate.
<i>logfile_max_files</i>	Max number if rotating logfiles.

Definition at line 220 of file logging.h.

10.26.4.11 set_level()

```
static void vxg::logger::set_level (
    logger_ptr log_ptr,
    loglevel lvl ) [inline], [static]
```

Change the logger object loglevel.

Parameters

<i>log_ptr</i>	Logger object pointer.
<i>lvl</i>	New loglevel.

Definition at line 259 of file logging.h.

10.26.4.12 trace() [1/2]

```
template<typename FormatString , typename... Args>
static void vxg::logger::trace (
    const FormatString & fmt,
    const Args &... args ) [inline], [static]
```

Definition at line 286 of file logging.h.

10.26.4.13 trace() [2/2]

```
template<typename T >
static void vxg::logger::trace (
    const T & msg ) [inline], [static]
```

Definition at line 290 of file logging.h.

10.26.4.14 warn() [1/2]

```
template<typename FormatString , typename... Args>
static void vxg::logger::warn (
    const FormatString & fmt,
    const Args &... args ) [inline], [static]
```

Definition at line 278 of file logging.h.

10.26.4.15 warn() [2/2]

```
template<typename T >
static void vxg::logger::warn (
    const T & msg ) [inline], [static]
```

Definition at line 305 of file logging.h.

The documentation for this class was generated from the following file:


- [logging.h](#)

10.27 vxg::cloud::agent::manager Class Reference


VXG Cloud agent manager class.

```
#include <agent/manager.h>
```

Inheritance diagram for vxg::cloud::agent::manager:



Collaboration diagram for vxg::cloud::agent::manager:



Public Types

- using [direct_upload_payload_map](#) = **std::map**< proto::upload_category, **std::shared_ptr**< void > >
- using [direct_upload_payload_map_ptr](#) = **std::shared_ptr**< [direct_upload_payload_map](#) >
- typedef **std::shared_ptr**< [manager](#) > ptr
shared_ptr to manager object

Public Member Functions

- bool [start](#) ()
Start internal workflow, this is the main function which starts all internal threads and connections.
- void [stop](#) ()
Stop manager, disconnect from the VXG Cloud.

Static Public Member Functions

- static [manager::ptr create](#) (const [agent::config](#) &config, [callback::ptr callback](#), const [proto::access_token](#) &[access_token](#), [std::vector](#)< [agent::media::stream::ptr](#) > media_streams, [std::vector](#)< [event_stream::ptr](#) > event_streams= [std::vector](#)< [event_stream::ptr](#) >(0))
Create manager object.

Protected Member Functions

- bool [handle_event](#) ([proto::event_object](#) &event, bool need_snapshot)
- bool [_update_storage_status](#) ()
- bool [handle_event_snapshot](#) ([proto::event_object](#) &event)
- bool [handle_event_meta_file](#) ([proto::event_object](#) &event)
- bool [__notify_record_event](#) ([std::string](#) stream_id, bool on)
- virtual bool [on_get_stream_config](#) ([proto::stream_config](#) &config)
- virtual bool [on_set_stream_config](#) (const [proto::stream_config](#) &config)
- virtual bool [on_get_motion_detection_config](#) ([proto::motion_detection_config](#) &config)
- virtual bool [on_set_motion_detection_config](#) (const [proto::motion_detection_config](#) &config)
- virtual bool [on_get_cam_video_config](#) ([proto::video_config](#) &config)
- virtual bool [on_set_cam_video_config](#) (const [proto::video_config](#) &config)
- virtual bool [on_get_cam_events_config](#) ([proto::events_config](#) &config)
- virtual bool [on_set_cam_events_config](#) (const [proto::events_config](#) &config)
- virtual bool [on_get_cam_audio_config](#) ([proto::audio_config](#) &config)
- virtual bool [on_set_cam_audio_config](#) (const [proto::audio_config](#) &config)
- virtual bool [on_get_ptz_config](#) ([proto::ptz_config](#) &config)
- virtual bool [on_cam_ptz](#) ([proto::ptz_command](#) command)
- virtual bool [on_cam_ptz_preset](#) ([proto::ptz_preset](#) &preset_op)
- virtual bool [on_get_osd_config](#) ([proto::osd_config](#) &config)
- virtual bool [on_set_osd_config](#) (const [proto::osd_config](#) &config)
- virtual bool [on_get_wifi_config](#) ([proto::wifi_config](#) &config)
- virtual bool [on_set_wifi_config](#) (const [proto::wifi_network](#) &config)
- virtual bool [on_stream_start](#) (const [std::string](#) &streamId, int publishSessionId, [proto::stream_reason](#) reason)
- virtual bool [on_stream_stop](#) (const [std::string](#) &streamId, [proto::stream_reason](#) reason)
- virtual bool [on_get_stream_caps](#) ([proto::stream_caps](#) &caps)
- virtual bool [on_get_supported_streams](#) ([proto::supported_streams_config](#) &supportedStreamsConfig)
- virtual bool [on_cam_upgrade_firmware](#) ([std::string](#) url)
- virtual bool [on_raw_message](#) ([std::string](#) client_id, [std::string](#) &data)
- virtual bool [on_set_stream_by_event](#) ([proto::stream_by_event_config](#) conf)
- virtual bool [on_get_stream_by_event](#) ([proto::stream_by_event_config](#) &conf)
- virtual bool [on_update_preview](#) ([std::string](#) url)
- virtual bool [on_direct_upload_url](#) (const [proto::command::direct_upload_url_base](#) &direct_upload, int eventId, int ref_id)
- virtual bool [on_get_log](#) ()
- virtual void [on_prepared](#) ()

- virtual void [on_closed](#) (int error, proto::command::bye_reason reason)
- virtual bool [on_get_timezone](#) (**std::string** &timezone)
- virtual bool [on_set_timezone](#) (**std::string** timezone)
- void [on_set_periodic_events](#) (const char *name, int [period](#), bool active)
- virtual bool [on_audio_file_play](#) (**std::string** url)
- virtual bool [on_start_backward](#) (**std::string** &url)
- virtual bool [on_stop_backward](#) (**std::string** &url)
- virtual bool [on_get_cam_memorycard_timeline](#) (proto::command::cam_memorycard_timeline &[timeline](#))
- virtual bool [on_cam_memorycard_synchronize](#) (proto::command::cam_memorycard_synchronize_status &synchronize_status, vxg::cloud::time start, vxg::cloud::time end)
- virtual bool [on_cam_memorycard_synchronize_cancel](#) (const **std::string** &request_id)
- virtual bool [on_cam_memorycard_recording](#) (const **std::string** &stream_id, bool enabled)
- virtual bool [on_trigger_event](#) (**std::string** event, json meta, cloud::time time)
- virtual bool [on_set_audio_detection](#) (const proto::audio_detection_config &conf)
- virtual bool [on_get_audio_detection](#) (proto::audio_detection_config &conf)
- virtual bool [on_set_log_enable](#) (bool bEnable)
- virtual bool [on_set_activity](#) (bool bEnable)
- virtual void [on_registered](#) (const **std::string** &sid)

10.27.1 Detailed Description

VXG Cloud agent manager class.

Definition at line 44 of file manager.h.

10.27.2 Member Typedef Documentation

10.27.2.1 direct_upload_payload_map

```
using vxg::cloud::agent::manager::direct_upload_payload_map = std::map<proto::upload_category,
std::shared_ptr<void> >
```

Definition at line 105 of file manager.h.

10.27.2.2 direct_upload_payload_map_ptr

```
using vxg::cloud::agent::manager::direct_upload_payload_map_ptr = std::shared_ptr<direct_upload_payload_map>
```

Definition at line 107 of file manager.h.

10.27.2.3 ptr

```
typedef std::shared_ptr<manager> vxg::cloud::agent::manager::ptr
```

shared_ptr to manager object

Definition at line 123 of file manager.h.

10.27.3 Member Function Documentation

10.27.3.1 __notify_record_event()

```
bool vxg::cloud::agent::manager::__notify_record_event (
    std::string stream_id,
    bool on ) [protected]
```

10.27.3.2 _update_storage_status()

```
bool vxg::cloud::agent::manager::_update_storage_status ( ) [protected]
```

10.27.3.3 create()

```
static manager::ptr vxg::cloud::agent::manager::create (
    const agent::config & config,
    callback::ptr callback,
    const proto::access_token & access_token,
    std::vector< agent::media::stream::ptr > media_streams,
    std::vector< event_stream::ptr > event_streams = std::vector< event_stream::ptr > (0)
) [static]
```

Create manager object.

Parameters

in	<i>config</i>	
in	<i>callback</i>	cm::callback object, should not be null
in	<i>access_token</i>	VXG Cloud access token
in	<i>media_streams</i>	List of std::shared_ptr to base_stream derived objects. Should have at least one element. base_stream is abstract class so you need to declare you own class derived from the base_stream or use one of the provided classes (rtsp_stream,...), basically each stream is for example one rtsp stream provided by the device. Each media stream device has should be represented as a separate base_stream derived object, currently only two streams per device are supported by the VXG Cloud.
in	<i>event_streams</i>	List of <i>event_stream::ptr</i> , can be empty. <i>event_stream</i> is abstract class so final implementation should use own class derived from the <i>event_stream</i> .
		Generated by Doxygen

Returns

[manager::ptr](#)

10.27.3.4 handle_event()

```
bool vxg::cloud::agent::manager::handle_event (
    proto::event_object & event,
    bool need_snapshot ) [protected]
```

10.27.3.5 handle_event_meta_file()

```
bool vxg::cloud::agent::manager::handle_event_meta_file (
    proto::event_object & event ) [protected]
```

10.27.3.6 handle_event_snapshot()

```
bool vxg::cloud::agent::manager::handle_event_snapshot (
    proto::event_object & event ) [protected]
```

10.27.3.7 on_audio_file_play()

```
virtual bool vxg::cloud::agent::manager::on_audio_file_play (
    std::string url ) [protected], [virtual]
```

10.27.3.8 on_cam_memorycard_recording()

```
virtual bool vxg::cloud::agent::manager::on_cam_memorycard_recording (
    const std::string & stream_id,
    bool enabled ) [protected], [virtual]
```

10.27.3.9 on_cam_memorycard_synchronize()

```
virtual bool vxg::cloud::agent::manager::on_cam_memorycard_synchronize (
    proto::command::cam_memorycard_synchronize_status & synchronize_status,
    vxg::cloud::time start,
    vxg::cloud::time end ) [protected], [virtual]
```

10.27.3.10 on_cam_memorycard_synchronize_cancel()

```
virtual bool vxg::cloud::agent::manager::on_cam_memorycard_synchronize_cancel (
    const std::string & request_id ) [protected], [virtual]
```

10.27.3.11 on_cam_ptz()

```
virtual bool vxg::cloud::agent::manager::on_cam_ptz (
    proto::ptz_command command ) [protected], [virtual]
```

10.27.3.12 on_cam_ptz_preset()

```
virtual bool vxg::cloud::agent::manager::on_cam_ptz_preset (
    proto::ptz_preset & preset_op ) [protected], [virtual]
```

10.27.3.13 on_cam_upgrade_firmware()

```
virtual bool vxg::cloud::agent::manager::on_cam_upgrade_firmware (
    std::string url ) [protected], [virtual]
```

10.27.3.14 on_closed()

```
virtual void vxg::cloud::agent::manager::on_closed (
    int error,
    proto::command::bye_reason reason ) [protected], [virtual]
```

10.27.3.15 on_direct_upload_url()

```
virtual bool vxg::cloud::agent::manager::on_direct_upload_url (
    const proto::command::direct_upload_url_base & direct_upload,
    int event_id,
    int ref_id ) [protected], [virtual]
```

10.27.3.16 on_get_audio_detection()

```
virtual bool vxg::cloud::agent::manager::on_get_audio_detection (
    proto::audio_detection_config & conf ) [protected], [virtual]
```

10.27.3.17 on_get_cam_audio_config()

```
virtual bool vxg::cloud::agent::manager::on_get_cam_audio_config (
    proto::audio_config & config ) [protected], [virtual]
```

10.27.3.18 on_get_cam_events_config()

```
virtual bool vxg::cloud::agent::manager::on_get_cam_events_config (
    proto::events_config & config ) [protected], [virtual]
```

10.27.3.19 on_get_cam_memorycard_timeline()

```
virtual bool vxg::cloud::agent::manager::on_get_cam_memorycard_timeline (
    proto::command::cam_memorycard_timeline & timeline ) [protected], [virtual]
```

10.27.3.20 on_get_cam_video_config()

```
virtual bool vxg::cloud::agent::manager::on_get_cam_video_config (
    proto::video_config & config ) [protected], [virtual]
```

10.27.3.21 on_get_log()

```
virtual bool vxg::cloud::agent::manager::on_get_log ( ) [protected], [virtual]
```

10.27.3.22 on_get_motion_detection_config()

```
virtual bool vxg::cloud::agent::manager::on_get_motion_detection_config (
    proto::motion_detection_config & config ) [protected], [virtual]
```

10.27.3.23 on_get_osd_config()

```
virtual bool vxg::cloud::agent::manager::on_get_osd_config (
    proto::osd_config & config ) [protected], [virtual]
```

10.27.3.24 on_get_ptz_config()

```
virtual bool vxg::cloud::agent::manager::on_get_ptz_config (
    proto::ptz_config & config ) [protected], [virtual]
```

10.27.3.25 on_get_stream_by_event()

```
virtual bool vxg::cloud::agent::manager::on_get_stream_by_event (
    proto::stream_by_event_config & conf ) [protected], [virtual]
```

10.27.3.26 on_get_stream_caps()

```
virtual bool vxg::cloud::agent::manager::on_get_stream_caps (
    proto::stream_caps & caps ) [protected], [virtual]
```

10.27.3.27 on_get_stream_config()

```
virtual bool vxg::cloud::agent::manager::on_get_stream_config (
    proto::stream_config & config ) [protected], [virtual]
```

10.27.3.28 on_get_supported_streams()

```
virtual bool vxg::cloud::agent::manager::on_get_supported_streams (
    proto::supported_streams_config & supportedStreamsConfig ) [protected], [virtual]
```

10.27.3.29 on_get_timezone()

```
virtual bool vxg::cloud::agent::manager::on_get_timezone (
    std::string & timezone ) [protected], [virtual]
```

10.27.3.30 on_get_wifi_config()

```
virtual bool vxg::cloud::agent::manager::on_get_wifi_config (
    proto::wifi_config & config ) [protected], [virtual]
```

10.27.3.31 on_prepared()

```
virtual void vxg::cloud::agent::manager::on_prepared ( ) [protected], [virtual]
```

10.27.3.32 on_raw_message()

```
virtual bool vxg::cloud::agent::manager::on_raw_message (
    std::string client_id,
    std::string & data ) [protected], [virtual]
```

10.27.3.33 on_registered()

```
virtual void vxg::cloud::agent::manager::on_registered (
    const std::string & sid ) [protected], [virtual]
```

10.27.3.34 on_set_activity()

```
virtual bool vxg::cloud::agent::manager::on_set_activity (
    bool bEnable ) [protected], [virtual]
```

10.27.3.35 on_set_audio_detection()

```
virtual bool vxg::cloud::agent::manager::on_set_audio_detection (
    const proto::audio_detection_config & conf ) [protected], [virtual]
```

10.27.3.36 on_set_cam_audio_config()

```
virtual bool vxg::cloud::agent::manager::on_set_cam_audio_config (
    const proto::audio_config & config ) [protected], [virtual]
```

10.27.3.37 on_set_cam_events_config()

```
virtual bool vxg::cloud::agent::manager::on_set_cam_events_config (
    const proto::events_config & config ) [protected], [virtual]
```

10.27.3.38 on_set_cam_video_config()

```
virtual bool vxg::cloud::agent::manager::on_set_cam_video_config (
    const proto::video_config & config ) [protected], [virtual]
```

10.27.3.39 on_set_log_enable()

```
virtual bool vxg::cloud::agent::manager::on_set_log_enable (
    bool bEnable ) [protected], [virtual]
```

10.27.3.40 on_set_motion_detection_config()

```
virtual bool vxg::cloud::agent::manager::on_set_motion_detection_config (
    const proto::motion_detection_config & config ) [protected], [virtual]
```

10.27.3.41 on_set_osd_config()

```
virtual bool vxg::cloud::agent::manager::on_set_osd_config (
    const proto::osd_config & config ) [protected], [virtual]
```

10.27.3.42 on_set_periodic_events()

```
void vxg::cloud::agent::manager::on_set_periodic_events (
    const char * name,
    int period,
    bool active ) [protected]
```

10.27.3.43 on_set_stream_by_event()

```
virtual bool vxg::cloud::agent::manager::on_set_stream_by_event (
    proto::stream_by_event_config conf ) [protected], [virtual]
```


10.27.3.44 on_set_stream_config()

```
virtual bool vxg::cloud::agent::manager::on_set_stream_config (
    const proto::stream\_config & config ) [protected], [virtual]
```

10.27.3.45 on_set_timezone()

```
virtual bool vxg::cloud::agent::manager::on_set_timezone (
    std::string timezone ) [protected], [virtual]
```

10.27.3.46 on_set_wifi_config()

```
virtual bool vxg::cloud::agent::manager::on_set_wifi_config (
    const proto::wifi\_network & config ) [protected], [virtual]
```

10.27.3.47 on_start_backward()

```
virtual bool vxg::cloud::agent::manager::on_start_backward (
    std::string & url ) [protected], [virtual]
```

10.27.3.48 on_stop_backward()

```
virtual bool vxg::cloud::agent::manager::on_stop_backward (
    std::string & url ) [protected], [virtual]
```

10.27.3.49 on_stream_start()

```
virtual bool vxg::cloud::agent::manager::on_stream_start (
    const std::string & streamId,
    int publishSessionID,
    proto::stream\_reason reason ) [protected], [virtual]
```

10.27.3.50 on_stream_stop()

```
virtual bool vxg::cloud::agent::manager::on_stream_stop (
    const std::string & streamId,
    proto::stream_reason reason ) [protected], [virtual]
```

10.27.3.51 on_trigger_event()

```
virtual bool vxg::cloud::agent::manager::on_trigger_event (
    std::string event,
    json meta,
    cloud::time time ) [protected], [virtual]
```

10.27.3.52 on_update_preview()

```
virtual bool vxg::cloud::agent::manager::on_update_preview (
    std::string url ) [protected], [virtual]
```

10.27.3.53 start()

```
bool vxg::cloud::agent::manager::start ( )
```

Start internal workflow, this is the main function which starts all internal threads and connections.

Returns

true started
false start failed

10.27.3.54 stop()

```
void vxg::cloud::agent::manager::stop ( )
```

Stop manager, disconnect from the VXG Cloud.


The documentation for this class was generated from the following file:

- [manager.h](#)


10.28 vxg::cloud::utils::motion::map Struct Reference

```
#include <utils/utils.h>
```

Inheritance diagram for vxg::cloud::utils::motion::map:



Collaboration diagram for vxg::cloud::utils::motion::map:



Public Member Functions

- [map](#) ()
- [map](#) (const [map](#) &motionMap)
- [map](#) & [operator=](#) (const **std::string** &motionMap)

Static Public Member Functions

- static **std::string** [pack](#) (const **std::string** &unpackedGrid)
- static **std::string** [unpack](#) (const **std::string** &packedMap, size_t outputLen)

10.28.1 Detailed Description

Definition at line 124 of file utils.h.

10.28.2 Constructor & Destructor Documentation

10.28.2.1 `map()` [1/2]

```
vxg::cloud::utils::motion::map::map ( ) [inline], [explicit]
```

Definition at line 125 of file `utils.h`.

10.28.2.2 `map()` [2/2]

```
vxg::cloud::utils::motion::map::map (
    const map & motionMap ) [inline]
```

Definition at line 127 of file `utils.h`.

10.28.3 Member Function Documentation

10.28.3.1 `operator=()`

```
map& vxg::cloud::utils::motion::map::operator= (
    const std::string & motionMap ) [inline]
```

Definition at line 129 of file `utils.h`.

10.28.3.2 `pack()`

```
static std::string vxg::cloud::utils::motion::map::pack (
    const std::string & unpackedGrid ) [static]
```

10.28.3.3 `unpack()`

```
static std::string vxg::cloud::utils::motion::map::unpack (
    const std::string & packedMap,
    size_t outputLen ) [static]
```

The documentation for this struct was generated from the following file:


- [utils.h](#)

10.29 vxg::media::Streamer::MediaFrame Struct Reference

Media frame container.

```
#include <streamer/base_streamer.h>
```

Collaboration diagram for vxg::media::Streamer::MediaFrame:



Public Member Functions

- bool [operator<](#) (const [MediaFrame](#) &rv)
Two frames comparison using timestamps.

Data Fields

- **std::vector< uint8_t >** [data](#)
Media frame data.
- **size_t** [len](#)
Media frame data length.
- **int64_t** [pts](#)
Media frame timestamp in timescale that corresponds to timescale.
- **int64_t** [dts](#)
Media frame decoding timestamp in timescale that corresponds to timescale.
- **int64_t** [duration](#)
Media frame duration if needed.
- bool [is_key](#)
Is key frame flag.
- **MediaType** [type](#)
Media frame type.
- **std::pair< int, int >** [timescale](#)
Timescale of pts and duration. ex. : 1/90000, 1/1000 etc.
- **int64_t** [time_realtime](#)
Real time if available from source, for ex.

Static Public Attributes

- static constexpr int64_t [NOPTS](#)

10.29.1 Detailed Description

Media frame container.

Definition at line 418 of file base_streamer.h.

10.29.2 Member Function Documentation

10.29.2.1 operator<()

```
bool vxg::media::Streamer::MediaFrame::operator< (
    const MediaFrame & rv ) [inline]
```

Two frames comparison using timestamps.

Parameters

<i>rv</i>	Right value
-----------	-------------

Returns

true

false

Definition at line 436 of file base_streamer.h.

10.29.3 Field Documentation

10.29.3.1 data

```
std::vector<uint8_t> vxg::media::Streamer::MediaFrame::data
```

Media frame data.

Definition at line 441 of file base_streamer.h.

10.29.3.2 dts

```
int64_t vxg::media::Streamer::MediaFrame::dts
```

Media frame decoding timestamp in timescale that corresponds to timescale.

Definition at line 448 of file base_streamer.h.

10.29.3.3 duration

```
int64_t vxg::media::Streamer::MediaFrame::duration
```

Media frame duration if needed.

Definition at line 450 of file base_streamer.h.

10.29.3.4 is_key

```
bool vxg::media::Streamer::MediaFrame::is_key
```

Is key frame flag.

Definition at line 452 of file base_streamer.h.

10.29.3.5 len

```
size_t vxg::media::Streamer::MediaFrame::len
```

Media frame data length.

Definition at line 443 of file base_streamer.h.

10.29.3.6 NOPTS

```
constexpr int64_t vxg::media::Streamer::MediaFrame::NOPTS [static], [constexpr]
```

Definition at line 438 of file base_streamer.h.

10.29.3.7 pts

```
int64_t vxg::media::Streamer::MediaFrame::pts
```

Media frame timestamp in timescale that corresponds to timescale.

Definition at line 445 of file base_streamer.h.

10.29.3.8 time_realtime

```
int64_t vxg::media::Streamer::MediaFrame::time_realtime
```

Real time if available from source, for ex.

pts based on NTP time from RTCP SR

Definition at line 459 of file base_streamer.h.

10.29.3.9 timescale

```
std::pair<int, int> vxg::media::Streamer::MediaFrame::timescale
```

Timescale of pts and duration. ex. : 1/90000, 1/1000 etc.

Definition at line 456 of file base_streamer.h.

10.29.3.10 type

```
MediaType vxg::media::Streamer::MediaFrame::type
```

Media frame type.

Definition at line 454 of file base_streamer.h.

The documentation for this struct was generated from the following file:

- [base_streamer.h](#)

10.30 vxg::cloud::agent::proto::motion_detection_caps Struct Reference

Motion detection capabilities camera capabilities that limit possible motion detection configuration.

```
#include <agent-proto/objects/caps.h>
```


Data Fields

- [size_t max_regions](#)
Mandatory: supported number of motion regions.
- [motion_sensitivity sensitivity](#)
Mandatory: ("region", "frame"), default "region"; indicates if sensitivity can be set for region or for whole frame only.
- [motion_region_shape region_shape](#)
Mandatory: ("rect", "any"), default "any"; specifies limitation of region shape.

10.30.1 Detailed Description

Motion detection capabilities camera capabilities that limit possible motion detection configuration.

Definition at line 336 of file caps.h.

10.30.2 Field Documentation

10.30.2.1 max_regions

```
size_t vxg::cloud::agent::proto::motion_detection_caps::max_regions
```

Mandatory: supported number of motion regions.

Definition at line 339 of file caps.h.

10.30.2.2 region_shape

```
motion_region_shape vxg::cloud::agent::proto::motion_detection_caps::region_shape
```

Mandatory: ("rect", "any"), default "any"; specifies limitation of region shape.

Definition at line 348 of file caps.h.

10.30.2.3 sensitivity

```
motion_sensitivity vxg::cloud::agent::proto::motion_detection_caps::sensitivity
```

Mandatory: ("region", "frame"), default "region"; indicates if sensitivity can be set for region or for whole frame only.

Definition at line 344 of file caps.h.

The documentation for this struct was generated from the following file:


- [caps.h](#)

10.31 vxg::cloud::agent::proto::motion_detection_config Struct Reference

Motion detection config.

```
#include <agent-proto/objects/config.h>
```

Collaboration diagram for vxg::cloud::agent::proto::motion_detection_config:



Data Fields

- int [columns](#)
Mandatory.
- int [rows](#)
Mandatory.
- [motion_detection_caps caps](#)
Mandatory for CM => SRV (reply to 'get_motion_detection') camera capabilities that limit possible motion detection configuration.
- [std::vector< motion_region > regions](#)
Mandatory List of motion regions.

10.31.1 Detailed Description

Motion detection config.

Definition at line 277 of file config.h.

10.31.2 Field Documentation

10.31.2.1 caps

[motion_detection_caps](#) vxg::cloud::agent::proto::motion_detection_config::caps

Mandatory for CM => SRV (reply to 'get_motion_detection') camera capabilities that limit possible motion detection configuration.

Definition at line 286 of file config.h.

10.31.2.2 columns

```
int vxg::cloud::agent::proto::motion_detection_config::columns
```

Mandatory.

Definition at line 280 of file config.h.

10.31.2.3 regions

```
std::vector<motion_region> vxg::cloud::agent::proto::motion_detection_config::regions
```

Mandatory List of motion regions.

Definition at line 289 of file config.h.

10.31.2.4 rows

```
int vxg::cloud::agent::proto::motion_detection_config::rows
```

Mandatory.

Definition at line 283 of file config.h.

The documentation for this struct was generated from the following file:


- [config.h](#)

10.32 vxg::cloud::agent::proto::motion_region Struct Reference

Motion detection related structs.

```
#include <agent-proto/objects/config.h>
```

Collaboration diagram for vxg::cloud::agent::proto::motion_region:



Data Fields

- **std::string** [region](#)
Mandatory: name of region if supported by camera.
- **std::string** [map](#)
Mandatory: String is packed with Apple Packbit algorithm and after that encoded with Base64.
- **size_t** [sensitivity](#)
Mandatory: range 0-100; 0 - minimal sensitivity.
- **bool** [enabled](#)
Mandatory: indicates that motion detection is enabled for the region.

10.32.1 Detailed Description

Motion detection related structs.

Motion region

Definition at line 240 of file config.h.

10.32.2 Field Documentation

10.32.2.1 [enabled](#)

```
bool vxg::cloud::agent::proto::motion_region::enabled
```

Mandatory: indicates that motion detection is enabled for the region.

Definition at line 262 of file config.h.

10.32.2.2 [map](#)

```
std::string vxg::cloud::agent::proto::motion_region::map
```

Mandatory: String is packed with Apple Packbit algorithm and after that encoded with Base64.

Bitstring where “1” denotes an active cell and a “0” an inactive cell. The first cell is in the upper left corner. Then the cell order goes first from left to right and then from up to down. If the number of cells is not a multiple of 8 the last byte is padded with zeros.

Definition at line 252 of file config.h.

10.32.2.3 region

```
std::string vxg::cloud::agent::proto::motion_region::region
```

Mandatory: name of region if supported by camera.

Definition at line 243 of file config.h.

10.32.2.4 sensitivity

```
size_t vxg::cloud::agent::proto::motion_region::sensitivity
```

Mandatory: range 0-100; 0 - minimal sensitivity.

If sensitivity is supported only for whole frame, the same value should be used for all regions.

Definition at line 258 of file config.h.


The documentation for this struct was generated from the following file:

- [config.h](#)

10.33 vxg::logger::options Struct Reference

```
#include <utils/logging.h>
```

Collaboration diagram for vxg::logger::options:



Data Fields

- `std::string` `log_pattern`
- `std::string` `logfile_path`
- `size_t` `logfile_max_size`
- `size_t` `logfile_max_files`
- `std::string` `crash_logfile_path`
- `std::string` `syslog_ident`
- `loglevel` `default_loglevel`
- `bool` `tcp_logsink_enabled`
- `std::string` `tcp_logsink_host`
- `uint16_t` `tcp_logsink_port`

10.33.1 Detailed Description

Definition at line 35 of file `logging.h`.

10.33.2 Field Documentation

10.33.2.1 `crash_logfile_path`

```
std::string vxg::logger::options::crash_logfile_path
```

Definition at line 41 of file `logging.h`.

10.33.2.2 `default_loglevel`

```
loglevel vxg::logger::options::default_loglevel
```

Definition at line 43 of file `logging.h`.

10.33.2.3 `log_pattern`

```
std::string vxg::logger::options::log_pattern
```

Definition at line 36 of file `logging.h`.

10.33.2.4 logfile_max_files

```
size_t vxg::logger::options::logfile_max_files
```

Definition at line 40 of file logging.h.

10.33.2.5 logfile_max_size

```
size_t vxg::logger::options::logfile_max_size
```

Definition at line 39 of file logging.h.

10.33.2.6 logfile_path

```
std::string vxg::logger::options::logfile_path
```

Definition at line 38 of file logging.h.

10.33.2.7 syslog_ident

```
std::string vxg::logger::options::syslog_ident
```

Definition at line 42 of file logging.h.

10.33.2.8 tcp_logsink_enabled

```
bool vxg::logger::options::tcp_logsink_enabled
```

Definition at line 44 of file logging.h.

10.33.2.9 tcp_logsink_host

```
std::string vxg::logger::options::tcp_logsink_host
```

Definition at line 45 of file logging.h.

10.33.2.10 tcp_logsink_port

uint16_t vxg::logger::options::tcp_logsink_port

Definition at line 46 of file logging.h.

The documentation for this struct was generated from the following file:


- [logging.h](#)

10.34 vxg::cloud::agent::proto::osd_caps Struct Reference

OSD capabilities.

```
#include <agent-proto/objects/caps.h>
```

Collaboration diagram for vxg::cloud::agent::proto::osd_caps:



Data Fields

- bool [system_id](#)
system_id: bool, True when OSD supports separate system_id enabling/disabling
- bool [system_id_text](#)
system_id_text: bool, True when OSD supports separate system_id customization
- bool [time](#)
time: bool, True when OSD supports separate time enabling/disabling
- **std::vector**< [time_format_n](#) > [time_format](#)
time_format: list of string, supported time formats.
- bool [date](#)
date: bool, True when OSD supports separate date enabling/disabling
- **std::vector**< **std::string** > [date_format](#)
date_format: list of string, supported date formats.
- **std::vector**< **std::string** > [font_size](#)
font_size: list of string, describes supported font sizes.
- **std::vector**< **std::pair**< **std::string**, **std::string** > > [font_color](#)
font_color: list of pairs [string (name), optional string (value)], predefined set of possible font colors.
- **std::vector**< **std::pair**< **std::string**, **std::string** > > [bkg_color](#)
bkg_color: list of pairs [string (name), optional string (value)], predefined set of possible background colors.
- bool [bkg_transp](#)
bkg_transp: bool, True when OSD supports background transparency
- **std::vector**< **std::string** > [alignment](#)
alignment: list of strings, supported OSD positions.

10.34.1 Detailed Description

OSD capabilities.

Definition at line 621 of file caps.h.

10.34.2 Field Documentation

10.34.2.1 alignment

```
std::vector< std::string> vxg::cloud::agent::proto::osd_caps::alignment
```

alignment: list of strings, supported OSD positions.

Empty list means – position can't be changed. Example: ["UpperLeft", "UpperRight", "LowerLeft", "LowerRight"]

Definition at line 660 of file caps.h.

10.34.2.2 bkg_color

```
std::vector< std::pair< std::string, std::string> > vxg::cloud::agent::proto::osd_caps↵
::bkg_color
```

bkg_color: list of pairs [string (name), optional string (value)], predefined set of possible background colors.

Empty list means – color selection is not supported. Optioanal value is a RGB color code in HEX. Example: [{"↵
Black", "000000"}]

Definition at line 654 of file caps.h.

10.34.2.3 bkg_transp

```
bool vxg::cloud::agent::proto::osd_caps::bkg_transp
```

bkg_transp: bool, True when OSD supports background transparency

Definition at line 656 of file caps.h.

10.34.2.4 date

```
bool vxg::cloud::agent::proto::osd_caps::date
```

date: bool, True when OSD supports separate date enabling/disabling

Definition at line 635 of file caps.h.

10.34.2.5 date_format

```
std::vector< std::string> vxg::cloud::agent::proto::osd_caps::date_format
```

date_format: list of string, supported date formats.

Empty list means – date format selection is not supported. Example: ["YYYY-MM-DD", "MM-DD-YYYY", "DD-MM-YYYY", "YYYY/MM/DD", "MM/DD/YYYY2", "DD/MM/YYYY"]

Definition at line 639 of file caps.h.

10.34.2.6 font_color

```
std::vector< std::pair< std::string, std::string> > vxg::cloud::agent::proto::osd_caps←  
::font_color
```

font_color: list of pairs [string (name), optional string (value)], predefined set of possible font colors.

Empty list means – color selection is not supported. Optioanal value is a RGB color code in HEX. Example: [{"↵
Orange", "FF9C00"}]

Definition at line 648 of file caps.h.

10.34.2.7 font_size

```
std::vector< std::string> vxg::cloud::agent::proto::osd_caps::font_size
```

font_size: list of string, describes supported font sizes.

Empty list means – font size format selection is not supported. Examples: ["16", "32", "48", "64", "auto"] or ["Small", "Normal", "Big"]

Definition at line 643 of file caps.h.

10.34.2.8 system_id

```
bool vxg::cloud::agent::proto::osd_caps::system_id
```

system_id: bool, True when OSD supports separate system_id enabling/disabling

Definition at line 624 of file caps.h.

10.34.2.9 system_id_text

```
bool vxg::cloud::agent::proto::osd_caps::system_id_text
```

system_id_text: bool, True when OSD supports separate system_id customization

Definition at line 627 of file caps.h.

10.34.2.10 time

```
bool vxg::cloud::agent::proto::osd_caps::time
```

time: bool, True when OSD supports separate time enabling/disabling

Definition at line 629 of file caps.h.

10.34.2.11 time_format

```
std::vector<time_format_n> vxg::cloud::agent::proto::osd_caps::time_format
```

time_format: list of string, supported time formats.

Empty list means – time format selection is not supported. Example: ["12h", "24h"]

Definition at line 633 of file caps.h.

The documentation for this struct was generated from the following file:


- [caps.h](#)

10.35 vxg::cloud::agent::osd_config Struct Reference

OSD config.

```
#include <agent-proto/objects/config.h>
```

Collaboration diagram for vxg::cloud::agent::osd_config:



Data Fields

- bool [system_id](#)
system_id: optional bool, enable/disable static part of OSD
- **std::string** [system_id_text](#)
system_id_text: optional string, a static content of OSD
- bool [time](#)
time: optional bool, enable/disable time part of OSD
- time_format_n [time_format](#)
time_format: optional string, one of predefined values from the time_format_n, should be included in caps.
- bool [date](#)
date: optional bool, enable/disable date part of OSD
- **std::string** [date_format](#)
date_format: optional string, one of predefined values from caps
- **std::string** [font_size](#)
font_size: optional string, one of predefined font sizes from caps
- **std::string** [font_color](#)
font_color: optional string, name of one of predefined font colors from caps
- **std::string** [bkg_color](#)
bkg_color: optional string, name of one of predefined background colors from caps
- bool [bkg_transp](#)
bkg_transp: optional bool, enable/disable OSD background transparency
- **std::string** [alignment](#)
alignment: optional string, one of predefined positions from caps
- osd_caps [caps](#)
OSD capabilities of the device.

10.35.1 Detailed Description

OSD config.

On Screen Display configuration object.

Definition at line 1134 of file config.h.

10.35.2 Field Documentation

10.35.2.1 alignment

```
std::string vxg::cloud::agent::osd_config::alignment
```

alignment: optional string, one of predefined positions from caps

Definition at line 1165 of file config.h.

10.35.2.2 bkg_color

```
std::string vxg::cloud::agent::osd_config::bkg_color
```

bkg_color: optional string, name of one of predefined background colors from caps

Definition at line 1161 of file config.h.

10.35.2.3 bkg_transp

```
bool vxg::cloud::agent::osd_config::bkg_transp
```

bkg_transp: optional bool, enable/disable OSD background transparency

Definition at line 1163 of file config.h.

10.35.2.4 caps

```
osd_caps vxg::cloud::agent::osd_config::caps
```

OSD capabilities of the device.

Definition at line 1168 of file config.h.

10.35.2.5 date

```
bool vxg::cloud::agent::osd_config::date
```

date: optional bool, enable/disable date part of OSD

Definition at line 1149 of file config.h.

10.35.2.6 date_format

```
std::string vxg::cloud::agent::osd_config::date_format
```

date_format: optional string, one of predefined values from caps

Definition at line 1152 of file config.h.

10.35.2.7 font_color

```
std::string vxg::cloud::agent::osd_config::font_color
```

font_color: optional string, name of one of predefined font colors from caps

Definition at line 1158 of file config.h.

10.35.2.8 font_size

```
std::string vxg::cloud::agent::osd_config::font_size
```

font_size: optional string, one of predefined font sizes from caps

Definition at line 1155 of file config.h.

10.35.2.9 system_id

```
bool vxg::cloud::agent::osd_config::system_id
```

system_id: optional bool, enable/disable static part of OSD

Definition at line 1137 of file config.h.

10.35.2.10 system_id_text

```
std::string vxg::cloud::agent::osd_config::system_id_text
```

system_id_text: optional string, a static content of OSD

Definition at line 1140 of file config.h.

10.35.2.11 time

```
bool vxg::cloud::agent::osd_config::time
```

time: optional bool, enable/disable time part of OSD

Definition at line 1143 of file config.h.

10.35.2.12 time_format

```
time_format_n vxg::cloud::agent::osd_config::time_format
```

time_format: optional string, one of predefined values from the time_format_n, should be included in caps.

Definition at line 1146 of file config.h.


The documentation for this struct was generated from the following file:

- [config.h](#)


10.36 vxg::cloud::period Struct Reference

```
#include <agent/timeline.h>
```

Inheritance diagram for vxg::cloud::period:



Collaboration diagram for vxg::cloud::period:



Public Member Functions

- [period](#) ([cloud::time](#) _begin=[utils::time::null\(\)](#), [cloud::time](#) _end=[utils::time::null\(\)](#))
- [period](#) ([agent::proto::command::get_direct_upload_url](#) l)
- bool [is_open](#) ()
- bool [is_null](#) ()
- bool [is_valid](#) ()
- bool [intersects](#) (const [period](#) &r)
- void [clear](#) ()
- [cloud::time::duration](#) [duration](#) ()
- bool [operator<](#) (const [period](#) &r)

Data Fields

- [cloud::time](#) [begin](#)
- [cloud::time](#) [end](#)

10.36.1 Detailed Description

Definition at line 23 of file timeline.h.

10.36.2 Constructor & Destructor Documentation

10.36.2.1 period() [1/2]

```
vxg::cloud::period::period (
    cloud::time _begin = utils::time::null(),
    cloud::time _end = utils::time::null() ) [inline]
```

Definition at line 27 of file timeline.h.

10.36.2.2 period() [2/2]

```
vxg::cloud::period::period (
    agent::proto::command::get_direct_upload_url l ) [inline]
```

Definition at line 32 of file timeline.h.

10.36.3 Member Function Documentation

10.36.3.1 clear()

```
void vxg::cloud::period::clear ( ) [inline]
```

Definition at line 57 of file timeline.h.

10.36.3.2 duration()

```
cloud::time::duration vxg::cloud::period::duration ( ) [inline]
```

Definition at line 62 of file timeline.h.

10.36.3.3 intersects()

```
bool vxg::cloud::period::intersects (
    const period & r ) [inline]
```

Definition at line 46 of file timeline.h.

10.36.3.4 is_null()

```
bool vxg::cloud::period::is_null ( ) [inline]
```

Definition at line 40 of file timeline.h.

10.36.3.5 is_open()

```
bool vxg::cloud::period::is_open ( ) [inline]
```

Definition at line 39 of file timeline.h.

10.36.3.6 is_valid()

```
bool vxg::cloud::period::is_valid ( ) [inline]
```

Definition at line 41 of file timeline.h.

10.36.3.7 operator<()

```
bool vxg::cloud::period::operator< (
    const period & r ) [inline]
```

Definition at line 64 of file timeline.h.

10.36.4 Field Documentation

10.36.4.1 begin

```
cloud::time vxg::cloud::period::begin
```

Definition at line 24 of file timeline.h.

10.36.4.2 end

`cloud::time vxg::cloud::period::end`

Definition at line 25 of file timeline.h.

The documentation for this struct was generated from the following file:


- [timeline.h](#)

10.37 vxg::cloud::agent::access_token::proxy_config Struct Reference

Socks proxy settings.

```
#include <agent-proto/objects/config.h>
```

Collaboration diagram for vxg::cloud::agent::access_token::proxy_config:



Data Fields

- `std::string socks4`
SOCKS4 proxy uri.
- `std::string socks5`
SOCKS5 proxy uri, ex. socks5://user:pwd@host:port.

10.37.1 Detailed Description

Socks proxy settings.

Definition at line 1194 of file config.h.

10.37.2 Field Documentation

10.37.2.1 socks4

`std::string vxg::cloud::agent::access_token::proxy_config::socks4`

SOCKS4 proxy uri.

Definition at line 1196 of file config.h.

10.37.2.2 socks5

`std::string vxg::cloud::agent::access_token::proxy_config::socks5`

SOCKS5 proxy uri, ex. socks5://user:pwd@host:port.

Definition at line 1198 of file config.h.

The documentation for this struct was generated from the following file:

- [config.h](#)

10.38 vxg::cloud::agent::ptz_command Struct Reference

PTZ command.

```
#include <agent-proto/objects/config.h>
```

Data Fields

- ptz_action [action](#)
action: string, Camera informs server about list of supported actions with 3.30 cam_ptz_conf (CM) command
- int [tm](#)
tm: optional int, operation time that allows to make PTZ with specified steps, msec

10.38.1 Detailed Description

PTZ command.

Definition at line 1112 of file config.h.

10.38.2 Field Documentation

10.38.2.1 action

```
ptz_action vxg::cloud::agent::ptz_command::action
```

action: string, Camera informs server about list of supported actions with 3.30 cam_ptz_conf (CM) command

Definition at line 1116 of file config.h.

10.38.2.2 tm

```
int vxg::cloud::agent::ptz_command::tm
```

tm: optional int, operation time that allows to make PTZ with specified steps, msec

Definition at line 1120 of file config.h.

The documentation for this struct was generated from the following file:


- [config.h](#)

10.39 vxg::cloud::agent::ptz_config Struct Reference

PTZ config.

```
#include <agent-proto/objects/config.h>
```

Collaboration diagram for vxg::cloud::agent::ptz_config:



Data Fields

- **std::vector**< ptz_action > [actions](#)
actions: list of strings, list of supported PTZ actions.
- int [maximum_number_of_presets](#)
maximum_number_of_presets: optional int, max number of supported presets when camera supports.
- **std::vector**< [ptz_preset](#) > [presets](#)
presets: optional list of structures [ptz_preset](#)

10.39.1 Detailed Description

PTZ config.

Definition at line 1087 of file config.h.

10.39.2 Field Documentation

10.39.2.1 actions

```
std::vector<ptz_action> vxg::cloud::agent::ptz_config::actions
```

actions: list of strings, list of supported PTZ actions.

Possible values: "left", "right", "top", "bottom", "zoom_in", "zoom_out", "stop". Server sends commands via 3.5 cam_ptz (SRV)

Definition at line 1091 of file config.h.

10.39.2.2 maximum_number_of_presets

```
int vxg::cloud::agent::ptz_config::maximum_number_of_presets
```

maximum_number_of_presets: optional int, max number of supported presets when camera supports.

Zero value, the missed parameter or missed or empty presets list are interpreted by server as "camera doesn't support PTZ"

Definition at line 1097 of file config.h.

10.39.2.3 presets

```
std::vector<ptz_preset> vxg::cloud::agent::ptz_config::presets
```

presets: optional list of structures [ptz_preset](#)

Definition at line 1100 of file config.h.

The documentation for this struct was generated from the following file:


- [config.h](#)

10.40 vxg::cloud::agent::ptz_preset Struct Reference

PTZ preset.

```
#include <agent-proto/objects/config.h>
```

Collaboration diagram for vxg::cloud::agent::ptz_preset:



Data Fields

- **std::string** [token](#)
token: string, an unique token of preset what is used for all operations with preset
- **std::string** [name](#)
name: string, user friendly name of preset
- **ptz_preset_action** [action](#)
actions: list of strings, required preset action.

10.40.1 Detailed Description

PTZ preset.

Definition at line 1069 of file config.h.

10.40.2 Field Documentation

10.40.2.1 action

```
ptz_preset_action vxg::cloud::agent::ptz_preset::action
```

actions: list of strings, required preset action.

Possible values: "create", "delete", "goto", "update"

Definition at line 1078 of file config.h.

10.40.2.2 name

```
std::string vxg::cloud::agent::ptz_preset::name
```

name: string, user friendly name of preset

Definition at line 1074 of file config.h.

10.40.2.3 token

```
std::string vxg::cloud::agent::ptz_preset::token
```

token: string, an unique token of preset what is used for all operations with preset

Definition at line 1072 of file config.h.

The documentation for this struct was generated from the following file:

- [config.h](#)

10.41 vxg::cloud::utils::queued_async_handler< T > Class Template Reference

```
#include <utils/queued-handler.h>
```

Public Types

- using [handler_func](#) = `std::function< void(const T &o)>`

Public Member Functions

- [queued_async_handler](#) ([handler_func](#) cb=nullptr)
- [~queued_async_handler](#) ()
- void [start](#) ()
- void [stop](#) ()
- void [push](#) (T o)
- [handler_func](#) [get_handler](#) ()
- void [set_handler](#) ([handler_func](#) h)

10.41.1 Detailed Description

```
template<class T>
class vxg::cloud::utils::queued_async_handler< T >
```

Definition at line 11 of file queued-handler.h.

10.41.2 Member Typedef Documentation

10.41.2.1 handler_func

```
template<class T >
using vxg::cloud::utils::queued_async_handler< T >::handler_func = std::function<void(const
T& o)>
```

Definition at line 13 of file queued-handler.h.

10.41.3 Constructor & Destructor Documentation

10.41.3.1 queued_async_handler()

```
template<class T >
vxg::cloud::utils::queued_async_handler< T >::queued_async_handler (
    handler_func cb = nullptr ) [inline]
```

Definition at line 23 of file queued-handler.h.

10.41.3.2 ~queued_async_handler()

```
template<class T >
vxg::cloud::utils::queued_async_handler< T >::~~queued_async_handler ( ) [inline]
```

Definition at line 24 of file queued-handler.h.

10.41.4 Member Function Documentation

10.41.4.1 `get_handler()`

```
template<class T >
handler_func vxg::cloud::utils::queued_async_handler< T >::get_handler ( ) [inline]
```

Definition at line 54 of file `queued-handler.h`.

10.41.4.2 `push()`

```
template<class T >
void vxg::cloud::utils::queued_async_handler< T >::push (
    T o ) [inline]
```

Definition at line 48 of file `queued-handler.h`.

10.41.4.3 `set_handler()`

```
template<class T >
void vxg::cloud::utils::queued_async_handler< T >::set_handler (
    handler_func h ) [inline]
```

Definition at line 55 of file `queued-handler.h`.

10.41.4.4 `start()`

```
template<class T >
void vxg::cloud::utils::queued_async_handler< T >::start ( ) [inline]
```

Definition at line 26 of file `queued-handler.h`.

10.41.4.5 `stop()`

```
template<class T >
void vxg::cloud::utils::queued_async_handler< T >::stop ( ) [inline]
```

Definition at line 39 of file `queued-handler.h`.

The documentation for this class was generated from the following file:

- [queued-handler.h](#)

10.42 vxg::media::stream_error::report Struct Reference

Media stream error report simple object.

```
#include <streamer/stream.h>
```

Data Fields

- [origin from](#)
Origin of the error.
- [error code](#)
Error code.

10.42.1 Detailed Description

Media stream error report simple object.

Definition at line 40 of file streamer/stream.h.

10.42.2 Field Documentation

10.42.2.1 code

```
error vxg::media::stream_error::report::code
```

Error code.

Definition at line 44 of file streamer/stream.h.

10.42.2.2 from

```
origin vxg::media::stream_error::report::from
```

Origin of the error.

Definition at line 42 of file streamer/stream.h.

The documentation for this struct was generated from the following file:


- [streamer/stream.h](#)

10.43 vxg::media::rtmp_sink Class Reference


RTMP sink class.

```
#include <streamer/rtmp_sink.h>
```

Inheritance diagram for vxg::media::rtmp_sink:



Collaboration diagram for vxg::media::rtmp_sink:



Public Member Functions

- [rtmp_sink](#) ()
Construct a new rtmp sink object.
- virtual bool [init](#) ([std::string](#) url) override
Overriden [vxg::media::ffmpeg::Sink::init](#)([std::string](#), [std::string](#)) "init" method with hidden output ffmpeg format.
- virtual [std::string](#) [name](#) () override
Sink name.
- virtual bool [droppable](#) () override
If sink of with dropping its media frames.
- bool [negotiate](#) ([std::vector](#)< [Streamer::StreamInfo](#) > streams_info)
Override [negotiate\(\)](#) for removing all data streams.

Additional Inherited Members

10.43.1 Detailed Description

RTMP sink class.

Definition at line 13 of file rtmp_sink.h.

10.43.2 Constructor & Destructor Documentation

10.43.2.1 rtmp_sink()

```
vxg::media::rtmp_sink::rtmp_sink ( ) [inline]
```

Construct a new rtmp sink object.

Definition at line 18 of file rtmp_sink.h.

10.43.3 Member Function Documentation

10.43.3.1 droppable()

```
virtual bool vxg::media::rtmp_sink::droppable ( ) [inline], [override], [virtual]
```

If sink of with dropping its media frames.

Returns

true Internal media thread allowed to drop frames if internal media queue is full.
false No media frames dropping allowed.

Reimplemented from [vxg::media::ffmpeg::Sink](#).

Definition at line 32 of file rtmp_sink.h.

10.43.3.2 init()

```
virtual bool vxg::media::rtmp_sink::init (  
    std::string url ) [inline], [override], [virtual]
```

Overriden [vxg::media::ffmpeg::Sink::init](#)(**std::string**, **std::string**) "init" method with hidden output ffmpeg format.

Parameters

<i>url</i>	RTMP url
------------	----------

Returns

true On success

false On failure

Reimplemented from [vxg::media::ffmpeg::Sink](#).

Definition at line 26 of file rtmp_sink.h.

10.43.3.3 name()

```
virtual std::string vxg::media::rtmp_sink::name ( ) [inline], [override], [virtual]
```

Sink name.

Returns

std::string

Reimplemented from [vxg::media::ffmpeg::Sink](#).

Definition at line 30 of file rtmp_sink.h.

10.43.3.4 negotiate()

```
bool vxg::media::rtmp_sink::negotiate (
    std::vector< Streamer::StreamInfo > streams_info ) [inline], [virtual]
```

Override [negotiate\(\)](#) for removing all data streams.

This is required for preventing buffering inside the ffmpeg muxer, ffmpeg waits for at least one packet for each stream or 10 seconds by default before output next chunk, this leads to 10 seconds delay if data track was added to output muxing context but no actual data packets were received hence sparse streams like onvif metadata may significantly increase delay.

Parameters

<i>in</i>	<i>streams_info</i>	- list of streams descriptions.
-----------	---------------------	---------------------------------

Returns

true
false

Reimplemented from [vxg::media::ffmpeg::Sink](#).

Definition at line 45 of file rtmp_sink.h.

The documentation for this class was generated from the following file:


- [rtmp_sink.h](#)

10.44 vxg::media::rtmp_source Class Reference


RTMP source class.

```
#include <streamer/rtmp_source.h>
```

Inheritance diagram for vxg::media::rtmp_source:



Collaboration diagram for vxg::media::rtmp_source:



Public Member Functions

- virtual bool [init](#) (**std::string** url)
Init source with url.

Additional Inherited Members

10.44.1 Detailed Description

RTMP source class.

Definition at line 13 of file rtmp_source.h.

10.44.2 Member Function Documentation

10.44.2.1 init()

```
virtual bool vxg::media::rtmp_source::init (
    std::string url ) [inline], [virtual]
```

Init source with url.

Parameters

<code>in</code>	<code>url</code>	RTMP url
-----------------	------------------	----------

Returns

true Success

false Failed

Reimplemented from [vsg::media::ffmpeg::Source](#).

Definition at line 24 of file `rtmp_source.h`.

The documentation for this class was generated from the following file:


- [rtmp_source.h](#)

10.45 vsg::media::rtsp_source Class Reference


RTSP source class.

```
#include <streamer/rtsp_source.h>
```

Inheritance diagram for `vsg::media::rtsp_source`:



Collaboration diagram for vxg::media::rtsp_source:



Public Types

- enum [transport](#) {
[UDP](#), [TCP](#), [UDP_MULTICAST](#), [HTTP](#),
[HTTPS](#), [ASYNC_TCP](#) }

Public Member Functions

- [rtsp_source](#) ([transport](#) rtp_transport=[transport::ASYNC_TCP](#), [std::vector](#)< [Streamer::MediaType](#) > media_types={}, [std::map](#)< [std::string](#), [std::string](#) > ffmpeg_opts={}, [std::chrono::seconds](#) time-out= [std::chrono::seconds](#)(0), [std::vector](#)< [Streamer::StreamInfo](#) > in_streams={})
Construct a new rtsp source object.
- virtual bool [init](#) ([std::string](#) url)
Overloaded init method.
- virtual [std::string](#) [name](#) () override
Source class name.

Protected Member Functions

- const char * [__transport_to_ff](#) ([transport](#) t)

Protected Attributes

- [std::map](#)< [std::string](#), [std::string](#) > [ffmpeg_opts_](#)

10.45.1 Detailed Description

RTSP source class.

Definition at line 13 of file rtsp_source.h.

10.45.2 Member Enumeration Documentation

10.45.2.1 transport

```
enum vxg::media::rtsp_source::transport
```

Enumerator

UDP	
TCP	
UDP_MULTICAST	
HTTP	
HTTPS	
ASYNC_TCP	

Definition at line 15 of file rtsp_source.h.

10.45.3 Constructor & Destructor Documentation

10.45.3.1 rtsp_source()

```
vxg::media::rtsp_source::rtsp_source (
    transport rtp_transport = transport::ASYNC_TCP,
    std::vector< Streamer::MediaType > media_types = {},
    std::map< std::string, std::string > ffmpeg_opts = {},
    std::chrono::seconds timeout = std::chrono::seconds(0),
    std::vector< Streamer::StreamInfo > in_streams = {} ) [inline]
```

Construct a new rtsp source object.

Parameters

in	<i>rtp_transport</i>	RTSP transport.
in	<i>media_types</i>	List of media types to ask from RTSP server, can be used to filter out unnecessary tracks. If empty all types will be requested.
in	<i>ffmpeg_opts</i>	Map of ffmpeg options key values pairs.

Parameters

in	<i>timeout</i>	RTSP client io timeout. Doesn't mean the connection will be closed after this timeout but specifies the amount of time ffmpeg spends in io loop spinning, infinite timeout causes spinning forever if connection wasn't closed but no data was received.
in	<i>in_streams</i>	Input streams. Media formats source should use instead of auto-detection, this may decrease source start time and memory usage. Empty array causes avformat_find_stream_info() usage.

Definition at line 74 of file rtsp_source.h.

10.45.4 Member Function Documentation

10.45.4.1 __transport_to_ff()

```
const char* vxg::media::rtsp_source::__transport_to_ff (
    transport t ) [inline], [protected]
```

Definition at line 28 of file rtsp_source.h.

10.45.4.2 init()

```
virtual bool vxg::media::rtsp_source::init (
    std::string url ) [inline], [virtual]
```

Overloaded init method.

Parameters

in	<i>url</i>	RTSP URL link
----	------------	---------------

Returns

true

false

Reimplemented from [vxg::media::ffmpeg::Source](#).

Definition at line 93 of file rtsp_source.h.

10.45.4.3 name()

```
virtual std::string vxg::media::rtsp_source::name ( ) [inline], [override], [virtual]
```

Source class name.

Returns

std::string

Reimplemented from [vxg::media::ffmpeg::Source](#).

Definition at line 185 of file `rtsp_source.h`.

10.45.5 Field Documentation

10.45.5.1 ffmpeg_opts_

```
std::map< std::string, std::string> vxg::media::rtsp_source::ffmpeg_opts_ [protected]
```

Definition at line 26 of file `rtsp_source.h`.

The documentation for this class was generated from the following file:


- [rtsp_source.h](#)

10.46 vxg::cloud::agent::media::rtsp_stream Class Reference


Implementation of the [media::stream](#) with RTSP source and NIY stubs.

```
#include <agent/rtsp-stream.h>
```

Inheritance diagram for `vxg::cloud::agent::media::rtsp_stream`:



Collaboration diagram for `vxg::cloud::agent::media::rtsp_stream`:



Public Types

- typedef `std::shared_ptr< rtsp_stream >` `ptr`

Public Member Functions

- `rtsp_stream` (const `std::string` &source_url, const `std::string` &name, `vxg::media::rtsp_source_ptr` rtsp_src= `std::make_shared< vxg::media::rtsp_source >`(rtsp_source::transport::ASYNC_TCP, `std::vector< vxg::media::Streamer::MediaType >` { `vxg::media::Streamer::VIDEO`, `vxg::media::Streamer::AUDIO`}), bool recorder_needs_source=false)
Construct a new rtsp stream object.
- virtual `~rtsp_stream` ()
- virtual bool `start` (`std::string` not_used="") override

Additional Inherited Members

10.46.1 Detailed Description

Implementation of the `media::stream` with RTSP source and NIY stubs.

Definition at line 17 of file rtsp-stream.h.

10.46.2 Member Typedef Documentation

10.46.2.1 ptr

```
typedef std::shared_ptr<rtsp_stream> vxg::cloud::agent::media::rtsp_stream::ptr
```

Definition at line 29 of file rtsp-stream.h.

10.46.3 Constructor & Destructor Documentation

10.46.3.1 rtsp_stream()

```
vxg::cloud::agent::media::rtsp_stream::rtsp_stream (
    const std::string & source_url,
    const std::string & name,
    vxg::media::rtsp_source_ptr rtsp_src = std::make_shared<vxg::media::rtsp_source>(
        _source::transport::ASYNC_TCP,
        std::vector<vxg::media::Streamer::MediaType> {
            bool recorder_needs_source = false ) [inline]
```

Construct a new rtsp stream object.

Parameters

<i>source_url</i>	RTSP url
<i>name</i>	Unique stream name
<i>rtsp_src</i>	external rtsp_source object pointer
<i>recorder_needs_source</i>	Indicates if stream needs source start before calling start_record() virtual method.

Definition at line 37 of file rtsp-stream.h.

10.46.3.2 ~rtsp_stream()

```
virtual vxg::cloud::agent::media::rtsp_stream::~~rtsp_stream ( ) [inline], [virtual]
```

Definition at line 52 of file rtsp-stream.h.

10.46.4 Member Function Documentation

10.46.4.1 start()

```
virtual bool vxg::cloud::agent::media::rtsp_stream::start (
    std::string not_used = "" ) [inline], [override], [virtual]
```

Reimplemented from [vxg::media::stream](#).

Definition at line 54 of file rtsp-stream.h.


The documentation for this class was generated from the following file:

- [rtsp-stream.h](#)


10.47 vxg::cloud::agent::synchronizer::segmenter Struct Reference

```
#include <agent/timeline-synchronizer.h>
```

Inheritance diagram for vxg::cloud::agent::synchronizer::segmenter:



Collaboration diagram for vxg::cloud::agent::synchronizer::segmenter:



Public Types

- typedef `std::shared_ptr< segmenter >` `ptr`

Public Member Functions

- virtual `~segmenter ()`
- bool `operator< (const segmenter &r)`
- bool `intersects (const segmenter &r)`

Data Fields

- `cloud::time cur_seg_start`
- `cloud::time cur_seg_stop`
- `cloud::time last_processed_time`
- `cloud::duration step`
- `cloud::duration delay`
- `std::atomic< bool > processed`
Processing finished, doesn't mean upload of all processed chunks is finished.
- `std::atomic< bool > canceled`
Canceled.
- `std::atomic< bool > finished`
Upload of all processed chunks finished, no matter what was result of the chunk upload attempt.
- `std::atomic< bool > realtime`
Realtime delay between chunks processing.
- `std::string ticket`
- `size_t chunks_planned`
- `size_t chunks_done`
- `size_t chunks_failed`
- `sync_status_report_cb sync_status_cb`
- `bool final_sync_status_reported`

10.47.1 Detailed Description

Definition at line 32 of file timeline-synchronizer.h.

10.47.2 Member Typedef Documentation

10.47.2.1 ptr

```
typedef std::shared_ptr<segmenter> vxg::cloud::agent::synchronizer::segmenter::ptr
```

Definition at line 72 of file timeline-synchronizer.h.

10.47.3 Constructor & Destructor Documentation

10.47.3.1 ~segmenter()

```
virtual vxg::cloud::agent::synchronizer::segmenter::~~segmenter ( ) [inline], [virtual]
```

Definition at line 55 of file timeline-synchronizer.h.

10.47.4 Member Function Documentation

10.47.4.1 intersects()

```
bool vxg::cloud::agent::synchronizer::segmenter::intersects (
    const segmenter & r ) [inline]
```

Definition at line 61 of file timeline-synchronizer.h.

10.47.4.2 operator<()

```
bool vxg::cloud::agent::synchronizer::segmenter::operator< (
    const segmenter & r ) [inline]
```

Definition at line 57 of file timeline-synchronizer.h.

10.47.5 Field Documentation

10.47.5.1 canceled

```
std::atomic<bool> vxg::cloud::agent::synchronizer::segmenter::canceled
```

Canceled.

Definition at line 42 of file timeline-synchronizer.h.

10.47.5.2 chunks_done

```
size_t vxg::cloud::agent::synchronizer::segmenter::chunks_done
```

Definition at line 50 of file timeline-synchronizer.h.

10.47.5.3 chunks_failed

```
size_t vxg::cloud::agent::synchronizer::segmenter::chunks_failed
```

Definition at line 51 of file timeline-synchronizer.h.

10.47.5.4 chunks_planned

```
size_t vxg::cloud::agent::synchronizer::segmenter::chunks_planned
```

Definition at line 49 of file timeline-synchronizer.h.

10.47.5.5 cur_seg_start

```
cloud::time vxg::cloud::agent::synchronizer::segmenter::cur_seg_start
```

Definition at line 33 of file timeline-synchronizer.h.

10.47.5.6 cur_seg_stop

```
cloud::time vxg::cloud::agent::synchronizer::segmenter::cur_seg_stop
```

Definition at line 34 of file timeline-synchronizer.h.

10.47.5.7 delay

```
cloud::duration vxg::cloud::agent::synchronizer::segmenter::delay
```

Definition at line 37 of file timeline-synchronizer.h.

10.47.5.8 final_sync_status_reported

```
bool vxg::cloud::agent::synchronizer::segmenter::final_sync_status_reported
```

Definition at line 53 of file timeline-synchronizer.h.

10.47.5.9 finished

```
std::atomic<bool> vxg::cloud::agent::synchronizer::segmenter::finished
```

Upload of all processed chunks finished, no matter what was result of the chunk upload attempt.

Definition at line 45 of file timeline-synchronizer.h.

10.47.5.10 last_processed_time

`cloud::time vxg::cloud::agent::synchronizer::segmenter::last_processed_time`

Definition at line 35 of file timeline-synchronizer.h.

10.47.5.11 processed

`std::atomic<bool> vxg::cloud::agent::synchronizer::segmenter::processed`

Processing finished, doesn't mean upload of all processed chunks is finished.

Definition at line 40 of file timeline-synchronizer.h.

10.47.5.12 realtime

`std::atomic<bool> vxg::cloud::agent::synchronizer::segmenter::realtime`

Realtime delay between chunks processing.

Definition at line 47 of file timeline-synchronizer.h.

10.47.5.13 step

`cloud::duration vxg::cloud::agent::synchronizer::segmenter::step`

Definition at line 36 of file timeline-synchronizer.h.

10.47.5.14 sync_status_cb

`sync_status_report_cb vxg::cloud::agent::synchronizer::segmenter::sync_status_cb`

Definition at line 52 of file timeline-synchronizer.h.

10.47.5.15 ticket

`std::string vxg::cloud::agent::synchronizer::segmenter::ticket`

Definition at line 48 of file timeline-synchronizer.h.

The documentation for this struct was generated from the following file:


- [timeline-synchronizer.h](#)

10.48 vxg::media::ffmpeg::Sink Class Reference


Base ffmpeg sink class.

```
#include <streamer/ffmpeg_sink.h>
```

Inheritance diagram for vxg::media::ffmpeg::Sink:



Collaboration diagram for vxg::media::ffmpeg::Sink:



Public Member Functions

- [Sink](#) ()
- virtual [~Sink](#) ()
- bool [init](#) ([std::string](#) url, [std::string](#) fmt, [std::shared_ptr](#)< [std::vector](#)< [uint8_t](#) >> data_buffer=nullptr)
Sink init.
- virtual bool [init](#) ([std::string](#) url="")
Init sink.
- virtual bool [finit](#) ()
Deinit sink.
- virtual void [stop](#) ()
- virtual void [error](#) ([Streamer::StreamError](#) stream_error)
Media processing error callback, called when ISink::process returned false or linked source's ISource::pullFrame returned false, or when ISource::error was called.
- virtual [std::string](#) [name](#) ()
Sink name.
- virtual bool [droppable](#) ()
If sink of with dropping its media frames.
- virtual bool [negotiate](#) ([std::vector](#)< [Streamer::StreamInfo](#) >)
Negotiation callback, this method called with collected from the ISource::negotiate media stream description.
- virtual [cloud::duration](#) [duration](#) ()
Processed stream duration.

Additional Inherited Members

10.48.1 Detailed Description

Base ffmpeg sink class.

Definition at line 12 of file ffmpeg_sink.h.

10.48.2 Constructor & Destructor Documentation

10.48.2.1 Sink()

```
vxg::media::ffmpeg::Sink::Sink ( )
```

10.48.2.2 ~Sink()

```
virtual vxg::media::ffmpeg::Sink::~Sink ( ) [virtual]
```

10.48.3 Member Function Documentation

10.48.3.1 droppable()

```
virtual bool vxg::media::ffmpeg::Sink::droppable ( ) [inline], [virtual]
```

If sink of with dropping its media frames.

Returns

true Internal media thread allowed to drop frames if internal media queue is full.

false No media frames dropping allowed.

Implements [vxg::media::Streamer::ISink](#).

Reimplemented in [vxg::media::rtmp_sink](#).

Definition at line 57 of file `ffmpeg_sink.h`.

10.48.3.2 duration()

```
virtual cloud::duration vxg::media::ffmpeg::Sink::duration ( ) [inline], [virtual]
```

Processed stream duration.

Returns

`duration`

Reimplemented from [vxg::media::Streamer::ISink](#).

Definition at line 59 of file `ffmpeg_sink.h`.

10.48.3.3 error()

```
virtual void vxg::media::ffmpeg::Sink::error (
    Streamer::StreamError error ) [inline], [virtual]
```

Media processing error callback, called when `ISink::process` returned false or linked source's `ISource::pullFrame` returned false, or when `ISource::error` was called.

Method may be overridden, default implementation calls `on_error_cb` that was provided by user with [set_error_cb\(\)](#).

Parameters

<i>error</i>	Error type.
--------------	-------------

Reimplemented from [vxg::media::Streamer::ISink](#).

Definition at line 33 of file `ffmpeg_sink.h`.

10.48.3.4 finit()

```
virtual bool vxg::media::ffmpeg::Sink::finit ( ) [virtual]
```

Deinit sink.

Returns

true finit success.

false finit failed.

Implements [vxg::media::Streamer::ISink](#).

10.48.3.5 init() [1/2]

```
bool vxg::media::ffmpeg::Sink::init (
    std::string url,
    std::string fmt,
    std::shared_ptr< std::vector< uint8_t >> data_buffer = nullptr )
```

[Sink](#) init.

Parameters

<i>url</i>	Output url
<i>fmt</i>	Output format
<i>data_buffer</i>	Output buffer for output to memory, if specified and not nullptr the <code>url</code> will be ignored.

Returns

true On success

false On failure

10.48.3.6 init() [2/2]

```
virtual bool vxg::media::ffmpeg::Sink::init (
    std::string url = "" ) [virtual]
```

Init sink.

Parameters

<i>in</i>	<i>url</i>	Url if needed.
-----------	------------	----------------

Returns

true init success.
false init failed.

Implements [vxg::media::Streamer::ISink](#).

Reimplemented in [vxg::media::rtmp_sink](#).

10.48.3.7 name()

```
virtual std::string vxg::media::ffmpeg::Sink::name ( ) [inline], [virtual]
```

[Sink](#) name.

Returns

std::string

Implements [vxg::media::Streamer::ISink](#).

Reimplemented in [vxg::media::rtmp_sink](#).

Definition at line 55 of file `ffmpeg_sink.h`.

10.48.3.8 negotiate()

```
virtual bool vxg::media::ffmpeg::Sink::negotiate (
    std::vector< Streamer::StreamInfo > info ) [virtual]
```

Negotiation callback, this method called with collected from the `ISource::negotiate` media stream description.

Parameters

<i>info</i>	List of elementary streams descriptions.
-------------	--

Returns

true If streams descriptions accepted.
false Streams not accepted, will cause media thread stopping.

Reimplemented from [vxg::media::Streamer::ISink](#).

Reimplemented in [vxg::media::rtmp_sink](#).

10.48.3.9 stop()

```
virtual void vxg::media::ffmpeg::Sink::stop ( ) [virtual]
```

Reimplemented from [vxg::media::Streamer::ISink](#).

The documentation for this class was generated from the following file:


- [ffmpeg_sink.h](#)

10.49 vxg::media::ffmpeg::Source Class Reference


Base ffmpeg source class.

```
#include <streamer/ffmpeg_source.h>
```

Inheritance diagram for vxg::media::ffmpeg::Source:



Collaboration diagram for vxg::media::ffmpeg::Source:



Public Member Functions

- **Source** (**std::vector**< **Streamer::StreamInfo** > suggested_input_streams={})
- virtual **~Source** ()
- bool **init** (**std::string** url, AVDictionary *opts, **std::string** fmt="")
Init ffmpeg source with specific ffmpeg options.
- bool **init** (**std::shared_ptr**< **std::vector**< uint8_t >> input_buffer, AVDictionary *opts, **std::string** fmt)
Init ffmpeg memory source with specific ffmpeg options.
- virtual bool **init** (**std::string** url="")
Init source.
- virtual void **finit** ()
Finit souce.
- virtual **std::shared_ptr**< **Streamer::MediaFrame** > **pullFrame** ()
Main method of the Mode::PULL mode data producing.
- virtual **std::string** **name** ()
Source class name.
- virtual **std::vector**< **Streamer::StreamInfo** > **negotiate** ()
Negotiation callback.
- virtual void **stop** ()

Additional Inherited Members

10.49.1 Detailed Description

Base ffmpeg source class.

Definition at line 10 of file ffmpeg_source.h.

10.49.2 Constructor & Destructor Documentation

10.49.2.1 Source()

```
vxg::media::ffmpeg::Source::Source (
    std::vector< Streamer::StreamInfo > suggested_input_streams = {} )
```

Definition at line 9 of file ffmpeg_source.cc.

10.49.2.2 ~Source()

```
vxg::media::ffmpeg::Source::~Source ( ) [virtual]
```

Definition at line 14 of file ffmpeg_source.cc.

10.49.3 Member Function Documentation

10.49.3.1 finit()

```
void vxg::media::ffmpeg::Source::finit ( ) [virtual]
```

Finit souce.

Implements [vxg::media::Streamer::ISource](#).

Definition at line 32 of file ffmpeg_source.cc.

10.49.3.2 init() [1/3]

```
bool vxg::media::ffmpeg::Source::init (
    std::shared_ptr< std::vector< uint8_t >> input_buffer,
    AVDictionary * opts,
    std::string fmt )
```

Init ffmpeg memory source with specific ffmpeg options.

Parameters

in	<i>input_buffer</i>	Input memory buffer containing whole media.
in	<i>opts</i>	ffmpeg options
in	<i>fmt</i>	ffmpeg input format to prevent auto-detection. ex.: "flv", "mp4", "http" etc.

Returns

true
false

Definition at line 22 of file ffmpeg_source.cc.

10.49.3.3 init() [2/3]

```
bool vxg::media::ffmpeg::Source::init (
    std::string url,
    AVDictionary * opts,
    std::string fmt = "" )
```

Init ffmpeg source with specific ffmpeg options.

Parameters

in	<i>url</i>	Url
in	<i>opts</i>	ffmpeg options
in	<i>fmt</i>	ffmpeg input format to prevent auto-detection. ex.: "flv", "rtsp", "http" etc.

Returns

true
false

Definition at line 16 of file ffmpeg_source.cc.

10.49.3.4 init() [3/3]

```
bool vxg::media::ffmpeg::Source::init (
    std::string url = "" ) [virtual]
```

Init source.

Parameters

<i>url</i>	Url if needed.
------------	----------------

Returns

true Init success.
false Init failed.

Implements [vxg::media::Streamer::ISource](#).

Reimplemented in [vxg::media::rtsp_source](#), and [vxg::media::rtmp_source](#).

Definition at line 28 of file `ffmpeg_source.cc`.

10.49.3.5 name()

```
virtual std::string vxg::media::ffmpeg::Source::name ( ) [inline], [virtual]
```

[Source](#) class name.

Returns

std::string

Implements [vxg::media::Streamer::ISource](#).

Reimplemented in [vxg::media::rtsp_source](#).

Definition at line 42 of file `ffmpeg_source.h`.

10.49.3.6 negotiate()

```
std::vector< Streamer::StreamInfo > vxg::media::ffmpeg::Source::negotiate ( ) [virtual]
```

Negotiation callback.

Called by internals. Class implementation should return the list of the streams info source will be producing for the sinks, this list will be then passed to the `ISink::negotiate` method.

Returns

std::vector<[Streamer::StreamInfo](#)>

Implements [vxg::media::Streamer::ISource](#).

Definition at line 36 of file `ffmpeg_source.cc`.

10.49.3.7 pullFrame()

```
std::shared_ptr< Streamer::MediaFrame > vxg::media::ffmpeg::Source::pullFrame ( ) [virtual]
```

Main method of the `Mode::PULL` mode data producing.

Called by internals if the source operation mode is `Mode::PULL`. Implementation should return media frame object with correctly filled fields.

Returns

std::shared_ptr<[MediaFrame](#)>

Implements [vxg::media::Streamer::ISource](#).

Definition at line 95 of file `ffmpeg_source.cc`.

10.49.3.8 stop()

```
void vxg::media::ffmpeg::Source::stop ( ) [virtual]
```

Reimplemented from [vxg::media::Streamer::ISource](#).

Definition at line 191 of file `ffmpeg_source.cc`.

The documentation for this class was generated from the following files:


- [ffmpeg_source.h](#)
- [ffmpeg_source.cc](#)

10.50 vxg::media::stream Class Reference


base media stream abstract class

```
#include <streamer/stream.h>
```

Inheritance diagram for vxg::media::stream:



Collaboration diagram for vxg::media::stream:



Public Types

- using `on_error_cb` = `std::function< void(const stream_error::report &error)>`
- typedef `std::shared_ptr< stream > ptr`
std::shared_ptr to the base::stream

Public Member Functions

- `stream (std::string name, Streamer::ISource::ptr source, Streamer::ISink::ptr sink)`
Construct a new base stream object.
- virtual `~stream ()`
- virtual bool `init_source (std::string url)`
Initialize the source.
- virtual void `finit_source ()`
Deinitialize source.
- virtual bool `init_sink (std::string uri)`
Init media sink.
- virtual void `finit_sink ()`
Deinitialize sink.
- virtual void `set_on_error_cb (on_error_cb e_cb)`
Set the on_error callback.

Protected Attributes

- `Streamer::ISource::ptr source_`
media source
- `Streamer::ISink::ptr sink_`
media sink

10.50.1 Detailed Description

base media stream abstract class

Media stream is the class representing media stream retranslation from the media source derived from the [Streamer::ISource](#) to the media sink derived from the [Streamer::ISink](#). For instance, media stream could be a pair of RTSP source and RTMP sink, i.e. such media stream will be a retranslator of the RTSP stream to the RTMP

Definition at line 56 of file streamer/stream.h.

10.50.2 Member Typedef Documentation

10.50.2.1 on_error_cb

```
using vxg::media::stream::on_error_cb = std::function<void(const stream_error::report& error)>
```

Definition at line 73 of file streamer/stream.h.

10.50.2.2 ptr

```
typedef std::shared_ptr<stream> vxg::media::stream::ptr
```

std::shared_ptr to the base_stream

Definition at line 77 of file streamer/stream.h.

10.50.3 Constructor & Destructor Documentation

10.50.3.1 stream()

```
vxg::media::stream::stream (
    std::string name,
    Streamer::ISource::ptr source,
    Streamer::ISink::ptr sink ) [inline]
```

Construct a new base stream object.

Parameters

<i>name</i>	Unique stream name which will be used by the VXG Cloud API
<i>source</i>	Source object pointer
<i>sink</i>	Sink object pointer

Definition at line 84 of file streamer/stream.h.

10.50.3.2 ~stream()

```
virtual vxg::media::stream::~~stream ( ) [inline], [virtual]
```

Reimplemented in [vxg::cloud::agent::media::stream](#).

Definition at line 104 of file streamer/stream.h.

10.50.4 Member Function Documentation

10.50.4.1 finit_sink()

```
virtual void vxg::media::stream::finit_sink ( ) [inline], [virtual]
```

Deinitialize sink.

Derived class deinitialize and deallocates base_stream::sink_

Definition at line 158 of file streamer/stream.h.

10.50.4.2 finit_source()

```
virtual void vxg::media::stream::finit_source ( ) [inline], [virtual]
```

Deinitialize source.

Definition at line 128 of file streamer/stream.h.

10.50.4.3 init_sink()

```
virtual bool vxg::media::stream::init_sink (
    std::string uri ) [inline], [virtual]
```

Init media sink.

Derived class should allocate and initialize base_stream::sink_ with RTMP sink publishing media stream to the RTMP server pointed by the uri

Parameters

<i>in</i>	<i>uri</i>	sink stream url if needed
-----------	------------	---------------------------

Returns

true Sink started
false Sink start failed

Definition at line 143 of file streamer/stream.h.

10.50.4.4 init_source()

```
virtual bool vxg::media::stream::init_source (  
    std::string url ) [inline], [virtual]
```

Initialize the source.

Called by the internal code, derived class should allocate and set base_stream::source_ with [Streamer::ISink](#) derived object pointer.

Parameters

<i>url</i>	source url
------------	------------

Returns

true if successfully initialized source
false if source initialization failed

Definition at line 115 of file streamer/stream.h.

10.50.4.5 set_on_error_cb()

```
virtual void vxg::media::stream::set_on_error_cb (  
    on\_error\_cb e_cb ) [inline], [virtual]
```

Set the on_error callback.

Parameters

<i>e_cb</i>	Callback
-------------	----------

Definition at line 264 of file streamer/stream.h.

10.50.5 Field Documentation

10.50.5.1 sink_

`Streamer::ISink::ptr vxg::media::stream::sink_ [protected]`

media sink

Definition at line 273 of file streamer/stream.h.

10.50.5.2 source_

`Streamer::ISource::ptr vxg::media::stream::source_ [protected]`

media source

Definition at line 271 of file streamer/stream.h.

The documentation for this class was generated from the following file:


- [streamer/stream.h](#)

10.51 vxg::cloud::agent::media::stream Class Reference


Cloud agent media stream abstract class.

```
#include <agent/stream.h>
```

Inheritance diagram for vxg::cloud::agent::media::stream:



Collaboration diagram for vxg::cloud::agent::media::stream:



Public Types

- typedef **std::shared_ptr**< [stream](#) > [ptr](#)
std::shared_ptr to the base_stream

Public Member Functions

- [stream](#) (**std::string** name, [vxg::media::Streamer::ISource::ptr](#) source, bool recorder_needs_source=false, [vxg::media::Streamer::ISink::ptr](#) sink= **std::make_shared**< [vxg::media::rtmp_sink](#) >())
Construct a new agent media stream object.
- virtual [~stream](#) ()

Additional Inherited Members

10.51.1 Detailed Description

Cloud agent media stream abstract class.

[vxg::media::stream](#) derived class with VXG Cloud proto callbacks

Definition at line 214 of file agent/stream.h.

10.51.2 Member Typedef Documentation

10.51.2.1 ptr

```
typedef std::shared_ptr<stream> vxg::cloud::agent::media::stream::ptr
```

std::shared_ptr to the base_stream

Definition at line 217 of file agent/stream.h.

10.51.3 Constructor & Destructor Documentation

10.51.3.1 stream()

```
vxg::cloud::agent::media::stream::stream (
    std::string name,
    vxg::media::Streamer::ISource::ptr source,
    bool recorder_needs_source = false,
    vxg::media::Streamer::ISink::ptr sink = std::make_shared<vxg::media::rtmp\_sink> ()
) [inline]
```

Construct a new agent media stream object.

Parameters

in	<i>name</i>	Unique stream name which will be used by the VXG Cloud API
in	<i>source</i>	Source object pointer
in	<i>recorder_needs_source</i>	Indicates if stream needs source start before calling start_record() virtual method.
in	<i>sink</i>	Sink object pointer, rtmp_sink as default

Definition at line 227 of file agent/stream.h.

10.51.3.2 ~stream()

```
virtual vxg::cloud::agent::media::stream::~~stream ( ) [inline], [virtual]
```

Reimplemented from [vxg::media::stream](#).

Definition at line 234 of file agent/stream.h.

The documentation for this class was generated from the following file:


- [agent/stream.h](#)

10.52 vxg::cloud::agent::media::stream_callbacks Class Reference

Cloud agent media stream callbacks abstract class.

```
#include <agent/stream.h>
```

Inheritance diagram for vxg::cloud::agent::media::stream_callbacks:



Public Member Functions

- [stream_callbacks](#) (bool recorder_needs_source)
Construct a new stream callbacks object.
- virtual [~stream_callbacks](#) ()
- virtual bool [get_stream_caps](#) (cloud::agent::proto::stream_caps &caps)=0
Get the media stream caps.
- virtual bool [get_supported_stream](#) (cloud::agent::proto::supported_stream_config &supported_stream)=0
Get the supported stream description.
- virtual bool [get_stream_config](#) (cloud::agent::proto::stream_config &config)=0
Get the stream config.
- virtual bool [set_stream_config](#) (const cloud::agent::proto::stream_config &config)=0
Set the streams config.
- virtual bool [get_snapshot](#) (cloud::agent::proto::event_object::snapshot_info_object &snapshot)=0
Get the snapshot image of this media stream.
- virtual bool [record_needs_source](#) ()
Should returns true if [agent::manager](#) should start stream source before calling [start_record\(\)](#)
- virtual bool [start_record](#) ()=0
Start recording of this media stream.
- virtual void [stop_record](#) ()=0
Stop recording of this stream.
- virtual **std::vector**< [cloud::agent::proto::video_clip_info](#) > [record_get_list](#) (cloud::time begin, cloud::time end, bool align=true)=0
Get list of the recorded clips for specific time period.
- virtual [cloud::agent::proto::video_clip_info](#) [record_export](#) (cloud::time begin, cloud::time end)=0
Export recorded clip for specified time.

10.52.1 Detailed Description

Cloud agent media stream callbacks abstract class.

VXG Cloud proto callbacks related to media stream

Definition at line 19 of file agent/stream.h.

10.52.2 Constructor & Destructor Documentation

10.52.2.1 stream_callbacks()

```
vxg::cloud::agent::media::stream_callbacks::stream_callbacks (
    bool recorder_needs_source ) [inline]
```

Construct a new stream callbacks object.

Parameters

<i>recorder_needs_source</i>	Indicates if stream needs source start
------------------------------	--

Definition at line 29 of file agent/stream.h.

10.52.2.2 ~stream_callbacks()

```
virtual vxg::cloud::agent::media::stream_callbacks::~~stream_callbacks ( ) [inline], [virtual]
```

Definition at line 31 of file agent/stream.h.

10.52.3 Member Function Documentation

10.52.3.1 get_snapshot()

```
virtual bool vxg::cloud::agent::media::stream_callbacks::get_snapshot (
    cloud::agent::proto::event_object::snapshot_info_object & snapshot ) [pure virtual]
```

Get the snapshot image of this media stream.

Parameters

out	<i>snapshot</i>	snapshot object
-----	-----------------	-----------------

Returns

true if snapshot is valid
false if snapshot is invalid

10.52.3.2 get_stream_caps()

```
virtual bool vxg::cloud::agent::media::stream_callbacks::get_stream_caps (
    cloud::agent::proto::stream_caps & caps ) [pure virtual]
```

Get the media stream caps.

video/audio elementary streams caps request passes caps with names of the elementary streams for which caps are required to be filled inside this method

Parameters

out	<i>caps</i>	
-----	-------------	--

Returns

true if `caps` valid
false if `caps` is invalid

Implemented in [vxd::cloud::agent::media::stream_callbacks_stub](#).

10.52.3.3 get_stream_config()

```
virtual bool vxd::cloud::agent::media::stream_callbacks::get_stream_config (
    vxd::cloud::agent::proto::stream_config & config ) [pure virtual]
```

Get the stream config.

Parameters

<code>in, out</code>	<code>config</code>	input config contains list of streams for which configuration should be returned
----------------------	---------------------	--

Returns

true if `config` is valid
false if `config` is invalid

Implemented in [vxd::cloud::agent::media::stream_callbacks_stub](#).

10.52.3.4 get_supported_stream()

```
virtual bool vxd::cloud::agent::media::stream_callbacks::get_supported_stream (
    vxd::cloud::agent::proto::supported_stream_config & supported_stream ) [pure virtual]
```

Get the supported stream description.

Parameters

<code>out</code>	<code>supported_stream</code>	Stream supported by device
------------------	-------------------------------	----------------------------

Returns

true if `supported_stream` is valid
false if `supported_stream` is not valid

10.52.3.5 record_export()

```
virtual cloud::agent::proto::video_clip_info vxg::cloud::agent::media::stream_callbacks←
::record_export (
    cloud::time begin,
    cloud::time end ) [pure virtual]
```

Export recorded clip for specified time.

Parameters

<i>begin</i>	
<i>end</i>	

Returns

proto::video_clip_info

Implemented in [vxg::cloud::agent::media::stream_callbacks_stub](#).

10.52.3.6 record_get_list()

```
virtual std::vector<cloud::agent::proto::video_clip_info> vxg::cloud::agent::media::stream←
callbacks::record_get_list (
    cloud::time begin,
    cloud::time end,
    bool align = true ) [pure virtual]
```

Get list of the recorded clips for specific time period.

Parameters

in	<i>begin</i>	beginning of the time period
in	<i>end</i>	ending of the time period
in	<i>align</i>	Align returned records to key frames and begin/end. If true the implementation should align returned records to not include data with timestamps less than <i>begin</i> and greater than <i>end</i> . Also any returned record MUST start with key frame and the last frame of any not last record in the list MUST be the frame prior to key frame - first frame of the next record.
in	<i>limit</i>	Max records number that may be returned. Value 0 means no limitation.

Returns

std::vector<proto::video_clip_info>

Implemented in [vxg::cloud::agent::media::stream_callbacks_stub](#).

10.52.3.7 record_needs_source()

```
virtual bool vxg::cloud::agent::media::stream_callbacks::record_needs_source ( ) [inline],
[virtual]
```

Should returns true if [agent::manager](#) should start stream source before calling [start_record\(\)](#)

Returns

true [agent::manager](#) should start stream source
false [agent::manager](#) may not start stream source

Definition at line 86 of file agent/stream.h.

10.52.3.8 set_stream_config()

```
virtual bool vxg::cloud::agent::media::stream_callbacks::set_stream_config (
    const cloud::agent::proto::stream\_config & config ) [pure virtual]
```

Set the streams config.

Parameters

in	<i>config</i>	input config contains list of streams for which configuration should be set
----	---------------	---

Returns

true if config successfully set
false if config failed to set

Implemented in [vxg::cloud::agent::media::stream_callbacks_stub](#).

10.52.3.9 start_record()

```
virtual bool vxg::cloud::agent::media::stream_callbacks::start_record ( ) [pure virtual]
```

Start recording of this media stream.

Called only if memory card is presented and can be used.

Returns

true if recording started
false if recording start failed

See also

[agent::event_stream::on_get_memorycard_info](#)

Implemented in [vxg::cloud::agent::media::stream_callbacks_stub](#).

10.52.3.10 stop_record()

```
virtual void vxg::cloud::agent::media::stream_callbacks::stop_record ( ) [pure virtual]
```

Stop recording of this stream.

Implemented in [vxg::cloud::agent::media::stream_callbacks_stub](#).


The documentation for this class was generated from the following file:

- [agent/stream.h](#)


10.53 vxg::cloud::agent::media::stream_callbacks_stub Class Reference

```
#include <agent/stream.h>
```

Inheritance diagram for vxg::cloud::agent::media::stream_callbacks_stub:



Collaboration diagram for vxg::cloud::agent::media::stream_callbacks_stub:



Public Member Functions

- `stream_callbacks_stub` (`std::string` name, bool `record_needs_source`)
Construct a new stream callbacks stub object.
- virtual `~stream_callbacks_stub` ()
- bool `get_supported_stream` (`proto::supported_stream_config` &config) override
- virtual bool `get_stream_caps` (`proto::stream_caps` &caps) override
Get the media stream caps.
- virtual bool `get_stream_config` (`proto::stream_config` &streamConfig) override
Get the stream config.
- virtual bool `set_stream_config` (const `proto::stream_config` &streamConfig) override
Set the streams config.
- virtual bool `get_snapshot` (`proto::event_object::snapshot_info_object` &snapshot) override
- virtual `std::vector< proto::video_clip_info >` `record_get_list` (`cloud::time` begin, `cloud::time` end, bool align) override
Get list of the recorded clips for specific time period.
- virtual `proto::video_clip_info` `record_export` (`cloud::time` begin, `cloud::time` end) override
Export recorded clip for specified time.
- virtual bool `start_record` () override
Start recording of this media stream.
- virtual void `stop_record` () override
Stop recording of this stream.

10.53.1 Detailed Description

Definition at line 128 of file `agent/stream.h`.

10.53.2 Constructor & Destructor Documentation

10.53.2.1 stream_callbacks_stub()

```
vxg::cloud::agent::media::stream_callbacks_stub::stream_callbacks_stub (
    std::string name,
    bool record_needs_source ) [inline]
```

Construct a new stream callbacks stub object.

Parameters

<i>name</i>	Stream name used for get_supported_stream() stub
<i>record_needs_source</i>	

Definition at line 142 of file agent/stream.h.

10.53.2.2 ~stream_callbacks_stub()

```
virtual vxg::cloud::agent::media::stream_callbacks_stub::~~stream_callbacks_stub ( ) [inline],
[virtual]
```

Definition at line 144 of file agent/stream.h.

10.53.3 Member Function Documentation

10.53.3.1 get_snapshot()

```
virtual bool vxg::cloud::agent::media::stream_callbacks_stub::get_snapshot (
    proto::event_object::snapshot_info_object & snapshot ) [inline], [override],
[virtual]
```

Definition at line 177 of file agent/stream.h.

10.53.3.2 get_stream_caps()

```
virtual bool vxg::cloud::agent::media::stream_callbacks_stub::get_stream_caps (
    proto::stream_caps & caps ) [inline], [override], [virtual]
```

Get the media stream caps.

video/audio elementary streams caps request passes caps with names of the elementary streams for which caps are required to be filled inside this method

Parameters

out	<i>caps</i>	
-----	-------------	--

Returns

true if *caps* valid

false if *caps* is invalid

Implements [vxg::cloud::agent::media::stream_callbacks](#).

Definition at line 157 of file agent/stream.h.

10.53.3.3 get_stream_config()

```
virtual bool vxg::cloud::agent::media::stream_callbacks_stub::get_stream_config (
    proto::stream_config & config ) [inline], [override], [virtual]
```

Get the stream config.

Parameters

in, out	<i>config</i>	input <i>config</i> contains list of streams for which configuration should be returned
---------	---------------	---

Returns

true if *config* is valid

false if *config* is invalid

Implements [vxg::cloud::agent::media::stream_callbacks](#).

Definition at line 163 of file agent/stream.h.

10.53.3.4 get_supported_stream()

```
bool vxg::cloud::agent::media::stream_callbacks_stub::get_supported_stream (
    proto::supported_stream_config & config ) [inline], [override]
```

Definition at line 146 of file agent/stream.h.

10.53.3.5 record_export()

```
virtual proto::video_clip_info vxg::cloud::agent::media::stream_callbacks_stub::record_export
(
    cloud::time begin,
    cloud::time end ) [inline], [override], [virtual]
```

Export recorded clip for specified time.

Parameters

<i>begin</i>	
<i>end</i>	

Returns

[proto::video_clip_info](#)

Implements [vxg::cloud::agent::media::stream_callbacks](#).

Definition at line 192 of file agent/stream.h.

10.53.3.6 record_get_list()

```
virtual std::vector<proto::video\_clip\_info> vxg::cloud::agent::media::stream_callbacks_stub↵
::record_get_list (
    cloud::time begin,
    cloud::time end,
    bool align ) [inline], [override], [virtual]
```

Get list of the recorded clips for specific time period.

Parameters

in	<i>begin</i>	beginning of the time period
in	<i>end</i>	ending of the time period
in	<i>align</i>	Align returned records to key frames and begin/end. If true the implementation should align returned records to not include data with timestamps less than <i>begin</i> and greater than <i>end</i> . Also any returned record MUST start with key frame and the last frame of any not last record in the list MUST be the frame prior to key frame - first frame of the next record.
in	<i>limit</i>	Max records number that may be returned. Value 0 means no limitation.

Returns

`std::vector<proto::video_clip_info>`

Implements [vxg::cloud::agent::media::stream_callbacks](#).

Definition at line 185 of file agent/stream.h.

10.53.3.7 set_stream_config()

```
virtual bool vxg::cloud::agent::media::stream_callbacks_stub::set_stream_config (
    const proto::stream\_config & config ) [inline], [override], [virtual]
```

Set the streams config.

Parameters

<code>in</code>	<code>config</code>	input <code>config</code> contains list of streams for which configuration should be set
-----------------	---------------------	--

Returns

`true` if `config` successfully set
`false` if `config` failed to set

Implements [vxg::cloud::agent::media::stream_callbacks](#).

Definition at line 170 of file `agent/stream.h`.

10.53.3.8 start_record()

```
virtual bool vxg::cloud::agent::media::stream_callbacks_stub::start_record ( ) [inline],
[override], [virtual]
```

Start recording of this media stream.

Called only if memory card is presented and can be used.

Returns

`true` if recording started
`false` if recording start failed

See also

`agent::event_stream::on_get_memorycard_info`

Implements [vxg::cloud::agent::media::stream_callbacks](#).

Definition at line 200 of file `agent/stream.h`.

10.53.3.9 stop_record()

```
virtual void vxg::cloud::agent::media::stream_callbacks_stub::stop_record ( ) [inline], [override],
[virtual]
```

Stop recording of this stream.

Implements [vxg::cloud::agent::media::stream_callbacks](#).

Definition at line 206 of file `agent/stream.h`.

The documentation for this class was generated from the following file:


- [agent/stream.h](#)

10.54 vxg::cloud::agent::proto::stream_caps Struct Reference

Media stream capabilities.

```
#include <agent-proto/objects/caps.h>
```

Collaboration diagram for vxg::cloud::agent::proto::stream_caps:



Data Structures

- struct [caps_audio_object](#)
Audio streams capabilities.
- struct [caps_video_object](#)
Video streams capabilities.

Data Fields

- **std::vector**< [caps_video_object](#) > [caps_video](#)
List of video streams capabilities.
- **std::vector**< [caps_audio_object](#) > [caps_audio](#)
List of audio streams capabilities.

10.54.1 Detailed Description

Media stream capabilities.

Definition at line 175 of file caps.h.

10.54.2 Field Documentation

10.54.2.1 caps_audio

```
std::vector<caps_audio_object> vxg::cloud::agent::proto::stream_caps::caps_audio
```

List of audio streams capabilities.

Definition at line 276 of file caps.h.

10.54.2.2 caps_video

```
std::vector<caps_video_object> vxg::cloud::agent::proto::stream_caps::caps_video
```

List of video streams capabilities.

Definition at line 274 of file caps.h.

The documentation for this struct was generated from the following file:


- [caps.h](#)

10.55 vxg::cloud::agent::proto::stream_config Struct Reference

Media stream config.

```
#include <agent-proto/objects/config.h>
```

Collaboration diagram for vxg::cloud::agent::proto::stream_config:



Data Fields

- **std::vector< [video_stream_config](#) > video**
List of video media stream configs.
- **std::vector< [audio_stream_config](#) > audio**
List of audio media stream configs.

10.55.1 Detailed Description

Media stream config.

Definition at line 219 of file config.h.

10.55.2 Field Documentation

10.55.2.1 audio

```
std::vector<audio_stream_config> vxg::cloud::agent::proto::stream_config::audio
```

List of audio media stream configs.

Definition at line 223 of file config.h.

10.55.2.2 video

```
std::vector<video_stream_config> vxg::cloud::agent::proto::stream_config::video
```

List of video media stream configs.

Definition at line 221 of file config.h.


The documentation for this struct was generated from the following file:

- [config.h](#)


10.56 vxg::cloud::stream_storage Class Reference

```
#include <agent/stream-storage.h>
```

Inheritance diagram for vxg::cloud::stream_storage:



Collaboration diagram for vxg::cloud::stream_storage:



Public Types

- using `ptr` = `shared_ptr< stream_storage >`

Public Member Functions

- `stream_storage` (`agent::media::stream::ptr` stream)
- virtual `~stream_storage` ()
- virtual `std::vector< item_ptr > list` (`cloud::time` start, `cloud::time` stop) override
- virtual `bool load` (`item_ptr` i) override
- virtual `bool store` (`item_ptr`) override
- virtual `bool store_async` (`item_ptr`, `async_store_finished_cb` finished_cb, `async_store_is_canceled_cb` is_↔ canceled_cb) override
- virtual `void erase` (`item_ptr`)

10.56.1 Detailed Description

Definition at line 10 of file stream-storage.h.

10.56.2 Member Typedef Documentation

10.56.2.1 ptr

```
using vxg::cloud::stream_storage::ptr = shared_ptr<stream_storage>
```

Definition at line 25 of file stream-storage.h.

10.56.3 Constructor & Destructor Documentation

10.56.3.1 stream_storage()

```
vxg::cloud::stream_storage::stream_storage (  
    agent::media::stream::ptr stream ) [inline]
```

Definition at line 26 of file stream-storage.h.

10.56.3.2 ~stream_storage()

```
virtual vxg::cloud::stream_storage::~~stream_storage ( ) [inline], [virtual]
```

Definition at line 27 of file stream-storage.h.

10.56.4 Member Function Documentation

10.56.4.1 erase()

```
virtual void vxg::cloud::stream_storage::erase (  
    item_ptr ) [inline], [virtual]
```

Implements [vxg::cloud::timed_storage](#).

Definition at line 64 of file stream-storage.h.

10.56.4.2 list()

```
virtual std::vector<item_ptr> vxg::cloud::stream_storage::list (  
    cloud::time start,  
    cloud::time stop ) [inline], [override], [virtual]
```

Implements [vxg::cloud::timed_storage](#).

Definition at line 29 of file stream-storage.h.

10.56.4.3 load()

```
virtual bool vxg::cloud::stream_storage::load (
    item_ptr i ) [inline], [override], [virtual]
```

Implements [vxg::cloud::timed_storage](#).

Definition at line 43 of file stream-storage.h.

10.56.4.4 store()

```
virtual bool vxg::cloud::stream_storage::store (
    item_ptr ) [inline], [override], [virtual]
```

Implements [vxg::cloud::timed_storage](#).

Definition at line 54 of file stream-storage.h.

10.56.4.5 store_async()

```
virtual bool vxg::cloud::stream_storage::store_async (
    item_ptr ,
    async_store_finished_cb finished_cb,
    async_store_is_canceled_cb is_canceled_cb ) [inline], [override], [virtual]
```

Reimplemented from [vxg::cloud::timed_storage](#).

Definition at line 56 of file stream-storage.h.

The documentation for this class was generated from the following file:


- [stream-storage.h](#)

10.57 vxg::media::Streamer::StreamInfo Struct Reference

Stream info description.

```
#include <streamer/base_streamer.h>
```

Collaboration diagram for vxg::media::Streamer::StreamInfo:



Data Structures

- struct [AudioInfo](#)
Audio stream info.
- struct [VideoInfo](#)
Video stream info.

Public Types

- enum [StreamType](#) {
ST_UNKNOWN, ST_VIDEO, ST_AUDIO, ST_DATA,
ST_ANY }
Stream type.
- enum [VideoCodec](#) { VC_UNKNOWN, VC_H264 }
Video codec type.
- enum [AudioCodec](#) {
AC_UNKNOWN, AC_AAC, AC_G711_U, AC_G711_A,
AC_LPCM, AC_G726, AC_OPUS }
Audio codec.
- enum [DataCodec](#) { DC_UNKNOWN, DC_ONVIF }
Data codec.

Data Fields

- [StreamType](#) type
Stream type.
- [VideoInfo](#) video
Video stream info. Should be filled if stream type is ST_VIDEO.
- [AudioInfo](#) audio
Audio stream info. Should be filled if stream type is ST_AUDIO.

10.57.1 Detailed Description

Stream info description.

Definition at line 311 of file base_streamer.h.

10.57.2 Member Enumeration Documentation

10.57.2.1 AudioCodec

```
enum vxg::media::Streamer::StreamInfo::AudioCodec
```

Audio codec.

Enumerator

AC_UNKNOWN	
AC_AAC	
AC_G711_U	
AC_G711_A	
AC_LPCM	
AC_G726	
AC_OPUS	

Definition at line 351 of file base_streamer.h.

10.57.2.2 DataCodec

```
enum vxg::media::Streamer::StreamInfo::DataCodec
```

Data codec.

Enumerator

DC_UNKNOWN	
DC_ONVIF	

Definition at line 384 of file base_streamer.h.

10.57.2.3 StreamType

```
enum vxg::media::Streamer::StreamInfo::StreamType
```

Stream type.

Enumerator

ST_UNKNOWN	
ST_VIDEO	
ST_AUDIO	
ST_DATA	
ST_ANY	

Definition at line 313 of file base_streamer.h.

10.57.2.4 VideoCodec

enum vxg::media::Streamer::StreamInfo::VideoCodec

Video codec type.

Enumerator

VC_UNKNOWN	
VC_H264	

Definition at line 316 of file base_streamer.h.

10.57.3 Field Documentation

10.57.3.1 audio

AudioInfo vxg::media::Streamer::StreamInfo::audio

Audio stream info. Should be filled if stream type is ST_AUDIO.

Definition at line 399 of file base_streamer.h.

10.57.3.2 type

StreamType vxg::media::Streamer::StreamInfo::type

Stream type.

Definition at line 395 of file base_streamer.h.

10.57.3.3 video

VideoInfo vxg::media::Streamer::StreamInfo::video

Video stream info. Should be filled if stream type is ST_VIDEO.

Definition at line 397 of file base_streamer.h.

The documentation for this struct was generated from the following file:


- [base_streamer.h](#)

10.58 vxg::cloud::agent::supported_stream_config Struct Reference

Supported stream config.

```
#include <agent-proto/objects/config.h>
```

Collaboration diagram for vxg::cloud::agent::supported_stream_config:



Data Fields

- **std::string** [id](#)
id: string, name of media stream, unique for the camera
- **std::string** [video](#)
video: optional string, video ES that is sent in this media stream
- **std::string** [audio](#)
audio: optional string, audio ES that is sent in this media stream

10.58.1 Detailed Description

Supported stream config.

Definition at line 1297 of file config.h.

10.58.2 Field Documentation

10.58.2.1 audio

std::string vxg::cloud::agent::supported_stream_config::audio

audio: optional string, audio ES that is sent in this media stream

Definition at line 1303 of file config.h.

10.58.2.2 id

std::string vxg::cloud::agent::supported_stream_config::id

id: string, name of media stream, unique for the camera

Definition at line 1299 of file config.h.

10.58.2.3 video

std::string vxg::cloud::agent::supported_stream_config::video

video: optional string, video ES that is sent in this media stream

Definition at line 1301 of file config.h.

The documentation for this struct was generated from the following file:


- [config.h](#)

10.59 vxg::cloud::agent::supported_streams_config Struct Reference

Supported streams config, list of [supported_stream_config](#).

```
#include <agent-proto/objects/config.h>
```

Collaboration diagram for vxg::cloud::agent::supported_streams_config:



Data Fields

- **std::vector< [supported_stream_config](#) >** **streams**
streams: list of [supported_stream_config](#) struct, camera media streams
- **std::vector< std::string >** **video_es**
list of string, camera video ES
- **std::vector< std::string >** **audio_es**
list of string, camera audio ES

10.59.1 Detailed Description

Supported streams config, list of [supported_stream_config](#).

Definition at line 1313 of file config.h.

10.59.2 Field Documentation

10.59.2.1 audio_es

```
std::vector< std::string> vxg::cloud::agent::supported_streams_config::audio_es
```

list of string, camera audio ES

Definition at line 1319 of file config.h.

10.59.2.2 streams

```
std::vector<supported_stream_config> vxg::cloud::agent::supported_streams_config::streams
```

streams: list of [supported_stream_config](#) struct, camera media streams

Definition at line 1315 of file config.h.

10.59.2.3 video_es

```
std::vector< std::string> vxg::cloud::agent::supported_streams_config::video_es
```

list of string, camera video ES

Definition at line 1317 of file config.h.


The documentation for this struct was generated from the following file:

- [config.h](#)

10.60 vxg::cloud::agent::synchronizer::sync_request Struct Reference

```
#include <agent/timeline-synchronizer.h>
```

Collaboration diagram for vxg::cloud::agent::synchronizer::sync_request:



Data Fields

- [segmenter_ptr segmenter](#)

10.60.1 Detailed Description

Definition at line 76 of file timeline-synchronizer.h.

10.60.2 Field Documentation

10.60.2.1 segmenter

```
segmenter\_ptr vxg::cloud::agent::synchronizer::sync_request::segmenter
```

Definition at line 77 of file timeline-synchronizer.h.

The documentation for this struct was generated from the following file:

- [timeline-synchronizer.h](#)

10.61 vxg::cloud::agent::synchronizer Class Reference

```
#include <agent/timeline-synchronizer.h>
```

Data Structures

- struct [config](#)
- struct [segmenter](#)
- struct [sync_request](#)

Public Types

- enum [sync_request_status](#) { [sync_request_status::PENDING](#), [sync_request_status::DONE](#), [sync_request_status::ERROR](#), [sync_request_status::CANCELED](#) }
- using [sync_status_report_cb](#) = `std::function< void(int progress, sync_request_status status, std::shared_ptr< segmenter > seg)>`
- using [segmenter_ptr](#) = `std::shared_ptr< segmenter >`
- using [sync_request_ptr](#) = `std::shared_ptr< sync_request >`
- typedef `std::shared_ptr< synchronizer > ptr`

Public Member Functions

- bool [start](#) ()
- void [stop](#) ()
- [sync_request_ptr](#) [sync](#) ([cloud::time](#) begin, [cloud::time](#) end=[utils::time::null\(\)](#), [sync_status_report_cb](#) status_report_cb=nullptr, `std::string` upload_token="", [cloud::duration](#) delay= `std::chrono::microseconds(0)`)
- void [sync_finalize](#) ([sync_request_ptr](#) req, [cloud::time](#) end)
- void [sync_cancel](#) (const `std::string` &ticket)

Static Public Member Functions

- static [ptr](#) [create](#) (const [synchronizer::config](#) &c, [vxg::cloud::sync::timeline_ptr](#) s, [vxg::cloud::sync::timeline_ptr](#) d)

10.61.1 Detailed Description

Definition at line 13 of file timeline-synchronizer.h.

10.61.2 Member Typedef Documentation

10.61.2.1 ptr

```
typedef std::shared_ptr<synchronizer> vxg::cloud::agent::synchronizer::ptr
```

Definition at line 695 of file timeline-synchronizer.h.

10.61.2.2 segmenter_ptr

```
using vxg::cloud::agent::synchronizer::segmenter_ptr = std::shared_ptr<segmenter>
```

Definition at line 74 of file timeline-synchronizer.h.

10.61.2.3 sync_request_ptr

```
using vxg::cloud::agent::synchronizer::sync_request_ptr = std::shared_ptr<sync_request>
```

Definition at line 79 of file timeline-synchronizer.h.

10.61.2.4 sync_status_report_cb

```
using vxg::cloud::agent::synchronizer::sync_status_report_cb = std::function<void(int progress,  
sync_request_status status, std::shared_ptr<segmenter> seg)>
```

Definition at line 30 of file timeline-synchronizer.h.

10.61.3 Member Enumeration Documentation

10.61.3.1 sync_request_status

```
enum vxg::cloud::agent::synchronizer::sync_request_status [strong]
```

Enumerator

PENDING	
DONE	
ERROR	
CANCELED	

Definition at line 18 of file timeline-synchronizer.h.

10.61.4 Member Function Documentation

10.61.4.1 create()

```
static ptr vxg::cloud::agent::synchronizer::create (
    const synchronizer::config & c,
    vxg::cloud::sync::timeline_ptr s,
    vxg::cloud::sync::timeline_ptr d ) [inline], [static]
```

Definition at line 697 of file timeline-synchronizer.h.

10.61.4.2 start()

```
bool vxg::cloud::agent::synchronizer::start ( ) [inline]
```

Definition at line 713 of file timeline-synchronizer.h.

10.61.4.3 stop()

```
void vxg::cloud::agent::synchronizer::stop ( ) [inline]
```

Definition at line 731 of file timeline-synchronizer.h.

10.61.4.4 sync()

```
sync_request_ptr vxg::cloud::agent::synchronizer::sync (
    cloud::time begin,
    cloud::time end = utils::time::null(),
    sync_status_report_cb status_report_cb = nullptr,
    std::string upload_token = "",
    cloud::duration delay = std::chrono::microseconds(0) ) [inline]
```

Definition at line 759 of file timeline-synchronizer.h.

10.61.4.5 sync_cancel()

```
void vxg::cloud::agent::synchronizer::sync_cancel (
    const std::string & ticket ) [inline]
```

Definition at line 801 of file timeline-synchronizer.h.

10.61.4.6 sync_finalize()

```
void vxg::cloud::agent::synchronizer::sync_finalize (
    sync_request_ptr req,
    cloud::time end ) [inline]
```

Definition at line 797 of file timeline-synchronizer.h.


The documentation for this class was generated from the following file:

- [timeline-synchronizer.h](#)

10.62 vxg::cloud::timed_storage Class Reference

```
#include <agent/timeline.h>
```

Inheritance diagram for vxg::cloud::timed_storage:



Data Structures

- struct [item](#)

Public Types

- typedef **std::shared_ptr**< struct [item](#) > [item_ptr](#)
- using [async_store_finished_cb](#) = **std::function**< void(bool)>
- using [async_store_is_canceled_cb](#) = **std::function**< bool(void)>

Public Member Functions

- [timed_storage](#) ()
- virtual [~timed_storage](#) ()
- virtual **std::vector**< [item_ptr](#) > [list](#) (cloud::time start, cloud::time stop)=0
- virtual bool [load](#) (item_ptr)=0
- virtual bool [store](#) (item_ptr)=0
- virtual bool [store_async](#) (item_ptr, [async_store_finished_cb](#) finished_cb, [async_store_is_canceled_cb](#) is_↵ canceled_cb)
- virtual void [erase](#) (item_ptr)=0
- virtual bool [init](#) ()
- virtual void [finit](#) ()

10.62.1 Detailed Description

Definition at line 67 of file timeline.h.

10.62.2 Member Typedef Documentation

10.62.2.1 `async_store_finished_cb`

```
using vxg::cloud::timed_storage::async_store_finished_cb = std::function<void(bool)>
```

Definition at line 114 of file timeline.h.

10.62.2.2 `async_store_is_canceled_cb`

```
using vxg::cloud::timed_storage::async_store_is_canceled_cb = std::function<bool(void)>
```

Definition at line 115 of file timeline.h.

10.62.2.3 `item_ptr`

```
typedef std::shared_ptr<struct item> vxg::cloud::timed_storage::item_ptr
```

Definition at line 108 of file timeline.h.

10.62.3 Constructor & Destructor Documentation

10.62.3.1 `timed_storage()`

```
vxg::cloud::timed_storage::timed_storage ( ) [inline]
```

Definition at line 69 of file timeline.h.

10.62.3.2 `~timed_storage()`

```
virtual vxg::cloud::timed_storage::~~timed_storage ( ) [inline], [virtual]
```

Definition at line 70 of file timeline.h.

10.62.4 Member Function Documentation

10.62.4.1 erase()

```
virtual void vxg::cloud::timed_storage::erase (
    item_ptr ) [pure virtual]
```

Implemented in [vxg::cloud::cloud_storage](#), and [vxg::cloud::stream_storage](#).

10.62.4.2 finit()

```
virtual void vxg::cloud::timed_storage::finit ( ) [inline], [virtual]
```

Definition at line 125 of file timeline.h.

10.62.4.3 init()

```
virtual bool vxg::cloud::timed_storage::init ( ) [inline], [virtual]
```

Definition at line 124 of file timeline.h.

10.62.4.4 list()

```
virtual std::vector<item_ptr> vxg::cloud::timed_storage::list (
    cloud::time start,
    cloud::time stop ) [pure virtual]
```

Implemented in [vxg::cloud::cloud_storage](#), and [vxg::cloud::stream_storage](#).

10.62.4.5 load()

```
virtual bool vxg::cloud::timed_storage::load (
    item_ptr ) [pure virtual]
```

Implemented in [vxg::cloud::cloud_storage](#), and [vxg::cloud::stream_storage](#).

10.62.4.6 store()

```
virtual bool vxg::cloud::timed_storage::store (
    item_ptr ) [pure virtual]
```

Implemented in [vxg::cloud::stream_storage](#), and [vxg::cloud::cloud_storage](#).

10.62.4.7 store_async()

```
virtual bool vxg::cloud::timed_storage::store_async (
    item_ptr ,
    async_store_finished_cb finished_cb,
    async_store_is_canceled_cb is_canceled_cb ) [inline], [virtual]
```

Reimplemented in [vxg::cloud::stream_storage](#).

Definition at line 116 of file [timeline.h](#).

The documentation for this class was generated from the following file:

- [timeline.h](#)

10.63 vxg::cloud::timeline< T > Class Template Reference

```
#include <agent/timeline.h>
```

Public Member Functions

- [timeline](#) (const vxg::cloud::agent::proto::access_token &access_token, transport::libwebsockets::http::ptr http=nullptr)
- [timeline](#) (std::string path)
- [std::vector< period > _squash_periods](#) ([std::vector< timed_storage::item_ptr >](#) periods)
- [std::vector< period > slices](#) ([cloud::time](#) start, [cloud::time](#) stop)

10.63.1 Detailed Description

```
template<class T>
class vxg::cloud::timeline< T >
```

Definition at line 457 of file [timeline.h](#).

10.63.2 Constructor & Destructor Documentation

10.63.2.1 timeline() [1/2]

```
template<class T >
vxg::cloud::timeline< T >::timeline (
    const vxg::cloud::agent::proto::access_token & access_token,
    transport::libwebsockets::http::ptr http = nullptr ) [inline]
```

Definition at line 461 of file timeline.h.

10.63.2.2 timeline() [2/2]

```
template<class T >
vxg::cloud::timeline< T >::timeline (
    std::string path ) [inline]
```

Definition at line 464 of file timeline.h.

10.63.3 Member Function Documentation**10.63.3.1 _squash_periods()**

```
template<class T >
std::vector<period> vxg::cloud::timeline< T >::_squash_periods (
    std::vector< timed_storage::item_ptr > periods ) [inline]
```

Definition at line 466 of file timeline.h.

10.63.3.2 slices()

```
template<class T >
std::vector<period> vxg::cloud::timeline< T >::slices (
    cloud::time start,
    cloud::time stop ) [inline]
```

Definition at line 497 of file timeline.h.

The documentation for this class was generated from the following file:

- [timeline.h](#)

10.64 vxg::cloud::sync::timeline Class Reference

```
#include <agent/timeline.h>
```

Public Types

- using `async_store_finished_cb` = `std::function< void(bool)>`
- using `async_store_is_canceled_cb` = `std::function< bool(void)>`

Public Member Functions

- `timeline` (`timed_storage_ptr` storage)
- virtual `~timeline` ()
- `std::vector< period > _squash_periods` (`std::vector< timed_storage::item_ptr >` periods)
- virtual bool `init` ()
- virtual void `finit` ()
- `std::vector< period > slices` (`cloud::time` start, `cloud::time` stop)
- `std::vector< timed_storage::item_ptr > list` (`cloud::time` start, `cloud::time` stop)
- bool `store` (`timed_storage::item_ptr` item)
- bool `load` (`timed_storage::item_ptr` item)
- virtual bool `store_async` (`timed_storage::item_ptr` item, `async_store_finished_cb` finished_cb, `async_store_is_canceled_cb` is_canceled_cb)

10.64.1 Detailed Description

Definition at line 503 of file `timeline.h`.

10.64.2 Member Typedef Documentation

10.64.2.1 `async_store_finished_cb`

```
using vxg::cloud::sync::timeline::async_store_finished_cb = std::function<void(bool)>
```

Definition at line 575 of file `timeline.h`.

10.64.2.2 `async_store_is_canceled_cb`

```
using vxg::cloud::sync::timeline::async_store_is_canceled_cb = std::function<bool(void)>
```

Definition at line 576 of file `timeline.h`.

10.64.3 Constructor & Destructor Documentation

10.64.3.1 timeline()

```
vxg::cloud::sync::timeline::timeline (
    timed_storage_ptr storage ) [inline]
```

Definition at line 508 of file timeline.h.

10.64.3.2 ~timeline()

```
virtual vxg::cloud::sync::timeline::~~timeline ( ) [inline], [virtual]
```

Definition at line 509 of file timeline.h.

10.64.4 Member Function Documentation

10.64.4.1 _squash_periods()

```
std::vector<period> vxg::cloud::sync::timeline::_squash_periods (
    std::vector< timed_storage::item_ptr > periods ) [inline]
```

Definition at line 511 of file timeline.h.

10.64.4.2 finit()

```
virtual void vxg::cloud::sync::timeline::finit ( ) [inline], [virtual]
```

Definition at line 543 of file timeline.h.

10.64.4.3 init()

```
virtual bool vxg::cloud::sync::timeline::init ( ) [inline], [virtual]
```

Definition at line 541 of file timeline.h.

10.64.4.4 list()

```
std::vector<timed_storage::item_ptr> vxg::cloud::sync::timeline::list (
    cloud::time start,
    cloud::time stop ) [inline]
```

Definition at line 550 of file timeline.h.

10.64.4.5 load()

```
bool vxg::cloud::sync::timeline::load (
    timed_storage::item_ptr item ) [inline]
```

Definition at line 568 of file timeline.h.

10.64.4.6 slices()

```
std::vector<period> vxg::cloud::sync::timeline::slices (
    cloud::time start,
    cloud::time stop ) [inline]
```

Definition at line 546 of file timeline.h.

10.64.4.7 store()

```
bool vxg::cloud::sync::timeline::store (
    timed_storage::item_ptr item ) [inline]
```

Definition at line 561 of file timeline.h.

10.64.4.8 store_async()

```
virtual bool vxg::cloud::sync::timeline::store_async (
    timed_storage::item_ptr item,
    async_store_finished_cb finished_cb,
    async_store_is_canceled_cb is_canceled_cb ) [inline], [virtual]
```

Definition at line 577 of file timeline.h.


The documentation for this class was generated from the following file:

- [timeline.h](#)

10.65 vxg::cloud::utils::uri Struct Reference

```
#include <utils/utils.h>
```

Collaboration diagram for vxg::cloud::utils::uri:



Static Public Member Functions

- static bool `parse` (const `std::string` &in_uri, `uri` &result)

Data Fields

- `std::string` `scheme`
- `std::string` `user`
- `std::string` `password`
- `std::string` `host`
- `std::string` `port`
- `std::string` `path`
- `std::string` `query`
- `std::string` `fragment`

10.65.1 Detailed Description

Definition at line 67 of file `utils.h`.

10.65.2 Member Function Documentation

10.65.2.1 parse()

```
static bool vxg::cloud::utils::uri::parse (  
    const std::string & in_uri,  
    uri & result ) [inline], [static]
```

Definition at line 77 of file utils.h.

10.65.3 Field Documentation

10.65.3.1 fragment

```
std::string vxg::cloud::utils::uri::fragment
```

Definition at line 75 of file utils.h.

10.65.3.2 host

```
std::string vxg::cloud::utils::uri::host
```

Definition at line 71 of file utils.h.

10.65.3.3 password

```
std::string vxg::cloud::utils::uri::password
```

Definition at line 70 of file utils.h.

10.65.3.4 path

```
std::string vxg::cloud::utils::uri::path
```

Definition at line 73 of file utils.h.

10.65.3.5 port

```
std::string vxg::cloud::utils::uri::port
```

Definition at line 72 of file utils.h.

10.65.3.6 query

```
std::string vxg::cloud::utils::uri::query
```

Definition at line 74 of file utils.h.

10.65.3.7 scheme

```
std::string vxg::cloud::utils::uri::scheme
```

Definition at line 68 of file utils.h.

10.65.3.8 user

```
std::string vxg::cloud::utils::uri::user
```

Definition at line 69 of file utils.h.

The documentation for this struct was generated from the following file:


- [utils.h](#)

10.66 vxg::cloud::agent::proto::video_caps Struct Reference

Video image capabilities.

```
#include <agent-proto/objects/caps.h>
```

Collaboration diagram for vxg::cloud::agent::proto::video_caps:



Data Fields

- **std::vector< mode > vert_flip**
vert_flip: list of string, supported vertical flip modes, possible values ["off", "on", "auto"]
- **std::vector< mode > horz_flip**
horz_flip: list of string, supported horizontal flip modes, possible values ["off", "on", "auto"]
- **std::vector< std::string > tdn**
tdn: list of string, supported TDM modes, possible values ["day", "night", "auto"]
- **std::vector< mode > ir_light**
ir_light: list of string, supported IR light modes, possible values ["off", "on", "auto"]
- **bool brightness**
brightness: bool, True when camera supports brightness control
- **bool contrast**
contrast: bool, True when camera supports contrast control
- **bool saturation**
saturation: bool, True when camera supports saturation control
- **bool sharpness**
sharpness: bool, True when camera supports sharpness control
- **std::vector< std::string > nr_type**
nr_type: list of string, supported noise reduce types.
- **bool nr_level**
nr_level: bool, True when noise reduce filter assumes control of NR level
- **std::vector< std::string > wb_type**
wb_type: list of string, supported white balance types.
- **bool pwr_frequency**
pwr_frequency: bool, True camera supports compensation of images flickering due to flashing of lamps in indoor environment

10.66.1 Detailed Description

Video image capabilities.

Definition at line 366 of file caps.h.

10.66.2 Field Documentation

10.66.2.1 brightness

```
bool vxg::cloud::agent::proto::video_caps::brightness
```

brightness: bool, True when camera supports brightness control

Definition at line 384 of file caps.h.

10.66.2.2 contrast

`bool vxg::cloud::agent::proto::video_caps::contrast`

contrast: bool, True when camera supports contrast control

Definition at line 387 of file caps.h.

10.66.2.3 horz_flip

`std::vector<mode> vxg::cloud::agent::proto::video_caps::horz_flip`

horz_flip: list of string, supported horizontal flip modes, possible values ["off", "on", "auto"]

Definition at line 373 of file caps.h.

10.66.2.4 ir_light

`std::vector<mode> vxg::cloud::agent::proto::video_caps::ir_light`

ir_light: list of string, supported IR light modes, possible values ["off", "on", "auto"]

Definition at line 381 of file caps.h.

10.66.2.5 nr_level

`bool vxg::cloud::agent::proto::video_caps::nr_level`

nr_level: bool, True when noise reduce filter assumes control of NR level

Definition at line 402 of file caps.h.

10.66.2.6 nr_type

`std::vector< std::string> vxg::cloud::agent::proto::video_caps::nr_type`

nr_type: list of string, supported noise reduce types.

Empty list when camera doesn't support it. Example: ["off", "normal", "expert"]

Definition at line 398 of file caps.h.

10.66.2.7 pwr_frequency

```
bool vxg::cloud::agent::proto::video_caps::pwr_frequency
```

pwr_frequency: bool, True camera supports compensation of images flickering due to flashing of lamps in indoor environment

Definition at line 411 of file caps.h.

10.66.2.8 saturation

```
bool vxg::cloud::agent::proto::video_caps::saturation
```

saturation: bool, True when camera supports saturation control

Definition at line 390 of file caps.h.

10.66.2.9 sharpness

```
bool vxg::cloud::agent::proto::video_caps::sharpness
```

sharpness: bool, True when camera supports sharpness control

Definition at line 393 of file caps.h.

10.66.2.10 tdn

```
std::vector< std::string> vxg::cloud::agent::proto::video_caps::tdn
```

tdn: list of string, supported TDM modes, possible values ["day", "night", "auto"]

Definition at line 377 of file caps.h.

10.66.2.11 vert_flip

```
std::vector<mode> vxg::cloud::agent::proto::video_caps::vert_flip
```

vert_flip: list of string, supported vertical flip modes, possible values ["off", "on", "auto"]

Definition at line 369 of file caps.h.

10.66.2.12 wb_type

```
std::vector< std::string> vxg::cloud::agent::proto::video_caps::wb_type
```

wb_type: list of string, supported white balance types.

Empty list when camera doesn't support it. Example: ["auto", "3200K (Indor)", "4200K (Fluo)", "5600K (Outdoor)"]

Definition at line 407 of file caps.h.

The documentation for this struct was generated from the following file:


- [caps.h](#)

10.67 vxg::cloud::agent::proto::video_clip_info Struct Reference

Video recoding(mp4 file) clip description,.

```
#include <agent-proto/objects/config.h>
```

Collaboration diagram for vxg::cloud::agent::proto::video_clip_info:



Data Fields

- [cloud::time tp_start](#)
Clip start time UTC.
- [cloud::time tp_stop](#)
Clip stop time UTC.
- [cloud::time local_start](#)
Clip start time local.
- [cloud::time local_stop](#)
Clip stop time local.
- int [video_width](#)
Video clip picture width.
- int [video_height](#)
Video clip picture height.
- **std::vector< uint8_t >** [data](#)
Video data buffer, we use move semantics internally so no data copying will be invoked.

10.67.1 Detailed Description

Video recoding(mp4 file) clip description,.

Definition at line 449 of file config.h.

10.67.2 Field Documentation

10.67.2.1 data

```
std::vector<uint8_t> vxg::cloud::agent::proto::video_clip_info::data
```

Video data buffer, we use move semantics internally so no data copying will be invoked.

Definition at line 475 of file config.h.

10.67.2.2 local_start

```
cloud::time vxg::cloud::agent::proto::video_clip_info::local_start
```

Clip start time local.

Definition at line 463 of file config.h.

10.67.2.3 local_stop

```
cloud::time vxg::cloud::agent::proto::video_clip_info::local_stop
```

Clip stop time local.

Definition at line 466 of file config.h.

10.67.2.4 tp_start

```
cloud::time vxg::cloud::agent::proto::video_clip_info::tp_start
```

Clip start time UTC.

Definition at line 458 of file config.h.

10.67.2.5 tp_stop

```
cloud::time vxg::cloud::agent::proto::video_clip_info::tp_stop
```

Clip stop time UTC.

Definition at line 460 of file config.h.

10.67.2.6 video_height

```
int vxg::cloud::agent::proto::video_clip_info::video_height
```

Video clip picture height.

Definition at line 471 of file config.h.

10.67.2.7 video_width

```
int vxg::cloud::agent::proto::video_clip_info::video_width
```

Video clip picture width.

Definition at line 469 of file config.h.

The documentation for this struct was generated from the following file:


- [config.h](#)

10.68 vxg::cloud::agent::proto::video_config Struct Reference

Video image config.

```
#include <agent-proto/objects/config.h>
```

Collaboration diagram for vxg::cloud::agent::proto::video_config:



Data Fields

- **std::string** [vert_flip](#)
vert_flip: optional string, vertical image flip mode: ["off", "on", "auto"]
- **std::string** [horz_flip](#)
horz_flip: optional string, horizontal image flip mode: ["off", "on", "auto"]
- **std::string** [tdn](#)
tdn: optional string, possible values ["day", "night", "auto"]
- **std::string** [ir_light](#)
ir_light: optional string, IR light for night conditions ["off", "on", "auto"]
- **int** [brightness](#)
brightness: optional int, a brightness value from range 0-100 (%)
- **int** [contrast](#)
contrast: optional int, a contrast value from range 0-100 (%)
- **int** [saturation](#)
saturation: optional int, a saturation value from range 0-100 (%)
- **int** [sharpness](#)
sharpness: optional int, a sharpness value from range 0-100 (%)
- **std::string** [nr_type](#)
nr_type: optional string, one of predefined noise reduce types from caps
- **int** [nr_level](#)
nr_level: optional int, level of noise reduce when filter requires it 0-100 (%)
- **std::string** [wb_type](#)

- wb_type: optional string, one of predefined white balance types from caps*
- int [pwr_frequency](#)
pwr_frequency: optional int, power line frequency [50, 60] (Hz)
- [video_caps caps](#)
caps

10.68.1 Detailed Description

Video image config.

Definition at line 306 of file config.h.

10.68.2 Field Documentation

10.68.2.1 brightness

```
int vxg::cloud::agent::proto::video_config::brightness
```

brightness: optional int, a brightness value from range 0-100 (%)

Definition at line 323 of file config.h.

10.68.2.2 caps

```
video\_caps vxg::cloud::agent::proto::video_config::caps
```

caps

Definition at line 349 of file config.h.

10.68.2.3 contrast

```
int vxg::cloud::agent::proto::video_config::contrast
```

contrast: optional int, a contrast value from range 0-100 (%)

Definition at line 326 of file config.h.

10.68.2.4 horz_flip

```
std::string vxg::cloud::agent::proto::video_config::horz_flip
```

horz_flip: optional string, horizontal image flip mode: ["off", "on", "auto"]

Definition at line 313 of file config.h.

10.68.2.5 ir_light

```
std::string vxg::cloud::agent::proto::video_config::ir_light
```

ir_light: optional string, IR light for night conditions ["off", "on", "auto"]

Definition at line 320 of file config.h.

10.68.2.6 nr_level

```
int vxg::cloud::agent::proto::video_config::nr_level
```

nr_level: optional int, level of noise reduce when filter requires it 0-100 (%)

Definition at line 339 of file config.h.

10.68.2.7 nr_type

```
std::string vxg::cloud::agent::proto::video_config::nr_type
```

nr_type: optional string, one of predefined noise reduce types from caps

Definition at line 335 of file config.h.

10.68.2.8 pwr_frequency

```
int vxg::cloud::agent::proto::video_config::pwr_frequency
```

pwr_frequency: optional int, power line frequency [50, 60] (Hz)

Definition at line 346 of file config.h.

10.68.2.9 saturation

```
int vxg::cloud::agent::proto::video_config::saturation
```

saturation: optional int, a saturation value from range 0-100 (%)

Definition at line 329 of file config.h.

10.68.2.10 sharpness

```
int vxg::cloud::agent::proto::video_config::sharpness
```

sharpness: optional int, a sharpness value from range 0-100 (%)

Definition at line 332 of file config.h.

10.68.2.11 tdn

```
std::string vxg::cloud::agent::proto::video_config::tdn
```

tdn: optional string, possible values ["day", "night", "auto"]

Definition at line 316 of file config.h.

10.68.2.12 vert_flip

```
std::string vxg::cloud::agent::proto::video_config::vert_flip
```

vert_flip: optional string, vertical image flip mode: ["off", "on", "auto"]

Definition at line 309 of file config.h.

10.68.2.13 wb_type

```
std::string vxg::cloud::agent::proto::video_config::wb_type
```

wb_type: optional string, one of predefined white balance types from caps

Definition at line 343 of file config.h.

The documentation for this struct was generated from the following file:


- [config.h](#)

10.69 vxg::cloud::agent::proto::video_stream_config Struct Reference

Video stream config.

```
#include <agent-proto/objects/config.h>
```

Collaboration diagram for vxg::cloud::agent::proto::video_stream_config:



Data Fields

- **std::string** [stream](#)
Mandatory: video ES to use.
- [video_format](#) **format**
Mandatory: video encoding format.
- **std::string** [profile](#)
Optional: profile that specifies format, when format assumes it.
- int [horz](#)
Mandatory: int (horz) - video resolution width x height.
- int [vert](#)
Mandatory: int (vert) - video resolution width x height.
- double [fps](#)
Mandatory: framerate.
- bool [vbr](#)
Mandatory: prefer VBR; if false or not set CBR should be used.
- int [gop](#)
Mandatory: gop size (I-Frame interval);.
- int [brt](#)
Optional: bitrate, kbps.
- int [vbr_brt](#)
Optional: bitrate for VBR, kbps.
- int [quality](#)
Optional: int [-4..4], quality profile hint for encoder, where 0 means normal.
- int [smoothing](#)
Optional: a smoothing value from range 0-100 (%)

10.69.1 Detailed Description

Video stream config.

Definition at line 83 of file config.h.

10.69.2 Field Documentation

10.69.2.1 brt

```
int vxg::cloud::agent::proto::video_stream_config::brt
```

Optional: bitrate, kbps.

Definition at line 117 of file config.h.

10.69.2.2 format

```
video_format vxg::cloud::agent::proto::video_stream_config::format
```

Mandatory: video encoding format.

Definition at line 90 of file config.h.

10.69.2.3 fps

```
double vxg::cloud::agent::proto::video_stream_config::fps
```

Mandatory: framerate.

Definition at line 105 of file config.h.

10.69.2.4 gop

```
int vxg::cloud::agent::proto::video_stream_config::gop
```

Mandatory: gop size (I-Frame interval);.

Definition at line 113 of file config.h.

10.69.2.5 horz

```
int vxg::cloud::agent::proto::video_stream_config::horz
```

Mandatory: int (horz) - video resolution width x height.

Definition at line 98 of file config.h.

10.69.2.6 profile

```
std::string vxg::cloud::agent::proto::video_stream_config::profile
```

Optional: profile that specifies format, when format assumes it.

Definition at line 94 of file config.h.

10.69.2.7 quality

```
int vxg::cloud::agent::proto::video_stream_config::quality
```

Optional: int [-4..4], quality profile hint for encoder, where 0 means normal.

Definition at line 125 of file config.h.

10.69.2.8 smoothing

```
int vxg::cloud::agent::proto::video_stream_config::smoothing
```

Optional: a smoothing value from range 0-100 (%)

Definition at line 129 of file config.h.

10.69.2.9 stream

```
std::string vxg::cloud::agent::proto::video_stream_config::stream
```

Mandatory: video ES to use.

Definition at line 86 of file config.h.

10.69.2.10 vbr

```
bool vxg::cloud::agent::proto::video_stream_config::vbr
```

Mandatory: prefer VBR; if false or not set CBR should be used.

Definition at line 109 of file config.h.

10.69.2.11 vbr_brt

```
int vxg::cloud::agent::proto::video_stream_config::vbr_brt
```

Optional: bitrate for VBR, kbps.

Definition at line 121 of file config.h.

10.69.2.12 vert

```
int vxg::cloud::agent::proto::video_stream_config::vert
```

Mandatory: int (vert) - video resolution width x height.

Definition at line 101 of file config.h.

The documentation for this struct was generated from the following file:


- [config.h](#)

10.70 vxg::media::Streamer::StreamInfo::VideoInfo Struct Reference

Video stream info.

```
#include <streamer/base_streamer.h>
```

Collaboration diagram for vxg::media::Streamer::StreamInfo::VideoInfo:



Data Fields

- [VideoCodec codec](#)
Video codec type.
- int [width](#)
Video width if needed.
- int [height](#)
Video height if needed.
- **std::pair**< int, int > [framerate](#)
Video framerate if needed.
- int [bitrate](#)
Video bitrate if needed.
- **std::pair**< int, int > [timebase](#)
Timescale of the timestamps, source fills it with timescale of timestamps source receives, [MediaFrame::pts](#) should use this timescale.
- **std::vector**< uint8_t > [extradata](#)
Can be AVC1 extradata or SPS/PPS, source fills it and sink should know and understand this format.

10.70.1 Detailed Description

Video stream info.

This structure as well as [ISink::negotiate](#) method aimed to inform sink about streams source provides, if sink don't care the values of this structure may be ignored.

Definition at line 325 of file `base_streamer.h`.

10.70.2 Field Documentation

10.70.2.1 bitrate

```
int vxg::media::Streamer::StreamInfo::VideoInfo::bitrate
```

Video bitrate if needed.

Definition at line 335 of file `base_streamer.h`.

10.70.2.2 codec

```
VideoCodec vxg::media::Streamer::StreamInfo::VideoInfo::codec
```

Video codec type.

Definition at line 327 of file `base_streamer.h`.

10.70.2.3 extradata

```
std::vector<uint8_t> vxg::media::Streamer::StreamInfo::VideoInfo::extradata
```

Can be AVC1 extradata or SPS/PPS, source fills it and sink should know and understand this format.

Definition at line 342 of file base_streamer.h.

10.70.2.4 framerate

```
std::pair<int, int> vxg::media::Streamer::StreamInfo::VideoInfo::framerate
```

Video framerate if needed.

Definition at line 333 of file base_streamer.h.

10.70.2.5 height

```
int vxg::media::Streamer::StreamInfo::VideoInfo::height
```

Video height if needed.

Definition at line 331 of file base_streamer.h.

10.70.2.6 timebase

```
std::pair<int, int> vxg::media::Streamer::StreamInfo::VideoInfo::timebase
```

Timescale of the timestamps, source fills it with timescale of timestamps source receives, [MediaFrame::pts](#) should use this timescale.

Definition at line 339 of file base_streamer.h.

10.70.2.7 width

```
int vxg::media::Streamer::StreamInfo::VideoInfo::width
```

Video width if needed.

Definition at line 329 of file base_streamer.h.

The documentation for this struct was generated from the following file:


- [base_streamer.h](#)

10.71 vxg::cloud::agent::proto::wifi_config Struct Reference

WiFi config.

```
#include <agent-proto/objects/config.h>
```

Collaboration diagram for vxg::cloud::agent::proto::wifi_config:



Data Fields

- **std::vector< [wifi_network](#) > networks**
List of [wifi_network](#) objects.

10.71.1 Detailed Description

WiFi config.

Definition at line 581 of file config.h.

10.71.2 Field Documentation

10.71.2.1 networks

```
std::vector<wifi\_network> vxg::cloud::agent::proto::wifi_config::networks
```

List of [wifi_network](#) objects.

Definition at line 583 of file config.h.

The documentation for this struct was generated from the following file:


- [config.h](#)

10.72 vxg::cloud::agent::proto::wifi_network Struct Reference

WiFi network object.

```
#include <agent-proto/objects/config.h>
```

Collaboration diagram for vxg::cloud::agent::proto::wifi_network:



Data Fields

- **std::string** [ssid](#)
ssid: string, network SSID
- **int** [signal](#)
signal: int, signal strength, dB
- **std::string** [mac](#)
mac: string, AP MAC address
- **std::vector< [wifi_encryption](#) >** [encryption_caps](#)
encryption_caps: list of string, supported encryption types,
- [wifi_encryption](#) [encryption](#)
encryption: string, current encryption type, see encryption_caps for possible values
- **std::string** [password](#)
password: string, network password

10.72.1 Detailed Description

WiFi network object.

Definition at line 552 of file config.h.

10.72.2 Field Documentation

10.72.2.1 encryption

`wifi_encryption vxg::cloud::agent::proto::wifi_network::encryption`

encryption: string, current encryption type, see encryption_caps for possible values

Definition at line 563 of file config.h.

10.72.2.2 encryption_caps

`std::vector<wifi_encryption> vxg::cloud::agent::proto::wifi_network::encryption_caps`

encryption_caps: list of string, supported encryption types,

Definition at line 560 of file config.h.

10.72.2.3 mac

`std::string vxg::cloud::agent::proto::wifi_network::mac`

mac: string, AP MAC address

Definition at line 558 of file config.h.

10.72.2.4 password

`std::string vxg::cloud::agent::proto::wifi_network::password`

password: string, network password

Definition at line 565 of file config.h.

10.72.2.5 signal

`int vxg::cloud::agent::proto::wifi_network::signal`

signal: int, signal strength, dB

Definition at line 556 of file config.h.

10.72.2.6 ssid

`std::string vxg::cloud::agent::proto::wifi_network::ssid`

ssid: string, network SSID

Definition at line 554 of file config.h.

The documentation for this struct was generated from the following file:

- [config.h](#)

Chapter 11


File Documentation

11.1 app-dev.md File Reference


11.2 arm-example.txt File Reference

11.3 base_streamer.h File Reference

```
#include <cstdlib>
#include <future>
#include <map>
#include <queue>
#include <string>
#include <pthread.h>
#include <streamer/stats.h>
#include <utils/logging.h>
#include <utils/utils.h>
Include dependency graph for base_streamer.h:
```



This graph shows which files directly or indirectly include this file:



Data Structures

- struct [vxg::media::Streamer::StreamInfo](#)
Stream info description.
- struct [vxg::media::Streamer::StreamInfo::VideoInfo](#)
Video stream info.
- struct [vxg::media::Streamer::StreamInfo::AudioInfo](#)
Audio stream info.
- struct [vxg::media::Streamer::MediaFrame](#)
Media frame container.
- class [vxg::media::Streamer::ISink](#)
- class [vxg::media::Streamer::ISource](#)
ISource interface class.

Namespaces

- [vxg](#)
- [vxg::media](#)
- [vxg::media::Streamer](#)

Macros

- `#define __BASE_STREAMER_H`

Typedefs

- using [vxg::media::Streamer::on_error_cb](#) = `std::function< void(Streamer::StreamError e)>`
On error callback, used for both [ISink](#) and [ISource](#) if was provided by user.

Enumerations

- enum `vvg::media::Streamer::DropDirection` { `vvg::media::Streamer::DROP_FRONT`, `vvg::media::Streamer::DROP_BACK` }
- enum `vvg::media::Streamer::StreamError` { `vvg::media::Streamer::E_NONE`, `vvg::media::Streamer::E_FATAL`, `vvg::media::Streamer::E_EOS` }
Stream error.
- enum `vvg::media::Streamer::MediaType` { `vvg::media::Streamer::UNKNOWN`, `vvg::media::Streamer::VIDEO`, `vvg::media::Streamer::VIDEO_AVC_SPS`, `vvg::media::Streamer::VIDEO_AVC_PPS`, `vvg::media::Streamer::VIDEO_SEQ_HDR`, `vvg::media::Streamer::AUDIO`, `vvg::media::Streamer::AUDIO_SEQ_HDR`, `vvg::media::Streamer::FLV`, `vvg::media::Streamer::DATA`, `vvg::media::Streamer::MAX` }
Media frame type.

Variables

- constexpr int `vvg::media::Streamer::SINK_THREAD_PRIO`
- constexpr int `vvg::media::Streamer::SRC_THREAD_PRIO`

11.3.1 Macro Definition Documentation

11.3.1.1 __BASE_STREAMER_H


```
#define __BASE_STREAMER_H
```

Definition at line 14 of file `base_streamer.h`.


11.4 build-system.md File Reference

11.5 callback.h File Reference

```
#include <string>
#include <agent-proto/proto.h>
#include <agent/config.h>
Include dependency graph for callback.h:
```



This graph shows which files directly or indirectly include this file:



Data Structures

- class `vxg::cloud::agent::callback`
VXG Cloud manager common callbacks class.

Namespaces

- `vxg`
- `vxg::cloud`
- `vxg::cloud::agent`
VXG Cloud Agent namespace.


11.6 caps.h File Reference

```


#include <string>
#include <vector>
#include <nlohmann/json.hpp>
#include <agent-proto/command/unset-helper.h>
#include <agent-proto/command/utls.h>

```

Include dependency graph for caps.h:



This graph shows which files directly or indirectly include this file:



Data Structures

- struct [vxg::cloud::agent::proto::stream_caps](#)
Media stream capabilities.
- struct [vxg::cloud::agent::proto::stream_caps::caps_video_object](#)
Video streams capabilities.
- struct [vxg::cloud::agent::proto::stream_caps::caps_audio_object](#)
Audio streams capabilities.
- struct [vxg::cloud::agent::proto::motion_detection_caps](#)
Motion detection capabilities camera capabilities that limit possible motion detection configuration.
- struct [vxg::cloud::agent::proto::video_caps](#)
Video image capabilities.
- struct [vxg::cloud::agent::proto::event_caps](#)
Events capabilities.
- struct [vxg::cloud::agent::proto::audio_caps](#)
Audio capabilities.
- struct [vxg::cloud::agent::proto::osd_caps](#)
OSD capabilities.

Namespaces

- [vxg](#)
- [vxg::cloud](#)
- [vxg::cloud::agent](#)
VXG Cloud Agent namespace.
- [vxg::cloud::agent::proto](#)

Macros

- `#define ignore_exception(...)`

Typedefs

- using `json` = `nlohmann::json`

Enumerations

- enum `vxg::cloud::agent::proto::mode` { `vxg::cloud::agent::proto::M_OFF`, `vxg::cloud::agent::proto::M_ON`, `vxg::cloud::agent::proto::M_AUTO`, `vxg::cloud::agent::proto::M_INVALID` }
Mode on/off.
 - enum `vxg::cloud::agent::proto::video_format` { `vxg::cloud::agent::proto::VF_H264`, `vxg::cloud::agent::proto::VF_H265`, `vxg::cloud::agent::proto::VF_MJPEG`, `vxg::cloud::agent::proto::VF_INVALID` }
Video codec format.
 - enum `vxg::cloud::agent::proto::audio_format` { `vxg::cloud::agent::proto::AF_G711A`, `vxg::cloud::agent::proto::AF_G711U`, `vxg::cloud::agent::proto::AF_RAW`, `vxg::cloud::agent::proto::AF_ADPCM`, `vxg::cloud::agent::proto::AF_MP3`, `vxg::cloud::agent::proto::AF_NELLY8`, `vxg::cloud::agent::proto::AF_NELLY16`, `vxg::cloud::agent::proto::AF_NELLY`, `vxg::cloud::agent::proto::AF_OPUS`, `vxg::cloud::agent::proto::AF_AAC`, `vxg::cloud::agent::proto::AF_SPEEX`, `vxg::cloud::agent::proto::AF_INVALID` }
Audio codec format.
 - enum `vxg::cloud::agent::proto::audio_file_format` { `vxg::cloud::agent::proto::AFF_AU_G711U`, `vxg::cloud::agent::proto::AFF_MP3`, `vxg::cloud::agent::proto::AFF_WAV_PCM`, `vxg::cloud::agent::proto::AFF_INVALID` }
Audio file format.
 - enum `vxg::cloud::agent::proto::motion_sensitivity` { `vxg::cloud::agent::proto::MS_REGION`, `vxg::cloud::agent::proto::MS_FRAME`, `vxg::cloud::agent::proto::MS_INVALID` }
Motion sensitivity.
 - enum `vxg::cloud::agent::proto::motion_region_shape` { `vxg::cloud::agent::proto::MR_RECTANGLE`, `vxg::cloud::agent::proto::MR_ANY`, `vxg::cloud::agent::proto::MR_INVALID` }
Motion region shape.
 - enum `vxg::cloud::agent::proto::ptz_action` { `vxg::cloud::agent::proto::A_LEFT`, `vxg::cloud::agent::proto::A_RIGHT`, `vxg::cloud::agent::proto::A_TOP`, `vxg::cloud::agent::proto::A_BOTTOM`, `vxg::cloud::agent::proto::A_ZOOM_IN`, `vxg::cloud::agent::proto::A_ZOOM_OUT`, `vxg::cloud::agent::proto::A_STOP`, `vxg::cloud::agent::proto::A_INVALID` }
PTZ actions.
 - enum `vxg::cloud::agent::proto::ptz_preset_action` { `vxg::cloud::agent::proto::PA_CREATE`, `vxg::cloud::agent::proto::PA_DELETE`, `vxg::cloud::agent::proto::PA_GOTO`, `vxg::cloud::agent::proto::PA_UPDATE`, `vxg::cloud::agent::proto::PA_INVALID` }
PTZ preset action.
 - enum `vxg::cloud::agent::proto::time_format_n` { `vxg::cloud::agent::proto::TF_12H`, `vxg::cloud::agent::proto::TF_24H`, `vxg::cloud::agent::proto::TF_INVALID` }
- 3.34 `get_osd_conf` (SRV) 3.35 `osd_conf` (CM) 3.36 `set_osd_conf` (SRV)

11.6.1 Macro Definition Documentation

11.6.1.1 ignore_exception

```
#define ignore_exception(
    ... )
```

Definition at line 20 of file caps.h.

11.6.2 Typedef Documentation


11.6.2.1 json

```
using json = nlohmann::json
```

Definition at line 12 of file caps.h.

11.7 cloud-agent-minimal.cc File Reference

```
#include <signal.h>
#include <args.hxx>
#include <agent/manager.h>
#include <agent/rtsp-stream.h>
#include <utils/logging.h>
#include <utils/properties.h>
Include dependency graph for cloud-agent-minimal.cc:
```



Functions

- static void [signal_handler](#) (int sig)
- bool [parse_args](#) (int argc, char **argv)
- int [main](#) (int argc, char **argv)

Variables

- agent::config [agent_config](#)
[Includes and namespaces]
- static bool [quit](#)
- static vxg::properties [props](#)
- std::string [vxg_cloud_token](#)
[Minimal callback class implementation]
- std::string [rtsp_url](#)

11.7.1 Function Documentation

11.7.1.1 `main()`

```
int main (  
    int argc,  
    char ** argv )
```

[Create and start agent object]

[Create and start agent object]

[Stop agent]

[Stop agent]

Definition at line 87 of file cloud-agent-minimal.cc.

11.7.1.2 `parse_args()`

```
bool parse_args (  
    int argc,  
    char ** argv )
```

Definition at line 48 of file cloud-agent-minimal.cc.

11.7.1.3 `signal_handler()`

```
static void signal_handler (  
    int sig ) [static]
```

Definition at line 20 of file cloud-agent-minimal.cc.

11.7.2 Variable Documentation

11.7.2.1 `agent_config`

```
agent::config agent_config
```

[Includes and namespaces]

Definition at line 15 of file cloud-agent-minimal.cc.

11.7.2.2 props

```
vxg::properties props [static]
```

Definition at line 18 of file cloud-agent-minimal.cc.

11.7.2.3 quit

```
bool quit [static]
```

Definition at line 17 of file cloud-agent-minimal.cc.

11.7.2.4 rtsp_url

```
std::string rtsp_url
```

Definition at line 46 of file cloud-agent-minimal.cc.

11.7.2.5 vxg_cloud_token

```
std::string vxg_cloud_token
```


[Minimal callback class implementation]

Definition at line 45 of file cloud-agent-minimal.cc.

11.8 cloud-agent.cc File Reference

```
#include <signal.h>
#include <args.hxx>
#include <agent/manager.h>
#include <agent/rtsp-stream.h>
#include <utils/logging.h>
#include <utils/properties.h>
```

Include dependency graph for cloud-agent.cc:



Functions

- static void [signal_handler](#) (int sig)
- bool [parse_args](#) (int argc, char **argv)
- int [main](#) (int argc, char **argv)

Variables

- agent::config [agent_config](#)
[Includes and namespaces]
- static bool [quit](#)
- static vxg::properties [props](#)
- **std::string** [vxg_cloud_token](#)
[Event stream callback class implementation]
- **std::string** [rtsp_url](#)

11.8.1 Function Documentation

11.8.1.1 main()

```
int main (
    int argc,
    char ** argv )
```

[Create and start agent object]

[Create and start agent object]

[Stop agent]

[Stop agent]

Definition at line 368 of file cloud-agent.cc.

11.8.1.2 parse_args()

```
bool parse_args (
    int argc,
    char ** argv )
```

Definition at line 336 of file cloud-agent.cc.

11.8.1.3 signal_handler()

```
static void signal_handler (  
    int sig ) [static]
```

Definition at line 20 of file cloud-agent.cc.

11.8.2 Variable Documentation

11.8.2.1 agent_config

```
agent::config agent_config
```

[Includes and namespaces]

Definition at line 15 of file cloud-agent.cc.

11.8.2.2 props

```
vsg::properties props [static]
```

Definition at line 17 of file cloud-agent.cc.

11.8.2.3 quit

```
bool quit [static]
```

Definition at line 16 of file cloud-agent.cc.

11.8.2.4 rtsp_url

```
std::string rtsp_url
```

Definition at line 334 of file cloud-agent.cc.

11.8.2.5 vxg_cloud_token

```
std::string vxg_cloud_token
```

[Event stream callback class implementation]

Definition at line 333 of file cloud-agent.cc.

11.9 compile.md File Reference


11.10 config.h File Reference

```
#include <iostream>
#include <string>
#include <vector>
#include <vxgcloudagent-config.h>
#include <nlohmann/json.hpp>
#include <agent-proto/command/unset-helper.h>
#include <agent-proto/command/utis.h>
#include <agent-proto/objects/caps.h>
#include <utis/base64.h>
#include <utis/logging.h>
#include <utis/utis.h>
```

Include dependency graph for config.h:



This graph shows which files directly or indirectly include this file:



Data Structures

- struct [vxg::cloud::agent::proto::video_stream_config](#)
Video stream config.
- struct [vxg::cloud::agent::proto::audio_stream_config](#)
Audio media stream config.
- struct [vxg::cloud::agent::proto::stream_config](#)
Media stream config.
- struct [vxg::cloud::agent::proto::motion_region](#)
Motion detection related structs.
- struct [vxg::cloud::agent::proto::motion_detection_config](#)
Motion detection config.
- struct [vxg::cloud::agent::proto::video_config](#)
Video image config.
- struct [vxg::cloud::agent::proto::video_clip_info](#)
Video recoding(mp4 file) clip description,.
- struct [vxg::cloud::agent::proto::wifi_network](#)
WiFi network object.
- struct [vxg::cloud::agent::proto::wifi_config](#)
WiFi config.
- struct [vxg::cloud::agent::event_config](#)
Event config.
- struct [vxg::cloud::agent::events_config](#)
Events config, list of [event_config](#) objects.
- struct [vxg::cloud::agent::audio_config](#)
Audio config.
- struct [vxg::cloud::agent::ptz_preset](#)
PTZ preset.
- struct [vxg::cloud::agent::ptz_config](#)
PTZ config.
- struct [vxg::cloud::agent::ptz_command](#)
PTZ command.
- struct [vxg::cloud::agent::osd_config](#)
OSD config.
- struct [vxg::cloud::agent::access_token](#)
VXG Cloud access token.
- struct [vxg::cloud::agent::access_token::proxy_config](#)
Socks proxy settings.
- struct [vxg::cloud::agent::supported_stream_config](#)
Supported stream config.
- struct [vxg::cloud::agent::supported_streams_config](#)
Supported streams config, list of [supported_stream_config](#).
- struct [vxg::cloud::agent::audio_detection_config](#)
5.6 [audio_detection_config](#) (CM) Current audio detection settings.
- struct [vxg::cloud::agent::audio_detection_config::audio_detection_conf_caps](#)

Namespaces

- [vxd](#)
- [vxd::cloud](#)
- [vxd::cloud::time_spec](#)
time point
- [nlohmann](#)
- [vxd::cloud::agent](#)
VXD Cloud Agent namespace.
- [vxd::cloud::agent::proto](#)

Typedefs

- using [vxd::cloud::time_spec::precision](#) = [std::chrono::microseconds](#)
- template<typename T >
using [vxd::cloud::time_spec::duration](#) = typename [std::conditional](#)< [std::is_same](#)< T, precision >::value, precision, [std::chrono::duration](#)< T > >::type
- using [vxd::cloud::time](#) = [std::chrono::time_point](#)< [std::chrono::system_clock](#), time_spec::precision >
- using [vxd::cloud::duration](#) = time_spec::duration< time_spec::precision >
- typedef wifi_config [vxd::cloud::agent::proto::wifi_list](#)
wifi_config

Enumerations

- enum [vxd::cloud::agent::proto::event_status](#) { [vxd::cloud::agent::proto::ES_OK](#), [vxd::cloud::agent::proto::ES_ERROR](#), [vxd::cloud::agent::proto::ES_INVALID](#) }
Event status.
- enum [vxd::cloud::agent::proto::event_type](#) { [vxd::cloud::agent::proto::ET_MOTION](#), [vxd::cloud::agent::proto::ET_SOUND](#), [vxd::cloud::agent::proto::ET_NET](#), [vxd::cloud::agent::proto::ET_RECORD](#), [vxd::cloud::agent::proto::ET_MEMORYCARD](#), [vxd::cloud::agent::proto::ET_WIFI](#), [vxd::cloud::agent::proto::ET_CUSTOM](#), [vxd::cloud::agent::proto::ET_INVALID](#) }
Types of events.
- enum [vxd::cloud::agent::proto::memorycard_status](#) { [vxd::cloud::agent::proto::MCS_NONE](#), [vxd::cloud::agent::proto::MCS_NORMAL](#), [vxd::cloud::agent::proto::MCS_NEED_FORMAT](#), [vxd::cloud::agent::proto::MCS_FORMATTING](#), [vxd::cloud::agent::proto::MCS_INITIALIZATION](#), [vxd::cloud::agent::proto::MCS_INVALID](#) }
Memory card status.
- enum [vxd::cloud::agent::proto::wifi_encryption](#) { [vxd::cloud::agent::proto::WFE_OPEN](#), [vxd::cloud::agent::proto::WFE_WEP](#), [vxd::cloud::agent::proto::WFE_WPA](#), [vxd::cloud::agent::proto::WFE_WPA2](#), [vxd::cloud::agent::proto::WFE_WPA_ENTERPRISE](#), [vxd::cloud::agent::proto::WFE_WPA2_ENTERPRISE](#), [vxd::cloud::agent::proto::WFE_INVALID](#) }
WiFi encryption type.
- enum [vxd::cloud::agent::proto::wifi_network_state](#) { [vxd::cloud::agent::proto::WNS_UNKNOWN](#), [vxd::cloud::agent::proto::WNS_INITIALIZE_0](#), [vxd::cloud::agent::proto::WNS_INITIALIZE_1](#), [vxd::cloud::agent::proto::WNS_TRY_CONNECT](#), [vxd::cloud::agent::proto::WNS_RECEIVING_IP](#), [vxd::cloud::agent::proto::WNS_CONNECTED](#), [vxd::cloud::agent::proto::WNS_DISCONNECTED](#) }
WiFi connection state.

Functions


- `std::string vxg::cloud::agent::proto::name () const`

11.10.1 Detailed Description


VXG Cloud CM protocol objects

11.11 event-manager.h File Reference

```
#include <agent/event-state.h>
#include <agent/event-stream.h>
#include <agent/timeline-synchronizer.h>
#include <utils/queued-handler.h>
Include dependency graph for event-manager.h:
```



This graph shows which files directly or indirectly include this file:



Data Structures

- class `vxg::cloud::agent::event_manager`
- struct `vxg::cloud::agent::event_manager::config`
- struct `vxg::cloud::agent::event_manager::event_state_report_cb`

Namespaces

- [vsg](#)
- [vsg::cloud](#)
- [vsg::cloud::agent](#)


VXG Cloud Agent namespace.

Typedefs


- using [vsg::cloud::agent::event_state_ptr](#) = `std::shared_ptr< event_state >`

11.13 event-stream.h File Reference

```
#include <vector>
#include <agent-proto/proto.h>
Include dependency graph for event-stream.h:
```



This graph shows which files directly or indirectly include this file:



Data Structures

- class `vvg::media::ffmpeg::Sink`

Base ffmpeg sink class.


Namespaces

- vxg
- vxg::media
- vxg::media::ffmpeg

11.15 ffmpeg_source.cc File Reference

```
#include <streamer/ffmpeg_sink.h>
#include <streamer/ffmpeg_source.h>
#include <iomanip>
#include <iostream>
```

Include dependency graph for ffmpeg_source.cc:



Namespaces


- vxg
- vxg::media

11.16 ffmpeg_source.h File Reference

```
#include "base_streamer.h"
#include "ffmpeg_common.h"
Include dependency graph for ffmpeg_source.h:
```



This graph shows which files directly or indirectly include this file:



Data Structures

- class [vvg::media::ffmpeg::Source](#)
Base *ffmpeg* source class.

Namespaces

- [vvg](#)
- [vvg::media](#)
- [vvg::media::ffmpeg](#)

11.17 logging.h File Reference

```


#include <spdlog/spdlog.h>
#include <spdlog/async.h>
#include <spdlog/async_logger.h>
#include <spdlog/cfg/env.h>
#include <spdlog/fmt/bin_to_hex.h>
#include <spdlog/sinks/dist_sink.h>
#include <spdlog/sinks/rotating_file_sink.h>
#include <spdlog/sinks/stdout_color_sinks.h>
#include <spdlog/sinks/syslog_sink.h>
#include <spdlog/sinks/tcp_sink.h>
#include <utils/loguru.h>
#include <fstream>

```

Include dependency graph for `logging.h`:



This graph shows which files directly or indirectly include this file:



Data Structures

- class `vxg::logger`
Logger class, current implementation based on spdlog.
- struct `vxg::logger::options`

Namespaces

- `vxg`

11.18 mainpage.md File Reference


11.19 manager.h File Reference

```


#include <agent-proto/command-handler.h>
#include <agent/callback.h>
#include <agent/config.h>
#include <agent/event-stream.h>
#include <cloud/CloudShareConnection.h>
#include <agent/stream-manager.h>
#include <agent/stream.h>
#include <agent/upload.h>
#include <net/http.h>
#include <utils/logging.h>
#include <agent/direct-upload-storage.h>
#include <agent/event-manager.h>
#include <agent/timeline-synchronizer.h>

```

Include dependency graph for manager.h:



This graph shows which files directly or indirectly include this file:



Data Structures

- class [vsg::cloud::agent::manager](#)
VXG Cloud agent manager class.

Namespaces

- [vsg](#)
- [vsg::cloud](#)
- [vsg::cloud::agent](#)
VXG Cloud Agent namespace.

Functions

- `std::string vsg::cloud::agent::version ()`
VXG Cloud Agent library version.


11.20 meson.build File Reference

11.21 queued-handler.h File Reference


```
#include <net/transport.h>
#include <functional>
```

```
#include <thread>
```

Include dependency graph for queued-handler.h:



This graph shows which files directly or indirectly include this file:



Data Structures

- class [vsg::cloud::utils::queued_async_handler< T >](#)

Namespaces


- [vsg](#)
- [vsg::cloud](#)
- [vsg::cloud::utils](#)

11.22.1 Detailed Description

RTMP sink

11.23 rtmp_source.h File Reference

```
#include "ffmpeg_source.h"
#include "stream.h"
Include dependency graph for rtmp_source.h:
```



Data Structures

- class `vvg::media::rtmp_source`
RTMP source class.

Namespaces


- vxg
- vxg::media

11.23.1 Detailed Description

RTMP source

11.24 rtsp-stream.h File Reference

```
#include <functional>
#include <agent/stream.h>
#include <streamer/rtsp_source.h>
Include dependency graph for rtsp-stream.h:
```




- Implementation of the `media::stream` with RISP source and NIY stubs.

- VXG Cloud Agent namespace.*

Include dependency graph for rtsp_source.h:

This graph shows which files directly or indirectly include this file:



Data Structures

- class `vvg::media::rtsp_source`
RTSP source class.

Namespaces

- `vvg`
- `vvg::media`

Typedefs

- using `vvg::media::rtsp_source_ptr` = `std::shared_ptr< rtsp_source >`

11.25.1 Detailed Description


RTSP source

11.26 stream-storage.h File Reference

```
#include <agent-proto/objects/config.h>
```

```
#include <agent/stream.h>
```

Include dependency graph for stream-storage.h:



Data Structures

- class [vvg::cloud::stream_storage](#)

Namespaces

- [vvg](#)
- [vvg::cloud](#)


11.27 stream.h File Reference

```
#include <map>
#include <memory>
#include <regex>
#include <streamer/base_streamer.h>
#include <utils/queued-handler.h>
#include <utils/utils.h>
```

Include dependency graph for streamer/stream.h:



This graph shows which files directly or indirectly include this file:



Data Structures

- struct `vxg::media::stream_error::report`
Media stream error report simple object.
- class `vxg::media::stream`
base media stream abstract class

Namespaces


- vxg
 - vxg::media
 - vxg::media::stream_error
- Media stream error namespace.*

Enumerations


- enum `vxg::media::stream_error::origin` : int { `vxg::media::stream_error::origin::O_SOURCE`, `vxg::media::stream_error::origin::O_UNKNOWN` }
Origin of the error.
- enum `vxg::media::stream_error::error` : int { `vxg::media::stream_error::error::E_CONNECT`, `vxg::media::stream_error::error::E_UNKNOWN` }
Error code.

11.28 stream.h File Reference

```
#include <map>
#include <memory>
#include <regex>
#include <agent-proto/objects/config.h>
#include <streamer/rtmp_sink.h>
#include <streamer/stream.h>
#include <utils/utils.h>
Include dependency graph for agent/stream.h:
```



This graph shows which files directly or indirectly include this file:



Data Structures

- class `vvg::cloud::agent::media::stream_callbacks`
Cloud agent media stream callbacks abstract class.
- class `vvg::cloud::agent::media::stream_callbacks_stub`
- class `vvg::cloud::agent::media::stream`
Cloud agent media stream abstract class.

Namespaces

- `vvg`
- `vvg::cloud`
- `vvg::cloud::agent`
VXG Cloud Agent namespace.
- `vvg::cloud::agent::media`


Typedefs

- using `vvg::cloud::agent::media::stream_ptr` = `std::shared_ptr< stream >`


11.29 timeline-synchronizer.h File Reference

```
#include <utils/profile.h>
#include <atomic>
#include <future>
#include <agent/timeline.h>
```

Include dependency graph for `timeline-synchronizer.h`:



This graph shows which files directly or indirectly include this file:



Data Structures

- class [vsg::cloud::agent::synchronizer](#)
- struct [vsg::cloud::agent::synchronizer::config](#)
- struct [vsg::cloud::agent::synchronizer::segmenter](#)
- struct [vsg::cloud::agent::synchronizer::sync_request](#)

Namespaces

- [vsg](#)
- [vsg::cloud](#)
- [vsg::cloud::agent](#)

VXG Cloud Agent namespace.

Typedefs

- using [vsg::cloud::agent::synchronizer_ptr](#) = `std::shared_ptr< synchronizer >`


11.30 timeline.h File Reference

```
#include <agent-proto/proto.h>
#include <net/http.h>
#include <utils/logging.h>
#include <utils/profile.h>
#include <utils/utils.h>
#include <cloud/CloudAPIEndpoints.h>
#include <cloud/cloud_api_v4.h>
#include <fstream>
#include <memory>
#include <vector>
```

Include dependency graph for timeline.h:



This graph shows which files directly or indirectly include this file:



Data Structures

- struct [vsg::cloud::period](#)
- class [vsg::cloud::timed_storage](#)
- struct [vsg::cloud::timed_storage::item](#)
- class [vsg::cloud::cloud_storage](#)
- class [vsg::cloud::timeline< T >](#)
- class [vsg::cloud::sync::timeline](#)

Namespaces

- [vsg](#)
- [vsg::cloud](#)
- [vsg::cloud::sync](#)

Typedefs

- typedef [std::shared_ptr< timed_storage >](#) [vsg::cloud::timed_storage_ptr](#)
- using [vsg::cloud::sync::timeline_ptr](#) = [std::shared_ptr< timeline >](#)


Functions

- bool [vsg::cloud::operator<](#) (const [timed_storage::item_ptr](#) l, const [timed_storage::item_ptr](#) r)


11.31 unset-helper.h File Reference

```
#include <chrono>
#include <limits>
#include <nlohmann/json.hpp>
#include <string>
#include <vector>
```

Include dependency graph for unset-helper.h:



This graph shows which files directly or indirectly include this file:



Data Structures

- struct [alter_bool](#)

alternative bool class Standard bool type has two states, this class adds 3rd state - undefined.

Namespaces

- [vxg](#)
- [vxg::cloud](#)
- [vxg::cloud::time_spec](#)

time point

Functions

- **std::string** [unset_value_for_impl](#) (**std::string** *)
- int [unset_value_for_impl](#) (int *)
Returns value of int type that can be treated as unset.
- double [unset_value_for_impl](#) (double *)
- uint64_t [unset_value_for_impl](#) (uint64_t *)
- int64_t [unset_value_for_impl](#) (int64_t *)
- [vxg::cloud::time](#) [unset_value_for_impl](#) ([vxg::cloud::time](#) *)
- [vxg::cloud::duration](#) [unset_value_for_impl](#) ([vxg::cloud::duration](#) *)

- `nlohmann::json unset_value_for_impl (nlohmann::json *)`
- `template<typename T >
T unset_value_for ()`
Template function which returns object value treated as 'unset' or uninitialized.
- `template<typename T >
std::vector< T > unset_value_for_impl (std::vector< T > *)`
- `template<typename T >
T unset_value_for_impl (T *)`
- `template<typename T >
bool __is_unset (T)`
Used for objects constructed from json, helps to check if original json object has specific field.
- `template<> bool __is_unset< int > (int t)`
Predicate function checks if int value was not initialized.
- `template<> bool __is_unset< std::string > (std::string t)`
- `template<> bool __is_unset< double > (double t)`
- `template<> bool __is_unset< vxg::cloud::time > (vxg::cloud::time t)`
- `template<> bool __is_unset< vxg::cloud::duration > (vxg::cloud::duration t)`
- `template<> bool __is_unset< nlohmann::json > (nlohmann::json t)`
- `template<> bool __is_unset< std::nullptr_t > (std::nullptr_t t)`
- `template<typename T >
bool __is_unset (nlohmann::json t)`
- `template<> bool __is_unset< alter_bool > (alter_bool t)`

Variables

- `const std::string UnsetString`
- `const vxg::cloud::time UnsetTime`
- `const vxg::cloud::duration UnsetDuration`
- `const int UnsetInt`
- `const double UnsetFloat`
- `const double UnsetDouble`
- `const uint64_t UnsetUInt64`
- `const int64_t UnsetInt64`

11.31.1 Function Documentation

11.31.1.1 __is_unset() [1/2]

```
template<typename T >
bool __is_unset (
    nlohmann::json t ) [inline]
```

Definition at line 155 of file unset-helper.h.

11.31.1.2 __is_unset() [2/2]

```
template<typename T >
bool __is_unset (
    T ) [inline]
```

Used for objects constructed from json, helps to check if original json object has specific field.

You need to declare template specification for new types.

See also

[__is_unset<int>\(int t\)](#)

Template Parameters

<i>T</i>	object of type
----------	----------------

Returns

true If object's field was actually set during construction, i.e. original json has such field in it's body.

false If object's field wasn't set, original json has no such field. It's also possible that json has such field but its value is set to value treated as unset value.

See also

[__is_unset<>\(\)](#)

Definition at line 104 of file unset-helper.h.

11.31.1.3 __is_unset< alter_bool >()

```
template<>
bool __is_unset< alter_bool > (
    alter_bool t ) [inline]
```

Definition at line 219 of file unset-helper.h.

11.31.1.4 __is_unset< double >()

```
template<>
bool __is_unset< double > (
    double t ) [inline]
```

Definition at line 126 of file unset-helper.h.

11.31.1.5 __is_unset< int >()

```
template<>
bool __is_unset< int > (
    int t ) [inline]
```

Predicate function checks if int value was not initialized.

Template Parameters

<i>int</i>	
------------	--

Parameters

<i>t</i>	
----------	--

Returns

true value is uninitialized.

false value is initialized.

See also

[unset_value_for<int>\(\)](#)

Definition at line 116 of file unset-helper.h.

11.31.1.6 `__is_unset<nlohmann::json>()`

```
template<>
bool __is_unset< nlohmann::json > (
    nlohmann::json t ) [inline]
```

Definition at line 141 of file unset-helper.h.

11.31.1.7 `__is_unset<std::nullptr_t>()`

```
template<>
bool __is_unset< std::nullptr_t > (
    std::nullptr_t t ) [inline]
```

Definition at line 150 of file unset-helper.h.

11.31.1.8 `__is_unset<std::string>()`

```
template<>
bool __is_unset< std::string > (
    std::string t ) [inline]
```

Definition at line 121 of file unset-helper.h.

11.31.1.9 __is_unset< vxg::cloud::duration >()

```
template<>
bool __is_unset< vxg::cloud::duration > (
    vxg::cloud::duration t ) [inline]
```

Definition at line 136 of file unset-helper.h.

11.31.1.10 __is_unset< vxg::cloud::time >()

```
template<>
bool __is_unset< vxg::cloud::time > (
    vxg::cloud::time t ) [inline]
```

Definition at line 131 of file unset-helper.h.

11.31.1.11 unset_value_for()

```
template<typename T >
T unset_value_for ( )
```

Template function which returns object value treated as 'unset' or uninitialized.

Template Parameters

<i>T</i>	
----------	--

Returns

T Value equals to conditionally 'unset'.

Definition at line 73 of file unset-helper.h.

11.31.1.12 unset_value_for_impl() [1/10]

```
double unset_value_for_impl (
    double * ) [inline]
```

Definition at line 39 of file unset-helper.h.

11.31.1.13 unset_value_for_impl() [2/10]

```
int unset_value_for_impl (  
    int * ) [inline]
```

Returns value of int type that can be treated as unset.

Returns

int

Definition at line 35 of file unset-helper.h.

11.31.1.14 unset_value_for_impl() [3/10]

```
int64_t unset_value_for_impl (  
    int64_t * ) [inline]
```

Definition at line 47 of file unset-helper.h.

11.31.1.15 unset_value_for_impl() [4/10]

```
nlohmann::json unset_value_for_impl (  
    nlohmann::json * ) [inline]
```

Definition at line 62 of file unset-helper.h.

11.31.1.16 unset_value_for_impl() [5/10]

```
std::string unset_value_for_impl (  
    std::string * ) [inline]
```

Definition at line 27 of file unset-helper.h.

11.31.1.17 unset_value_for_impl() [6/10]

```
template<typename T >  
std::vector<T> unset_value_for_impl (  
    std::vector< T > * ) [inline]
```

Definition at line 78 of file unset-helper.h.

11.31.1.18 unset_value_for_impl() [7/10]

```
template<typename T >
T unset_value_for_impl (
    T * )
```

Definition at line 85 of file unset-helper.h.

11.31.1.19 unset_value_for_impl() [8/10]

```
uint64_t unset_value_for_impl (
    uint64_t * ) [inline]
```

Definition at line 43 of file unset-helper.h.

11.31.1.20 unset_value_for_impl() [9/10]

```
vxg::cloud::duration unset_value_for_impl (
    vxg::cloud::duration * ) [inline]
```

Definition at line 57 of file unset-helper.h.

11.31.1.21 unset_value_for_impl() [10/10]

```
vxg::cloud::time unset_value_for_impl (
    vxg::cloud::time * ) [inline]
```

Definition at line 51 of file unset-helper.h.

11.31.2 Variable Documentation

11.31.2.1 UnsetDouble

```
const double UnsetDouble
```

Definition at line 229 of file unset-helper.h.

11.31.2.2 UnsetDuration

```
const vxg::cloud::duration UnsetDuration
```

Definition at line 225 of file unset-helper.h.

11.31.2.3 UnsetFloat

```
const double UnsetFloat
```

Definition at line 228 of file unset-helper.h.

11.31.2.4 UnsetInt

```
const int UnsetInt
```

Definition at line 227 of file unset-helper.h.

11.31.2.5 UnsetInt64

```
const int64_t UnsetInt64
```

Definition at line 231 of file unset-helper.h.

11.31.2.6 UnsetString

```
const std::string UnsetString
```

Definition at line 223 of file unset-helper.h.

11.31.2.7 UnsetTime

```
const vxg::cloud::time UnsetTime
```

Definition at line 224 of file unset-helper.h.

11.31.2.8 UnsetUInt64


```
const uint64_t UnsetUInt64
```

Definition at line 230 of file unset-helper.h.


11.32 utils.h File Reference

```
#include <chrono>
#include <memory>
#include <random>
#include <regex>
#include <stdexcept>
#include <string>
```

Include dependency graph for utils.h:



This graph shows which files directly or indirectly include this file:



Data Structures

- struct [vxg::cloud::utils::uri](#)
- struct [vxg::cloud::utils::motion::map](#)

Namespaces

- [vsg](#)
- [vsg::cloud](#)
- [vsg::cloud::time_spec](#)
 - time point*
- [vsg::cloud::utils](#)
- [vsg::cloud::utils::time](#)
- [vsg::cloud::utils::motion](#)
- [vsg::cloud::utils::gcc_abi](#)
- [std](#)

Typedefs

- using [vsg::cloud::time_spec::precision_ratio](#) = [std::micro](#)

Functions

- void [vsg::cloud::utils::set_thread_name](#) ([std::string](#) name)
- [cloud::time](#) [vsg::cloud::utils::time::now](#) ()
- [std::string](#) [vsg::cloud::utils::time::now_ISO8601.UTC](#) ()
- [std::string](#) [vsg::cloud::utils::time::now_ISO8601.UTC_packed](#) ()
- [std::string](#) [vsg::cloud::utils::time::to_iso_8601](#) ([cloud::time](#) t)
- [std::string](#) [vsg::cloud::utils::time::to_iso](#) ([cloud::time](#) t)
- [std::string](#) [vsg::cloud::utils::time::to_iso2](#) ([cloud::time](#) t)
- [std::string](#) [vsg::cloud::utils::time::to_iso_packed](#) ([cloud::time](#) t)
- [std::string](#) [vsg::cloud::utils::time::to_iso_local](#) ([cloud::time](#) t)
- [cloud::time](#) [vsg::cloud::utils::time::from_double](#) ([double](#) t)
- [double](#) [vsg::cloud::utils::time::to_double](#) ([cloud::time](#) t)
- [cloud::time](#) [vsg::cloud::utils::time::from_iso](#) ([std::string](#) st)
- [cloud::time](#) [vsg::cloud::utils::time::from_iso2](#) ([std::string](#) st)
- [cloud::time](#) [vsg::cloud::utils::time::from_iso_packed](#) ([std::string](#) st)
- bool [vsg::cloud::utils::time::iso_time_valid](#) (const [std::string](#) &s)
- [cloud::time](#) [vsg::cloud::utils::time::null](#) ()
- [cloud::time](#) [vsg::cloud::utils::time::epoch](#) ()
- [cloud::time](#) [vsg::cloud::utils::time::max](#) ()
- bool [vsg::cloud::utils::time::is_iso_packed](#) (const [std::string](#) &s)
- bool [vsg::cloud::utils::time::is_iso](#) (const [std::string](#) &s)
- [template](#)<[typename](#)... Args>
 - [std::string](#) [vsg::cloud::utils::string_format](#) (const [std::string](#) &format, Args... args)
- [std::string](#) [vsg::cloud::utils::string_trim](#) (const [std::string](#) &name, [std::regex](#) regx)
- [std::string](#) [vsg::cloud::utils::string_trim](#) (const [std::string](#) &name)
- [std::vector](#)< [std::string](#) > [vsg::cloud::utils::string_split](#) (const [std::string](#) &s, char delimiter)
- bool [vsg::cloud::utils::string_startswith](#) ([std::string](#) const &fullString, [std::string](#) const &start)
- bool [vsg::cloud::utils::string_endswith](#) ([std::string](#) const &fullString, [std::string](#) const &ending)
- bool [vsg::cloud::utils::string_replace](#) ([std::string](#) &str, const [std::string](#) &from, const [std::string](#) &to)
- [std::string](#) [vsg::cloud::utils::string_urlencode](#) (const [std::string](#) &value)
- [std::string](#) [vsg::cloud::utils::string_urldecode](#) (const [std::string](#) &text)
- [std::string](#) [vsg::cloud::utils::string_tolower](#) (const [std::string](#) &s)
- [std::string](#) [vsg::cloud::utils::string_toupper](#) (const [std::string](#) &s)
- bool [vsg::cloud::utils::string_contains](#) ([std::string](#) s, char c)
- bool [vsg::cloud::utils::string_contains](#) ([std::string](#) s, [std::string](#) substring)
- [std::string](#) [vsg::cloud::utils::dirname](#) (const [std::string](#) &filepath)
- [std::string](#) [vsg::cloud::utils::gcc_abi::demangle](#) ([std::string](#) name)
- [std::string](#) [vsg::cloud::utils::random_string](#) (size_t length=32)
- [template](#)<[typename](#) T , [typename](#)... CONSTRUCTOR_ARGS>
 - [std::unique_ptr](#)< T > [std::make_unique](#) (CONSTRUCTOR_ARGS &&... constructor_args)

Index

- `__BASE_STREAMER_H`
 - `base_streamer.h`, 301
- `__is_unset`
 - `unset-helper.h`, 333
- `__is_unset< alter_bool >`
 - `unset-helper.h`, 334
- `__is_unset< double >`
 - `unset-helper.h`, 334
- `__is_unset< int >`
 - `unset-helper.h`, 334
- `__is_unset< nlohmann::json >`
 - `unset-helper.h`, 335
- `__is_unset< std::nullptr_t >`
 - `unset-helper.h`, 335
- `__is_unset< std::string >`
 - `unset-helper.h`, 335
- `__is_unset< vxg::cloud::duration >`
 - `unset-helper.h`, 335
- `__is_unset< vxg::cloud::time >`
 - `unset-helper.h`, 336
- `__notify_record_event`
 - `vxg::cloud::agent::manager`, 164
- `__transport_to_ff`
 - `vxg::media::rtsp_source`, 215
- `_squash_periods`
 - `vxg::cloud::sync::timeline`, 275
 - `vxg::cloud::timeline< T >`, 273
- `_update_storage_status`
 - `vxg::cloud::agent::manager`, 164
- `~ISink`
 - `vxg::media::Streamer::ISink`, 139
- `~Sink`
 - `vxg::media::ffmpeg::Sink`, 225
- `~Source`
 - `vxg::media::ffmpeg::Source`, 231
- `~cloud_storage`
 - `vxg::cloud::cloud_storage`, 107
- `~event_manager`
 - `vxg::cloud::agent::event_manager`, 118
- `~event_state`
 - `vxg::cloud::agent::event_state`, 121
- `~event_state_changed_cb`
 - `vxg::cloud::agent::event_state::event_state_changed_cb`, vxg::media::Streamer::StreamInfo, 260
 - 124
- `~event_state_report_cb`
 - `vxg::cloud::agent::event_manager::event_state_report_cb`, vxg::media::Streamer::StreamInfo, 260
 - 127
- `~event_stream`
 - `vxg::cloud::agent::event_stream`, 131
- `~queued_async_handler`
 - `vxg::cloud::utils::queued_async_handler< T >`, 203
- `~rtsp_stream`
 - `vxg::cloud::agent::media::rtsp_stream`, 218
- `~segmenter`
 - `vxg::cloud::agent::synchronizer::segmenter`, 220
- `~stream`
 - `vxg::cloud::agent::media::stream`, 241
 - `vxg::media::stream`, 237
- `~stream_callbacks`
 - `vxg::cloud::agent::media::stream_callbacks`, 243
- `~stream_callbacks_stub`
 - `vxg::cloud::agent::media::stream_callbacks_stub`, 249
- `~stream_storage`
 - `vxg::cloud::stream_storage`, 257
- `~timed_storage`
 - `vxg::cloud::timed_storage`, 270
- `~timeline`
 - `vxg::cloud::sync::timeline`, 275
- `A_BOTTOM`
 - `vxg::cloud::agent::proto`, 53
- `A_INVALID`
 - `vxg::cloud::agent::proto`, 53
- `A_LEFT`
 - `vxg::cloud::agent::proto`, 53
- `A_RIGHT`
 - `vxg::cloud::agent::proto`, 53
- `A_STOP`
 - `vxg::cloud::agent::proto`, 53
- `A_TOP`
 - `vxg::cloud::agent::proto`, 53
- `A_ZOOM_IN`
 - `vxg::cloud::agent::proto`, 53
- `A_ZOOM_OUT`
 - `vxg::cloud::agent::proto`, 53
- `AC_AAC`
 - `vxg::media::Streamer::StreamInfo`, 260
- `AC_G711_A`
 - `vxg::media::Streamer::StreamInfo`, 260
- `AC_G711_U`
 - `vxg::media::Streamer::StreamInfo`, 260
- `AC_G726`
 - `vxg::media::Streamer::StreamInfo`, 260
- `AC_LPCM`
 - `vxg::media::Streamer::StreamInfo`, 260
- `AC_OPUS`
 - `vxg::media::Streamer::StreamInfo`, 260

- AC_UNKNOWN
 - vxg::media::Streamer::StreamInfo, 260
- action
 - vxg::cloud::agent::ptz_command, 199
 - vxg::cloud::agent::ptz_preset, 202
- actions
 - vxg::cloud::agent::ptz_config, 200
- active
 - vxg::cloud::agent::event_config, 115
 - vxg::cloud::agent::event_state, 122
- AF_AAC
 - vxg::cloud::agent::proto, 51
- AF_ADPCM
 - vxg::cloud::agent::proto, 51
- AF_G711A
 - vxg::cloud::agent::proto, 51
- AF_G711U
 - vxg::cloud::agent::proto, 51
- AF_INVALID
 - vxg::cloud::agent::proto, 51
- AF_MP3
 - vxg::cloud::agent::proto, 51
- AF_NELLY
 - vxg::cloud::agent::proto, 51
- AF_NELLY16
 - vxg::cloud::agent::proto, 51
- AF_NELLY8
 - vxg::cloud::agent::proto, 51
- AF_OPUS
 - vxg::cloud::agent::proto, 51
- AF_RAW
 - vxg::cloud::agent::proto, 51
- AF_SPEEX
 - vxg::cloud::agent::proto, 51
- AFF_AU_G711U
 - vxg::cloud::agent::proto, 50
- AFF_INVALID
 - vxg::cloud::agent::proto, 50
- AFF_MP3
 - vxg::cloud::agent::proto, 50
- AFF_WAV_PCM
 - vxg::cloud::agent::proto, 50
- agent_config
 - cloud-agent-minimal.cc, 306
 - cloud-agent.cc, 309
- alignment
 - vxg::cloud::agent::osd_config, 191
 - vxg::cloud::agent::proto::osd_caps, 187
- alter_bool, 73
 - alter_bool, 74
 - B_FALSE, 74
 - B_INVALID, 74
 - B_TRUE, 74
 - from_json, 75
 - n_alter_bool, 73
 - operator bool, 74
 - operator=, 74
 - to_json, 75
 - val, 75
- api_uri
 - vxg::cloud::agent::access_token, 72
- app-dev.md, 299
- arm-example.txt, 299
- async_ready
 - vxg::cloud::timed_storage::item, 152
- async_store_finished_cb
 - vxg::cloud::sync::timeline, 274
 - vxg::cloud::timed_storage, 270
- async_store_is_canceled_cb
 - vxg::cloud::sync::timeline, 274
 - vxg::cloud::timed_storage, 270
- ASYNC_TCP
 - vxg::media::rtsp_source, 214
- attach_qos_report_to_motion
 - vxg::cloud::agent::event_manager::config, 108
- AUDIO
 - vxg::media::Streamer, 68
- audio
 - vxg::cloud::agent::proto::stream_config, 255
 - vxg::cloud::agent::supported_stream_config, 262
 - vxg::media::Streamer::StreamInfo, 261
- audio_es
 - vxg::cloud::agent::supported_streams_config, 264
- audio_file_format
 - vxg::cloud::agent::proto, 50
- audio_file_formats
 - vxg::cloud::agent::proto::audio_caps, 76
- audio_format
 - vxg::cloud::agent::proto, 50
- AUDIO_SEQ_HDR
 - vxg::media::Streamer, 68
- AudioCodec
 - vxg::media::Streamer::StreamInfo, 259
- B_FALSE
 - alter_bool, 74
- B_INVALID
 - alter_bool, 74
- B_TRUE
 - alter_bool, 74
- backward
 - vxg::cloud::agent::proto::audio_caps, 77
- backward_formats
 - vxg::cloud::agent::proto::audio_caps, 77
- base_streamer.h, 299
 - __BASE_STREAMER_H, 301
- begin
 - vxg::cloud::period, 196
- bitrate
 - vxg::media::Streamer::StreamInfo::AudioInfo, 86
 - vxg::media::Streamer::StreamInfo::VideoInfo, 294
- bkg_color
 - vxg::cloud::agent::osd_config, 191
 - vxg::cloud::agent::proto::osd_caps, 187
- bkg_transp
 - vxg::cloud::agent::osd_config, 191
 - vxg::cloud::agent::proto::osd_caps, 187

- brightness
 - vxg::cloud::agent::proto::video_caps, 280
 - vxg::cloud::agent::proto::video_config, 287
- brt
 - vxg::cloud::agent::proto::audio_stream_config, 85
 - vxg::cloud::agent::proto::stream_caps::caps_audio_object, rtsp_url, 309
 - 101
 - vxg::cloud::agent::proto::stream_caps::caps_video_object, vxg_cloud_token, 309
 - 103
 - vxg::cloud::agent::proto::video_stream_config, 291
- build-system.md, 301
- callback.h, 301
- cam_base_uri
 - vxg::cloud::agent::access_token, 72
- CANCELED
 - vxg::cloud::agent::synchronizer, 267
- canceled
 - vxg::cloud::agent::synchronizer::segmenter, 221
- caps
 - vxg::cloud::agent::audio_config, 79
 - vxg::cloud::agent::audio_detection_config, 83
 - vxg::cloud::agent::event_config, 115
 - vxg::cloud::agent::osd_config, 191
 - vxg::cloud::agent::proto::motion_detection_config, 180
 - vxg::cloud::agent::proto::video_config, 287
- caps.h, 302
 - ignore_exception, 304
 - json, 305
- caps_audio
 - vxg::cloud::agent::proto::stream_caps, 253
- caps_eq
 - vxg::cloud::agent::event_config, 114
- caps_video
 - vxg::cloud::agent::proto::stream_caps, 254
- category
 - vxg::cloud::timed_storage::item, 153
- channels
 - vxg::media::Streamer::StreamInfo::AudioInfo, 87
- chunks_done
 - vxg::cloud::agent::synchronizer::segmenter, 221
- chunks_failed
 - vxg::cloud::agent::synchronizer::segmenter, 221
- chunks_planned
 - vxg::cloud::agent::synchronizer::segmenter, 221
- clear
 - vxg::cloud::period, 195
 - vxg::cloud::timed_storage::item, 153
- cloud-agent-minimal.cc, 305
 - agent_config, 306
 - main, 306
 - parse_args, 306
 - props, 306
 - quit, 307
 - rtsp_url, 307
 - signal_handler, 306
 - vxg_cloud_token, 307
- cloud-agent.cc, 307
 - agent_config, 309
 - main, 308
 - parse_args, 308
 - props, 309
 - quit, 309
 - signal_handler, 308
 - cloud_storage
 - vxg::cloud::cloud_storage, 107
 - code
 - vxg::media::stream_error::report, 205
 - codec
 - vxg::media::Streamer::StreamInfo::AudioInfo, 87
 - vxg::media::Streamer::StreamInfo::VideoInfo, 294
 - columns
 - vxg::cloud::agent::proto::motion_detection_config, 180
 - compile.md, 310
 - config
 - vxg::cloud::agent::event_state, 122
 - config.h, 310
 - contrast
 - vxg::cloud::agent::proto::video_caps, 280
 - vxg::cloud::agent::proto::video_config, 287
 - crash_logfile_path
 - vxg::logger::options, 184
 - create
 - vxg::cloud::agent::manager, 164
 - vxg::cloud::agent::synchronizer, 267
 - critical
 - vxg::logger, 156
 - cur_seg_start
 - vxg::cloud::agent::synchronizer::segmenter, 222
 - cur_seg_stop
 - vxg::cloud::agent::synchronizer::segmenter, 222
 - custom_event_name
 - vxg::cloud::agent::event_config, 116
- DATA
 - vxg::media::Streamer, 68
- data
 - vxg::cloud::agent::proto::video_clip_info, 284
 - vxg::cloud::timed_storage::item, 153
 - vxg::media::Streamer::MediaFrame, 176
- data_state
 - vxg::cloud::timed_storage::item, 152
- DataCodec
 - vxg::media::Streamer::StreamInfo, 260
- date
 - vxg::cloud::agent::osd_config, 191
 - vxg::cloud::agent::proto::osd_caps, 187
- date_format
 - vxg::cloud::agent::osd_config, 192
 - vxg::cloud::agent::proto::osd_caps, 188
- DC_ONVIF
 - vxg::media::Streamer::StreamInfo, 260
- DC_UNKNOWN
 - vxg::media::Streamer::StreamInfo, 260

- debug
 - vxg::logger, 156
- default_loglevel
 - vxg::logger::options, 184
- delay
 - vxg::cloud::agent::synchronizer::segmenter, 222
- demangle
 - vxg::cloud::utils::gcc_abi, 61
- direct_upload_payload_map
 - vxg::cloud::agent::manager, 163
- direct_upload_payload_map_ptr
 - vxg::cloud::agent::manager, 163
- dirname
 - vxg::cloud::utils, 58
- DONE
 - vxg::cloud::agent::synchronizer, 267
- DROP_BACK
 - vxg::media::Streamer, 68
- DROP_FRONT
 - vxg::media::Streamer, 68
- DropDirection
 - vxg::media::Streamer, 67
- droppable
 - vxg::media::ffmpeg::Sink, 226
 - vxg::media::rtmp_sink, 207
 - vxg::media::Streamer::ISink, 139
- pts
 - vxg::media::Streamer::MediaFrame, 176
- duration
 - vxg::cloud, 44
 - vxg::cloud::period, 195
 - vxg::cloud::time_spec, 56
 - vxg::media::ffmpeg::Sink, 226
 - vxg::media::Streamer::ISink, 139
 - vxg::media::Streamer::MediaFrame, 177
- E_CONNECT
 - vxg::media::stream_error, 66
- E_EOS
 - vxg::media::Streamer, 68
- E_FATAL
 - vxg::media::Streamer, 68
- E_NONE
 - vxg::media::Streamer, 68
- E_PROCESS
 - vxg::media::stream_error, 66
- E_UNKNOWN
 - vxg::media::stream_error, 66
- echo_cancel
 - vxg::cloud::agent::audio_config, 79
 - vxg::cloud::agent::proto::audio_caps, 77
- empty
 - vxg::cloud::timed_storage::item, 152, 153
- enabled
 - vxg::cloud::agent::events_config, 136
 - vxg::cloud::agent::proto::motion_region, 182
- encryption
 - vxg::cloud::agent::proto::wifi_network, 297
- encryption_caps
 - vxg::cloud::agent::proto::wifi_network, 298
- end
 - vxg::cloud::period, 196
- epoch
 - vxg::cloud::utils::time, 62
- erase
 - vxg::cloud::cloud_storage, 107
 - vxg::cloud::stream_storage, 257
 - vxg::cloud::timed_storage, 271
- ERROR
 - vxg::cloud::agent::synchronizer, 267
- error
 - vxg::logger, 157
 - vxg::media::ffmpeg::Sink, 226
 - vxg::media::stream_error, 66
 - vxg::media::Streamer::ISink, 140
 - vxg::media::Streamer::ISource, 147
- ES_ERROR
 - vxg::cloud::agent::proto, 51
- ES_INVALID
 - vxg::cloud::agent::proto, 51
- ES_OK
 - vxg::cloud::agent::proto, 51
- ET_CUSTOM
 - vxg::cloud::agent::proto, 51
- ET_INVALID
 - vxg::cloud::agent::proto, 51
- ET_MEMORYCARD
 - vxg::cloud::agent::proto, 51
- ET_MOTION
 - vxg::cloud::agent::proto, 51
- ET_NET
 - vxg::cloud::agent::proto, 51
- ET_RECORD
 - vxg::cloud::agent::proto, 51
- ET_SOUND
 - vxg::cloud::agent::proto, 51
- ET_WIFI
 - vxg::cloud::agent::proto, 51
- event
 - vxg::cloud::agent::event_config, 116
- event-manager.h, 313
- event-state.h, 314
- event-stream.h, 315
- event_manager
 - vxg::cloud::agent::event_manager, 118
- event_manager_ptr
 - vxg::cloud::agent, 47
- event_state
 - vxg::cloud::agent::event_state, 121
- event_state_changed_cb
 - vxg::cloud::agent::event_state::event_state_changed_cb, 124
- event_state_changed_cb_ptr
 - vxg::cloud::agent::event_state, 120
- event_state_ptr
 - vxg::cloud::agent, 47
- event_state_report_cb

- vxg::cloud::agent::event_manager::event_state_reporter, 126
- event_state_report_cb_ptr
 - vxg::cloud::agent::event_manager, 117
- event_status
 - vxg::cloud::agent::proto, 51
- event_stream
 - vxg::cloud::agent::event_stream, 130
- event_type
 - vxg::cloud::agent::proto, 51
- events
 - vxg::cloud::agent::events_config, 136
- extradata
 - vxg::media::Streamer::StreamInfo::AudioInfo, 87
 - vxg::media::Streamer::StreamInfo::VideoInfo, 294
- ffmpeg_opts_
 - vxg::media::rtsp_source, 216
- ffmpeg_sink.h, 316
- ffmpeg_source.cc, 317
- ffmpeg_source.h, 317
- final_sync_status_reported
 - vxg::cloud::agent::synchronizer::segmenter, 222
- finished
 - vxg::cloud::agent::synchronizer::segmenter, 222
- finit
 - vxg::cloud::agent::event_stream, 131
 - vxg::cloud::sync::timeline, 275
 - vxg::cloud::timed_storage, 271
 - vxg::media::ffmpeg::Sink, 227
 - vxg::media::ffmpeg::Source, 231
 - vxg::media::Streamer::ISink, 140
 - vxg::media::Streamer::ISource, 148
- finit_sink
 - vxg::media::stream, 237
- finit_source
 - vxg::media::stream, 237
- FLV
 - vxg::media::Streamer, 68
- font_color
 - vxg::cloud::agent::osd_config, 192
 - vxg::cloud::agent::proto::osd_caps, 188
- font_size
 - vxg::cloud::agent::osd_config, 192
 - vxg::cloud::agent::proto::osd_caps, 188
- format
 - vxg::cloud::agent::proto::audio_stream_config, 85
 - vxg::cloud::agent::proto::video_stream_config, 291
- formats
 - vxg::cloud::agent::proto::stream_caps::caps_audio_object, 101
 - vxg::cloud::agent::proto::stream_caps::caps_video_object, 103
- fps
 - vxg::cloud::agent::proto::stream_caps::caps_video_object, 104
 - vxg::cloud::agent::proto::video_stream_config, 291
- fragment
 - vxg::cloud::utils::uri, 278
- generate
 - vxg::media::Streamer::StreamInfo::VideoInfo, 295
- from
 - vxg::media::stream_error::report, 205
- from_double
 - vxg::cloud::utils::time, 62
- from_iso
 - vxg::cloud::utils::time, 62
- from_iso2
 - vxg::cloud::utils::time, 62
- from_iso_packed
 - vxg::cloud::utils::time, 62
- from_json
 - alter_bool, 75
- get_event_config
 - vxg::cloud::agent::events_config, 135
- get_events
 - vxg::cloud::agent::event_manager, 118
 - vxg::cloud::agent::event_stream, 131
- get_handler
 - vxg::cloud::utils::queued_async_handler< T >, 204
- get_snapshot
 - vxg::cloud::agent::media::stream_callbacks, 243
 - vxg::cloud::agent::media::stream_callbacks_stub, 249
- get_stream_caps
 - vxg::cloud::agent::media::stream_callbacks, 243
 - vxg::cloud::agent::media::stream_callbacks_stub, 249
- get_stream_config
 - vxg::cloud::agent::media::stream_callbacks, 244
 - vxg::cloud::agent::media::stream_callbacks_stub, 250
- get_supported_stream
 - vxg::cloud::agent::media::stream_callbacks, 244
 - vxg::cloud::agent::media::stream_callbacks_stub, 250
- gop
 - vxg::cloud::agent::proto::stream_caps::caps_video_object, 104
 - vxg::cloud::agent::proto::video_stream_config, 291
- handle_event
 - vxg::cloud::agent::manager, 165
- handle_event_meta_file
 - vxg::cloud::agent::manager, 165
- handle_event_payload_cb
 - vxg::cloud::agent::event_manager, 118
- handle_event_snapshot
 - vxg::cloud::agent::manager, 165
- handler_func
 - vxg::cloud::utils::queued_async_handler< T >, 203
- height
 - vxg::media::Streamer::StreamInfo::VideoInfo, 295
- horz
 - vxg::cloud::agent::proto::video_stream_config, 291

- horz_flip
 - vxg::cloud::agent::proto::video_caps, 281
 - vxg::cloud::agent::proto::video_config, 287
- host
 - vxg::cloud::utils::uri, 278
- HTTP
 - vxg::media::rtsp_source, 214
- HTTPS
 - vxg::media::rtsp_source, 214
- id
 - vxg::cloud::agent::supported_stream_config, 262
- ignore_exception
 - caps.h, 304
- info
 - vxg::logger, 157, 158
- init
 - vxg::cloud::agent::event_stream, 132
 - vxg::cloud::sync::timeline, 275
 - vxg::cloud::timed_storage, 271
 - vxg::media::ffmpeg::Sink, 227
 - vxg::media::ffmpeg::Source, 231, 232
 - vxg::media::rtmp_sink, 207
 - vxg::media::rtmp_source, 211
 - vxg::media::rtsp_source, 215
 - vxg::media::Streamer::ISink, 140
 - vxg::media::Streamer::ISource, 148
- init_sink
 - vxg::media::stream, 237
- init_source
 - vxg::media::stream, 238
- instance
 - vxg::logger, 158
- internal_hidden
 - vxg::cloud::agent::proto::event_caps, 111
- intersects
 - vxg::cloud::agent::synchronizer::segmenter, 221
 - vxg::cloud::period, 195
- ir_light
 - vxg::cloud::agent::proto::video_caps, 281
 - vxg::cloud::agent::proto::video_config, 288
- is_iso
 - vxg::cloud::utils::time, 62
- is_iso_packed
 - vxg::cloud::utils::time, 62
- is_key
 - vxg::media::Streamer::MediaFrame, 177
- is_null
 - vxg::cloud::period, 195
- is_open
 - vxg::cloud::period, 196
- is_valid
 - vxg::cloud::period, 196
- ISink
 - vxg::media::Streamer::ISink, 139
- iso_time_valid
 - vxg::cloud::utils::time, 63
- ISource
 - vxg::media::Streamer::ISource, 147
- item
 - vxg::cloud::timed_storage::item, 152
- item_ptr
 - vxg::cloud::timed_storage, 270
- json
 - caps.h, 305
- JSON_DEFINE_TYPE_INTRUSIVE
 - vxg::cloud::agent::audio_detection_config, 83
 - vxg::cloud::agent::audio_detection_config::audio_detection_conf_cap
 - 81
- last_processed_time
 - vxg::cloud::agent::synchronizer::segmenter, 222
- len
 - vxg::media::Streamer::MediaFrame, 177
- length
 - vxg::cloud::agent::audio_detection_config, 83
- level
 - vxg::cloud::agent::audio_detection_config, 83
 - vxg::cloud::agent::audio_detection_config::audio_detection_conf_cap
 - 81
- list
 - vxg::cloud::cloud_storage, 107
 - vxg::cloud::stream_storage, 257
 - vxg::cloud::sync::timeline, 275
 - vxg::cloud::timed_storage, 271
- load
 - vxg::cloud::cloud_storage, 107
 - vxg::cloud::stream_storage, 257
 - vxg::cloud::sync::timeline, 276
 - vxg::cloud::timed_storage, 271
- loaded
 - vxg::cloud::timed_storage::item, 152
- local_start
 - vxg::cloud::agent::proto::video_clip_info, 284
- local_stop
 - vxg::cloud::agent::proto::video_clip_info, 284
- log_pattern
 - vxg::logger::options, 184
- logfile_max_files
 - vxg::logger::options, 184
- logfile_max_size
 - vxg::logger::options, 185
- logfile_path
 - vxg::logger::options, 185
- logger_ptr
 - vxg::logger, 155
- logging.h, 318
- loglevel
 - vxg::logger, 156
- lvl_crit
 - vxg::logger, 156
- lvl_debug
 - vxg::logger, 156
- lvl_error
 - vxg::logger, 156
- lvl_info
 - vxg::logger, 156

- lvl_off
 - vxg::logger, 156
- lvl_trace
 - vxg::logger, 156
- lvl_warn
 - vxg::logger, 156
- M_AUTO
 - vxg::cloud::agent::proto, 52
- M_INVALID
 - vxg::cloud::agent::proto, 52
- M_OFF
 - vxg::cloud::agent::proto, 52
- M_ON
 - vxg::cloud::agent::proto, 52
- mac
 - vxg::cloud::agent::proto::wifi_network, 298
- main
 - cloud-agent-minimal.cc, 306
 - cloud-agent.cc, 308
- mainpage.md, 319
- make_unique
 - std, 43
- manager.h, 319
- map
 - vxg::cloud::agent::proto::motion_region, 182
 - vxg::cloud::utils::motion::map, 174
- MAX
 - vxg::media::Streamer, 68
- max
 - vxg::cloud::utils::time, 63
- max_regions
 - vxg::cloud::agent::proto::motion_detection_caps, 179
- maximum_number_of_presets
 - vxg::cloud::agent::ptz_config, 200
- MCS_FORMATTING
 - vxg::cloud::agent::proto, 52
- MCS_INITIALIZATION
 - vxg::cloud::agent::proto, 52
- MCS_INVALID
 - vxg::cloud::agent::proto, 52
- MCS_NEED_FORMAT
 - vxg::cloud::agent::proto, 52
- MCS_NONE
 - vxg::cloud::agent::proto, 52
- MCS_NORMAL
 - vxg::cloud::agent::proto, 52
- media_type
 - vxg::cloud::timed_storage::item, 153
- MediaType
 - vxg::media::Streamer, 68
- memorycard_status
 - vxg::cloud::agent::proto, 52
- meson.build, 320
- mic
 - vxg::cloud::agent::proto::audio_caps, 77
- mic_gain
 - vxg::cloud::agent::audio_config, 79
- mic_mute
 - vxg::cloud::agent::audio_config, 79
- Mode
 - vxg::media::Streamer::ISource, 146
- mode
 - vxg::cloud::agent::proto, 52
- mode_
 - vxg::media::Streamer::ISource, 150
- motion_region_shape
 - vxg::cloud::agent::proto, 52
- motion_sensitivity
 - vxg::cloud::agent::proto, 53
- MR_ANY
 - vxg::cloud::agent::proto, 52
- MR_INVALID
 - vxg::cloud::agent::proto, 52
- MR_RECTANGLE
 - vxg::cloud::agent::proto, 52
- MS_FRAME
 - vxg::cloud::agent::proto, 53
- MS_INVALID
 - vxg::cloud::agent::proto, 53
- MS_REGION
 - vxg::cloud::agent::proto, 53
- n_alter_bool
 - alter_bool, 73
- name
 - vxg::cloud::agent::event_config, 115
 - vxg::cloud::agent::proto, 55
 - vxg::cloud::agent::ptz_preset, 202
 - vxg::media::ffmpeg::Sink, 228
 - vxg::media::ffmpeg::Source, 233
 - vxg::media::rtmp_sink, 209
 - vxg::media::rtsp_source, 215
 - vxg::media::Streamer::ISink, 142
 - vxg::media::Streamer::ISource, 148
- name_eq
 - vxg::cloud::agent::event_config, 115
- need_record
 - vxg::cloud::agent::event_state, 122
- negotiate
 - vxg::media::ffmpeg::Sink, 228
 - vxg::media::ffmpeg::Source, 233
 - vxg::media::rtmp_sink, 209
 - vxg::media::Streamer::ISink, 142
 - vxg::media::Streamer::ISource, 148
- networks
 - vxg::cloud::agent::proto::wifi_config, 296
- nlohmann, 25
- NO_PTS
 - vxg::media::Streamer::MediaFrame, 177
- notify
 - vxg::cloud::agent::event_stream, 132
- notify_event
 - vxg::cloud::agent::event_manager, 118
- now
 - vxg::cloud::utils::time, 63
- now_ISO8601_UTC

- vxg::cloud::utils::time, 63
- now_ISO8601.UTC_packed
 - vxg::cloud::utils::time, 63
- nr_level
 - vxg::cloud::agent::proto::video_caps, 281
 - vxg::cloud::agent::proto::video_config, 288
- nr_type
 - vxg::cloud::agent::proto::video_caps, 281
 - vxg::cloud::agent::proto::video_config, 288
- null
 - vxg::cloud::utils::time, 63
- O_SINK
 - vxg::media::stream_error, 66
- O_SOURCE
 - vxg::media::stream_error, 66
- O_UNKNOWN
 - vxg::media::stream_error, 66
- on_audio_file_play
 - vxg::cloud::agent::callback, 90
 - vxg::cloud::agent::manager, 165
- on_bye
 - vxg::cloud::agent::callback, 90
- on_cam_memorycard_recording
 - vxg::cloud::agent::manager, 165
- on_cam_memorycard_synchronize
 - vxg::cloud::agent::manager, 165
- on_cam_memorycard_synchronize_cancel
 - vxg::cloud::agent::manager, 165
- on_cam_ptz
 - vxg::cloud::agent::callback, 90
 - vxg::cloud::agent::manager, 166
- on_cam_ptz_preset
 - vxg::cloud::agent::callback, 91
 - vxg::cloud::agent::manager, 166
- on_cam_upgrade_firmware
 - vxg::cloud::agent::callback, 91
 - vxg::cloud::agent::manager, 166
- on_closed
 - vxg::cloud::agent::manager, 166
- on_direct_upload_url
 - vxg::cloud::agent::manager, 166
- on_error_cb
 - vxg::media::stream, 236
 - vxg::media::Streamer, 67
- on_error_cb_
 - vxg::media::Streamer::ISink, 143
 - vxg::media::Streamer::ISource, 150
- on_event_continue
 - vxg::cloud::agent::event_manager::event_state_report_cb, 127
- on_event_start
 - vxg::cloud::agent::event_manager::event_state_report_cb, 127
- on_event_stop
 - vxg::cloud::agent::event_manager::event_state_report_cb, 127
- on_event_trigger
 - vxg::cloud::agent::event_manager::event_state_report_cb, 127
- on_get_audio_detection
 - vxg::cloud::agent::callback, 92
 - vxg::cloud::agent::manager, 166
- on_get_cam_audio_config
 - vxg::cloud::agent::callback, 92
 - vxg::cloud::agent::manager, 167
- on_get_cam_events_config
 - vxg::cloud::agent::manager, 167
- on_get_cam_memorycard_timeline
 - vxg::cloud::agent::manager, 167
- on_get_cam_video_config
 - vxg::cloud::agent::callback, 92
 - vxg::cloud::agent::manager, 167
- on_get_log
 - vxg::cloud::agent::callback, 93
 - vxg::cloud::agent::manager, 167
- on_get_memorycard_info
 - vxg::cloud::agent::callback, 93
- on_get_motion_detection_config
 - vxg::cloud::agent::callback, 93
 - vxg::cloud::agent::manager, 167
- on_get_osd_config
 - vxg::cloud::agent::callback, 94
 - vxg::cloud::agent::manager, 167
- on_get_ptz_config
 - vxg::cloud::agent::callback, 94
 - vxg::cloud::agent::manager, 168
- on_get_stream_by_event
 - vxg::cloud::agent::manager, 168
- on_get_stream_caps
 - vxg::cloud::agent::manager, 168
- on_get_stream_config
 - vxg::cloud::agent::manager, 168
- on_get_supported_streams
 - vxg::cloud::agent::manager, 168
- on_get_timezone
 - vxg::cloud::agent::callback, 95
 - vxg::cloud::agent::manager, 168
- on_get_wifi_config
 - vxg::cloud::agent::callback, 95
 - vxg::cloud::agent::manager, 168
- on_need_stream_sync_continue
 - vxg::cloud::agent::event_manager::event_state_report_cb, 128
- on_need_stream_sync_start
 - vxg::cloud::agent::event_manager::event_state_report_cb, 128
- on_need_stream_sync_stop
 - vxg::cloud::agent::event_manager::event_state_report_cb, 128
- on_ongoing
 - vxg::cloud::agent::event_state::event_state_changed_cb, 124
- on_prepared
 - vxg::cloud::agent::manager, 169
- on_raw_message

- vxg::cloud::agent::manager, 169
- on_raw_msg
 - vxg::cloud::agent::callback, 96
- on_registered
 - vxg::cloud::agent::callback, 96
 - vxg::cloud::agent::manager, 169
- on_set_activity
 - vxg::cloud::agent::manager, 169
- on_set_audio_detection
 - vxg::cloud::agent::callback, 96
 - vxg::cloud::agent::manager, 169
- on_set_cam_audio_config
 - vxg::cloud::agent::callback, 97
 - vxg::cloud::agent::manager, 169
- on_set_cam_events_config
 - vxg::cloud::agent::manager, 169
- on_set_cam_video_config
 - vxg::cloud::agent::callback, 97
 - vxg::cloud::agent::manager, 170
- on_set_log_enable
 - vxg::cloud::agent::manager, 170
- on_set_motion_detection_config
 - vxg::cloud::agent::callback, 97
 - vxg::cloud::agent::manager, 170
- on_set_osd_config
 - vxg::cloud::agent::callback, 98
 - vxg::cloud::agent::manager, 170
- on_set_periodic_events
 - vxg::cloud::agent::manager, 170
- on_set_stream_by_event
 - vxg::cloud::agent::manager, 170
- on_set_stream_config
 - vxg::cloud::agent::manager, 170
- on_set_timezone
 - vxg::cloud::agent::callback, 98
 - vxg::cloud::agent::manager, 171
- on_set_wifi_config
 - vxg::cloud::agent::callback, 99
 - vxg::cloud::agent::manager, 171
- on_start_backward
 - vxg::cloud::agent::manager, 171
- on_start_backward_audio
 - vxg::cloud::agent::callback, 99
- on_started
 - vxg::cloud::agent::event_state::event_state_changed_cb, 125
- on_stop_backward
 - vxg::cloud::agent::manager, 171
- on_stop_backward_audio
 - vxg::cloud::agent::callback, 99
- on_stopped
 - vxg::cloud::agent::event_state::event_state_changed_cb, 125
- on_stream_start
 - vxg::cloud::agent::manager, 171
- on_stream_stop
 - vxg::cloud::agent::manager, 171
- on_trigger_event
 - vxg::cloud::agent::callback, 100
 - vxg::cloud::agent::manager, 172
- on_triggered
 - vxg::cloud::agent::event_state::event_state_changed_cb, 125
- on_update_preview
 - vxg::cloud::agent::manager, 172
- operator bool
 - alter_bool, 74
- operator<
 - vxg::cloud, 45
 - vxg::cloud::agent::synchronizer::segmenter, 221
 - vxg::cloud::period, 196
 - vxg::cloud::timed_storage::item, 153
 - vxg::media::Streamer::MediaFrame, 176
- operator=
 - alter_bool, 74
 - vxg::cloud::agent::event_state, 122
 - vxg::cloud::utils::motion::map, 174
- origin
 - vxg::media::stream_error, 66
- PA_CREATE
 - vxg::cloud::agent::proto, 54
- PA_DELETE
 - vxg::cloud::agent::proto, 54
- PA_GOTO
 - vxg::cloud::agent::proto, 54
- PA_INVALID
 - vxg::cloud::agent::proto, 54
- PA_UPDATE
 - vxg::cloud::agent::proto, 54
- pack
 - vxg::cloud::agent::access_token, 72
 - vxg::cloud::utils::motion::map, 174
- parse
 - vxg::cloud::agent::access_token, 72
 - vxg::cloud::utils::uri, 277
- parse_args
 - cloud-agent-minimal.cc, 306
 - cloud-agent.cc, 308
- password
 - vxg::cloud::agent::proto::wifi_network, 298
 - vxg::cloud::utils::uri, 278
- path
 - vxg::cloud::utils::uri, 278
- PENDING
 - vxg::cloud::agent::synchronizer, 267
- period
 - vxg::cloud::agent::event_config, 116
 - vxg::cloud::period, 194, 195
- periodic
 - vxg::cloud::agent::proto::event_caps, 112
- port
 - vxg::cloud::utils::uri, 278
- precision
 - vxg::cloud::time_spec, 56
- precision_ratio
 - vxg::cloud::time_spec, 57

- presets
 - vxg::cloud::agent::ptz_config, 200
- process
 - vxg::media::Streamer::ISink, 142
- processed
 - vxg::cloud::agent::synchronizer::segmenter, 223
- profile
 - vxg::cloud::agent::proto::video_stream_config, 292
- profiles
 - vxg::cloud::agent::proto::stream_caps::caps_video_object, vxg::cloud::utils, 58
 - 104
- props
 - cloud-agent-minimal.cc, 306
 - cloud-agent.cc, 309
- ptr
 - vxg::cloud::agent::access_token, 72
 - vxg::cloud::agent::callback, 89
 - vxg::cloud::agent::event_stream, 129
 - vxg::cloud::agent::manager, 163
 - vxg::cloud::agent::media::rtsp_stream, 217
 - vxg::cloud::agent::media::stream, 240
 - vxg::cloud::agent::synchronizer, 266
 - vxg::cloud::agent::synchronizer::segmenter, 220
 - vxg::cloud::stream_storage, 256
 - vxg::media::stream, 236
 - vxg::media::Streamer::ISink, 138
 - vxg::media::Streamer::ISource, 145
- PtrU
 - vxg::media::Streamer::ISink, 138
- pts
 - vxg::media::Streamer::MediaFrame, 177
- ptz_action
 - vxg::cloud::agent::proto, 53
- ptz_preset_action
 - vxg::cloud::agent::proto, 53
- PULL
 - vxg::media::Streamer::ISource, 147
- pullFrame
 - vxg::media::ffmpeg::Source, 233
 - vxg::media::Streamer::ISource, 149
- PUSH
 - vxg::media::Streamer::ISource, 147
- push
 - vxg::cloud::utils::queued_async_handler< T >, 204
- pushFrame
 - vxg::media::Streamer::ISource, 149
- pwr_frequency
 - vxg::cloud::agent::proto::video_caps, 281
 - vxg::cloud::agent::proto::video_config, 288
- quality
 - vxg::cloud::agent::proto::stream_caps::caps_video_object, vxg::cloud::utils, 104
 - vxg::cloud::agent::proto::video_stream_config, 292
- query
 - vxg::cloud::utils::uri, 279
- queued-handler.h, 320
- queued_async_handler
 - vxg::cloud::utils::queued_async_handler< T >, 203
- queued_async_handler_ptr
 - vxg::cloud::utils, 58
- quit
 - cloud-agent-minimal.cc, 307
 - cloud-agent.cc, 309
- random_string
 - vxg::cloud::utils, 58
- realtime
 - vxg::cloud::agent::synchronizer::segmenter, 223
- record_by_event_upload_step
 - vxg::cloud::agent::synchronizer::config, 110
- record_export
 - vxg::cloud::agent::media::stream_callbacks, 244
 - vxg::cloud::agent::media::stream_callbacks_stub, 250
- record_get_list
 - vxg::cloud::agent::media::stream_callbacks, 245
 - vxg::cloud::agent::media::stream_callbacks_stub, 251
- record_needs_source
 - vxg::cloud::agent::media::stream_callbacks, 245
- region
 - vxg::cloud::agent::proto::motion_region, 182
- region_shape
 - vxg::cloud::agent::proto::motion_detection_caps, 179
- regions
 - vxg::cloud::agent::proto::motion_detection_config, 181
- reset
 - vxg::logger, 158
- resolutions
 - vxg::cloud::agent::proto::stream_caps::caps_video_object, 104
- rows
 - vxg::cloud::agent::proto::motion_detection_config, 181
- rtmp_sink
 - vxg::media::rtmp_sink, 207
- rtmp_sink.h, 322
- rtmp_source.h, 323
- rtsp-stream.h, 323
- rtsp_source
 - vxg::media::rtsp_source, 214
- rtsp_source.h, 324
- rtsp_source_ptr
 - vxg::media, 65
- rtsp_stream
 - vxg::cloud::agent::media::rtsp_stream, 217
- url
 - cloud-agent-minimal.cc, 307
 - cloud-agent.cc, 309
- samplerate
 - vxg::media::Streamer::StreamInfo::AudioInfo, 87
- saturation

- vxg::cloud::agent::proto::video_caps, [282](#)
- vxg::cloud::agent::proto::video_config, [288](#)
- scheme
 - vxg::cloud::utils::uri, [279](#)
- SDM_NONE
 - vxg::cloud::agent::event_state, [121](#)
- SDM_STREAM
 - vxg::cloud::agent::event_state, [121](#)
- SDM_UPLOAD
 - vxg::cloud::agent::event_state, [121](#)
- segmenter
 - vxg::cloud::agent::synchronizer::sync_request, [265](#)
- segmenter_ptr
 - vxg::cloud::agent::synchronizer, [266](#)
- send_qos_report_as_separate_event
 - vxg::cloud::agent::event_manager::config, [109](#)
- send_qos_report_period_sec
 - vxg::cloud::agent::event_manager::config, [109](#)
- sensitivity
 - vxg::cloud::agent::proto::motion_detection_caps, [179](#)
 - vxg::cloud::agent::proto::motion_region, [183](#)
- set_eos
 - vxg::media::Streamer::ISink, [143](#)
- set_eos_cb
 - vxg::media::Streamer::ISink, [143](#)
- set_error_cb
 - vxg::media::Streamer::ISink, [143](#)
 - vxg::media::Streamer::ISource, [149](#)
- set_events
 - vxg::cloud::agent::event_manager, [119](#)
 - vxg::cloud::agent::event_stream, [132](#)
- set_handler
 - vxg::cloud::utils::queued_async_handler< T >, [204](#)
- set_level
 - vxg::logger, [159](#)
- set_on_error_cb
 - vxg::media::stream, [238](#)
- set_stream_config
 - vxg::cloud::agent::media::stream_callbacks, [246](#)
 - vxg::cloud::agent::media::stream_callbacks_stub, [251](#)
- set_thread_name
 - vxg::cloud::utils, [58](#)
- set_trigger_recording
 - vxg::cloud::agent::event_stream, [133](#)
- sharpness
 - vxg::cloud::agent::proto::video_caps, [282](#)
 - vxg::cloud::agent::proto::video_config, [289](#)
- signal
 - vxg::cloud::agent::proto::wifi_network, [298](#)
- signal_handler
 - cloud-agent-minimal.cc, [306](#)
 - cloud-agent.cc, [308](#)
- Sink
 - vxg::media::ffmpeg::Sink, [225](#)
- sink_
 - vxg::media::stream, [239](#)
- SINK_THREAD_PRIO
 - vxg::media::Streamer, [69](#)
- slices
 - vxg::cloud::sync::timeline, [276](#)
 - vxg::cloud::timeline< T >, [273](#)
- smoothing
 - vxg::cloud::agent::proto::stream_caps::caps_video_object, [105](#)
 - vxg::cloud::agent::proto::video_stream_config, [292](#)
- snapshot
 - vxg::cloud::agent::event_config, [116](#)
 - vxg::cloud::agent::proto::event_caps, [112](#)
- socks4
 - vxg::cloud::agent::access_token::proxy_config, [198](#)
- socks5
 - vxg::cloud::agent::access_token::proxy_config, [198](#)
- Source
 - vxg::media::ffmpeg::Source, [231](#)
- source_
 - vxg::media::stream, [239](#)
- spkr
 - vxg::cloud::agent::proto::audio_caps, [77](#)
- spkr_mute
 - vxg::cloud::agent::audio_config, [79](#)
- spkr_vol
 - vxg::cloud::agent::audio_config, [80](#)
- SRC_THREAD_PRIO
 - vxg::media::Streamer, [69](#)
- srt
 - vxg::cloud::agent::proto::audio_stream_config, [85](#)
 - vxg::cloud::agent::proto::stream_caps::caps_audio_object, [101](#)
- ssid
 - vxg::cloud::agent::proto::wifi_network, [298](#)
- ST_ANY
 - vxg::media::Streamer::StreamInfo, [260](#)
- ST_AUDIO
 - vxg::media::Streamer::StreamInfo, [260](#)
- ST_DATA
 - vxg::media::Streamer::StreamInfo, [260](#)
- ST_UNKNOWN
 - vxg::media::Streamer::StreamInfo, [260](#)
- ST_VIDEO
 - vxg::media::Streamer::StreamInfo, [260](#)
- start
 - vxg::cloud::agent::event_manager, [119](#)
 - vxg::cloud::agent::event_state, [122](#)
 - vxg::cloud::agent::event_stream, [133](#)
 - vxg::cloud::agent::manager, [172](#)
 - vxg::cloud::agent::media::rtsp_stream, [218](#)
 - vxg::cloud::agent::synchronizer, [268](#)
 - vxg::cloud::utils::queued_async_handler< T >, [204](#)
- start_record
 - vxg::cloud::agent::media::stream_callbacks, [246](#)

- vxg::cloud::agent::media::stream_callbacks_stub, 252
- state
 - vxg::cloud::timed_storage::item, 154
- state_emulation
 - vxg::cloud::agent::proto::event_caps, 112
- state_emulation_report_delay
 - vxg::cloud::agent::proto::event_caps, 112
- stateful
 - vxg::cloud::agent::event_state, 123
 - vxg::cloud::agent::proto::event_caps, 112
- stateful_event_continuation_kick_snapshot
 - vxg::cloud::agent::event_manager::config, 109
- std, 25
 - make_unique, 43
- step
 - vxg::cloud::agent::synchronizer::segmenter, 223
- stop
 - vxg::cloud::agent::event_manager, 119
 - vxg::cloud::agent::event_state, 123
 - vxg::cloud::agent::event_stream, 133
 - vxg::cloud::agent::manager, 172
 - vxg::cloud::agent::synchronizer, 268
 - vxg::cloud::utils::queued_async_handler< T >, 204
 - vxg::media::ffmpeg::Sink, 229
 - vxg::media::ffmpeg::Source, 233
- stop_record
 - vxg::cloud::agent::media::stream_callbacks, 246
 - vxg::cloud::agent::media::stream_callbacks_stub, 252
- store
 - vxg::cloud::cloud_storage, 108
 - vxg::cloud::stream_storage, 258
 - vxg::cloud::sync::timeline, 276
 - vxg::cloud::timed_storage, 271
- store_async
 - vxg::cloud::stream_storage, 258
 - vxg::cloud::sync::timeline, 276
 - vxg::cloud::timed_storage, 272
- stream
 - vxg::cloud::agent::event_config, 116
 - vxg::cloud::agent::media::stream, 240
 - vxg::cloud::agent::proto::audio_stream_config, 85
 - vxg::cloud::agent::proto::event_caps, 113
 - vxg::cloud::agent::proto::video_stream_config, 292
 - vxg::media::stream, 236
- stream-storage.h, 325
- stream.h, 326, 327
- stream_callbacks
 - vxg::cloud::agent::media::stream_callbacks, 242
- stream_callbacks_stub
 - vxg::cloud::agent::media::stream_callbacks_stub, 248
- stream_delivery_mode
 - vxg::cloud::agent::event_state, 120
- stream_ptr
 - vxg::cloud::agent::media, 48
- stream_storage
 - vxg::cloud::stream_storage, 257
- StreamError
 - vxg::media::Streamer, 68
- streams
 - vxg::cloud::agent::proto::stream_caps::caps_audio_object, 101
 - vxg::cloud::agent::proto::stream_caps::caps_video_object, 105
 - vxg::cloud::agent::supported_streams_config, 264
- StreamType
 - vxg::media::Streamer::StreamInfo, 260
- string_contains
 - vxg::cloud::utils, 58
- string_endswith
 - vxg::cloud::utils, 59
- string_format
 - vxg::cloud::utils, 59
- string_replace
 - vxg::cloud::utils, 59
- string_split
 - vxg::cloud::utils, 59
- string_startswith
 - vxg::cloud::utils, 59
- string_tolower
 - vxg::cloud::utils, 60
- string_toupper
 - vxg::cloud::utils, 60
- string_trim
 - vxg::cloud::utils, 60
- string_urldecode
 - vxg::cloud::utils, 60
- string_urlencode
 - vxg::cloud::utils, 60
- swap
 - vxg::cloud::agent::event_state, 123
- sync
 - vxg::cloud::agent::synchronizer, 268
- sync_cancel
 - vxg::cloud::agent::synchronizer, 268
- sync_finalize
 - vxg::cloud::agent::synchronizer, 268
- sync_request_ptr
 - vxg::cloud::agent::synchronizer, 267
- sync_request_status
 - vxg::cloud::agent::synchronizer, 267
- sync_status_cb
 - vxg::cloud::agent::synchronizer::segmenter, 223
- sync_status_report_cb
 - vxg::cloud::agent::synchronizer, 267
- synchronizer_ptr
 - vxg::cloud::agent, 47
- syslog_ident
 - vxg::logger::options, 185
- system_id
 - vxg::cloud::agent::osd_config, 192
 - vxg::cloud::agent::proto::osd_caps, 188
- system_id_text

- vxg::cloud::agent::osd_config, 192
 - vxg::cloud::agent::proto::osd_caps, 189
- TCP
 - vxg::media::rtsp_source, 214
- tcp_logsink_enabled
 - vxg::logger::options, 185
- tcp_logsink_host
 - vxg::logger::options, 185
- tcp_logsink_port
 - vxg::logger::options, 185
- tdn
 - vxg::cloud::agent::proto::video_caps, 282
 - vxg::cloud::agent::proto::video_config, 289
- TF_12H
 - vxg::cloud::agent::proto, 54
- TF_24H
 - vxg::cloud::agent::proto, 54
- TF_INVALID
 - vxg::cloud::agent::proto, 54
- ticket
 - vxg::cloud::agent::synchronizer::segmenter, 223
- time
 - vxg::cloud, 44
 - vxg::cloud::agent::osd_config, 193
 - vxg::cloud::agent::proto::osd_caps, 189
- time_format
 - vxg::cloud::agent::osd_config, 193
 - vxg::cloud::agent::proto::osd_caps, 189
- time_format_n
 - vxg::cloud::agent::proto, 54
- time_realtime
 - vxg::media::Streamer::MediaFrame, 178
- timebase
 - vxg::media::Streamer::StreamInfo::AudioInfo, 87
 - vxg::media::Streamer::StreamInfo::VideoInfo, 295
- timed_storage
 - vxg::cloud::timed_storage, 270
- timed_storage_ptr
 - vxg::cloud, 45
- timeline
 - vxg::cloud::sync::timeline, 274
 - vxg::cloud::timeline< T >, 272, 273
- timeline-synchronizer.h, 328
- timeline.h, 330
- timeline_ptr
 - vxg::cloud::sync, 56
- timescale
 - vxg::media::Streamer::MediaFrame, 178
- tm
 - vxg::cloud::agent::ptz_command, 199
- to_double
 - vxg::cloud::utils::time, 63
- to_iso
 - vxg::cloud::utils::time, 64
- to_iso2
 - vxg::cloud::utils::time, 64
- to_iso_8601
 - vxg::cloud::utils::time, 64
- to_iso_local
 - vxg::cloud::utils::time, 64
- to_iso_packed
 - vxg::cloud::utils::time, 64
- to_json
 - alter_bool, 75
- token
 - vxg::cloud::agent::ptz_preset, 202
- tp_start
 - vxg::cloud::agent::proto::video_clip_info, 284
- tp_stop
 - vxg::cloud::agent::proto::video_clip_info, 284
- trace
 - vxg::logger, 159, 160
- transport
 - vxg::media::rtsp_source, 214
- trigger
 - vxg::cloud::agent::proto::event_caps, 113
- trigger_event
 - vxg::cloud::agent::event_manager, 119
 - vxg::cloud::agent::event_stream, 134
- type
 - vxg::media::Streamer::MediaFrame, 178
 - vxg::media::Streamer::StreamInfo, 261
- UDP
 - vxg::media::rtsp_source, 214
- UDP_MULTICAST
 - vxg::media::rtsp_source, 214
- UNKNOWN
 - vxg::media::Streamer, 68
- unpack
 - vxg::cloud::utils::motion::map, 174
- unset-helper.h, 331
 - __is_unset, 333
 - __is_unset< alter_bool >, 334
 - __is_unset< double >, 334
 - __is_unset< int >, 334
 - __is_unset< nlohmann::json >, 335
 - __is_unset< std::nullptr_t >, 335
 - __is_unset< std::string >, 335
 - __is_unset< vxg::cloud::duration >, 335
 - __is_unset< vxg::cloud::time >, 336
 - unset_value_for, 336
 - unset_value_for_impl, 336–338
 - UnsetDouble, 338
 - UnsetDuration, 338
 - UnsetFloat, 339
 - UnsetInt, 339
 - UnsetInt64, 339
 - UnsetString, 339
 - UnsetTime, 339
 - UnsetUInt64, 339
- unset_value_for
 - unset-helper.h, 336
- unset_value_for_impl
 - unset-helper.h, 336–338
- UnsetDouble
 - unset-helper.h, 338

- UnsetDuration
 - unset-helper.h, 338
- UnsetFloat
 - unset-helper.h, 339
- UnsetInt
 - unset-helper.h, 339
- UnsetInt64
 - unset-helper.h, 339
- UnsetString
 - unset-helper.h, 339
- UnsetTime
 - unset-helper.h, 339
- UnsetUInt64
 - unset-helper.h, 339
- user
 - vxg::cloud::utils::uri, 279
- utils.h, 340
- val
 - alter_bool, 75
- vbr
 - vxg::cloud::agent::proto::stream_caps::caps_video_object, 105
 - vxg::cloud::agent::proto::video_stream_config, 292
- vbr_brt
 - vxg::cloud::agent::proto::stream_caps::caps_video_object, 105
 - vxg::cloud::agent::proto::video_stream_config, 293
- VC_H264
 - vxg::media::Streamer::StreamInfo, 261
- VC_UNKNOWN
 - vxg::media::Streamer::StreamInfo, 261
- version
 - vxg::cloud::agent, 47
- vert
 - vxg::cloud::agent::proto::video_stream_config, 293
- vert_flip
 - vxg::cloud::agent::proto::video_caps, 282
 - vxg::cloud::agent::proto::video_config, 289
- VF_H264
 - vxg::cloud::agent::proto, 54
- VF_H265
 - vxg::cloud::agent::proto, 54
- VF_INVALID
 - vxg::cloud::agent::proto, 54
- VF_MJPEG
 - vxg::cloud::agent::proto, 54
- VIDEO
 - vxg::media::Streamer, 68
- video
 - vxg::cloud::agent::proto::stream_config, 255
 - vxg::cloud::agent::supported_stream_config, 263
 - vxg::media::Streamer::StreamInfo, 261
- VIDEO_AVC_PPS
 - vxg::media::Streamer, 68
- VIDEO_AVC_SPS
 - vxg::media::Streamer, 68
- video_es
 - vxg::cloud::agent::supported_streams_config, 264
- video_format
 - vxg::cloud::agent::proto, 54
- video_height
 - vxg::cloud::agent::proto::video_clip_info, 285
- VIDEO_SEQ_HDR
 - vxg::media::Streamer, 68
- video_width
 - vxg::cloud::agent::proto::video_clip_info, 285
- VideoCodec
 - vxg::media::Streamer::StreamInfo, 260
- vxg, 43
- vxg::cloud, 44
 - duration, 44
 - operator<, 45
 - time, 44
 - timed_storage_ptr, 45
- vxg::cloud::agent, 45
 - event_manager_ptr, 47
 - event_state_ptr, 47
 - synchronizer_ptr, 47
 - version, 47
- vxg::cloud::agent::access_token, 71
 - api_uri, 72
 - cam_base_uri, 72
 - pack, 72
 - parse, 72
 - ptr, 72
- vxg::cloud::agent::access_token::proxy_config, 197
 - socks4, 198
 - socks5, 198
- vxg::cloud::agent::audio_config, 78
 - caps, 79
 - echo_cancel, 79
 - mic_gain, 79
 - mic_mute, 79
 - spkr_mute, 79
 - spkr_vol, 80
- vxg::cloud::agent::audio_detection_config, 82
 - caps, 83
 - JSON_DEFINE_TYPE_INTRUSIVE, 83
 - length, 83
 - level, 83
- vxg::cloud::agent::audio_detection_config::audio_detection_conf_caps, 80
 - JSON_DEFINE_TYPE_INTRUSIVE, 81
 - level, 81
- vxg::cloud::agent::callback, 88
 - on_audio_file_play, 90
 - on_bye, 90
 - on_cam_ptz, 90
 - on_cam_ptz_preset, 91
 - on_cam_upgrade_firmware, 91
 - on_get_audio_detection, 92
 - on_get_cam_audio_config, 92
 - on_get_cam_video_config, 92
 - on_get_log, 93
 - on_get_memorycard_info, 93
 - on_get_motion_detection_config, 93

- on_get_osd_config, 94
- on_get_ptz_config, 94
- on_get_timezone, 95
- on_get_wifi_config, 95
- on_raw_msg, 96
- on_registered, 96
- on_set_audio_detection, 96
- on_set_cam_audio_config, 97
- on_set_cam_video_config, 97
- on_set_motion_detection_config, 97
- on_set_osd_config, 98
- on_set_timezone, 98
- on_set_wifi_config, 99
- on_start_backward_audio, 99
- on_stop_backward_audio, 99
- on_trigger_event, 100
- ptr, 89
- vxg::cloud::agent::event_config, 113
 - active, 115
 - caps, 115
 - caps_eq, 114
 - custom_event_name, 116
 - event, 116
 - name, 115
 - name_eq, 115
 - period, 116
 - snapshot, 116
 - stream, 116
- vxg::cloud::agent::event_manager, 117
 - ~event_manager, 118
 - event_manager, 118
 - event_state_report_cb_ptr, 117
 - get_events, 118
 - handle_event_payload_cb, 118
 - notify_event, 118
 - set_events, 119
 - start, 119
 - stop, 119
 - trigger_event, 119
- vxg::cloud::agent::event_manager::config, 108
 - attach_qos_report_to_motion, 108
 - send_qos_report_as_separate_event, 109
 - send_qos_report_period_sec, 109
 - stateful_event_continuation_kick_snapshot, 109
- vxg::cloud::agent::event_manager::event_state_report_cb, 126
 - ~event_state_report_cb, 127
 - event_state_report_cb, 126
 - on_event_continue, 127
 - on_event_start, 127
 - on_event_stop, 127
 - on_event_trigger, 127
 - on_need_stream_sync_continue, 128
 - on_need_stream_sync_start, 128
 - on_need_stream_sync_stop, 128
- vxg::cloud::agent::event_state, 119
 - ~event_state, 121
 - active, 122
 - config, 122
 - event_state, 121
 - event_state_changed_cb_ptr, 120
 - need_record, 122
 - operator=, 122
 - SDM_NONE, 121
 - SDM_STREAM, 121
 - SDM_UPLOAD, 121
 - start, 122
 - stateful, 123
 - stop, 123
 - stream_delivery_mode, 120
 - swap, 123
- vxg::cloud::agent::event_state::event_state_changed_cb, 124
 - ~event_state_changed_cb, 124
 - event_state_changed_cb, 124
 - on_ongoing, 124
 - on_started, 125
 - on_stopped, 125
 - on_triggered, 125
- vxg::cloud::agent::event_stream, 128
 - ~event_stream, 131
 - event_stream, 130
 - finit, 131
 - get_events, 131
 - init, 132
 - notify, 132
 - ptr, 129
 - set_events, 132
 - set_trigger_recording, 133
 - start, 133
 - stop, 133
 - trigger_event, 134
- vxg::cloud::agent::events_config, 134
 - enabled, 136
 - events, 136
 - get_event_config, 135
- vxg::cloud::agent::manager, 161
 - __notify_record_event, 164
 - _update_storage_status, 164
 - create, 164
 - direct_upload_payload_map, 163
 - direct_upload_payload_map_ptr, 163
 - handle_event, 165
 - handle_event_meta_file, 165
 - handle_event_snapshot, 165
 - on_audio_file_play, 165
 - on_cam_memorycard_recording, 165
 - on_cam_memorycard_synchronize, 165
 - on_cam_memorycard_synchronize_cancel, 165
 - on_cam_ptz, 166
 - on_cam_ptz_preset, 166
 - on_cam_upgrade_firmware, 166
 - on_closed, 166
 - on_direct_upload_url, 166
 - on_get_audio_detection, 166
 - on_get_cam_audio_config, 167

- on_get_cam_events_config, 167
- on_get_cam_memorycard_timeline, 167
- on_get_cam_video_config, 167
- on_get_log, 167
- on_get_motion_detection_config, 167
- on_get_osd_config, 167
- on_get_ptz_config, 168
- on_get_stream_by_event, 168
- on_get_stream_caps, 168
- on_get_stream_config, 168
- on_get_supported_streams, 168
- on_get_timezone, 168
- on_get_wifi_config, 168
- on_prepared, 169
- on_raw_message, 169
- on_registered, 169
- on_set_activity, 169
- on_set_audio_detection, 169
- on_set_cam_audio_config, 169
- on_set_cam_events_config, 169
- on_set_cam_video_config, 170
- on_set_log_enable, 170
- on_set_motion_detection_config, 170
- on_set_osd_config, 170
- on_set_periodic_events, 170
- on_set_stream_by_event, 170
- on_set_stream_config, 170
- on_set_timezone, 171
- on_set_wifi_config, 171
- on_start_backward, 171
- on_stop_backward, 171
- on_stream_start, 171
- on_stream_stop, 171
- on_trigger_event, 172
- on_update_preview, 172
- ptr, 163
- start, 172
- stop, 172
- vxg::cloud::agent::media, 47
 - stream_ptr, 48
- vxg::cloud::agent::media::rtsp_stream, 216
 - ~rtsp_stream, 218
 - ptr, 217
 - rtsp_stream, 217
 - start, 218
- vxg::cloud::agent::media::stream, 239
 - ~stream, 241
 - ptr, 240
 - stream, 240
- vxg::cloud::agent::media::stream_callbacks, 241
 - ~stream_callbacks, 243
 - get_snapshot, 243
 - get_stream_caps, 243
 - get_stream_config, 244
 - get_supported_stream, 244
 - record_export, 244
 - record_get_list, 245
 - record_needs_source, 245
 - set_stream_config, 246
 - start_record, 246
 - stop_record, 246
 - stream_callbacks, 242
- vxg::cloud::agent::media::stream_callbacks_stub, 247
 - ~stream_callbacks_stub, 249
 - get_snapshot, 249
 - get_stream_caps, 249
 - get_stream_config, 250
 - get_supported_stream, 250
 - record_export, 250
 - record_get_list, 251
 - set_stream_config, 251
 - start_record, 252
 - stop_record, 252
 - stream_callbacks_stub, 248
- vxg::cloud::agent::osd_config, 190
 - alignment, 191
 - bkg_color, 191
 - bkg_transp, 191
 - caps, 191
 - date, 191
 - date_format, 192
 - font_color, 192
 - font_size, 192
 - system_id, 192
 - system_id_text, 192
 - time, 193
 - time_format, 193
- vxg::cloud::agent::proto, 48
 - A_BOTTOM, 53
 - A_INVALID, 53
 - A_LEFT, 53
 - A_RIGHT, 53
 - A_STOP, 53
 - A_TOP, 53
 - A_ZOOM_IN, 53
 - A_ZOOM_OUT, 53
 - AF_AAC, 51
 - AF_ADPCM, 51
 - AF_G711A, 51
 - AF_G711U, 51
 - AF_INVALID, 51
 - AF_MP3, 51
 - AF_NELLY, 51
 - AF_NELLY16, 51
 - AF_NELLY8, 51
 - AF_OPUS, 51
 - AF_RAW, 51
 - AF_SPEEX, 51
 - AFF_AU_G711U, 50
 - AFF_INVALID, 50
 - AFF_MP3, 50
 - AFF_WAV_PCM, 50
 - audio_file_format, 50
 - audio_format, 50
 - ES_ERROR, 51
 - ES_INVALID, 51

ES_OK, 51
ET_CUSTOM, 51
ET_INVALID, 51
ET_MEMORYCARD, 51
ET_MOTION, 51
ET_NET, 51
ET_RECORD, 51
ET_SOUND, 51
ET_WIFI, 51
event_status, 51
event_type, 51
M_AUTO, 52
M_INVALID, 52
M_OFF, 52
M_ON, 52
MCS_FORMATTING, 52
MCS_INITIALIZATION, 52
MCS_INVALID, 52
MCS_NEED_FORMAT, 52
MCS_NONE, 52
MCS_NORMAL, 52
memorycard_status, 52
mode, 52
motion_region_shape, 52
motion_sensitivity, 53
MR_ANY, 52
MR_INVALID, 52
MR_RECTANGLE, 52
MS_FRAME, 53
MS_INVALID, 53
MS_REGION, 53
name, 55
PA_CREATE, 54
PA_DELETE, 54
PA_GOTO, 54
PA_INVALID, 54
PA_UPDATE, 54
ptz_action, 53
ptz_preset_action, 53
TF_12H, 54
TF_24H, 54
TF_INVALID, 54
time_format_n, 54
VF_H264, 54
VF_H265, 54
VF_INVALID, 54
VF_MJPEG, 54
video_format, 54
WFE_INVALID, 55
WFE_OPEN, 55
WFE_WEP, 55
WFE_WPA, 55
WFE_WPA2, 55
WFE_WPA2_ENTERPRISE, 55
WFE_WPA_ENTERPRISE, 55
wifi_encryption, 54
wifi_list, 50
wifi_network_state, 55
WNS_CONNECTED, 55
WNS_INITIALIZE_0, 55
WNS_INITIALIZE_1, 55
WNS_INVALID, 55
WNS_RECEIVING_IP, 55
WNS_TRY_CONNECT, 55
WNS_UNKNOWN, 55
vxg::cloud::agent::proto::audio_caps, 76
 audio_file_formats, 76
 backward, 77
 backward_formats, 77
 echo_cancel, 77
 mic, 77
 spkr, 77
vxg::cloud::agent::proto::audio_stream_config, 84
 brt, 85
 format, 85
 srt, 85
 stream, 85
vxg::cloud::agent::proto::event_caps, 111
 internal_hidden, 111
 periodic, 112
 snapshot, 112
 state_emulation, 112
 state_emulation_report_delay, 112
 stateful, 112
 stream, 113
 trigger, 113
vxg::cloud::agent::proto::motion_detection_caps, 178
 max_regions, 179
 region_shape, 179
 sensitivity, 179
vxg::cloud::agent::proto::motion_detection_config, 180
 caps, 180
 columns, 180
 regions, 181
 rows, 181
vxg::cloud::agent::proto::motion_region, 181
 enabled, 182
 map, 182
 region, 182
 sensitivity, 183
vxg::cloud::agent::proto::osd_caps, 186
 alignment, 187
 bkg_color, 187
 bkg_transp, 187
 date, 187
 date_format, 188
 font_color, 188
 font_size, 188
 system_id, 188
 system_id_text, 189
 time, 189
 time_format, 189
vxg::cloud::agent::proto::stream_caps, 253
 caps_audio, 253
 caps_video, 254

- vxg::cloud::agent::proto::stream_caps::caps_audio_object, 100
 - brt, 101
 - formats, 101
 - srt, 101
 - streams, 101
- vxg::cloud::agent::proto::stream_caps::caps_video_object, 102
 - brt, 103
 - formats, 103
 - fps, 104
 - gop, 104
 - profiles, 104
 - quality, 104
 - resolutions, 104
 - smoothing, 105
 - streams, 105
 - vbr, 105
 - vbr_brt, 105
- vxg::cloud::agent::proto::stream_config, 254
 - audio, 255
 - video, 255
- vxg::cloud::agent::proto::video_caps, 279
 - brightness, 280
 - contrast, 280
 - horz_flip, 281
 - ir_light, 281
 - nr_level, 281
 - nr_type, 281
 - pwr_frequency, 281
 - saturation, 282
 - sharpness, 282
 - tdn, 282
 - vert_flip, 282
 - wb_type, 282
- vxg::cloud::agent::proto::video_clip_info, 283
 - data, 284
 - local_start, 284
 - local_stop, 284
 - tp_start, 284
 - tp_stop, 284
 - video_height, 285
 - video_width, 285
- vxg::cloud::agent::proto::video_config, 285
 - brightness, 287
 - caps, 287
 - contrast, 287
 - horz_flip, 287
 - ir_light, 288
 - nr_level, 288
 - nr_type, 288
 - pwr_frequency, 288
 - saturation, 288
 - sharpness, 289
 - tdn, 289
 - vert_flip, 289
 - wb_type, 289
- vxg::cloud::agent::proto::video_stream_config, 290
 - brt, 291
 - format, 291
 - fps, 291
 - gop, 291
 - horz, 291
 - profile, 292
 - quality, 292
 - smoothing, 292
 - stream, 292
 - vbr, 292
 - vbr_brt, 293
 - vert, 293
- vxg::cloud::agent::proto::wifi_config, 296
 - networks, 296
- vxg::cloud::agent::proto::wifi_network, 297
 - encryption, 297
 - encryption_caps, 298
 - mac, 298
 - password, 298
 - signal, 298
 - ssid, 298
- vxg::cloud::agent::ptz_command, 198
 - action, 199
 - tm, 199
- vxg::cloud::agent::ptz_config, 199
 - actions, 200
 - maximum_number_of_presets, 200
 - presets, 200
- vxg::cloud::agent::ptz_preset, 201
 - action, 202
 - name, 202
 - token, 202
- vxg::cloud::agent::supported_stream_config, 262
 - audio, 262
 - id, 262
 - video, 263
- vxg::cloud::agent::supported_streams_config, 263
 - audio_es, 264
 - streams, 264
 - video_es, 264
- vxg::cloud::agent::synchronizer, 265
 - CANCELED, 267
 - create, 267
 - DONE, 267
 - ERROR, 267
 - PENDING, 267
 - ptr, 266
 - segmenter_ptr, 266
 - start, 268
 - stop, 268
 - sync, 268
 - sync_cancel, 268
 - sync_finalize, 268
 - sync_request_ptr, 267
 - sync_request_status, 267
 - sync_status_report_cb, 267
- vxg::cloud::agent::synchronizer::config, 110
 - record_by_event_upload_step, 110

- vxg::cloud::agent::synchronizer::segmenter, 219
 - ~segmenter, 220
 - canceled, 221
 - chunks_done, 221
 - chunks_failed, 221
 - chunks_planned, 221
 - cur_seg_start, 222
 - cur_seg_stop, 222
 - delay, 222
 - final_sync_status_reported, 222
 - finished, 222
 - intersects, 221
 - last_processed_time, 222
 - operator<, 221
 - processed, 223
 - ptr, 220
 - realtime, 223
 - step, 223
 - sync_status_cb, 223
 - ticket, 223
- vxg::cloud::agent::synchronizer::sync_request, 265
 - segmenter, 265
- vxg::cloud::cloud_storage, 106
 - ~cloud_storage, 107
 - cloud_storage, 107
 - erase, 107
 - list, 107
 - load, 107
 - store, 108
- vxg::cloud::period, 193
 - begin, 196
 - clear, 195
 - duration, 195
 - end, 196
 - intersects, 195
 - is_null, 195
 - is_open, 196
 - is_valid, 196
 - operator<, 196
 - period, 194, 195
- vxg::cloud::stream_storage, 255
 - ~stream_storage, 257
 - erase, 257
 - list, 257
 - load, 257
 - ptr, 256
 - store, 258
 - store_async, 258
 - stream_storage, 257
- vxg::cloud::sync, 55
 - timeline_ptr, 56
- vxg::cloud::sync::timeline, 273
 - _squash_periods, 275
 - ~timeline, 275
 - async_store_finished_cb, 274
 - async_store_is_canceled_cb, 274
 - finit, 275
 - init, 275
 - list, 275
 - load, 276
 - slices, 276
 - store, 276
 - store_async, 276
 - timeline, 274
- vxg::cloud::time_spec, 56
 - duration, 56
 - precision, 56
 - precision_ratio, 57
- vxg::cloud::timed_storage, 269
 - ~timed_storage, 270
 - async_store_finished_cb, 270
 - async_store_is_canceled_cb, 270
 - erase, 271
 - finit, 271
 - init, 271
 - item_ptr, 270
 - list, 271
 - load, 271
 - store, 271
 - store_async, 272
 - timed_storage, 270
- vxg::cloud::timed_storage::item, 150
 - async_ready, 152
 - category, 153
 - clear, 153
 - data, 153
 - data_state, 152
 - empty, 152, 153
 - item, 152
 - loaded, 152
 - media_type, 153
 - operator<, 153
 - state, 154
- vxg::cloud::timeline< T >, 272
 - _squash_periods, 273
 - slices, 273
 - timeline, 272, 273
- vxg::cloud::utils, 57
 - dirname, 58
 - queued_async_handler_ptr, 58
 - random_string, 58
 - set_thread_name, 58
 - string_contains, 58
 - string_endswith, 59
 - string_format, 59
 - string_replace, 59
 - string_split, 59
 - string_startswith, 59
 - string_tolower, 60
 - string_toupper, 60
 - string_trim, 60
 - string_urldecode, 60
 - string_urlencode, 60
- vxg::cloud::utils::gcc_abi, 61
 - demangle, 61
- vxg::cloud::utils::motion, 61

- vxg::cloud::utils::motion::map, 173
 - map, 174
 - operator=, 174
 - pack, 174
 - unpack, 174
- vxg::cloud::utils::queued_async_handler< T >, 202
 - ~queued_async_handler, 203
 - get_handler, 204
 - handler_func, 203
 - push, 204
 - queued_async_handler, 203
 - set_handler, 204
 - start, 204
 - stop, 204
- vxg::cloud::utils::time, 61
 - epoch, 62
 - from_double, 62
 - from_iso, 62
 - from_iso2, 62
 - from_iso_packed, 62
 - is_iso, 62
 - is_iso_packed, 62
 - iso_time_valid, 63
 - max, 63
 - now, 63
 - now_ISO8601.UTC, 63
 - now_ISO8601.UTC_packed, 63
 - null, 63
 - to_double, 63
 - to_iso, 64
 - to_iso2, 64
 - to_iso_8601, 64
 - to_iso_local, 64
 - to_iso_packed, 64
- vxg::cloud::utils::uri, 277
 - fragment, 278
 - host, 278
 - parse, 277
 - password, 278
 - path, 278
 - port, 278
 - query, 279
 - scheme, 279
 - user, 279
- vxg::logger, 154
 - critical, 156
 - debug, 156
 - error, 157
 - info, 157, 158
 - instance, 158
 - logger_ptr, 155
 - loglevel, 156
 - lvl_crit, 156
 - lvl_debug, 156
 - lvl_error, 156
 - lvl_info, 156
 - lvl_off, 156
 - lvl_trace, 156
 - lvl_warn, 156
 - reset, 158
 - set_level, 159
 - trace, 159, 160
 - warn, 160
- vxg::logger::options, 183
 - crash_logfile_path, 184
 - default_loglevel, 184
 - log_pattern, 184
 - logfile_max_files, 184
 - logfile_max_size, 185
 - logfile_path, 185
 - syslog_ident, 185
 - tcp_logsink_enabled, 185
 - tcp_logsink_host, 185
 - tcp_logsink_port, 185
- vxg::media, 64
 - rtsp_source_ptr, 65
- vxg::media::ffmpeg, 65
- vxg::media::ffmpeg::Sink, 224
 - ~Sink, 225
 - droppable, 226
 - duration, 226
 - error, 226
 - finit, 227
 - init, 227
 - name, 228
 - negotiate, 228
 - Sink, 225
 - stop, 229
- vxg::media::ffmpeg::Source, 229
 - ~Source, 231
 - finit, 231
 - init, 231, 232
 - name, 233
 - negotiate, 233
 - pullFrame, 233
 - Source, 231
 - stop, 233
- vxg::media::rtmp_sink, 206
 - droppable, 207
 - init, 207
 - name, 209
 - negotiate, 209
 - rtmp_sink, 207
- vxg::media::rtmp_source, 210
 - init, 211
- vxg::media::rtsp_source, 212
 - __transport_to_ff, 215
 - ASYNC_TCP, 214
 - ffmpeg_opts_, 216
 - HTTP, 214
 - HTTPS, 214
 - init, 215
 - name, 215
 - rtsp_source, 214
 - TCP, 214
 - transport, 214

- UDP, 214
- UDP_MULTICAST, 214
- vxg::media::stream, 234
 - ~stream, 237
 - finit_sink, 237
 - finit_source, 237
 - init_sink, 237
 - init_source, 238
 - on_error_cb, 236
 - ptr, 236
 - set_on_error_cb, 238
 - sink_, 239
 - source_, 239
 - stream, 236
- vxg::media::stream_error, 65
 - E_CONNECT, 66
 - E_PROCESS, 66
 - E_UNKNOWN, 66
 - error, 66
 - O_SINK, 66
 - O_SOURCE, 66
 - O_UNKNOWN, 66
 - origin, 66
- vxg::media::stream_error::report, 205
 - code, 205
 - from, 205
- vxg::media::Streamer, 67
 - AUDIO, 68
 - AUDIO_SEQ_HDR, 68
 - DATA, 68
 - DROP_BACK, 68
 - DROP_FRONT, 68
 - DropDirection, 67
 - E_EOS, 68
 - E_FATAL, 68
 - E_NONE, 68
 - FLV, 68
 - MAX, 68
 - MediaType, 68
 - on_error_cb, 67
 - SINK_THREAD_PRIO, 69
 - SRC_THREAD_PRIO, 69
 - StreamError, 68
 - UNKNOWN, 68
 - VIDEO, 68
 - VIDEO_AVC_PPS, 68
 - VIDEO_AVC_SPS, 68
 - VIDEO_SEQ_HDR, 68
- vxg::media::Streamer::ISink, 137
 - ~ISink, 139
 - droppable, 139
 - duration, 139
 - error, 140
 - finit, 140
 - init, 140
 - ISink, 139
 - name, 142
 - negotiate, 142
 - on_error_cb_, 143
 - process, 142
 - ptr, 138
 - PtrU, 138
 - set_eos, 143
 - set_eos_cb, 143
 - set_error_cb, 143
- vxg::media::Streamer::ISource, 144
 - error, 147
 - finit, 148
 - init, 148
 - ISource, 147
 - Mode, 146
 - mode_, 150
 - name, 148
 - negotiate, 148
 - on_error_cb_, 150
 - ptr, 145
 - PULL, 147
 - pullFrame, 149
 - PUSH, 147
 - pushFrame, 149
 - set_error_cb, 149
- vxg::media::Streamer::MediaFrame, 175
 - data, 176
 - dts, 176
 - duration, 177
 - is_key, 177
 - len, 177
 - NO_PTS, 177
 - operator<, 176
 - pts, 177
 - time_realtime, 178
 - timescale, 178
 - type, 178
- vxg::media::Streamer::StreamInfo, 258
 - AC_AAC, 260
 - AC_G711_A, 260
 - AC_G711_U, 260
 - AC_G726, 260
 - AC_LPCM, 260
 - AC_OPUS, 260
 - AC_UNKNOWN, 260
 - audio, 261
 - AudioCodec, 259
 - DataCodec, 260
 - DC_ONVIF, 260
 - DC_UNKNOWN, 260
 - ST_ANY, 260
 - ST_AUDIO, 260
 - ST_DATA, 260
 - ST_UNKNOWN, 260
 - ST_VIDEO, 260
 - StreamType, 260
 - type, 261
 - VC_H264, 261
 - VC_UNKNOWN, 261
 - video, 261

- VideoCodec, [260](#)
- vxg::media::Streamer::StreamInfo::AudioInfo, [86](#)
 - bitrate, [86](#)
 - channels, [87](#)
 - codec, [87](#)
 - extradata, [87](#)
 - samplerate, [87](#)
 - timebase, [87](#)
- vxg::media::Streamer::StreamInfo::VideoInfo, [293](#)
 - bitrate, [294](#)
 - codec, [294](#)
 - extradata, [294](#)
 - framerate, [295](#)
 - height, [295](#)
 - timebase, [295](#)
 - width, [295](#)
- vxg_cloud_token
 - cloud-agent-minimal.cc, [307](#)
 - cloud-agent.cc, [309](#)
- warn
 - vxg::logger, [160](#)
- wb_type
 - vxg::cloud::agent::proto::video_caps, [282](#)
 - vxg::cloud::agent::proto::video_config, [289](#)
- WFE_INVALID
 - vxg::cloud::agent::proto, [55](#)
- WFE_OPEN
 - vxg::cloud::agent::proto, [55](#)
- WFE_WEP
 - vxg::cloud::agent::proto, [55](#)
- WFE_WPA
 - vxg::cloud::agent::proto, [55](#)
- WFE_WPA2
 - vxg::cloud::agent::proto, [55](#)
- WFE_WPA2_ENTERPRISE
 - vxg::cloud::agent::proto, [55](#)
- WFE_WPA_ENTERPRISE
 - vxg::cloud::agent::proto, [55](#)
- width
 - vxg::media::Streamer::StreamInfo::VideoInfo, [295](#)
- wifi_encryption
 - vxg::cloud::agent::proto, [54](#)
- wifi_list
 - vxg::cloud::agent::proto, [50](#)
- wifi_network_state
 - vxg::cloud::agent::proto, [55](#)
- WNS_CONNECTED
 - vxg::cloud::agent::proto, [55](#)
- WNS_INITIALIZE_0
 - vxg::cloud::agent::proto, [55](#)
- WNS_INITIALIZE_1
 - vxg::cloud::agent::proto, [55](#)
- WNS_INVALID
 - vxg::cloud::agent::proto, [55](#)
- WNS_RECEIVING_IP
 - vxg::cloud::agent::proto, [55](#)
- WNS_TRY_CONNECT
 - vxg::cloud::agent::proto, [55](#)
- WNS_UNKNOWN
 - vxg::cloud::agent::proto, [55](#)